

# Problem 2460: Apply Operations to an Array

## Problem Information

Difficulty: [Easy](#)

Acceptance Rate: 0.00%

Paid Only: No

## Problem Description

You are given a

0-indexed

array

nums

of size

n

consisting of

non-negative

integers.

You need to apply

$n - 1$

operations to this array where, in the

i

th

operation (

0-indexed

), you will apply the following on the

i

th

element of

nums

:

If

`nums[i] == nums[i + 1]`

, then multiply

`nums[i]`

by

2

and set

`nums[i + 1]`

to

0

. Otherwise, you skip this operation.

After performing

all

the operations,

shift

all the

0

's to the

end

of the array.

For example, the array

[1,0,2,0,0,1]

after shifting all its

0

's to the end, is

[1,2,1,0,0,0]

.

Return

the resulting array

.

Note

that the operations are applied

sequentially

, not all at once.

Example 1:

Input:

nums = [1,2,2,1,1,0]

Output:

[1,4,2,0,0,0]

Explanation:

We do the following operations: -  $i = 0$ : nums[0] and nums[1] are not equal, so we skip this operation. -  $i = 1$ : nums[1] and nums[2] are equal, we multiply nums[1] by 2 and change nums[2] to 0. The array becomes [1,

4

,

0

,1,1,0]. -  $i = 2$ : nums[2] and nums[3] are not equal, so we skip this operation. -  $i = 3$ : nums[3] and nums[4] are equal, we multiply nums[3] by 2 and change nums[4] to 0. The array becomes [1,4,0,

2

,

0

,0]. - i = 4: nums[4] and nums[5] are equal, we multiply nums[4] by 2 and change nums[5] to 0. The array becomes [1,4,0,2,

0

,

0

]. After that, we shift the 0's to the end, which gives the array [1,4,2,0,0,0].

Example 2:

Input:

nums = [0,1]

Output:

[1,0]

Explanation:

No operation can be applied, we just shift the 0 to the end.

Constraints:

2 <= nums.length <= 2000

0 <= nums[i] <= 1000

## Code Snippets

**C++:**

```
class Solution {  
public:  
    vector<int> applyOperations(vector<int>& nums) {
```

```
}  
};
```

### Java:

```
class Solution {  
    public int[] applyOperations(int[] nums) {  
  
    }  
}
```

### Python3:

```
class Solution:  
    def applyOperations(self, nums: List[int]) -> List[int]:
```

### Python:

```
class Solution(object):  
    def applyOperations(self, nums):  
        """  
        :type nums: List[int]  
        :rtype: List[int]  
        """
```

### JavaScript:

```
/**  
 * @param {number[]} nums  
 * @return {number[]}  
 */  
var applyOperations = function(nums) {  
  
};
```

### TypeScript:

```
function applyOperations(nums: number[]): number[] {  
  
};
```

**C#:**

```
public class Solution {  
    public int[] ApplyOperations(int[] nums) {  
  
    }  
}
```

**C:**

```
/**  
 * Note: The returned array must be malloced, assume caller calls free().  
 */  
int* applyOperations(int* nums, int numsSize, int* returnSize) {  
  
}
```

**Go:**

```
func applyOperations(nums []int) []int {  
  
}
```

**Kotlin:**

```
class Solution {  
    fun applyOperations(nums: IntArray): IntArray {  
  
    }  
}
```

**Swift:**

```
class Solution {  
    func applyOperations(_ nums: [Int]) -> [Int] {  
  
    }  
}
```

**Rust:**

```
impl Solution {  
    pub fn apply_operations(nums: Vec<i32>) -> Vec<i32> {
```

```
}  
}
```

### Ruby:

```
# @param {Integer[]} nums  
# @return {Integer[]}  
def apply_operations(nums)  
  
end
```

### PHP:

```
class Solution {  
  
    /**  
     * @param Integer[] $nums  
     * @return Integer[]  
     */  
    function applyOperations($nums) {  
  
    }  
}
```

### Dart:

```
class Solution {  
    List<int> applyOperations(List<int> nums) {  
  
    }  
}
```

### Scala:

```
object Solution {  
    def applyOperations(nums: Array[Int]): Array[Int] = {  
  
    }  
}
```

### Elixir:



```

defmodule Solution do
  @spec apply_operations(nums :: [integer]) :: [integer]
  def apply_operations(nums) do

  end

  end
end

```

## Erlang:

```

-spec apply_operations(Nums :: [integer()]) -> [integer()].
apply_operations(Nums) ->
.

```

## Racket:

```

(define/contract (apply-operations nums)
  (-> (listof exact-integer?) (listof exact-integer?))
  )

```

# Solutions

## C++ Solution:

```

/*
 * Problem: Apply Operations to an Array
 * Difficulty: Easy
 * Tags: array
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

class Solution {
public:
    vector<int> applyOperations(vector<int>& nums) {

    }

};

```

## Java Solution:

```

/**
 * Problem: Apply Operations to an Array
 * Difficulty: Easy
 * Tags: array
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

class Solution {
public int[] applyOperations(int[] nums) {

}

}

```

### Python3 Solution:

```

"""
Problem: Apply Operations to an Array
Difficulty: Easy
Tags: array

Approach: Use two pointers or sliding window technique
Time Complexity: O(n) or O(n log n)
Space Complexity: O(1) to O(n) depending on approach
"""

class Solution:
    def applyOperations(self, nums: List[int]) -> List[int]:
        # TODO: Implement optimized solution
        pass

```

### Python Solution:

```

class Solution(object):
    def applyOperations(self, nums):
        """
        :type nums: List[int]
        :rtype: List[int]
        """

```

## JavaScript Solution:

```
/**
 * Problem: Apply Operations to an Array
 * Difficulty: Easy
 * Tags: array
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

/**
 * @param {number[]} nums
 * @return {number[]}
 */
var applyOperations = function(nums) {

};
```

## TypeScript Solution:

```
/**
 * Problem: Apply Operations to an Array
 * Difficulty: Easy
 * Tags: array
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

function applyOperations(nums: number[]): number[] {

};
```

## C# Solution:

```
/*
 * Problem: Apply Operations to an Array
 * Difficulty: Easy
 * Tags: array
 *
 */
```

```

* Approach: Use two pointers or sliding window technique
* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(1) to O(n) depending on approach
*/

public class Solution {
public int[] ApplyOperations(int[] nums) {

}

}

```

### C Solution:

```

/*
* Problem: Apply Operations to an Array
* Difficulty: Easy
* Tags: array
*
* Approach: Use two pointers or sliding window technique
* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(1) to O(n) depending on approach
*/

/**
* Note: The returned array must be malloced, assume caller calls free().
*/
int* applyOperations(int* nums, int numsSize, int* returnSize) {

}

```

### Go Solution:

```

// Problem: Apply Operations to an Array
// Difficulty: Easy
// Tags: array
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(1) to O(n) depending on approach

func applyOperations(nums []int) []int {

```

```
}
```

### Kotlin Solution:

```
class Solution {  
    fun applyOperations(nums: IntArray): IntArray {  
  
    }  
}
```

### Swift Solution:

```
class Solution {  
    func applyOperations(_ nums: [Int]) -> [Int] {  
  
    }  
}
```

### Rust Solution:

```
// Problem: Apply Operations to an Array  
// Difficulty: Easy  
// Tags: array  
//  
// Approach: Use two pointers or sliding window technique  
// Time Complexity: O(n) or O(n log n)  
// Space Complexity: O(1) to O(n) depending on approach  
  
impl Solution {  
    pub fn apply_operations(nums: Vec<i32>) -> Vec<i32> {  
  
    }  
}
```

### Ruby Solution:

```
# @param {Integer[]} nums  
# @return {Integer[]}  
def apply_operations(nums)
```

```
end
```

### PHP Solution:

```
class Solution {  
  
    /**  
     * @param Integer[] $nums  
     * @return Integer[]  
     */  
    function applyOperations($nums) {  
  
    }  
}
```

### Dart Solution:

```
class Solution {  
    List<int> applyOperations(List<int> nums) {  
  
    }  
}
```

### Scala Solution:

```
object Solution {  
    def applyOperations(nums: Array[Int]): Array[Int] = {  
  
    }  
}
```

### Elixir Solution:

```
defmodule Solution do  
    @spec apply_operations(nums :: [integer]) :: [integer]  
    def apply_operations(nums) do  
  
    end  
end
```

### Erlang Solution:

```
-spec apply_operations(Nums :: [integer()]) -> [integer()].  
apply_operations(Nums) ->  
.
```

### **Racket Solution:**

```
(define/contract (apply-operations nums)  
  (-> (listof exact-integer?) (listof exact-integer?))  
  )
```