

Problem 1714: Sum Of Special Evenly-Spaced Elements In Array

Problem Information

Difficulty: **Hard**

Acceptance Rate: 0.00%

Paid Only: No

Problem Description

You are given a

0-indexed

integer array

nums

consisting of

n

non-negative integers.

You are also given an array

queries

, where

queries[i] = [x

i

, y

i

]

. The answer to the

i

th

query is the sum of all

nums[j]

where

x

i

$\leq j < n$

and

$(j - x$

i

)

is divisible by

y

i

.

Return

an array

answer

where

`answer.length == queries.length`

and

`answer[i]`

is the answer to the

`i`

th

query

modulo

10

9

+ 7

.

Example 1:

Input:

`nums = [0,1,2,3,4,5,6,7], queries = [[0,3],[5,1],[4,2]]`

Output:

[9,18,10]

Explanation:

The answers of the queries are as follows: 1) The j indices that satisfy this query are 0, 3, and 6. $\text{nums}[0] + \text{nums}[3] + \text{nums}[6] = 9$ 2) The j indices that satisfy this query are 5, 6, and 7. $\text{nums}[5] + \text{nums}[6] + \text{nums}[7] = 18$ 3) The j indices that satisfy this query are 4 and 6. $\text{nums}[4] + \text{nums}[6] = 10$

Example 2:

Input:

$\text{nums} = [100, 200, 101, 201, 102, 202, 103, 203]$, $\text{queries} = [[0, 7]]$

Output:

[303]

Constraints:

$n == \text{nums.length}$

$1 \leq n \leq 5 * 10$

4

$0 \leq \text{nums}[i] \leq 10$

9

$1 \leq \text{queries.length} \leq 1.5 * 10$

5

$0 \leq x$

i

< n

1 <= y

i

<= 5 * 10

4

Code Snippets

C++:

```
class Solution {
public:
    vector<int> solve(vector<int>& nums, vector<vector<int>>& queries) {

    }
};
```

Java:

```
class Solution {
    public int[] solve(int[] nums, int[][] queries) {

    }
}
```

Python3:

```
class Solution:
    def solve(self, nums: List[int], queries: List[List[int]]) -> List[int]:
```

Python:

```
class Solution(object):
    def solve(self, nums, queries):
        """
        :type nums: List[int]
```

```

:type queries: List[List[int]]
:rtype: List[int]
"""

```

JavaScript:

```

/**
 * @param {number[]} nums
 * @param {number[][]} queries
 * @return {number[]}
 */
var solve = function(nums, queries) {

};

```

TypeScript:

```

function solve(nums: number[], queries: number[][]): number[] {

};

```

C#:

```

public class Solution {
    public int[] Solve(int[] nums, int[][] queries) {

    }
}

```

C:

```

/**
 * Note: The returned array must be malloced, assume caller calls free().
 */
int* solve(int* nums, int numsSize, int** queries, int queriesSize, int*
queriesColSize, int* returnSize) {

}

```

Go:

```
func solve(nums []int, queries [][]int) []int {

}
```

Kotlin:

```
class Solution {
    fun solve(nums: IntArray, queries: Array<IntArray>): IntArray {

    }
}
```

Swift:

```
class Solution {
    func solve(_ nums: [Int], _ queries: [[Int]]) -> [Int] {

    }
}
```

Rust:

```
impl Solution {
    pub fn solve(nums: Vec<i32>, queries: Vec<Vec<i32>>) -> Vec<i32> {

    }
}
```

Ruby:

```
# @param {Integer[]} nums
# @param {Integer[][]} queries
# @return {Integer[]}
def solve(nums, queries)

end
```

PHP:

```
class Solution {

    /**
     * @param Integer[] $nums
     */
}
```

```

* @param Integer[][] $queries
* @return Integer[]
*/
function solve($nums, $queries) {

}

}

```

Dart:

```

class Solution {
  List<int> solve(List<int> nums, List<List<int>> queries) {

  }
}

```

Scala:

```

object Solution {
  def solve(nums: Array[Int], queries: Array[Array[Int]]): Array[Int] = {

  }
}

```

Elixir:

```

defmodule Solution do
  @spec solve(nums :: [integer], queries :: [[integer]]) :: [integer]
  def solve(nums, queries) do

  end
end

```

Erlang:

```

-spec solve(Nums :: [integer()], Queries :: [[integer()]]) -> [integer()].
solve(Nums, Queries) ->
.

```

Racket:


```
(define/contract (solve nums queries)
  (-> (listof exact-integer?) (listof (listof exact-integer?)) (listof
exact-integer?))
)
```

Solutions

C++ Solution:

```
/*
 * Problem: Sum Of Special Evenly-Spaced Elements In Array
 * Difficulty: Hard
 * Tags: array, dp
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */

class Solution {
public:
    vector<int> solve(vector<int>& nums, vector<vector<int>>& queries) {

    }
};
```

Java Solution:

```
/**
 * Problem: Sum Of Special Evenly-Spaced Elements In Array
 * Difficulty: Hard
 * Tags: array, dp
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */

class Solution {
    public int[] solve(int[] nums, int[][] queries) {
```

```
}  
}
```

Python3 Solution:

```
"""  
Problem: Sum Of Special Evenly-Spaced Elements In Array  
Difficulty: Hard  
Tags: array, dp  
  
Approach: Use two pointers or sliding window technique  
Time Complexity: O(n) or O(n log n)  
Space Complexity: O(n) or O(n * m) for DP table  
"""  
  
class Solution:  
    def solve(self, nums: List[int], queries: List[List[int]]) -> List[int]:  
        # TODO: Implement optimized solution  
        pass
```

Python Solution:

```
class Solution(object):  
    def solve(self, nums, queries):  
        """  
        :type nums: List[int]  
        :type queries: List[List[int]]  
        :rtype: List[int]  
        """
```

JavaScript Solution:

```
/**  
 * Problem: Sum Of Special Evenly-Spaced Elements In Array  
 * Difficulty: Hard  
 * Tags: array, dp  
 *  
 * Approach: Use two pointers or sliding window technique  
 * Time Complexity: O(n) or O(n log n)  
 * Space Complexity: O(n) or O(n * m) for DP table  
 */
```

```

/**
 * @param {number[]} nums
 * @param {number[][]} queries
 * @return {number[]}
 */
var solve = function(nums, queries) {

};

```

TypeScript Solution:

```

/**
 * Problem: Sum Of Special Evenly-Spaced Elements In Array
 * Difficulty: Hard
 * Tags: array, dp
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */

function solve(nums: number[], queries: number[][]): number[] {

};

```

C# Solution:

```

/*
 * Problem: Sum Of Special Evenly-Spaced Elements In Array
 * Difficulty: Hard
 * Tags: array, dp
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */

public class Solution {
    public int[] Solve(int[] nums, int[][] queries) {

```

```
}  
}
```

C Solution:

```
/*  
 * Problem: Sum Of Special Evenly-Spaced Elements In Array  
 * Difficulty: Hard  
 * Tags: array, dp  
 *  
 * Approach: Use two pointers or sliding window technique  
 * Time Complexity: O(n) or O(n log n)  
 * Space Complexity: O(n) or O(n * m) for DP table  
 */  
  
/**  
 * Note: The returned array must be malloced, assume caller calls free().  
 */  
int* solve(int* nums, int numsSize, int** queries, int queriesSize, int*  
queriesColSize, int* returnSize) {  
  
}
```

Go Solution:

```
// Problem: Sum Of Special Evenly-Spaced Elements In Array  
// Difficulty: Hard  
// Tags: array, dp  
//  
// Approach: Use two pointers or sliding window technique  
// Time Complexity: O(n) or O(n log n)  
// Space Complexity: O(n) or O(n * m) for DP table  
  
func solve(nums []int, queries [][]int) []int {  
  
}
```

Kotlin Solution:

```
class Solution {  
    fun solve(nums: IntArray, queries: Array<IntArray>): IntArray {
```

```
}  
}
```

Swift Solution:

```
class Solution {  
    func solve(_ nums: [Int], _ queries: [[Int]]) -> [Int] {  
  
    }  
}
```

Rust Solution:

```
// Problem: Sum Of Special Evenly-Spaced Elements In Array  
// Difficulty: Hard  
// Tags: array, dp  
//  
// Approach: Use two pointers or sliding window technique  
// Time Complexity: O(n) or O(n log n)  
// Space Complexity: O(n) or O(n * m) for DP table  
  
impl Solution {  
    pub fn solve(nums: Vec<i32>, queries: Vec<Vec<i32>>) -> Vec<i32> {  
  
    }  
}
```

Ruby Solution:

```
# @param {Integer[]} nums  
# @param {Integer[][]} queries  
# @return {Integer[]}  
def solve(nums, queries)  
  
end
```

PHP Solution:

```
class Solution {
```

```

/**
 * @param Integer[] $nums
 * @param Integer[][] $queries
 * @return Integer[]
 */
function solve($nums, $queries) {

}
}

```

Dart Solution:

```

class Solution {
  List<int> solve(List<int> nums, List<List<int>> queries) {

  }
}

```

Scala Solution:

```

object Solution {
  def solve(nums: Array[Int], queries: Array[Array[Int]]): Array[Int] = {

  }
}

```

Elixir Solution:

```

defmodule Solution do
  @spec solve(nums :: [integer], queries :: [[integer]]) :: [integer]
  def solve(nums, queries) do

  end
end

```

Erlang Solution:

```

-spec solve(Nums :: [integer()], Queries :: [[integer()]]) -> [integer()].
solve(Nums, Queries) ->
.

```

Racket Solution:

```
(define/contract (solve nums queries)
  (-> (listof exact-integer?) (listof (listof exact-integer?)) (listof
exact-integer?))
)
```