

# Problem 95: Unique Binary Search Trees II

## Problem Information

Difficulty: **Medium**

Acceptance Rate: 0.00%

Paid Only: No

## Problem Description

Given an integer

$n$

, return

all the structurally unique

'BST'

s (binary search trees), which has exactly

$n$

nodes of unique values from

1


to

$n$

. Return the answer in

any order

•



Input:

$$n = 3$$

Output:

```
[[1,null,2,null,3],[1,null,3,2],[2,1,3],[3,1,null,null,2],[3,2,null,1]]
```

Example 2:

Input:

$$n = 1$$

Output:

[[1]]

Constraints:

$$1 \leq n \leq 8$$

## Code Snippets

**C++:**

```
/**
 * Definition for a binary tree node.
```

```

* struct TreeNode {
* int val;
* TreeNode *left;
* TreeNode *right;
* TreeNode() : val(0), left(nullptr), right(nullptr) {}
* TreeNode(int x) : val(x), left(nullptr), right(nullptr) {}
* TreeNode(int x, TreeNode *left, TreeNode *right) : val(x), left(left),
right(right) {}
* };
*/
class Solution {
public:
vector<TreeNode*> generateTrees(int n) {

}

};

```

## Java:

```

/**
 * Definition for a binary tree node.
 * public class TreeNode {
 * int val;
 * TreeNode left;
 * TreeNode right;
 * TreeNode() {}
 * TreeNode(int val) { this.val = val; }
 * TreeNode(int val, TreeNode left, TreeNode right) {
 * this.val = val;
 * this.left = left;
 * this.right = right;
 * }
 * }
 */
class Solution {
public List<TreeNode> generateTrees(int n) {

}

}

```

## Python3:

```

# Definition for a binary tree node.
# class TreeNode:
# def __init__(self, val=0, left=None, right=None):
# self.val = val
# self.left = left
# self.right = right
class Solution:
def generateTrees(self, n: int) -> List[Optional[TreeNode]]:

```

## Python:

```

# Definition for a binary tree node.
# class TreeNode(object):
# def __init__(self, val=0, left=None, right=None):
# self.val = val
# self.left = left
# self.right = right
class Solution(object):
def generateTrees(self, n):
    """
    :type n: int
    :rtype: List[Optional[TreeNode]]
    """

```

## JavaScript:

```

/**
 * Definition for a binary tree node.
 * function TreeNode(val, left, right) {
 *   this.val = (val===undefined ? 0 : val)
 *   this.left = (left===undefined ? null : left)
 *   this.right = (right===undefined ? null : right)
 * }
 */
/**
 * @param {number} n
 * @return {TreeNode[]}
 */
var generateTrees = function(n) {

};

```

## TypeScript:

```

/**
 * Definition for a binary tree node.
 * class TreeNode {
 *   val: number
 *   left: TreeNode | null
 *   right: TreeNode | null
 *   constructor(val?: number, left?: TreeNode | null, right?: TreeNode | null)
 *   {
 *     this.val = (val===undefined ? 0 : val)
 *     this.left = (left===undefined ? null : left)
 *     this.right = (right===undefined ? null : right)
 *   }
 * }
 */

function generateTrees(n: number): Array<TreeNode | null> {

};

```

## C#:

```

/**
 * Definition for a binary tree node.
 * public class TreeNode {
 *   public int val;
 *   public TreeNode left;
 *   public TreeNode right;
 *   public TreeNode(int val=0, TreeNode left=null, TreeNode right=null) {
 *     this.val = val;
 *     this.left = left;
 *     this.right = right;
 *   }
 * }
 */

public class Solution {
    public IList<TreeNode> GenerateTrees(int n) {

    }
}

```

## C:

```

/**
 * Definition for a binary tree node.
 * struct TreeNode {
 *   int val;
 *   struct TreeNode *left;
 *   struct TreeNode *right;
 * };
 */
/**
 * Note: The returned array must be malloced, assume caller calls free().
 */
struct TreeNode** generateTrees(int n, int* returnSize) {

}

```

## Go:

```

/**
 * Definition for a binary tree node.
 * type TreeNode struct {
 *   Val int
 *   Left *TreeNode
 *   Right *TreeNode
 * }
 */
func generateTrees(n int) []*TreeNode {

}

```

## Kotlin:

```

/**
 * Example:
 * var ti = TreeNode(5)
 * var v = ti.`val`
 * Definition for a binary tree node.
 * class TreeNode(var `val`: Int) {
 *   var left: TreeNode? = null
 *   var right: TreeNode? = null
 * }
 */
class Solution {
fun generateTrees(n: Int): List<TreeNode?> {

```

```
}  
}
```

## Swift:

```
/**  
 * Definition for a binary tree node.  
 * public class TreeNode {  
 * public var val: Int  
 * public var left: TreeNode?  
 * public var right: TreeNode?  
 * public init() { self.val = 0; self.left = nil; self.right = nil; }  
 * public init(_ val: Int) { self.val = val; self.left = nil; self.right =  
nil; }  
 * public init(_ val: Int, _ left: TreeNode?, _ right: TreeNode?) {  
 * self.val = val  
 * self.left = left  
 * self.right = right  
 * }  
 * }  
 */  
class Solution {  
func generateTrees(_ n: Int) -> [TreeNode?] {  
  
}  
}
```

## Rust:

```
// Definition for a binary tree node.  
// #[derive(Debug, PartialEq, Eq)]  
// pub struct TreeNode {  
// pub val: i32,  
// pub left: Option<Rc<RefCell<TreeNode>>>,  
// pub right: Option<Rc<RefCell<TreeNode>>>,  
// }  
//  
// impl TreeNode {  
// #[inline]  
// pub fn new(val: i32) -> Self {  
// TreeNode {  

```

```

// val,
// left: None,
// right: None
// }
// }
// }

use std::rc::Rc;
use std::cell::RefCell;

impl Solution {
pub fn generate_trees(n: i32) -> Vec<Option<Rc<RefCell<TreeNode>>>> {

}

}

```

## Ruby:

```

# Definition for a binary tree node.
# class TreeNode
# attr_accessor :val, :left, :right
# def initialize(val = 0, left = nil, right = nil)
# @val = val
# @left = left
# @right = right
# end
# end

# @param {Integer} n
# @return {TreeNode[]}
def generate_trees(n)

end

```

## PHP:

```

/**
 * Definition for a binary tree node.
 * class TreeNode {
 * public $val = null;
 * public $left = null;
 * public $right = null;
 * function __construct($val = 0, $left = null, $right = null) {
 * $this->val = $val;
 * $this->left = $left;

```



```

* $this->right = $right;
* }
* }
*/
class Solution {

/**
 * @param Integer $n
 * @return TreeNode[]
 */
function generateTrees($n) {

}

}

```

### Dart:

```

/**
 * Definition for a binary tree node.
 * class TreeNode {
 *   int val;
 *   TreeNode? left;
 *   TreeNode? right;
 *   TreeNode([this.val = 0, this.left, this.right]);
 * }
 */
class Solution {
  List<TreeNode?> generateTrees(int n) {

  }

}

```

### Scala:

```

/**
 * Definition for a binary tree node.
 * class TreeNode(_value: Int = 0, _left: TreeNode = null, _right: TreeNode =
 * null) {
 *   var value: Int = _value
 *   var left: TreeNode = _left
 *   var right: TreeNode = _right
 * }

```

```

*/
object Solution {
  def generateTrees(n: Int): List[TreeNode] = {

  }
}

```

## Elixir:

```

# Definition for a binary tree node.
#
# defmodule TreeNode do
#   @type t :: %__MODULE__{
#     val: integer,
#     left: TreeNode.t() | nil,
#     right: TreeNode.t() | nil
#   }
#   defstruct val: 0, left: nil, right: nil
# end

defmodule Solution do
  @spec generate_trees(n :: integer) :: [TreeNode.t | nil]
  def generate_trees(n) do

  end
end

```

## Erlang:

```

%% Definition for a binary tree node.
%%
%% -record(tree_node, {val = 0 :: integer(),
%%   left = null :: 'null' | #tree_node{},
%%   right = null :: 'null' | #tree_node{}}).

-spec generate_trees(N :: integer()) -> [#tree_node{} | null].
generate_trees(N) ->
.

```

## Racket:

```

; Definition for a binary tree node.
#|

; val : integer?
; left : (or/c tree-node? #f)
; right : (or/c tree-node? #f)
(struct tree-node
  (val left right) #:mutable #:transparent)

; constructor
(define (make-tree-node [val 0])
  (tree-node val #f #f))

|#

(define/contract (generate-trees n)
  (-> exact-integer? (listof (or/c tree-node? #f))))
)

```

## Solutions

### C++ Solution:

```

/*
 * Problem: Unique Binary Search Trees II
 * Difficulty: Medium
 * Tags: tree, dp, search
 *
 * Approach: DFS or BFS traversal
 * Time Complexity: O(n) where n is number of nodes
 * Space Complexity: O(n) or O(n * m) for DP table
 */

/**
 * Definition for a binary tree node.
 * struct TreeNode {
 *   int val;
 *   TreeNode *left;
 *   TreeNode *right;
 *   TreeNode() : val(0), left(nullptr), right(nullptr) {}
 *   TreeNode(int x) : val(x), left(nullptr), right(nullptr) {}
 */

```

```

* TreeNode(int x, TreeNode *left, TreeNode *right) : val(x), left(left),
right(right) {}
* };
*/
class Solution {
public:
vector<TreeNode*> generateTrees(int n) {

}
};

```

### Java Solution:

```

/**
 * Problem: Unique Binary Search Trees II
 * Difficulty: Medium
 * Tags: tree, dp, search
 *
 * Approach: DFS or BFS traversal
 * Time Complexity: O(n) where n is number of nodes
 * Space Complexity: O(n) or O(n * m) for DP table
 */

/**
 * Definition for a binary tree node.
 * public class TreeNode {
 * int val;
 * TreeNode left;
 * TreeNode right;
 * TreeNode() {}
 * TreeNode(int val) { this.val = val; }
 * TreeNode(int val, TreeNode left, TreeNode right) {
 * this.val = val;
 * this.left = left;
 * this.right = right;
 * }
 * }
 */
class Solution {
public List<TreeNode> generateTrees(int n) {

```

```
}  
}
```

### Python3 Solution:

```
"""  
Problem: Unique Binary Search Trees II  
Difficulty: Medium  
Tags: tree, dp, search  
  
Approach: DFS or BFS traversal  
Time Complexity: O(n) where n is number of nodes  
Space Complexity: O(n) or O(n * m) for DP table  
"""  
  
# Definition for a binary tree node.  
# class TreeNode:  
#     def __init__(self, val=0, left=None, right=None):  
#         self.val = val  
#         self.left = left  
#         self.right = right  
class Solution:  
    def generateTrees(self, n: int) -> List[Optional[TreeNode]]:  
        # TODO: Implement optimized solution  
        pass
```

### Python Solution:

```
# Definition for a binary tree node.  
# class TreeNode(object):  
#     def __init__(self, val=0, left=None, right=None):  
#         self.val = val  
#         self.left = left  
#         self.right = right  
class Solution(object):  
    def generateTrees(self, n):  
        """  
        :type n: int  
        :rtype: List[Optional[TreeNode]]  
        """
```

## JavaScript Solution:

```
/**
 * Problem: Unique Binary Search Trees II
 * Difficulty: Medium
 * Tags: tree, dp, search
 *
 * Approach: DFS or BFS traversal
 * Time Complexity: O(n) where n is number of nodes
 * Space Complexity: O(n) or O(n * m) for DP table
 */

/**
 * Definition for a binary tree node.
 * function TreeNode(val, left, right) {
 *   this.val = (val===undefined ? 0 : val)
 *   this.left = (left===undefined ? null : left)
 *   this.right = (right===undefined ? null : right)
 * }
 */

/**
 * @param {number} n
 * @return {TreeNode[]}
 */
var generateTrees = function(n) {

};
```

## TypeScript Solution:

```
/**
 * Problem: Unique Binary Search Trees II
 * Difficulty: Medium
 * Tags: tree, dp, search
 *
 * Approach: DFS or BFS traversal
 * Time Complexity: O(n) where n is number of nodes
 * Space Complexity: O(n) or O(n * m) for DP table
 */

/**
 * Definition for a binary tree node.
 * class TreeNode {
```

```

* val: number
* left: TreeNode | null
* right: TreeNode | null
* constructor(val?: number, left?: TreeNode | null, right?: TreeNode | null)
{
* this.val = (val===undefined ? 0 : val)
* this.left = (left===undefined ? null : left)
* this.right = (right===undefined ? null : right)
* }
* }
*/

function generateTrees(n: number): Array<TreeNode | null> {

};

```

## C# Solution:

```

/*
* Problem: Unique Binary Search Trees II
* Difficulty: Medium
* Tags: tree, dp, search
*
* Approach: DFS or BFS traversal
* Time Complexity: O(n) where n is number of nodes
* Space Complexity: O(n) or O(n * m) for DP table
*/

/**
* Definition for a binary tree node.
* public class TreeNode {
* public int val;
* public TreeNode left;
* public TreeNode right;
* public TreeNode(int val=0, TreeNode left=null, TreeNode right=null) {
* this.val = val;
* this.left = left;
* this.right = right;
* }
* }
*/

```

```

public class Solution {
    public IList<TreeNode> GenerateTrees(int n) {

    }

}

```

## C Solution:

```

/*
 * Problem: Unique Binary Search Trees II
 * Difficulty: Medium
 * Tags: tree, dp, search
 *
 * Approach: DFS or BFS traversal
 * Time Complexity: O(n) where n is number of nodes
 * Space Complexity: O(n) or O(n * m) for DP table
 */

/**
 * Definition for a binary tree node.
 * struct TreeNode {
 *     int val;
 *     struct TreeNode *left;
 *     struct TreeNode *right;
 * };
 */

/**
 * Note: The returned array must be malloced, assume caller calls free().
 */
struct TreeNode** generateTrees(int n, int* returnSize) {

}

```

## Go Solution:

```

// Problem: Unique Binary Search Trees II
// Difficulty: Medium
// Tags: tree, dp, search
//
// Approach: DFS or BFS traversal
// Time Complexity: O(n) where n is number of nodes

```



```
// Space Complexity: O(n) or O(n * m) for DP table

/**
 * Definition for a binary tree node.
 * type TreeNode struct {
 *     Val int
 *     Left *TreeNode
 *     Right *TreeNode
 * }
 */
func generateTrees(n int) []*TreeNode {

}
```

### Kotlin Solution:

```
/**
 * Example:
 * var ti = TreeNode(5)
 * var v = ti.`val`
 * Definition for a binary tree node.
 * class TreeNode(var `val`: Int) {
 *     var left: TreeNode? = null
 *     var right: TreeNode? = null
 * }
 */
class Solution {
fun generateTrees(n: Int): List<TreeNode?> {

}

}
```

### Swift Solution:

```
/**
 * Definition for a binary tree node.
 * public class TreeNode {
 *     public var val: Int
 *     public var left: TreeNode?
 *     public var right: TreeNode?
 *     public init() { self.val = 0; self.left = nil; self.right = nil; }
 * }
```

```

* public init(_ val: Int) { self.val = val; self.left = nil; self.right =
nil; }
* public init(_ val: Int, _ left: TreeNode?, _ right: TreeNode?) {
* self.val = val
* self.left = left
* self.right = right
* }
* }
*/

class Solution {
func generateTrees(_ n: Int) -> [TreeNode?] {

}

}

```

## Rust Solution:

```

// Problem: Unique Binary Search Trees II
// Difficulty: Medium
// Tags: tree, dp, search
//
// Approach: DFS or BFS traversal
// Time Complexity: O(n) where n is number of nodes
// Space Complexity: O(n) or O(n * m) for DP table

// Definition for a binary tree node.
// #[derive(Debug, PartialEq, Eq)]
// pub struct TreeNode {
//     pub val: i32,
//     pub left: Option<Rc<RefCell<TreeNode>>>,
//     pub right: Option<Rc<RefCell<TreeNode>>>,
// }
//
// impl TreeNode {
//     #[inline]
//     pub fn new(val: i32) -> Self {
//         TreeNode {
//             val,
//             left: None,
//             right: None
//         }
//     }
// }

```

```

// }
// }
use std::rc::Rc;
use std::cell::RefCell;
impl Solution {
pub fn generate_trees(n: i32) -> Vec<Option<Rc<RefCell<TreeNode>>>> {

}
}

```

### Ruby Solution:

```

# Definition for a binary tree node.
# class TreeNode
# attr_accessor :val, :left, :right
# def initialize(val = 0, left = nil, right = nil)
# @val = val
# @left = left
# @right = right
# end
# end
# @param {Integer} n
# @return {TreeNode[]}
def generate_trees(n)

end

```

### PHP Solution:

```

/**
 * Definition for a binary tree node.
 * class TreeNode {
 * public $val = null;
 * public $left = null;
 * public $right = null;
 * function __construct($val = 0, $left = null, $right = null) {
 * $this->val = $val;
 * $this->left = $left;
 * $this->right = $right;
 * }
 * }
 */

```

```

*/
class Solution {

/**
 * @param Integer $n
 * @return TreeNode[]
 */
function generateTrees($n) {

}

}

```

### Dart Solution:

```

/**
 * Definition for a binary tree node.
 * class TreeNode {
 *   int val;
 *   TreeNode? left;
 *   TreeNode? right;
 *   TreeNode([this.val = 0, this.left, this.right]);
 * }
 */
class Solution {
  List<TreeNode?> generateTrees(int n) {

  }

}

```

### Scala Solution:

```

/**
 * Definition for a binary tree node.
 * class TreeNode(_value: Int = 0, _left: TreeNode = null, _right: TreeNode =
 * null) {
 *   var value: Int = _value
 *   var left: TreeNode = _left
 *   var right: TreeNode = _right
 * }
 */
object Solution {

```

```
def generateTrees(n: Int): List[TreeNode] = {

}

}
```

### Elixir Solution:

```
# Definition for a binary tree node.
#
# defmodule TreeNode do
#   @type t :: %__MODULE__{
#     val: integer,
#     left: TreeNode.t() | nil,
#     right: TreeNode.t() | nil
#   }
#   defstruct val: 0, left: nil, right: nil
# end

defmodule Solution do
  @spec generate_trees(n :: integer) :: [TreeNode.t | nil]
  def generate_trees(n) do

  end
end
```

### Erlang Solution:

```
%% Definition for a binary tree node.
%%
%% -record(tree_node, {val = 0 :: integer(),
%% left = null :: 'null' | #tree_node{},
%% right = null :: 'null' | #tree_node{}}).

-spec generate_trees(N :: integer()) -> [#tree_node{} | null].
generate_trees(N) ->
.

```

### Racket Solution:

```
; Definition for a binary tree node.
#|
```

```
; val : integer?
; left : (or/c tree-node? #f)
; right : (or/c tree-node? #f)
(struct tree-node
  (val left right) #:mutable #:transparent)

; constructor
(define (make-tree-node [val 0])
  (tree-node val #f #f))

|#

(define/contract (generate-trees n)
  (-> exact-integer? (listof (or/c tree-node? #f))))
)
```