

Problem 1582: Special Positions in a Binary Matrix

Problem Information

Difficulty: [Easy](#)

Acceptance Rate: 0.00%

Paid Only: No

Problem Description

Given an

$m \times n$

binary matrix

`mat`

, return

the number of special positions in

`mat`

.

A position

(i, j)

is called

special

if

`mat[i][j] == 1`

and all other elements in row

`i`

and column

`j`

are

0

(rows and columns are

0-indexed

).

Example 1:

1	0	0
0	0	1
1	0	0

Input:

```
mat = [[1,0,0],[0,0,1],[1,0,0]]
```

Output:

1

Explanation:

(1, 2) is a special position because $\text{mat}[1][2] == 1$ and all other elements in row 1 and column 2 are 0.

Example 2:

1	0	0
0	1	0
0	0	1

Input:

```
mat = [[1,0,0],[0,1,0],[0,0,1]]
```

Output:

3

Explanation:

(0, 0), (1, 1) and (2, 2) are special positions.

Constraints:

$m == \text{mat.length}$

$n == \text{mat}[i].\text{length}$

$1 \leq m, n \leq 100$

$\text{mat}[i][j]$

is either

0

or

1

.

Code Snippets

C++:

```
class Solution {
public:
    int numSpecial(vector<vector<int>>& mat) {

    }
};
```

Java:

```
class Solution {
    public int numSpecial(int[][] mat) {

    }
}
```

Python3:

```
class Solution:
    def numSpecial(self, mat: List[List[int]]) -> int:
```

Python:

```
class Solution(object):
    def numSpecial(self, mat):
        """
        :type mat: List[List[int]]
        :rtype: int
        """
```

JavaScript:

```
/**
 * @param {number[][]} mat
 * @return {number}
 */
var numSpecial = function(mat) {

};
```

TypeScript:

```
function numSpecial(mat: number[][]): number {

};
```

C#:

```
public class Solution {
    public int NumSpecial(int[][] mat) {

    }
}
```

C:

```
int numSpecial(int** mat, int matSize, int* matColSize) {

}
```

Go:

```
func numSpecial(mat [][]int) int {  
  
}
```

Kotlin:

```
class Solution {  
    fun numSpecial(mat: Array<IntArray>): Int {  
  
    }  
}
```

Swift:

```
class Solution {  
    func numSpecial(_ mat: [[Int]]) -> Int {  
  
    }  
}
```

Rust:

```
impl Solution {  
    pub fn num_special(mat: Vec<Vec<i32>>) -> i32 {  
  
    }  
}
```

Ruby:

```
# @param {Integer[][]} mat  
# @return {Integer}  
def num_special(mat)  
  
end
```

PHP:

```
class Solution {  
  
    /**
```

```

* @param Integer[][] $mat
* @return Integer
*/
function numSpecial($mat) {

}
}

```

Dart:

```

class Solution {
  int numSpecial(List<List<int>> mat) {

  }
}

```

Scala:

```

object Solution {
  def numSpecial(mat: Array[Array[Int]]): Int = {

  }
}

```

Elixir:

```

defmodule Solution do
  @spec num_special(mat :: [[integer]]) :: integer
  def num_special(mat) do

  end
end

```

Erlang:

```

-spec num_special(Mat :: [[integer()]]) -> integer().
num_special(Mat) ->
.

```

Racket:

```
(define/contract (num-special mat)
  (-> (listof (listof exact-integer?)) exact-integer?)
)
```

Solutions

C++ Solution:

```
/*
 * Problem: Special Positions in a Binary Matrix
 * Difficulty: Easy
 * Tags: array
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

class Solution {
public:
    int numSpecial(vector<vector<int>>& mat) {

    }
};
```

Java Solution:

```
/**
 * Problem: Special Positions in a Binary Matrix
 * Difficulty: Easy
 * Tags: array
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

class Solution {
    public int numSpecial(int[][] mat) {

    }
}
```



```
}
```

Python3 Solution:

```
"""
Problem: Special Positions in a Binary Matrix
Difficulty: Easy
Tags: array

Approach: Use two pointers or sliding window technique
Time Complexity: O(n) or O(n log n)
Space Complexity: O(1) to O(n) depending on approach
"""

class Solution:
    def numSpecial(self, mat: List[List[int]]) -> int:
        # TODO: Implement optimized solution
        pass
```

Python Solution:

```
class Solution(object):
    def numSpecial(self, mat):
        """
        :type mat: List[List[int]]
        :rtype: int
        """
```

JavaScript Solution:

```
/**
 * Problem: Special Positions in a Binary Matrix
 * Difficulty: Easy
 * Tags: array
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

/**
```

```

* @param {number[][]} mat
* @return {number}
*/
var numSpecial = function(mat) {

};

```

TypeScript Solution:

```

/**
 * Problem: Special Positions in a Binary Matrix
 * Difficulty: Easy
 * Tags: array
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

function numSpecial(mat: number[][]): number {

};

```

C# Solution:

```

/*
 * Problem: Special Positions in a Binary Matrix
 * Difficulty: Easy
 * Tags: array
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

public class Solution {
    public int NumSpecial(int[][] mat) {

    }
}

```

C Solution:

```
/*
 * Problem: Special Positions in a Binary Matrix
 * Difficulty: Easy
 * Tags: array
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

int numSpecial(int** mat, int matSize, int* matColSize) {

}
```

Go Solution:

```
// Problem: Special Positions in a Binary Matrix
// Difficulty: Easy
// Tags: array
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(1) to O(n) depending on approach

func numSpecial(mat [][]int) int {

}
```

Kotlin Solution:

```
class Solution {
    fun numSpecial(mat: Array<IntArray>): Int {

    }
}
```

Swift Solution:

```
class Solution {
    func numSpecial(_ mat: [[Int]]) -> Int {
```

```
}  
}
```

Rust Solution:

```
// Problem: Special Positions in a Binary Matrix  
// Difficulty: Easy  
// Tags: array  
//  
// Approach: Use two pointers or sliding window technique  
// Time Complexity: O(n) or O(n log n)  
// Space Complexity: O(1) to O(n) depending on approach  
  
impl Solution {  
    pub fn num_special(mat: Vec<Vec<i32>>) -> i32 {  
  
    }  
}
```

Ruby Solution:

```
# @param {Integer[][]} mat  
# @return {Integer}  
def num_special(mat)  
  
end
```

PHP Solution:

```
class Solution {  
  
    /**  
     * @param Integer[][] $mat  
     * @return Integer  
     */  
    function numSpecial($mat) {  
  
    }  
}
```

Dart Solution:

```
class Solution {  
  int numSpecial(List<List<int>> mat) {  
  
  }  
}
```

Scala Solution:

```
object Solution {  
  def numSpecial(mat: Array[Array[Int]]): Int = {  
  
  }  
}
```

Elixir Solution:

```
defmodule Solution do  
  @spec num_special(mat :: [[integer]]) :: integer  
  def num_special(mat) do  
  
  end  
end
```

Erlang Solution:

```
-spec num_special(Mat :: [[integer()]]) -> integer().  
num_special(Mat) ->  
.
```

Racket Solution:

```
(define/contract (num-special mat)  
  (-> (listof (listof exact-integer?)) exact-integer?)  
)
```