

Problem 1094: Car Pooling

Problem Information

Difficulty: Medium

Acceptance Rate: 56.14%

Paid Only: No

Tags: Array, Sorting, Heap (Priority Queue), Simulation, Prefix Sum

Problem Description

There is a car with `capacity` empty seats. The vehicle only drives east (i.e., it cannot turn around and drive west).

You are given the integer `capacity` and an array `trips` where `trips[i] = [numPassengersi, fromi, toi]` indicates that the `ith` trip has `numPassengersi` passengers and the locations to pick them up and drop them off are `fromi` and `toi` respectively. The locations are given as the number of kilometers due east from the car's initial location.

Return `true` if it is possible to pick up and drop off all passengers for all the given trips, or `false` otherwise.

Example 1:

Input: trips = [[2,1,5],[3,3,7]], capacity = 4 **Output:** false

Example 2:

Input: trips = [[2,1,5],[3,3,7]], capacity = 5 **Output:** true

Constraints:

* `1` <= trips.length <= 1000 * `trips[i].length == 3` * `1` <= numPassengersi <= 100 * `0` <= fromi < toi <= 1000 * `1` <= capacity <= 105`

Code Snippets

C++:

```
class Solution {  
public:  
    bool carPooling(vector<vector<int>>& trips, int capacity) {  
  
    }  
};
```

Java:

```
class Solution {  
    public boolean carPooling(int[][] trips, int capacity) {  
  
    }  
}
```

Python3:

```
class Solution:  
    def carPooling(self, trips: List[List[int]], capacity: int) -> bool:
```