

# Problem 1906: Minimum Absolute Difference Queries

## Problem Information

Difficulty: **Medium**

Acceptance Rate: 0.00%

Paid Only: No

## Problem Description

The

minimum absolute difference

of an array

a

is defined as the

minimum value

of

$|a[i] - a[j]|$

, where

$0 \leq i < j < a.length$

and

$a[i] \neq a[j]$

. If all elements of

a

are the

same

, the minimum absolute difference is

-1

.

For example, the minimum absolute difference of the array

[5,

2

,

3

,7,2]

is

$$|2 - 3| = 1$$

. Note that it is not

0

because

$a[i]$

and

`a[j]`

must be different.

You are given an integer array

`nums`

and the array

`queries`

where

`queries[i] = [l`

`i`

`, r`

`i`

`]`

. For each query

`i`

, compute the

minimum absolute difference

of the

subarray

`nums[l`

`i`

...r

i

]

containing the elements of

nums

between the

0-based

indices

l

i

and

r

i

(

inclusive

).

Return

an

array

ans

where

ans[i]

is the answer to the

i

th

query

.

A

subarray

is a contiguous sequence of elements in an array.

The value of

$|x|$

is defined as:

$x$

if

$x \geq 0$

.

$-x$

if

$x < 0$

.

Example 1:

Input:

nums = [1,3,4,8], queries = [[0,1],[1,2],[2,3],[0,3]]

Output:

[2,1,4,1]

Explanation:

The queries are processed as follows: - queries[0] = [0,1]: The subarray is [

1

,

3

] and the minimum absolute difference is  $|1-3| = 2$ . - queries[1] = [1,2]: The subarray is [

3

,

4

] and the minimum absolute difference is  $|3-4| = 1$ . - queries[2] = [2,3]: The subarray is [

4

,

8

] and the minimum absolute difference is  $|4-8| = 4$ . - queries[3] = [0,3]: The subarray is [1,

3

,

4

,8] and the minimum absolute difference is  $|3-4| = 1$ .

Example 2:

Input:

nums = [4,5,2,2,7,10], queries = [[2,3],[0,2],[0,5],[3,5]]

Output:

[-1,1,1,3]

Explanation:

The queries are processed as follows: - queries[0] = [2,3]: The subarray is [2,2] and the minimum absolute difference is -1 because all the elements are the same. - queries[1] = [0,2]: The subarray is [

4

,

5

,2] and the minimum absolute difference is  $|4-5| = 1$ . - queries[2] = [0,5]: The subarray is [

4

,

5

,2,2,7,10] and the minimum absolute difference is  $|4-5| = 1$ . - queries[3] = [3,5]: The subarray is [2,

7

,

10

] and the minimum absolute difference is  $|7-10| = 3$ .

Constraints:

$2 \leq \text{nums.length} \leq 10$

5

$1 \leq \text{nums}[i] \leq 100$

$1 \leq \text{queries.length} \leq 2 * 10$

4

$0 \leq l$

i

$< r$

i

$< \text{nums.length}$

**Code Snippets**



### C++:

```
class Solution {
public:
    vector<int> minDifference(vector<int>& nums, vector<vector<int>>& queries) {

    }
};
```

### Java:

```
class Solution {
    public int[] minDifference(int[] nums, int[][] queries) {

    }
}
```

### Python3:

```
class Solution:
    def minDifference(self, nums: List[int], queries: List[List[int]]) ->
        List[int]:
```

### Python:

```
class Solution(object):
    def minDifference(self, nums, queries):
        """
        :type nums: List[int]
        :type queries: List[List[int]]
        :rtype: List[int]
        """
```

### JavaScript:

```
/**
 * @param {number[]} nums
 * @param {number[][]} queries
 * @return {number[]}
 */
var minDifference = function(nums, queries) {

};
```

### TypeScript:

```
function minDifference(nums: number[], queries: number[][]): number[] {  
  
};
```

### C#:

```
public class Solution {  
    public int[] MinDifference(int[] nums, int[][] queries) {  
  
    }  
}
```

### C:

```
/**  
 * Note: The returned array must be malloced, assume caller calls free().  
 */  
int* minDifference(int* nums, int numsSize, int** queries, int queriesSize,  
int* queriesColSize, int* returnSize) {  
  
}
```

### Go:

```
func minDifference(nums []int, queries [][]int) []int {  
  
}
```

### Kotlin:

```
class Solution {  
    fun minDifference(nums: IntArray, queries: Array<IntArray>): IntArray {  
  
    }  
}
```

### Swift:

```
class Solution {  
    func minDifference(_ nums: [Int], _ queries: [[Int]]) -> [Int] {  
  
    }  
}
```

```
}  
}
```

### Rust:

```
impl Solution {  
    pub fn min_difference(nums: Vec<i32>, queries: Vec<Vec<i32>>) -> Vec<i32> {  
  
    }  
}
```

### Ruby:

```
# @param {Integer[]} nums  
# @param {Integer[][]} queries  
# @return {Integer[]}  
def min_difference(nums, queries)  
  
end
```

### PHP:

```
class Solution {  
  
    /**  
     * @param Integer[] $nums  
     * @param Integer[][] $queries  
     * @return Integer[]  
     */  
    function minDifference($nums, $queries) {  
  
    }  
}
```

### Dart:

```
class Solution {  
    List<int> minDifference(List<int> nums, List<List<int>> queries) {  
  
    }  
}
```

## Scala:

```
object Solution {  
  def minDifference(nums: Array[Int], queries: Array[Array[Int]]): Array[Int] =  
  {  
  
  }  
}
```

## Elixir:

```
defmodule Solution do  
  @spec min_difference(nums :: [integer], queries :: [[integer]]) :: [integer]  
  def min_difference(nums, queries) do  
  
  end  
end
```

## Erlang:

```
-spec min_difference(Nums :: [integer()], Queries :: [[integer()]]) ->  
[integer()].  
min_difference(Nums, Queries) ->  
.
```

## Racket:

```
(define/contract (min-difference nums queries)  
  (-> (listof exact-integer?) (listof (listof exact-integer?)) (listof  
    exact-integer?))  
  )
```

## Solutions

### C++ Solution:

```
/*  
 * Problem: Minimum Absolute Difference Queries  
 * Difficulty: Medium  
 * Tags: array, hash  
 *  
 * Approach: Use two pointers or sliding window technique
```

```

* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(n) for hash map
*/

class Solution {
public:
vector<int> minDifference(vector<int>& nums, vector<vector<int>>& queries) {

}

};

```

### Java Solution:

```

/**
 * Problem: Minimum Absolute Difference Queries
 * Difficulty: Medium
 * Tags: array, hash
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

class Solution {
public int[] minDifference(int[] nums, int[][] queries) {

}

}

```

### Python3 Solution:

```

"""
Problem: Minimum Absolute Difference Queries
Difficulty: Medium
Tags: array, hash

Approach: Use two pointers or sliding window technique
Time Complexity: O(n) or O(n log n)
Space Complexity: O(n) for hash map
"""

```

```

class Solution:
    def minDifference(self, nums: List[int], queries: List[List[int]]) ->
    List[int]:
        # TODO: Implement optimized solution
        pass

```

## Python Solution:

```

class Solution(object):
    def minDifference(self, nums, queries):
        """
        :type nums: List[int]
        :type queries: List[List[int]]
        :rtype: List[int]
        """

```

## JavaScript Solution:

```

/**
 * Problem: Minimum Absolute Difference Queries
 * Difficulty: Medium
 * Tags: array, hash
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

/**
 * @param {number[]} nums
 * @param {number[][]} queries
 * @return {number[]}
 */
var minDifference = function(nums, queries) {

};

```

## TypeScript Solution:

```

/**
 * Problem: Minimum Absolute Difference Queries

```

```

* Difficulty: Medium
* Tags: array, hash
*
* Approach: Use two pointers or sliding window technique
* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(n) for hash map
*/

function minDifference(nums: number[], queries: number[][]): number[] {

};

```

### C# Solution:

```

/*
* Problem: Minimum Absolute Difference Queries
* Difficulty: Medium
* Tags: array, hash
*
* Approach: Use two pointers or sliding window technique
* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(n) for hash map
*/

public class Solution {
    public int[] MinDifference(int[] nums, int[][] queries) {

    }
}

```

### C Solution:

```

/*
* Problem: Minimum Absolute Difference Queries
* Difficulty: Medium
* Tags: array, hash
*
* Approach: Use two pointers or sliding window technique
* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(n) for hash map
*/

```

```

/**
 * Note: The returned array must be malloced, assume caller calls free().
 */
int* minDifference(int* nums, int numsSize, int** queries, int queriesSize,
int* queriesColSize, int* returnSize) {

}

```

### Go Solution:

```

// Problem: Minimum Absolute Difference Queries
// Difficulty: Medium
// Tags: array, hash
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(n) for hash map

func minDifference(nums []int, queries [][]int) []int {

}

```

### Kotlin Solution:

```

class Solution {
    fun minDifference(nums: IntArray, queries: Array<IntArray>): IntArray {

    }
}

```

### Swift Solution:

```

class Solution {
    func minDifference(_ nums: [Int], _ queries: [[Int]]) -> [Int] {

    }
}

```

### Rust Solution:



```

// Problem: Minimum Absolute Difference Queries
// Difficulty: Medium
// Tags: array, hash
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(n) for hash map

impl Solution {
    pub fn min_difference(nums: Vec<i32>, queries: Vec<Vec<i32>> > -> Vec<i32> {

    }
}

```

### Ruby Solution:

```

# @param {Integer[]} nums
# @param {Integer[][]} queries
# @return {Integer[]}
def min_difference(nums, queries)

end

```

### PHP Solution:

```

class Solution {

    /**
     * @param Integer[] $nums
     * @param Integer[][] $queries
     * @return Integer[]
     */
    function minDifference($nums, $queries) {

    }

}

```

### Dart Solution:

```

class Solution {
    List<int> minDifference(List<int> nums, List<List<int>> queries) {

```

```
}  
}
```

### Scala Solution:

```
object Solution {  
  def minDifference(nums: Array[Int], queries: Array[Array[Int]]): Array[Int] =  
  {  
  
  }  
}
```

### Elixir Solution:

```
defmodule Solution do  
  @spec min_difference(nums :: [integer], queries :: [[integer]]) :: [integer]  
  def min_difference(nums, queries) do  
  
  end  
end
```

### Erlang Solution:

```
-spec min_difference(Nums :: [integer()], Queries :: [[integer()]]) ->  
[integer()].  
min_difference(Nums, Queries) ->  
.
```

### Racket Solution:

```
(define/contract (min-difference nums queries)  
  (-> (listof exact-integer?) (listof (listof exact-integer?)) (listof  
    exact-integer?))  
  )
```