

# Problem 732: My Calendar III

## Problem Information

Difficulty: **Hard**

Acceptance Rate: 0.00%

Paid Only: No

## Problem Description

A

k

-booking happens when

k

events have some non-empty intersection (i.e., there is some time that is common to all

k

events.)

You are given some events

[startTime, endTime)

, after each given event, return an integer

k

representing the maximum

k

-booking between all the previous events.

Implement the

MyCalendarThree

class:

MyCalendarThree()

Initializes the object.

int book(int startTime, int endTime)

Returns an integer

k

representing the largest integer such that there exists a

k

-booking in the calendar.

Example 1:

Input

```
["MyCalendarThree", "book", "book", "book", "book", "book", "book"]  
[[], [10, 20], [50, 60], [10, 40], [5, 15], [5, 10], [25, 55]]
```

Output

```
[null, 1, 1, 2, 3, 3, 3]
```

Explanation

```
MyCalendarThree myCalendarThree = new MyCalendarThree();  
myCalendarThree.book(10, 20); // return 1  
myCalendarThree.book(50, 60); // return 1  
myCalendarThree.book(10, 40); //
```

return 2 myCalendarThree.book(5, 15); // return 3 myCalendarThree.book(5, 10); // return 3  
myCalendarThree.book(25, 55); // return 3

Constraints:

$0 \leq \text{startTime} < \text{endTime} \leq 10$

9

At most

400

calls will be made to

book

.

## Code Snippets

**C++:**

```
class MyCalendarThree {
public:
    MyCalendarThree() {

    }

    int book(int startTime, int endTime) {

    }
};

/**
 * Your MyCalendarThree object will be instantiated and called as such:
 * MyCalendarThree* obj = new MyCalendarThree();
 * int param_1 = obj->book(startTime,endTime);
 */
```

## Java:

```
class MyCalendarThree {

    public MyCalendarThree() {

    }

    public int book(int startTime, int endTime) {

    }

}

/**
 * Your MyCalendarThree object will be instantiated and called as such:
 * MyCalendarThree obj = new MyCalendarThree();
 * int param_1 = obj.book(startTime,endTime);
 */
```

## Python3:

```
class MyCalendarThree:

    def __init__(self):

    def book(self, startTime: int, endTime: int) -> int:

    # Your MyCalendarThree object will be instantiated and called as such:
    # obj = MyCalendarThree()
    # param_1 = obj.book(startTime,endTime)
```

## Python:

```
class MyCalendarThree(object):

    def __init__(self):

    def book(self, startTime, endTime):
        """
```

```

:type startTime: int
:type endTime: int
:rtype: int
"""

# Your MyCalendarThree object will be instantiated and called as such:
# obj = MyCalendarThree()
# param_1 = obj.book(startTime,endTime)

```

### JavaScript:

```

var MyCalendarThree = function() {

};

/**
 * @param {number} startTime
 * @param {number} endTime
 * @return {number}
 */
MyCalendarThree.prototype.book = function(startTime, endTime) {

};

/**
 * Your MyCalendarThree object will be instantiated and called as such:
 * var obj = new MyCalendarThree()
 * var param_1 = obj.book(startTime,endTime)
 */

```

### TypeScript:

```

class MyCalendarThree {
  constructor() {

  }

  book(startTime: number, endTime: number): number {

```

```

}
}

/**
 * Your MyCalendarThree object will be instantiated and called as such:
 * var obj = new MyCalendarThree()
 * var param_1 = obj.book(startTime,endTime)
 */

```

### C#:

```

public class MyCalendarThree {

    public MyCalendarThree() {

    }

    public int Book(int startTime, int endTime) {

    }

}

/**
 * Your MyCalendarThree object will be instantiated and called as such:
 * MyCalendarThree obj = new MyCalendarThree();
 * int param_1 = obj.Book(startTime,endTime);
 */

```

### C:

```

typedef struct {

} MyCalendarThree;

MyCalendarThree* myCalendarThreeCreate() {

}

```

```

int myCalendarThreeBook(MyCalendarThree* obj, int startTime, int endTime) {

}

void myCalendarThreeFree(MyCalendarThree* obj) {

}

/**
 * Your MyCalendarThree struct will be instantiated and called as such:
 * MyCalendarThree* obj = myCalendarThreeCreate();
 * int param_1 = myCalendarThreeBook(obj, startTime, endTime);

 * myCalendarThreeFree(obj);
 */

```

## Go:

```

type MyCalendarThree struct {

}

func Constructor() MyCalendarThree {

}

func (this *MyCalendarThree) Book(startTime int, endTime int) int {

}

/**
 * Your MyCalendarThree object will be instantiated and called as such:
 * obj := Constructor();
 * param_1 := obj.Book(startTime,endTime);
 */

```

## Kotlin:

```

class MyCalendarThree() {

    fun book(startTime: Int, endTime: Int): Int {

    }

}

/**
 * Your MyCalendarThree object will be instantiated and called as such:
 * var obj = MyCalendarThree()
 * var param_1 = obj.book(startTime,endTime)
 */

```

### Swift:

```

class MyCalendarThree {

    init() {

    }

    func book(_ startTime: Int, _ endTime: Int) -> Int {

    }

}

/**
 * Your MyCalendarThree object will be instantiated and called as such:
 * let obj = MyCalendarThree()
 * let ret_1: Int = obj.book(startTime, endTime)
 */

```

### Rust:

```

struct MyCalendarThree {

}

/**
 * `&self` means the method takes an immutable reference.

```

```

* If you need a mutable reference, change it to `&mut self` instead.
*/
impl MyCalendarThree {

    fn new() -> Self {

    }

    fn book(&self, start_time: i32, end_time: i32) -> i32 {

    }
}

/**
 * Your MyCalendarThree object will be instantiated and called as such:
 * let obj = MyCalendarThree::new();
 * let ret_1: i32 = obj.book(startTime, endTime);
 */

```

## Ruby:

```

class MyCalendarThree
  def initialize()

  end

  =begin
  :type start_time: Integer
  :type end_time: Integer
  :rtype: Integer
  =end
  def book(start_time, end_time)

  end

end

# Your MyCalendarThree object will be instantiated and called as such:
# obj = MyCalendarThree.new()
# param_1 = obj.book(start_time, end_time)

```

## PHP:

```
class MyCalendarThree {  
    /**  
    */  
    function __construct() {  
  
    }  
  
    /**  
    * @param Integer $startTime  
    * @param Integer $endTime  
    * @return Integer  
    */  
    function book($startTime, $endTime) {  
  
    }  
}  
  
/**  
* Your MyCalendarThree object will be instantiated and called as such:  
* $obj = MyCalendarThree();  
* $ret_1 = $obj->book($startTime, $endTime);  
*/
```

## Dart:

```
class MyCalendarThree {  
  
    MyCalendarThree() {  
  
    }  
  
    int book(int startTime, int endTime) {  
  
    }  
}  
  
/**  
* Your MyCalendarThree object will be instantiated and called as such:  
* MyCalendarThree obj = MyCalendarThree();  
* int param1 = obj.book(startTime,endTime);  
*/
```

```
*/
```

### Scala:

```
class MyCalendarThree() {  
  
  def book(startTime: Int, endTime: Int): Int = {  
  
  }  
  
}  
  
/**  
 * Your MyCalendarThree object will be instantiated and called as such:  
 * val obj = new MyCalendarThree()  
 * val param_1 = obj.book(startTime,endTime)  
 */
```

### Elixir:

```
defmodule MyCalendarThree do  
  @spec init_() :: any  
  def init_() do  
  
  end  
  
  @spec book(start_time :: integer, end_time :: integer) :: integer  
  def book(start_time, end_time) do  
  
  end  
end  
  
# Your functions will be called as such:  
# MyCalendarThree.init_()  
# param_1 = MyCalendarThree.book(start_time, end_time)  
  
# MyCalendarThree.init_ will be called before every test case, in which you  
# can do some necessary initializations.
```

### Erlang:

```

-spec my_calendar_three_init_() -> any().
my_calendar_three_init_() ->
.

-spec my_calendar_three_book(StartTime :: integer(), EndTime :: integer()) ->
integer().
my_calendar_three_book(StartTime, EndTime) ->
.

%% Your functions will be called as such:
%% my_calendar_three_init_(),
%% Param_1 = my_calendar_three_book(StartTime, EndTime),

%% my_calendar_three_init_ will be called before every test case, in which
you can do some necessary initializations.

```

## Racket:

```

(define my-calendar-three%
  (class object%
    (super-new)

    (init-field)

    ; book : exact-integer? exact-integer? -> exact-integer?
    (define/public (book start-time end-time)
      )))

;; Your my-calendar-three% object will be instantiated and called as such:
;; (define obj (new my-calendar-three%))
;; (define param_1 (send obj book start-time end-time))

```

## Solutions

### C++ Solution:

```

/*
 * Problem: My Calendar III
 * Difficulty: Hard
 * Tags: array, tree, search

```

```

*
* Approach: Use two pointers or sliding window technique
* Time Complexity:  $O(n)$  or  $O(n \log n)$ 
* Space Complexity:  $O(h)$  for recursion stack where h is height
*/

class MyCalendarThree {
public:
    MyCalendarThree() {

    }

    int book(int startTime, int endTime) {

    }
};

/**
 * Your MyCalendarThree object will be instantiated and called as such:
 * MyCalendarThree* obj = new MyCalendarThree();
 * int param_1 = obj->book(startTime,endTime);
 */

```

## Java Solution:

```

/**
 * Problem: My Calendar III
 * Difficulty: Hard
 * Tags: array, tree, search
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity:  $O(n)$  or  $O(n \log n)$ 
 * Space Complexity:  $O(h)$  for recursion stack where h is height
 */

class MyCalendarThree {

    public MyCalendarThree() {

    }

}

```

```

public int book(int startTime, int endTime) {

}

}

/**
 * Your MyCalendarThree object will be instantiated and called as such:
 * MyCalendarThree obj = new MyCalendarThree();
 * int param_1 = obj.book(startTime,endTime);
 */

```

### Python3 Solution:

```

"""
Problem: My Calendar III
Difficulty: Hard
Tags: array, tree, search

Approach: Use two pointers or sliding window technique
Time Complexity: O(n) or O(n log n)
Space Complexity: O(h) for recursion stack where h is height
"""

class MyCalendarThree:

    def __init__(self):

    def book(self, startTime: int, endTime: int) -> int:
        # TODO: Implement optimized solution
        pass

```

### Python Solution:

```

class MyCalendarThree(object):

    def __init__(self):

    def book(self, startTime, endTime):
        """

```

```

:type startTime: int
:type endTime: int
:rtype: int
"""

# Your MyCalendarThree object will be instantiated and called as such:
# obj = MyCalendarThree()
# param_1 = obj.book(startTime,endTime)

```

### JavaScript Solution:

```

/**
 * Problem: My Calendar III
 * Difficulty: Hard
 * Tags: array, tree, search
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(h) for recursion stack where h is height
 */

var MyCalendarThree = function() {

};

/**
 * @param {number} startTime
 * @param {number} endTime
 * @return {number}
 */
MyCalendarThree.prototype.book = function(startTime, endTime) {

};

/**
 * Your MyCalendarThree object will be instantiated and called as such:
 * var obj = new MyCalendarThree()
 * var param_1 = obj.book(startTime,endTime)
 */

```

```
*/
```

### TypeScript Solution:

```
/**
 * Problem: My Calendar III
 * Difficulty: Hard
 * Tags: array, tree, search
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(h) for recursion stack where h is height
 */

class MyCalendarThree {
  constructor() {

  }

  book(startTime: number, endTime: number): number {

  }
}

/**
 * Your MyCalendarThree object will be instantiated and called as such:
 * var obj = new MyCalendarThree()
 * var param_1 = obj.book(startTime,endTime)
 */
```

### C# Solution:

```
/*
 * Problem: My Calendar III
 * Difficulty: Hard
 * Tags: array, tree, search
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(h) for recursion stack where h is height
 */
```

```

public class MyCalendarThree {

    public MyCalendarThree() {

    }

    public int Book(int startTime, int endTime) {

    }

}

/**
 * Your MyCalendarThree object will be instantiated and called as such:
 * MyCalendarThree obj = new MyCalendarThree();
 * int param_1 = obj.Book(startTime,endTime);
 */

```

## C Solution:

```

/*
 * Problem: My Calendar III
 * Difficulty: Hard
 * Tags: array, tree, search
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(h) for recursion stack where h is height
 */

typedef struct {

} MyCalendarThree;

MyCalendarThree* myCalendarThreeCreate() {

}

```

```

int myCalendarThreeBook(MyCalendarThree* obj, int startTime, int endTime) {

}

void myCalendarThreeFree(MyCalendarThree* obj) {

}

/**
 * Your MyCalendarThree struct will be instantiated and called as such:
 * MyCalendarThree* obj = myCalendarThreeCreate();
 * int param_1 = myCalendarThreeBook(obj, startTime, endTime);
 *
 * myCalendarThreeFree(obj);
 */

```

### Go Solution:

```

// Problem: My Calendar III
// Difficulty: Hard
// Tags: array, tree, search
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(h) for recursion stack where h is height

type MyCalendarThree struct {

}

func Constructor() MyCalendarThree {

}

func (this *MyCalendarThree) Book(startTime int, endTime int) int {

}

```

```

/**
 * Your MyCalendarThree object will be instantiated and called as such:
 * obj := Constructor();
 * param_1 := obj.Book(startTime,endTime);
 */

```

### Kotlin Solution:

```

class MyCalendarThree() {

    fun book(startTime: Int, endTime: Int): Int {

    }

}

/**
 * Your MyCalendarThree object will be instantiated and called as such:
 * var obj = MyCalendarThree()
 * var param_1 = obj.book(startTime,endTime)
 */

```

### Swift Solution:

```

class MyCalendarThree {

    init() {

    }

    func book(_ startTime: Int, _ endTime: Int) -> Int {

    }

}

/**
 * Your MyCalendarThree object will be instantiated and called as such:
 * let obj = MyCalendarThree()
 * let ret_1: Int = obj.book(startTime, endTime)
 */

```

```
*/
```

## Rust Solution:

```
// Problem: My Calendar III
// Difficulty: Hard
// Tags: array, tree, search
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(h) for recursion stack where h is height

struct MyCalendarThree {

}

/**
 * `&self` means the method takes an immutable reference.
 * If you need a mutable reference, change it to `&mut self` instead.
 */
impl MyCalendarThree {

    fn new() -> Self {

    }

    fn book(&self, start_time: i32, end_time: i32) -> i32 {

    }
}

/**
 * Your MyCalendarThree object will be instantiated and called as such:
 * let obj = MyCalendarThree::new();
 * let ret_1: i32 = obj.book(startTime, endTime);
 */
```

## Ruby Solution:

```

class MyCalendarThree
  def initialize()

  end

  =begin
  :type start_time: Integer
  :type end_time: Integer
  :rtype: Integer
  =end
  def book(start_time, end_time)

  end

end

# Your MyCalendarThree object will be instantiated and called as such:
# obj = MyCalendarThree.new()
# param_1 = obj.book(start_time, end_time)

```

## PHP Solution:

```

class MyCalendarThree {
    /**
     *
     */
    function __construct() {

    }

    /**
     * @param Integer $startTime
     * @param Integer $endTime
     * @return Integer
     */
    function book($startTime, $endTime) {

    }
}

```

```

* Your MyCalendarThree object will be instantiated and called as such:
* $obj = MyCalendarThree();
* $ret_1 = $obj->book($startTime, $endTime);
*/

```

### Dart Solution:

```

class MyCalendarThree {

  MyCalendarThree() {}

  int book(int startTime, int endTime) {}

}

/**
 * Your MyCalendarThree object will be instantiated and called as such:
 * MyCalendarThree obj = MyCalendarThree();
 * int param1 = obj.book(startTime,endTime);
 */

```

### Scala Solution:

```

class MyCalendarThree() {

  def book(startTime: Int, endTime: Int): Int = {

  }

}

/**
 * Your MyCalendarThree object will be instantiated and called as such:
 * val obj = new MyCalendarThree()
 * val param_1 = obj.book(startTime,endTime)
 */

```

### Elixir Solution:

```

defmodule MyCalendarThree do
  @spec init_() :: any
  def init_() do

  end

  @spec book(start_time :: integer, end_time :: integer) :: integer
  def book(start_time, end_time) do

  end
end

# Your functions will be called as such:
# MyCalendarThree.init_()
# param_1 = MyCalendarThree.book(start_time, end_time)

# MyCalendarThree.init_ will be called before every test case, in which you
can do some necessary initializations.

```

### Erlang Solution:

```

-spec my_calendar_three_init_() -> any().
my_calendar_three_init_() ->
.

-spec my_calendar_three_book(StartTime :: integer(), EndTime :: integer()) ->
integer().
my_calendar_three_book(StartTime, EndTime) ->
.

%% Your functions will be called as such:
%% my_calendar_three_init_(),
%% Param_1 = my_calendar_three_book(StartTime, EndTime),

%% my_calendar_three_init_ will be called before every test case, in which
you can do some necessary initializations.

```

### Racket Solution:

```

(define my-calendar-three%
  (class object%

```

```
(super-new)
```

```
(init-field)
```

```
; book : exact-integer? exact-integer? -> exact-integer?
```

```
(define/public (book start-time end-time)
```

```
)))
```

```
;; Your my-calendar-three% object will be instantiated and called as such:
```

```
;; (define obj (new my-calendar-three%))
```

```
;; (define param_1 (send obj book start-time end-time))
```