

Problem 3413: Maximum Coins From K Consecutive Bags

Problem Information

Difficulty: **Medium**

Acceptance Rate: 0.00%

Paid Only: No

Problem Description

There are an infinite amount of bags on a number line, one bag for each coordinate. Some of these bags contain coins.

You are given a 2D array

`coins`

, where

`coins[i] = [l`

`i`

, `r`

`i`

, `c`

`i`

`]`

denotes that every bag from

l

i

to

r

i

contains

c

i

coins.

The segments that

coins

contain are non-overlapping.

You are also given an integer

k

.

Return the

maximum

amount of coins you can obtain by collecting

k

consecutive bags.

Example 1:

Input:

coins = [[8,10,1],[1,3,2],[5,6,4]], k = 4

Output:

10

Explanation:

Selecting bags at positions

[3, 4, 5, 6]

gives the maximum number of coins:

$2 + 0 + 4 + 4 = 10$

.

Example 2:

Input:

coins = [[1,10,3]], k = 2

Output:

6

Explanation:

Selecting bags at positions

[1, 2]

gives the maximum number of coins:

$$3 + 3 = 6$$

.

Constraints:

$$1 \leq \text{coins.length} \leq 10$$

$$5$$

$$1 \leq k \leq 10$$

$$9$$

$$\text{coins}[i] == [l$$

i

, r

i

, c

i

]

$$1 \leq l$$

i

$$\leq r$$

i

$$\leq 10$$

9

1 <= c

i

<= 1000

The given segments are non-overlapping.

Code Snippets

C++:

```
class Solution {
public:
    long long maximumCoins(vector<vector<int>>& coins, int k) {

    }
};
```

Java:

```
class Solution {
    public long maximumCoins(int[][] coins, int k) {

    }
}
```

Python3:

```
class Solution:
    def maximumCoins(self, coins: List[List[int]], k: int) -> int:
```

Python:

```
class Solution(object):
    def maximumCoins(self, coins, k):
        """
        :type coins: List[List[int]]
```

```

:type k: int
:rtype: int
"""

```

JavaScript:

```

/**
 * @param {number[][]} coins
 * @param {number} k
 * @return {number}
 */
var maximumCoins = function(coins, k) {

};

```

TypeScript:

```

function maximumCoins(coins: number[][], k: number): number {

};

```

C#:

```

public class Solution {
    public long MaximumCoins(int[][] coins, int k) {

    }
}

```

C:

```

long long maximumCoins(int** coins, int coinsSize, int* coinsColSize, int k)
{

}

```

Go:

```

func maximumCoins(coins [][]int, k int) int64 {

}

```

Kotlin:

```
class Solution {  
    fun maximumCoins(coins: Array<IntArray>, k: Int): Long {  
  
    }  
}
```

Swift:

```
class Solution {  
    func maximumCoins(_ coins: [[Int]], _ k: Int) -> Int {  
  
    }  
}
```

Rust:

```
impl Solution {  
    pub fn maximum_coins(coins: Vec<Vec<i32>>, k: i32) -> i64 {  
  
    }  
}
```

Ruby:

```
# @param {Integer[][]} coins  
# @param {Integer} k  
# @return {Integer}  
def maximum_coins(coins, k)  
  
end
```

PHP:

```
class Solution {  
  
    /**  
     * @param Integer[][] $coins  
     * @param Integer $k  
     * @return Integer  
     */  
    function maximumCoins($coins, $k) {
```

```
}  
}
```

Dart:

```
class Solution {  
  int maximumCoins(List<List<int>> coins, int k) {  
  
  }  
}
```

Scala:

```
object Solution {  
  def maximumCoins(coins: Array[Array[Int]], k: Int): Long = {  
  
  }  
}
```

Elixir:

```
defmodule Solution do  
  @spec maximum_coins(coins :: [[integer]], k :: integer) :: integer  
  def maximum_coins(coins, k) do  
  
  end  
end
```

Erlang:

```
-spec maximum_coins(Coins :: [[integer()]], K :: integer()) -> integer().  
maximum_coins(Coins, K) ->  
.
```

Racket:

```
(define/contract (maximum-coins coins k)  
  (-> (listof (listof exact-integer?)) exact-integer? exact-integer?)  
  )
```


Solutions

C++ Solution:

```
/*
 * Problem: Maximum Coins From K Consecutive Bags
 * Difficulty: Medium
 * Tags: array, greedy, sort, search
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

class Solution {
public:
    long long maximumCoins(vector<vector<int>>& coins, int k) {

    }
};
```

Java Solution:

```
/**
 * Problem: Maximum Coins From K Consecutive Bags
 * Difficulty: Medium
 * Tags: array, greedy, sort, search
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

class Solution {
    public long maximumCoins(int[][] coins, int k) {

    }
}
```

Python3 Solution:

```
"""
Problem: Maximum Coins From K Consecutive Bags
```

Difficulty: Medium

Tags: array, greedy, sort, search

Approach: Use two pointers or sliding window technique

Time Complexity: $O(n)$ or $O(n \log n)$

Space Complexity: $O(1)$ to $O(n)$ depending on approach

"""

```
class Solution:
```

```
def maximumCoins(self, coins: List[List[int]], k: int) -> int:
```

```
# TODO: Implement optimized solution
```

```
pass
```

Python Solution:

```
class Solution(object):
```

```
def maximumCoins(self, coins, k):
```

```
"""
```

```
:type coins: List[List[int]]
```

```
:type k: int
```

```
:rtype: int
```

```
"""
```

JavaScript Solution:

```
/**
```

```
 * Problem: Maximum Coins From K Consecutive Bags
```

```
 * Difficulty: Medium
```

```
 * Tags: array, greedy, sort, search
```

```
 *
```

```
 * Approach: Use two pointers or sliding window technique
```

```
 * Time Complexity:  $O(n)$  or  $O(n \log n)$ 
```

```
 * Space Complexity:  $O(1)$  to  $O(n)$  depending on approach
```

```
 */
```

```
/**
```

```
 * @param {number[][]} coins
```

```
 * @param {number} k
```

```
 * @return {number}
```

```
 */
```

```
var maximumCoins = function(coins, k) {
```

```
};
```

TypeScript Solution:

```
/**
 * Problem: Maximum Coins From K Consecutive Bags
 * Difficulty: Medium
 * Tags: array, greedy, sort, search
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

function maximumCoins(coins: number[][], k: number): number {

};
```

C# Solution:

```
/*
 * Problem: Maximum Coins From K Consecutive Bags
 * Difficulty: Medium
 * Tags: array, greedy, sort, search
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

public class Solution {
    public long MaximumCoins(int[][] coins, int k) {

    }
}
```

C Solution:

```
/*
 * Problem: Maximum Coins From K Consecutive Bags
```

```

* Difficulty: Medium
* Tags: array, greedy, sort, search
*
* Approach: Use two pointers or sliding window technique
* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(1) to O(n) depending on approach
*/

long long maximumCoins(int** coins, int coinsSize, int* coinsColSize, int k)
{

}

```

Go Solution:

```

// Problem: Maximum Coins From K Consecutive Bags
// Difficulty: Medium
// Tags: array, greedy, sort, search
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(1) to O(n) depending on approach

func maximumCoins(coins [][]int, k int) int64 {

}

```

Kotlin Solution:

```

class Solution {
    fun maximumCoins(coins: Array<IntArray>, k: Int): Long {

    }
}

```

Swift Solution:

```

class Solution {
    func maximumCoins(_ coins: [[Int]], _ k: Int) -> Int {

    }
}

```

```
}
```

Rust Solution:

```
// Problem: Maximum Coins From K Consecutive Bags
// Difficulty: Medium
// Tags: array, greedy, sort, search
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(1) to O(n) depending on approach

impl Solution {
    pub fn maximum_coins(coins: Vec<Vec<i32>>, k: i32) -> i64 {

    }
}
```

Ruby Solution:

```
# @param {Integer[][]} coins
# @param {Integer} k
# @return {Integer}
def maximum_coins(coins, k)

end
```

PHP Solution:

```
class Solution {

    /**
     * @param Integer[][] $coins
     * @param Integer $k
     * @return Integer
     */
    function maximumCoins($coins, $k) {

    }

}
```

Dart Solution:

```
class Solution {  
  int maximumCoins(List<List<int>> coins, int k) {  
  
  }  
}
```

Scala Solution:

```
object Solution {  
  def maximumCoins(coins: Array[Array[Int]], k: Int): Long = {  
  
  }  
}
```

Elixir Solution:

```
defmodule Solution do  
  @spec maximum_coins(coins :: [[integer]], k :: integer) :: integer  
  def maximum_coins(coins, k) do  
  
  end  
end
```

Erlang Solution:

```
-spec maximum_coins(Coins :: [[integer()]], K :: integer()) -> integer().  
maximum_coins(Coins, K) ->  
.
```

Racket Solution:

```
(define/contract (maximum-coins coins k)  
  (-> (listof (listof exact-integer?)) exact-integer? exact-integer?)  
  )
```