

Problem 2630: Memoize II

Problem Information

Difficulty: Hard

Acceptance Rate: 0.00%

Paid Only: No

Problem Description

Given a function

fn

, return a

memoized

version of that function.

A

memoized

function is a function that will never be called twice with the same inputs. Instead it will return a cached value.

fn

can be any function and there are no constraints on what type of values it accepts. Inputs are considered identical if they are

===

to each other.

Example 1:

Input:

```
getInputs = () => [[2,2],[2,2],[1,2]] fn = function (a, b) { return a + b; }
```

Output:

```
[{"val":4,"calls":1},{ "val":4,"calls":1},{ "val":3,"calls":2}]
```

Explanation:

```
const inputs = getInputs(); const memoized = memoize(fn); for (const arr of inputs) {  
  memoized(...arr); }
```

For the inputs of (2, 2): $2 + 2 = 4$, and it required a call to `fn()`. For the inputs of (2, 2): $2 + 2 = 4$, but those inputs were seen before so no call to `fn()` was required. For the inputs of (1, 2): $1 + 2 = 3$, and it required another call to `fn()` for a total of 2.

Example 2:

Input:

```
getInputs = () => [[{},{ }],[{},{ }],[{},{ }]] fn = function (a, b) { return ({...a, ...b}); }
```

Output:

```
[{"val":{ },"calls":1},{ "val":{ },"calls":2},{ "val":{ },"calls":3}]
```

Explanation:

Merging two empty objects will always result in an empty object. It may seem like there should only be 1 call to `fn()` because of cache-hits, however none of those objects are `===` to each other.

Example 3:

Input:

```
getInputs = () => { const o = {}; return [[o,o],[o,o],[o,o]]; } fn = function (a, b) { return ({...a, ...b}); }  
}
```

Output:

```
[{"val":{},"calls":1},{"val":{},"calls":1},{"val":{},"calls":1}]
```

Explanation:

Merging two empty objects will always result in an empty object. The 2nd and 3rd third function calls result in a cache-hit. This is because every object passed in is identical.

Constraints:

1 <= inputs.length <= 10

5

0 <= inputs.flat().length <= 10

5

inputs[i][j] != NaN

Code Snippets

JavaScript:

```
/**  
 * @param {Function} fn  
 * @return {Function}  
 */  
function memoize(fn) {  
  
  return function() {  
  
  }  
}
```

```

/**
 * let callCount = 0;
 * const memoizedFn = memoize(function (a, b) {
 *   callCount += 1;
 *   return a + b;
 * })
 * memoizedFn(2, 3) // 5
 * memoizedFn(2, 3) // 5
 * console.log(callCount) // 1
 */

```

TypeScript:

```

type Fn = (...params: any) => any

function memoize(fn: Fn): Fn {

  return function() {

  }

}

/**
 * let callCount = 0;
 * const memoizedFn = memoize(function (a, b) {
 *   callCount += 1;
 *   return a + b;
 * })
 * memoizedFn(2, 3) // 5
 * memoizedFn(2, 3) // 5
 * console.log(callCount) // 1
 */

```

Solutions

JavaScript Solution:

```

/**
 * Problem: Memoize II
 * Difficulty: Hard
 * Tags: general
 *
 * Approach: Optimized algorithm based on problem constraints
 * Time Complexity: O(n) to O(n^2) depending on approach
 * Space Complexity: O(1) to O(n) depending on approach
 */

/**
 * @param {Function} fn
 * @return {Function}
 */
function memoize(fn) {

return function() {

}

}

/**
 * let callCount = 0;
 * const memoizedFn = memoize(function (a, b) {
 *   callCount += 1;
 *   return a + b;
 * })
 * memoizedFn(2, 3) // 5
 * memoizedFn(2, 3) // 5
 * console.log(callCount) // 1
 */

```

TypeScript Solution:

```

/**
 * Problem: Memoize II
 * Difficulty: Hard
 * Tags: general
 *
 * Approach: Optimized algorithm based on problem constraints
 * Time Complexity: O(n) to O(n^2) depending on approach

```

```
* Space Complexity: O(1) to O(n) depending on approach
*/

type Fn = (...params: any) => any

function memoize(fn: Fn): Fn {

  return function() {

  }

}

/**
 * let callCount = 0;
 * const memoizedFn = memoize(function (a, b) {
 *   callCount += 1;
 *   return a + b;
 * })
 * memoizedFn(2, 3) // 5
 * memoizedFn(2, 3) // 5
 * console.log(callCount) // 1
 */
```