

# Problem 2242: Maximum Score of a Node Sequence

## Problem Information

Difficulty: **Hard**

Acceptance Rate: 0.00%

Paid Only: No

## Problem Description

There is an

undirected

graph with

$n$

nodes, numbered from

0

to

$n - 1$

.

You are given a

0-indexed

integer array

scores

of length

$n$

where

$scores[i]$

denotes the score of node

$i$

. You are also given a 2D integer array

$edges$

where

$edges[i] = [a$

$i$

,  $b$

$i$

$]$

denotes that there exists an

undirected

edge connecting nodes

$a$

$i$

and

b

i

.

A node sequence is

valid

if it meets the following conditions:

There is an edge connecting every pair of

adjacent

nodes in the sequence.

No node appears more than once in the sequence.

The score of a node sequence is defined as the

sum

of the scores of the nodes in the sequence.

Return

the

maximum score

of a valid node sequence with a length of

4


.

If no such sequence exists, return

-1

.

Example 1:



Input:

scores = [5,2,9,8,4], edges = [[0,1],[1,2],[2,3],[0,2],[1,3],[2,4]]


Output:

24

Explanation:

The figure above shows the graph and the chosen node sequence [0,1,2,3]. The score of the node sequence is  $5 + 2 + 9 + 8 = 24$ . It can be shown that no other node sequence has a score of more than 24. Note that the sequences [3,1,2,0] and [1,0,2,3] are also valid and have a score of 24. The sequence [0,3,2,4] is not valid since no edge connects nodes 0 and 3.

Example 2:



Input:

scores = [9,20,6,4,11,12], edges = [[0,3],[5,3],[2,4],[1,3]]

Output:

-1

Explanation:

The figure above shows the graph. There are no valid node sequences of length 4, so we return -1.

Constraints:

$n == \text{scores.length}$

$4 \leq n \leq 5 * 10$

4

$1 \leq \text{scores}[i] \leq 10$

8

$0 \leq \text{edges.length} \leq 5 * 10$

4

edges[i].length == 2

0 <= a

i

, b

i

<= n - 1

a

i

!= b

i

There are no duplicate edges.

## Code Snippets

### C++:

```
class Solution {  
public:  
    int maximumScore(vector<int>& scores, vector<vector<int>>& edges) {  
  
    }  
};
```

### Java:

```
class Solution {  
    public int maximumScore(int[] scores, int[][] edges) {
```

```
}  
}
```

### Python3:

```
class Solution:  
    def maximumScore(self, scores: List[int], edges: List[List[int]]) -> int:
```

### Python:

```
class Solution(object):  
    def maximumScore(self, scores, edges):  
        """  
        :type scores: List[int]  
        :type edges: List[List[int]]  
        :rtype: int  
        """
```

### JavaScript:

```
/**  
 * @param {number[]} scores  
 * @param {number[][]} edges  
 * @return {number}  
 */  
var maximumScore = function(scores, edges) {  
  
};
```

### TypeScript:

```
function maximumScore(scores: number[], edges: number[][]): number {  
  
};
```

### C#:

```
public class Solution {  
    public int MaximumScore(int[] scores, int[][] edges) {  
  
    }  
}
```

```
}
```

### C:

```
int maximumScore(int* scores, int scoresSize, int** edges, int edgesSize,
int* edgesColSize) {

}
```

### Go:

```
func maximumScore(scores []int, edges [][]int) int {

}
```

### Kotlin:

```
class Solution {
    fun maximumScore(scores: IntArray, edges: Array<IntArray>): Int {

    }
}
```

### Swift:

```
class Solution {
    func maximumScore(_ scores: [Int], _ edges: [[Int]]) -> Int {

    }
}
```

### Rust:

```
impl Solution {
    pub fn maximum_score(scores: Vec<i32>, edges: Vec<Vec<i32>>) -> i32 {

    }
}
```

### Ruby:

```

# @param {Integer[]} scores
# @param {Integer[][]} edges
# @return {Integer}
def maximum_score(scores, edges)

end

```

## PHP:

```

class Solution {

    /**
     * @param Integer[] $scores
     * @param Integer[][] $edges
     * @return Integer
     */
    function maximumScore($scores, $edges) {

    }

}

```

## Dart:

```

class Solution {
  int maximumScore(List<int> scores, List<List<int>> edges) {

  }

}

```

## Scala:

```

object Solution {
  def maximumScore(scores: Array[Int], edges: Array[Array[Int]]): Int = {

  }

}

```

## Elixir:

```

defmodule Solution do
  @spec maximum_score(scores :: [integer], edges :: [[integer]]) :: integer
  def maximum_score(scores, edges) do

```

```
end  
end
```

### Erlang:

```
-spec maximum_score(Scores :: [integer()], Edges :: [[integer()]]) ->  
integer().  
maximum_score(Scores, Edges) ->  
.
```

### Racket:

```
(define/contract (maximum-score scores edges)  
  (-> (listof exact-integer?) (listof (listof exact-integer?)) exact-integer?)  
  )
```

## Solutions

### C++ Solution:

```
/*  
 * Problem: Maximum Score of a Node Sequence  
 * Difficulty: Hard  
 * Tags: array, graph, sort  
 *  
 * Approach: Use two pointers or sliding window technique  
 * Time Complexity: O(n) or O(n log n)  
 * Space Complexity: O(1) to O(n) depending on approach  
 */  
  
class Solution {  
public:  
    int maximumScore(vector<int>& scores, vector<vector<int>>& edges) {  
  
    }  
};
```

### Java Solution:

```

/**
 * Problem: Maximum Score of a Node Sequence
 * Difficulty: Hard
 * Tags: array, graph, sort
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

class Solution {
public int maximumScore(int[] scores, int[][] edges) {

}
}

```

### Python3 Solution:

```

"""
Problem: Maximum Score of a Node Sequence
Difficulty: Hard
Tags: array, graph, sort

Approach: Use two pointers or sliding window technique
Time Complexity: O(n) or O(n log n)
Space Complexity: O(1) to O(n) depending on approach
"""

class Solution:
def maximumScore(self, scores: List[int], edges: List[List[int]]) -> int:
# TODO: Implement optimized solution
pass

```

### Python Solution:

```

class Solution(object):
def maximumScore(self, scores, edges):
"""
:type scores: List[int]
:type edges: List[List[int]]
:rtype: int
"""

```

## JavaScript Solution:

```
/**
 * Problem: Maximum Score of a Node Sequence
 * Difficulty: Hard
 * Tags: array, graph, sort
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

/**
 * @param {number[]} scores
 * @param {number[][]} edges
 * @return {number}
 */
var maximumScore = function(scores, edges) {

};
```

## TypeScript Solution:

```
/**
 * Problem: Maximum Score of a Node Sequence
 * Difficulty: Hard
 * Tags: array, graph, sort
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

function maximumScore(scores: number[], edges: number[][]): number {

};
```

## C# Solution:

```
/*
 * Problem: Maximum Score of a Node Sequence
 * Difficulty: Hard
```

```

* Tags: array, graph, sort
*
* Approach: Use two pointers or sliding window technique
* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(1) to O(n) depending on approach
*/

public class Solution {
public int MaximumScore(int[] scores, int[][] edges) {

}
}

```

### C Solution:

```

/*
* Problem: Maximum Score of a Node Sequence
* Difficulty: Hard
* Tags: array, graph, sort
*
* Approach: Use two pointers or sliding window technique
* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(1) to O(n) depending on approach
*/

int maximumScore(int* scores, int scoresSize, int** edges, int edgesSize,
int* edgesColSize) {

}

```

### Go Solution:

```

// Problem: Maximum Score of a Node Sequence
// Difficulty: Hard
// Tags: array, graph, sort
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(1) to O(n) depending on approach

func maximumScore(scores []int, edges [][]int) int {

```

```
}
```

### Kotlin Solution:

```
class Solution {  
    fun maximumScore(scores: IntArray, edges: Array<IntArray>): Int {  
  
    }  
}
```

### Swift Solution:

```
class Solution {  
    func maximumScore(_ scores: [Int], _ edges: [[Int]]) -> Int {  
  
    }  
}
```

### Rust Solution:

```
// Problem: Maximum Score of a Node Sequence  
// Difficulty: Hard  
// Tags: array, graph, sort  
//  
// Approach: Use two pointers or sliding window technique  
// Time Complexity: O(n) or O(n log n)  
// Space Complexity: O(1) to O(n) depending on approach  
  
impl Solution {  
    pub fn maximum_score(scores: Vec<i32>, edges: Vec<Vec<i32>>) -> i32 {  
  
    }  
}
```

### Ruby Solution:

```
# @param {Integer[]} scores  
# @param {Integer[][]} edges  
# @return {Integer}  
def maximum_score(scores, edges)
```

```
end
```

### PHP Solution:

```
class Solution {  
  
    /**  
     * @param Integer[] $scores  
     * @param Integer[][] $edges  
     * @return Integer  
     */  
    function maximumScore($scores, $edges) {  
  
    }  
}
```

### Dart Solution:

```
class Solution {  
    int maximumScore(List<int> scores, List<List<int>> edges) {  
  
    }  
}
```

### Scala Solution:

```
object Solution {  
    def maximumScore(scores: Array[Int], edges: Array[Array[Int]]): Int = {  
  
    }  
}
```

### Elixir Solution:

```
defmodule Solution do  
    @spec maximum_score(scores :: [integer], edges :: [[integer]]) :: integer  
    def maximum_score(scores, edges) do  
  
    end  
end
```

### Erlang Solution:

```
-spec maximum_score(Scores :: [integer()], Edges :: [[integer()]]) ->
integer().
maximum_score(Scores, Edges) ->
.
```

### Racket Solution:

```
(define/contract (maximum-score scores edges)
  (-> (listof exact-integer?) (listof (listof exact-integer?)) exact-integer?)
)
```