

Problem 2671: Frequency Tracker

Problem Information

Difficulty: Medium

Acceptance Rate: 30.45%

Paid Only: No

Tags: Hash Table, Design

Problem Description

Design a data structure that keeps track of the values in it and answers some queries regarding their frequencies.

Implement the `FrequencyTracker` class.

* `FrequencyTracker()`: Initializes the `FrequencyTracker` object with an empty array initially.
* `void add(int number)`: Adds `number` to the data structure. * `void deleteOne(int number)`: Deletes **one** occurrence of `number` from the data structure. The data structure **may not** contain `number`, and in this case nothing is deleted. * `bool hasFrequency(int frequency)`: Returns `true` if there is a number in the data structure that occurs `frequency` number of times, otherwise, it returns `false`.

Example 1:

Input `["FrequencyTracker", "add", "add", "hasFrequency"]` `[[], [3], [3], [2]]` **Output** `[null, null, null, true]` **Explanation** `FrequencyTracker frequencyTracker = new FrequencyTracker(); frequencyTracker.add(3); // The data structure now contains [3] frequencyTracker.add(3); // The data structure now contains [3, 3] frequencyTracker.hasFrequency(2); // Returns true, because 3 occurs twice`

Example 2:

Input `["FrequencyTracker", "add", "deleteOne", "hasFrequency"]` `[[], [1], [1], [1]]` **Output** `[null, null, null, false]` **Explanation** `FrequencyTracker frequencyTracker = new FrequencyTracker(); frequencyTracker.add(1); // The data structure now contains [1] frequencyTracker.deleteOne(1); // The data structure becomes empty []`

frequencyTracker.hasFrequency(1); // Returns false, because the data structure is empty

****Example 3:****

****Input**** ["FrequencyTracker", "hasFrequency", "add", "hasFrequency"] [[], [2], [3], [1]]

****Output**** [null, false, null, true] ****Explanation**** FrequencyTracker frequencyTracker = new FrequencyTracker(); frequencyTracker.hasFrequency(2); // Returns false, because the data structure is empty frequencyTracker.add(3); // The data structure now contains [3] frequencyTracker.hasFrequency(1); // Returns true, because 3 occurs once

****Constraints:****

* `1 <= number <= 105` * `1 <= frequency <= 105` * At most, `2 * 105` calls will be made to `add`, `deleteOne`, and `hasFrequency` in ****total****.

Code Snippets

C++:

```
class FrequencyTracker {
public:
    FrequencyTracker() {

    }

    void add(int number) {

    }

    void deleteOne(int number) {

    }

    bool hasFrequency(int frequency) {

    }
};

/**
 * Your FrequencyTracker object will be instantiated and called as such:
```

```

* FrequencyTracker* obj = new FrequencyTracker();
* obj->add(number);
* obj->deleteOne(number);
* bool param_3 = obj->hasFrequency(frequency);
*/

```

Java:

```

class FrequencyTracker {

    public FrequencyTracker() {

    }

    public void add(int number) {

    }

    public void deleteOne(int number) {

    }

    public boolean hasFrequency(int frequency) {

    }

}

/**
 * Your FrequencyTracker object will be instantiated and called as such:
 * FrequencyTracker obj = new FrequencyTracker();
 * obj.add(number);
 * obj.deleteOne(number);
 * boolean param_3 = obj.hasFrequency(frequency);
 */

```

Python3:

```

class FrequencyTracker:

    def __init__(self):

```

```
def add(self, number: int) -> None:
```

```
def deleteOne(self, number: int) -> None:
```

```
def hasFrequency(self, frequency: int) -> bool:
```

```
# Your FrequencyTracker object will be instantiated and called as such:
```

```
# obj = FrequencyTracker()
```

```
# obj.add(number)
```

```
# obj.deleteOne(number)
```

```
# param_3 = obj.hasFrequency(frequency)
```