

# Problem 1914: Cyclically Rotating a Grid

## Problem Information

Difficulty: **Medium**

Acceptance Rate: 0.00%

Paid Only: No

## Problem Description

You are given an

$m \times n$

integer matrix

grid

, where

$m$

and

$n$

are both

even

integers, and an integer

$k$

.

The matrix is composed of several layers, which is shown in the below image, where each color is its own layer:

1	1	1	1
1	2	2	1
1	2	2	1
1	2	2	1
1	2	2	1
1	1	1	1

A cyclic rotation of the matrix is done by cyclically rotating

each layer

in the matrix. To cyclically rotate a layer once, each element in the layer will take the place of the adjacent element in the

counter-clockwise

direction. An example rotation is shown below:

1	← 2	← 3	← 4
16	↓ 1	← 2	5
15	↓ 8	3	6
14	↓ 7	4	7
13	↓ 6	→ 5	8
12	→ 11	→ 10	9

Before rotation

2	3	4	5
1	2	3	6
16	1	4	7
15	8	5	8
14	7	6	9
13	12	11	10

After rotation with k = 1

Return

the matrix after applying

k

cyclic rotations to it

.

Example 1:

40	10
30	20

**Before Any Rotations**

10	20
40	30

**After One Rotation**

Input:

grid = [[40,10],[30,20]], k = 1

Output:

[[10,20],[40,30]]

Explanation:

The figures above represent the grid at every state.

Example 2:

1	2	3	4
5	6	7	8
9	10	11	12
13	14	15	16

**Before Any Rotations**

2	3	4	8
1	7	11	12
5	6	10	16
9	13	14	15

**After One Rotation**

3	4	8	12
2	11	10	16
1	7	6	15
5	9	13	14

## After Two Rotations

Input:

```
grid = [[1,2,3,4],[5,6,7,8],[9,10,11,12],[13,14,15,16]], k = 2
```

Output:

```
[[3,4,8,12],[2,11,10,16],[1,7,6,15],[5,9,13,14]]
```

Explanation:

The figures above represent the grid at every state.

Constraints:

```
m == grid.length
```

```
n == grid[i].length
```

```
2 <= m, n <= 50
```

Both

m

and

n

are

even

integers.

$1 \leq \text{grid}[i][j] \leq$

5000

$1 \leq k \leq 10$

9

## Code Snippets

### C++:

```
class Solution {
public:
    vector<vector<int>> rotateGrid(vector<vector<int>>& grid, int k) {

    }
};
```

### Java:

```
class Solution {
    public int[][] rotateGrid(int[][] grid, int k) {

    }
}
```

### Python3:

```
class Solution:
    def rotateGrid(self, grid: List[List[int]], k: int) -> List[List[int]]:
```

### Python:

```
class Solution(object):
    def rotateGrid(self, grid, k):
        """
        :type grid: List[List[int]]
        :type k: int
        :rtype: List[List[int]]
        """
```

### JavaScript:

```
/**
 * @param {number[][]} grid
 * @param {number} k
 * @return {number[][]}
 */
var rotateGrid = function(grid, k) {

};
```

### TypeScript:

```
function rotateGrid(grid: number[][], k: number): number[][] {

};
```

### C#:

```
public class Solution {
    public int[][] RotateGrid(int[][] grid, int k) {

    }
}
```

### C:

```

/**
 * Return an array of arrays of size *returnSize.
 * The sizes of the arrays are returned as *returnColumnSizes array.
 * Note: Both returned array and *columnSizes array must be malloced, assume
 caller calls free().
 */
int** rotateGrid(int** grid, int gridSize, int* gridColSize, int k, int*
returnSize, int** returnColumnSizes){

}

```

### Go:

```

func rotateGrid(grid [][]int, k int) [][]int {

}

```

### Kotlin:

```

class Solution {
fun rotateGrid(grid: Array<IntArray>, k: Int): Array<IntArray> {

}

}

```

### Swift:

```

class Solution {
func rotateGrid(_ grid: [[Int]], _ k: Int) -> [[Int]] {

}

}

```

### Rust:

```

impl Solution {
pub fn rotate_grid(grid: Vec<Vec<i32>>, k: i32) -> Vec<Vec<i32>> {

}

}

```

### Ruby:



```

# @param {Integer[][]} grid
# @param {Integer} k
# @return {Integer[][]}
def rotate_grid(grid, k)

end

```

## PHP:

```

class Solution {

    /**
     * @param Integer[][] $grid
     * @param Integer $k
     * @return Integer[][]
     */
    function rotateGrid($grid, $k) {

    }

}

```

## Scala:

```

object Solution {
    def rotateGrid(grid: Array[Array[Int]], k: Int): Array[Array[Int]] = {

    }

}

```

## Racket:

```

(define/contract (rotate-grid grid k)
  (-> (listof (listof exact-integer?)) exact-integer? (listof (listof
exact-integer?)))

)

```

## Solutions

### C++ Solution:

```

/*
 * Problem: Cyclically Rotating a Grid
 * Difficulty: Medium
 * Tags: array
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

class Solution {
public:
    vector<vector<int>> rotateGrid(vector<vector<int>>& grid, int k) {

    }
};

```

### Java Solution:

```

/**
 * Problem: Cyclically Rotating a Grid
 * Difficulty: Medium
 * Tags: array
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

class Solution {
public int[][] rotateGrid(int[][] grid, int k) {

    }
}

```

### Python3 Solution:

```

"""
Problem: Cyclically Rotating a Grid
Difficulty: Medium
Tags: array

```

```

Approach: Use two pointers or sliding window technique
Time Complexity:  $O(n)$  or  $O(n \log n)$ 
Space Complexity:  $O(1)$  to  $O(n)$  depending on approach
"""

class Solution:
    def rotateGrid(self, grid: List[List[int]], k: int) -> List[List[int]]:
        # TODO: Implement optimized solution
        pass

```

### Python Solution:

```

class Solution(object):
    def rotateGrid(self, grid, k):
        """
        :type grid: List[List[int]]
        :type k: int
        :rtype: List[List[int]]
        """

```

### JavaScript Solution:

```

/**
 * Problem: Cyclically Rotating a Grid
 * Difficulty: Medium
 * Tags: array
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity:  $O(n)$  or  $O(n \log n)$ 
 * Space Complexity:  $O(1)$  to  $O(n)$  depending on approach
 */

/**
 * @param {number[][]} grid
 * @param {number} k
 * @return {number[][]}
 */
var rotateGrid = function(grid, k) {

};

```

### TypeScript Solution:

```
/**
 * Problem: Cyclically Rotating a Grid
 * Difficulty: Medium
 * Tags: array
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

function rotateGrid(grid: number[][], k: number): number[][] {

};
```

### C# Solution:

```
/*
 * Problem: Cyclically Rotating a Grid
 * Difficulty: Medium
 * Tags: array
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

public class Solution {
    public int[][] RotateGrid(int[][] grid, int k) {

    }
}
```

### C Solution:

```
/*
 * Problem: Cyclically Rotating a Grid
 * Difficulty: Medium
 * Tags: array
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
```

```

* Space Complexity: O(1) to O(n) depending on approach
*/

/**
* Return an array of arrays of size *returnSize.
* The sizes of the arrays are returned as *returnColumnSizes array.
* Note: Both returned array and *columnSizes array must be malloced, assume
caller calls free().
*/
int** rotateGrid(int** grid, int gridSize, int* gridColSize, int k, int*
returnSize, int** returnColumnSizes){

}

```

### Go Solution:

```

// Problem: Cyclically Rotating a Grid
// Difficulty: Medium
// Tags: array
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(1) to O(n) depending on approach

func rotateGrid(grid [][]int, k int) [][]int {

}

```

### Kotlin Solution:

```

class Solution {
fun rotateGrid(grid: Array<IntArray>, k: Int): Array<IntArray> {

}
}

```

### Swift Solution:

```

class Solution {
func rotateGrid(_ grid: [[Int]], _ k: Int) -> [[Int]] {

```

```
}  
}
```

### Rust Solution:

```
// Problem: Cyclically Rotating a Grid  
// Difficulty: Medium  
// Tags: array  
//  
// Approach: Use two pointers or sliding window technique  
// Time Complexity: O(n) or O(n log n)  
// Space Complexity: O(1) to O(n) depending on approach  
  
impl Solution {  
    pub fn rotate_grid(grid: Vec<Vec<i32>>, k: i32) -> Vec<Vec<i32>> {  
  
    }  
}
```

### Ruby Solution:

```
# @param {Integer[][]} grid  
# @param {Integer} k  
# @return {Integer[][]}  
def rotate_grid(grid, k)  
  
end
```

### PHP Solution:

```
class Solution {  
  
    /**  
     * @param Integer[][] $grid  
     * @param Integer $k  
     * @return Integer[][]  
     */  
    function rotateGrid($grid, $k) {  
  
    }  
}
```

### Scala Solution:

```
object Solution {  
  def rotateGrid(grid: Array[Array[Int]], k: Int): Array[Array[Int]] = {  
  
  }  
}
```

### Racket Solution:

```
(define/contract (rotate-grid grid k)  
  (-> (listof (listof exact-integer?)) exact-integer? (listof (listof  
    exact-integer?)))  
  
)
```