

Problem 1375: Number of Times Binary String Is Prefix-Aligned

Problem Information

Difficulty: Medium

Acceptance Rate: 65.91%

Paid Only: No

Tags: Array

Problem Description

You have a **1-indexed** binary string of length n where all the bits are `0` initially. We will flip all the bits of this binary string (i.e., change them from `0` to `1`) one by one. You are given a **1-indexed** integer array `flips` where `flips[i]` indicates that the bit at index `flips[i]` will be flipped in the i th step.

A binary string is **prefix-aligned** if, after the i th step, all the bits in the **inclusive** range `[1, i]` are ones and all the other bits are zeros.

Return the number of times the binary string is prefix-aligned during the flipping process.

Example 1:

Input: `flips = [3,2,4,1,5]` **Output:** `2` **Explanation:** The binary string is initially "00000". After applying step 1: The string becomes "00100", which is not prefix-aligned. After applying step 2: The string becomes "01100", which is not prefix-aligned. After applying step 3: The string becomes "01110", which is not prefix-aligned. After applying step 4: The string becomes "11110", which is prefix-aligned. After applying step 5: The string becomes "11111", which is prefix-aligned. We can see that the string was prefix-aligned 2 times, so we return 2.

Example 2:

Input: `flips = [4,1,2,3]` **Output:** `1` **Explanation:** The binary string is initially "0000". After applying step 1: The string becomes "0001", which is not prefix-aligned. After applying step 2: The string becomes "1001", which is not prefix-aligned. After applying step 3: The string becomes "1101", which is not prefix-aligned. After applying step 4: The string becomes

"1111", which is prefix-aligned. We can see that the string was prefix-aligned 1 time, so we return 1.

****Constraints:****

* `n == flips.length` * `1 <= n <= 5 * 10^4` * `flips` is a permutation of the integers in the range `[1, n]`.

Code Snippets

C++:

```
class Solution {
public:
    int numTimesAllBlue(vector<int>& flips) {

    }
};
```

Java:

```
class Solution {
    public int numTimesAllBlue(int[] flips) {

    }
}
```

Python3:

```
class Solution:
    def numTimesAllBlue(self, flips: List[int]) -> int:
```