

# Problem 2244: Minimum Rounds to Complete All Tasks

## Problem Information

Difficulty: Medium

Acceptance Rate: 0.00%

Paid Only: No

## Problem Description

You are given a

0-indexed

integer array

tasks

, where

tasks[i]

represents the difficulty level of a task. In each round, you can complete either 2 or 3 tasks of the

same difficulty level

.

Return

the

minimum

rounds required to complete all the tasks, or

-1

if it is not possible to complete all the tasks.

Example 1:

Input:

tasks = [2,2,3,3,2,4,4,4,4,4]

Output:

4

Explanation:

To complete all the tasks, a possible plan is: - In the first round, you complete 3 tasks of difficulty level 2. - In the second round, you complete 2 tasks of difficulty level 3. - In the third round, you complete 3 tasks of difficulty level 4. - In the fourth round, you complete 2 tasks of difficulty level 4. It can be shown that all the tasks cannot be completed in fewer than 4 rounds, so the answer is 4.

Example 2:

Input:

tasks = [2,3,3]

Output:

-1

Explanation:

There is only 1 task of difficulty level 2, but in each round, you can only complete either 2 or 3 tasks of the same difficulty level. Hence, you cannot complete all the tasks, and the answer is -1.

Constraints:

$1 \leq \text{tasks.length} \leq 10$

5

$1 \leq \text{tasks}[i] \leq 10$

9

Note:

This question is the same as

2870: Minimum Number of Operations to Make Array Empty.

## Code Snippets

**C++:**

```
class Solution {
public:
    int minimumRounds(vector<int>& tasks) {

    }
};
```

**Java:**

```
class Solution {
    public int minimumRounds(int[] tasks) {

    }
}
```

**Python3:**

```
class Solution:
    def minimumRounds(self, tasks: List[int]) -> int:
```

## Python:

```
class Solution(object):  
    def minimumRounds(self, tasks):  
        """  
        :type tasks: List[int]  
        :rtype: int  
        """
```

## JavaScript:

```
/**  
 * @param {number[]} tasks  
 * @return {number}  
 */  
var minimumRounds = function(tasks) {  
  
};
```

## TypeScript:

```
function minimumRounds(tasks: number[]): number {  
  
};
```

## C#:

```
public class Solution {  
    public int MinimumRounds(int[] tasks) {  
  
    }  
}
```

## C:

```
int minimumRounds(int* tasks, int tasksSize) {  
  
}
```

## Go:

```
func minimumRounds(tasks []int) int {
```

```
}
```

### Kotlin:

```
class Solution {  
    fun minimumRounds(tasks: IntArray): Int {  
  
    }  
}
```

### Swift:

```
class Solution {  
    func minimumRounds(_ tasks: [Int]) -> Int {  
  
    }  
}
```

### Rust:

```
impl Solution {  
    pub fn minimum_rounds(tasks: Vec<i32>) -> i32 {  
  
    }  
}
```

### Ruby:

```
# @param {Integer[]} tasks  
# @return {Integer}  
def minimum_rounds(tasks)  
  
end
```

### PHP:

```
class Solution {  
  
    /**  
     * @param Integer[] $tasks  
     * @return Integer  
     */  
}
```

```
function minimumRounds($tasks) {

}

}
```

### Dart:

```
class Solution {
  int minimumRounds(List<int> tasks) {

  }
}
```

### Scala:

```
object Solution {
  def minimumRounds(tasks: Array[Int]): Int = {

  }
}
```

### Elixir:

```
defmodule Solution do
  @spec minimum_rounds(tasks :: [integer]) :: integer
  def minimum_rounds(tasks) do

  end
end
```

### Erlang:

```
-spec minimum_rounds(Tasks :: [integer()]) -> integer().
minimum_rounds(Tasks) ->
.
```

### Racket:

```
(define/contract (minimum-rounds tasks)
  (-> (listof exact-integer?) exact-integer?)
)
```

## Solutions

### C++ Solution:

```
/*
 * Problem: Minimum Rounds to Complete All Tasks
 * Difficulty: Medium
 * Tags: array, greedy, hash
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

class Solution {
public:
    int minimumRounds(vector<int>& tasks) {

    }
};
```

### Java Solution:

```
/**
 * Problem: Minimum Rounds to Complete All Tasks
 * Difficulty: Medium
 * Tags: array, greedy, hash
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

class Solution {
    public int minimumRounds(int[] tasks) {

    }
}
```

### Python3 Solution:

```

"""
Problem: Minimum Rounds to Complete All Tasks
Difficulty: Medium
Tags: array, greedy, hash

Approach: Use two pointers or sliding window technique
Time Complexity: O(n) or O(n log n)
Space Complexity: O(n) for hash map
"""

class Solution:
    def minimumRounds(self, tasks: List[int]) -> int:
        # TODO: Implement optimized solution
        pass

```

### Python Solution:

```

class Solution(object):
    def minimumRounds(self, tasks):
        """
        :type tasks: List[int]
        :rtype: int
        """

```

### JavaScript Solution:

```

/**
 * Problem: Minimum Rounds to Complete All Tasks
 * Difficulty: Medium
 * Tags: array, greedy, hash
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

/**
 * @param {number[]} tasks
 * @return {number}
 */
var minimumRounds = function(tasks) {

```



```
};
```

### TypeScript Solution:

```
/**
 * Problem: Minimum Rounds to Complete All Tasks
 * Difficulty: Medium
 * Tags: array, greedy, hash
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

function minimumRounds(tasks: number[]): number {

};
```

### C# Solution:

```
/*
 * Problem: Minimum Rounds to Complete All Tasks
 * Difficulty: Medium
 * Tags: array, greedy, hash
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

public class Solution {
    public int MinimumRounds(int[] tasks) {

    }
}
```

### C Solution:

```
/*
 * Problem: Minimum Rounds to Complete All Tasks
 * Difficulty: Medium
```

```

* Tags: array, greedy, hash
*
* Approach: Use two pointers or sliding window technique
* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(n) for hash map
*/

int minimumRounds(int* tasks, int tasksSize) {

}

```

### Go Solution:

```

// Problem: Minimum Rounds to Complete All Tasks
// Difficulty: Medium
// Tags: array, greedy, hash
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(n) for hash map

func minimumRounds(tasks []int) int {

}

```

### Kotlin Solution:

```

class Solution {
    fun minimumRounds(tasks: IntArray): Int {

    }
}

```

### Swift Solution:

```

class Solution {
    func minimumRounds(_ tasks: [Int]) -> Int {

    }
}

```

### Rust Solution:

```
// Problem: Minimum Rounds to Complete All Tasks
// Difficulty: Medium
// Tags: array, greedy, hash
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(n) for hash map

impl Solution {
    pub fn minimum_rounds(tasks: Vec<i32>) -> i32 {

    }
}
```

### Ruby Solution:

```
# @param {Integer[]} tasks
# @return {Integer}
def minimum_rounds(tasks)

end
```

### PHP Solution:

```
class Solution {

    /**
     * @param Integer[] $tasks
     * @return Integer
     */
    function minimumRounds($tasks) {

    }

}
```

### Dart Solution:

```
class Solution {
    int minimumRounds(List<int> tasks) {
```

```
}  
}
```

### Scala Solution:

```
object Solution {  
  def minimumRounds(tasks: Array[Int]): Int = {  
  
  }  
}
```

### Elixir Solution:

```
defmodule Solution do  
  @spec minimum_rounds(tasks :: [integer]) :: integer  
  def minimum_rounds(tasks) do  
  
  end  
end
```

### Erlang Solution:

```
-spec minimum_rounds(Tasks :: [integer()]) -> integer().  
minimum_rounds(Tasks) ->  
.
```

### Racket Solution:

```
(define/contract (minimum-rounds tasks)  
  (-> (listof exact-integer?) exact-integer?)  
)
```