

Web Programming Fundamentals

CIS 241: Web Fun

Announcement

The pseudo codepen is available now

[View Course Content](#)

CIS 241: Web Fun

Announcement

The pseudo codepen is available

You can add/edit/modify the **source code directly**

[View Course Content](#)

```
body { font-family: Helvetica; }  
h1 { text-align: center; }  
a { text-align: center; }  
p { border: 3px solid hotpink;  
    background-color: lavenderblush; }
```

[Pseudo-codepen](#)

CIS 241: Web Fun

How do we get from this...

Announcement
 The pseudo codepen is available
 You can add/edit/modify the source code directly

[View Course Content](#)

CIS 241: Web Fun

... to this?

Announcement
 The pseudo codepen is available
 You can add/edit/modify the source code directly

[View Course Content](#)

Types of HTML elements

Each HTML element is categorized by the HTMLspec into one of three-ish categories:

1. **block**: large blocks of content, has height and width
`<p>`, `<h1>`, `<blockquote>`, `<ol>`, `<ul>`, `<table>`
2. **inline**: small amount of content, no height or width
`<a>`, `<em>`, `<strong>`, `<br>`
 - a. **inline block**: inline content with height and width
`<img>`
3. **metadata**: information about the page, usually not visible
`<title>`, `<meta>`

Block elements

- Take up the full width of the page (**flows top to bottom**)
- Have a height and width
- Can have block or inline elements as children



Block elements

About block elements

They flow top to bottom

<h1> is block-level, so it extends the full width of the page by default

Note how block-level elements (**h1**, **p**) flow top to bottom

Q: What does this look like in the browser?

```
h1 {
  border: 5px solid red;
  width: 50%;
}
```

Block elements

About block elements

They flow top to bottom

<h1> is block-level, so its width can be modified. Block-level elements still flow top to bottom

Inline elements

<a>, ,
.

Take up only as much width as needed
(flows left to right)


No width/height

No child block elem

Cannot be positioned

with float or position

- Must position its containing block element instead



Inline elements

Programming Resources [CIS 241](#) [MDN](#) [W3S](#)

```
<strong id="red" >Web programming resources:</strong>
<a href="http://localhost:22022/course-content/section/section2
html-css/lesson/Intro-To-HTML-And-CSS" >CIS 241</a>
<a
href="http://localhost:22022/websites/developer.mozilla.org/en-
US/">MDN</a>
<a href="http://localhost:22022/websites/w3schools.com/">W3S</a>
```

Inline elements

Q: What does this look like in the browser?

```
strong {
  border: 5px solid red;
  width: 1000px;}

```

Programming Resources [CIS 241](#) [MDN](#) [W3S](#)

Inline elements

Q: What does this look like in the browser?

```
strong {
  border: 5px solid red;
  width: 1000px;} /*Will not work; strong
is inline */
```

Programming Resources [CIS 241](#) [MDN](#) [W3S](#)

Cannot set width on inline element, so it is ignored

Inline-block

 with display:

inline-block

- Width is the size of the content, ie. It takes only as much space as needed (flows left to right)

- can have height/width

- can have child as block element

-can be positioned



- Block : flows top-to-bottom; has height/width
<p>, <h1>, , <table>
- Inline: flows left-to-right; does not have height/width <a>, , ,

 - Inline block: flows left-to-right; has height/width equal to size of the content

Review

The **text-align** [CSS](#) property sets the horizontal alignment of the inline-level content inside a block element or table-cell box. This means it works like [vertical-align](#) but in the horizontal direction.

```
span {background-color: yellow;}
a {display: block; text-align: center;}
</style>
</head>
<body>
<h1>CIS 241: Web Fun</h1>
<p>
  <strong>Announcement</strong><br/>
  The pseudo codepen is available <br/>
  You can add/edit/modify the <span>source code
  directly</span>
</p>
<a href="http://localhost:22822/course-
content/section/section1-html-css/lesson/certificate" >
  View Course Content</a>
```

Inline elements

CIS 241: Web Fun

Announcement

The pseudo codepen is available
You can add/edit/modify the **source code directly**

[Pseudo-codepen](#)

[View Course Content](#)

```
p {background-color: lavenderblush; display:inline-block;}
a {display: block; text-align: center;}
</style>
</head>
<body>
<h1>CIS 241: Web Fun</h1>
<p>
  <strong>Announcement</strong><br/>
  The pseudo codepen is available <br/>
  You can add/edit/modify the <span>source code
  directly</span>
</p>
<a href="http://localhost:22822/course-
content/section/section1-html-css/lesson/certificate" >
  View Course Content</a>
```

Inline elements

CIS 241: Web Fun

Announcement

The pseudo codepen is available
You can add/edit/modify the **source code directly**

[View Course Content](#)

```
body {font-family: Helvetica; font-size:2em; text-align: center;}
h1 { text-align: center;}
p {border: 3px hotpink solid; background-color: lavenderblush; display:
block}
span {background-color: yellow;}
a {display: block; text-align: center;}
<h1>CIS 241: Web Fun</h1>
<p>
<strong>Announcement</strong><br/>
The pseudo codepen is available <br/>
You can add/edit/modify the <span>source code directly</span>
</p>
<a href="http://localhost:22022/course-content/section/section1-html-
css/lesson/certificate" >View Course Content</a>
```

CIS 241: Web Fun

[Pseudo-codepen](#)

Announcement

The pseudo codepen is available
You can add/edit/modify the **source code directly**

[View Course Content](#)

Selector summary

Example	Example described
p	All <p> elements
.abc	All elements with the abc class, i.e. class="abc"
#abc	Element with the abc id, i.e. id="abc"
p.abc	<p> elements with abc class
p#abc	<p> element with abc id (p is redundant)
div strong	 elements that are descendants of a <div>
h2, div	<h2> elements and <div>s

Common bugs

p.abc vs p.abc
p.abc vs p, .abc

A <p> element with the **abc** class **vs**
An element with the **abc** class that descends from <p>
•An element with the **abc** class that descends from <p> **vs**
All <p> elements *and* all elements with the **abc** class