

1. Which of the following correctly defines a route? (select all that apply)

Show Results

17/18 Students Answered

- A { path: "/", component: Home } ✓
- B { path: "/about", name: 'about', component: About } ✓ optional -- name
- C { path: "/products" } ✗
- D { path: "/services", name: 'services' } ✗
- E { path: "/contact-us", name: 'contact', component: ContactForm } ✓

Show explanation





2. Given the following router config:

```
const routes = [  
  {  
    path: '/',  
    name: 'home',  
    component: Home  
  },  
  {  
    path: '/about',  
    name: 'about',  
    component: About  
  },  
  {  
    path: '/contact',  
    name: 'contact',  
    component: Contact  
  }  
]
```

Which of the following are valid router-links? Select all that apply:

Show Results

17/18 Students Answered

- A `<router-link to="/home">Home</router-link>`  no path called /home
- B `<router-link to="/about">About</router-link>` 
- C `<router-link v-bind:to="{ component: About }">About</router-link>` 
- D `<router-link v-bind:to="{ name: 'contact' }">Contact</router-link>` 

i Show explanation 

3. What is the correct way to define a dynamic segment while setting up a route?

Show Results

17/18 Students Answered

- A path: "/book-review/:book_id" ✓
- B path: "/book-review", dynamic: "book_id" ✗
- C path: "/book-review", param: "book_id" ✗
- D path: "/book-review/#book_id" ✗

4. What built-in CSS class is applied to the <router-link> of the current page?

Show Results

17/18 Students Answered

- A .current
- B .link-current
- C
- D .router-link-active ✓
- E .this-page

5. Which component displays the content of a route's matched component when the user clicks on a link?

Show Results

17/18 Students Answered

- A `<router-link></router-link>`
- B `<template></template>`
- C `<router-route></router-route>`
- D `<router-view></router-view>` ←

6. If you had the following router configuration, how would you access the book's ID in the BookReview component?

```
const routes = [  
  {  
    path: '/book-review/:book_id',  
    name: 'book',  
    component: BookReview  
  }  
]
```

Show Results

17/18 Students Answered

- A `this.params.book_id` ✗
- B `$book_id` ✗
- C `this.$route.params.book_id` ✓
- D `this.book_id` ✗

7. What's the resulting URL from the following this.\$router.push call?

this.\$router.push(({ path: 'users', query: { active: 'true' } })); script

Show Results

17/18 Students Answered

- A /users path is correct but missing the query part
- B /path/users/true ✗
- C /users/active/true ✗
- D /users?active=true ✓

i Show explanation ▼