

```
GNU nano 2.7.1 server.c
#include <stdio.h>
#include <unistd.h>
#include <sys/socket.h>
#include <sys/un.h>
#include <string.h>

#define SOCKET_PATH "/tmp/my_socket"

int main()
{
    int server_fd, client_fd;
    struct sockaddr_un address;
    char buffer[100];

    // Create socket
    server_fd = socket(AF_UNIX, SOCK_STREAM, 0);

    // Set socket address
    address.sun_family = AF_UNIX;
    strcpy(address.sun_path, SOCKET_PATH);

    // Remove old socket
    unlink(SOCKET_PATH);

    // Bind socket to path
    bind(server_fd, (struct sockaddr *)&address, sizeof(address));

    // Wait for client
    listen(server_fd, 5);

    printf("Server waiting...\n");

    // Accept client
    client_fd = accept(server_fd, NULL, NULL);

    // Receive message
    read(client_fd, buffer, sizeof(buffer));
}

GNU nano 2.7.1 client.c
#include <stdio.h>
#include <unistd.h>
#include <sys/socket.h>
#include <sys/un.h>
#include <string.h>

#define SOCKET_PATH "/tmp/my_socket"

int main()
{
    int client_fd;
    struct sockaddr_un address;
    char message[] = "Hello Server";

    client_fd = socket(AF_UNIX, SOCK_STREAM, 0);

    address.sun_family = AF_UNIX;
    strcpy(address.sun_path, SOCKET_PATH);

    connect(client_fd, (struct sockaddr *)&address, sizeof(address));

    write(client_fd, message, strlen(message) + 1);

    close(client_fd);

    return 0;
}
```

```
nsirichandana@SIRI:~/OSLAB$ gcc server.c -o server
nsirichandana@SIRI:~/OSLAB$ ./server
Server waiting...
Message from client: Hello Server
nsirichandana@SIRI:~/OSLAB$

nsirichandana@SIRI:~/OSLAB$ gcc client.c -o client
nsirichandana@SIRI:~/OSLAB$ ./client
nsirichandana@SIRI:~/OSLAB$ ./client
nsirichandana@SIRI:~/OSLAB$ nano client.c
nsirichandana@SIRI:~/OSLAB$
```