
Attention-Sink Signatures Dissociate During Vision–Language Pretraining

Samvat Tiwari

Independent Researcher · samvat.t@gmail.com

Abstract

The attention sink is usually described as one phenomenon, but it is measured through three separate signatures: attention concentration on the sink position (Sink_1^e , per query head), a near-zero value-norm there (v-ratio, per KV head), and an outsized residual-stream norm there (h-ratio, per layer, which we read as a massive-activation proxy). In text language models the three co-occur so reliably that a study can report whichever one it measures and generalise to the sink. If they move apart, that inference fails, and whether a lever removed the sink depends on which signature was tracked.

We test this where the signatures can be watched forming: multimodal pretraining with a randomly initialized decoder. We train a 222M-parameter vision–language model, a SigLIP-B/16 encoder feeding a randomly initialized SmolLM2-135M-architecture decoder in which position 0 is the first image token and there is no BOS, under four levers — standard softmax attention, output-gated softmax, unnormalized sigmoid attention, and decoder initialization from a pretrained text LM.

They come apart. Across $n = 2\text{--}3$ seeds per arm the four levers land in four distinct corners of the three-signature space, and no two arms share a signature triple. The value-norm axis alone is strongly drained, mildly drained, or amplified, and which occurs differs by lever. On a low-repetition run over one billion fresh tokens (2.39 effective visual epochs), the massive-activation proxy more than doubles while attention concentration stays at exactly zero. The per-head relationship between concentration and value-norm flips sign from one arm to the next. Prior text-only work separates massive activations from attention sinks. We add dense, joint tracking of all three under randomly initialized decoders in the multimodal setting, and show that all three, value-norm drain included, respond separately to ordinary training-time choices.

1. Introduction

Decoder-only transformers learn a habit early in training. They send a large share of attention to the first token or tokens of a sequence, whatever those tokens contain. The habit has practical weight: streaming inference methods depend on it [1], the extreme activation outliers that come with it make quantization harder [2], and a survey now organizes a subfield around how to interpret it and how to remove it [3].

In text language models the sink does not arrive alone. Three measurements move together. Attention concentrates on the sink token. The value vector there drops to a near-zero norm, called value-state drain [4]. The residual stream there grows an abnormally large norm, called a massive activation [2, 5]. Gu et al. [6] report that these effects settle on the same few tokens, and Queipo-de-Llano, Arroyo et al. [7] that they appear near step 1000. This co-occurrence has led the field to treat the three signatures as facets of one attention-sink phenomenon.

The field disputes whether they really are one phenomenon. One line argues for causal unity: massive activations mathematically require representational compression, and ablating them removes both compression valleys and sink formation [7]. A related view holds that outlier-driven rescaling by attention and residual sinks is *essential* to stable training [8]. Two recent studies pull the other way, each separating a pair of the signatures by intervention: a change of normalization scheme crushes the massive-activation spike while the sink ratio survives [9], and a value-scale intervention keeps the sink while suppressing massive activations [10]. Both are text-only, and each separates at most two of the three.

Which signature a study measures therefore decides what it can conclude. If the three quantities move independently, a lever that clears concentration while leaving the value path untouched looks like a fix under one metric and a failure under the next, and two papers can disagree about whether the sink was removed while both are right about what they measured. This is not only bookkeeping: sink-like attention has been tied to hallucination and weak visual grounding in deployed vision-language models [13–16], so which signature a mitigation moves has practical weight. We measure all three at once, throughout training, and test no downstream behavior here.

Vision-language models make a sharp instrument for the question. The multimodal setting changes what position 0 is: our sequence starts with 49 image tokens and has no BOS token, so the candidate sink token is a visual token, without the special-token machinery that text-LM sink accounts use. The multimodal sink studies we know also analyze mostly frozen, already-trained backbones at inference time [11, 12], and where one tracks alignment checkpoints [11] it follows sink-dimension magnitude rather than the three signatures (§4). A reader still cannot see there whether the signatures arrive together, in sequence, or independently while they form in a decoder that starts from random weights. That requires pretraining with a randomly initialized decoder and all three logged separately from step 0.

We work at deliberately small scale. The model is a 222M-parameter nanoVLM [17], where a pretrained SigLIP-B/16 encoder [18] feeds a randomly initialized decoder with the SmoLLM2-135M architecture [19]. Four levers each target one sink-relevant mechanism (§2): standard softmax attention (*baseline*), a Qiu-style G1 output gate in our zero-initialized variant [20] (*gate*), unnormalized sigmoid attention, which removes the normalization from which sinks are argued to come [6] (*sigmoid*), and initialization from the pretrained SmoLLM2 text model, which imports whatever sink structure text pretraining built (*textinit*). A validated probe logs all three signatures every 100 steps. The four-arm comparison reuses a small image pool, so we re-test the central negative result under low repetition, on a fresh stream of one billion tokens (*RF*, 2.39 effective visual epochs).

Contributions.

1. **Four levers, four corners ($n = 2\text{--}3$ seeds/arm).** The four arms reach four different corners of the three-signature space, and no two share a signature triple. The value-norm ratio alone is strongly drained, mildly drained, or amplified, and which occurs differs by lever (Fig. 1, Table 1). The arms are not a factorial design, so we report distinct intervention-associated profiles, not isolated causal effects.
2. **Low-repetition decoupling at 1B tokens ($n = 1$).** On a fresh stream at 2.39 effective visual epochs, with a held-out loss that never turns upward, the massive-activation proxy rises from an h-ratio of 1.43 to 3.22, about $2.3\times$. Attention concentration stays at exactly zero for the entire single-seed run, and no head ever crosses the sink threshold (§3.2, §5).
3. **No consistent-sign head-level relationship.** The per-head correlation between concentration and value-norm flips sign across arms ($+0.76$ baseline $\rightarrow -0.79$ textinit, pooled -0.20 , over 90 KV groups per arm). We report these descriptively (§3.3).

Text-only work already separates massive activations from concentration [9, 10], so decoupling by itself is not new and we do not claim it. The new part is the conjunction: dense, joint tracking of all three signatures under randomly initialized decoders in a multimodal model, with value-norm drain as a third axis that moves on its own.

2. Setup

Model and token layout. All runs use a 222M-parameter nanoVLM [17]. A pretrained, trainable SigLIP-B/16 vision encoder [18] feeds a decoder with the SmoLLM2-135M architecture [19] through a learned modality projector. The decoder has 30 layers of grouped-query attention, with 9 query heads per layer sharing 3 KV heads, so it has 270 (layer, query-head) pairs but only 90 (layer, KV-group) value projections, a distinction that matters in §3.3. The decoder trains **from random initialization** in every arm except *textinit*, because the point is to watch the signatures form. Each sequence holds 49 image tokens as a causal prefix, then 79 left-padded text tokens, for 128 tokens in all. **Position 0 is the first image token, and there is no BOS token.** What happens at position 0 is therefore a property

of the visual prefix in the arms with a randomly initialized decoder, not of inherited BOS machinery. *textinit* is the exception by design: it imports first-position structure from text pretraining, and shows a sink before any multimodal step (§3.1).

Arms. We use four training levers. Each lever targets one sink-relevant mechanism. Everything else stays byte-identical across arms.

arm	attention	LM init	ViT init	lever precedent
<i>baseline</i>	softmax	random	pretrained	—
<i>glgate</i>	softmax + elementwise σ -gate (zero-init, post-SDPA)	random	pretrained	G1 gating [20]
<i>sigmoid</i>	unnormalized sigmoid, no softmax	random	pretrained	Gu et al. [6]
<i>textinit</i>	softmax	pretrained SmolLM2-135M	pretrained	— (novel control)

The *glgate* and *sigmoid* levers have established sink effects in text-only models [20, 6]. The *textinit* lever has no precedent in the sink literature. It works as an inheritance control, importing whatever sink structure text pretraining already built into SmolLM2.

A scale confound in our gate variant. Qiu et al. [20] use ordinary initialization for the G1 gate. We initialize at exactly zero, so the sigmoid opens at $\sigma(0) = 0.5$ and the arm begins as a half-scale attention-output intervention as well as a gating one. We call it **Qiu-style G1 in our zero-initialized variant** throughout (§5).

Data and the two training regimes. The four-arm comparison trains on four curated subsets of the_cauldron [21], about 146K images, matched at about 100M tokens per arm. *textinit* stops at 60M tokens, where its signatures have plateaued (§3.1). Reuse of that pool gives high visual-epoch counts, so a reader could treat a “no sink emerges” result as an overfitting artifact. The **RF** arm (random-fresh) answers that objection: the *baseline* recipe re-trained on a fresh FineVision stream [22] to 1B tokens, over about 4.6M natural images, at **2.39 effective visual epochs**. RF is therefore a **low-repetition** run, not a repetition-free one, since examples do repeat about 2.4 times on average. We estimate the overlap between the fresh pool and the repeated subsets at under 3%, from the config-level composition of the two pools rather than image-level deduplication. Swapping datasets trades the repetition confound for a domain-shift confound, which §5 takes up.

Three signatures, tracked separately. We log the three sink symptoms that the text-LM literature reports together, each at its own granularity, following Gu et al. [6] at a fixed sequence length. The decoder has $L = 30$ layers, $H = 9$ query heads per layer, and $G = 3$ KV heads per layer. Every quantity below is averaged over valid query positions and over the fixed probe batch.

Concentration ($\text{Sink}^\varepsilon_1$) is the fraction of the $L \cdot H = 270$ (layer, query-head) pairs whose mean attention to position 0 exceeds ε . We use the $\varepsilon = 0.3$ default of [6] and check $\varepsilon \in \{0.2, 0.4\}$. Cross-arm tables report the stricter $\varepsilon = 0.2$, which makes an absence claim harder to pass.

Value-norm ratio (v-ratio) is the value norm at position 0 divided by the mean value norm over the other valid positions, computed per layer and then averaged over the 30 layers. Below 1 is value-drain [4]. Above 1 is amplification. Under grouped-query attention a value vector belongs to a KV group and repeats across 3 query heads, so the ratio rests on $L \cdot G = 90$ independent value projections, not 270. This matters for §3.3.

Residual-norm ratio (h-ratio) is the residual-stream norm at position 0 divided by the mean norm over the other positions, again per layer and then averaged over the 30 layers. We call it a **massive-activation proxy**, because massive activations are normally defined by channel-level outliers [2, 5], which we never measured (§5).

All three metrics **anchor on position 0 by construction**. We state this as a measurement choice and check it: at seed 0, per-position attention mass makes position 0 the maximum-mass token in every arm (Appendix C). §5 handles the remaining seed-level caveat. The *sigmoid* arm reports the row-normalized attention view, which keeps concentration comparable across arms, and we also log the raw sigmoid mass (Appendix D).

Why a sink is expected at all. Softmax forces every attention row to sum to one, so a head with nothing informative to retrieve must still place its mass somewhere. Gu et al. [6] argue that the sink token absorbs that surplus and acts “more like key biases.” Our *sigmoid* arm, which removes normalization, is the direct test of that constraint.

Probe. The function `probe_sinks()` re-walks the decoder from the live module weights in eager mode, in fp32, with no gradients, independent of the training path, which uses fused SDPA kernels, autocast and `torch.compile`. Every call validates its hidden states against the real forward pass to a relative error below 10^{-2} , so the probe cannot drift from what the trained model computes. The probe batch is fixed across all runs and seeds, so every number here is comparable run to run, and probes fire every 100 optimizer steps, dense enough to timestamp each signature’s first threshold crossing (§3.4). Appendix F gives the probe-batch composition, token accounting and validation protocol.

Recipe. We use AdamW with weight decay 0.1, following [6], and a gradient clip of 1.0. The schedule is cosine with 3% warmup. The learning rates are 4×10^{-4} for the language model, 2×10^{-3} for the projector, and 10^{-4} for the vision encoder. We use bf16 autocast, `torch.compile`, and a batch size of 128. Arms in a comparison differ only in the lever under test. We use two seeds for *baseline* and *sigmoid*, three for *glgate* and *textinit*, and one for *RF*.

Validation losses, and what they do and do not license. Training stays healthy in all reported runs. At the matched 100M-token checkpoint the held-out losses are 1.182 for *baseline*, 1.133 for *glgate*, 1.206 for *sigmoid* and 0.877 for *textinit*, and RF reaches 0.638 at 1B tokens (Appendix F). Two cautions. *textinit* starts from a pretrained text decoder, so its lower loss reflects unequal competence rather than a lever effect, and only *baseline*, *glgate* and *sigmoid* are equal-token, equal-initialization comparisons. The repeated-data arms also show a large train–validation asymmetry (`val_seen` near 0.44 against `val_unseen` near 1.18), the overfitting signal that motivates RF. RF has no distinct seen split, so the weaker statement its data supports is that its held-out loss falls throughout and never turns upward (§5). **We did not run MMStar or any other downstream benchmark on any arm**, so this paper makes no capability claim (§5).

3. Results




Figure 1: Decoupling phase-portrait. Trajectories of every arm in concentration-against-value-norm space (left) and concentration against the residual-norm ratio (right, log scale). Circles mark initialization, diamonds the final checkpoint, at about 100M tokens for *baseline*, *glgate* and *sigmoid*, 60M for *textinit*, and 1B for *RF*. Seed 0 unless labelled. **Note the metric difference from the tables:** the horizontal axis is the *maximum* attention→pos0 over heads, whereas Table 1 reports Sink^E_1 , the *fraction of query heads above a threshold*, so an arm can sit off zero here while its Sink^E stays 0.000. Paths are smoothed and the end markers use raw values (Appendix D). Were the three signatures one phenomenon, these trajectories would move along one direction.

3.1 Four training levers reach four different signature corners

Table 1 collapses the seeds into per-arm ranges, each arm read at its final matched checkpoint: about 100M tokens for baseline, glgate and sigmoid, and 60M for *textinit*, whose signatures have plateaued by then. Appendix B gives the per-seed table. **No two arms share a signature triple.**

Table 1 — the four corners (n = 2–3 seeds per arm). Concentration is $\text{Sink}^{0.2}_1$, the fraction of the 270 (layer, query-head) pairs whose mean attention→pos0 exceeds 0.2. The v-ratio rests on 90 (layer, KV-head) value projections and the h-ratio on 30 layers (§2).

arm	concentration	value-norm	massive-activation proxy
baseline	absent (0.000)	mild drain (0.69–0.72)	moderate (1.7–2.2)
glgate	near-absent (0.004–0.011)	milder drain (0.81–0.85)	moderate (1.7–2.2)
sigmoid	strong (0.76–0.83)	amplified (1.48–1.60)	no strong asymmetry (1.1–1.3)
textinit	strong (0.56–0.85)	strong drain (0.38–0.63)	extreme (5.5–42.5)

The value-norm axis alone takes three qualitatively different directions: drained hard, drained mildly, or amplified above 1. No arm leaves it unchanged.

The corners separate pairwise on single axes. *glgate* differs from *baseline* on the value-norm axis alone, since concentration is absent or near-absent and the residual-norm ratio moderate in both, while the gate makes the baseline’s mild drain milder still, a 15–19% drain rather than none. *sigmoid* and *textinit* both reach strong concentration and then part on the *direction* of the value-norm move and on the residual-norm ratio. Each arm shows a distinct intervention-associated profile. The arms are not a factorial design, so we do not attribute these profiles to isolated causal effects of single levers. The trajectories in Figure 1 separate early and do not share one origin: *textinit* starts from a pretrained text decoder, with an inherited sink already in place.

Reproducibility differs by arm. *glgate* is tightest, at $\text{Sink}^{0.2}_1$ of 0.004, 0.011 and 0.0037 across three seeds. The corner of *textinit* repeats across seeds and its magnitudes do not: seed 0 sits far above the other two on every signature at once, at h-ratio 42.5 against 5.5–12.2, partly because at seeds 1 and 2 its peak signatures move off position 0, where our metrics anchor (§3.4, Appendix B). We therefore report the massive-activation proxy of *textinit* as a **range (5.5–42.5×) with a median near 12×** throughout, and treat the corner as the reproducible claim rather than any magnitude.

3.2 The massive-activation proxy grows across 1B low-repetition tokens while concentration stays at zero

The four-arm comparison reuses a 146K-image pool, so a reader could read its “concentration never emerges” result as an overfitting artifact. The RF arm addresses that: the identical *baseline* recipe on a fresh FineVision stream to one billion tokens, at **2.39 effective visual epochs**. Examples still repeat, about 2.4 times on average, so this is a **low-repetition** run rather than a repetition-free one. Its held-out loss falls through the full billion tokens and never turns upward (§2, §5).

Concentration never arrives. $\text{Sink}^{0.3}_1 = 0.000$ across the entire 0 → 1B run, with no head of the 270 crossing the threshold at any of about 700 probes. The massive-activation proxy, in the same run, keeps growing far past warmup.

Table 2 — RF (fresh stream, 2.39 visual epochs, n = 1 seed), init → 1B tokens.

signature	@ init	@ 1B	net
$\text{Sink}^{0.3}_1$ (concentration)	0.000	0.000	flat zero, entire run
max attn→pos0	0.056	0.098	≈flat, far below threshold
h-ratio (massive-activation proxy)	1.43	3.22	≈2.3×, positive long-horizon trend
v-ratio (value-norm)	1.00	0.69	net drain, non-monotone

Warmup does not explain the rise. The h-ratio climbs from 2.40 at about 57M tokens to 3.22 at 1B, long after the 3% warmup window closes, though not monotonically at probe resolution, so we report it as a positive long-horizon trend. In Figure 1, at right, the violet trajectory climbs and never moves rightward. The v-ratio ends below its initialization value, but about 75% of that drop happens in the first 57M tokens and it then recovers part of it, so we report it as supporting context rather than ongoing emergence. **The massive-activation proxy grows about 2.3× across a full billion tokens of multimodal training while attention concentration never leaves zero (n = 1 seed, §5).**

3.3 No consistent-sign head-level relationship between concentration and value-norm

A tight coupling between concentration and value-drain should at minimum hold the sign of their per-head correlation constant across regimes. It does not. Table 3 reports the Pearson r between $\text{attn} \rightarrow \text{pos0}$ and value-norm ratio at each arm’s final checkpoint, over the 90 (layer, KV-group) observations: a value vector is shared by 3 query heads, so we average a group’s query-head attention rather than triplicate its value observation (§2). Appendix Fig. A2 plots the scatter.

Table 3 — $r(\text{attn} \rightarrow \text{pos0}, \text{v-ratio})$, final checkpoint. Descriptive only, no p-values.

baseline	g1gate	sigmoid	textinit	RF	pooled
+0.76	+0.57	−0.04	−0.79	+0.51	−0.20

These correlations are **descriptive statistics, not inferential ones**, and we deliberately report no significance tests: heads within a layer are not independent, and each arm rests on a single seed here, so a p-value would mislead. Collapsing to the 90 KV groups removes the pseudoreplication a per-query-head reading would introduce and leaves the picture unchanged (Appendix D).

The pattern is about **sign**, which pseudoreplication does not manufacture. Heads that attend more to position 0 have *larger* value norms in the baseline regime and *smaller* ones under text initialization, and the pooled correlation is weak only because arms of opposite sign cancel. We therefore claim no consistent-sign relationship across arms. We do not claim the absence of a coupling law: a fixed coupling would show one sign everywhere, and it does not.

3.4 Ordering: norm signatures lead, and concentration is late, mirrored, or absent




Figure 2: Sink birth and ordering. Seed 0 throughout. *Top*: a time-to-event view. Each shaded track spans the tokens for which we observed that arm (60M to 1B). A filled marker is the first probe at which a signature crossed its per-head threshold ($h > 2$, $v < 0.8$, $\text{attn} \rightarrow \text{pos} > 0.3$). A hollow marker at a track's end means it never crossed within the observed run. **All crossing times are interval-censored** at the 100-step probe cadence, so two signatures crossing within one interval of each other should not be read as ordered. *Bottom*: birth-maps, the step at which each (layer, query-head) pair first crosses the concentration threshold. No baseline and no RF head ever crosses. 1% of g1gate heads do, against 89% for sigmoid and 87% for textinit.

Dense probing lets us timestamp each signature’s arrival (Figure 2), and the ordering stays consistent inside each arm family. In the softmax arms with randomly initialized decoders, *baseline* and *g1gate* and *RF*, the norm signatures come early: the residual-norm ratio crosses within the first few to about 15M tokens and value-drain follows within about 50M. Concentration never comes. No baseline or RF head ever crosses it, and g1gate reaches 1% of heads, a single-layer blip late in training. *sigmoid* mirrors that pattern, with concentration crossing at about 6M tokens and 89% of heads eventually, while neither norm signature ever crosses. *textinit* inherits its norm signatures rather than growing them: value-drain and an elevated residual-norm ratio are both present at 0 tokens, imported with the pretrained text-LM weights. Concentration is *not* inherited the same way, since $\text{Sink}^{0.3}_1$ is 0.000 at step 0 and crosses before 1M tokens. Even in the arm that imports the most sink structure, the norm signatures precede concentration.

The sink stripe: every query attends to the first image token — absent in baseline, total in textinit, and already present at init (inherited)




Figure 3: The sink stripe. Query $\times$ key attention of each arm's top sink head, row-normalized, seed 0. Panels are labelled with seed, step and token count. Top row early in training (step 250, about 2.4M tokens), bottom row the final checkpoint. The cyan line marks key = pos0, the dotted line the image-to-text boundary. The pos0 stripe is *absent* in baseline throughout and strong in textinit (attn $\rightarrow$ pos0 = 0.62 at its final checkpoint), and the rightmost panel shows it *already present at step 0* in textinit, inherited from the text language model. The *sigmoid* column uses head L7H3, the arm's top sink head on the fixed probe batch. Its heat maps are re-rendered from an auxiliary streaming batch, while every printed sigmoid number comes from the fixed probe batch (Appendix D).

Figure 3 shows the same result at the level of a single head. The vertical stripe at key = pos0 marks every query attending to the first image token. It is absent in *baseline* at both checkpoints and strong in *textinit*, and the rightmost panel carries the most weight: **the stripe is already there at step 0 in textinit**, imported with the text-LM weights before the model has seen one image.

The *sigmoid* arm needs one measurement note, because row-normalization changes the object being measured and Gu et al. [6] state their result for *unnormalized* sigmoid attention. The concentration this arm develops is a **relative** reallocation of a shrinking gate budget onto position 0, not the growth of a large absolute mass there (Appendix D). We report the row-normalized view in the tables so the arms stay comparable.

Attention-entropy collapse, the text-LM literature's usual correlate of concentration, separates the same way: only *sigmoid* and *textinit* collapse (Appendix Fig. A3). It tracks the concentration axis, not the norm axes.

The signatures also dissociate in position. A per-position scan across all three *textinit* seeds shows they need not share a token. At seed 0 they coincide at position 0. At seed 1 the attention maximum stays there while the residual peak moves to pos1 and the value minimum to pos5. At seed 2 they separate furthest, attention at **pos1** and both norm extrema at **pos13**. The arms with randomly initialized decoders behave differently: position 0 stays the maximum-mass token in *baseline*, *glgate* and *sigmoid* at every seed scanned, and in *RF* the attention argmax sits at pos1 with mass 0.100 against 0.083 at position 0, a diffuse profile rather than a sink (Appendix C).

We report this as a supporting observation, not a second headline. It has one consequence for measurement: because all three metrics anchor on position 0, the *textinit* magnitudes at seeds 1 and 2 are read at a token that is no longer the peak and therefore **understate** the arm's true peaks, a further reason to report that arm as a range and a median (§3.1, §5). The anchoring holds for the randomly initialized decoders, which carry the central negative result. Appendix E sets out, as untested hypotheses, how each lever might move a different axis.

4. Related Work

Attention sinks and their companions in text language models. Gu et al. [6] give the canonical empirical account: the sink token acts “more like key biases, storing extra attention scores, which could be non-informative and not contribute to the value computation.” They report small key and value norms at the sink as part of the same phenomenon, connect it to massive residual-stream activations [2, 5], and show that unnormalized sigmoid attention prevents sink formation in text models up to 1B parameters, the result our *sigmoid* arm builds on. Guo et al. [4] describe the concentration and value-drain coupling as “active-dormant” heads. Queipo-de-Llano, Arroyo et al. [7] make the strongest unity claim, and the only genuinely *causal* one: massive activations mathematically require representational compression, and ablating a model’s layer-0 massive activation removes both compression valleys and sink formation. Across Pythia checkpoints they find the three appearing together near step 1000 and staying synchronized. We reserve the term “causally unified” for that result alone. Peng et al. [24] trace a first-position sink circuit emerging early in from-scratch text pretraining, in text only, without separating the signatures.

Prior decoupling results: text-only, two axes. Two recent papers already separate pairs of these signatures in text models, and we scope our claim around them. Sun, Canziani, LeCun and Zhu [9] show that massive activations and attention sinks are dissociable architectural artifacts: a change of normalization scheme crushes the massive-activation spike while the sink ratio survives, a two-way dissociation in text only, through a normalization lever, on trained checkpoints. Chen and Yao [10] decouple the same pair from the opposite direction and from scratch, where a value-scale intervention in 0.1–0.3B text models keeps the sinks and suppresses massive activations. Neither treats value-norm drain as a third axis that moves on its own, and neither is multimodal. Fesser et al. [23] give the closest external support for tracking the value norm separately: one sink pattern can hide two algorithms, an “adaptive nop” (a no-op, where the head suppresses its own update by routing to a null token) and a “broadcast” that redistributes global information, and nop sinks show negligible value norms where broadcast sinks produce low-rank outputs. That work diagnoses trained vision transformers rather than tracking emergence, but it independently motivates treating the value norm as diagnostic rather than decorative. On the opposite side, Qiu et al. [8] hold that outlier-driven rescaling by attention and residual sinks is essential to stable training. The field is unsettled both on whether these signatures separate and on whether anyone should remove them.

Multimodal sinks: mostly frozen backbones, inference time. Luo et al. [11] identify high-norm attention-sink tokens that originate in the vision transformer, and separate ViT-propagated sinks from LLM-emerged sinks. Their Appendix A.4 does track sink-dimension magnitudes across alignment checkpoints, so a training-time view of multimodal sinks is not without precedent. That view uses a frozen vision transformer and a pretrained language model, and follows sink-dimension magnitude rather than the three signatures separately. Choi et al. [12] likewise distinguish vision-sinks from language-sinks in a frozen model and gate them by layer. Both establish that multimodal sinks have distinct vision-side and language-side origins, which our *textinit* inheritance result fits. What is not yet available there is dense, joint tracking of concentration, value-norm and residual-norm as separate quantities in a decoder that starts from random weights. Vision transformers also grow high-norm “register” tokens of their own [25], which is why the pretrained encoder gets its own limitation in §5. A separate line ties these signatures to hallucination and grounding failure in deployed models and intervenes at inference time [13–16], which is the main practical reason it matters which signature a mitigation moves.

The gating lever. Qiu et al. [20] introduce the head-specific elementwise sigmoid gate on attention output that our *glgate* arm adapts. In text models it “largely reduces the attention score allocated to the first token and decreases massive activations” while improving quality. Our variant differs in one way that matters: Qiu et al. use ordinary initialization, and we initialize at exactly zero, so the gate opens at $\sigma(0) = 0.5$ and applies a half-scale factor at step 0 (§2), leaving gating and initial scaling confounded. With that caveat, concentration is already absent in our baseline, so the axis on which the gated arm differs is the value-norm axis: the drain becomes milder, from 0.69–0.72 to 0.81–0.85, rather than being removed. That stays invisible unless the three signatures are logged separately.

Positioning. The closest prior work separates at most two of the three axes, in text-only models, and the multimodal studies work mostly on frozen models. Our claim is therefore the conjunction: **dense, joint tracking of concentration, value-norm drain, and the residual-norm ratio as separately measured quantities, in multimodal pre-**

training with a randomly initialized decoder, adding value-norm drain as a third axis beyond the massive-activation-vs-sink dissociations shown in text models [9, 10]. We do not claim priority on decoupling itself, and we do not claim that prior multimodal work cannot study emergence.

5. Limitations

Metrics anchored on position 0. We measure all three signatures at the first image token, verified by per-position attention *mass* rather than *argmax* alone. Position 0 is the maximum-mass token in every arm at seed 0, and stays so for *baseline*, *glgate* and *sigmoid* at every seed scanned. It does **not** in *textinit*, where at seed 1 the residual peak moves to pos1 and the value minimum to pos5, and at seed 2 the attention maximum sits at pos1 while both norm extrema sit at pos13 (Appendix C). Our pos0-anchored magnitudes for *textinit* at those seeds therefore *understate* its peaks, a further reason we report that arm as a range and a median and treat its corner rather than its magnitudes as the claim. In *RF* the attention *argmax* sits at pos1, but with mass 0.100 against 0.083 at pos0, a diffuse profile rather than a displaced sink, so the RF negative result does not depend on the anchor.

The gate arm carries a scale confound. We initialize the G1 gate at exactly zero, so it opens at $\sigma(0) = 0.5$ and halves attention output at step 0, where Qiu et al. [20] use ordinary initialization (§2). Gating and initial output scaling are therefore confounded in our *glgate* arm, and its differences from baseline cannot be attributed to gating alone. A scale-matched control is future work.

Pretrained vision encoder: no arm is fully from scratch. The SigLIP encoder is pretrained and trainable in every arm, and *textinit* additionally uses a pretrained decoder. What we study is therefore vision–language pretraining with randomly initialized decoders, not from-scratch training of the whole model, and we word it that way throughout. Vision transformers grow high-norm register tokens of their own [25], and sinks can propagate from a vision transformer into a large vision–language model [11], so part of our residual-norm signal could be inherited rather than decoder-formed. Our defense is the trajectory: the h-ratio starts at 1.0–1.4 and *rises* to 3.22 across 1B tokens in RF, where pure inheritance from a static encoder predicts a high, flat h-ratio from step 0. A randomly initialized vision transformer, which would isolate the decoder entirely, is future work.

The h-ratio is a proxy, not a measurement of massive activations. Massive activations are normally defined by channel-level outliers [2, 5]. We measured a position-specific residual-norm ratio and never computed channel-level statistics, so we report the h-ratio as a massive-activation proxy (§2). A large h-ratio is consistent with massive activations but does not establish them.

Token scale. Our runs reach at most 1B tokens per arm, against the roughly 5B tokens that are canonical in the text-LM sink literature [6]. Sink emergence is early relative to that budget, and text-LM sinks form near step 1000 [7], far inside our range. We nonetheless cannot rule out that a signature absent at 1B tokens emerges later.

Reproducibility of *textinit* magnitudes. The massive-activation proxy of *textinit* is seed-sensitive, at an h-ratio spanning 5.5–42.5 across three seeds, with seed 0 the consistent outlier on every signature. The corner is the reproducible claim: strong concentration, plus strong drain, plus a large residual-norm ratio. No specific magnitude is.

Provenance and seed count. We trust the seed-0 raw probes for the four-arm comparison from a checksummed archive summary rather than re-derive them first-hand. We *did* independently re-derive seeds 1 and 2, and that audit caught a metric-labeling error in an earlier internal consolidation (Appendix G). *baseline* and *sigmoid* have two seeds, *glgate* and *textinit* three, and the RF arm a **single seed**. RF also contains one **weights-only optimizer restart at about 57M tokens** that an out-of-memory error forced: the weights were reloaded and the AdamW moment estimates discarded, so RF is not a single uninterrupted optimizer trajectory. The audit verified continuity across that seam, where the v-ratio and h-ratio are identical at the shared checkpoint, a double-covered 600-step overlap diverges only within probe noise, and concentration reads 0.000 on both sides. Concentration was reproducibly zero across both seeds of the repeated-data baseline, which we take as adequate support for the negative claim. A second fresh-data seed would strengthen it.

What cannot be checked on RF. RF has no distinct seen split, so we cannot run for it the `val_seen` / `val_unseen` comparison that exposes memorization in the repeated arms, and the weaker statement its data supports is that its held-out loss falls throughout and never turns upward (§2). Its streaming shuffle buffer was also reduced from 1500 to 500 examples partway through, again for memory reasons, so stream ordering is not homogeneous across the run, though the $\text{Sink}^{0.3}_1 = 0.000$ result and the h-ratio rise both hold within each regime separately. The RF probe batch is also still the **fixed repeated-the_cauldron tail** used by the other arms. That keeps RF’s signatures comparable to the repeated arms, which is what the negative result needs, but it means they are measured on data from the other distribution.

Domain shift in the fresh-data control. RF reduces repetition by a change of dataset, which introduces a domain-shift confound in its place. We accepted the trade deliberately, because repetition is the dominant confound, and chose the fresh pool to minimize shift. The under-3% overlap figure is an estimate from config-level composition, not image-level deduplication (§2), and we did not run a third, domain-matched control. That control, which would compare fresh and repeated data at matched domain, is the known follow-up.

We report no benchmark accuracy. We measure sink signatures with the probe of §2. We did not run downstream benchmark evaluation, such as MMStar, on any arm. We make no claim about how signature dissociation relates to downstream capability.

6. Conclusion

We tracked concentration, value-norm drain, and a residual-norm ratio that we read as a massive-activation proxy as separate quantities, across multimodal pretraining with randomly initialized decoders. They came apart everywhere we looked. Four training levers produced four different signature corners, and the value-norm axis alone moved in three directions. On a low-repetition, single-seed run over a billion fresh tokens, at 2.39 effective visual epochs, the massive-activation proxy grew about $2.3\times$ while concentration never left zero. The per-head correlation between the first two flipped sign across arms. The signatures even arrived in different orders, and under text initialization they separated in position as well.

Text-LM work documents real interactions among these signatures, including a causal route from massive activations to sinks and compression valleys [7]. Our results show the coupling is not obligatory: each axis moved separately under ordinary levers, extending the two-way text-only dissociations [9, 10] to a third axis and a new setting. For interpretability and mitigation work the practical result is blunt. One signature is not a proxy for the others. A model with no attention sink can still carry a growing residual-norm asymmetry, and a gate that changes value-drain can leave the other axes where they were.

Next steps. Train a randomly initialized vision encoder, to isolate the decoder’s contribution to the residual-norm signal. Extend the fresh-data run past 1B tokens, to match text-LM budgets. Run a scale-matched gate control, to separate gating from the half-scale confound of §2. Each would sharpen what this paper measures: when the signatures form, and in what combinations.

Reproducibility. A self-validating probe (§2) computes all signatures on a fixed probe batch, from dense logs taken every 100 steps. The Appendix holds the per-seed tables. We release the code, the probe, the run configurations, and the per-run logs at <https://github.com/nemesis8932/vlm-sink-emergence>, and the training checkpoints at <https://huggingface.co/datasets/nemesismaniac/vlm-sink-emergence-ckpts>.

References


- [1] G. Xiao, Y. Tian, B. Chen, S. Han, M. Lewis. *Efficient Streaming Language Models with Attention Sinks*. ICLR 2024. arXiv:2309.17453.
- [2] M. Sun, X. Chen, J. Z. Kolter, Z. Liu. *Massive Activations in Large Language Models*. COLM 2024. arXiv:2402.17762.
- [3] Z. Su et al. *Attention Sink in Transformers: A Survey on Utilization, Interpretation, and Mitigation*. arXiv:2604.10098, 2026.

- [4] T. Guo, D. Pai, Y. Bai, J. Jiao, M. I. Jordan, S. Mei. *Active-Dormant Attention Heads: Mechanistically Demystifying Extreme-Token Phenomena in LLMs*. CPAL 2025. arXiv:2410.13835.
- [5] N. Cancedda. *Spectral Filters, Dark Signals, and Attention Sinks*. ACL 2024 (pp. 4792–4808). arXiv:2402.09221.
- [6] X. Gu, T. Pang, C. Du, Q. Liu, F. Zhang, C. Du, Y. Wang, M. Lin. *When Attention Sink Emerges in Language Models: An Empirical View*. ICLR 2025. arXiv:2410.10781.
- [7] N. Queipo-de-Llano, D. Arroyo, F. Barbero, Y. Dong, M. Bronstein, Y. LeCun, R. Schwartz-Ziv. *Attention Sinks and Compression Valleys in LLMs are Two Sides of the Same Coin*. arXiv:2510.06477, 2025.
- [8] Z. Qiu et al. *A Unified View of Attention and Residual Sinks: Outlier-Driven Rescaling is Essential for Transformer Training*. arXiv:2601.22966, 2026.
- [9] M. Sun, A. Canziani, Y. LeCun, C. Zhu. *The Spike, the Sparse and the Sink: Anatomy of Massive Activations and Attention Sinks*. arXiv:2603.05498, 2026.
- [10] Y. Chen, Z. Yao. *Attention Sinks Induce Gradient Sinks*. arXiv:2603.17771, 2026.
- [11] Y. Luo et al. *To Sink or Not to Sink: Visual Information Pathways in LVLMs*. arXiv:2510.08510, 2025.
- [12] J. Choi, J. Kim, S. Kim, S. Hong, J.-H. Park. *When Sinks Help or Hurt: Unified Framework for Attention Sink in Large Vision-Language Models*. ECCV 2026. arXiv:2604.03316.
- [13] S. Kang, J. Kim, J. Kim, S. J. Hwang. *See What You Are Told: Visual Attention Sink in Large Multimodal Models*. ICLR 2025. arXiv:2503.03321.
- [14] T. Shukla, Z. Kira. *SAGE: Sink-Aware Grounded Decoding for Multimodal Hallucination Mitigation*. arXiv:2603.27898, 2026.
- [15] X. Zhang, Y. Zhu, C. Gu, J. Cao, H. Cheng, K. Wu. *What Drives Attention Sinks? A Study of Massive Activations and Rotational Positional Encoding in Large Vision–Language Models*. Information Processing & Management, 63(2A), art. 104431, 2026. DOI 10.1016/j.ipm.2025.104431.
- [16] J. Binkowski, K. Adamczewski, T. Kajdanowicz. *Attention Sinks as Internal Signals for Hallucination Detection in Large Language Models*. arXiv:2604.10697, 2026.
- [17] L. Wiedmann, A. Roy Gosthipaty, A. Marafioti. *nanoVLM*. GitHub repository, 2025. <https://github.com/huggingface/nano-VLM>.
- [18] X. Zhai, B. Mustafa, A. Kolesnikov, L. Beyer. *Sigmoid Loss for Language Image Pre-Training (SigLIP)*. ICCV 2023. arXiv:2303.15343.
- [19] L. Ben Allal et al. *SmolLM2: When Smol Goes Big — Data-Centric Training of a Small Language Model*. arXiv:2502.02737, 2025.
- [20] Z. Qiu et al. *Gated Attention for Large Language Models: Non-linearity, Sparsity, and Attention-Sink-Free*. NeurIPS 2025. arXiv:2505.06708.
- [21] H. Laurençon, L. Tronchon, M. Cord, V. Sanh. *What Matters When Building Vision-Language Models?* (Idefics2 / The Cauldron). NeurIPS 2024. arXiv:2405.02246.
- [22] L. Wiedmann, O. Zohar, A. Mahla, X. Wang, R. Li, T. Frere, L. von Werra, A. Roy Gosthipaty, A. Marafioti. *FineVision: Open Data Is All You Need*. arXiv:2510.17269, 2025.
- [23] L. Fesser, M. Jacobs, T. Fel, A. Keller, S. Kakade. *A Unifying View of Attention Sinks: Two Algorithms, Two Solutions*. arXiv:2606.08105, 2026.
- [24] R. Peng, R. Li, M. Chen, Y. Zhou, Q. Guo, X. Qiu. *How Attention Sinks Emerge in Large Language Models: An Interpretability Perspective*. arXiv:2603.06591, 2026.
- [25] T. Darcet, M. Oquab, J. Mairal, P. Bojanowski. *Vision Transformers Need Registers*. ICLR 2024. arXiv:2309.16588.

Appendix

A. Supporting figures

Where the concentration sink lives: per-(layer,head) attn→pos0 over training



row-normalized attention (sigmoid raw gate ≈ 0.5 everywhere $\neq$ concentration); shared scale 0-0.6

Figure A1: Where concentration lives in the network. Mean attention to pos0 for each of the 270 (layer, query-head) pairs through training, row-normalized; seed 0 for every arm, run to each arm's final checkpoint (174M tokens baseline, 103M g1gate, 102M sigmoid, 60M textinit, 1B RF). baseline and RF stay cold throughout. textinit is hot from initialization. sigmoid lights up a band of mid-network layers.

No universal coupling: the concentration-value-norm sign is arm-dependent




Figure A2: No consistent-sign head-level relationship. Concentration against value-norm ratio for each (layer, KV-group) pair at each arm's final checkpoint, seed 0, at $n = 90$ pairs per arm. Grouping this way avoids triplicating each value-norm observation across the 3 query heads that share it, so these correlations are descriptive and we report no p-values (§3.3). The sign of the correlation flips by arm, from +0.76 in baseline to -0.79 in textinit (Table 3). The pooled cloud is weak, at -0.20, only because arms of opposite sign cancel. Do not read it as an uncorrelated cloud. Most individual arms show a strong $|r|$.




Figure A3: Entropy collapse tracks concentration only. Mean attention entropy through training, seed 0, to each arm's final checkpoint. Only sigmoid and textinit collapse. baseline, g1gate, and RF stay flat. The entropy-collapse correlate from the text-LM literature therefore follows the concentration axis, not the norm axes.

B. Full per-seed signature table

This table gives the per-seed values behind the collapsed ranges of Table 1, and adds the maximum attention→pos0 where we have it. We logged that metric for seeds 1 and 2 only, because the seed-0 archive summary does not include it. We trust the seed-0 values from a checksummed archive rather than re-derive them first-hand (§5). Each arm is read at its final matched checkpoint. All three signatures of *textinit* have plateaued at 60M tokens, and its h-ratio changes by less than 10% from 60M to 100M in the seeds that continued.

arm	seed	tokens	Sink ^{0.2} ₁	mean attn→pos0	max attn→pos0	v-ratio	h-ratio
baseline	s0	101M	0.000	0.068	—	0.723	2.16
baseline	s1	100M	0.000	0.062	—	0.687	1.71
g1gate	s0	101M	0.004	0.068	—	0.805	1.67
g1gate	s1	100M	0.011	0.073	~0.21	0.845	2.04
g1gate	s2	100M	0.0037	0.072	~0.22	0.854	2.24
sigmoid	s0	102M	0.830	0.377	—	1.479	1.10
sigmoid	s1	100M	0.756	0.311	—	1.603	1.30
textinit	s0	60M	0.852	0.627	—	0.377	42.5
textinit	s1	60M	0.556	0.235	~0.53	0.634	5.50
textinit	s2	60M	0.578	0.232	~0.59	0.484	12.2

baseline and *sigmoid* are tight across both of their seeds. *textinit* is the loose arm: seed 0 sits far above the other two on every signature at once, at Sink 0.85 against 0.56–0.58, mean attn→pos0 0.63 against 0.23, and h-ratio 42.5 against 5.5–12.2. The h-ratio has plateaued by 60–100M tokens in both lower seeds, so the spread is genuine seed sensitivity rather than an unconverged transient. Part of it is positional (Appendix C.2).

A note on g1gate. Both seeds with max-attention data show one head at about 0.21–0.22 maximum attention→pos0. That single head does clear the strict $\epsilon = 0.2$ threshold, which is why the arm’s Sink^{0.2}₁ is small but not exactly zero, and no head comes close to the $\epsilon = 0.3$ default of [6]. The arm mean meanwhile stays near 0.07 and Sink^{0.2}₁ stays far below 0.05. That pattern repeats across seeds.

C. Per-position attention mass (seed 0)

This table gives the mean and max-head attention mass by position at seed 0. It confirms that position 0 is the maximum-mass token in every arm, by mass rather than by argmax count alone. It is the direct check behind the position-0 anchoring defense of §5.

arm	mass@pos0 (mean)	max-head@pos0	argmax-mass position	reading
baseline	0.06	0.17	0	pos0 max; diffuse (no sink)
g1gate	0.07	0.23	0	pos0 max; diffuse
sigmoid	0.30	0.66	0	pos0 max; broad raw-sigmoid mass
textinit	0.63	0.99	0	pos0 max; razor spike (pos1 = 0.009)

C.2 Per-position scan at the remaining seeds, and for RF

We re-dumped per-position attention mass at the other seeds and for RF, and per-position residual and value norms for all three *textinit* seeds. The table gives the position at which each quantity peaks (for value norms, the position at which the norm is smallest).

run	seed	attention-mass argmax	residual-norm peak	value-norm minimum	reading
baseline	s0, s1	0	—	—	pos0 max
g1gate	s0, s1, s2	0	—	—	pos0 max
sigmoid	s0, s1	0	—	—	pos0 max
textinit	s0	0	0	0	all three coincide
textinit	s1	0	1	5	norms move off pos0
textinit	s2	1	13	13	attention separates from coincident norm extrema
RF	s0	1	—	—	mass 0.100 vs 0.083 at pos0; diffuse, not a sink

Two readings follow. Position 0 remains the maximum-mass token in every arm with a randomly initialized decoder, so the pos0 anchoring holds where the central negative result lives. In *textinit* the three signatures need not share a token, which is the positional dissociation reported in §3.4 and the reason the pos0-anchored textinit magnitudes at seeds 1 and 2 understate that arm’s peaks.

D. Measurement and rendering details

Figure 1 smoothing. Paths are smoothed with a moving average, 5 points on the horizontal axis and 9 on the vertical. The faint dots behind each path are the unsmoothed per-probe values, and the initialization and final markers use raw values.

Correlations at the uncollapsed 270 pairs. Table 3 collapses to the 90 (layer, KV-group) observations. At the uncollapsed 270 (layer, query-head) pairs the same quantities read +0.67 for baseline, +0.53 for g1gate, −0.03 for sigmoid, −0.76 for textinit, and +0.43 for RF. Every sign and every ordering survives the collapse.

Raw against row-normalized sigmoid attention. Row-normalization changes the object being measured, and Gu et al. [6] state their result for *unnormalized* sigmoid attention. Head L7H3 of the sigmoid arm sends 0.873 of its row-normalized attention to position 0 at the final checkpoint, which is the arm maximum. Its raw gate mass to position 0 is 0.065, and the raw mass summed over all keys in that row is 0.110. The row does not sum to one, and pos0 takes about 59% of what little gate mass the head opens at all. Early in training the same head shows the opposite picture: raw pos0 mass 0.309 against a raw row sum of 6.44, so under 5% of a very large gate budget. The concentration this arm develops is therefore a relative reallocation of a shrinking gate budget onto position 0, not the growth of a large absolute mass there (§3.4). Raw and row-normalized values here come from the same fixed probe batch as every other number in this paper, masked to valid query positions.

Sigmoid heat-map provenance. The sigmoid column of Figure 3 uses head L7H3 (0-indexed), the arm’s top sink head on the fixed probe batch. An earlier dump selected heads by raw, unnormalized gate score, picked different heads, and understated the arm. The sigmoid heat maps are re-rendered from an auxiliary streaming batch, because the saved matrices covered the superseded heads. Every printed sigmoid number, in the text and in the tables, comes from the fixed probe batch. The pos0 share printed on each panel is computed over valid query positions, the same convention as the tables.

E. Interpretation (untested hypotheses)

This appendix is **speculative**. Nothing in it is tested by our experiments, and none of it is a claim of this paper. We include it because a reader is entitled to ask *why* the signatures come apart, and because these hypotheses are cheap to state and testable later.

Gu et al. [6] account for the sink as a key bias: softmax must distribute a full unit of attention mass per row, and a head with nothing informative to retrieve parks the surplus on a token whose value contributes little. If that account is right, each of our levers touches a different part of it, which would explain why each moves a different axis.

- *g1gate*. An output gate can suppress whatever the attended position injects into the residual stream. A model with that gate may be able to *afford* concentration, because concentration no longer forces a matching change in the value path. That would be consistent with a gate whose measured effect here is on the value-norm axis rather than the concentration axis. Fesser et al. [23] make a compatible argument from another direction: they distinguish a sink that acts as an “adaptive nop” (a no-op: the head suppresses its own update by routing attention to a token whose value contributes nothing), recognizable by a negligible value norm, from a sink that broadcasts global information, and they note that gating implicitly assumes the nop mechanism. If that is right, a gate should act on the value-norm axis first, which is where our gated arm differs from baseline.
- *sigmoid*. Removing the softmax removes the sum-to-one constraint itself. A head with nothing to retrieve can simply attend weakly to everything, with no surplus to park. On this reading the value amplification we observe is what the value path does when it is no longer compensating for a forced allocation.
- *textinit*. A pretrained text decoder arrives with sink machinery already built. Our observation that its norm signatures are present at step 0 while concentration crosses later would then reflect import of structure followed by re-targeting onto a visual prefix, rather than formation from scratch.

Each of these is a hypothesis about mechanism. Testing them needs interventions we did not run: gate-scale sweeps that separate gating from the half-scale confound of §2, sigmoid runs at matched effective attention temperature, and text-initialized runs with the sink machinery ablated before alignment.

F. Reporting details

Token accounting: one token is one image token or one non-padding text token. A full sequence contributes 49 image tokens plus its non-padding text tokens, so a step of batch 128 contributes at most 16,384 tokens and about 9.5K on average. All “M tokens” figures in this paper use that definition.

Probe batch: the fixed probe batch holds $n = 32$ samples, drawn with `random.seed(0)` from the repeated `the_cauldron` tail. We label this probe version `v1-repeatedtail-32`. RF uses the same probe batch as the repeated arms, so its signatures stay comparable to theirs even though its training stream differs (§5).

Validation: a 1,024-example held-out pool, evaluated every 500 steps. Each estimate is the mean over the first 512 examples of that pool, in four batches of 128 in fixed order. We report `val_unseen`, which holds out images. For the repeated arms we also log `val_seen`, which re-uses training images with fresh question–answer text. The RF run has no distinct seen split: at 2.39 visual epochs its `val_seen` loader re-uses the held-out pool, so we report only `val_unseen` for RF. The seed-0 archive values for the matched 100M-token checkpoint are 1.161 for *baseline*, 1.138 for *g1gate*, 1.108 for *sigmoid*, and 0.832 for *textinit*; the main-text values are seed 1 or 2. For RF the held-out loss goes from 1.35 over the first ten evaluations to 0.68 over the last ten, and the fitted slope over the second half of the run stays negative.

Aggregation: each per-layer or per-head quantity is first averaged over the probe batch and over valid query positions, then aggregated by the formulas of §2.

G. Notes on metric hygiene

We record two corrections that we made during the audit of the numbers in this paper. First, an earlier internal consolidation mixed two metrics in one column, mean and max attention→pos0, and thereby manufactured an apparent seed anomaly in *g1gate*. Re-derived like-for-like, the anomaly disappears, and *g1gate* becomes the most reproducible arm. Second, an earlier draft claimed that the residual-norm peak of *textinit* “stays pinned at pos0.” We checked that claim against the norm dump. It is wrong. The $\|h\|$ peak sits at pos0, pos1 or pos13, depending on the seed (Appendix C.2). That is the positional dissociation reported in §3.4, which states the corrected form.