
Attention-Sink Signatures Dissociate During Vision–Language Pretraining

Anonymous Author(s)

Affiliation

Address

email

Abstract

1 Attention sinks, token positions that draw heavy attention while contributing little, are a widely
2 studied target of interventions in language models and are often linked, though not causally,
3 to hallucinations in vision-language models. A sink is defined by attention concentration
4 (Sink_1^c), but in text LMs it reliably arrives with two companions: a drained value norm (v-ratio)
5 and massive activations (h-ratio) at the same position. We measure these three signatures
6 during multimodal pretraining: a 222M vision-language model with a randomly initialized
7 decoder, position 0 being an image token, no BOS, trained under four levers: softmax attention,
8 output-gated softmax, unnormalized sigmoid attention, and initialization from a pretrained text
9 LM. We find that the signatures come apart, across 2-3 seeds, depending on which train-time
10 lever was applied. Most notably: on a 1B fresh-token run (2.39 effective visual epochs, single
11 seed), the massive-activation proxy more than doubles while attention concentration stays at
12 exactly zero at every threshold we test. Value-norm drain emerges as a third axis, apart from
13 the massive-activation vs. sink dissociations known from text-only models.

14 1 Introduction

15 Decoder-only transformers pick up a habit early in training. A large share of attention goes to the
16 first token or tokens of a sequence, whatever they contain. Streaming inference depends on that habit
17 [1], the activation outliers that ride along with it make quantization harder [2], and a survey now
18 organizes a subfield around interpreting and removing it [3].

19 The sink does not arrive alone. Three measurements move together in text language models. Attention
20 concentrates on the sink token. The value vector there drops to a near-zero norm, called value-state
21 drain [4]. The residual stream there grows an abnormally large norm, called a massive activation
22 [2, 5]. These effects settle on the same few tokens [6] and appear near step 1000 [7], and the field
23 reads the co-occurrence as permission to treat all three as facets of one attention-sink phenomenon.

24 Whether they really are one phenomenon is contested. One line argues for causal unity: massive
25 activations mathematically require representational compression, and ablating them removes both
26 compression valleys and sink formation [7], while a related view holds that outlier-driven rescaling
27 by attention and residual sinks is essential to stable training [8]. Two recent text-only studies pull the
28 other way, each separating one pair of the signatures, by normalization scheme [9] or by value scale
29 [10]. Neither separates all three.

30 Which signature a study measures decides what it can conclude. If the three move independently,
31 a lever that clears concentration while leaving the value path alone reads as a fix under one metric
32 and a failure under the next, and two papers can disagree while both are right. Sink-like attention
33 has also been tied to hallucination and weak visual grounding in deployed vision–language models
34 [13, 14, 15, 16], so a mitigation credited with removing the sink may leave the signature that mattered
35 untouched. We measure all three at once, throughout training, and test no downstream behavior.

Vision–language models suit the question, because the multimodal setting changes what position 0 is. Our sequence starts with 49 image tokens and has no BOS token, so the candidate sink token is a visual token, without the special-token machinery that text-LM sink accounts lean on. The multimodal sink studies we know analyze mostly frozen, already-trained backbones at inference time [11, 12], and the one training-time view follows a single magnitude rather than three signatures (§2). Telling whether the signatures arrive together, in sequence, or independently takes a randomly initialized decoder with all three logged separately from step 0.

We work at small scale by choice. The model is a 222M-parameter nanoVLM [17] with a pretrained SigLIP-B/16 encoder [18] and a randomly initialized decoder of the SmoLLM2-135M architecture [19], trained under four levers that each target one sink-relevant mechanism (§3): softmax attention (*baseline*), a zero-initialized Qiu-style G1 output gate [20] (*gate*), unnormalized sigmoid attention, which removes the normalization sinks are argued to come from [6] (*sigmoid*), and initialization from the pretrained SmoLLM2 text model (*textinit*). A validated probe logs all three signatures every 100 steps. Because the four-arm comparison reuses a small image pool, we re-test the central negative result on a fresh stream of one billion tokens (*RF*, 2.39 effective visual epochs).

Contributions Decoupling itself is not new [9, 10] and we do not claim it. What is new is the conjunction. We track all three signatures jointly, from step 0, under randomly initialized decoders in a multimodal model, and add value-norm drain as a third axis. Across four levers ($n = 2\text{--}3$ seeds per arm) the arms reach four different corners of the three-signature space, no two sharing a triple, and the value-norm ratio alone is strongly drained, mildly drained or amplified depending on the lever (Fig. 1, Table 1). The arms are not a factorial design, so these are intervention-associated profiles rather than isolated causal effects. Two observations carry the most weight.

- *Low-repetition decoupling at 1B tokens ($n = 1$).* On a fresh stream at 2.39 effective visual epochs, with training healthy throughout (§3), the massive-activation proxy rises from an h-ratio of 1.43 to 3.22, about $2.3\times$, while concentration stays at exactly zero and no head ever crosses the sink threshold (§4.2, §5).
- *No consistent-sign head-level relationship.* The per-head correlation between concentration and value-norm flips sign across arms at seed 0, $+0.76$ in baseline to -0.79 in textinit with a pooled -0.20 , over 90 KV groups per arm, reported descriptively (§4.3).

2 Related work

Sinks and their companions in text language models Gu et al. [6] give the canonical account. The sink token acts “more like key biases, storing extra attention scores,” carries small key and value norms, and connects to massive residual-stream activations [2, 5]. They also show that unnormalized sigmoid attention prevents sink formation in text models up to 1B parameters, which our *sigmoid* arm builds on. Guo et al. [4] call the concentration and value-drain coupling “active-dormant” heads. Queipo-de-Llano, Arroyo et al. [7] make the strongest unity claim, and the only causal one. Ablating a model’s layer-0 massive activation removes both compression valleys and sink formation (§1). We reserve “causally unified” for that result. Peng et al. [24] trace a first-position sink circuit emerging early in from-scratch text pretraining, without separating the signatures.

Prior decoupling results, text-only, two axes Two papers already separate pairs of these signatures, and we scope our claim around them. Sun, Canziani, LeCun and Zhu [9] show that a change of normalization scheme crushes the massive-activation spike while the sink ratio survives. Chen and Yao [10] go the other way, from scratch. A value-scale intervention in 0.1–0.3B text models keeps the sinks and suppresses massive activations. Neither treats value-norm drain as a third axis, and neither is multimodal. Fesser et al. [23] give the closest support for tracking the value norm separately. One sink pattern can hide an “adaptive nop” with negligible value norms or a “broadcast” that redistributes global information, though that work diagnoses trained vision transformers rather than tracking emergence. Qiu et al. [8] argue the opposite case, that outlier-driven rescaling by attention and residual sinks is essential to stable training. The field has settled neither question.

Multimodal sinks, mostly frozen backbones at inference time Luo et al. [11] separate ViT-propagated from LLM-emerged sinks. Their Appendix A.4 tracks sink-dimension magnitudes across alignment checkpoints, so a training-time view has precedent, but on a frozen vision transformer

with a pretrained language model, following one magnitude rather than three signatures. Choi et al. [12] likewise distinguish vision-sinks from language-sinks in a frozen model and gate them by layer. Both establish distinct vision-side and language-side origins, which our *textinit* inheritance result fits. Neither gives dense, joint tracking of the three quantities in a decoder that starts from random weights. Vision transformers also grow high-norm “register” tokens of their own [25], hence the pretrained-encoder limitation in §5. A separate line ties these signatures to hallucination and grounding failure in deployed models and intervenes at inference time [13, 14, 15, 16], the practical reason it matters which signature a mitigation moves.

The gating lever Qiu et al. [20] introduce the head-specific elementwise sigmoid gate on attention output that our *g1gate* arm adapts. In text models it “largely reduces the attention score allocated to the first token and decreases massive activations” while improving quality. Our zero-initialized variant confounds gating with initial output scaling (§3, §5). With that caveat, concentration is already absent in our baseline, so the gated arm differs on the value-norm axis (the v-ratio of §3). The drain becomes milder, 0.69–0.72 to 0.81–0.85, rather than disappearing, a difference invisible unless the three signatures are logged separately.

Positioning The closest prior work separates at most two of the three axes, in text-only models, and the multimodal studies work on frozen ones. Our claim is the conjunction. We track concentration, value-norm drain and the residual-norm ratio jointly and separately in multimodal pretraining with a randomly initialized decoder, which adds value-norm drain as a third axis beyond the text-only dissociations [9, 10].

3 Setup

3.1 Model and arms

All runs use a 222M-parameter nanoVLM [17]. A pretrained, trainable SigLIP-B/16 vision encoder [18] feeds a decoder with the SmolLM2-135M architecture [19] through a learned projector. The decoder has 30 layers of grouped-query attention, 9 query heads per layer sharing 3 KV heads, so there are 270 (layer, query-head) pairs but only 90 (layer, KV-group) value projections. §4.3 depends on that distinction. Each sequence is 49 image tokens as a causal prefix followed by 79 left-padded text tokens, 128 in all. There is no BOS token, so **position 0 is the first image token**.

Four training levers each target one sink-relevant mechanism. Everything else stays byte-identical across arms.

arm	attention	LM init	ViT init	lever precedent
<i>baseline</i>	softmax	random	pretrained	—
<i>g1gate</i>	softmax + elementwise σ -gate (zero-init, post-SDPA)	random	pretrained	G1 gating [20]
<i>sigmoid</i>	unnormalized softmax, no sigmoid	random	pretrained	Gu et al. [6]
<i>textinit</i>	softmax	pretrained SmolLM2-135M	pretrained	— (novel control)

The decoder starts from random weights in every arm except *textinit*, which loads the pretrained SmolLM2 decoder and imports whatever first-position structure text pretraining built into it (§4.1). *g1gate* and *sigmoid* have established sink effects in text-only models [20, 6]. *sigmoid* also tests the standard account of why a sink forms: softmax makes every attention row sum to one, so a head with nothing to retrieve must park its mass somewhere [6]. One caveat on the gate. Unlike Qiu et al. [20], we initialize it at exactly zero, so it opens at $\sigma(0) = 0.5$ and the arm starts as a half-scale output intervention as well as a gated one. We write “Qiu-style G1 in our zero-initialized variant” throughout (§5).

3.2 Data and the two training regimes

The four-arm comparison trains on four curated subsets of the_cauldron [21], about 146K images, matched at about 100M tokens per arm. *textinit* stops at 60M, where its signatures have plateaued (§4.1). *baseline* and *sigmoid* have two seeds, *g1gate* and *textinit* three. The optimizer is AdamW with

weight decay 0.1, following [6], gradient clip 1.0 and a cosine schedule with 3% warmup (Appendix A).

Reusing a 146K-image pool for 100M tokens means high visual-epoch counts. The RF arm (random-fresh) answers that objection. It re-trains the *baseline* recipe on a fresh FineVision stream [22] to 1B tokens over about 4.6M natural images, at 2.39 effective visual epochs. That is a low-repetition run rather than a repetition-free one, since examples repeat about 2.4 times on average. We estimate the overlap between the fresh pool and the repeated subsets at under 3%, from config-level composition rather than image-level deduplication. RF has one seed. Swapping datasets trades the repetition confound for a domain-shift confound (§5).

Training stays healthy in every reported run (held-out losses in Appendix A). Two cautions. The lower *textinit* loss reflects its pretrained decoder, not the lever, so only *baseline*, *glgate* and *sigmoid* are equal-token, equal-initialization comparisons. And the repeated-data arms show a large train-validation gap (*val_seen* near 0.44 against *val_unseen* near 1.18), the overfitting signal that motivates RF. RF has no seen split. Its held-out loss ends at 0.638 with a negative fitted slope over the second half, individual evaluations fluctuating (§5). We did not run MMStar or any other downstream benchmark on any arm, so this paper makes no capability claim.

3.3 Three signatures, tracked separately

We log the three sink symptoms the text-LM literature reports together, each at its own granularity, following Gu et al. [6] at fixed sequence length. Every quantity below is averaged over valid query positions and over a fixed probe batch.

Concentration ($\text{Sink}_\epsilon^\dagger$) is the fraction of the 270 (layer, query-head) pairs whose mean attention to position 0 exceeds ϵ . We use the $\epsilon = 0.3$ default of [6] and check $\epsilon \in \{0.2, 0.4\}$. Cross-arm tables report the stricter $\epsilon = 0.2$, which makes an absence claim harder to pass.

Value-norm ratio (v-ratio) is the value norm at position 0 divided by the mean value norm over the other valid positions, per layer and averaged over the 30 layers. Below 1 is value-drain [4], above 1 amplification. A value vector belongs to a KV group and is shared by 3 query heads, so the ratio rests on 90 distinct value projections, not 270 (§4.3).

Residual-norm ratio (h-ratio) is the residual-stream norm at position 0 divided by the mean norm over the other positions, per layer and averaged over the 30 layers. We call it a massive-activation proxy. The literature defines massive activations by channel-level outliers [2, 5], which we never measured (§5).

All three anchor on position 0 by construction, and we check that choice. At seed 0, per-position attention mass makes position 0 the maximum-mass token in every arm (Appendix E), and §5 covers the seed-level exception. The *sigmoid* arm reports the row-normalized attention view, which keeps concentration comparable across arms, and we also log the raw sigmoid mass (Appendix F).

A probe recomputes all three from the live weights every 100 optimizer steps, on the same 32-sample batch for every run and seed, and validates itself against the real forward pass on every call (Appendix A).

4 Results

4.1 Four training levers reach four different signature corners

Table 1 collapses the seeds into per-arm ranges, each arm at its final matched checkpoint, about 100M tokens or 60M for *textinit*, whose signatures have plateaued by then (per-seed table in Appendix D). No two arms share a signature triple.

The value-norm axis alone takes three directions, drained hard, drained mildly and amplified, and the corners separate pairwise on single axes. *glgate* differs from *baseline* on the value-norm axis alone: concentration absent or near-absent and the residual-norm ratio moderate in both, while the gate makes the mild drain milder still, a 15–19% drain rather than none. *sigmoid* and *textinit* both reach strong concentration and then part on the direction of the value-norm move and on the residual-norm ratio. The *sigmoid* corner is relative, since its concentration is row-normalized over a shrinking raw gate budget, with top-head raw pos0 mass 0.065 at the final checkpoint (Appendix F). The arms are




Figure 1: **Decoupling phase-portrait.** Every arm in concentration-against-value-norm space (left) and against the residual-norm ratio (right, log scale). Circles mark initialization, diamonds the final checkpoint (about 100M tokens, 60M for *textinit*, 1B for *RF*), seed 0 unless labelled. The horizontal axis is the *maximum* attention→pos0 over heads, not Table 1’s fraction above threshold, so an arm can sit off zero here with $\text{Sink}^\epsilon = 0.000$. Paths smoothed, end markers raw (Appendix F). Were the three signatures one phenomenon, these trajectories would move along one direction.

Table 1: **The four corners (n = 2–3 seeds per arm).** Concentration is $\text{Sink}_1^{0.2}$, the fraction of the 270 (layer, query-head) pairs whose mean attention→pos0 exceeds 0.2. The v-ratio rests on 90 (layer, KV-group) value projections and the h-ratio on 30 layers (§3).

arm	concentration	value-norm	massive-activation proxy
baseline	absent (0.000)	mild drain (0.69–0.72)	moderate (1.7–2.2)
g1gate	near-absent (0.004–0.011)	milder drain (0.81–0.85)	moderate (1.7–2.2)
sigmoid	strong (0.76–0.83)	amplified (1.48–1.60)	no strong asymmetry (1.1–1.3)
textinit	strong (0.56–0.85)	strong drain (0.38–0.63)	extreme (5.5–42.5)

181 not a factorial design, so these are intervention-associated profiles rather than isolated causal effects.
 182 The trajectories in Figure 1 separate early and do not share one origin. *textinit* starts from a pretrained
 183 decoder that already carries a subthreshold first-position bias, $\text{Sink}_1^{0.3}$ still 0.000 at step 0.

184 Reproducibility differs by arm. *g1gate* is tightest, $\text{Sink}_1^{0.2}$ of 0.004, 0.011 and 0.0037 across three
 185 seeds. The *textinit* corner repeats across seeds and its magnitudes do not: seed 0 sits far above
 186 the other two on every signature, h-ratio 42.5 against 5.5–12.2, partly because at seeds 1 and 2
 187 its peaks move off position 0, where our metrics anchor (Appendix D, I). We therefore report its
 188 massive-activation proxy as a range, 5.5–42.5 $\times$ with a median near 12 $\times$, and treat the corner rather
 189 than any magnitude as the claim.

190 The corners also separate in time (Fig. A4, seed 0, Appendix I). *baseline*, *g1gate* and *RF* cross
 191 the norm thresholds without ever crossing concentration. *sigmoid* is the mirror image, crossing
 192 concentration without either norm threshold. *textinit* starts above both norm thresholds and crosses
 193 concentration later. Where a run crosses both kinds, the norm signatures come first, and under text
 194 initialization the three need not even settle on the same token (Appendix I). Appendix G offers
 195 untested hypotheses for why each lever moves a different axis. Figure 2 shows the separation inside a
 196 single head. Its rightmost panel carries the most weight: the *textinit* stripe is already there at step 0,
 197 imported with the text-LM weights before the model has seen one image.




Figure 2: **The sink stripe.** Query $\times$ key attention of each arm’s top sink head, row-normalized, seed 0. Top row is early training (step 250, about 2.4M tokens), bottom row the final checkpoint. The cyan line marks key = pos0, the dotted line the image-to-text boundary. The stripe is absent in baseline throughout, strong in textinit (attn $\rightarrow$ pos0 = 0.62 at its final checkpoint), and already present at step 0 in textinit (rightmost panel), inherited from the text LM. The sigmoid heat maps come from an auxiliary streaming batch, while every printed sigmoid number comes from the fixed probe batch (Appendix F).

Table 2: **RF (fresh stream, n = 1 seed), init $\rightarrow$ 1B tokens.**

signature	@ init	@ 1B	net
Sink ₁ ^{0.3} (concentration)	0.000	0.000	flat zero, entire run
max attn $\rightarrow$ pos0	0.056	0.098	$\approx$ flat, far below threshold
h-ratio (massive-activation proxy)	1.43	3.22	$\approx$ 2.3 $\times$, positive long-horizon trend
v-ratio (value-norm)	1.00	0.69	net drain, non-monotone

4.2 The proxy grows across 1B low-repetition tokens with concentration at zero

The four-arm comparison reuses a 146K-image pool, so its “concentration never emerges” result could be an overfitting artifact. The RF arm answers that with the identical *baseline* recipe on a fresh FineVision stream to one billion tokens at 2.39 effective visual epochs, low repetition rather than none, with a held-out loss that ends at 0.638 on a negative fitted slope over the second half while individual evaluations fluctuate (§3, §5). Concentration never arrives. Sink₁^{0.3} = **0.000 across the entire 0 $\rightarrow$ 1B run**, and no head of the 270 crosses the threshold at any of about 700 probes.

Warmup does not explain the rise. The h-ratio climbs from 2.40 at about 57M tokens to 3.22 at 1B, long after the 3% warmup window closes, though not monotonically at probe resolution, hence a positive long-horizon trend. In Figure 1, right, the violet trajectory climbs and never moves rightward. The v-ratio ends below its initialization value, but about 75% of that drop happens in the first 57M tokens and part then recovers, so it is supporting context rather than ongoing emergence.

4.3 No consistent-sign head-level concentration–value-norm relationship

A tight coupling between concentration and value-drain should at least hold the sign of their per-head correlation constant across regimes. It does not. Table 3 gives the Pearson r between attention $\rightarrow$ pos0 and value-norm ratio at each arm’s final checkpoint, seed 0, over the 90 (layer, KV-group) observations, averaging a group’s query-head attention rather than triplicating its value observation (§3, scatter in Fig. A2, Appendix C).

Table 3: $R(\text{attn} \rightarrow \text{pos0}, \text{v-ratio})$, final checkpoint, seed 0.

baseline	g1gate	sigmoid	textinit	RF	pooled
+0.76	+0.57	−0.03	−0.79	+0.51	−0.20

These correlations are descriptive, not inferential. Heads within a layer are not independent and each arm rests on a single seed here, so a p-value would mislead and we report none. Collapsing to the 90 KV groups removes the pseudoreplication a per-query-head reading would introduce, and the picture does not change (Appendix F). The pattern is about sign, which pseudoreplication does not manufacture. Heads attending more to position 0 have larger value norms in the baseline regime and smaller ones under text initialization, and the pooled correlation is weak only because arms of opposite sign cancel. We claim that no consistent-sign relationship holds across arms, not that no coupling law exists. A fixed coupling would show one sign everywhere, and it does not.

5 Discussion and limitations

Across the arms the three signatures land in different corners, and no single one predicts the others. For VLM work the consequence is direct. An intervention judged on concentration alone can leave value-norm drain or the residual-norm ratio where they were, and a model with no concentration sink can still grow a residual-norm asymmetry, as RF does. What that licenses depends on the limits below. Appendix B gives the full account of each.

The h-ratio is a proxy. The literature defines massive activations by channel-level outliers [2, 5]. We measured a position-specific residual-norm ratio and never computed channel-level statistics (§3). A large h-ratio is consistent with massive activations without establishing them.

RF is one seed and one run. The 1B-token result rests on a single seed with one weights-only optimizer restart at about 57M tokens, the weights reloaded and the AdamW moments discarded. The audit verified continuity across that seam (Appendix B). Concentration was reproducibly zero across both repeated-data baseline seeds, which supports the negative claim, and a second fresh-data seed would strengthen it. RF also has no seen split, and it buys low repetition by changing dataset, so it trades the repetition confound for a domain-shift one. The under-3% overlap figure is config-level, not image-level.

The gate arm carries a scale confound. Zero-initializing the G1 gate opens it at $\sigma(0) = 0.5$ and halves attention output at step 0, where Qiu et al. [20] use ordinary initialization. Gating and initial output scaling are confounded in *g1gate*, and a scale-matched control is future work.

No arm is fully from scratch, and the metrics anchor on position 0. The SigLIP encoder is pretrained in every arm, and vision transformers grow high-norm tokens of their own [25], so part of the residual-norm signal could be inherited. Our defense is the trajectory. The h-ratio starts at 1.0–1.4 and rises to 3.22 across 1B tokens in RF, where a static inherited source predicts a high, flat value from step 0. Position 0 is the maximum-mass token in every arm at seed 0 and at every seed for the random-decoder arms, but not for *textinit* at seeds 1 and 2, where the peaks move (Appendix E). Those magnitudes understate the arm’s peaks, so we report *textinit* as a corner and a range, 5.5–42.5 $\times$, and not as a magnitude.

Scale and scope. Runs reach at most 1B tokens against roughly 5B canonical in the text-LM sink literature [6]. Text-LM sinks form near step 1000 [7], well inside our range, but a signature absent at 1B could still emerge later. The seed-0 probes for the four-arm comparison come from a checksummed archive summary, and seeds 1 and 2 were re-derived first-hand (Appendix B.5, Appendix H). We ran no downstream benchmark on any arm and make no capability claim.

6 Conclusion

The coupling is lever-dependent. Across four training levers, the three signatures land in four distinct corners: value norms are strongly drained, mildly drained, or amplified, and on a billion fresh tokens the massive-activation proxy more than doubles while concentration stays at zero. This extends two-way dissociations in text-only models [9, 10] to a third, separately measured axis in multimodal

261 pretraining. In text LMs, massive activations can causally produce sinks [7]; our results show the
262 coupling can also fail to form.

263 The practical implication is simple: across our arms, no one signature was a proxy for the others. A
264 model without a concentration sink can still develop a growing residual-norm asymmetry, and an
265 intervention judged on one signature may leave the others unchanged.

266 **Next steps** A randomly initialized vision encoder, to isolate what the decoder contributes to the
267 residual-norm signal. A fresh-data run past 1B tokens. A scale-matched gate control, to separate
268 gating from the half-scale confound of §3.

269 **Reproducibility** A self-validating probe (§3) computes all signatures on a fixed probe batch, from
270 logs taken every 100 steps, and the Appendix holds the per-seed tables. We will release the code,
271 the probe, the run configurations, the per-run logs, and the training checkpoints on acceptance. We
272 withhold the links for double-blind review.

273 References

- 274 [1] G. Xiao, Y. Tian, B. Chen, S. Han, M. Lewis. *Efficient Streaming Language Models with Attention Sinks*.
275 ICLR 2024. arXiv:2309.17453.
- 276 [2] M. Sun, X. Chen, J. Z. Kolter, Z. Liu. *Massive Activations in Large Language Models*. COLM 2024.
277 arXiv:2402.17762.
- 278 [3] Z. Su et al. *Attention Sink in Transformers: A Survey on Utilization, Interpretation, and Mitigation*.
279 arXiv:2604.10098, 2026.
- 280 [4] T. Guo, D. Pai, Y. Bai, J. Jiao, M. I. Jordan, S. Mei. *Active-Dormant Attention Heads: Mechanistically*
281 *Demystifying Extreme-Token Phenomena in LLMs*. CPAL 2025. arXiv:2410.13835.
- 282 [5] N. Cancedda. *Spectral Filters, Dark Signals, and Attention Sinks*. ACL 2024 (pp. 4792–4808).
283 arXiv:2402.09221.
- 284 [6] X. Gu, T. Pang, C. Du, Q. Liu, F. Zhang, C. Du, Y. Wang, M. Lin. *When Attention Sink Emerges in*
285 *Language Models: An Empirical View*. ICLR 2025. arXiv:2410.10781.
- 286 [7] N. Queipo-de-Llano, D. Arroyo, F. Barbero, Y. Dong, M. Bronstein, Y. LeCun, R. Shwartz-Ziv. *Attention*
287 *Sinks and Compression Valleys in LLMs are Two Sides of the Same Coin*. arXiv:2510.06477, 2025.
- 288 [8] Z. Qiu et al. *A Unified View of Attention and Residual Sinks: Outlier-Driven Rescaling is Essential for*
289 *Transformer Training*. arXiv:2601.22966, 2026.
- 290 [9] M. Sun, A. Canziani, Y. LeCun, C. Zhu. *The Spike, the Sparse and the Sink: Anatomy of Massive*
291 *Activations and Attention Sinks*. arXiv:2603.05498, 2026.
- 292 [10] Y. Chen, Z. Yao. *Attention Sinks Induce Gradient Sinks*. arXiv:2603.17771, 2026.
- 293 [11] Y. Luo et al. *To Sink or Not to Sink: Visual Information Pathways in LVLMs*. arXiv:2510.08510, 2025.
- 294 [12] J. Choi, J. Kim, S. Kim, S. Hong, J.-H. Park. *When Sinks Help or Hurt: Unified Framework for Attention*
295 *Sink in Large Vision-Language Models*. ECCV 2026. arXiv:2604.03316.
- 296 [13] S. Kang, J. Kim, J. Kim, S. J. Hwang. *See What You Are Told: Visual Attention Sink in Large Multimodal*
297 *Models*. ICLR 2025. arXiv:2503.03321.
- 298 [14] T. Shukla, Z. Kira. *SAGE: Sink-Aware Grounded Decoding for Multimodal Hallucination Mitigation*.
299 arXiv:2603.27898, 2026.
- 300 [15] X. Zhang, Y. Zhu, C. Gu, J. Cao, H. Cheng, K. Wu. *What Drives Attention Sinks? A Study of Massive*
301 *Activations and Rotational Positional Encoding in Large Vision–Language Models*. Information Processing
302 & Management, 63(2A), art. 104431, 2026. DOI 10.1016/j.ipm.2025.104431.
- 303 [16] J. Binkowski, K. Adamczewski, T. Kajdanowicz. *Attention Sinks as Internal Signals for Hallucination*
304 *Detection in Large Language Models*. arXiv:2604.10697, 2026.
- 305 [17] L. Wiedmann, A. Roy Gosthipaty, A. Marafioti. *nanoVLM*. GitHub repository, 2025.
306 <https://github.com/huggingface/nanoVLM>.

- 307 [18] X. Zhai, B. Mustafa, A. Kolesnikov, L. Beyer. *Sigmoid Loss for Language Image Pre-Training (SigLIP)*.
308 ICCV 2023. arXiv:2303.15343.
- 309 [19] L. Ben Allal et al. *SmolLM2: When Smol Goes Big — Data-Centric Training of a Small Language Model*.
310 arXiv:2502.02737, 2025.
- 311 [20] Z. Qiu et al. *Gated Attention for Large Language Models: Non-linearity, Sparsity, and Attention-Sink-Free*.
312 NeurIPS 2025. arXiv:2505.06708.
- 313 [21] H. Laurençon, L. Tronchon, M. Cord, V. Sanh. *What Matters When Building Vision-Language Models?*
314 (Idefics2 / The Cauldron). NeurIPS 2024. arXiv:2405.02246.
- 315 [22] L. Wiedmann, O. Zohar, A. Mahla, X. Wang, R. Li, T. Frere, L. von Werra, A. Roy Gosthipaty, A. Marafioti.
316 *FineVision: Open Data Is All You Need*. arXiv:2510.17269, 2025.
- 317 [23] L. Fesser, M. Jacobs, T. Fel, A. Keller, S. Kakade. *A Unifying View of Attention Sinks: Two Algorithms,*
318 *Two Solutions*. arXiv:2606.08105, 2026.
- 319 [24] R. Peng, R. Li, M. Chen, Y. Zhou, Q. Guo, X. Qiu. *How Attention Sinks Emerge in Large Language*
320 *Models: An Interpretability Perspective*. arXiv:2603.06591, 2026.
- 321 [25] T. Darcet, M. Oquab, J. Mairal, P. Bojanowski. *Vision Transformers Need Registers*. ICLR 2024.
322 arXiv:2309.16588.

A Extended methodology

Probe. The function `probe_sinks()` re-walks the decoder from the live module weights in eager mode, fp32, no gradients, independent of the training path (fused SDPA kernels, autocast, `torch.compile`). Every call validates its hidden states against the real forward pass to a relative error below 10^{-2} , so the probe cannot drift from what the trained model computes. The probe batch is fixed across all runs and seeds, which keeps every number comparable, and probes fire every 100 optimizer steps.

Recipe. AdamW with weight decay 0.1, following [6], gradient clip 1.0, cosine schedule with 3% warmup. Arms in a comparison differ only in the lever under test.

Optimization. The learning rates are 4×10^{-4} for the language model, 2×10^{-3} for the projector, and 10^{-4} for the vision encoder. We use bf16 autocast, `torch.compile`, and a batch size of 128.

Token accounting. One token is one image token or one non-padding text token. A full sequence contributes 49 image tokens plus its non-padding text tokens, so a step of batch 128 contributes at most 16,384 tokens and about 9.5K on average. All “M tokens” figures in this paper use that definition.

Probe batch. The fixed probe batch holds $n = 32$ samples, drawn with `random.seed(0)` from the repeated `the_cauldron` tail. We label this probe version `v1-repeatedtail-32`. RF uses the same probe batch as the repeated arms, so its signatures stay comparable to theirs even though its training stream differs (§5).

Validation. A 1,024-example held-out pool, evaluated every 500 steps. Each estimate is the mean over the first 512 examples of that pool, in four batches of 128 in fixed order. We report `val_unseen`, which holds out images. For the repeated arms we also log `val_seen`, which re-uses training images with fresh question–answer text. The RF run has no distinct seen split. At 2.39 visual epochs its `val_seen` loader re-uses the held-out pool, so we report only `val_unseen` for RF. At the matched 100M-token checkpoint the held-out losses are 1.182 for *baseline*, 1.133 for *g1gate*, 1.206 for *sigmoid* and 0.877 for *textinit*, and RF reaches 0.638 at 1B tokens. The seed-0 archive values for that checkpoint are 1.161 for *baseline*, 1.138 for *g1gate*, 1.108 for *sigmoid*, and 0.832 for *textinit*, so the first set is seed 1 or 2. For RF the held-out loss goes from 1.35 over the first ten evaluations to 0.68 over the last ten, and the fitted slope over the second half of the run stays negative.

LLM assistance. Large-language-model coding assistants were used to write and refactor the training, probe and analysis code, and to edit prose. The experimental design, the measurements, the analysis decisions and the claims are the authors’ own. The released repository keeps its commit history, including the assistant-authored commits.

Aggregation. Each per-layer or per-head quantity is first averaged over the probe batch and over valid query positions, then aggregated by the formulas of §3.

B Extended limitations

Section 5 states each limit in one paragraph. This appendix keeps the evidence behind each.

B.1 Metrics anchored on position 0

We measure all three signatures at the first image token, and check that anchor by per-position attention *mass* rather than *argmax* alone. Position 0 is the maximum-mass token in every arm at seed 0, and it stays so for *baseline*, *g1gate* and *sigmoid* at every seed we scanned. It does not in *textinit*, where at seeds 1 and 2 the peaks move to other positions (per-position table in Appendix E). The pos0-anchored *textinit* magnitudes at those seeds therefore understate its peaks, one more reason to treat that arm’s corner rather than its magnitudes as the claim. In *RF* the attention *argmax* sits at pos1, but with mass 0.053 against 0.044 at pos0, a diffuse profile rather than a displaced sink, so the RF result does not depend on the anchor.

369 B.2 The gate arm carries a scale confound

370 We initialize the G1 gate at exactly zero, so it opens at $\sigma(0) = 0.5$ and halves attention output at
371 step 0, where Qiu et al. [20] use ordinary initialization (§3). Gating and initial output scaling are
372 therefore confounded in *glgate*. We cannot attribute its differences from baseline to gating alone,
373 and a scale-matched control is future work.

374 B.3 Pretrained vision encoder

375 The SigLIP encoder is pretrained and trainable in every arm, and *textinit* also uses a pretrained
376 decoder. We study vision–language pretraining with randomly initialized decoders, not from-scratch
377 training of the whole model. Vision transformers grow high-norm register tokens of their own [25],
378 and sinks can propagate from a vision transformer into a vision–language model [11], so part of our
379 residual-norm signal could be inherited rather than decoder-formed. Our defense is the trajectory.
380 The h-ratio starts at 1.0–1.4 and rises to 3.22 across 1B tokens in RF, where inheritance from a static
381 encoder predicts a high, flat h-ratio from step 0. A randomly initialized vision transformer, which
382 would isolate the decoder, is future work.

383 B.4 Reproducibility of textinit magnitudes

384 The massive-activation proxy of *textinit* is seed-sensitive, an h-ratio of 5.5–42.5 across three seeds,
385 with seed 0 the outlier on every signature. The reproducible claim is the corner: strong concentration,
386 strong drain, large residual-norm ratio. No specific magnitude is.

387 B.5 Provenance and seed count

388 The seed-0 raw probes for the four-arm comparison come from a checksummed archive summary
389 rather than first-hand re-derivation. Seeds 1 and 2 we did re-derive independently, an audit that
390 caught a metric-labeling error in an earlier internal consolidation (Appendix H). *baseline* and *sigmoid*
391 have two seeds, *glgate* and *textinit* three, RF a single seed. RF also contains one weights-only
392 optimizer restart at about 57M tokens, forced by an out-of-memory error. We reloaded the weights
393 and discarded the AdamW moment estimates, so RF is not one uninterrupted optimizer trajectory.
394 The audit verified continuity across that seam: v-ratio and h-ratio identical at the shared checkpoint, a
395 double-covered 600-step overlap diverging only within probe noise, concentration 0.000 on both sides.
396 Concentration was reproducibly zero across both repeated-data baseline seeds, adequate support for
397 the negative claim, and a second fresh-data seed would strengthen it.

398 B.6 What the RF control does and does not establish

399 RF has no distinct seen split, so we cannot run for it the `val_seen / val_unseen` comparison
400 that exposes memorization in the repeated arms. The weaker statement its data supports is the
401 falling-slope statement of §3. Its streaming shuffle buffer dropped from 1500 to 500 examples
402 partway through, again for memory, so stream ordering is not homogeneous, though the $\text{Sink}_1^{0.3}$
403 = 0.000 result and the h-ratio rise hold within each regime separately. Its probe batch is still the
404 fixed repeated-the-cauldron tail used by the other arms. That keeps RF’s signatures comparable to
405 theirs, which is what the negative result needs, at the cost of measuring them on data from the other
406 distribution. And RF buys lower repetition by changing dataset, so it trades the repetition confound
407 for a domain-shift one, and we chose the fresh pool to minimize shift. The under-3% overlap figure is
408 config-level, not image-level (§3), and the third, domain-matched control we did not run is the known
409 follow-up.

410 C Supporting figures

411 D Full per-seed signature table

412 This table gives the per-seed values behind the collapsed ranges of Table 1, and adds the maximum
413 attention→pos0 where we have it. We logged that metric for seeds 1 and 2 only, because the seed-0
414 archive summary does not include it. We trust the seed-0 values from a checksummed archive rather

Where the concentration sink lives: per-(layer,head) attn→pos0 over training




Figure 3: **Where concentration lives in the network.** Mean attention to pos0 for each of the 270 (layer, query-head) pairs through training, row-normalized, seed 0 for every arm, run to each arm’s final checkpoint (174M tokens baseline, 103M g1gate, 102M sigmoid, 60M textinit, 1B RF). baseline and RF stay cold throughout. textinit is hot from initialization. sigmoid lights up a band of mid-network layers.

than re-derive them first-hand (§5). Each arm is read at its final matched checkpoint. All three signatures of *textinit* have plateaued at 60M tokens, and its h-ratio changes by less than 10% from 60M to 100M in the seeds that continued.

arm	seed	tokens	$\text{Sink}_1^{0.2}$	mean attn→pos0	max attn→pos0	v-ratio	h-ratio
baseline	s0	101M	0.000	0.068	—	0.723	2.16
baseline	s1	100M	0.000	0.062	—	0.687	1.71
g1gate	s0	101M	0.004	0.068	—	0.805	1.67
g1gate	s1	100M	0.011	0.073	~0.21	0.845	2.04
g1gate	s2	100M	0.0037	0.072	~0.22	0.854	2.24
sigmoid	s0	102M	0.830	0.377	—	1.479	1.10
sigmoid	s1	100M	0.756	0.311	—	1.603	1.30
textinit	s0	60M	0.852	0.627	—	0.377	42.5
textinit	s1	60M	0.556	0.235	~0.53	0.634	5.50
textinit	s2	60M	0.578	0.232	~0.59	0.484	12.2

baseline and *sigmoid* are tight across both of their seeds. *textinit* is the loose arm. Seed 0 sits far above the other two on every signature at once, at Sink 0.85 against 0.56–0.58, mean attn→pos0 0.63 against 0.23, and h-ratio 42.5 against 5.5–12.2. The h-ratio has plateaued by 60–100M tokens in both lower seeds, so the spread is genuine seed sensitivity rather than an unconverged transient. Part of it is positional (Appendix E.2).

No universal coupling: the concentration-value-norm sign is arm-dependent




Figure 4: **No consistent-sign head-level relationship.** Concentration against value-norm ratio for each (layer, KV-group) pair at each arm’s final checkpoint, seed 0, at $n = 90$ pairs per arm. Grouping this way avoids triplicating each value-norm observation across the 3 query heads that share it, so these correlations are descriptive and we report no p-values (§3.3). The sign of the correlation flips by arm, from +0.76 in baseline to −0.79 in textinit (Table 3). The pooled cloud is weak, at −0.20, only because arms of opposite sign cancel. Do not read it as an uncorrelated cloud. Most individual arms show a strong lr .

A note on glgate. Both seeds with max-attention data show one head at about 0.21–0.22 maximum attention→pos0. That single head does clear the strict $\epsilon = 0.2$ threshold, which is why the arm’s Sink₁^{0.2} is small but not exactly zero, and no head comes close to the $\epsilon = 0.3$ default of [6]. The arm mean meanwhile stays near 0.07 and Sink₁^{0.2} stays far below 0.05. That pattern repeats across seeds.

E Per-position attention mass (seed 0)

This table gives the mean and max-head attention mass by position at seed 0. It confirms that position 0 is the maximum-mass token in every arm, by mass rather than by argmax count alone. It is the direct check behind the position-0 anchoring defense of §5.

arm	mass@pos0 (mean)	max-head@pos0	argmax-mass position	reading
baseline	0.06	0.17	0	pos0 max; diffuse (no sink)
glgate	0.07	0.23	0	pos0 max; diffuse
sigmoid	0.30	0.66	0	pos0 max; broad raw-sigmoid mass
textinit	0.63	0.99	0	pos0 max; razor spike (pos1 = 0.009)

E.1 Per-position scan at the remaining seeds, and for RF

We re-dumped per-position attention mass at the other seeds and for RF, and per-position residual and value norms for all three *textinit* seeds. The table gives the position at which each quantity peaks (for value norms, the position at which the norm is smallest).




Figure 5: **Entropy collapse tracks concentration only.** Mean attention entropy through training, seed 0, to each arm’s final checkpoint. Only sigmoid and textinit collapse. baseline, g1gate, and RF stay flat. The entropy-collapse correlate from the text-LM literature therefore follows the concentration axis, not the norm axes.

run	seed	attention-mass argmax	residual-norm peak	value-norm minimum	reading
baseline	s0, s1	0	—	—	pos0 max
g1gate	s0, s1, s2	0	—	—	pos0 max
sigmoid	s0, s1	0	—	—	pos0 max
textinit	s0	0	0	0	all three coincide
textinit	s1	0	1	5	norms move off pos0
437 textinit	s2	1	13	13	attention separates from co- incident norm extrema
RF	s0	1	—	—	mass 0.053 vs 0.044 at pos0, diffuse, not a sink

438 Two readings follow. Position 0 remains the maximum-mass token in every arm with a randomly
439 initialized decoder, so the pos0 anchoring holds where the central negative result lives. In *textinit* the
440 three signatures need not share a token, which is the positional dissociation of Appendix I and the
441 reason the pos0-anchored textinit magnitudes at seeds 1 and 2 understate that arm’s peaks.

F Measurement and rendering details

Figure 1 smoothing Paths are smoothed with a moving average, 5 points on the horizontal axis and 9 on the vertical. The faint dots behind each path are the unsmoothed per-probe values, and the initialization and final markers use raw values.

Correlations at the uncollapsed 270 pairs Table 3 collapses to the 90 (layer, KV-group) observations. At the uncollapsed 270 (layer, query-head) pairs the same quantities read +0.67 for baseline, +0.53 for *g1gate*, −0.03 for sigmoid, −0.76 for *textinit*, and +0.43 for RF. Every sign and every ordering survives the collapse.

Raw against row-normalized sigmoid attention Row-normalization changes the object being measured, and Gu et al. [6] state their result for *unnormalized* sigmoid attention. Head L7H3 of the sigmoid arm sends 0.873 of its row-normalized attention to position 0 at the final checkpoint, which is the arm maximum. Its raw gate mass to position 0 is 0.065, and the raw mass summed over all keys in that row is 0.110. The row does not sum to one, and *pos0* takes about 59% of what little gate mass the head opens at all. Early in training the same head shows the opposite picture: raw *pos0* mass 0.309 against a raw row sum of 6.44, so under 5% of a very large gate budget. The concentration this arm develops is therefore a relative reallocation of a shrinking gate budget onto position 0, not the growth of a large absolute mass there (Appendix I). Raw and row-normalized values here come from the same fixed probe batch as every other number in this paper, masked to valid query positions.

Sigmoid heat-map provenance The sigmoid column of Figure 2 uses head L7H3 (0-indexed), the arm’s top sink head on the fixed probe batch. An earlier dump selected heads by raw, unnormalized gate score, picked different heads, and understated the arm. The sigmoid heat maps are re-rendered from an auxiliary streaming batch, because the saved matrices covered the superseded heads. Every printed sigmoid number, in the text and in the tables, comes from the fixed probe batch. The *pos0* share printed on each panel is computed over valid query positions, the same convention as the tables.

G Interpretation (untested hypotheses)

This appendix is **speculative**. Nothing in it is tested by our experiments, and none of it is a claim of this paper. We include it because a reader is entitled to ask *why* the signatures come apart, and because these hypotheses are cheap to state and testable later.

Gu et al. [6] account for the sink as a key bias. Softmax must distribute a full unit of attention mass per row, and a head with nothing informative to retrieve parks the surplus on a token whose value contributes little. If that account is right, each of our levers touches a different part of it, which would explain why each moves a different axis.

- *g1gate*. An output gate can suppress whatever the attended position injects into the residual stream. A model with that gate may be able to *afford* concentration, because concentration no longer forces a matching change in the value path. That would be consistent with a gate whose measured effect here is on the value-norm axis rather than the concentration axis. Fesser et al. [23] make a compatible argument from another direction. They distinguish two kinds of sink. An “adaptive nop” head suppresses its own update by routing attention to a token whose value contributes nothing, and a negligible value norm identifies it. A broadcast head instead spreads global information. They note that gating implicitly assumes the nop mechanism. If that is right, a gate should act on the value-norm axis first, which is where our gated arm differs from baseline.
- *sigmoid*. Removing the softmax removes the sum-to-one constraint itself. A head with nothing to retrieve can simply attend weakly to everything, with no surplus to park. On this reading the value amplification we observe is what the value path does when it is no longer compensating for a forced allocation.
- *textinit*. A pretrained text decoder arrives with sink machinery already built. Our observation that its norm signatures are present at step 0 while concentration crosses later would then reflect import of structure followed by re-targeting onto a visual prefix, rather than formation from scratch.

Each of these is a hypothesis about mechanism. Testing them needs interventions we did not run: gate-scale sweeps that separate gating from the half-scale confound of §3, sigmoid runs at matched




Figure 6: **When each signature first crosses threshold.** Seed 0 throughout. Time-to-event tracks spanning the tokens over which we observed each arm (60M to 1B). A filled marker is the first probe at which a signature crossed its threshold ($h > 2$, $v < 0.8$, $\text{attn} \rightarrow \text{pos0} > 0.3$). A hollow marker at a track’s end means it never crossed. **Crossing times are interval-censored** at the 100-step probe cadence (head-level map in Fig. A5).

effective attention temperature, and text-initialized runs with the sink machinery ablated before alignment.

H Notes on metric hygiene

We record three corrections that we made during the audit of the numbers in this paper. First, an earlier internal consolidation mixed two metrics in one column, mean and max attention $\rightarrow$ pos0, and thereby manufactured an apparent seed anomaly in *g1gate*. Re-derived like-for-like, the anomaly disappears, and *g1gate* becomes the most reproducible arm. Second, an earlier draft claimed that the residual-norm peak of *textinit* “stays pinned at pos0.” We checked that claim against the norm dump. It is wrong. The $\|h\|$ peak sits at pos0, pos1 or pos13, depending on the seed (Appendix E.2). That is the positional dissociation reported in Appendix I, which states the corrected form. Third, the per-position script normalized the profile over a 20-position display slice rather than the full 128, which inflated the reported RF masses to 0.100 and 0.083. The true full-sequence values are **0.053 at pos1 and 0.044 at pos0**. The diffuse-profile reading is unchanged, and the softmax-arm rows of Appendix E were unaffected, because those profiles already sum to one over the full sequence.

I I. ordering, the sigmoid measurement note, and positional dissociation

This appendix holds the detail behind the ordering paragraph of §4.1.

Timings In the softmax arms with randomly initialized decoders, *baseline* and *g1gate* and *RF*, the residual-norm ratio crosses its threshold within the first few to about 15M tokens and value-drain follows within about 50M. Concentration never comes. No baseline or RF head ever crosses it, and *g1gate* reaches 1% of heads, a single-layer blip late in training. *sigmoid* mirrors that pattern, with concentration crossing at about 6M tokens and 89% of heads eventually, against 87% for *textinit*, while neither *sigmoid* norm signature ever crosses (Fig. A5). *textinit* inherits its norm signatures rather than growing them. Value-drain and an elevated residual-norm ratio are both present at 0 tokens, imported with the pretrained text-LM weights. Concentration is *not* inherited the same way, since $\text{Sink}_1^{0.3}$ is 0.000 at step 0 and crosses before 1M tokens. Even in the arm that imports the most sink structure, the norm signatures precede concentration. Crossing times are interval-censored at the 100-step probe cadence, so two signatures that cross within one interval should not be read as ordered.




Figure 7: **Birth-maps.** The step at which each (layer, query-head) pair first crosses the concentration threshold ($\text{attn} \rightarrow \text{pos0} > 0.3$), seed 0, for the three arms in which any head crosses. No *baseline* and no *RF* head ever crosses. 1% of *g1gate* heads do, against 89% for *sigmoid* and 87% for *textinit*. This is the head-level view behind Fig. A4.

520 **The sigmoid arm needs one measurement note**, because row-normalization changes the object being
521 measured and Gu et al. [6] state their result for *unnormalized* sigmoid attention. The concentration
522 this arm develops is a **relative** reallocation of a shrinking gate budget onto position 0, not the growth
523 of a large absolute mass there (Appendix F). We report the row-normalized view in the tables so the
524 arms stay comparable.

525 **Entropy collapse** Attention-entropy collapse, the text-LM literature’s usual correlate of concentra-
526 tion, separates the same way: only *sigmoid* and *textinit* collapse (Fig. A3). It tracks the concentration
527 axis, not the norm axes.

528 **The signatures also dissociate in position** A per-position scan across all three *textinit* seeds shows
529 they need not share a token. At seed 0 they coincide at position 0. At seed 1 the attention maximum
530 stays there while the residual peak moves to pos1 and the value minimum to pos5. At seed 2 they
531 separate furthest, attention at **pos1** and both norm extrema at **pos13**. The arms with randomly
532 initialized decoders behave differently: position 0 stays the maximum-mass token in *baseline*, *g1gate*
533 and *sigmoid* at every seed scanned, and in *RF* the attention argmax sits at pos1 with mass 0.053
534 against 0.044 at position 0, a diffuse profile rather than a sink (Appendix E).

535 We report this as a supporting observation, not a second headline. It has one consequence for
536 measurement. All three metrics anchor on position 0, so the *textinit* magnitudes at seeds 1 and 2 are
537 read at a token that is no longer the peak and therefore **understate** the arm’s true peaks, a further
538 reason to report that arm as a range and a median (§4.1, §5). The anchoring holds for the randomly
539 initialized decoders, which carry the central negative result.

NeurIPS Paper Checklist

1. Claims

Question: Do the main claims made in the abstract and introduction accurately reflect the paper’s contributions and scope?

Answer: [\[Yes\]](#)

Justification: The abstract and Section 1 state exactly the three contributions the paper supports, each with its scope attached: four signature corners at $n = 2-3$ seeds per arm, the low-repetition 1B-token result at a single seed, and the sign-flipping per-head correlation reported at seed 0 and described as descriptive rather than inferential. Section 1 also states plainly that two-way decoupling in text-only models is not ours, and that no downstream behaviour is tested here.

Guidelines:

- The answer NA means that the abstract and introduction do not include the claims made in the paper.
- The abstract and/or introduction should clearly state the claims made, including the contributions made in the paper and important assumptions and limitations. A No or NA answer to this question will not be perceived well by the reviewers.
- The claims made should match theoretical and experimental results, and reflect how much the results can be expected to generalize to other settings.
- It is fine to include aspirational goals as motivation as long as it is clear that these goals are not attained by the paper.

2. Limitations

Question: Does the paper discuss the limitations of the work performed by the authors?

Answer: [\[Yes\]](#)

Justification: Section 5 is a dedicated Limitations section covering position-0 anchoring, the scale confound in the gate arm, the pretrained vision encoder, the h-ratio being a proxy rather than a channel-level measurement of massive activations, token scale, seed-level reproducibility of the textinit magnitudes, provenance and seed counts including the RF optimizer restart, what the RF control cannot establish, domain shift, and the absence of any benchmark accuracy.

Guidelines:

- The answer NA means that the paper has no limitation while the answer No means that the paper has limitations, but those are not discussed in the paper.
- The authors are encouraged to create a separate "Limitations" section in their paper.
- The paper should point out any strong assumptions and how robust the results are to violations of these assumptions.
- The authors should reflect on the scope of the claims made, e.g., if the approach was only tested on a few datasets or with a few runs.
- The authors should reflect on the factors that influence the performance of the approach.
- The authors should discuss the computational efficiency of the proposed algorithms and how they scale with dataset size.
- If applicable, the authors should discuss possible limitations of their approach to address problems of privacy and fairness.
- While the authors might fear that complete honesty about limitations might be used by reviewers as grounds for rejection, a worse outcome might be that reviewers discover limitations that aren’t acknowledged in the paper.

3. Theory assumptions and proofs

Question: For each theoretical result, does the paper provide the full set of assumptions and a complete (and correct) proof?

Answer: [\[N/A\]](#)

Justification: The paper is empirical and contains no theorems, formal claims or proofs.

Guidelines:

- The answer NA means that the paper does not include theoretical results.

- All the theorems, formulas, and proofs in the paper should be numbered and cross-referenced.
- All assumptions should be clearly stated or referenced in the statement of any theorems.
- The proofs can either appear in the main paper or the supplemental material, but if they appear in the supplemental material, the authors are encouraged to provide a short proof sketch to provide intuition.
- Inversely, any informal proof provided in the core of the paper should be complemented by formal proofs provided in appendix or supplemental material.
- Theorems and Lemmas that the proof relies upon should be properly referenced.

4. Experimental result reproducibility

Question: Does the paper fully disclose all the information needed to reproduce the main experimental results of the paper to the extent that it affects the main claims and/or conclusions of the paper (regardless of whether the code and data are provided or not)?

Answer: [\[Yes\]](#)

Justification: Section 2 gives the model, token layout, the four training levers, the datasets, the definition of each of the three signatures, the probe and its self-validation tolerance, the optimizer recipe and the seed counts. Appendix F adds the learning rates, precision, batch size, probe-batch composition, token accounting and the validation protocol. Appendix B gives the per-seed numbers behind every collapsed range in Table 1.

Guidelines:

- The answer NA means that the paper does not include experiments.
- If the paper includes experiments, a No answer to this question will not be perceived well by the reviewers: Making the paper reproducible is important, regardless of whether the code and data are provided or not.
- If the contribution is a dataset and/or model, the authors should describe the steps taken to make their results reproducible or verifiable.
- Depending on the contribution, reproducibility can be accomplished in various ways.

5. Open access to data and code

Question: Does the paper provide open access to the data and code, with sufficient instructions to faithfully reproduce the main experimental results, as described in supplemental material?

Answer: [\[No\]](#)

Justification: The code, probe, run configurations, per-run logs and training checkpoints are prepared for release and the paper commits to releasing them on acceptance, but the links are withheld at submission to preserve double-blind review, and no anonymized mirror is provided. Both datasets used are public and cited. The paper is written so the results can be reproduced from the description alone.

Guidelines:

- The answer NA means that paper does not include experiments requiring code.
- Please see the NeurIPS code and data submission guidelines for more details.
- While we encourage the release of code and data, we understand that this might not be possible, so No is an acceptable answer.
- The instructions should contain the exact command and environment needed to run to reproduce the results.
- The authors should provide instructions on data access and preparation.
- The authors should provide scripts to reproduce all experimental results.
- At submission time, to preserve anonymity, the authors should release anonymized versions (if applicable).

6. Experimental setting/details

Question: Does the paper specify all the training and test details (e.g., data splits, hyperparameters, how they were chosen, type of optimizer) necessary to understand the results?

Answer: [\[Yes\]](#)

Justification: Section 2 specifies the optimizer, weight decay, gradient clipping, schedule and warmup, the token budgets per arm, the held-out split behaviour, and the seed counts. Appendix F specifies the per-module learning rates, the precision and the batch size. Every arm differs only in the lever under test, which Section 2 states explicitly.

Guidelines:

- The answer NA means that the paper does not include experiments.
- The experimental setting should be presented in the core of the paper to a level of detail that is necessary to appreciate the results and make sense of them.
- The full details can be provided either with the code, in appendix, or as supplemental material.

7. Experiment statistical significance

Question: Does the paper report error bars suitably and correctly defined or other appropriate information about the statistical significance of the experiments?

Answer: [No]

Justification: We report no error bars or significance tests, and say so explicitly. Instead, the main tables give per-arm ranges over 2–3 seeds and Appendix B gives every per-seed value, so the seed-level variability is fully visible. Section 3.3 states that the per-head correlations are descriptive rather than inferential, because heads within a layer are not independent and each arm rests on a single seed, so a p-value would mislead. Section 5 states that the RF arm is a single seed. With these seed counts, error bars would convey false precision.

Guidelines:

- The answer NA means that the paper does not include experiments.
- The authors should answer Yes if the results are accompanied by error bars, confidence intervals, or statistical significance tests, at least for the experiments that support the main claims of the paper.
- The factors of variability that the error bars are capturing should be clearly stated.
- The method for calculating the error bars should be explained.
- The assumptions made should be given.
- It should be clear whether the error bar is the standard deviation or the standard error of the mean.
- It is OK to report 1-sigma error bars, but one should state it.
- For asymmetric distributions, the authors should be careful not to show in tables or figures symmetric error bars that would yield results that are out of range.
- If error bars are reported in tables or plots, the authors should explain in the text how they were calculated and reference the corresponding figures or tables in the text.

8. Experiments compute resources

Question: For each experiment, does the paper provide sufficient information on the computer resources (type of compute workers, memory, time of execution) needed to reproduce the experiments?

Answer: [No]

Justification: The paper states the token budget of every run, which fixes the dominant cost, but it does not state the accelerator type, memory or wall-clock time. Two memory-driven events are disclosed in Section 5, the weights-only optimizer restart in the RF run and the reduction of the streaming shuffle buffer, because they affect interpretation of the results rather than only the cost.

Guidelines:

- The answer NA means that the paper does not include experiments.
- The paper should indicate the type of compute workers CPU or GPU, internal cluster, or cloud provider, including relevant memory and storage.
- The paper should provide the amount of compute required for each of the individual experimental runs as well as estimate the total compute.
- The paper should disclose whether the full research project required more compute than the experiments reported in the paper.

9. Code of ethics

693 Question: Does the research conducted in the paper conform, in every respect, with the NeurIPS
694 Code of Ethics?

695 Answer: [Yes]

696 Justification: The work trains small vision–language models on public, already-published image–
697 text corpora, involves no human subjects and no personal data, and releases no model with
698 foreseeable misuse potential. Anonymity is preserved in this submission.

699 Guidelines:

- 700 • The answer NA means that the authors have not reviewed the NeurIPS Code of Ethics.
- 701 • If the authors answer No, they should explain the special circumstances that require a deviation
702 from the Code of Ethics.
- 703 • The authors should make sure to preserve anonymity.

704 10. **Broader impacts**

705 Question: Does the paper discuss both potential positive societal impacts and negative societal
706 impacts of the work performed?

707 Answer: [N/A]

708 Justification: This is foundational measurement work on the internal mechanics of 222M-parameter
709 research models. It proposes no application, releases no deployable system, and improves no
710 capability. Its practical consequence is confined to how interpretability and mitigation work
711 reports attention sinks, which the Conclusion states.

712 Guidelines:

- 713 • The answer NA means that there is no societal impact of the work performed.
- 714 • If the authors answer NA or No, they should explain why their work has no societal impact or
715 why the paper does not address societal impact.
- 716 • Examples of negative societal impacts include potential malicious or unintended uses, fairness
717 considerations, privacy considerations, and security considerations.
- 718 • The conference expects that many papers will be foundational research and not tied to particular
719 applications, let alone deployments.
- 720 • The authors should consider possible harms that could arise when the technology is being used
721 as intended and functioning correctly, harms that could arise when the technology is being used
722 as intended but gives incorrect results, and harms following from misuse of the technology.
- 723 • If there are negative societal impacts, the authors could also discuss possible mitigation
724 strategies.

725 11. **Safeguards**

726 Question: Does the paper describe safeguards that have been put in place for responsible release
727 of data or models that have a high risk for misuse (e.g., pre-trained language models, image
728 generators, or scraped datasets)?

729 Answer: [N/A]

730 Justification: The artefacts are 222M-parameter research checkpoints trained for a measurement
731 study. They are far below any capability threshold that would carry misuse risk, and no dataset is
732 released.

733 Guidelines:

- 734 • The answer NA means that the paper poses no such risks.
- 735 • Released models that have a high risk for misuse or dual-use should be released with necessary
736 safeguards to allow for controlled use of the model.
- 737 • Datasets that have been scraped from the Internet could pose safety risks. The authors should
738 describe how they avoided releasing unsafe images.
- 739 • We recognize that providing effective safeguards is challenging, and many papers do not require
740 this, but we encourage authors to take this into account and make a best faith effort.

741 12. **Licenses for existing assets**

742 Question: Are the creators or original owners of assets (e.g., code, data, models), used in the
743 paper, properly credited and are the license and terms of use explicitly mentioned and properly
744 respected?

745 Answer: [No]

746 Justification: Every existing asset is cited to its original paper at the point of use: the nanoVLM
747 codebase, the SigLIP-B/16 encoder, the SmolLM2 architecture and weights, and both image–text
748 corpora. The paper does not, however, enumerate the license of each asset by name, so this answer
749 is No rather than Yes. All assets are publicly released for research use and were used within those
750 terms.

751 Guidelines:

- 752 • The answer NA means that the paper does not use existing assets.
- 753 • The authors should cite the original paper that produced the code package or dataset.
- 754 • The authors should state which version of the asset is used and, if possible, include a URL.
- 755 • The name of the license (e.g., CC-BY 4.0) should be included for each asset.
- 756 • For scraped data from a particular source, the copyright and terms of service of that source
757 should be provided.
- 758 • If assets are released, the license, copyright information, and terms of use in the package should
759 be provided.
- 760 • For existing datasets that are re-packaged, both the original license and the license of the
761 derived asset should be provided.
- 762 • If this information is not available online, the authors are encouraged to reach out to the asset’s
763 creators.

764 **13. New assets**

765 Question: Are new assets introduced in the paper well documented and is the documentation
766 provided alongside the assets?

767 Answer: [N/A]

768 Justification: No new asset is released with this submission. The code, probe, run configura-
769 tions, logs and checkpoints are held for release on acceptance, at which point they will carry
770 documentation.

771 Guidelines:

- 772 • The answer NA means that the paper does not release new assets.
- 773 • Researchers should communicate the details of the dataset/code/model as part of their submis-
774 sions via structured templates.
- 775 • The paper should discuss whether and how consent was obtained from people whose asset is
776 used.
- 777 • At submission time, remember to anonymize your assets (if applicable).

778 **14. Crowdsourcing and research with human subjects**

779 Question: For crowdsourcing experiments and research with human subjects, does the paper
780 include the full text of instructions given to participants and screenshots, if applicable, as well as
781 details about compensation (if any)?

782 Answer: [N/A]

783 Justification: The work involves no crowdsourcing and no human subjects.

784 Guidelines:

- 785 • The answer NA means that the paper does not involve crowdsourcing nor research with human
786 subjects.
- 787 • Including this information in the supplemental material is fine, but if the main contribution of
788 the paper involves human subjects, then as much detail as possible should be included in the
789 main paper.
- 790 • According to the NeurIPS Code of Ethics, workers involved in data collection, curation, or
791 other labor should be paid at least the minimum wage in the country of the data collector.

792 **15. Institutional review board (IRB) approvals or equivalent for research with human subjects**

793 Question: Does the paper describe potential risks incurred by study participants, whether such
794 risks were disclosed to the subjects, and whether Institutional Review Board (IRB) approvals
795 (or an equivalent approval/review based on the requirements of your country or institution) were
796 obtained?

797 Answer: [N/A]
 798 Justification: The work involves no human subjects, so no IRB review or equivalent applies.
 799 Guidelines:
 800 • The answer NA means that the paper does not involve crowdsourcing nor research with human
 801 subjects.
 802 • Depending on the country in which research is conducted, IRB approval (or equivalent) may
 803 be required for any human subjects research.
 804 • We recognize that the procedures for this may vary significantly between institutions and
 805 locations, and we expect authors to adhere to the NeurIPS Code of Ethics and the guidelines
 806 for their institution.
 807 • For initial submissions, do not include any information that would break anonymity.

808 **16. Declaration of LLM usage**
 809 Question: Does the paper describe the usage of LLMs if it is an important, original, or non-
 810 standard component of the core methods in this research? Note that if the LLM is used only for
 811 writing, editing, or formatting purposes and does not impact the core methodology, scientific rigor,
 812 or originality of the research, declaration is not required.
 813 Answer: [N/A]
 814 Justification: Language models appear in this work as the object of study, a 135M-parameter
 815 decoder trained and probed by the authors. No large language model forms part of the method.
 816 LLM coding assistants were used to write and refactor the training, probe and analysis code and
 817 to edit prose, which Appendix A discloses; the experimental design, measurements, analysis
 818 decisions and claims are the authors' own, so this use does not affect the methodology, rigor or
 819 originality of the research.
 820 Guidelines:
 821 • The answer NA means that the core method development in this research does not involve
 822 LLMs as any important, original, or non-standard components.
 823 • Please refer to our LLM policy in the NeurIPS handbook for what should or should not be
 824 described.