

Visoka škola strukovnih studija  
za informacione i komunikacione  
tehnologije



# Flex shop

Smer: Internet tehnologije  
Modul: Web programiranje  
Predmet: Web Programiranja PHP 2

Nenad Jevtić 60/20

# Sadržaj

1. Uvod .....	4
1.1 Korišćeni programski jezici .....	4
1.2 Template .....	4
2. Organizacija .....	5
2.1 Dijagram baze .....	5
2.2 Izgled sajta i opis funkcionalnosti .....	5
2.2.1 / .....	5
2.2.2 /products.....	7
2.2.3 /products/{id}.....	7
2.2.4 /contact.....	9
2.2.5 /cart.....	9
2.2.6 /checkout .....	10
2.2.7 /login .....	10
2.2.8 /register .....	11
2.2.9 /author .....	11
2.2.10 /adminpanel.....	12
2.2.11 /answermessage/{id}.....	13
2.2.12 /adduser .....	14
2.2.13 /removeuser .....	14
2.2.14 /orders .....	15
2.2.15 /orders/{id} .....	15
2.2.16 /updateproduct/{id}.....	16
3. Kodovi .....	17
3.1 Controllers.....	17
3.1.1 AdminController.php .....	17
3.1.2 AuthorController.php.....	18
3.1.3 CartController.php .....	19
3.1.4 CheckoutController.php.....	21
3.1.5 ContactController.....	22
3.1.6 Controller.php.....	23
3.1.7 HomeController.php .....	23
3.1.8 LoginController.php .....	24
3.1.9 MessageController.php.....	25
3.1.10 ProductController.php .....	26

3.1.11 RegisterController.php.....	27
3.1.12 UserController.php .....	28
3.2 Middleware .....	29
3.2.1 isAdmin.php .....	29
3.2.2 NotAuthorized.php .....	29
3.2.3 Authorized.php .....	30
3.2.4 CartExist.php .....	31
3.3 Requests.....	31
3.3.1 AddUserRequest.php .....	31
3.3.2 LoginRequest.php .....	32
3.3.3 RegisterRequest.php.....	33
3.3.4 UpdateProductRequest.php .....	33
3.4 Models .....	34
3.4.1 Brand.php.....	34
3.4.2 Cart.php .....	35
3.4.3 Category.php.....	36
3.4.4 Checkout.php.....	36
3.4.5 Info.php.....	38
3.4.6 Message.php.....	39
3.4.7 Navigation.php.....	39
3.4.8 Product.php .....	39
3.4.9 Receipt.php .....	42
3.4.10 Size.php.....	43
3.4.11 Statistic.php .....	43
3.4.12 User.php.....	44
3.5 JavaScript .....	45
3.5.1 main.js.....	45
3.5.2 custom.js .....	46
3.6 Views .....	54
3.6.1 Fixed .....	54
3.6.2 Layouts .....	63
3.6.3 Pages .....	64
3.6.4 Components.....	102
3.7 Routes .....	104
3.7.1 web.php .....	104

# 1.Uvod

## 1.1 Korišćeni programski jezici

-Za izradu sajta korišćeni su:

- PHP,
- Laravel,
- HTML,
- CSS + Bootstrap,
- JavaScript,
- AJAX
- jQuery,
- MySQL.

-Radno okruženje: [PhpStorm](#)


## 1.2 Template

Za izradu sajta korišćen je template preuzet sa sajta:

<https://themewagon.com/themes/multishop-free-bootstrap-4-ecommerce-website-template/>


## 2. Organizacija

### 2.1 Dijagram baze




### 2.2 Izgled sajta i opis funkcionalnosti


#### 2.2.1 /



Meni je dinamički ispisan iz baze podataka. Razlikuje se u zavisnosti da li je korisnik ulogovan ili ne.




Ispisani brendovi kao i broj proizvoda tog brenda. Dinamicki iz baze prikazani neki od proizvoda.




Footer svih stranica kojima korisnik moze pristupiti.

## 2.2.2 /products



Sa leve strane se nalaze filteri po kategorijama, brendovima, polu i ceni. Dinamički su ispisani proizvodi putem PHP funkcija kojim se dohvataju podaci iz baze podataka. Takođe iznad proizvoda se nalazi i search box gde se mogu pretraživati proizvodi. Na dugme clear filters se svi filteri brišu. Paginacija proizvoda.

## 2.2.3 /products/{id}



Klikom na jedan od proizvoda dobijamo prikaz proizvoda, sa sve dostupnim veličinama, količinom, cenom kao i specifikacijom.

Availability: In stock

Sizes: ☐ M ☐ XL

Select size.

—

0


+

 Add To Cart


Invalid quantity.

Ukoliko veličina nije izabrana ili je količina veća od 99 ili manja od 0 dobijamo obaveštenje da moramo izabrati veličinu kao i uneti ispravnu količinu.


**ON SALE**




Basketball shorts  
**\$12.00** ~~\$25.00~~



Highwaist Shorts  
**\$9.00** ~~\$15.00~~



Mom Fit Jeans  
**\$18.00** ~~\$20.00~~



Mom Fit Jeans  
**\$25.00**

Ispod proizvoda se nalazi slider sa proizvodima koji su na akciji.



## 2.2.4 /contact

[Home](#) / [Contact](#)

### CONTACT US

Message

Send Message

Zdravka Čelara 16, Beograd, Srbija

flexshop\_info@gmail.com

011 123 4567

Na stranici contact postoji validacija forme gde se podaci moraju uneti u ispravnom formatu. Ukoliko su svi uslovi ispunjeni poruka se šalje i dobijamo obaveštenje o uspešno poslatoj poruci.

## 2.2.5 /cart

**FLEX SHOP**

Customer Service  
011 123 4567

WORLD OF CLOTHS

[Home](#) [Shop](#) [Contact](#) [Author](#)

[Home](#) / [Shop](#) / Shopping Cart

Products	Price	Quantity	Size	Total	Remove
Oversize sweatshirt	\$12.00	x1	M	\$12.00	

CART SUMMARY

Subtotal

\$12.00

Shipping

\$10

Total

\$22.00

Proceed To Checkout

Na stranici cart se prikazuju svi proizvodi koji su uspešno uneti u korpu. U zavisnosti da li je korisnik ulogovan ili ne, razlikuje se i način čuvanja stavki korpe. Ukoliko je korpa prazna dobijamo obaveštenje da je korpa prazna, te se ne možemo checkout-ovati. Ukoliko je proizvod isti ali se razlikuje veličina, u korpi se kreira nova stavka sa drugom veličinom.

## 2.2.6 /checkout

The checkout page is divided into three main sections: BILLING ADDRESS, ORDER TOTAL, and PAYMENT.

**BILLING ADDRESS**

First Name	Last Name
John	Doe
E-mail	Address Line 1
example@email.com	123 Street
Country	City
Select country	New York
ZIP Code	
123	

**ORDER TOTAL**

Products		
Oversize sweatshirt (M)	x1	\$12.00
Subtotal		\$12.00
Shipping		\$10.00
Total		\$22.00

**PAYMENT**

☒ Paypal

☐ Direct Check

☐ Bank Transfer

[Place Order](#)

Na stranici checkout postoji validacija forme gde se podaci moraju uneti u ispravnom formatu. Ukoliko je sve to ispunjeno dobijamo obaveštenje da je narudžbina uspešno poslata.


## 2.2.7 /login

The login page features a central "Sign In" form with the following fields and elements:

- Field: name@example.com
- Field: Password
- Button: SIGN IN

Na stranici login postoji validacija forme gde se podaci moraju uneti u ispravnom formatu. Ukoliko korisnik sa zadatim email-om ne postoji u bazi ili nije uneta ispravna lozinka, dobija se odgovarajuće obaveštenje. Korisnici koji su ulogovani ni na koji način ne mogu pristupiti ovoj stranici.

## 2.2.8 /register




The screenshot shows a registration form titled "Create an account". It contains the following input fields: First name, Last name, Username, Email Address, Address, City, Postal code, a dropdown menu for Country (currently showing "Serbia"), Password, and Confirm Password. A yellow "REGISTER" button is located at the bottom center of the form. To the right of the button is a small yellow icon of a person.

Na stranici register postoji validacija podataka gde se podaci moraju uneti u ispravnom formatu.

Ukoliko su svi uslovi ispunjeni dobijamo obaveštenje da je registracija uspešna i vrši se redirekcija na stranicu sa proizvodima.

## 2.2.9 /author



The screenshot shows the "Author" page of the "WORLD OF CLOTHS" website. The header includes the site logo and navigation links: Home, Shop, Contact, and Author. A shopping cart icon is visible in the top right corner. The main content area features a profile picture of a man, a title "Author", and a bio: "Hi, my name is Nenad Jevtić, and I am a desktop and web developer. I was lucky enough to work for several fun, exciting and successful StartUps that helped me to become who I am now. I am always thinking about speed, performance optimisation, scalability and the way to improve workflow for each individual project. Communication with me is simple, you are free to call me anytime you want. I keep up to date with the latest technologies and consider myself a very quick study able to pick up another technology in a very short amount of time as needed." Below the bio is a yellow button labeled "Visit portfolio".

Na autor stranici postoje podaci o autoru kao i link ka autorovom portfoliju.

## 2.2.10 /adminpanel

**FLEX SHOP ADMIN PANEL**

Dashboard

ACTIONS

Users

Orders

Dashboard

EARNINGS (MONTHLY) \$8,130.00

EARNINGS (ANNUAL) \$98,915.00

USERS 4

ORDERS 2

Messages

Message Id	Name	Subject	Email	Message	Sent at	Action
3	Nenad	Test	lazar@gmail.com	test	2023-01-15 13:03:53	Answer
4	Nenad	asd	lazar@gmail.com	atad	2023-01-15 13:04:02	Answer
5	Nenad	Test	lazar@gmail.com	adwad	2023-01-15 13:04:37	Answer
6	Nenad Jevtic	asd	lazar@gmail.com	adwsd	2023-01-15 13:06:57	Answer
7	Nenad Jevtic	Test	lazar@gmail.com	adwsd	2023-01-15 13:07:33	Answer

Na admin panelu administratori imaju pregled u pristigle poruke, očekivanu mesečnu i godišnju zaradu, broj korisnika kao i broj porudžbina.

U levom sidebar-u administratori mogu dodati/obrisati korisnika kao i pregledati listu porudžbina ili detaljnije određenu porudžbinu.

Users

User Id	Name	Email	Username	Role	Registration date	Action
1	Nenad Jevtic	nenad.jevtic.60.20@ict.edu.rs	nenad.jevtic.60.20	Administrator	2023-01-21 17:34:26	Forbidden
2	Test Nalog	testnalog@gmail.com	test.nalog.12	User	2023-01-21 21:52:09	Block
5	Dacha Stevic	dacha@gmail.com	dachastevic10	Administrator	2023-01-21 17:28:53	Forbidden
9	Milos Resanovic	somiresa@gmail.com	somiresa10	User	2023-01-21 22:08:22	Block

Statistics

Clear log

Name	Email	Action
Nenad Jevtic	nenad.jevtic.60.20@ict.edu.rs	Login
Nenad Jevtic	nenad.jevtic.60.20@ict.edu.rs	Login
Nenad Jevtic	nenad.jevtic.60.20@ict.edu.rs	Login

Takođe administratori mogu blokirati i odblokirati sve korisnike koji nisu administratori. U vidu tabele je prikazana statistika, tj. Ključni događaji na stranici, kao i korisnik koji je to akciju izvršio (Login, Logout, Register)

Products								
Product Id	Product name	Category	Brand	Gender	Price	Sale	In stock	View
17	Sweatshorts	Shorts	BSFN	Male	\$10.00	True	True	<button>Update product</button>
18	Sweatshorts	Shorts	BSFN	Male	\$12.00	False	True	<button>Update product</button>
19	Basketball shorts	Shorts	BSFN	Male	\$12.00	True	True	<button>Update product</button>
34	Quilted jacket with hood	Jackets	BSFN	Female	\$55.00	False	True	<button>Update product</button>
42	T-shirt with round neck	Shirts	BSFN	Male	\$15.00	False	True	<button>Update product</button>
43	T-shirt with layering	Shirts	BSFN	Male	\$10.00	False	True	<button>Update product</button>
3	Sweatshirt with shoulder detail	Jumpers	Fb Fashion	Female	\$7.00	False	False	<button>Update product</button>
4	Oversize sweatshirt	Jumpers	Fb Fashion	Female	\$10.00	False	True	<button>Update product</button>

Prikaz svih proizvoda gde je moguće izmeniti proizvod.

2.2.11 /answermessage/{id}

**FLEX SHOP**  
ADMIN PANEL

- Dashboard
- ACTIONS
- Users
- Orders

Nenad Jevtic

## Message details

Message ID: 8

Name: Nenad Jevtic

Email: lazar@gmail.com

Message: Test


Answer:

Send answer

Copyright © Flex Shop 2022

Ispisani su detalji same poruke gde administrator može odgovoriti na poruku.


## 2.2.12 /adduser



The screenshot shows the 'FLEX SHOP ADMIN PANEL' interface. On the left is a blue sidebar with a gear icon and the text 'FLEX SHOP ADMIN PANEL'. Below this are links for 'Dashboard', 'Users', and 'Orders'. The 'Users' link is highlighted. The main content area is titled 'Add user' and contains a form with the following fields: 'First name', 'Last name', 'Username', 'Email Address', 'Administrator' (a dropdown menu), 'Password', and 'Confirm Password'. At the bottom of the form is a teal button labeled 'Add user'. In the top right corner of the admin panel, the name 'Nenad Jevtic' is displayed.

Na stranici add user administrator može dodati korisnik, gde mu takođe može dodeliti ulogu (User, Administrator). Forma mora biti validna da bi se korisnik uspešno dodao, u suprotnom dobijamo obaveštenje koji podaci nisu ispravno uneti.


## 2.2.13 /removeuser



The screenshot shows a form titled 'Select user:'. It contains a dropdown menu with the text 'Test Nalog' and a teal button labeled 'Remove user'.

Administrator može izabrati korisnika koji nije administrator iz padajuće liste i obrisati ga.

### 2.2.14 /orders



FLEX SHOP

ADMIN PANEL

Dashboard

Users

Orders

←

Nenad Jevtic


Orders

Order Id	Full Name	Email	Full Address	Country	Total	Order date	Action
23	Nenad Jevtic	nenad.jevtic.60.20@ict.edu.rs	Test adresa, Beograd 11000	Serbia	\$135.00	2023-01-22 00:25:01	Show receipt
29	Test Nalog	testnalog@gmail.com	Test adresa 2, Moscow 12345	Russia	\$136.00	2023-01-22 00:38:06	Show receipt

Copyright © Flex Shop 2022

Prikazane izlistane sve narudžbine, gde se klikom na dugme Show receipt, može pogledati detaljno sama narudžbina.

### 2.2.15 /orders/{id}



FLEX SHOP

ADMIN PANEL

Dashboard

ACTIONS

Users

Orders

Order details


Product Name	Price	Size	Quantity
Oversize sweatshirt	\$12.00	M	2
Hoodie	\$15.00	M	3
Washed Slim Fit Denim	\$28.00	L	2

Go back

Copyright © Flex Shop 2022

### Detaljan prikaz same porudžbine

## 2.2.16 /updateproduct/{id}



The screenshot displays the 'FLEX SHOP ADMIN PANEL' interface. On the left is a blue sidebar with a 'Dashboard' link and an 'ACTIONS' section containing 'Users' and 'Orders'. The main content area is titled 'Update product "Sweatshorts"'. It features four input fields: 'Product Name' (containing 'Sweatshorts'), 'Price' (containing '10.00'), 'Material' (containing 'Cotton'), and 'Country of origin' (containing 'Poland'). A teal 'Update product' button is positioned at the bottom center of the form. The top right corner shows the user 'Nenad Jevtic'.

Izmena proizvoda, forma mora biti validna da bi se proizvod uspešno ažurirao.



## 3.Kodovi

### 3.1 Controllers

#### 3.1.1 AdminController.php

```
<?php

namespace App\Http\Controllers;

use App\Http\Requests\UpdateProductRequest;
use App\Models\Message;
use App\Models\Product;
use App\Models\Receipt;
use App\Models\Statistic;
use App\Models\User;
use Couchbase\QueryException;
use Illuminate\Http\Request;

class AdminController extends Controller
{
    public function index() {
        $this->data['message']=Message::all();
        $productModel=new Product();
        $this->data['products']=$productModel->fetchProductsInfo();
        $receiptModel=new Receipt();
        $userModel=new User();
        $this->data['earningsMonthly']=30*($receiptModel->ShowEarnings());
        $this->data['earningsYearly']=365*($receiptModel->ShowEarnings());
        $this->data['orders']=$receiptModel->showOrders();
        $this->data['users']=User::all();
        $this->data['statistics']=Statistic::all();
        $this->data['userCount']=$userModel->userCount();

        return view('pages.admins.home',['data'=>$this->data]);
    }

    public function clearStats() {
        Statistic::truncate();

        return redirect()->back();
    }

    public function unblockUser($id) {
        $user=\DB::table('users')
            ->where('users.user_id','=',$id)
            ->update([
                'is_banned'=>0
            ]);

        return redirect()->back();
    }

    public function blockUser($id) {
        $user=\DB::table('users')
```

```

        ->where('users.user_id','='.$id)
        ->update([
            'is_banned'=>1
        ]);

        return redirect()->back();
    }

    public function showOrders() {
        $this->data['orders']=Receipt::all();
        return view('pages.admins.orders',['data'=>$this->data]);
    }

    public function showSingleReceipt($id) {
        $receiptModel=new Receipt();
        $this->data['orderDetails']=$receiptModel->fetchSingleOrder($id);
        return view('pages.admins.single_order',['data'=>$this->data]);
    }

    public function updateProduct($id) {
        $productModel=new Product();
        $product=$productModel->fetchProductForUpdate($id);
        $this->data['productUpdate']=$product;

        return view('pages.admins.updateProduct',['data'=>$this->data]);
    }

    public function updateProductPrice(UpdateProductRequest $request) {
        try {
            $product_name=$request->product_name;
            $price=$request->price;
            $id=$request->id;
            $material=$request->material;
            $coo=$request->coo;
            $productModel=new Product();
            $productModel->updateProduct($product_name,$price,$id,$material,$coo);

            return redirect()->back()->with('success-msg','Product
updated!');
        } catch (\Exception $e) {
            return redirect()->back()->with('error-msg',$e->getMessage());
        }
    }
}

```

### 3.1.2 AuthorController.php

```

<?php

namespace App\Http\Controllers;

use Illuminate\Http\Request;

class AuthorController extends Controller
{

```

```

    public function index() {
        return view('pages.author', ['data'=>$this->data]);
    }
}

```

### 3.1.3 CartController.php

```

<?php

namespace App\Http\Controllers;

use App\Models\Cart;
use Illuminate\Http\Request;

class CartController extends Controller
{
    public function index() {
        $cartModel=new Cart();
        $cartProducts=$cartModel->cartProducts();
        $cartId=[];
        if(session()->has('user')){
            $cart=$cartModel->fetchCart();
            if($cart){
                foreach ($cart as $c){
                    array_push($cartId,$c->product_id);
                }
                $this->data['cartProducts']=$cartProducts;
                $this->data['cart']=$cart;
            }else{
                $cart=null;
                $this->data['cart']=$cart;
            }

        }elseif(session()->has('cart')){
            $cart=session('cart');
            foreach ($cart as $c){
                array_push($cartId,$c->product_id);
            }
            $this->data['cartProducts']=$cartProducts;
            $this->data['cart']=$cart;
        }else{
            $cart=null;
            $this->data['cart']=$cart;
        }

        return view('pages.cart', ['data'=>$this->data]);
    }

    public function addToCart(Request $request){
        $size=$request->size;
        $qty=$request->qty;
        $product_id=$request->product_id;
        $cartModel=new Cart();
        $products=[];
        try {
            if(session()->has('user')){
                $user_id=session('user')->user_id;
                if($cartModel->existInCart($size,$product_id,$user_id)){
                    $qtyOld=$cartModel->

```

```

>oldQuantity($product_id,$size,$user_id);
    $qty=$qty+$qtyOld->qty;
    $cartModel-
>updateQuantity($product_id,$size,$user_id,$qty);
    }else{
        $cartModel-
>insertIntoCart($product_id,$size,$user_id,$qty);
    }
    }elseif(session()->has('cart'))
    {
        $cart=session('cart');
        $filterCart= $this->filterCart($cart, $product_id, $size);
        if($filterCart){
            foreach ($cart as $c){
                if($c->product_id==$product_id && $c->size==$size){
                    $c->qty=$c->qty+$qty;
                    session()->put('cart',$cart);
                    break;
                }
            }
        }else{
            $product=new \stdClass();
            $product->size=$size;
            $product->qty=$qty;
            $product->product_id=$product_id;
            $products=session('cart');
            array_push($products,$product);
            session()->put('cart',$products);
        }
    }else{
        $product=new \stdClass();
        $product->size=$size;
        $product->qty=$qty;
        $product->product_id=$product_id;
        array_push($products,$product);
        session()->put('cart',$products);
    }
    return true;
}catch(\Exception $e){
    return false;
}

}

function filterCart($cart,$product_id,$size):int{
    $br=0;
    foreach ($cart as $c){
        if($c->product_id==$product_id && $c->size==$size){
            $br++;
        }
    }

    return $br;
}

function removeFromCart(Request $request){
    $product_id=$request->product_id;
    $size=$request->size;
    if(session()->has('user')){
        try {

```

```

        $cartModel=new Cart();
        $cartModel->removeFromCart($product_id,$size);
        return true;
    }catch(\Exception $e){
        return false;
    }
}elseif(session()->has('cart')){
    try {
        $cart=session('cart');
        for($i=0;$i<count($cart);$i++){
            if($cart[$i]->product_id==$product_id && $cart[$i]-
>size==$size){
                unset($cart[$i]);
                break;
            }
        }
        session()->put('cart',$cart);
        return true;
    }catch(\Exception $e){
        return false;
    }
}
}
}
}

```

### 3.1.4 CheckoutController.php

```

<?php

namespace App\Http\Controllers;

use App\Models\Checkout;
use Illuminate\Http\Request;
use Symfony\Component\HttpFoundation\File\Exception\ExtensionFileException;

class CheckoutController extends Controller
{
    public function index(){
        $checkoutModel=new Checkout();
        $checkoutProducts=$checkoutModel->checkoutProducts();
        $cartId=[];
        if(session()->has('user')){
            $cart=$checkoutModel->fetchCart();
            $user=$checkoutModel->fetchUser();
            foreach ($cart as $c){
                array_push($cartId,$c->product_id);
            }
            $this->data['userInfo']=$user;
            $this->data['cartProducts']=$checkoutProducts;
            $this->data['cart']=$cart;
        }else{
            $cart=session('cart');
            foreach ($cart as $c){
                array_push($cartId,$c->product_id);
            }
        }
    }
}

```

```

    }
    $this->data['cartProducts']=$checkoutProducts;
    $this->data['cart']=$cart;
}

return view('pages.checkout',['data'=>$this->data]);
}

function confirmOrder(Request $request){
    $first_name=$request->first_name;
    $last_name=$request->last_name;
    $email=$request->email;
    $postal_code=$request->postal_code;
    $country=$request->country;
    $city=$request->city;
    $address=$request->address;

    try {
        $checkoutModel=new Checkout();
        $user=0;
        if(session()->has('user')){
            $cart=$checkoutModel->fetchCart();
            $user=1;
        }else{
            $cart=session('cart');
        }
        $checkoutModel->
>insertOrder($first_name,$last_name,$email,$postal_code,$country,$city,$address,$cart);
        if($user){
            $checkoutModel->emptyCart();
        }else{
            session()->forget('cart');
        }
        return true;
    }catch(\Exception $e){
        return false;
    }
}
}

```

### 3.1.5 ContactController

```

<?php

namespace App\Http\Controllers;

use Illuminate\Http\Request;

class ContactController extends Controller
{
    public function index(){
        return view('pages.contact',['data'=>$this->data]);
    }
}

```

```
}  
}
```

### 3.1.6 Controller.php

```
<?php  
  
namespace App\Http\Controllers;  
  
use App\Models\Navigation;  
use Illuminate\Foundation\Auth\Access\AuthorizesRequests;  
use Illuminate\Foundation\Bus\DispatchesJobs;  
use Illuminate\Foundation\Validation\ValidatesRequests;  
use Illuminate\Routing\Controller as BaseController;  
  
class Controller extends BaseController  
{  
    use AuthorizesRequests, DispatchesJobs, ValidatesRequests;  
  
    public $data=[];  
  
    public function __construct()  
    {  
        $menu=Navigation::all();  
        $this->data['menu']=$menu;  
    }  
}
```

### 3.1.7 HomeController.php

```
<?php  
  
namespace App\Http\Controllers;  
  
use App\Models\Brand;  
use App\Models\Product;  
use Illuminate\Http\Request;  
  
class HomeController extends Controller  
{  
    public function index() {  
        $brandModel=new Brand();  
        $brand=$brandModel->fetchBrands();  
        $products=new Product();  
        $products=$products->fetchProductsHome();  
        $brandImage=$brandModel->fetchBrandImage();  
        $this->data['products']=$products;  
        $this->data['brandsImage']=$brandImage;  
        $this->data['brandsCount']=$brand;  
        return view('pages.home',['data'=>$this->data]);  
    }  
}
```

### 3.1.8 LoginController.php

```
<?php

namespace App\Http\Controllers;

use App\Http\Requests\LoginRequest;
use App\Models\Statistic;
use App\Models\User;
use Illuminate\Support\Facades\Auth;

class LoginController extends Controller
{
    public function index(){
        return view('pages.login',['data'=>$this->data]);
    }

    public function login(LoginRequest $request){
        $email=$request->email;
        $password=md5($request->password);
        $user=User::where('email',$email)->first();
        if(!$user){
            return redirect()->back()->with('error-msg', 'No user found!');
        }
        if($password != $user->password){
            return redirect()->back()->with('error-msg', 'Wrong
password!');
        }
        if($user->is_banned){
            return redirect()->back()->with('error-msg', 'Account banned!
Contact support.');
```

```
        }else{
            $user_id=$user->user_id;
            $userModel=new User();
            $userModel->updateLogin($user_id);
            $request->session()->put('user',$user);
            Statistic::create([
                'name'=>session('user')->first_name.' '.session('user')->last_name,
                'email'=>session('user')->email,
                'action'=>'Login'
            ]);
            return redirect()->route('Browse products');
        }
    }

    public function logout(){
        $userModel=new User();
        $user_id=session('user')->user_id;
        $userModel->updateLogout($user_id);
        Statistic::create([
            'name'=>session('user')->first_name.' '.session('user')->last_name,
            'email'=>session('user')->email,
            'action'=>'Logout'
        ]);
    }
}
```



```

        session()->forget('user');
        return redirect()->route('Home');
    }
}

```

### 3.1.9 MessageController.php

```

<?php

namespace App\Http\Controllers;

use App\Models\Message;
use Illuminate\Database\QueryException;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\Response;
use Illuminate\Support\Facades\Mail;
use App\Mail\AnswerMail;

class MessageController extends Controller
{
    public function index($id) {
        $this->data['message']=Message::find($id);
        return view('pages.admins.answerMessage',['data'=>$this->data]);
    }
    public function sendMessage(Request $request){
        $name = $request->name;
        $email = $request->email;
        $subject=$request->subject;
        $message = $request->message;

        try {
            $newMessage = Message::create([
                'name'=>$name,
                'email'=>$email,
                'subject'=>$subject,
                'text'=>$message,
                'is_answered'=>0
            ]);
            $newMessage -> save();
            return Response::json(array('status'=>201,'message'=>'Dobar insert!'));
        } catch (QueryException $e) {
            \DB::rollback();
            return Response::json(array('status'=>409,'message'=>$e->getMessage()));
        }
    }

    public function sendAnswer(Request $request){
        try {
            $id=$request->messageId;
            $id=substr($id,12);
            $name=$request->name;
            $nameSend=substr($name,6);
            $email=$request->email;
            $email=substr($email,7);

```

```

        $text=$request->text;
        $message=$request->message;

        Mail::to($email)->send(new
AnswerMail($nameSend,$text,$message)); //Mailovi se salju na mailtrap
        \DB::table('messages')
            ->where('messages.message_id','=',$id)
            ->update([
                'is_answered'=>1
            ]);

        return true;
    }catch(\Exception $e){
        return false;
    }
}
}

```

### 3.1.10 ProductController.php

```

<?php

namespace App\Http\Controllers;

use App\Models\Brand;
use App\Models\Category;
use App\Models\Product;
use App\Models\Size;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\DB;

class ProductController extends Controller
{
    public function index(Request $request){
        $model=new Product();
        $proizvodi=$model->fetchProducts($request);
        $filters=session('filter');
        $this->data['categoryId']=null;
        $this->data['brandId']=null;
        $this->data['genderId']=null;
        $this->data['search']=null;
        $this->data['price']=null;
        if($filters){
            if($filters['category']){
                $this->data['categoryId']=$filters['category'];
            }
            if($filters['brand']){
                $this->data['brandId']=$filters['brand'];
            }
            if($filters['gender']){
                $this->data['genderId']=$filters['gender'];
            }
            if($filters['search']){
                $this->data['search']=$filters['search'];
            }
            if($filters['price']){
                $this->data['price']=$filters['price'];
            }
        }
    }
}

```

```

    }
    $this->data['category']=Category::all();
    $this->data['brand']=Brand::all();
    $this->data['size']=Size::all();
    $this->data['products']=$proizvodi;
    return view('pages.shop',['data'=>$this->data]);
}

public function showOne($id){
    $model=new Product();
    $productInfo=$model->fetchOne($id);
    $productSizes=$model->fetchSizes($id);
    $productScroller=$model->fetchProductScroller();
    $this->data['productScroller']=$productScroller;
    $this->data['productInfo']=$productInfo;
    $this->data['productSizes']=$productSizes;
    return view('pages.singleProduct',['data'=>$this->data]);
}
}

```

### 3.1.11 RegisterController.php

```

<?php

namespace App\Http\Controllers;

use App\Http\Requests\RegisterRequest;
use App\Models\Info;
use App\Models\Statistic;
use App\Models\User;

class RegisterController extends Controller
{
    public function index(){
        return view('pages.register',['data'=>$this->data]);
    }

    public function register(RegisterRequest $request){
        $first_name=$request->post('first_name');
        $last_name=$request->post('last_name');
        $email=$request->post('email');
        $username=$request->post('username');
        $password=$request->post('password');
        //$confirm=$request->post('confirmPassword');
        $address=$request->post('address');
        $postal_code=$request->post('postal_code');
        $city=$request->post('city');
        $country=$request->post('country');

        $id=User::insertGetId([
            'user_id'=>null,
            'first_name'=>$first_name,
            'last_name'=>$last_name,
            'email'=>$email,
            'username'=>$username,
            'password'=>md5($password),
            'role_id'=>2,
            'is_logged_in'=>1
        ]);
    }
}

```

```

        Info::create([
            'user_info_id'=>null,
            'address'=>$address,
            'city'=>$city,
            'postal_code'=>$postal_code,
            'country'=>$country,
            'user_id'=>$id
        ]);
        $request->session()->put('user',User::where('user_id',$id)-
>first());
        Statistic::create([
            'name'=>session('user')->first_name.' '.session('user')-
>last_name,
            'email'=>session('user')->email,
            'action'=>'Register'
        ]);

        return redirect()->route('Browse products');
    }
}

```

### 3.1.12 UserController.php

```

<?php

namespace App\Http\Controllers;

use App\Http\Requests\AddUserRequest;
use App\Models\User;
use Illuminate\Http\Request;

class UserController extends Controller
{
    public function index(){
        return view('pages.admins.addUser');
    }

    public function addUser(AddUserRequest $request){
        $first_name=$request->post('first_name');
        $last_name=$request->post('last_name');
        $email=$request->post('email');
        $username=$request->post('username');
        $password=$request->post('password');
        $role=$request->post('role');
        $id=User::insert([
            'user_id'=>null,
            'first_name'=>$first_name,
            'last_name'=>$last_name,
            'email'=>$email,
            'username'=>$username,
            'password'=>md5($password),
            'role_id'=>$role,
            'is_logged_in'=>0
        ]);

        return redirect()->back()->with('success-msg', 'User added!');
    }
}

```

```

public function indexRemove() {
    $this->data['users']=User::where('role_id',2)->get();
    return view('pages.admins.removeUser',['data'=>$this->data]);
}

public function removeUser(Request $request){
    try {
        $id=$request->post('user');
        $userModel=new User();
        User::where('user_id',$id)->delete();
        $userModel->removeUserDetail($id);

        return redirect()->back()->with('success-msg', 'User
removed!');
    } catch (\Exception $e) {
        return redirect()->back()->with('error-msg', $e->getMessage());
    }
}
}

```

## 3.2 Middleware

### 3.2.1 isAdmin.php

```

<?php

namespace App\Http\Middleware;

use Closure;
use Illuminate\Http\Request;

class isAdmin
{
    /**
     * Handle an incoming request.
     *
     * @param  \Illuminate\Http\Request  $request
     * @param  \Closure(\Illuminate\Http\Request):
     (\Illuminate\Http\Response|\Illuminate\Http\RedirectResponse)  $next
     * @return \Illuminate\Http\Response|\Illuminate\Http\RedirectResponse
     */
    public function handle(Request $request, Closure $next)
    {
        if(session()->has('user')){
            if(session('user')->role_id==1){
                return $next($request);
            }
        }
        return redirect()->back();
    }
}

```

### 3.2.2 NotAuthorized.php

```

<?php

namespace App\Http\Middleware;

use Closure;
use Illuminate\Http\Request;

class NotAuthorized
{
    /**
     * Handle an incoming request.
     *
     * @param  \Illuminate\Http\Request  $request
     * @param  \Closure(\Illuminate\Http\Request):
     * (\Illuminate\Http\Response|\Illuminate\Http\RedirectResponse)  $next
     * @return \Illuminate\Http\Response|\Illuminate\Http\RedirectResponse
     */
    public function handle(Request $request, Closure $next)
    {
        if(session('user')){
            return redirect()->back();
        }
        return $next($request);
    }
}

```

### 3.2.3 Authorized.php

```

<?php

namespace App\Http\Middleware;

use Closure;
use Illuminate\Http\Request;

class Authorized
{
    /**
     * Handle an incoming request.
     *
     * @param  \Illuminate\Http\Request  $request
     * @param  \Closure(\Illuminate\Http\Request):
     * (\Illuminate\Http\Response|\Illuminate\Http\RedirectResponse)  $next
     * @return \Illuminate\Http\Response|\Illuminate\Http\RedirectResponse
     */
    public function handle(Request $request, Closure $next)
    {
        if(session()->has('user')){
            return $next($request);
        }
        return redirect()->back();
    }
}

```

### 3.2.4 CartExist.php

```
<?php

namespace App\Http\Middleware;

use App\Models\Cart;
use Closure;
use Illuminate\Http\Request;

class CartExist
{
    /**
     * Handle an incoming request.
     *
     * @param  \Illuminate\Http\Request  $request
     * @param  \Closure(\Illuminate\Http\Request): (\Illuminate\Http\Response|\Illuminate\Http\RedirectResponse)  $next
     * @return \Illuminate\Http\Response|\Illuminate\Http\RedirectResponse
     */
    public function handle(Request $request, Closure $next)
    {
        if(session()->has('user')){
            $cartModel=new Cart();
            $cart=$cartModel->fetchCart();
            if(count($cart)!=0){
                return $next($request);
            }else{
                return redirect('/products');
            }
        }elseif(session()->has('cart') && count(session('cart'))!=0){
            return $next($request);
        }else{
            return redirect('/products');
        }
    }
}
```

## 3.3 Requests

### 3.3.1 AddUserRequest.php

```
<?php

namespace App\Http\Requests;

use Illuminate\Foundation\Http\FormRequest;
use Illuminate\Validation\Rules\Password;

class AddUserRequest extends FormRequest
{
    /**
     * Determine if the user is authorized to make this request.
     *
     * @return bool
     */
    public function authorize()
    {
    }
```

```

        return true;
    }

    /**
     * Get the validation rules that apply to the request.
     *
     * @return array<string, mixed>
     */
    public function rules()
    {
        return [
            'first_name'=>'min:3|max:20|string|required',
            'last_name'=>'min:3|max:20|string|required',
            'email'=>'email:rfc,dns|string|required|unique:users,email',
            'username' =>
'required|string|regex:/\w*$\/|max:255|unique:users,username',
            'role'=>'required',
            'password'=>['required_with:confirmPassword', Password::min(8)-
>mixedCase()->numbers()],
            'confirmPassword'=>['same:password', Password::min(8)-
>mixedCase()->numbers()]
        ];
    }
}

```

### 3.3.2 LoginRequest.php

```

<?php

namespace App\Http\Requests;

use Illuminate\Foundation\Http\FormRequest;

class LoginRequest extends FormRequest
{
    /**
     * Determine if the user is authorized to make this request.
     *
     * @return bool
     */
    public function authorize()
    {
        return true;
    }

    /**
     * Get the validation rules that apply to the request.
     *
     * @return array<string, mixed>
     */
    public function rules()
    {
        return [
            'email'=>'email:rfc,dns|required',
            'password'=>'min:4|required'
        ];
    }
}

```



### 3.3.3 RegisterRequest.php

```
<?php

namespace App\Http\Requests;

use Illuminate\Foundation\Http\FormRequest;
use Illuminate\Validation\Rules\Password;

class RegisterRequest extends FormRequest
{
    /**
     * Determine if the user is authorized to make this request.
     *
     * @return bool
     */
    public function authorize()
    {
        return true;
    }

    /**
     * Get the validation rules that apply to the request.
     *
     * @return array<string, mixed>
     */
    public function rules()
    {
        return [
            'first_name' => 'min:3|max:20|string|required',
            'last_name' => 'min:3|max:20|string|required',
            'email' => 'email:rfc,dns|string|required|unique:users,email',
            'username' =>
                'required|string|regex:/\w*$/|max:255|unique:users,username',
            'address' => 'min:5|max:50|string|required',
            'city' => 'min:5|max:50|string|required',
            'postal_code' => 'min:3|max:6|string|required',
            'password' => ['required_with:confirmPassword', Password::min(8)-
                >mixedCase()->numbers()],
            'confirmPassword' => ['same:password', Password::min(8)-
                >mixedCase()->numbers()],
        ];
    }
}
```

### 3.3.4 UpdateProductRequest.php

```
<?php

namespace App\Http\Requests;

use Illuminate\Foundation\Http\FormRequest;

class UpdateProductRequest extends FormRequest
{
    /**
     * Determine if the user is authorized to make this request.
```

```

    *
    * @return bool
    */
    public function authorize()
    {
        return true;
    }

    /**
     * Get the validation rules that apply to the request.
     *
     * @return array<string, mixed>
     */
    public function rules()
    {
        return [
            'id'=>'required',
            'product_name'=>'required|max:30|min:4',
            'price'=>'required|min:1|max:9999|numeric',
            'material'=>'required|min:5|max:30',
            'coo'=>'required|min:5|max:30'
        ];
    }
}

```

## 3.4 Models

### 3.4.1 Brand.php

```

<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;

class Brand extends Model
{
    use HasFactory;

    public function fetchBrands() {
        $brands=\DB::table('brands')
            ->join('products','products.brand_id','=','brands.brand_id')
            -
>select('brands.brand_id','brands.brand_name',\DB::raw('count(products.product_id) as product_number'))
            ->groupBy('brands.brand_id','brands.brand_name')->get();

        return $brands;
    }

    public function fetchBrandImage() {
        \DB::statement("SET sql_mode=(SELECT REPLACE(@@sql_mode,'ONLY_FULL_GROUP_BY',''));");
        $brands=\DB::table('products')
            -
>join('pictures','products.product_id','=','pictures.product_id')

```

```

        ->select('products.brand_id','pictures.src','pictures.alt')
        ->groupBy('products.brand_id')->get();
        \DB::statement("SET sql_mode=(SELECT CONCAT(@@sql_mode,
        ',ONLY_FULL_GROUP_BY'))");
        return $brands;
    }
}

```

### 3.4.2 Cart.php

```

<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;

class Cart extends Model
{
    use HasFactory;

    public function cartProducts() {
        $products=\DB::table('products')
        -
        >join('pictures','products.product_id','=','pictures.product_id')
        ->join('prices','prices.product_id','=','products.product_id')
        -
        >select('products.product_id','products.product_name','pictures.src','pictures.alt','prices.newPrice')
        ->get();

        return $products;
    }

    public function fetchCart(){
        $user_id=session('user')->user_id;
        $cart=\DB::table('cart')
        ->where('cart.user_id','=',$user_id)
        ->get();

        return $cart;
    }

    public function existInCart($size,$product_id,$user_id){
        $product=\DB::table('cart')
        ->where('cart.user_id','=',$user_id)
        ->where('cart.size','=',$size)
        ->where('cart.product_id','=',$product_id)
        ->select('*')->get();

        return count($product);
    }

    public function removeFromCart($product_id,$size){
        $user_id=session('user')->user_id;
        $product=\DB::table('cart')
        ->where('cart.user_id','=',$user_id)
        ->where('cart.size','=',$size)
        ->where('cart.product_id','=',$product_id)
    }
}

```

```

        ->delete();

        return $product;
    }

    public function oldQuantity($product_id,$size,$user_id) {
        $qtyOld=\DB::table('cart')
            ->where('cart.product_id','=', $product_id)
            ->where('cart.size','=', $size)
            ->where('cart.user_id','=', $user_id)
            ->select('cart.qty')
            ->first();

        return $qtyOld;
    }

    public function updateQuantity($product_id,$size,$user_id,$qty) {
        \DB::table('cart')
            ->where('cart.product_id','=', $product_id)
            ->where('cart.size','=', $size)
            ->where('cart.user_id','=', $user_id)
            ->update(['cart.qty'=>$qty]);
    }

    public function insertIntoCart($product_id,$size,$user_id,$qty) {
        \DB::table('cart')->insert([
            'user_id' => $user_id,
            'product_id' => $product_id,
            'qty'=>$qty,
            'size'=>$size
        ]);
    }
}

```

### 3.4.3 Category.php

```

<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;

class Category extends Model
{
    use HasFactory;
}

```

### 3.4.4 Checkout.php

```

<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;

```

```

class Checkout extends Model
{
    use HasFactory;

    public function checkoutProducts(){
        $products=\DB::table('products')
            ->join('prices','prices.product_id','=', 'products.product_id')
            -
>select('products.product_id','products.product_name','prices.newPrice')
            ->get();

        return $products;
    }
    public function fetchCart(){
        $user_id=session('user')->user_id;
        $cart=\DB::table('cart')
            ->where('cart.user_id','=', $user_id)
            ->get();

        return $cart;
    }

    public function emptyCart(){
        $user_id=session('user')->user_id;
        $cart=\DB::table('cart')
            ->where('cart.user_id','=', $user_id)
            ->delete();

        return $cart;
    }

    public function fetchUser(){
        $user_id=session('user')->user_id;
        $user=\DB::table('users')
            ->join('infos','users.user_id','=', 'infos.user_id')
            ->where('users.user_id','=', $user_id)
            -
>select('infos.city','infos.postal_code','infos.address','infos.country')
            ->first();

        return $user;
    }

    public function
insertOrder($first_name,$last_name,$email,$postal_code,$country,$city,$address,$cart){
        $subtotal=0;
        $products=\DB::table('products')
            -
>join('prices','products.product_id','=', 'prices.product_id')
            ->select('products.product_id','prices.newPrice')
            ->get();
        for($i=0;$i<count($cart);$i++){
            for($j=0;$j<count($products);$j++){
                if($cart[$i]->product_id==$products[$j]->product_id){
                    $subtotal=$subtotal+($cart[$i]->qty*$products[$j]-
>newPrice);
                    break;
                }
            }
        }
    }
}

```

```

    }
    $total=$subtotal+10;
    $id=\DB::table('receipts')
        ->insertGetId([
            'first_name'=>$first_name,
            'last_name'=>$last_name,
            'address'=>$address,
            'city'=>$city,
            'zip'=>$postal_code,
            'email'=>$email,
            'country'=>$country,
            'subtotal'=>$subtotal,
            'shipping_fee'=>10,
            'total'=>$total
        ]);
    for ($i=0;$i<count($cart);$i++) {
        for ($j=0;$j<count($products);$j++) {
            if ($cart[$i]->product_id==$products[$j]->product_id) {
                \DB::table('receipt_item')
                    ->insert([
                        'product_id'=>$products[$j]->product_id,
                        'price'=>$products[$j]->newPrice,
                        'size'=>$cart[$i]->size,
                        'quantity'=>$cart[$i]->qty,
                        'receipt_id'=>$id
                    ]);
                break;
            }
        }
    }

    return true;
}
}

```

### 3.4.5 Info.php

```

<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;

class Info extends Model
{
    use HasFactory;

    protected $guarded = [];
}

```

### 3.4.6 Message.php

```
<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;

class Message extends Model
{
    use HasFactory;

    protected $primaryKey='message_id';
    protected $guarded = ['message_id','created_at'];
}
```

### 3.4.7 Navigation.php

```
<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;

class Navigation extends Model
{
    use HasFactory;
}
```

### 3.4.8 Product.php

```
<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\DB;

class Product extends Model
{
    use HasFactory;
    public function fetchProducts(Request $request){
        $proizvodi= DB::table('products')
        -
        >join('pictures','products.product_id','=','pictures.product_id')
        ->join('prices','products.product_id','=','prices.product_id');
        if($request->has('category')){
            $proizvodi=$proizvodi->whereIn('products.category_id',$request-
            >get('category'));
        }
    }
}
```

```

    }
    if($request->has('brand')){
        $proizvodi=$proizvodi->whereIn('products.brand_id',$request-
>get('brand'));
    }
    if($request->has('gender')){
        $proizvodi=$proizvodi->whereIn('products.gender_id',$request-
>get('gender'));
    }
    if($request->has('search')){
        $proizvodi=$proizvodi-
>where('products.product_name','like','%'.$request->get('search').'%');
    }

    if($request->has('price')){
        $price=$request->get('price');
        if($price==1){
            $proizvodi=$proizvodi-
>WhereBetween('prices.newPrice',[0,20]);
        }
        if($price==2){
            $proizvodi=$proizvodi-
>WhereBetween('prices.newPrice',[20,40]);
        }
        if($price==3){
            $proizvodi=$proizvodi-
>WhereBetween('prices.newPrice',[40,60]);
        }
    }
    if($request->has('gender') || $request->has('brand') || $request-
>has('category') || $request->has('search') || $request->has('price')){
        session()->put('filter',[
            'brand'=>$request->get('brand'),
            'category'=>$request->get('category'),
            'gender'=>$request->get('gender'),
            'search'=>$request->get('search'),
            'price'=>$request->get('price')
        ]);
    }
    $proizvodi=$proizvodi-
>select('products.*','prices.oldPrice','prices.newPrice','pictures.src','pi
ctures.alt');
    return $proizvodi->paginate(15)->withQueryString();
}

public function fetchOne($id){
    $productInfo=\DB::table('products')
    -
>join('pictures','products.product_id','=','pictures.picture_id')
    ->join('prices','products.product_id','=','prices.product_id')
    -
>join('categories','categories.category_id','=','products.category_id')
    ->join('brands','brands.brand_id','=','products.brand_id')
    ->join('genders','genders.gender_id','=','products.gender_id')
    ->where('products.product_id','=',$id)
    -
>select('products.*','prices.oldPrice','prices.newPrice','pictures.src','pi
ctures.alt','genders.gender_name','brands.brand_name','categories.category_
name')
    ->first();
}

```



```

        return $productInfo;
    }

    public function fetchProductForUpdate($id) {
        $product=\DB::table('products')
            ->join('prices','products.product_id','=', 'prices.product_id')
            ->where('products.product_id','=', $id)
            -
>select('products.product_id','products.product_name','prices.newPrice','pr
oducts.material','products.coo')
            ->first();

        return $product;
    }

    public function fetchSizes($id) {
        $productSizes=\DB::table('sizes')
            -
>join('products_sizes','products_sizes.size_id','=', 'sizes.size_id')
            ->where('products_sizes.product_id','=', $id)
            ->select('sizes.size_name') ->get();

        return $productSizes;
    }

    public function fetchProductScroller() {
        $products=\DB::table('products')
            -
>join('pictures','pictures.product_id','=', 'products.product_id')
            ->join('prices','prices.product_id','=', 'products.product_id')
            ->where('products.sale','=', '1')
            -
>select('products.product_id','products.product_name','pictures.src','pictu
res.alt','prices.newPrice','prices.oldPrice') ->get();
        return $products;
    }

    public function fetchProductsHome() {
        $products=\DB::table('products')
            -
>join('pictures','pictures.product_id','=', 'products.product_id')
            ->join('prices','prices.product_id','=', 'products.product_id')
            -
>select('products.product_id','products.product_name','pictures.src','pictu
res.alt','prices.newPrice','prices.oldPrice')
            ->inRandomOrder()
            ->limit(8)
            ->get();
        return $products;
    }

    public function fetchProductsInfo() {
        $products=\DB::table('products')
            -
>join('categories','products.category_id','=', 'categories.category_id')
            ->join('brands','products.brand_id','=', 'brands.brand_id')
            ->join('genders','genders.gender_id','=', 'products.gender_id')
            ->join('prices','prices.product_id','=', 'products.product_id')
            -
>select('products.product_id','products.product_name','categories.category_
name','brands.brand name','genders.gender name','prices.newPrice','products

```

```

.sale', 'products.inStock')
    ->get();
    return $products;
}

public function updateProduct($product_name, $price, $id, $material, $coo) {
    $oldPrice=\DB::table('prices')
        ->where('prices.product_id','=', $id)
        ->select('prices.newPrice')
        ->first();
    $oldPrice=$oldPrice->newPrice;
    if($oldPrice!=$price){
        $product=\DB::table('products')
            -
>join('prices', 'products.product_id','=', 'prices.product_id')
            ->where('products.product_id','=', $id)
            ->update([
                'prices.oldPrice'=>$oldPrice,
                'prices.newPrice'=>$price,
                'products.product_name'=>$product_name,
                'products.material'=>$material,
                'products.coo'=>$coo
            ]);
    }else{
        $product=\DB::table('products')
            -
>join('prices', 'products.product_id','=', 'prices.product_id')
            ->where('products.product_id','=', $id)
            ->update([
                'products.product_name'=>$product_name,
                'products.material'=>$material,
                'products.coo'=>$coo
            ]);
    }

    return $product;
}
}

```

### 3.4.9 Receipt.php

```

<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;

class Receipt extends Model
{
    use HasFactory;

    public function ShowEarnings(){
        $total=\DB::table('receipts')
            ->sum('receipts.total');

        return $total;
    }
}

```

```

    public function showOrders() {
        $count=\DB::table('receipts')
            ->count('receipts.receipt_id');

        return $count;
    }

    public function fetchSingleOrder($id){
        $orderDetails=\DB::table('receipt_item')
            -
>join('products','products.product_id','=','receipt_item.product_id')
            ->where('receipt_item.receipt_id','=',$id)
            -
>select('receipt_item.receipt_id','products.product_id','products.product_n
ame','receipt_item.price','receipt_item.size','receipt_item.quantity')
            ->get();

        return $orderDetails;
    }
}

```

#### 3.4.10 Size.php

```

<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;

class Size extends Model
{
    use HasFactory;
}

```

#### 3.4.11 Statistic.php

```

<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;

class Statistic extends Model
{
    use HasFactory;

    protected $guarded=['statistic_id'];
}

```

### 3.4.12 User.php

```
<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;

class User extends Model
{
    use HasFactory;

    protected $guarded = [];
    protected $hidden = ['password'];

    public function updateLogin($user_id) {
        $user=\DB::table('users')
            ->where('users.user_id','=',$user_id)
            ->update(['is_logged_in'=>1]);
        return $user;
    }

    public function updateLogout($user_id) {
        $user=\DB::table('users')
            ->where('users.user_id','=',$user_id)
            ->update(['is_logged_in'=>0]);
        return $user;
    }

    public function userCount() {
        $userCount=\DB::table('users')
            ->count('users.user_id');

        return $userCount;
    }

    public function removeUserDetail($id) {
        $user=\DB::table('infos')
            ->where('infos.user_id','=',$id)
            ->delete();

        return $user;
    }
}
```

## 3.5 JavaScript

### 3.5.1 main.js

```
(function ($) {  
    "use strict";  
  
    // Dropdown on mouse hover  
    $(document).ready(function () {  
        function toggleNavbarMethod() {  
            if ($(window).width() > 992) {  
                $('.navbar .dropdown').on('mouseover', function () {  
                    $('.dropdown-toggle', this).trigger('click');  
                }).on('mouseout', function () {  
                    $('.dropdown-toggle', this).trigger('click').blur();  
                });  
            } else {  
                $('.navbar .dropdown').off('mouseover').off('mouseout');  
            }  
        }  
        toggleNavbarMethod();  
        $(window).resize(toggleNavbarMethod);  
    });  
  
    // Back to top button  
    $(window).scroll(function () {  
        if ($(this).scrollTop() > 100) {  
            $('.back-to-top').fadeIn('slow');  
        } else {  
            $('.back-to-top').fadeOut('slow');  
        }  
    });  
    $('.back-to-top').click(function () {  
        $('html, body').animate({scrollTop: 0}, 1500, 'easeInOutExpo');  
        return false;  
    });  
  
    // Vendor carousel  
    $('.vendor-carousel').owlCarousel({  
        loop: true,  
        margin: 29,  
        nav: false,  
        autoplay: true,  
        smartSpeed: 1000,  
        responsive: {  
            0:{  
                items:2  
            },  
            576:{  
                items:3  
            },  
            768:{  
                items:4  
            },  
            992:{  
                items:5  
            },  
            1200:{
```

```

        items:6
    }
}
});

// Related carousel
$('.related-carousel').owlCarousel({
    loop: true,
    margin: 29,
    nav: false,
    autoplay: true,
    smartSpeed: 1000,
    responsive: {
        0:{
            items:1
        },
        576:{
            items:2
        },
        768:{
            items:3
        },
        992:{
            items:4
        }
    }
});

// Product Quantity
$('.quantity button').on('click', function () {
    var button = $(this);
    var oldValue = button.parent().parent().find('input').val();
    if (button.hasClass('btn-plus')) {
        var newVal = parseFloat(oldValue) + 1;
    } else {
        if (oldValue > 0) {
            var newVal = parseFloat(oldValue) - 1;
        } else {
            newVal = 0;
        }
    }
    button.parent().parent().find('input').val(newVal);
});
})(jQuery);

```

### 3.5.2 custom.js

```

window.onload=function () {

    var url = window.location.pathname;
    url = url.substring(url.lastIndexOf('/')+1);
    if(url=='/contact'){
        $("#sendMessageButton").click(function () {
            sendMessage();
        });
    }
}

```

```

if(url=='/cart' || url=='/checkout'){
    fillTotal();
}

$("#submitOrder").click(function (){
    submitOrder();
});

$("#sendAnswer").click(function (){
    sendMessageToEmail();
});

$.ajaxSetup({
    headers: {
        'X-CSRF-TOKEN': $('meta[name="csrf-token"]').attr('content')
    }
});

function sendMessageToEmail(){
    let messageId=$('#messageId').text();
    let name=$('#answerName').text();
    let email=$('#answerEmail').text();
    let message=$('#answerMessage').text();
    let text=$('#answer').val();
    if(text==" " || !text.trim()){
        let fieldText=document.getElementById('textError');
        fieldText.classList.remove('hidden');
        fieldText.innerText='Enter answer';
    }else{
        let fieldText=document.getElementById('textError');
        fieldText.classList.add('hidden');

        let data={
            messageId:messageId,
            name:name,
            email:email,
            message:message,
            text:text
        }
        $.ajax({
            url:'/answermessage',
            method:'POST',
            data:data,
            dataType:'JSON',
            success:function(result){
                let status=document.getElementById('status');
                status.innerHTML='Answer sent.';
                status.classList.add('text-success');
                status.classList.remove('hidden');
                const timer=setTimeout(function(){
                    status.classList.remove('add');
                },2000);
                const timer1=setTimeout(function(){
                    window.location.href='/adminpanel';
                },2000);
            },
            error:function(xhr){
                console.log(xhr);
                let status=document.getElementById('status');
                status.innerHTML='An error occurred';
            }
        });
    }
}

```

```

        status.classList.add('text-danger');
        status.classList.remove('hidden');
        const timer=setTimeout(function(){
            status.classList.remove('add');
        },2000);
    }
    });
}

function submitOrder(){
    checkFirstName();
    checkLastName();
    checkEmail();
    checkAddress();
    checkCity();
    checkPostalCode();
    let country=$('#country').val();
    if(country==" " || !country.trim()){
        let fieldCountry=document.getElementById('errorCountry');
        fieldCountry.classList.remove('hidden');
        fieldCountry.classList.add('text-danger');
        fieldCountry.innerText='Select country.';
    }else{
        let fieldCountry=document.getElementById('errorCountry');
        fieldCountry.classList.add('hidden');
        fieldCountry.innerText='';
    }

    if(checkFirstName() && checkLastName() && checkEmail() &&
    checkAddress() && checkCity() && checkPostalCode() && country.trim()){
        let data={
            first_name:$('#first_name').val(),
            last_name:$('#last_name').val(),
            email:$('#email').val(),
            country:$('#country').val(),
            address:$('#address').val(),
            city:$('#city').val(),
            postal_code:$('#postal_code').val()
        }

        $.ajax({
            url:'/confirmorder',
            type:'POST',
            data:data,
            dataType:'JSON',
            success:function (result){
                let status=document.getElementById('status');
                status.innerHTML='Order sent.';
                status.classList.add('text-success');
                status.classList.remove('hidden');
                const timer=setTimeout(function(){
                    status.classList.remove('add');
                },2000);
                const timer1=setTimeout(function(){
                    window.location.href='/';
                },2000);
            },
            error:function (xhr){
                console.log(xhr);
                let status=document.getElementById('status');
                status.innerHTML='An error occurred!';
            }
        });
    }
}

```



```

        status.classList.add('text-danger');
        status.classList.remove('hidden');
        const timer=setTimeout(function(){
            status.classList.remove('add');
        },2000);
    }
    });
}

let regName=/^[A-ZČĆŠĐŽ]{1}[a-zčćšđž]{2,12}$/;
function checkFirstName(){
    let firstName=$("#first_name").val();
    if (!regName.test(firstName)) {
        let fieldName = document.getElementById("errorFirstName");
        if (firstName == "" || !firstName.trim()) {
            fieldName.innerHTML = "Enter your first name!";
        } else {
            fieldName.innerHTML = "Invalid name format!";
        }
        fieldName.style.color="red";
        fieldName.classList.remove("hidden");
        return false;
    }
    if (regName.test(firstName)) {
        let fieldName = document.getElementById("errorFirstName");
        fieldName.classList.add("hidden");
        return true;
    }
}

function checkLastName(){
    let lastName=$("#last_name").val();
    if (!regName.test(lastName)) {
        let fieldLastName = document.getElementById("errorLastName");
        if (lastName == "" || !lastName.trim()) {
            fieldLastName.innerHTML = "Enter your first name!";
        } else {
            fieldLastName.innerHTML = "Invalid name format!";
        }
        fieldLastName.style.color="red";
        fieldLastName.classList.remove("hidden");
        return false;
    }
    if (regName.test(lastName)) {
        let fieldLastName = document.getElementById("errorLastName");
        fieldLastName.classList.add("hidden");
        return true;
    }
}

function checkAddress(){
    let regAddress= /^[A-ZČĆŠĐŽ]{1}[a-zčćšđž]{2,15}(\s[A-ZČĆŠĐŽa-zčćšđž0-9]{1,15})+$/;
    let address=document.getElementById("address").value;
    if (!regAddress.test(address)) {
        let fieldAddress = document.getElementById("errorAddress");
        if (address == "" || !address.trim())
            fieldAddress.innerHTML = "Enter your address";
        else fieldAddress.innerHTML = "Invalid address format!";
        fieldAddress.style.color="red";
    }
}

```

```

        fieldAddress.classList.remove("hidden");
        return false;
    }
    if (regAddress.test(address)) {
        let fieldAddress = document.getElementById("errorAddress");
        fieldAddress.classList.add("hidden");
        return true;
    }
}

function checkCity() {
    let regCity=/^[a-zA-Z\u0080-\u024F]+(?:[\s-][a-zA-Z\u0080-\u024F]+)*$/;
    let city=document.getElementById("city").value;
    if (!regCity.test(city)) {
        let fieldCity = document.getElementById("errorCity");
        if (city == "" || !city.trim())
            fieldCity.innerHTML = "Enter city name";
        else fieldCity.innerHTML = "Invalid city name!";
        fieldCity.style.color="red";
        fieldCity.classList.remove("hidden");
        return false;
    }
    if (regCity.test(city)) {
        let fieldCity = document.getElementById("errorCity");
        fieldCity.classList.add("hidden");
        return true;
    }
}

function checkPostalCode() {
    let regZip=/^\d{5}$/;
    let postal_code=$("#postal_code").val();
    if (!regZip.test(postal_code)) {
        let fieldZip = document.getElementById("errorZip");
        if (postal_code == "" || !postal_code.trim())
            fieldZip.innerHTML = "Enter postcode/ZIP!";
        else fieldZip.innerHTML = "Invalid postcode/ZIP!";
        fieldZip.style.color="red";
        fieldZip.classList.remove("hidden");
        return false;
    }
    if (regZip.test(postal_code)) {
        let fieldZip = document.getElementById("errorZip");
        fieldZip.classList.add("hidden");
        return true;
    }
}

function fillTotal() {
    let s=0;
    let price=$("#price");
    if(price.length!=0) {
        for(let i=0;i<price.length;i++){
            price[i]=price[i].innerHTML;
            s=s+parseInt(price[i].substring(1));
        }
        let subtotal=document.getElementById('subtotal');
        subtotal.innerHTML='$'+s+'.00';
        let total=document.getElementById('total');
        let st=s+10;
        total.innerHTML='$'+st+'.00';
    }
}

```

```

    }

    }

    function sendMessage() {
        checkName();
        checkEmail();
        let subject=document.getElementById('subject').value;
        if(!subject.trim() || subject == ""){
            let errorSubject=document.getElementById('errorSubject');
            errorSubject.innerHTML = "Enter subject!";
            errorSubject.classList.add('mb-1');
            errorSubject.style.color="red";
            errorSubject.classList.remove("hidden");
        }else{
            let errorSubject=document.getElementById('errorSubject');
            errorSubject.classList.add("hidden");
        }
        let message=document.getElementById('message').value;
        if(!message.trim() || message == ""){
            let errorMessage=document.getElementById('errorMessage');
            errorMessage.innerHTML = "Enter message!";
            errorMessage.classList.add('mb-1');
            errorMessage.style.color="red";
            errorMessage.classList.remove("hidden");
        }else{
            let errorMessage=document.getElementById('errorMessage');
            errorMessage.classList.add("hidden");
        }
        if(checkName() && checkEmail() && subject.trim() && subject != ""
        && message.trim() && message != ""){
            let data={
                name:$("#name").val(),
                email:$("#email").val(),
                subject:subject,
                message:message
            }

            $.ajax({
                url: '/messages',
                type: 'POST',
                data: data,
                dataType: 'JSON',
                success: function (result) {
                    let status=document.getElementById('status');
                    status.classList.add('text-success');
                    status.classList.add('mt-2');
                    status.classList.remove('hidden');
                    status.innerHTML="Message sent.";
                    const timer=setTimeout(function(){
                        window.location.href = '/contact';
                    },2000);
                },
                error: function (xhr) {
                    console.log(xhr);
                    let status=document.getElementById('status');
                    status.classList.add('text-danger');
                    status.classList.add('mt-2');
                    status.classList.remove('hidden');
                    status.innerHTML="Message not sent.";
                    const timer=setTimeout(function(){
                        status.classList.add('hidden');
                    },2000);
                }
            });
        }
    }
}

```

```

        },2000);
    }
    });
}

function checkName() {
    let name=document.getElementById('name').value;
    let regName= /^[A-ZČĆŠĐŽ][a-zčćšđž]{2,15}(\s[A-ZČĆŠĐŽ][a-zčćšđž]{2,15})?(\s[A-ZČĆŠĐŽ][a-zčćšđž]{2,20})\s*$/;
    name.replace(/\s\s+/g, " ");
    if (!regName.test(name)) {
        let errorName = document.getElementById("errorName");
        if (name == "" || !name.trim()) {
            errorName.innerHTML = "Enter your name and last name!";
        } else {
            errorName.innerHTML = "Invalid name format!";
        }
        errorName.style.color="red";
        errorName.classList.add('mb-1');
        errorName.classList.remove("hidden");
        return false;
    }
    if (regName.test(name)) {
        let errorName = document.getElementById("errorName");
        errorName.classList.add("hidden");
        return true;
    }
}

function checkEmail(){
    let email=document.getElementById('email').value;
    let regEmail=/^[\\w-\\.]+@([\\w-]+\\.)+[\\w-]{2,4}$/;
    if (!regEmail.test(email)) {
        let errorEmail = document.getElementById("errorEmail");
        if (email == "" || !email.trim())
            errorEmail.innerHTML = "Enter email!";
        else errorEmail.innerHTML = "Invalid email format!";
        errorEmail.style.color="red";
        errorEmail.classList.add('mb-1');
        errorEmail.classList.remove("hidden");
        return false;
    }
    if (regEmail.test(email)) {
        let errorEmail = document.getElementById("errorEmail");
        errorEmail.classList.add("hidden");
        return true;
    }
}

function dodajUkorpu(product_id) {
    var size=checkSizeSelected();
    var qty=checkQuantity();
    let product={
        size:size,
        qty:parseInt(qty),
        product_id:product_id
    }
}

```

```

    if(size && qty){
        $.ajax({
            url: '/addcart',
            type: 'POST',
            data: product,
            dataType: 'JSON',
            success: function (result) {
                let status=document.getElementById('status');
                status.classList.add('text-success');
                status.classList.add('mt-2');
                status.innerHTML="Added to cart.";
            },
            error: function (xhr) {
                console.log(xhr);
                let status=document.getElementById('status');
                status.classList.add('text-danger');
                status.classList.add('mt-2');
                status.innerHTML="An error occured.";
            }
        });
    }
}

function checkSizeSelected(){
    if($(".size:checked").length!=0){
        for(let i=0;i<($(".size").length);i++){
            if($(".size:checked")){

if(!document.getElementById("sizes").classList.contains("hidden")){

document.getElementById("sizes").classList.add("hidden");
                }
                return $(".size:checked").val();
            }
        }
    }else{
        document.getElementById("sizes").classList.remove("hidden");
        return false;
    }
}

function checkQuantity(){
    let qty=document.getElementById("qty").value;
    if(qty<1 || qty>99){

document.getElementById("quantityError").classList.remove("hidden");
        return false;
    }else{
        document.getElementById("quantityError").classList.add("hidden");
        return qty;
    }
}

function deleteProductFromCart(size,product_id){
    let data={
        product_id:product_id,
        size:size
    }
    console.log(data);
    $.ajax({

```

```

        type: 'POST',
        url: '/deletefromcart',
        data: data,
        dataType: 'JSON',
        success: function() {
            let field=document.getElementById('status');
            field.classList.add('text-success');
            field.classList.remove('hidden');
            field.innerHTML='Removed from cart.';
            const timer=setTimeout(function(){
                field.classList.add('hidden');
            },2000);
            window.location.href='/cart';
        },
        error: function(xhr) {
            console.log(xhr);
            let field=document.getElementById('status');
            field.classList.add('text-danger');
            field.classList.remove('hidden');
            field.innerHTML='An error occurred.';
            const timer=setTimeout(function(){
                field.classList.add('hidden');
            },2000);
        }
    });
}

```

## 3.6 Views

### 3.6.1 Fixed

#### 3.6.1.1 Admins

##### 3.6.1.1.1 footer.blade.php

```

<!-- Footer -->
<footer class="sticky-footer bg-white">
    <div class="container my-auto">
        <div class="copyright text-center my-auto">
            <span>Copyright &copy; Flex Shop 2022</span>
        </div>
    </div>
</footer>
<!-- End of Footer -->

```

##### 3.6.1.1.2 head.blade.php

```

<head>

    <meta charset="utf-8">
    <meta http-equiv="X-UA-Compatible" content="IE=edge">
    <meta name="viewport" content="width=device-width, initial-scale=1,
shrink-to-fit=no">
    <meta name="description" content="@yield('description')">
    <meta name="author" content="Nenad Jevtic 60/20">

    <title>@yield('title')</title>

```

```

<!-- Favicon -->
<link href="{{asset('assets/img/favicon.ico')}}" rel="icon">
<!-- Custom styles for this page -->
<meta name="csrf-token" content="{{ csrf_token() }}">
<!-- Custom fonts for this template-->
<link href="{{asset('assets/admins/vendor/fontawesome-free/css/all.min.css')}}" rel="stylesheet" type="text/css">
<link

href="https://fonts.googleapis.com/css?family=Nunito:200,200i,300,300i,400,400i,600,600i,700,700i,800,800i,900,900i"
rel="stylesheet">

<!-- Custom styles for this template-->
<link href="{{asset('assets/admins/css/sb-admin-2.min.css')}}"
rel="stylesheet">

</head>

```

### 3.6.1.1.3 navbar.blade.php

```

<!-- Topbar -->
<nav class="navbar navbar-expand navbar-light bg-white topbar mb-4 static-top shadow">

    <!-- Sidebar Toggle (Topbar) -->
    <button id="sidebarToggleTop" class="btn btn-link d-md-none rounded-circle mr-3">
        <i class="fa fa-bars"></i>
    </button>

    {{--
        <!-- Topbar Search -->
        <form
            class="d-none d-sm-inline-block form-inline mr-auto ml-md-3 my-2 my-md-0 mw-100 navbar-search">
            <div class="input-group">
                <input type="text" class="form-control bg-light border-0 small" placeholder="Search for..."
                    aria-label="Search" aria-describedby="basic-addon2">
                <div class="input-group-append">
                    <button class="btn btn-primary" type="button">
                        <i class="fas fa-search fa-sm"></i>
                    </button>
                </div>
            </div>
        </form>--}}

    <!-- Topbar Navbar -->
    <ul class="navbar-nav ml-auto">

        <!-- Nav Item - Search Dropdown (Visible Only XS) -->
        <li class="nav-item dropdown no-arrow d-sm-none">
            <a class="nav-link dropdown-toggle" href="#"
                id="searchDropdown" role="button"
                data-toggle="dropdown" aria-haspopup="true" aria-expanded="false">
                <i class="fas fa-search fa-fw"></i>
            </a>

```

```

        <!-- Dropdown - Messages -->
        <div class="dropdown-menu dropdown-menu-right p-3 shadow
animated--grow-in"
            aria-labelledby="searchDropdown">
            <form class="form-inline mr-auto w-100 navbar-search">
                <div class="input-group">
                    <input type="text" class="form-control bg-light
border-0 small"
                        placeholder="Search for..." aria-
label="Search"
                        aria-describedby="basic-addon2">
                    <div class="input-group-append">
                        <button class="btn btn-primary" type="button">
                            <i class="fas fa-search fa-sm"></i>
                        </button>
                    </div>
                </div>
            </form>
        </div>
    </li>

    <div class="topbar-divider d-none d-sm-block"></div>

    <!-- Nav Item - User Information -->
    <li class="nav-item dropdown no-arrow">
        <a class="nav-link dropdown-toggle" href="#" id="userDropdown"
role="button"
            data-toggle="dropdown" aria-haspopup="true" aria-
expanded="false">
            <span class="mr-2 d-none d-lg-inline text-gray-600
small">{{session('user')->first_name.' '.session('user')->
last_name}}</span>
        </a>
        <!-- Dropdown - User Information -->
        <div class="dropdown-menu dropdown-menu-right shadow animated--
grow-in"
            aria-labelledby="userDropdown">
            <a class="dropdown-item" href="/">
                Home page
            </a>
            <a class="dropdown-item" href="/logout">
                <i class="fas fa-sign-out-alt fa-sm fa-fw mr-2 text-
gray-400"></i>
                Logout
            </a>
        </div>
    </li>

</ul>

</nav>
<!-- End of Topbar -->

```

#### 3.6.1.1.4 scripts.blade.php

```

<script
src="{{asset('assets/admins/vendor/jquery/jquery.min.js')}}"></script>
<script

```



```

src="{{asset('assets/admins/vendor/bootstrap/js/bootstrap.bundle.min.js')}}"
"></script>

<script src="https://kit.fontawesome.com/41bd7e5f70.js"
crossorigin="anonymous"></script>
<!-- Core plugin JavaScript-->
<script src="{{asset('assets/admins/vendor/jquery-
easing/jquery.easing.min.js')}}"></script>
<script src="{{asset('assets/js/custom.js')}}"></script>
<!-- Custom scripts for all pages-->
<script src="{{asset('assets/admins/js/sb-admin-2.min.js')}}"></script>

<!-- Page level plugins -->
<script
src="{{asset('assets/admins/vendor/datatables/jquery.dataTables.min.js')}}"
></script>
<script
src="{{asset('assets/admins/vendor/datatables/dataTables.bootstrap4.min.js'
)}}"></script>

<!-- Page level custom scripts -->
<script src="{{asset('assets/admins/js/demo/datatables-
demo.js')}}"></script>

```

### 3.6.1.1.5 sidebar.blade.php

```

<!-- Sidebar -->
<ul class="navbar-nav bg-gradient-primary sidebar sidebar-dark accordion"
id="accordionSidebar">

    <!-- Sidebar - Brand -->
    <a class="sidebar-brand d-flex align-items-center justify-content-
center" href="/">
        <div class="sidebar-brand-icon rotate-n-15">
            <i class="fa fa-sharp fa-solid fa-gears"></i>
        </div>
        <div class="sidebar-brand-text mx-3">Flex Shop <sup>Admin
panel</sup></div>
    </a>

    <!-- Divider -->
    <hr class="sidebar-divider my-0">

    <!-- Nav Item - Dashboard -->
    <li class="nav-item active">
        <a class="nav-link" href="/adminpanel">
            <i class="fas fa-fw fa-tachometer-alt"></i>
            <span>Dashboard</span></a>
    </li>

    <!-- Divider -->
    <hr class="sidebar-divider">

    <!-- Heading -->
    <div class="sidebar-heading">
        Actions
    </div>

    <!-- Nav Item - Pages Collapse Menu -->

```

```

        <li class="nav-item">
            <a class="nav-link collapsed" href="#" data-toggle="collapse" data-
target="#collapseTwo"
                aria-expanded="true" aria-controls="collapseTwo">
                <i class="fa fa-solid fa-user"></i>
                <span>Users</span>
            </a>
            <div id="collapseTwo" class="collapse" aria-labelledby="headingTwo"
data-parent="#accordionSidebar">
                <div class="bg-white py-2 collapse-inner rounded">
                    <h6 class="collapse-header">Actions:</h6>
                    <a class="collapse-item" href="/adduser">Add user</a>
                    <a class="collapse-item" href="/removeuser">Remove user</a>
                </div>
            </div>
        </li>

        <!-- Divider -->
        <hr class="sidebar-divider">

        <!-- Nav Item - Charts -->
        <li class="nav-item">
            <a class="nav-link" href="/orders">
                <i class="fa fa-solid fa-receipt"></i>
                <span>Orders</span></a>
        </li>

        <!-- Divider -->
        <hr class="sidebar-divider d-none d-md-block">

        <!-- Sidebar Toggler (Sidebar) -->
        <div class="text-center d-none d-md-inline">
            <button class="rounded-circle border-0"
id="sidebarToggle"></button>
        </div>

    </ul>
    <!-- End of Sidebar -->

```

### 3.6.1.2 Users

#### 3.6.1.2.1 footer.blade.php

```

<div class="container-fluid bg-dark text-secondary mt-5 pt-5">
    <div class="row px-xl-5 pt-5">
        <div class="col-lg-3 col-md-12 mb-5 pr-3 pr-xl-5">
            <h5 class="text-secondary text-uppercase mb-4">Get In
Touch</h5>
            {{--
                <p class="mb-4">No dolore ipsum accusam no lorem. Invidunt
sed clita kasd clita et et dolor sed dolor. Rebum tempor no vero est magna
amet no</p>--}}
            <p class="mb-2 pt-4"><i class="fa fa-map-marker-alt text-
primary mr-3"></i>Zdravka Čelara 16, Beograd, Srbija</p>
            <p class="mb-2"><i class="fa fa-envelope text-primary mr-
3"></i>flexshop_info@gmail.com</p>
            <p class="mb-0"><i class="fa fa-phone-alt text-primary mr-
3"></i>011 123 4567</p>
        </div>
        <div class="col-lg-9 col-md-12">
            <div class="row justify-content-between">
                <div class="col-md-5 mb-5 w-100">

```

```

Mission</h5>
    <h5 class="text-secondary text-uppercase mb-4">Our
    <p class="w-75">
        To understand and reconstruct the newest trends in
        fashion for men and women.
    </p>
    <p class="w-75">
        Flex shop aims to dress dynamic people and fashion
        lovers who are young at heart.
    </p>
    {{--<div class="d-flex flex-column justify-content-
start">
        <a class="text-secondary mb-2" href="#"><i
class="fa fa-angle-right mr-2"></i>Home</a>
        <a class="text-secondary mb-2" href="#"><i
class="fa fa-angle-right mr-2"></i>Our Shop</a>
        <a class="text-secondary mb-2" href="#"><i
class="fa fa-angle-right mr-2"></i>Shop Detail</a>
        <a class="text-secondary mb-2" href="#"><i
class="fa fa-angle-right mr-2"></i>Shopping Cart</a>
        <a class="text-secondary mb-2" href="#"><i
class="fa fa-angle-right mr-2"></i>Checkout</a>
        <a class="text-secondary" href="#"><i class="fa fa-
angle-right mr-2"></i>Contact Us</a>
    </div>--}}
    </div>
    <div class="col-md-3 mb-5">
        <h5 class="text-secondary text-uppercase text-center
mb-4">Social Media</h5>
        <div class="d-flex flex-column socialMedia">
            <div class="d-flex justify-content-around w-100">
                <a class="text-secondary mb-2 w-25"
href="https://www.instagram.com"><i class="fa fa-instagram"></i></a>
                <a class="text-secondary mb-2 w-25"
href="https://www.facebook.com"><i class="fa fa-facebook-square"></i></a>
                <a class="text-secondary mb-2 w-25"
href="https://www.linkedin.com"><i class="fa fa-linkedin"></i></a>
            </div>
            <div class="d-flex justify-content-around w-100">
                <a class="text-secondary mb-2 w-25"
href="https://www.twitter.com"><i class="fa fa-twitter"></i></a>
                <a class="text-secondary mb-2 w-25"
href="{{asset('documentation.pdf')}}"><i class="fa fa-file-pdf"></i></a>
                <a class="text-secondary mb-2 w-25"
href="{{asset('robots.txt')}}"><i class="fa fa-robot"></i></a>
            </div>
        </div>
    </div>
    <div class="col-md-4 mb-5">
        <h5 class="text-secondary text-uppercase mb-
4">Newsletter</h5>
        <p>Sign up to our newsletter and always be up to date
        with our offers.</p>
        <form action="">
            <div class="input-group">
                <input type="text" class="form-control"
placeholder="Your Email Address">
                <div class="input-group-append">
                    <button class="btn btn-primary">Sign

```

```

Up</button>
        </div>
    </div>
</form>
</div>
</div>
</div>
</div>
<div class="row border-top mx-xl-5 py-4" style="border-color: rgba(256,
256, 256, .1) !important;">
    <div class="col-md-6 px-xl-0">
        <p class="mb-md-0 text-center text-md-left text-secondary">
            &copy; <a class="text-primary" href="/">Flex Shop</a>. All
Rights Reserved. Designed
            by
            <a class="text-primary"
href="https://nenadjevtic01.github.io/portfolio">Nenad Jevtic</a>
        </p>
    </div>
    <div class="col-md-6 px-xl-0 text-center text-md-right">
        
    </div>
</div>
</div>

<!-- Back to Top -->
<a href="#" class="btn btn-primary back-to-top"><i class="fa fa-angle-
double-up"></i></a>

```

### 3.6.1.2.2 head.blade.php

```

<head>
    <meta charset="utf-8">
    <title>@yield('title')</title>
    <meta content="width=device-width, initial-scale=1.0" name="viewport">
    <meta content="@yield('keywords')" name="keywords">
    <meta content="@yield('description')" name="description">
    <meta name="csrf-token" content="{{ csrf_token() }}">

    <!-- Favicon -->
    <link href="{{asset('assets/img/favicon.ico')}}" rel="icon">

    <!-- Google Web Fonts -->
    <link rel="preconnect" href="https://fonts.gstatic.com">
    <link
href="https://fonts.googleapis.com/css2?family=Roboto:wght@400;500;700&dis
lay=swap" rel="stylesheet">

    <!-- Font Awesome -->
    {{-- <link href="https://cdnjs.cloudflare.com/ajax/libs/font-
awesome/5.10.0/css/all.min.css" rel="stylesheet">--}}
    <script src="https://kit.fontawesome.com/41bd7e5f70.js"
crossorigin="anonymous"></script>
    <!-- Libraries Stylesheet -->
    <link href="{{asset('assets/lib/animate/animate.min.css')}}"
rel="stylesheet">
    <link
href="{{asset('assets/lib/owlcarousel/assets/owl.carousel.min.css')}}">

```

```

rel="stylesheet">

    <!-- Customized Bootstrap Stylesheet -->
    <link href="{{asset('assets/css/style.css')}}" rel="stylesheet">
</head>

```

### 3.6.1.2.3 navbar.blade.php

```

<div class="container-fluid bg-dark mb-30">
    <div class="row px-xl-5">
        <div class="col-lg-3 d-none d-lg-block">
            <div class="d-flex align-items-center justify-content-center
bg-primary w-100" style="height: 65px; padding: 0 30px;">
                <h6 class="text-dark m-0"><i class="fa fa-solid fa-
globe"></i> WORLD OF CLOTHS</h6>
                <!-- <i class="fa fa-angle-down text-dark"></i>-->
            </div>
        </div>
        <div class="col-lg-9">
            <nav class="navbar navbar-expand-lg bg-dark navbar-dark py-3
py-lg-0 px-0">
                <a href="" class="text-decoration-none d-block d-lg-none">
                    <span class="h1 text-uppercase text-dark bg-light px-
2">Flex</span>
                    <span class="h1 text-uppercase text-light bg-primary
px-2 ml-n1">Shop</span>
                </a>
                <button type="button" class="navbar-toggler" data-
toggle="collapse" data-target="#navbarCollapse">
                    <span class="navbar-toggler-icon"></span>
                </button>
                <div class="collapse navbar-collapse justify-content-
between" id="navbarCollapse">
                    <div class="navbar-nav mr-auto py-0">
                        @foreach($data['menu'] as $m)
                            <a href="{{ $m->path }}" class="nav-item nav-
link">{{ $m->title }}</a>
                        @endforeach
                        @if(session()->has('user'))
                            @if(session('user')->role_id==1)
                                <a href="/adminpanel" class="nav-item
nav-link">Admin panel</a>
                            @endif
                        @endif
                    </div>
                    <div class="navbar-nav ml-auto py-0 d-none d-lg-block">
                        <a href="{{ route('Cart') }}" class="btn px-0 ml-3">
                            <i class="fas fa-shopping-cart text-
primary"></i>
                            <span id="numberOfProducts" class="badge text-
secondary border border-secondary rounded-circle" style="padding-bottom:
2px;">
                                @if(session()->has('user'))
                                    {{count(\DB::table('cart')-
>where('cart.user_id','=',session('user')->user_id)->get())}}
                                @elseif(session()->has('cart'))
                                    {{count(session('cart'))}}
                                @else
                                    0

```

```

                                @endif
                            </span>
                        </a>
                    </div>
                </div>
            </nav>
        </div>
    </div>
</div>

```

#### 3.6.1.2.4 scripts.blade.php

```

<!-- JavaScript Libraries -->
<script src="https://code.jquery.com/jquery-3.4.1.min.js"></script>
<script
src="https://stackpath.bootstrapcdn.com/bootstrap/4.4.1/js/bootstrap.bundle
.min.js"></script>
<script src="{{asset('assets/lib/easing/easing.min.js')}}"></script>
<script
src="{{asset('assets/lib/owlcarousel/owl.carousel.min.js')}}"></script>
<script src="{{asset('assets/js/custom.js')}}"></script>
<!-- Contact Javascript File -->

<!-- Template Javascript -->
<script src="{{asset('assets/js/main.js')}}"></script>

```

#### 3.6.1.2.5 topbar.blade.php

```

<div class="container-fluid">
    <div class="row bg-secondary py-1 px-xl-5">
        <div class="col-lg-12 text-center text-lg-right">
            <div class="d-inline-flex align-items-center">
                <div class="btn-group">
                    @if(session()->has('user'))
                        <span class="mr-2 my-auto">Welcome,
{{session('user')->first_name.' '.session('user')->last_name}}</span>
                    @endif
                    <button type="button" class="btn btn-sm btn-light
dropdown-toggle" data-toggle="dropdown">My Account</button>
                    @if(session()->has('user'))
                        <div class="dropdown-menu dropdown-menu-right">
                            <a class="dropdown-item"
href="{{route('Logout')}}">Logout</a>
                        </div>
                    @else
                        <div class="dropdown-menu dropdown-menu-right">
                            <a class="dropdown-item" href="{{route('Login
page')}}">Login</a>
                            <a class="dropdown-item" href="{{route('Register
page')}}">Sign up</a>
                        </div>
                    @endif
                </div>
            </div>
        </div>
    </div>
    <div class="row align-items-center bg-light py-3 px-xl-5 d-none d-lg-

```

```

flex">
    <div class="col-lg-4">
        <a href="/" class="text-decoration-none">
            <span class="h1 text-uppercase text-primary bg-dark px-2">Flex</span>
            <span class="h1 text-uppercase text-dark bg-primary px-2 ml-n1">Shop</span>
        </a>
    </div>
    <div class="col-lg-4 col-6 text-left">
    </div>
    <div class="col-lg-4 col-6 text-right">
        <p class="m-0">Customer Service</p>
        <h5 class="m-0">011 123 4567</h5>
    </div>
</div>
</div>

```

### 3.6.2 Layouts

#### 3.6.2.1 *admin.blade.php*

```

<!DOCTYPE html>
<html lang="en">
@include('fixed.admins.head')
<body id="page-top">

<!-- Page Wrapper -->
<div id="wrapper">
    @include('fixed.admins.sidebar')
    <div id="content-wrapper" class="d-flex flex-column">
        @yield('content')
        @include('fixed.admins.footer')
    </div>
    <!-- End of Content Wrapper -->

</div>
@include('fixed.admins.scripts')
</body>

</html>

```

#### 3.6.2.2 *layout.blade.php*

```

<!DOCTYPE html>
<html lang="en">

@include('fixed.head')
<body>
    @include('fixed.topbar')
    @include('fixed.navbar')

    @yield('content')

    @include('fixed.footer')
    @include('fixed.scripts')

```

```
</body>
</html>
```

### 3.6.3 Pages

#### 3.6.3.1 Admins

##### 3.6.3.1.1 addUser.blade.php

```
@extends('layouts.admin')
@section('title')
    Flex Shop - Add user
@endsection
@section('description')
    Add user
@endsection
@section('content')
    <div id="content">
        @include('fixed.admins.navbar')
        <section class='section-margin--small mb-5'>
            <div class='container d-flex justify-content-center'>
                <div class='col-12 col-md-9 col-lg-6 mt-3 d-flex flex-column
align-items-center'>
                    <h3 class='center mb-5'>Add user</h3>
                    <form class='row login_form' action='/adduser'
method="POST" >
                        @csrf
                        <div class='col-md-12 col-lg-6 form-group my-3'>
                            <input type='text' class='form-control'
name='first_name' placeholder='First name' />
                        </div>
                        <div class='col-md-12 col-lg-6 form-group my-3'>
                            <input type='text' class='form-control'
name='last_name' placeholder='Last name' />
                        </div>
                        <div class='col-md-12 form-group my-3'>
                            <input type='text' class='form-control'
name='username' placeholder='Username' />
                        </div>
                        <div class='col-md-12 form-group my-3'>
                            <input type='text' class='form-control'
name='email' placeholder='Email Address' />
                        </div>
                        <div class='col-md-12 form-group my-3'>
                            <select name="role" class="custom-select">
                                <option value='1'>Administrator</option>
                                <option value='2'>User</option>
                            </select>
                        </div>
                        <div class='col-md-12 form-group my-3'>
                            <input type='password' class='form-control'
name='password' placeholder='Password' />
                        </div>
                        <div class='col-md-12 form-group my-3'>
                            <input type='password' class='form-control'
name='confirmPassword' placeholder='Confirm Password' />
                        </div>
                        <div class='col-md-12 form-group my-3'>
                            <button type='submit' class='btn btn-info w-
```



```

100'>Add user</button>
        </div>
        <hr class="my-4">
        @if(session('success-msg'))
            <div class="alert alert-success col-md-12 rounded-
lg">
                <p>
                    @if (session('success-msg'))
                        {{session('success-msg')}}
                    @endif
                </p>
            </div>
        @endif
        @if($errors->any() || session('error-msg'))
            <div class="alert alert-danger col-md-12 rounded-
lg">
                <ul>
                    @if ($errors->any())
                        @foreach ($errors->all() as $error)
                            <li>{{ $error }}</li>
                        @endforeach
                    @endif
                    @if (session('error-msg'))
                        <li>{{session('error-msg')}}</li>
                    @endif
                </ul>
            </div>
        @endif
    </form>
</div>
</div>
</section>
</div>
@endsection

```

### 3.6.3.1.2 answerMessage.blade.php

```

@extends('layouts.admin')
@section('title')
    Flex Shop - Answer message {{ $data['message']->message_id }}
@endsection
@section('description')
    Answer message
@endsection
@section('content')
    <div id="content">
        @include('fixed.admins.navbar')
        <div class="section">
            <div class="container m-5">
                <div class="mb-3">
                    <h1>Message details</h1>
                </div>
                <div>
                    <h5 id="messageId" class="my-3">Message ID:
                    {{ $data['message']->message_id }}</h5>
                    <h5 id="answerName" class="my-3">Name: {{ $data['message']->
                    name }}</h5>
                    <h5 id="answerEmail" class="my-3">Email:
                    {{ $data['message']->email }}</h5>
                </div>
            </div>
        </div>
    </div>

```

```

        <div class="d-flex flex-row my-3">
            <div class="mr-3">
                <h5>Message: </h5>
            </div>
            <div class="margin-left-20">
                <h5 id="answerMessage">{{ $data['message'] -
>text}}</h5>
            </div>
        </div>
        <form action="">
            <div class="d-flex flex-row">
                <div class="mr-3">
                    <h5>Answer: </h5>
                </div>
                <div class="margin-left-20">
                    <textarea cols="70" rows="3" class="rounded
border-info" id="answer" placeholder="Type here..."></textarea>
                    <p class="text-danger hidden"
id="textError"></p>
                </div>
            </div>
            <br/>
            <div>
                <button class="btn btn-info " type="button"
id="sendAnswer">Send answer</button>
                <p id="status" class="my-2"></p>
            </div>
        </form>
    </div>
</div>
</div>
@endsection

```

### 3.6.3.1.3 answerTemplate.blade.php

```

<div class="d-flex flex-column justify-content-center">
    <h4>Hi {{ $name }},</h4>
    <h4>Message: {{ $messageText }}</h4>
    <p>Answer to your message: {{ $text }}</p>
    <span>Flex shop admin team</span>
</div>

```

### 3.6.3.1.4 home.blade.php

```

@extends('layouts.admin')
@section('title')
    Flex Shop - Admin panel
@endsection
@section('description')
    Admin page
@endsection
@section('content')
    <div id="content">
        @include('fixed.admins.navbar')
        <!-- Begin Page Content -->
        <div class="container-fluid">

```

```

        <!-- Page Heading -->
        <div class="d-sm-flex align-items-center justify-content-
between mb-4">
            <h1 class="h3 mb-0 text-gray-800">Dashboard</h1>
            {{--
                <a href="#" class="d-none d-sm-inline-block btn btn-sm
btn-primary shadow-sm"><i
                    class="fas fa-download fa-sm text-white-50"></i>
Generate Report</a>--}}
            </div>

        <!-- Content Row -->
        <div class="row">

            <!-- Earnings (Monthly) Card Example -->
            <div class="col-xl-3 col-md-6 mb-4">
                <div class="card border-left-primary shadow h-100 py-
2">
                    <div class="card-body">
                        <div class="row no-gutters align-items-center">
                            <div class="col mr-2">
                                <div class="text-xs font-weight-bold
text-primary text-uppercase mb-1">
                                    Earnings (Monthly)</div>
                                <div class="h5 mb-0 font-weight-bold
text-gray-800">${{number_format($data['earningsMonthly'],2)}}</div>
                                </div>
                                <div class="col-auto">
                                    <i class="fas fa-calendar fa-2x text-
gray-300"></i>
                                </div>
                            </div>
                        </div>
                    </div>
                </div>

            <!-- Earnings (Monthly) Card Example -->
            <div class="col-xl-3 col-md-6 mb-4">
                <div class="card border-left-success shadow h-100 py-
2">
                    <div class="card-body">
                        <div class="row no-gutters align-items-center">
                            <div class="col mr-2">
                                <div class="text-xs font-weight-bold
text-success text-uppercase mb-1">
                                    Earnings (Annual)</div>
                                <div class="h5 mb-0 font-weight-bold
text-gray-800">${{number_format($data['earningsYearly'],2)}}</div>
                                </div>
                                <div class="col-auto">
                                    <i class="fas fa-dollar-sign fa-2x
text-gray-300"></i>
                                </div>
                            </div>
                        </div>
                    </div>
                </div>

            <!-- Earnings (Monthly) Card Example -->
            <div class="col-xl-3 col-md-6 mb-4">
                <div class="card border-left-info shadow h-100 py-2">

```

```

        <div class="card-body">
            <div class="row no-gutters align-items-center">
                <div class="col mr-2">
                    <div class="text-xs font-weight-bold
text-info text-uppercase mb-1">
                        Users</div>
                    <div class="h5 mb-0 font-weight-bold
text-gray-800">{{ $data['userCount'] }}</div>
                </div>
                <div class="col-auto">
                    <i class="fa fa-solid fa-user fa-2x
text-gray-300"></i>
                </div>
            </div>
        </div>
    </div>
</div>
<!-- Orders Card Example -->
<div class="col-xl-3 col-md-6 mb-4">
    <div class="card border-left-warning shadow h-100 py-
2">
        <div class="card-body">
            <div class="row no-gutters align-items-center">
                <div class="col mr-2">
                    <div class="text-xs font-weight-bold
text-warning text-uppercase mb-1">
                        Orders</div>
                    <div class="h5 mb-0 font-weight-bold
text-gray-800">{{ $data['orders'] }}</div>
                </div>
                <div class="col-auto">
                    <i class="fa fa-solid fa-receipt fa-2x
text-gray-300"></i>
                </div>
            </div>
        </div>
    </div>
</div>
</div>
</div>
</div>
<div class="section">
    <div class="card shadow mb-4">
        <div class="card-header py-3 w-100">
            <h6 class="m-0 font-weight-bold text-
primary">Messages</h6>
        </div>
        <div class="card-body">
            <div class="table-responsive">
                <table class="table table-bordered w-100">
                    <thead>
                        <tr>
                            <th>Message Id</th>
                            <th>Name</th>
                            <th>Subject</th>
                            <th>Email</th>
                            <th>Message</th>
                            <th>Sent at</th>
                            <th>Action</th>
                        </tr>
                    </thead>

```

```

        <tbody>
        @foreach($data['message'] as $m)
            <tr>
                <td>{{ $m->message_id }}</td>
                <td>{{ $m->name }}</td>
                <td>{{ $m->subject }}</td>
                <td>{{ $m->email }}</td>
                <td>{{ $m->text }}</td>
                <td>{{ $m->created_at }}</td>
                <td>
                    @if(!$m->is_answered)
                        <a
href="/answermessage/{{ $m->message_id }}" class="btn btn-success">Answer</a>
                    @else
                        <button disabled class="btn
btn-info">Answered</button>
                    @endif
                </td>
            </tr>
        @endforeach
        </tbody>
    </table>
</div>
</div>
</div>
</div>

<div class="section">
    <div class="card shadow mb-4">
        <div class="card-header py-3 w-100">
            <h6 class="m-0 font-weight-bold text-
primary">Users</h6>
        </div>
        <div class="card-body">
            <div class="table-responsive">
                <table class="table table-bordered w-100">
                    <thead>
                        <tr>
                            <th>User Id</th>
                            <th>Name</th>
                            <th>Email</th>
                            <th>Username</th>
                            <th>Role</th>
                            <th>Registration date</th>
                            <th>Action</th>
                        </tr>
                    </thead>
                    <tbody>
                        @foreach($data['users'] as $u)
                            <tr>
                                <td>{{ $u->user_id }}</td>
                                <td>{{ $u->first_name.' '.$u->
last_name }}</td>
                                <td>{{ $u->email }}</td>
                                <td>{{ $u->username }}</td>
                                <td>
                                    @if($u->role_id==1)
                                        Administrator
                                    @else
                                        User
                                    @endif
                                </td>
                            </tr>
                        @endforeach
                    </tbody>
                </table>
            </div>
        </div>
    </div>
</div>

```

```

                </td>
                <td>{{ $u->registration_date }}</td>
                <td>
                    @if($u->is_banned)
                        @if($u->role_id==2)
                            <a
href="/unblockuser/{{ $u->user_id }}" class="btn btn-warning">Unblock</a>
                        @else
                            <button disabled
class="btn btn-info">Forbidden</button>
                        @endif
                    @else
                        @if($u->role_id==2)
                            <a
href="/blockuser/{{ $u->user_id }}" class="btn btn-danger">Block</a>
                        @else
                            <button disabled
class="btn btn-info">Forbidden</button>
                        @endif
                    @endif
                </td>
            </tr>
        @endforeach
    </tbody>
</table>
</div>
</div>
</div>
<div class="section">
    <div class="card shadow mb-4">
        <div class="card-header py-3 w-100 d-flex justify-
content-between align-items-center">
            <h6 class="m-0 font-weight-bold text-
primary">Statistics</h6>
            @if(count($data['statistics']))
                <a href="/clearstats" class="btn btn-
success">Clear log</a>
            @endif
        </div>
        <div class="card-body">
            <div class="table-responsive">
                @if(count($data['statistics']))
                    <table class="table table-bordered w-100">
                        <thead>
                            <tr>
                                <th>Name</th>
                                <th>Email</th>
                                <th>Action</th>
                            </tr>
                        </thead>
                        <tbody>
                            @foreach($data['statistics'] as $s)
                                <tr>
                                    <td>{{ $s->name }}</td>
                                    <td>{{ $s->email }}</td>
                                    <td>{{ $s->action }}</td>
                                </tr>
                            @endforeach
                        </tbody>
                    </table>
                @endif
            </div>
        </div>
    </div>
</div>

```

```

        @else
            <h5>No statistic</h5>
        @endif
    </div>
</div>
</div>
</div>

<div class="section">
    <div class="card shadow mb-4">
        <div class="card-header py-3 w-100">
            <h6 class="m-0 font-weight-bold text-
primary">Products</h6>
        </div>
        <div class="card-body">
            <div class="table-responsive">
                <table class="table table-bordered w-100">
                    <thead>
                        <tr>
                            <th>Product Id</th>
                            <th>Product name</th>
                            <th>Category</th>
                            <th>Brand</th>
                            <th>Gender</th>
                            <th>Price</th>
                            <th>Sale</th>
                            <th>In stock</th>
                            <th>View</th>
                        </tr>
                    </thead>
                    <tbody>
                        @foreach($data['products'] as $m)
                            <tr>
                                <td>{{ $m->product_id }}</td>
                                <td>{{ $m->product_name }}</td>
                                <td>{{ $m->category_name }}</td>
                                <td>{{ $m->brand_name }}</td>
                                <td>{{ $m->gender_name }}</td>
                                <td>${{ $m->newPrice }}</td>
                                <td>{{ $m->sale ? 'True' :
'False' }}</td>
                                <td>{{ $m->inStock ? 'True' :
'False' }}</td>
                                <td>
                                    <a href="/updateproduct/{{ $m-
>product_id }}" class="btn btn-success">Update product</a>
                                </td>
                            </tr>
                        @endforeach
                    </tbody>
                </table>
            </div>
        </div>
    </div>
</div>
</div>

</div>
<!-- /.container-fluid -->

</div>

```

```

        <!-- End of Main Content -->
    @endsection

```

### 3.6.3.1.5 orders.blade.php

```

@extends('layouts.admin')
@section('title')
    Flex Shop - Orders
@endsection
@section('description')
    Orders
@endsection
@section('content')
    <div id="content">
        @include('fixed.admins.navbar')
        <div class="section">
            <div class="card shadow mb-4">
                <div class="card-header py-3 w-100">
                    <h6 class="m-0 font-weight-bold text-
primary">Orders</h6>
                </div>
                <div class="card-body">
                    <div class="table-responsive">
                        @if(count($data['orders']))
                            <table class="table table-bordered w-100">
                                <thead>
                                    <tr>
                                        <th>Order Id</th>
                                        <th>Full Name</th>
                                        <th>Email</th>
                                        <th>Full Address</th>
                                        <th>Country</th>
                                        <th>Total</th>
                                        <th>Order date</th>
                                        <th>Action</th>
                                    </tr>
                                </thead>
                                <tbody>
                                    @foreach($data['orders'] as $o)
                                        <tr>
                                            <td>{{ $o->receipt_id }}</td>
                                            <td>{{ $o->first_name.' '.$o->
last_name }}</td>
                                            <td>{{ $o->email }}</td>
                                            <td>{{ $o->address.' '.$o->city.' '.$o->
zip }}</td>
                                            <td>{{ $o->country }}</td>
                                            <td>{{ $o->total }}</td>
                                            <td>{{ $o->date }}</td>
                                            <td>
                                                <a href="/orders/{{ $o->
receipt_id }}" class="btn btn-info">Show receipt</a>
                                            </td>
                                        </tr>
                                    @endforeach
                                </tbody>
                            </table>
                        @else
                            <h6>No orders</h6>

```



```

        @endif
    </div>
</div>
</div>
</div>
</div>
@endsection

```

### 3.6.3.1.6 removeUser.blade.php

```

@extends('layouts.admin')
@section('title')
    Flex Shop - Remove user
@endsection
@section('description')
    Remove user
@endsection
@section('content')
    <div id="content" >
        @include('fixed.admins.navbar')
        <div class="container-fluid p-5">
            <form action="/removeuser" method="POST" class="d-flex flex-
column align-items-center">
                @csrf
                <label for="userSelect">Select user:</label>
                <select name="user" id="userSelect" class="custom-select w-
25 m-2">
                    @foreach($data['users'] as $d)
                        <option value="{{ $d->user_id }}">{{ $d->first_name.'
' . $d->last_name }}</option>
                    @endforeach
                </select>
                <button type="submit" class="btn btn-info m-5">Remove
user</button>
                @if(session('success-msg'))
                    <div class="alert alert-success col-md-12 w-50 rounded-
lg">
                        <p>
                            @if (session('success-msg'))
                                {{session('success-msg')}}
                            @endif
                        </p>
                    </div>
                @endif
                @if($errors->any() || session('error-msg'))
                    <div class="alert alert-danger col-md-12 w-50 rounded-
lg">
                        <ul>
                            @if ($errors->any())
                                @foreach ($errors->all() as $error)
                                    <li>{{ $error }}</li>
                                @endforeach
                            @endif
                            @if (session('error-msg'))
                                <li>{{session('error-msg')}}</li>
                            @endif
                        </ul>
                    </div>
                @endif
            </div>
        </div>
    </div>

```

```

        </form>
    </div>
</div>
@endsection

```

### 3.6.3.1.7 single\_order.blade.php

```

@extends('layouts.admin')
@section('title')
    Flex Shop - Order details
@endsection
@section('description')
    Single order
@endsection
@section('content')
    <div id="content">
        @include('fixed.admins.navbar')
        <div class="container-fluid">
            <div class="section">
                <div class="card shadow mb-4">
                    <div class="card-header py-3 w-100">
                        <h6 class="m-0 font-weight-bold text-primary">Order
details</h6>
                    </div>
                    <div class="card-body">
                        <div class="table-responsive">
                            @if(count($data['orderDetails']))
                                <table class="table table-bordered w-100">
                                    <thead>
                                        <tr>
                                            <th>Product Name</th>
                                            <th>Price</th>
                                            <th>Size</th>
                                            <th>Quantity</th>
                                        </tr>
                                    </thead>
                                    <tbody>
                                        @foreach($data['orderDetails'] as $o)
                                            <tr>
                                                <td><a href="/products/{{ $o-
>product_id }}">{{ $o->product_name }}</a></td>
                                                <td>{{ $o->price }}</td>
                                                <td>{{ $o->size }}</td>
                                                <td>{{ $o->quantity }}</td>
                                            </tr>
                                        @endforeach
                                    </tbody>
                                </table>
                            @else
                                <h6>No details about order</h6>
                            @endif
                        </div>
                    </div>
                </div>
                <a href="/orders" class="btn btn-success">Go back</a>
            </div>
        </div>
    </div>
@endsection

```

### 3.6.3.1.8 updateProduct.blade.php

```
@extends('layouts.admin')
@section('title')
    Flex Shop - Admin panel
@endsection
@section('description')
    Admin page
@endsection
@section('content')
    <div id="content">
        @include('fixed.admins.navbar')
        <section class='section-margin--small mb-5'>
            <div class='container d-flex justify-content-center'>
                <div class='col-12 col-md-9 col-lg-6 mt-3 d-flex flex-
column align-items-center'>
                    <h3 class='center mb-5'>Update product
"{{$data['productUpdate']->product_name}}"</h3>
                    <form class='row login_form' action='/updateproduct'
method="POST" >
                        @csrf
                        <div class='col-md-12 form-group my-3'>
                            <input type='text' class='form-control' hidden
name='id' value="{{$data['productUpdate']->product_id}}" />
                        </div>
                        <div class='col-md-12 form-group my-3'>
                            Product Name:
                            <input type='text' class='form-control'
name='product_name' placeholder='Enter product name'
value="{{$data['productUpdate']->product_name}}" />
                        </div>
                        <div class='col-md-12 form-group my-3'>
                            Price:
                            <input type='text' class='form-control'
value="{{$data['productUpdate']->newPrice}}" name='price' />
                        </div>
                        <div class='col-md-12 form-group my-3'>
                            Material:
                            <input type='text' class='form-control'
value="{{$data['productUpdate']->material}}" name='material' />
                        </div>
                        <div class='col-md-12 form-group my-3'>
                            Country of origin:
                            <input type='text' class='form-control'
value="{{$data['productUpdate']->coo}}" name='coo' />
                        </div>
                        <div class='col-md-12 form-group my-3 d-flex
justify-content-center'>
                            <button type='submit' class='btn btn-info w-
50'>Update product</button>
                        </div>
                        <hr class="my-4">
                        @if(session('success-msg'))
                            <div class="alert alert-success col-md-12
rounded-lg">
                                <p>
                                    @if (session('success-msg'))
                                        {{session('success-msg')}}
                                    @endif
                                </p>
                            </div>
                        @endif
                    </div>
                </div>
            </section>
        </div>
    </div>
```

```

        </div>
    @endif
    @if($errors->any() || session('error-msg'))
        <div class="alert alert-danger col-md-12 w-75
rounded-lg">
            <ul>
                @if ($errors->any())
                    @foreach ($errors->all() as $error)
                        <li>{{ $error }}</li>
                    @endforeach
                @endif
                @if (session('error-msg'))
                    <li>{{session('error-msg')}}</li>
                @endif
            </ul>
        </div>
    @endif
</form>
</div>
</div>
</section>
</div>
@endsection

```

### 3.6.3.2 Users

#### 3.6.3.2.1 author.blade.php

```

@extends('layouts.layout')
@section('title')
    Flex Shop - Author
@endsection
@section('keywords')
    author, site, laravel , php2
@endsection
@section('description')
    Author page
@endsection
@section('content')
    <div class="product_image_area my-5">
        <div class="container py-5" id="jedanProizvod">
            <div class='row s_product_inner proizvodMargin'>
                <div class='col-lg-6 rounded'>
                    <img class='img-fluid col-md-12 authorImage'
src='{{asset('assets/img/Author.jpg')}}' alt='Author image' />
                </div>
                <div class='col-lg-5 offset-lg-1'>
                    <div class='s_product_text d-flex flex-column align-
items-center'>
                        <h3 class="pb-5">Author</h3>
                        <p class='authorText font-italic'>Hi, my name is
Nenad Jevtić, and I am a desktop and web developer. I was lucky enough to
work for several fun, exciting and successful StartUps that helped me to
become who I am now. I am always thinking about speed, performance
optimisation, scalability and the way to improve workflow for each
individual project. Communication with me is simple, you are free to call
me anytime you want. I keep up to date with the latest technologies and
consider myself a very quick study able to pick up another technology in a
very short amount of time as needed.</p>

```

```

        <div>
            <a class='btn btn-primary mx-2'
href='https://nenadjevtic01.github.io/portfolio'>Visit portfolio</a>
        </div>
    </div>
</div>
</div>
</div>
</div>
</div>
@endsection

```

### 3.6.3.2.2 cart.blade.php

```

@extends('layouts.layout')
@section('title')
    Flex Shop - Cart
@endsection
@section('keywords')
    cart, shop, online
@endsection
@section('description')
    Cart
@endsection
@section('content')
    <!-- Breadcrumb Start -->
    <div class="container-fluid">
        <div class="row px-xl-5">
            <div class="col-12">
                <nav class="breadcrumb bg-light mb-30">
                    <a class="breadcrumb-item text-dark" href="/">Home</a>
                    <a class="breadcrumb-item text-dark"
href="/products">Shop</a>
                    <span class="breadcrumb-item active">Shopping
Cart</span>
                </nav>
            </div>
        </div>
    </div>
    <!-- Breadcrumb End -->

    <!-- Cart Start -->
    <div class="container-fluid">
        <div class="row px-xl-5">
            <div class="col-lg-8 table-responsive mb-5">
                <table class="table table-light table-borderless table-
hover text-center mb-0">
                    <thead class="thead-dark">
                        <tr>
                            <th>Products</th>
                            <th>Price</th>
                            <th>Quantity</th>
                            <th>Size</th>
                            <th>Total</th>
                            <th>Remove</th>
                        </tr>
                    </thead>
                    <tbody class="align-middle">
                        <@if($data['cart']!=null)
                            <@if(count($data['cart'])!=0)

```

```

        @for($i=0;$i<count($data['cart']);$i++)

@for($j=0;$j<count($data['cartProducts']);$j++)
        @if($data['cart'][$i]-
>product_id==$data['cartProducts'][$j]->product_id)
            <tr>
                <td class="align-middle">alt }}" style="width: 50px;">
                <a
href="/products/{{ $data['cartProducts'][$j]-
>product_id }}">{{ $data['cartProducts'][$j]->product_name}}</a></td>
                <td class="align-
middle">${{doubleval($data['cartProducts'][$j]->newPrice)}}.00</td>
                <td class="align-
middle">x{{ $data['cart'][$i]->qty}}
                </td>
                <td class="align-
middle">{{ $data['cart'][$i]->size}}</td>
                <td class="align-middle"><p
class="price mx-auto">${{ $data['cart'][$i]->qty*$data['cartProducts'][$j]-
>newPrice}}.00</p></td>
                <td class="align-
middle"><button class="btn btn-sm btn-danger"
onclick="deleteProductFromCart('{{ $data['cart'][$i]-
>size}}','{{ $data['cart'][$i]->product_id}}')"><i class="fa fa-
times"></i></button></td>
            </tr>
        @endif
    @endfor
@endfor
@else
    <tr>
        <td colspan="6">Empty</td>
    </tr>
    @endif
@else
    <tr>
        <td colspan="6">Empty</td>
    </tr>
    @endif
</tbody>
</table>
<p id="status" class="hidden"></p>
</div>
<div class="col-lg-4">
    @if($data['cart']!=null)
        @if(count($data['cart'])!=0)
            <h5 class="section-title position-relative text-uppercase
mb-3"><span class="bg-secondary pr-3">Cart Summary</span></h5>
            <div class="bg-light p-30 mb-5">
                <div class="border-bottom pb-2">
                    <div class="d-flex justify-content-between mb-3">
                        <h6>Subtotal</h6>
                        <h6 id="subtotal"></h6>
                    </div>
                    <div class="d-flex justify-content-between">
                        <h6 class="font-weight-medium">Shipping</h6>
                        <h6 class="font-weight-medium">$10</h6>
                    </div>
                </div>
            </div>
        @endif
    </div>

```

```

        <div class="pt-2">
            <div class="d-flex justify-content-between mt-2">
                <h5>Total</h5>
                <h5 id="total"></h5>
            </div>
            <a href="/checkout" class="btn btn-block btn-
primary font-weight-bold my-3 py-3">Proceed To Checkout</a>
            </div>
        </div>
        @else
            <div class="bg-light p-30 mb-5">
                <div class="pt-2">
                    <a href="/products" class="btn btn-block
btn-primary font-weight-bold my-3 py-3">Browse products</a>
                </div>
            </div>
        @endif
        @else
            <div class="bg-light p-3 mb-5 d-flex justify-content-
center">
                <div class="pt-2 w-75">
                    <a href="/products" class="btn btn-block btn-
primary font-weight-bold my-3 py-3">Browse products</a>
                </div>
            </div>
        @endif
    </div>
</div>
<!-- Cart End -->
@endsection

```

### 3.6.3.2.3 checkout.blade.php

```

@extends('layouts.layout')
@section('title')
    Flex Shop - Checkout
@endsection
@section('keywords')
    checkout, product, cart, shop
@endsection
@section('description')
    Checkout page
@endsection
@section('content')
    <!-- Breadcrumb Start -->
    <div class="container-fluid">
        <div class="row px-xl-5">
            <div class="col-12">
                <nav class="breadcrumb bg-light mb-30">
                    <a class="breadcrumb-item text-dark" href="/">Home</a>
                    <a class="breadcrumb-item text-dark"
href="/products">Shop</a>
                    <span class="breadcrumb-item active">Checkout</span>
                </nav>
            </div>
        </div>
    </div>
    <!-- Breadcrumb End -->

```

```

<!-- Checkout Start -->
<div class="container-fluid">
  <div class="row px-xl-5">
    <div class="col-lg-8">
      <h5 class="section-title position-relative text-uppercase mb-3"><span class="bg-secondary pr-3">Billing Address</span></h5>
      <div class="bg-light p-30 mb-5">
        <div class="row">
          @if(session()->has('user'))
            <div class="col-md-6 form-group">
              <label>First Name</label>
              <input class="form-control" type="text"
placeholder="John" value="{{session('user')->first_name}}" id="first_name">
              <p id="errorFirstName" class="hidden pt-1"></p>
            </div>
            <div class="col-md-6 form-group">
              <label>Last Name</label>
              <input class="form-control" type="text"
placeholder="Doe" value="{{session('user')->last_name}}" id="last_name">
              <p id="errorLastName" class="hidden pt-1"></p>
            </div>
            <div class="col-md-6 form-group">
              <label>E-mail</label>
              <input class="form-control" type="text"
placeholder="example@email.com" value="{{session('user')->email}}"
id="email">
              <p id="errorEmail" class="hidden pt-1"></p>
            </div>
            <div class="col-md-6 form-group">
              <label>Address Line 1</label>
              @if($data['userInfo'])
                <input class="form-control" type="text"
placeholder="123 Street" value="{{ $data['userInfo']->address }}"
id="address">
              @else
                <input class="form-control" type="text"
placeholder="123 Street" id="address">
              @endif
              <p id="errorAddress" class="hidden pt-1"></p>
            </div>
            <div class="col-md-6 form-group">
              <label>Country</label>
              @if($data['userInfo'])
                <select class="custom-select" id="country">
                  @if($data['userInfo']->country=='')
                    <option value="" selected>Select
country</option>
                  @else
                    <option value="">Select
country</option>
                  @endif
                  @if($data['userInfo']->country=='Serbia')
                    <option value="Serbia"
selected>Serbia</option>
                  @else
                    <option value="Serbia">Serbia</option>
                  @endif
                  @if($data['userInfo']->country=='Russia')
                    <option value="Russia"
selected>Russia</option>

```



```

        @else
            <option value="Russia">Russia</option>
        @endif
        @if($data['userInfo']->country=='United
States')
            <option value="United States"
selected>United States</option>
        @else
            <option value="United States">United
States</option>
        @endif
        @if($data['userInfo']->country=='Croatia')
            <option value="Croatia"
selected>Croatia</option>
        @else
            <option
value="Croatia">Croatia</option>
        @endif
        @if($data['userInfo']->country=='Bosnia and
Herzegovina')
            <option value="Bosnia and Herzegovina"
selected>Bosnia and Herzegovina</option>
        @else
            <option value="Bosnia and
Herzegovina">Bosnia and Herzegovina</option>
        @endif
        @if($data['userInfo']->country=='Montenegro')
            <option value="Montenegro"
selected>Montenegro</option>
        @else
            <option
value="Montenegro">Montenegro</option>
        @endif
    </select>
    @else
        <select class="custom-select"
name="country" id="country">
            <option value="" selected>Select
country</option>
            <option value="Serbia">Serbia</option>
            <option value="Russia">Russia</option>
            <option value="United States">United
States</option>
            <option
value="Croatia">Croatia</option>
            <option value="Bosnia and
Herzegovina">Bosnia and Herzegovina</option>
            <option
value="Montenegro">Montenegro</option>
        </select>
    @endif
    <p id="errorCountry" class="hidden pt-1"></p>
</div>
<div class="col-md-6 form-group">
    <label>City</label>
    @if($data['userInfo'])
        <input class="form-control" type="text"
placeholder="New York" value="{{ $data['userInfo']->city }}" id="city">
    @else
        <input class="form-control" type="text"

```

```

placeholder="New York" id="city">
    @endif
    <p id="errorCity" class="hidden pt-1"></p>
</div>
<div class="col-md-6 form-group">
    <label>ZIP Code</label>
    @if($data['userInfo'])
        <input class="form-control" type="text"
placeholder="123" value="{{ $data['userInfo']->postal_code }}"
id="postal_code">
    @else
        <input class="form-control" type="text"
placeholder="123" id="postal_code">
    @endif
    <p id="errorZip" class="hidden pt-1"></p>
</div>
{{--
d-flex">
    <div class="custom-control custom-checkbox">
        <input type="checkbox" class="custom-
control-input" id="shipto">
        <label class="custom-control-label"
for="shipto" data-toggle="collapse" data-target="#shipping-address">Ship
to different address</label>
    </div>
</div>--}}
    @else
        <div class="col-md-6 form-group">
            <label>First Name</label>
            <input class="form-control" type="text"
placeholder="John" id="first_name">
            <p id="errorFirstName" class="hidden pt-
1"></p>
        </div>
        <div class="col-md-6 form-group">
            <label>Last Name</label>
            <input class="form-control" type="text"
placeholder="Doe" id="last_name">
            <p id="errorLastName" class="hidden pt-
1"></p>
        </div>
        <div class="col-md-6 form-group">
            <label>E-mail</label>
            <input class="form-control" type="text"
placeholder="example@email.com" id="email">
            <p id="errorEmail" class="hidden pt-1"></p>
        </div>
        <div class="col-md-6 form-group">
            <label>Address Line 1</label>
            <input class="form-control" type="text"
placeholder="123 Street" id="address">
            <p id="errorAddress" class="hidden pt-
1"></p>
        </div>
        <div class="col-md-6 form-group">
            <label>Country</label>
            <select class="custom-select" id="country">
                <option value="" selected>Select
country</option>
                <option value="Serbia">Serbia</option>
                <option value="Russia">Russia</option>
            </select>
        </div>
    @endif
</div>

```

```

States</option>
                                <option value="United States">United
value="Croatia">Croatia</option>
                                <option value="Bosnia and
Herzegovina">Bosnia and Herzegovina</option>
                                <option
value="Montenegro">Montenegro</option>
                                </select>
                                <p id="errorCountry" class="hidden pt-
1"></p>
                                </div>
                                <div class="col-md-6 form-group">
                                    <label>City</label>
                                    <input class="form-control" type="text"
placeholder="New York" id="city">
                                    <p id="errorCity" class="hidden pt-1"></p>
                                </div>
                                <div class="col-md-6 form-group">
                                    <label>ZIP Code</label>
                                    <input class="form-control" type="text"
placeholder="123" id="postal_code">
                                    <p id="errorZip" class="hidden pt-1"></p>
                                </div>
                                <div class="col-md-12 justify-content-
center d-flex">
                                <div class="custom-control custom-
checkbox">
                                    <input type="checkbox" class="custom-
control-input" id="shipto">
                                    <label class="custom-control-label"
for="shipto" data-toggle="collapse" data-target="#shipping-address">Ship
to different address</label>
                                </div>
                                </div>--}}
                                @endif
                                </div>
                                </div>
                                <div class="collapse mb-5" id="shipping-address">
                                    <h5 class="section-title position-relative text-
uppercase mb-3"><span class="bg-secondary pr-3">Shipping
Address</span></h5>
                                    <div class="bg-light p-30">
                                        <div class="row">
                                            <div class="col-md-6 form-group">
                                                <label>First Name</label>
                                                <input class="form-control" type="text"
placeholder="John">
                                            </div>
                                            <div class="col-md-6 form-group">
                                                <label>Last Name</label>
                                                <input class="form-control" type="text"
placeholder="Doe">
                                            </div>
                                            <div class="col-md-6 form-group">
                                                <label>E-mail</label>
                                                <input class="form-control" type="text"
placeholder="example@email.com">
                                            </div>
                                            <div class="col-md-6 form-group">
                                                <label>Address Line 1</label>

```

```

placeholder="123 Street">
    <input class="form-control" type="text"
    </div>
    <div class="col-md-6 form-group">
        <label>Country</label>
        <select class="custom-select"
name="country">
            <option value="Serbia"
selected>Serbia</option>
            <option value="Russia">Russia</option>
            <option value="United States">United
States</option>
            <option
value="Croatia">Croatia</option>
            <option value="Bosnia and
Herzegovina">Bosnia and Herzegovina</option>
            <option
value="Montenegro">Montenegro</option>
        </select>
    </div>
    <div class="col-md-6 form-group">
        <label>City</label>
        <input class="form-control" type="text"
placeholder="New York">
    </div>
    <div class="col-md-6 form-group">
        <label>ZIP Code</label>
        <input class="form-control" type="text"
placeholder="123">
    </div>
</div>
</div>
</div>--}}
</div>
<div class="col-lg-4">
    <h5 class="section-title position-relative text-uppercase
mb-3"><span class="bg-secondary pr-3">Order Total</span></h5>
    <div class="bg-light p-30 mb-5">
        <div class="border-bottom">
            <h6 class="mb-3">Products</h6>
            @for ($i=0;$i<count($data['cart']);$i++)
                @for ($j=0;$j<count($data['cartProducts']);$j++)
                    @if ($data['cart'][$i]-
>product_id==$data['cartProducts'][$j]->product_id)
                        <div class="d-flex justify-content-
between">
                            <a
href="/products/{{ $data['cart'][$i]-
>product_id }}">{{ $data['cartProducts'][$j]->product_name }}
                            ({{ $data['cart'][$i]->size }})</a>
                            <div class="d-flex">
                                <p>x</p>
                                <p>{{ $data['cart'][$i]-
>qty }}</p>
                            </div>
                                <p
class="price">${{{ $data['cart'][$i]->qty*$data['cartProducts'][$j]-
>newPrice }}.00</p>
                            </div>
                        @break
                    @endif

```

```

        @endfor
    @endfor
</div>
<div class="border-bottom pt-3 pb-2">
    <div class="d-flex justify-content-between mb-3">
        <h6>Subtotal</h6>
        <h6 id="subtotal"></h6>
    </div>
    <div class="d-flex justify-content-between">
        <h6 class="font-weight-medium">Shipping</h6>
        <h6 class="font-weight-medium">$10.00</h6>
    </div>
</div>
<div class="pt-2">
    <div class="d-flex justify-content-between mt-2">
        <h5>Total</h5>
        <h5 id="total"></h5>
    </div>
</div>
</div>
<div class="mb-5">
    <h5 class="section-title position-relative text-
uppercase mb-3"><span class="bg-secondary pr-3">Payment</span></h5>
    <div class="bg-light p-3">
        <div class="form-group">
            <div class="custom-control custom-radio">
                <input type="radio" class="custom-control-
input" checked name="payment" id="paypal">
                <label class="custom-control-label"
for="paypal">Paypal</label>
            </div>
        </div>
        <div class="form-group">
            <div class="custom-control custom-radio">
                <input type="radio" class="custom-control-
input" name="payment" id="directcheck">
                <label class="custom-control-label"
for="directcheck">Direct Check</label>
            </div>
        </div>
        <div class="form-group mb-4">
            <div class="custom-control custom-radio">
                <input type="radio" class="custom-control-
input" name="payment" id="banktransfer">
                <label class="custom-control-label"
for="banktransfer">Bank Transfer</label>
            </div>
        </div>
        <button class="btn btn-block btn-primary font-
weight-bold py-3" id="submitOrder">Place Order</button>
        <p class="hidden checkoutStatus pt-2"
id="status"></p>
    </div>
</div>
</div>
</div>
</div>
<!-- Checkout End -->
@endsection

```

### 3.6.3.2.4 contact.blade.php

```
@extends('layouts.layout')
@section('title')
    Flex Shop - Contact
@endsection
@section('keywords')
    contact, form, cloths, product
@endsection
@section('description')
    Contact us.
@endsection
@section('content')
    <!-- Breadcrumb Start -->
    <div class="container-fluid">
        <div class="row px-xl-5">
            <div class="col-12">
                <nav class="breadcrumb bg-light mb-30">
                    <a class="breadcrumb-item text-dark" href="/">Home</a>
                    <span class="breadcrumb-item active">Contact</span>
                </nav>
            </div>
        </div>
    </div>
    <!-- Breadcrumb End -->

    <!-- Contact Start -->
    <div class="container-fluid">
        <h2 class="section-title position-relative text-uppercase mx-xl-5 mb-4"><span class="bg-secondary pr-3">Contact Us</span></h2>
        <div class="row px-xl-5">
            <div class="col-lg-7 mb-5">
                <div class="contact-form bg-light p-30">
                    <div id="success"></div>
                    <form name="sendMessage" id="contactForm"
novalidate="novalidate">
                        <div class="control-group">
                            @if(session()->has('user'))
                                <input type="text" class="form-control"
id="name" placeholder="Your Name"
                                required="required" data-validation-
required-message="Please enter your name" value="{{session('user')->first_name.' '.session('user')->last_name}}"/>
                                <p class="help-block text-danger hidden"
id="errorName"></p>
                            @else
                                <input type="text" class="form-control"
id="name" placeholder="Your Name"
                                required="required" data-validation-
required-message="Please enter your name" />
                                <p class="help-block text-danger hidden"
id="errorName"></p>
                            @endif
                        </div>
                        <div class="control-group">
                            @if(session()->has('user'))
                                <input type="email" class="form-control"
id="email" placeholder="Your Email"
                                required="required" data-validation-
```

```

required-message="Please enter your email" value="{{session('user')-
>email}}"/>
        <p class="help-block text-danger hidden"
id="errorEmail"></p>
        @else
        <input type="email" class="form-control"
id="email" placeholder="Your Email"
        required="required" data-validation-
required-message="Please enter your email" />
        <p class="help-block text-danger hidden"
id="errorEmail"></p>
        @endif
    </div>
    <div class="control-group">
        <input type="text" class="form-control"
id="subject" placeholder="Subject"
        required="required" data-validation-
required-message="Please enter a subject" />
        <p class="help-block text-danger hidden"
id="errorSubject"></p>
    </div>
    <div class="control-group">
        <textarea class="form-control" rows="8"
id="message" placeholder="Message"
        required="required"
data-validation-required-
message="Please enter your message"></textarea>
        <p class="help-block text-danger hidden"
id="errorMessage"></p>
    </div>
    <div>
        <button class="btn btn-primary py-2 px-4"
type="button" id="sendMessageButton">Send
        Message</button>
        <p class="help-block pt-1 hidden "
id="status"></p>
    </div>
</form>
</div>
</div>
<div class="col-lg-5 mb-5">
    <div class="bg-light p-30 mb-30">
        <iframe style="width: 100%; height: 250px; border:0;"
src="https://www.google.com/maps/embed?pb=!1m18!1m12!1m3!1d2830.35867171445
76!2d20.482226115312177!3d44.81425718459575!2m3!1f0!2f0!3f0!3m2!1i1024!2i76
8!4f13.1!3m3!1m2!1s0x475a7a9609031735%3A0xc17ed71f59ac4725!2z0JLQuNGB0L7Qut
CwINCY0KbQoiDRiNC60L7Qu9Cw!5e0!3m2!1ssr!2srs!4v1670364660676!5m2!1ssr!2srs"
width="600" height="450" style="border:0;" allowfullscreen=""
loading="lazy" referrerpolicy="no-referrer-when-downgrade"></iframe>
    </div>
    <div class="bg-light p-30 mb-3">
        <p class="mb-2"><i class="fa fa-map-marker-alt text-
primary mr-3"></i>Zdravka Čelara 16, Beograd, Srbija</p>
        <p class="mb-2"><i class="fa fa-envelope text-primary
mr-3"></i>flexshop_info@gmail.com</p>
        <p class="mb-2"><i class="fa fa-phone-alt text-primary
mr-3"></i>011 123 4567</p>
    </div>
</div>
</div>
</div>

```

```

        <!-- Contact End -->
    @endsection

```

### 3.6.3.2.5 home.blade.php

```

@extends('layouts.layout')
@section('title')
    Flex Shop - Home
@endsection
@section('keywords')
    shop, flex, home, clothes
@endsection
@section('description')
    Flex shop - Clothing store
@endsection

@section('content')
    @include('components.slider')
    <!-- Featured Start -->
    <div class="container-fluid pt-5">
        <div class="row px-xl-5 pb-3">
            <div class="col-lg-3 col-md-6 col-sm-12 pb-1">
                <div class="d-flex align-items-center bg-light mb-4"
style="padding: 30px;">
                    <h1 class="fa fa-check text-primary m-0 mr-3"></h1>
                    <h5 class="font-weight-semi-bold m-0">Quality
Product</h5>
                </div>
            </div>
            <div class="col-lg-3 col-md-6 col-sm-12 pb-1">
                <div class="d-flex align-items-center bg-light mb-4"
style="padding: 30px;">
                    <h1 class="fa fa-shipping-fast text-primary m-0 mr-
2"></h1>
                    <h5 class="font-weight-semi-bold m-0">Free
Shipping</h5>
                </div>
            </div>
            <div class="col-lg-3 col-md-6 col-sm-12 pb-1">
                <div class="d-flex align-items-center bg-light mb-4"
style="padding: 30px;">
                    <h1 class="fas fa-exchange-alt text-primary m-0 mr-
3"></h1>
                    <h5 class="font-weight-semi-bold m-0">14-Day
Return</h5>
                </div>
            </div>
            <div class="col-lg-3 col-md-6 col-sm-12 pb-1">
                <div class="d-flex align-items-center bg-light mb-4"
style="padding: 30px;">
                    <h1 class="fa fa-phone-volume text-primary m-0 mr-
3"></h1>
                    <h5 class="font-weight-semi-bold m-0">24/7 Support</h5>
                </div>
            </div>
        </div>
    <!-- Featured End -->

```



```

        <!--Brand Start -->
        <div class="container-fluid pt-5">
            <h2 class="section-title position-relative text-uppercase mx-xl-5 mb-4"><span class="bg-secondary pr-3">Brands</span></h2>
            <div class="row px-xl-5 pb-3">
                @for($i=0;$i<4;$i++)
                    <div class="col-lg-3 col-md-4 col-sm-6 pb-1">
                        <div class="text-decoration-none">
                            <div class="cat-item d-flex align-items-center mb-4">
                                <div class="overflow-hidden" style="width: 100px; height: 100px;">
                                    alt }}">
                                </div>
                                <div class="flex-fill pl-3">
                                    <h6>{{ $data['brandsCount'][$i]->brand_name }}</h6>
                                    <small class="text-body">{{ $data['brandsCount'][$i]->product_number }} Products</small>
                                </div>
                            </div>
                        </div>
                    </div>
                @endfor
            </div>
        <!--Brand End -->

        <!-- Products Start -->
        <div class="container-fluid pt-5 pb-3">
            <h2 class="section-title position-relative text-uppercase mx-xl-5 mb-4"><span class="bg-secondary pr-3">Featured Products</span></h2>
            <div class="row px-xl-5">
                @foreach($data['products'] as $p)
                    @include('components.product', ['lg'=>3, 'md'=>4])
                @endforeach
            </div>
        </div>
        <!-- Products End -->
    @endsection

```

### 3.6.3.2.6 login.blade.php

```

@extends('layouts.layout')
@section('title')
    Flex Shop - Login
@endsection
@section('keywords')
    login, form, cart, shop
@endsection
@section('description')
    Login to site.
@endsection
@section('content')
    <div class="container">
        <div class="row">
            <div class="col-sm-9 col-md-7 col-lg-5 mx-auto">
                <div class="card border-0 shadow rounded-3 my-5">
                    <div class="card-body p-4 p-sm-5">

```

```
<h5 class="card-title text-center mb-5 fw-light fs-5">Sign In</h5>

    <form action="{{route('Login')}}" method="POST">
        @csrf
        <div class="form-floating mb-4">
            <input type="email" class="form-control"
name="email" placeholder="name@example.com">
        </div>
        <div class="form-floating mb-4">
            <input type="password" class="form-control"
name="password" placeholder="Password">
        </div>
        <div class="d-grid">
            <button class="btn btn-primary btn-login
text-uppercase fw-bold" type="submit">Sign
in</button>
        </div>
        <hr class="my-4">
        @if($errors->any() || session('error-msg'))
            <div class="alert alert-danger col-md-12
rounded-lg">

                <ul>
                    @if ($errors->any())
                        @foreach ($errors->all() as
$error)

                            <li>{{ $error }}</li>
                        @endforeach
                    @endif
                    @if (session('error-msg'))
                        <li>{{session('error-
msg')}}</li>
                    @endif
                </ul>
            </div>
        @endif
    </form>
</div>
</div>
</div>
</div>
</div>
@endsection
```

#### 3.6.3.2.7 register.blade.php

```
@extends('layouts.layout')
@section('title')
    Flex Shop - Registration
@endsection
@section('keywords')
    register, site, products
@endsection
@section('description')
    Register form
@endsection
@section('content')
    <div class="container">
        <div class="row justify-content-center">
            <div class="col-lg-9">
```

```

        <div class="login_form_inner register_form_inner">
            <h3 class="py-4">Create an account</h3>
            <form class="row login_form justify-content-center"
action="{{route('Register')}}" method="POST" >
                @csrf
                <div class="col-md-12 form-group">
                    <input type="text" class="form-control"
name="first_name" placeholder="First name" onfocus="this.placeholder = ''"
onblur="this.placeholder = 'First name'">
                </div>
                <div class="col-md-12 form-group">
                    <input type="text" class="form-control"
name="last_name" placeholder="Last name" onfocus="this.placeholder = ''"
onblur="this.placeholder = 'Last name'">
                </div>
                <div class="col-md-12 form-group">
                    <input type="text" class="form-control"
name="username" placeholder="Username" onfocus="this.placeholder = ''"
onblur="this.placeholder = 'Username'">
                </div>
                <div class="col-md-12 form-group">
                    <input type="text" class="form-control"
name="email" placeholder="Email Address" onfocus="this.placeholder = ''"
onblur="this.placeholder = 'Email Address'">
                </div>
                <div class="col-md-12 form-group">
                    <input type="text" class="form-control"
name="address" placeholder="Address" onfocus="this.placeholder = ''"
onblur="this.placeholder = 'Address'">
                </div>
                <div class="col-md-12 form-group">
                    <input type="text" class="form-control"
name="city" placeholder="City" onfocus="this.placeholder = ''"
onblur="this.placeholder = 'City'">
                </div>
                <div class="col-md-12 form-group">
                    <input type="text" class="form-control"
name="postal_code" placeholder="Postal code" onfocus="this.placeholder = ''"
onblur="this.placeholder = 'Postal code'">
                </div>
                <div class="col-md-12 form-group">
                    <select class="custom-select" name="country">
                        <option value="Serbia"
selected>Serbia</option>
                        <option value="Russia">Russia</option>
                        <option value="United States">United
States</option>
                        <option value="Croatia">Croatia</option>
                        <option value="Bosnia and
Herzegovina">Bosnia and Herzegovina</option>
                        <option
value="Montenegro">Montenegro</option>
                    </select>
                </div>
                <div class="col-md-12 form-group">
                    <input type="password" class="form-control"
name="password" placeholder="Password" onfocus="this.placeholder = ''"
onblur="this.placeholder = 'Password'">
                </div>
                <div class="col-md-12 form-group">
                    <input type="password" class="form-control"

```

```

name="confirmPassword" placeholder="Confirm Password"
onfocus="this.placeholder = ''" onblur="this.placeholder = 'Confirm
Password'">
        </div>
        <div class="col-md-6 form-group">
            <button type="submit" value="Register"
class="btn btn-primary btn-login text-uppercase fw-bold w-100 py-
2">Register</button>
        </div>
        @if($errors->any() || session('error-msg'))
        <div class="alert alert-danger col-md-9
rounded-lg">
            <ul>
            @if ($errors->any())
                @foreach ($errors->all() as $error)
                    <li>{{ $error }}</li>
                @endforeach
            @endif
            @if (session('error-msg'))
                <li>{{session('error-msg')}}</li>
            @endif
            </ul>
        </div>
        @endif
    </form>
</div>
</div>
</div>
</div>
@endsection

```

### 3.6.3.2.8 shop.blade.php

```

@extends('layouts.layout')
@section('title')
    Flex Shop - Shop
@endsection
@section('keywords')
    products, browse, shop, online
@endsection
@section('description')
    Browse all products online.
@endsection

@section('content')
    <!-- Breadcrumb Start -->
    <div class="container-fluid">
        <div class="row px-xl-5">
            <div class="col-12">
                <nav class="breadcrumb bg-light mb-30">
                    <a class="breadcrumb-item text-dark" href="/">Home</a>
                    <span class="breadcrumb-item active">Shop</span>
                </nav>
            </div>
        </div>
    </div>
    <!-- Breadcrumb End -->
    <!-- Shop Start -->

```

```

<div class="container-fluid">
  <div class="row px-xl-5">
    <!-- Shop Sidebar Start -->
    <div class="col-lg-3 col-md-4">
      <form action="/products" method="GET">
        @csrf
        <div class="p-4">
          <div class="d-flex align-items-center justify-content-center flex-column">
            <input type="submit" class="btn btn-primary mb-2" value="Apply/Search">
            @if(session()->has('filter'))
              <a class="btn btn-primary" href="/clearfilter">Clear filter</a>
            @endif
          </div>
        </div>
        <h5 class="section-title position-relative text-uppercase mb-3"><span class="bg-secondary pr-3">Search</span></h5>
        <div class="bg-light p-4 mb-30">
          <div class="custom-checkbox d-flex align-items-center justify-content-center">
            @if($data['search']!=null)
              <input type="text" name="search" value="{{ $data['search'] }}" class="form-control"/>
            @else
              <input type="text" name="search" placeholder="Search..." class="form-control"/>
            @endif
          </div>
        </div>
        <!-- Brand Start -->
        <h5 class="section-title position-relative text-uppercase mb-3"><span class="bg-secondary pr-3">Filter by brand</span></h5>
        <div class="bg-light p-4 mb-30">
          @foreach($data['brand'] as $b)
            @if($data['brandId']!=null)
              @if(in_array($b->brand_id,$data['brandId']))
                <div class="custom-control custom-checkbox d-flex align-items-center justify-content-between mb-3">
                  <input type="checkbox" checked name="brand[]" value="{{ $b->brand_id }}" class="custom-control-input" id="{{ $b->brand_name }}">
                  <label class="custom-control-label" for="{{ $b->brand_name }}">{{ $b->brand_name }}</label>
                </div>
              @else
                <div class="custom-control custom-checkbox d-flex align-items-center justify-content-between mb-3">
                  <input type="checkbox" name="brand[]" value="{{ $b->brand_id }}" class="custom-control-input" id="{{ $b->brand_name }}">
                  <label class="custom-control-label" for="{{ $b->brand_name }}">{{ $b->brand_name }}</label>
                </div>
              @endif
            @else
              <div class="custom-control custom-checkbox d-flex align-items-center justify-content-between mb-3">
                <input type="checkbox" name="brand[]"

```

```

value="{{ $b->brand_id }}" class="custom-control-input" id="{{ $b->brand_name }}">
        <label class="custom-control-label"
for="{{ $b->brand_name }}">{{ $b->brand_name }}</label>
        </div>
    @endif

    @endforeach

</div>
<!-- Brand End -->
<!-- Brand Start -->
<h5 class="section-title position-relative text-uppercase mb-3"><span class="bg-secondary pr-3">Filter by gender</span></h5>
<div class="bg-light p-4 mb-30">
    @if($data['genderId']!=null)
        @if(in_array(1,$data['genderId']))
            <div class="custom-control custom-checkbox d-
flex align-items-center justify-content-between mb-3">
                <input type="checkbox" checked
name="gender[]" value='1' class="custom-control-input" id="Male">
                <label class="custom-control-label"
for="Male">Male</label>
            </div>
        @else
            <div class="custom-control custom-checkbox d-
flex align-items-center justify-content-between mb-3">
                <input type="checkbox" name="gender[]"
value='1' class="custom-control-input" id="Male">
                <label class="custom-control-label"
for="Male">Male</label>
            </div>
        @endif
        @if(in_array(2,$data['genderId']))
            <div class="custom-control custom-checkbox
d-flex align-items-center justify-content-between mb-3">
                <input type="checkbox" checked
name="gender[]" value='2' class="custom-control-input" id="Female">
                <label class="custom-control-label"
for="Female">Female</label>
            </div>
        @else
            <div class="custom-control custom-checkbox
d-flex align-items-center justify-content-between mb-3">
                <input type="checkbox" name="gender[]"
value='2' class="custom-control-input" id="Female">
                <label class="custom-control-label"
for="Female">Female</label>
            </div>
        @endif
        @else
            <div class="custom-control custom-checkbox d-flex
align-items-center justify-content-between mb-3">
                <input type="checkbox" name="gender[]"
value='1' class="custom-control-input" id="Male">
                <label class="custom-control-label"
for="Male">Male</label>
            </div>
            <div class="custom-control custom-checkbox d-flex
align-items-center justify-content-between mb-3">
                <input type="checkbox" name="gender[]"
value='2' class="custom-control-input" id="Female">

```

```

                                <label class="custom-control-label"
for="Female">Female</label>
                                </div>
                                @endif

                                </div>
                                <!-- Brand End -->
                                <!-- Price Start -->
                                <h5 class="section-title position-relative text-uppercase
mb-3"><span class="bg-secondary pr-3">Filter by price</span></h5>
                                <div class="bg-light p-4 mb-30">
                                    @if($data['price']!=null)
                                        @if($data['price']==1)
                                            <div class="custom-control custom-radio d-flex
align-items-center justify-content-between mb-3">
                                                <input type="radio" class="custom-control-
input" checked name="price" value="1" id="price-1">
                                                <label class="custom-control-label"
for="price-1">$0 - $20</label>
                                            </div>
                                        @else
                                            <div class="custom-control custom-radio d-flex
align-items-center justify-content-between mb-3">
                                                <input type="radio" class="custom-control-
input" name="price" value="1" id="price-1">
                                                <label class="custom-control-label"
for="price-1">$0 - $20</label>
                                            </div>
                                        @endif
                                        @if($data['price']==2)
                                            <div class="custom-control custom-radio d-
flex align-items-center justify-content-between mb-3">
                                                <input type="radio" checked
class="custom-control-input" name="price" value="2" id="price-3">
                                                <label class="custom-control-label"
for="price-3">$20 - $40</label>
                                            </div>
                                        @else
                                            <div class="custom-control custom-radio d-
flex align-items-center justify-content-between mb-3">
                                                <input type="radio" class="custom-
control-input" name="price" value="2" id="price-3">
                                                <label class="custom-control-label"
for="price-3">$20 - $40</label>
                                            </div>
                                        @endif
                                        @if($data['price']==3)
                                            <div class="custom-control custom-radio d-
flex align-items-center justify-content-between mb-3">
                                                <input type="radio" checked
class="custom-control-input" name="price" value="3" id="price-4">
                                                <label class="custom-control-label"
for="price-4">$40 - $60</label>
                                            </div>
                                        @else
                                            <div class="custom-control custom-radio d-
flex align-items-center justify-content-between mb-3">
                                                <input type="radio" class="custom-
control-input" name="price" value="3" id="price-4">
                                                <label class="custom-control-label"
for="price-4">$40 - $60</label>

```

```

        </div>
    @endif
    @else
        <div class="custom-control custom-radio d-flex
align-items-center justify-content-between mb-3">
            <input type="radio" class="custom-control-
input" name="price" value="1" id="price-1">
            <label class="custom-control-label" for="price-
1">$0 - $20</label>
        </div>
        <div class="custom-control custom-radio d-flex
align-items-center justify-content-between mb-3">
            <input type="radio" class="custom-control-
input" name="price" value="2" id="price-3">
            <label class="custom-control-label" for="price-
3">$20 - $40</label>
        </div>
        <div class="custom-control custom-radio d-flex
align-items-center justify-content-between mb-3">
            <input type="radio" class="custom-control-
input" name="price" value="3" id="price-4">
            <label class="custom-control-label" for="price-
4">$40 - $60</label>
        </div>
    @endif
</div>
<!-- Price End -->

<!-- Category Start -->
<h5 class="section-title position-relative text-uppercase
mb-3"><span class="bg-secondary pr-3">Filter by category</span></h5>
<div class="bg-light p-4 mb-30">

        @foreach($data['category'] as $c)
            @if($data['categoryId']!=null)
                @if(in_array($c-
>category_id,$data['categoryId']))
                    <div class="custom-control custom-checkbox
d-flex align-items-center justify-content-between mb-3">
                        <input type="checkbox" checked
class="custom-control-input" name="category[]" value="{{ $c->category_id }}"
id="{{ $c->category_name }}">
                        <label class="custom-control-label"
for="{{ $c->category_name }}">{{ $c->category_name }}</label>
                    </div>
                @else
                    <div class="custom-control custom-checkbox
d-flex align-items-center justify-content-between mb-3">
                        <input type="checkbox" class="custom-
control-input" name="category[]" value="{{ $c->category_id }}" id="{{ $c-
>category_name }}">
                        <label class="custom-control-label"
for="{{ $c->category_name }}">{{ $c->category_name }}</label>
                    </div>
                @endif
            @else
                <div class="custom-control custom-checkbox
d-flex align-items-center justify-content-between mb-3">
                    <input type="checkbox" class="custom-
control-input" name="category[]" value="{{ $c->category_id }}" id="{{ $c-
>category_name }}">

```



```

                                <label class="custom-control-label"
for="{{ $c->category_name }}">{{ $c->category_name }}</label>
                                </div>
                                @endif
                                @endforeach
                                </div>

                                </div>--}}

                                </form>
                                <!-- Size End -->
                                </div>
                                <!-- Shop Sidebar End -->

                                <!-- Shop Product Start -->
                                <div class="col-lg-9 col-md-8">
                                    <div class="row pb-3">
                                        <div class="col-12 pb-1">
                                            <div class="d-flex align-items-center justify-
content-between mb-4">
                                                <div>
                                                </div>

                                                </div>
                                            </div>
                                            @foreach($data['products'] as $p)
@include('components.product', ['lg'=>4, 'md'=>6, 'p'=>$p])
                                            @endforeach

                                            <div class="col-12">
                                                <nav class="d-flex justify-content-center">
                                                    {{$data['products']-
>links("pagination::bootstrap-4") }}

                                                    </nav>
                                                </div>
                                            </div>
                                        </div>
                                    </div>
                                <!-- Shop Product End -->
                                </div>
                                </div>
                                <!-- Shop End -->
@endsection

```

### 3.6.3.2.9 singleProduct.blade.php

```

@extends('layouts.layout')
@section('title')
    Flex Shop - {{$data['productInfo']->product_name}}
@endsection
@section('keywords')
    product, single
@endsection
@section('description')

@endsection
@section('content')

```

```

{{--      {{session()->forget('cart')}}--}}
{{--      {{dd(session('cart'))}}--}}
<!-- Breadcrumb Start -->
<div class="container-fluid">
    <div class="row px-xl-5">
        <div class="col-12">
            <nav class="breadcrumb bg-light mb-30">
                <a class="breadcrumb-item text-dark" href="/">Home</a>
                <a class="breadcrumb-item text-dark"
href="/products">Shop</a>
                <span class="breadcrumb-item
active">{{ $data['productInfo']->product_name }}</span>
            </nav>
        </div>
    </div>
</div>
<!-- Breadcrumb End -->

<!-- Shop Detail Start -->
<div class="container-fluid pb-5">
    <div class="row px-xl-5">
        <div class="col-lg-5 mb-30">
            <div id="product-carousel" class="carousel slide" data-
ride="carousel">
                <div class="carousel-inner bg-light">
                    <div class="carousel-item active">
                        alt }}">
                    </div>
                </div>
            </div>
        </div>
        <div class="col-lg-7 h-auto mb-30">
            <div class="h-100 bg-light p-30">
                <h3>{{ $data['productInfo']->product_name }}</h3>
                <div class="d-flex mb-3">

                    </div>
                    <div class="d-flex">
                        @if($data['productInfo']->oldPrice!=null)
                            <h3 class="text-danger font-weight-semi-bold
mb-4 mr-4">${ $data['productInfo']->newPrice }</h3>
                            <h5 style="text-decoration: line-through"
class="font-weight-semi-bold mt-1 strike">${ $data['productInfo']->
oldPrice }</h5>
                        @else
                            <h3 class="font-weight-semi-bold mb-4 mr-
4">${ $data['productInfo']->newPrice }</h3>
                        @endif
                    </div>
                <p class="mb-4">
                    Category: {{ $data['productInfo']->category_name }}
                    <hr>
                    Brand: {{ $data['productInfo']->brand_name }}
                    <hr>
                    Availibility: {{ $data['productInfo']->inStock ? 'In
stock' : 'Unavailable' }}
                </p>
                <div class="d-flex">
                    <form novalidate="novalidate">

```

```

        @if(count($data['productSizes'])!=0)
        <strong class="text-dark mr-3">Sizes:</strong>
        @foreach($data['productSizes'] as $p)
        <div class="custom-control custom-radio
custom-control-inline">
            <input type="radio" class="custom-
control-input size" value="{{ $p->size_name }}" id="{{ $p->size_name }}"
name="size">
            <label class="custom-control-label"
for="{{ $p->size_name }}">{{ $p->size_name }}</label>
        </div>
        @endforeach
        <p class="hidden text-danger pt-2"
id="sizes">Select size.</p>
        @else
        <div class="custom-control custom-radio
custom-control-inline">
            <strong class="text-dark mr-
3">Unavailable</strong>
        </div>
        @endif
    </form>
</div>
@if(count($data['productSizes'])!=0)
<div class="d-flex align-items-center mb-4 pt-2">
    <div class="input-group quantity mr-3"
style="width: 130px;">
        <div class="input-group-btn">
            <button class="btn btn-primary btn-minus">
                <i class="fa fa-minus"></i>
            </button>
        </div>
        <input type="number" id="qty" min="1" max="99"
class="form-control bg-secondary border-0 text-center" value="1">
        <div class="input-group-btn">
            <button class="btn btn-primary btn-plus">
                <i class="fa fa-plus"></i>
            </button>
        </div>
        <div>
            <button class="btn btn-primary px-3 "
onclick="dodajUkorpu('{{ $data['productInfo']->product_id }}')><i class="fa
fa-shopping-cart mr-1"></i> Add To
            Cart</button></div>
        </div>
        <p class="hidden text-danger"
id="quantityError">Invalid quantity.</p><br>
        <p class="text" id="status"></p>
        @else
        <div class="d-flex align-items-center mb-4 pt-2">
            <div class="input-group quantity mr-3"
style="width: 130px;">
                <div class="input-group-btn">
                    <button class="btn btn-primary disabled
btn-minus" disabled>
                        <i class="fa fa-minus"></i>
                    </button>
                </div>
                <input type="number" id="qty" disabled
class=" disabled form-control bg-secondary border-0 text-center" min="1"
max="99" value="1">

```

```

        <div class="input-group-btn">
            <button class="btn btn-primary disabled
btn-plus" disabled>
                <i class="fa fa-plus"></i>
            </button>
        </div>
    </div>
    <button class="btn btn-primary px-3 disabled"
onclick="dodajUkorpu({{$data['productInfo']->product_id}})" disabled><i
class="fa fa-shopping-cart mr-1"></i> Add To
    Cart</button>
</div>
@endif
{{--<div class="d-flex pt-2">
    <strong class="text-dark mr-2">Share on:</strong>
    <div class="d-inline-flex">
        <a class="text-dark px-2" href="">
            <i class="fab fa-facebook-f"></i>
        </a>
        <a class="text-dark px-2" href="">
            <i class="fab fa-twitter"></i>
        </a>
        <a class="text-dark px-2" href="">
            <i class="fab fa-linkedin-in"></i>
        </a>
        <a class="text-dark px-2" href="">
            <i class="fab fa-pinterest"></i>
        </a>
    </div>
</div>--}}
</div>
</div>
<div class="row px-xl-5">
    <div class="col">
        <div class="bg-light p-30">
            <div class="nav nav-tabs mb-4">
                <a class="nav-item nav-link text-dark active" data-
toggle="tab">Information</a>
            </div>
            <div class="tab-content">
                <div class="tab-pane fade show active" id="tab-
pane-2">
                    <h4 class="mb-3">Additional Information</h4>
                    {{{--
                        <p>Eos no lorem eirmod diam diam, eos elitr
et gubergren diam sea. Consetetur vero aliquyam invidunt duo dolores et duo
sit. Vero diam ea vero et dolore rebum, dolor rebum eirmod consetetur
invidunt sed sed et, lorem duo et eos elitr, sadipscing kasd ipsum rebum
diam. Dolore diam stet rebum sed tempor kasd eirmod. Takimata kasd ipsum
accusam sadipscing, eos dolores sit no ut diam consetetur duo justo est,
sit sanctus diam tempor aliquyam eirmod nonumy rebum dolor accusam, ipsum
kasd eos consetetur at sit rebum, diam kasd invidunt tempor lorem, ipsum
lorem elitr sanctus eirmod takimata dolor ea invidunt.</p>--}}
                    <div class="row">
                        <div class="col-md-6">
                            <ul class="list-group list-group-
flush">
                                <li class="list-group-item px-0">
                                    Category:
                                    {{{$data['productInfo']->category_name}}
                                </li>

```

```

<li class="list-group-item px-0">
    Brand: {{ $data['productInfo']->brand_name }}
</li>
<li class="list-group-item px-0">
    Gender: {{ $data['productInfo']->gender_name }}
</li>
<li class="list-group-item px-0">
    </li>
</ul>
</div>
<div class="col-md-6">
    <ul class="list-group list-group-flush">
        <li class="list-group-item px-0">
            Material:
            {{ $data['productInfo']->material }}
        </li>
        <li class="list-group-item px-0">
            Country of origin:
            {{ $data['productInfo']->coo }}
        </li>
        <li class="list-group-item px-0">
            &nbsp;
        </li>
        <li class="list-group-item px-0">
            </li>
        </ul>
    </div>
</div>
</div>
</div>
</div>
</div>
</div>
</div>
</div>
<!-- Shop Detail End -->

<!-- Products Start -->
<div class="container-fluid py-5">
    <h2 class="section-title position-relative text-uppercase mx-xl-5 mb-4"><span class="bg-secondary pr-3">On sale</span></h2>
    <div class="row px-xl-5">
        <div class="col">
            <div class="owl-carousel related-carousel">
                @foreach($data['productScroller'] as $p)
                    @include('components.sliderProduct')
                @endforeach
            </div>
        </div>
    </div>
</div>
</div>
<!-- Products End -->
@endsection

```

### 3.6.4 Components

#### 3.6.4.1 *product.blade.php*

```
<div class="col-lg-{{$lg}} col-md-{{$md}} col-sm-6 pb-1">
    <div class="product-item bg-light mb-4">
        <div class="product-img position-relative overflow-hidden">
            alt}}">
            <div class="product-action">
                <a class="btn btn-outline-dark btn-square"
href="/products/{{$p->product_id}}"><i class="fa fa-shopping-cart"></i></a>
            </div>
        </div>
        <div class="text-center py-4">
            <a class="h6 text-decoration-none text-truncate"
href="/products/{{$p->product_id}}">{{$p->product_name}}</a>
            <div class="d-flex align-items-center justify-content-center
mt-2">

                @if($p->oldPrice!=null)
                    <h5 class="text-danger">{{$p->newPrice}}</h5>
                    <h6 class="text-muted ml-2"><del>{{$p-
>oldPrice}}</del></h6>
                @else
                    <h5>{{$p->newPrice}}</h5>
                @endif
            </div>
            <div class="d-flex align-items-center justify-content-
center mb-1">
                </div>
            </div>
        </div>
    </div>
</div>
```

#### 3.6.4.2 *slider.blade.php*

```
<div class="container-fluid mb-3">
    <div class="row px-xl-5">
        <div class="col-lg-8">
            <div id="header-carousel" class="carousel slide carousel-fade
mb-30 mb-lg-0" data-ride="carousel">
                <ol class="carousel-indicators">
                    <li data-target="#header-carousel" data-slide-to="0"
class="active"></li>
                    <li data-target="#header-carousel" data-slide-
to="1"></li>
                </ol>
                <div class="carousel-inner">
                    <div class="carousel-item position-relative active"
style="height: 430px;">
                        
                        <div class="carousel-caption d-flex flex-column
align-items-center justify-content-center">
                            <div class="p-3" style="max-width: 700px;">
                                <h1 class="display-4 text-white mb-3
```

```

animate__animated animate__fadeInDown">Up To 60% Off</h1>
        <p class="mx-md-5 px-5 animate__animated
animate__bounceIn">Year Sale</p>
        <a class="btn btn-outline-light py-2 px-4
mt-3 animate__animated animate__fadeInUp" href="/products">Shop Now</a>
        </div>
    </div>
</div>
<div class="carousel-item position-relative"
style="height: 430px;">
    
    <div class="carousel-caption d-flex flex-column
align-items-center justify-content-center">
        <div class="p-3" style="max-width: 700px;">
            <h1 class="display-4 text-white mb-3
animate__animated animate__fadeInDown">Quality Guarantee</h1>
            <p class="mx-md-5 px-5 animate__animated
animate__bounceIn">Our products are made from high quality materials</p>
            <a class="btn btn-outline-light py-2 px-4
mt-3 animate__animated animate__fadeInUp" href="/products">Shop Now</a>
            </div>
        </div>
    </div>
</div>
</div>
</div>
<div class="col-lg-4">
    <div class="product-offer mb-30" style="height: 200px;">
        
        <div class="offer-text">
            <h3 class="text-white mb-3">Affordable prices</h3>
        </div>
    </div>
    <div class="product-offer mb-30" style="height: 200px;">
        
        <div class="offer-text">
            <h3 class="text-white mb-3">Product reliability</h3>
        </div>
    </div>
</div>
</div>
</div>

```

### 3.6.4.3 sliderProduct.blade.php

```

<div class="product-item bg-light">
    <div class="product-img position-relative overflow-hidden">
        alt)}}">
        <div class="product-action">
            <a class="btn btn-outline-dark btn-square"
href="/products/{{asset('assets/'.$p->product_id)}}"><i class="fa fa-shopping-cart"></i></a>
        </div>
    </div>

```

```

        <div class="text-center py-4">
            <a class="h6 text-decoration-none text-truncate"
href="/products/{{ $p->product_id }}">{{ $p->product_name }}</a>
            <div class="d-flex align-items-center justify-content-center mt-2">
                <h5 class="text-danger">${{ $p->newPrice }}</h5>
                @if($p->oldPrice!=null)
                <h6 class="text-muted ml-2"><del>${{ $p->oldPrice }}</del></h6>
                @endif
            </div>
            <div class="d-flex align-items-center justify-content-center mb-1">

        </div>
    </div>
</div>

```

## 3.7 Routes

### 3.7.1 web.php

```

<?php

use Illuminate\Support\Facades\Route;

/*
|-----
| Web Routes
|-----
|
| Here is where you can register web routes for your application. These
| routes are loaded by the RouteServiceProvider within a group which
| contains the "web" middleware group. Now create something great!
|
*/

Route::middleware(['authorized'])->group(function() {
    Route::get('/logout', [\App\Http\Controllers\LoginController::class,
'logout'])->name('Logout');
});

Route::middleware(['admin'])->group(function() {

Route::get('/adminpanel', [\App\Http\Controllers\AdminController::class, 'index'])->name('Admin panel');

Route::get('/answermessage/{id}', [\App\Http\Controllers\MessageController::
class, 'index'])->name('Answer message');

Route::post('/answermessage', [\App\Http\Controllers\MessageController::clas
s, 'sendAnswer'])->name('Send answer');

Route::get('/adduser', [\App\Http\Controllers\UserController::class, 'index']
)>name('Add user');

Route::post('/adduser', [\App\Http\Controllers\UserController::class, 'addUse
r'])->name('Insert user');

Route::get('/removeuser', [\App\Http\Controllers\UserController::class, 'inde
xRemove'])->name('Remove user');

```



```

Route::post('/removeuser', [\App\Http\Controllers\UserController::class, 'removeUser'])->name('Delete user');

Route::get('/unlockuser/{id}', [\App\Http\Controllers\AdminController::class, 'unlockUser'])->name('Unblock user');

Route::get('/blockuser/{id}', [\App\Http\Controllers\AdminController::class, 'blockUser'])->name('Block user');

Route::get('/clearstats', [\App\Http\Controllers\AdminController::class, 'clearStats'])->name('Clear stats');

Route::get('/orders', [\App\Http\Controllers\AdminController::class, 'showOrders'])->name('Show orders');

Route::get('/orders/{id}', [\App\Http\Controllers\AdminController::class, 'showSingleReceipt'])->name('Show single receipt');

Route::get('/updateproduct/{id}', [\App\Http\Controllers\AdminController::class, 'updateProduct'])->name('Update product');

Route::post('/updateproduct', [\App\Http\Controllers\AdminController::class, 'updateProductPrice'])->name('Update product price');
});

Route::get('/', [\App\Http\Controllers\HomeController::class, 'index'])->name('Home');
Route::post('/messages', [\App\Http\Controllers\MessageController::class, 'sendMessage'])->name('Send message');
Route::get('/products', [\App\Http\Controllers\ProductController::class, 'index'])->name('Browse products');
Route::post('/addcart', [\App\Http\Controllers\CartController::class, 'addToCart'])->name('Add to cart');
Route::post('/deletefromcart', [\App\Http\Controllers\CartController::class, 'removeFromCart'])->name('Remove from cart');
Route::get('/clearfilter', function () {
    session()->forget('filter');
    return redirect()->route('Browse products');
});

Route::get('/contact', [\App\Http\Controllers>ContactController::class, 'index'])->name('Contact');
Route::get('/products/{id}', [\App\Http\Controllers\ProductController::class, 'showOne'])->name('Show one');
Route::get('/author', [\App\Http\Controllers\AuthorController::class, 'index'])->name('Author');
Route::get('/cart', [\App\Http\Controllers\CartController::class, 'index'])->name('Cart');

Route::middleware(['cartExist'])->group(function () {

Route::get('/checkout', [\App\Http\Controllers\CheckoutController::class, 'index'])->name('Checkout');

Route::post('/confirmorder', [\App\Http\Controllers\CheckoutController::class, 'confirmOrder'])->name('Confirm order');
});

Route::middleware(['notauthorized'])->group(function () {

Route::get('/login', [\App\Http\Controllers>LoginController::class, 'index'])->name('Login page');

```

```
Route::post('/login', [\App\Http\Controllers\LoginController::class, 'login']
)->name('Login');

Route::get('/register', [\App\Http\Controllers\RegisterController::class, 'index'])->name('Register page');

Route::post('/register', [\App\Http\Controllers\RegisterController::class, 'register'])->name('Register');
});
```



Nenad Jevtić 60/20

Web programiranje PHP 2

Datum: 26. 01. 2023.

Mesto: Beograd