

JSP Exception Handling

Using Java Exception Handling

test1.jsp

```
<%@ page language="java" %>
<%
    try
    {
        int x=10,y=0;
        int[] a={10,20};
        out.print(a[2]);
        out.print(x/y);
    }
    catch(ArrayIndexOutOfBoundsException ie)
    {
        out.print(ie);
    }
    catch(ArithmeticException ae)
    {
        out.print(ae);
    }
    catch(Exception e)
    {
        out.print(e);
    }
%>
```

java.lang.Exceptions Types

- ArithmeticException
- ArrayIndexOutOfBoundsException
- ClassNotFoundException
- FileNotFoundException
- IOException
- InterruptedException
- NoSuchFieldException
- NoSuchMethodException
- NullPointerException
- NumberFormatException
- RuntimeException
- StringIndexOutOfBoundsException

Using Page Directive

test.jsp

```
<%@ page language="java" errorPage="error.jsp"%>
<html>
<body>
    <%
        int x=10,y=0;
        int[] a={10,20};
    %>
    Answer = <%=x/y%>
    Value <%=a[2]%>
</body>
</html>
```

error.jsp

```
<%@ page language="java" isErrorPage="true"%>
<html>
<body>
<h3> Error :<font color="red"><%=exception%></font></h3>
<p> Message : <%=exception.getMessage()%> </p>
<p> Error stack : <% exception.printStackTrace(response.getWriter()); %>
</body>
</html>
```

Using Deployment Descriptor

test.jsp

```
<%@ page language="java" errorPage="error.jsp"%>
<html>
<body>
    Answer = <%=10/0%>
</body>
</html>
```

error.html

```
<html>
<body>
<h3> Error :<font color="red">Run Time Exception</font></h3>
</body>
</html>
```

error.jsp

```
<%@ page language="java" isErrorPage="true"%>
<html>
<body>
<h3> Compilation Error :<font color="red"><%=exception%></font></h3>
</body>
</html>
```

web.xml

```
<web-app>

    <error-page>
        <error-code>500</error-code>
        <location>/error.jsp </location>
    </error-page>

    <error-page>
        <exception-type>java.lang.Exception</exception-type>
        <location>/error.html</location>
    </error-page>

</web-app>
```