

JSTL C

```
<%@ page language="java" contentType="text/html; charset=UTF-8" pageEncoding="UTF-8"%>
<%@ taglib prefix="c" uri="jakarta.tags.core" %>
<html>
<head>
    <title>JSP Directive & JSTL Tags</title>
</head>
<body>

    <!-- 1. Variables and Simple Conditions --%>
    <c:set var="str" value="SPKM"/>
    <br>
    <c:if test="${str == 'SPKM'}">
        <c:out value="Hello ${str}"/>
    </c:if>

    <!-- 2. Multi-case Conditions (If-Else If-Else) --%>
    <c:choose>
        <c:when test="${str == 'SPKM'}">
            <p>Welcome to campus!</p>
        </c:when>
        <c:when test="${str == 'BCA'}">
            <p>Welcome to college!</p>
        </c:when>
        <c:otherwise>
            <p>Welcome, User!</p>
        </c:otherwise>
    </c:choose>

    <!-- 3. Standard Loops (For Loop) --%>
    <c:forEach var="i" begin="1" end="5" step="1">
        <p>Number: <c:out value="${i}"/></p>
    </c:forEach>

    <!-- 4. String Tokenization (Looping through a list) --%>
    <c:forTokens items="Java,JSP,JSTL,Jakarta" delims="," var="skill">
        <li>Skill: ${skill}</li>
    </c:forTokens>

    <!-- SIMILAR JAVA CODE (Scriptlets for comparison) --%>

    <%
        // 1. Equivalent Java for Variables & Simple Condition
        String str = "SPKM";
        if(str.equals("SPKM")) {
            out.print("<br>Hello " + str);
        }

        // 2. Equivalent Java for Multi-case Conditions
        if(str.equals("SPKM")) {
            out.print("<p>Welcome to campus!</p>");
        } else if(str.equals("BCA")) {
            out.print("<p>Welcome to college!</p>");
        } else {
            out.print("<p>Welcome, User!</p>");
        }

        // 3. Equivalent Java for Loops
        for(int i = 1; i <= 5; i++) {
            out.print("<p>Number: " + i + "</p>");
        }

        // 4. Equivalent Java for Tokenization
        String skills = "Java,JSP,JSTL,Jakarta";
        for(String skill : skills.split(",")) {
            out.print("<li>Skill: " + skill + "</li>");
        }
    %>

</body>
</html>
```