

## **Lab 2: Import Data to Neo4j**

### **Building Your Knowledge Graph**

## Concepts Introduced

**Neo4j Spark Connector** - A library that enables bidirectional data transfer between Spark DataFrames and Neo4j graphs.

### Key Concepts:

- **Nodes** - Entities in the graph (Customer, Account, Stock)
- **Relationships** - Connections between nodes (HAS\_ACCOUNT, AT\_BANK)
- **Properties** - Key-value attributes on nodes and relationships
- **Labels** - Categories that classify nodes (like table names)

### Graph vs Relational:

- Relationships are first-class citizens, not foreign keys
- Traversing connections is  $O(1)$ , not  $O(n)$  JOINS
- Schema-flexible: add properties without migrations

# The Neo4j Spark Connector


Bridges two data models:

Databricks (Tables)	Neo4j (Graph)
Rows become	Nodes
Foreign keys become	Relationships
Columns become	Properties

Why use both?

- Tables excel at aggregations and analytics
- Graphs excel at relationship traversals and pattern matching

## The Bridge: Neo4j Spark Connector



Data flows both ways through familiar DataFrame APIs.

## What the Neo4j Spark Connector Enables

- **Read** from Neo4j into Spark DataFrames
- **Write** from DataFrames into Neo4j
- **Stream** for continuous synchronization
- **Query** GDS algorithms and get results as DataFrames

No custom ETL scripts. Native Spark integration.

## The Key Insight: Graphs and Tables Are Interchangeable

Graphs and tables map bidirectionally:

Graph:

`(Person)-[:HAS]->(Job)`






Tables:

Person: [id, name, age]

Job: [id, title, salary]

HAS: [person\_id, job\_id, since]

- **Nodes**  rows (one table per label)
- **Relationships**  rows with source and target columns
- **Properties**  columns

This means you can both **export graphs to tables** and **import tables into graphs**.

## What We're Creating

Financial Knowledge Graph

(Customer)-[:HAS\_ACCOUNT]->(Account)-[:AT\_BANK]->(Bank)

|  
[:HAS\_POSITION]

|  
v

(Position)-[:OF\_SECURITY]->(Stock)-[:OF\_COMPANY]->(Company)

**764 nodes** across 7 types | **814 relationships** across 7 types

## Key Steps

1. **Configure** - Connect Spark to Neo4j via secrets
2. **Create constraints** - Indexes before data load
3. **Write nodes** - DataFrames become graph nodes
4. **Write relationships** - Foreign keys become edges
5. **Validate** - Verify counts match expectations

**Best Practice:** Use `coalesce(1)` for relationship writes to prevent deadlocks.



## Basic Node Write

```
df.write \  
  .format("org.neo4j.spark.DataSource") \  
  .option("url", "neo4j://localhost:7687") \  
  .option("authentication.type", "basic") \  
  .option("authentication.basic.username", "neo4j") \  
  .option("authentication.basic.password", "password") \  
  .option("labels", ":Customer") \  
  .option("node.keys", "customer_id") \  
  .mode("Overwrite") \  
  .save()
```

**Key options:** `labels` defines node labels, `node.keys` defines uniqueness.

**Save modes:** `Overwrite` uses MERGE (upsert), `Append` uses CREATE (always inserts).

## How MERGE Works

The write generates Cypher that merges rows in batches:

```
UNWIND $batch AS row
MERGE (n:Customer {customer_id: row.customer_id})
SET n.name = row.name, n.email = row.email, n.created_at = row.created_at
```

**UNWIND** unpacks the list, processing all rows in a single transaction.

## Basic Relationship Write

```
df.write.format("org.neo4j.spark.DataSource") \
    .mode("Append") \
    .option("relationship", "HAS_ACCOUNT") \
    .option("relationship.save.strategy", "keys") \
    .option("relationship.source.save.mode", "Match") \
    .option("relationship.source.labels", ":Customer") \
    .option("relationship.source.node.keys", "customer_id:customer_id") \
    .option("relationship.target.save.mode", "Match") \
    .option("relationship.target.labels", ":Account") \
    .option("relationship.target.node.keys", "account_id:account_id") \
    .save()
```

**Creates:** (:Customer {customer\_id})-[:HAS\_ACCOUNT]->(:Account {account\_id})

### Key Settings:

- **relationship** — The relationship type to create (e.g., `HAS_ACCOUNT` )
- **relationship.save.strategy: "keys"** — Match existing nodes by key properties
- **relationship.source/target.save.mode: "Match"** — Find existing nodes (don't create new ones)
- **relationship.source/target.node.keys** — Map DataFrame columns to node keys ( `df_col:node_prop` )

**Next:** Export graph data back to Delta Lake for AI agents