

# The Org Manual

---

Release 9.0 (release 9.0)

**by Carsten Dominik**

with contributions by Bastien Guerry, Nicolas Goaziou, Eric Schulte, Jambunathan K, Dan Davison, Thomas Dye, David O'Toole, and Philip Rooke.

---

This manual is for Org version 9.0 (release'9.0).

Copyright © 2004–2016 Free Software Foundation, Inc.

Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.3 or any later version published by the Free Software Foundation; with no Invariant Sections, with the Front-Cover Texts being “A GNU Manual,” and with the Back-Cover Texts as in (a) below. A copy of the license is included in the section entitled “GNU Free Documentation License.”

(a) The FSF’s Back-Cover Text is: “You have the freedom to copy and modify this GNU manual.”

## Short Contents

1	Introduction . . . . .	1
2	Document structure . . . . .	6
3	Tables . . . . .	19
4	Hyperlinks . . . . .	38
5	TODO items . . . . .	46
6	Tags . . . . .	59
7	Properties and columns . . . . .	64
8	Dates and times . . . . .	73
9	Capture - Refile - Archive . . . . .	89
10	Agenda views . . . . .	100
11	Markup for rich export . . . . .	128
12	Exporting . . . . .	135
13	Publishing . . . . .	183
14	Working with source code . . . . .	194
15	Miscellaneous . . . . .	224
A	Hacking . . . . .	237
B	MobileOrg . . . . .	252
C	History and acknowledgments . . . . .	254
D	GNU Free Documentation License . . . . .	260
	Concept index . . . . .	268
	Key index . . . . .	277
	Command and function index . . . . .	282
	Variable index . . . . .	286

# Table of Contents

<b>1</b>	<b>Introduction</b>	<b>1</b>
1.1	Summary	1
1.2	Installation	2
1.3	Activation	3
1.4	Feedback	3
1.5	Typesetting conventions used in this manual	4
<b>2</b>	<b>Document structure</b>	<b>6</b>
2.1	Outlines	6
2.2	Headlines	6
2.3	Visibility cycling	6
2.3.1	Global and local cycling	6
2.3.2	Initial visibility	8
2.3.3	Catching invisible edits	8
2.4	Motion	8
2.5	Structure editing	9
2.6	Sparse trees	11
2.7	Plain lists	12
2.8	Drawers	15
2.9	Blocks	16
2.10	Footnotes	16
2.11	The Orgstruct minor mode	17
2.12	Org syntax	18
<b>3</b>	<b>Tables</b>	<b>19</b>
3.1	The built-in table editor	19
3.2	Column width and alignment	22
3.3	Column groups	23
3.4	The Orgtbl minor mode	24
3.5	The spreadsheet	24
3.5.1	References	24
3.5.2	Formula syntax for Calc	27
3.5.3	Emacs Lisp forms as formulas	29
3.5.4	Durations and time values	29
3.5.5	Field and range formulas	29
3.5.6	Column formulas	30
3.5.7	Lookup functions	31
3.5.8	Editing and debugging formulas	31
3.5.9	Updating the table	34
3.5.10	Advanced features	34
3.6	Org-Plot	36

<b>4</b>	<b>Hyperlinks</b>	<b>38</b>
4.1	Link format	38
4.2	Internal links	38
4.2.1	Radio targets	39
4.3	External links	39
4.4	Handling links	41
4.5	Using links outside Org	44
4.6	Link abbreviations	44
4.7	Search options in file links	45
4.8	Custom Searches	45
<b>5</b>	<b>TODO items</b>	<b>46</b>
5.1	Basic TODO functionality	46
5.2	Extended use of TODO keywords	47
5.2.1	TODO keywords as workflow states	47
5.2.2	TODO keywords as types	48
5.2.3	Multiple keyword sets in one file	48
5.2.4	Fast access to TODO states	49
5.2.5	Setting up keywords for individual files	49
5.2.6	Faces for TODO keywords	50
5.2.7	TODO dependencies	50
5.3	Progress logging	52
5.3.1	Closing items	52
5.3.2	Tracking TODO state changes	52
5.3.3	Tracking your habits	53
5.4	Priorities	55
5.5	Breaking tasks down into subtasks	56
5.6	Checkboxes	56
<b>6</b>	<b>Tags</b>	<b>59</b>
6.1	Tag inheritance	59
6.2	Setting tags	59
6.3	Tag hierarchy	62
6.4	Tag searches	63
<b>7</b>	<b>Properties and columns</b>	<b>64</b>
7.1	Property syntax	64
7.2	Special properties	66
7.3	Property searches	66
7.4	Property Inheritance	67
7.5	Column view	67
7.5.1	Defining columns	68
7.5.1.1	Scope of column definitions	68
7.5.1.2	Column attributes	68
7.5.2	Using column view	70
7.5.3	Capturing column view	71
7.6	The Property API	72

<b>8</b>	<b>Dates and times</b>	<b>73</b>
8.1	Timestamps, deadlines, and scheduling	73
8.2	Creating timestamps	74
8.2.1	The date/time prompt	75
8.2.2	Custom time format	77
8.3	Deadlines and scheduling	77
8.3.1	Inserting deadlines or schedules	78
8.3.2	Repeated tasks	79
8.4	Clocking work time	80
8.4.1	Clocking commands	81
8.4.2	The clock table	83
8.4.3	Resolving idle time and continuous clocking	85
8.5	Effort estimates	86
8.6	Taking notes with a timer	87
<b>9</b>	<b>Capture - Refile - Archive</b>	<b>89</b>
9.1	Capture	89
9.1.1	Setting up capture	89
9.1.2	Using capture	89
9.1.3	Capture templates	90
9.1.3.1	Template elements	91
9.1.3.2	Template expansion	93
9.1.3.3	Templates in contexts	94
9.2	Attachments	95
9.3	RSS feeds	96
9.4	Protocols for external access	96
9.5	Refile and copy	97
9.6	Archiving	97
9.6.1	Moving a tree to the archive file	98
9.6.2	Internal archiving	98
<b>10</b>	<b>Agenda views</b>	<b>100</b>
10.1	Agenda files	100
10.2	The agenda dispatcher	101
10.3	The built-in agenda views	102
10.3.1	The weekly/daily agenda	102
10.3.2	The global TODO list	104
10.3.3	Matching tags and properties	105
10.3.4	Timeline for a single file	108
10.3.5	Search view	108
10.3.6	Stuck projects	108
10.4	Presentation and sorting	109
10.4.1	Categories	109
10.4.2	Time-of-day specifications	109
10.4.3	Sorting agenda items	110
10.4.4	Filtering/limiting agenda items	111
10.5	Commands in the agenda buffer	113

10.6	Custom agenda views .....	121
10.6.1	Storing searches .....	122
10.6.2	Block agenda .....	123
10.6.3	Setting options for custom commands .....	123
10.7	Exporting agenda views .....	124
10.8	Using column view in the agenda .....	126
<b>11</b>	<b>Markup for rich export .....</b>	<b>128</b>
11.1	Paragraphs, line breaks, and quoting .....	128
11.2	Emphasis and monospace .....	128
11.3	Horizontal rules .....	129
11.4	Images and Tables .....	129
11.5	Literal examples .....	129
11.6	Special symbols .....	131
11.7	Subscripts and superscripts .....	132
11.8	Embedded L <sup>A</sup> T <sub>E</sub> X .....	132
11.8.1	L <sup>A</sup> T <sub>E</sub> X fragments .....	132
11.8.2	Previewing L <sup>A</sup> T <sub>E</sub> X fragments .....	133
11.8.3	Using C <sup>D</sup> L <sup>A</sup> T <sub>E</sub> X to enter math .....	134
<b>12</b>	<b>Exporting .....</b>	<b>135</b>
12.1	The export dispatcher .....	135
12.2	Export settings .....	136
12.3	Table of contents .....	139
12.4	Include files .....	140
12.5	Macro replacement .....	141
12.6	Comment lines .....	142
12.7	ASCII/Latin-1/UTF-8 export .....	142
12.8	Beamer export .....	143
12.8.1	Beamer export commands .....	143
12.8.2	Beamer specific export settings .....	144
12.8.3	Sectioning, Frames and Blocks in Beamer .....	144
12.8.4	Beamer specific syntax .....	145
12.8.5	Editing support .....	146
12.8.6	A Beamer example .....	146
12.9	HTML export .....	147
12.9.1	HTML export commands .....	147
12.9.2	HTML Specific export settings .....	147
12.9.3	HTML doctypes .....	148
12.9.4	HTML preamble and postamble .....	149
12.9.5	Quoting HTML tags .....	149
12.9.6	Links in HTML export .....	150
12.9.7	Tables in HTML export .....	150
12.9.8	Images in HTML export .....	151
12.9.9	Math formatting in HTML export .....	151
12.9.10	Text areas in HTML export .....	152
12.9.11	CSS support .....	152
12.9.12	JavaScript supported display of web pages .....	153

12.10	$\text{\LaTeX}$ export .....	154
12.10.1	$\text{\LaTeX}$ export commands .....	154
12.10.2	$\text{\LaTeX}$ specific export settings .....	155
12.10.3	$\text{\LaTeX}$ header and sectioning structure .....	156
12.10.4	Quoting $\text{\LaTeX}$ code .....	156
12.10.5	Tables in $\text{\LaTeX}$ export .....	156
12.10.6	Images in $\text{\LaTeX}$ export .....	158
12.10.7	Plain lists in $\text{\LaTeX}$ export .....	159
12.10.8	Source blocks in $\text{\LaTeX}$ export .....	159
12.10.9	Example blocks in $\text{\LaTeX}$ export .....	160
12.10.10	Special blocks in $\text{\LaTeX}$ export .....	160
12.10.11	Horizontal rules in $\text{\LaTeX}$ export .....	161
12.11	Markdown export .....	161
12.12	OpenDocument Text export .....	162
12.12.1	Pre-requisites for ODT export .....	162
12.12.2	ODT export commands .....	162
12.12.3	ODT specific export settings .....	162
12.12.4	Extending ODT export .....	163
12.12.5	Applying custom styles .....	163
12.12.6	Links in ODT export .....	164
12.12.7	Tables in ODT export .....	164
12.12.8	Images in ODT export .....	165
12.12.9	Math formatting in ODT export .....	166
12.12.10	Labels and captions in ODT export .....	167
12.12.11	Literal examples in ODT export .....	168
12.12.12	Advanced topics in ODT export .....	168
12.13	Org export .....	173
12.14	Texinfo export .....	173
12.14.1	Texinfo export commands .....	173
12.14.2	Texinfo specific export settings .....	173
12.14.3	Texinfo file header .....	174
12.14.4	Texinfo title and copyright page .....	174
12.14.5	Texinfo ‘Top’ node .....	175
12.14.6	Headings and sectioning structure .....	175
12.14.7	Indices .....	176
12.14.8	Quoting Texinfo code .....	176
12.14.9	Plain lists in Texinfo export .....	176
12.14.10	Tables in Texinfo export .....	176
12.14.11	Images in Texinfo export .....	177
12.14.12	Special blocks .....	177
12.14.13	A Texinfo example .....	177
12.15	iCalendar export .....	178
12.16	Other built-in back-ends .....	179
12.17	Advanced configuration .....	179
12.18	Export in foreign buffers .....	182



<b>13</b>	<b>Publishing</b>	<b>183</b>
13.1	Configuration	183
13.1.1	The variable <code>org-publish-project-alist</code>	183
13.1.2	Sources and destinations for files	183
13.1.3	Selecting files	184
13.1.4	Publishing action	184
13.1.5	Options for the exporters	185
13.1.6	Links between published files	189
13.1.7	Generating a sitemap	189
13.1.8	Generating an index	190
13.2	Uploading files	191
13.3	Sample configuration	191
13.3.1	Example: simple publishing configuration	191
13.3.2	Example: complex publishing configuration	192
13.4	Triggering publication	192
<b>14</b>	<b>Working with source code</b>	<b>194</b>
14.1	Structure of code blocks	194
14.2	Editing source code	195
14.3	Exporting code blocks	196
14.4	Extracting source code	196
14.5	Evaluating code blocks	198
14.6	Library of Babel	199
14.7	Languages	199
14.8	Header arguments	200
14.8.1	Using header arguments	200
14.8.2	Specific header arguments	203
14.8.2.1	<code>:var</code>	203
14.8.2.2	<code>:results</code>	207
14.8.2.3	<code>:file</code>	209
14.8.2.4	<code>:file-desc</code>	209
14.8.2.5	<code>:file-ext</code>	209
14.8.2.6	<code>:output-dir</code>	209
14.8.2.7	<code>:dir</code> and remote execution	209
14.8.2.8	<code>:exports</code>	210
14.8.2.9	<code>:tangle</code>	211
14.8.2.10	<code>:mkdirp</code>	211
14.8.2.11	<code>:comments</code>	211
14.8.2.12	<code>:padline</code>	211
14.8.2.13	<code>:no-expand</code>	212
14.8.2.14	<code>:session</code>	212
14.8.2.15	<code>:noweb</code>	212
14.8.2.16	<code>:noweb-ref</code>	213
14.8.2.17	<code>:noweb-sep</code>	214
14.8.2.18	<code>:cache</code>	214
14.8.2.19	<code>:sep</code>	215
14.8.2.20	<code>:hlines</code>	215
14.8.2.21	<code>:colnames</code>	216

14.8.2.22	:rownames	217
14.8.2.23	:shebang	217
14.8.2.24	:tangle-mode	217
14.8.2.25	:eval	217
14.8.2.26	:wrap	218
14.8.2.27	:post	218
14.8.2.28	:prologue	219
14.8.2.29	:epilogue	219
14.9	Results of evaluation	219
14.9.1	Non-session	220
14.9.1.1	:results value	220
14.9.1.2	:results output	220
14.9.2	Session	220
14.9.2.1	:results value	220
14.9.2.2	:results output	220
14.10	Noweb reference syntax	221
14.11	Key bindings and useful functions	221
14.12	Batch execution	222
<b>15</b>	<b>Miscellaneous</b>	<b>224</b>
15.1	Completion	224
15.2	Easy templates	224
15.3	Speed keys	225
15.4	Code evaluation and security issues	225
15.5	Customization	226
15.6	Summary of in-buffer settings	226
15.7	The very busy C-c C-c key	230
15.8	A cleaner outline view	230
15.9	Using Org on a tty	232
15.10	Interaction with other packages	233
15.10.1	Packages that Org cooperates with	233
15.10.2	Packages that lead to conflicts with Org mode	234
15.11	org-crypt.el	235
<b>Appendix A</b>	<b>Hacking</b>	<b>237</b>
A.1	Hooks	237
A.2	Add-on packages	237
A.3	Adding hyperlink types	237
A.4	Adding export back-ends	238
A.5	Context-sensitive commands	239
A.6	Tables and lists in arbitrary syntax	239
A.6.1	Radio tables	240
A.6.2	A L <sup>A</sup> T <sub>E</sub> X example of radio tables	241
A.6.3	Translator functions	242
A.6.4	Radio lists	243
A.7	Dynamic blocks	244
A.8	Special agenda views	245
A.9	Speeding up your agendas	246

A.10	Extracting agenda information .....	247
A.11	Using the property API .....	248
A.12	Using the mapping API .....	249
<b>Appendix B</b>	<b>MobileOrg .....</b>	<b>252</b>
B.1	Setting up the staging area .....	252
B.2	Pushing to MobileOrg .....	252
B.3	Pulling from MobileOrg .....	253
<b>Appendix C</b>	<b>History and acknowledgments</b>	
	.....	<b>254</b>
C.1	From Carsten .....	254
C.2	From Bastien .....	255
C.3	List of contributions .....	255
<b>Appendix D</b>	<b>GNU Free Documentation License</b>	
	.....	<b>260</b>
<b>Concept index</b> .....		<b>268</b>
<b>Key index</b> .....		<b>277</b>
<b>Command and function index</b> .....		<b>282</b>
<b>Variable index</b> .....		<b>286</b>

# 1 Introduction

## 1.1 Summary

Org is a mode for keeping notes, maintaining TODO lists, and project planning with a fast and effective plain-text system. It also is an authoring system with unique support for literate programming and reproducible research.

Org is implemented on top of Outline mode, which makes it possible to keep the content of large files well structured. Visibility cycling and structure editing help to work with the tree. Tables are easily created with a built-in table editor. Plain text URL-like links connect to websites, emails, Usenet messages, BBDB entries, and any files related to the projects.

Org develops organizational tasks around notes files that contain lists or information about projects as plain text. Project planning and task management makes use of metadata which is part of an outline node. Based on this data, specific entries can be extracted in queries and create dynamic *agenda views* that also integrate the Emacs calendar and diary. Org can be used to implement many different project planning schemes, such as David Allen's GTD system.

Org files can serve as a single source authoring system with export to many different formats such as HTML, L<sup>A</sup>T<sub>E</sub>X, Open Document, and Markdown. New export backends can be derived from existing ones, or defined from scratch.

Org files can include source code blocks, which makes Org uniquely suited for authoring technical documents with code examples. Org source code blocks are fully functional; they can be evaluated in place and their results can be captured in the file. This makes it possible to create a single file reproducible research compendium.

Org keeps simple things simple. When first fired up, it should feel like a straightforward, easy to use outliner. Complexity is not imposed, but a large amount of functionality is available when needed. Org is a toolbox. Many users actually run only a (very personal) fraction of Org's capabilities, and know that there is more whenever they need it.

All of this is achieved with strictly plain text files, the most portable and future-proof file format. Org runs in Emacs. Emacs is one of the most widely ported programs, so that Org mode is available on every major platform.

There is a website for Org which provides links to the newest version of Org, as well as additional information, frequently asked questions (FAQ), links to tutorials, etc. This page is located at <http://orgmode.org>.

An earlier version (7.3) of this manual is available as a [paperback book from Network Theory Ltd.](#)

## 1.2 Installation

Org is part of recent distributions of GNU Emacs, so you normally don't need to install it. If, for one reason or another, you want to install Org on top of this pre-packaged version, there are three ways to do it:

- By using Emacs package system.
- By downloading Org as an archive.
- By using Org's git repository.

We **strongly recommend** to stick to a single installation method.

### Using Emacs packaging system

Recent Emacs distributions include a packaging system which lets you install Emacs libraries. You can install Org with *M-x package-install RET org*.

**Important:** you need to do this in a session where no `.org` file has been visited, i.e., where no Org built-in function have been loaded. Otherwise autoload Org functions will mess up the installation.

Then, to make sure your Org configuration is taken into account, initialize the package system with `(package-initialize)` in your `.emacs` before setting any Org option. If you want to use Org's package repository, check out the [Org ELPA page](#).

### Downloading Org as an archive

You can download Org latest release from [Org's website](#). In this case, make sure you set the load-path correctly in your `.emacs`:

```
(add-to-list 'load-path "~/path/to/orgdir/lisp")
```

The downloaded archive contains contributed libraries that are not included in Emacs. If you want to use them, add the `contrib` directory to your load-path:

```
(add-to-list 'load-path "~/path/to/orgdir/contrib/lisp" t)
```

Optionally, you can compile the files and/or install them in your system. Run `make help` to list compilation and installation options.

### Using Org's git repository

You can clone Org's repository and install Org like this:

```
$ cd ~/src/
$ git clone git://orgmode.org/org-mode.git
$ make autoloads
```

Note that in this case, `make autoloads` is mandatory: it defines Org's version in `org-version.el` and Org's autoloads in `org-loaddefs.el`.

Remember to add the correct load-path as described in the method above.

You can also compile with `make`, generate the documentation with `make doc`, create a local configuration with `make config` and install Org with `make install`. Please run `make help` to get the list of compilation/installation options.

For more detailed explanations on Org's build system, please check the Org Build System page on [Worg](#).

## 1.3 Activation

Org mode buffers need font-lock to be turned on: this is the default in Emacs<sup>1</sup>.

There are compatibility issues between Org mode and some other Elisp packages, please take the time to check the list (see [Section 15.10.2 \[Conflicts\]](#), page 234).

The four Org commands `org-store-link`, `org-capture`, `org-agenda`, and `org-iswitchb` should be accessible through global keys (i.e., anywhere in Emacs, not just in Org buffers). Here are suggested bindings for these keys, please modify the keys to your own liking.

```
(global-set-key "\C-cl" 'org-store-link)
(global-set-key "\C-ca" 'org-agenda)
(global-set-key "\C-cc" 'org-capture)
(global-set-key "\C-cb" 'org-iswitchb)
```

Files with the `.org` extension use Org mode by default. To turn on Org mode in a file that does not have the extension `.org`, make the first line of a file look like this:

```
MY PROJECTS    -*- mode: org; -*-
```

which will select Org mode for this buffer no matter what the file's name is. See also the variable `org-insert-mode-line-in-empty-file`.

Many commands in Org work on the region if the region is *active*. To make use of this, you need to have `transient-mark-mode` turned on, which is the default. If you do not like `transient-mark-mode`, you can create an active region by using the mouse to select a region, or pressing `C-SPC` twice before moving the cursor.

## 1.4 Feedback

If you find problems with Org, or if you have questions, remarks, or ideas about it, please mail to the Org mailing list [emacs-orgmode@gnu.org](mailto:emacs-orgmode@gnu.org). You can subscribe to the list [on this web page](#). If you are not a member of the mailing list, your mail will be passed to the list after a moderator has approved it<sup>2</sup>.

For bug reports, please first try to reproduce the bug with the latest version of Org available—if you are running an outdated version, it is quite possible that the bug has been fixed already. If the bug persists, prepare a report and provide as much information as possible, including the version information of Emacs (*M-x emacs-version RET*) and Org (*M-x org-version RET*), as well as the Org related setup in `.emacs`. The easiest way to do this is to use the command

```
M-x org-submit-bug-report RET
```

which will put all this information into an Emacs mail buffer so that you only need to add your description. If you are not sending the Email from within Emacs, please copy and paste the content into your Email program.

Sometimes you might face a problem due to an error in your Emacs or Org mode setup. Before reporting a bug, it is very helpful to start Emacs with minimal customizations and

<sup>1</sup> If you don't use font-lock globally, turn it on in Org buffer with `(add-hook 'org-mode-hook 'turn-on-font-lock)`

<sup>2</sup> Please consider subscribing to the mailing list, in order to minimize the work the mailing list moderators have to do.

reproduce the problem. Doing so often helps you determine if the problem is with your customization or with Org mode itself. You can start a typical minimal session with a command like the example below.

```
$ emacs -Q -l /path/to/minimal-org.el
```

However if you are using Org mode as distributed with Emacs, a minimal setup is not necessary. In that case it is sufficient to start Emacs as `emacs -Q`. The `minimal-org.el` setup file can have contents as shown below.

```
;;; Minimal setup to load latest 'org-mode'

;; activate debugging
(setq debug-on-error t
      debug-on-signal nil
      debug-on-quit nil)

;; add latest org-mode to load path
(add-to-list 'load-path (expand-file-name "/path/to/org-mode/lisp"))
(add-to-list 'load-path (expand-file-name "/path/to/org-mode/contrib/lisp" t))
```

If an error occurs, a backtrace can be very useful (see below on how to create one). Often a small example file helps, along with clear information about:

1. What exactly did you do?
2. What did you expect to happen?
3. What happened instead?

Thank you for helping to improve this program.

## How to create a useful backtrace

If working with Org produces an error with a message you don't understand, you may have hit a bug. The best way to report this is by providing, in addition to what was mentioned above, a *backtrace*. This is information from the built-in debugger about where and how the error occurred. Here is how to produce a useful backtrace:

1. Reload uncompiled versions of all Org mode Lisp files. The backtrace contains much more information if it is produced with uncompiled code. To do this, use

```
C-u M-x org-reload RET
```

or select **Org -> Refresh/Reload -> Reload Org uncompiled** from the menu.

2. Go to the **Options** menu and select **Enter Debugger on Error**.
3. Do whatever you have to do to hit the error. Don't forget to document the steps you take.
4. When you hit the error, a **\*Backtrace\*** buffer will appear on the screen. Save this buffer to a file (for example using `C-x C-w`) and attach it to your bug report.

## 1.5 Typesetting conventions used in this manual

## TODO keywords, tags, properties, etc.

Org mainly uses three types of keywords: TODO keywords, tags and property names. In this manual we use the following conventions:

TODO

**WAITING**     TODO keywords are written with all capitals, even if they are user-defined.

boss

**ARCHIVE**     User-defined tags are written in lowercase; built-in tags with special meaning are written with all capitals.

Release

**PRIORITY**    User-defined properties are capitalized; built-in properties with special meaning are written with all capitals.

Moreover, Org uses *option keywords* (like `#+TITLE` to set the title) and *environment keywords* (like `#+BEGIN_EXPORT html` to start a HTML environment). They are written in uppercase in the manual to enhance its readability, but you can use lowercase in your Org file.

## Key bindings and commands

The manual suggests a few global key bindings, in particular `C-c a` for `org-agenda` and `C-c c` for `org-capture`. These are only suggestions, but the rest of the manual assumes that these key bindings are in place in order to list commands by key access.

Also, the manual lists both the keys and the corresponding commands for accessing a functionality. Org mode often uses the same key for different functions, depending on context. The command that is bound to such keys has a generic name, like `org-metaright`. In the manual we will, wherever possible, give the function that is internally called by the generic command. For example, in the chapter on document structure, `M-right` will be listed to call `org-do-demote`, while in the chapter on tables, it will be listed to call `org-table-move-column-right`. If you prefer, you can compile the manual without the command names by unsetting the flag `cmdnames` in `org.texi`.



## 2 Document structure

Org is based on Outline mode and provides flexible commands to edit the structure of the document.

### 2.1 Outlines

Org is implemented on top of Outline mode. Outlines allow a document to be organized in a hierarchical structure, which (at least for me) is the best representation of notes and thoughts. An overview of this structure is achieved by folding (hiding) large parts of the document to show only the general document structure and the parts currently being worked on. Org greatly simplifies the use of outlines by compressing the entire show/hide functionality into a single command, `org-cycle`, which is bound to the `TAB` key.

### 2.2 Headlines

Headlines define the structure of an outline tree. The headlines in Org start with one or more stars, on the left margin<sup>12</sup>. For example:

```
* Top level headline
** Second level
*** 3rd level
    some text
*** 3rd level
    more text

* Another top level headline
```

Note that a headline named after `org-footnote-section`, which defaults to ‘Footnotes’, is considered as special. A subtree with this headline will be silently ignored by exporting functions.

Some people find the many stars too noisy and would prefer an outline that has white-space followed by a single star as headline starters. [Section 15.8 \[Clean view\]](#), page 230, describes a setup to realize this.

An empty line after the end of a subtree is considered part of it and will be hidden when the subtree is folded. However, if you leave at least two empty lines, one empty line will remain visible after folding the subtree, in order to structure the collapsed view. See the variable `org-cycle-separator-lines` to modify this behavior.

### 2.3 Visibility cycling

#### 2.3.1 Global and local cycling

Outlines make it possible to hide parts of the text in the buffer. Org uses just two commands, bound to `TAB` and `S-TAB` to change the visibility in the buffer.

<sup>1</sup> See the variables `org-special-ctrl-a/e`, `org-special-ctrl-k`, and `org-ctrl-k-protect-subtree` to configure special behavior of `C-a`, `C-e`, and `C-k` in headlines.

<sup>2</sup> Clocking only works with headings indented less than 30 stars.

TAB org-cycle

*Subtree cycling*: Rotate current subtree among the states

```
,-> FOLDED -> CHILDREN -> SUBTREE --.
'-----'
```

The cursor must be on a headline for this to work<sup>3</sup>. When the cursor is at the beginning of the buffer and the first line is not a headline, then TAB actually runs global cycling (see below)<sup>4</sup>. Also when called with a prefix argument (*C-u* TAB), global cycling is invoked.

*S-TAB* org-global-cycle

*C-u* TAB *Global cycling*: Rotate the entire buffer among the states

```
,-> OVERVIEW -> CONTENTS -> SHOW ALL --.
'-----'
```

When *S-TAB* is called with a numeric prefix argument N, the CONTENTS view up to headlines of level N will be shown. Note that inside tables, *S-TAB* jumps to the previous field.

*C-u C-u* TAB org-set-startup-visibility

Switch back to the startup visibility of the buffer (see [Section 2.3.2 \[Initial visibility\]](#), page 8).

*C-u C-u C-u* TAB outline-show-all

Show all, including drawers.

*C-c C-r* org-reveal

Reveal context around point, showing the current entry, the following heading and the hierarchy above. Useful for working near a location that has been exposed by a sparse tree command (see [Section 2.6 \[Sparse trees\]](#), page 11) or an agenda command (see [Section 10.5 \[Agenda commands\]](#), page 113). With a prefix argument show, on each level, all sibling headings. With a double prefix argument, also show the entire subtree of the parent.

*C-c C-k* outline-show-branches

Expose all the headings of the subtree, CONTENT view for just one subtree.

*C-c* TAB outline-show-children

Expose all direct children of the subtree. With a numeric prefix argument N, expose all children down to level N.

*C-c C-x b* org-tree-to-indirect-buffer

Show the current subtree in an indirect buffer<sup>5</sup>. With a numeric prefix argument N, go up to level N and then take that tree. If N is negative then go up that many levels. With a *C-u* prefix, do not remove the previously used indirect buffer.

<sup>3</sup> see, however, the option `org-cycle-emulate-tab`.

<sup>4</sup> see the option `org-cycle-global-at-bob`.

<sup>5</sup> The indirect buffer (see [Section “Indirect Buffers” in GNU Emacs Manual](#)) will contain the entire buffer, but will be narrowed to the current tree. Editing the indirect buffer will also change the original buffer, but without affecting visibility in that buffer.

`C-c C-x v` `org-copy-visible`  
 Copy the *visible* text in the region into the kill ring.

### 2.3.2 Initial visibility

When Emacs first visits an Org file, the global state is set to OVERVIEW, i.e., only the top level headlines are visible<sup>6</sup>. This can be configured through the variable `org-startup-folded`, or on a per-file basis by adding one of the following lines anywhere in the buffer:

```
#+STARTUP: overview
#+STARTUP: content
#+STARTUP: showall
#+STARTUP: showeverything
```

Furthermore, any entries with a ‘VISIBILITY’ property (see [Chapter 7 \[Properties and columns\]](#), [page 64](#)) will get their visibility adapted accordingly. Allowed values for this property are `folded`, `children`, `content`, and `all`.

`C-u C-u TAB` `org-set-startup-visibility`  
 Switch back to the startup visibility of the buffer, i.e., whatever is requested by startup options and ‘VISIBILITY’ properties in individual entries.

### 2.3.3 Catching invisible edits

Sometimes you may inadvertently edit an invisible part of the buffer and be confused on what has been edited and how to undo the mistake. Setting `org-catch-invisible-edits` to non-`nil` will help prevent this. See the docstring of this option on how Org should catch invisible edits and process them.

## 2.4 Motion

The following commands jump to other headlines in the buffer.

<code>C-c C-n</code>	<code>org-next-visible-heading</code>
Next heading.	
<code>C-c C-p</code>	<code>org-previous-visible-heading</code>
Previous heading.	
<code>C-c C-f</code>	<code>org-forward-same-level</code>
Next heading same level.	
<code>C-c C-b</code>	<code>org-backward-same-level</code>
Previous heading same level.	
<code>C-c C-u</code>	<code>outline-up-heading</code>
Backward to higher level heading.	
<code>C-c C-j</code>	<code>org-goto</code>
Jump to a different place without changing the current outline visibility. Shows the document structure in a temporary buffer, where you can use the following keys to find your destination:	

---

<sup>6</sup> When `org-agenda-inhibit-startup` is non-`nil`, Org will not honor the default visibility state when first opening a file for the agenda (see [Section A.9 \[Speeding up your agendas\]](#), [page 246](#)).

TAB	Cycle visibility.
down / up	Next/previous visible headline.
RET	Select this location.
/	Do a Sparse-tree search
The following keys work if you turn off <code>org-goto-auto-isearch</code>	
n / p	Next/previous visible headline.
f / b	Next/previous headline same level.
u	One level up.
0-9	Digit argument.
q	Quit

See also the option `org-goto-interface`.

## 2.5 Structure editing

<i>M-RET</i>	<code>org-insert-heading</code>
Insert a new heading/item with the same level as the one at point.	
If the command is used at the <i>beginning</i> of a line, and if there is a heading or a plain list item (see <a href="#">Section 2.7 [Plain lists]</a> , page 12) at point, the new heading/item is created <i>before</i> the current line. When used at the beginning of a regular line of text, turn that line into a heading.	
When this command is used in the middle of a line, the line is split and the rest of the line becomes the new item or headline. If you do not want the line to be split, customize <code>org-M-RET-may-split-line</code> .	
Calling the command with a <code>C-u</code> prefix unconditionally inserts a new heading at the end of the current subtree, thus preserving its contents. With a double <code>C-u C-u</code> prefix, the new heading is created at the end of the parent subtree instead.	
<i>C-RET</i>	<code>org-insert-heading-respect-content</code>
Insert a new heading at the end of the current subtree.	
<i>M-S-RET</i>	<code>org-insert-todo-heading</code>
Insert new TODO entry with same level as current heading. See also the variable <code>org-treat-insert-todo-heading-as-state-change</code> .	
<i>C-S-RET</i>	<code>org-insert-todo-heading-respect-content</code>
Insert new TODO entry with same level as current heading. Like <i>C-RET</i> , the new headline will be inserted after the current subtree.	
TAB	<code>org-cycle</code>
In a new entry with no text yet, the first TAB demotes the entry to become a child of the previous one. The next TAB makes it a parent, and so on, all the way to top level. Yet another TAB, and you are back to the initial level.	
<i>M-left</i>	<code>org-do-promote</code>
Promote current heading by one level.	
<i>M-right</i>	<code>org-do-demote</code>
Demote current heading by one level.	

<i>M-S-left</i>	<code>org-promote-subtree</code>
Promote the current subtree by one level.	
<i>M-S-right</i>	<code>org-demote-subtree</code>
Demote the current subtree by one level.	
<i>M-S-up</i>	<code>org-move-subtree-up</code>
Move subtree up (swap with previous subtree of same level).	
<i>M-S-down</i>	<code>org-move-subtree-down</code>
Move subtree down (swap with next subtree of same level).	
<i>M-h</i>	<code>org-mark-element</code>
Mark the element at point. Hitting repeatedly will mark subsequent elements of the one just marked. E.g., hitting <i>M-h</i> on a paragraph will mark it, hitting <i>M-h</i> immediately again will mark the next one.	
<i>C-c @</i>	<code>org-mark-subtree</code>
Mark the subtree at point. Hitting repeatedly will mark subsequent subtrees of the same level than the marked subtree.	
<i>C-c C-x C-w</i>	<code>org-cut-subtree</code>
Kill subtree, i.e., remove it from buffer but save in kill ring. With a numeric prefix argument N, kill N sequential subtrees.	
<i>C-c C-x M-w</i>	<code>org-copy-subtree</code>
Copy subtree to kill ring. With a numeric prefix argument N, copy the N sequential subtrees.	
<i>C-c C-x C-y</i>	<code>org-paste-subtree</code>
Yank subtree from kill ring. This does modify the level of the subtree to make sure the tree fits in nicely at the yank position. The yank level can also be specified with a numeric prefix argument, or by yanking after a headline marker like <i>****</i> .	
<i>C-y</i>	<code>org-yank</code>
Depending on the options <code>org-yank-adjusted-subtrees</code> and <code>org-yank-folded-subtrees</code> , Org's internal <code>yank</code> command will paste subtrees folded and in a clever way, using the same command as <i>C-c C-x C-y</i> . With the default settings, no level adjustment will take place, but the yanked tree will be folded unless doing so would swallow text previously visible. Any prefix argument to this command will force a normal <code>yank</code> to be executed, with the prefix passed along. A good way to force a normal yank is <i>C-u C-y</i> . If you use <code>yank-pop</code> after a yank, it will yank previous kill items plainly, without adjustment and folding.	
<i>C-c C-x c</i>	<code>org-clone-subtree-with-time-shift</code>
Clone a subtree by making a number of sibling copies of it. You will be prompted for the number of copies to make, and you can also specify if any timestamps in the entry should be shifted. This can be useful, for example, to create a number of tasks related to a series of lectures to prepare. For more details, see the docstring of the command <code>org-clone-subtree-with-time-shift</code> .	

<code>C-c C-w</code>	<code>org-refile</code> Refile entry or region to a different location. See <a href="#">Section 9.5 [Refile and copy]</a> , <a href="#">page 97</a> .
<code>C-c ^</code>	<code>org-sort</code> Sort same-level entries. When there is an active region, all entries in the region will be sorted. Otherwise the children of the current headline are sorted. The command prompts for the sorting method, which can be alphabetically, numerically, by time (first timestamp with active preferred, creation time, scheduled time, deadline time), by priority, by TODO keyword (in the sequence the keywords have been defined in the setup) or by the value of a property. Reverse sorting is possible as well. You can also supply your own function to extract the sorting key. With a <code>C-u</code> prefix, sorting will be case-sensitive.
<code>C-x n s</code>	<code>org-narrow-to-subtree</code> Narrow buffer to current subtree.
<code>C-x n b</code>	<code>org-narrow-to-block</code> Narrow buffer to current block.
<code>C-x n w</code>	<code>widen</code> Widen buffer to remove narrowing.
<code>C-c *</code>	<code>org-toggle-heading</code> Turn a normal line or plain list item into a headline (so that it becomes a subheading at its location). Also turn a headline into a normal line by removing the stars. If there is an active region, turn all lines in the region into headlines. If the first line in the region was an item, turn only the item lines into headlines. Finally, if the first line is a headline, remove the stars from all headlines in the region.

When there is an active region (Transient Mark mode), promotion and demotion work on all headlines in the region. To select a region of headlines, it is best to place both point and mark at the beginning of a line, mark at the beginning of the first headline, and point at the line just after the last headline to change. Note that when the cursor is inside a table (see [Chapter 3 \[Tables\]](#), [page 19](#)), the Meta-Cursor keys have different functionality.

## 2.6 Sparse trees

An important feature of Org mode is the ability to construct *sparse trees* for selected information in an outline tree, so that the entire document is folded as much as possible, but the selected information is made visible along with the headline structure above it<sup>7</sup>. Just try it out and you will see immediately how it works.

Org mode contains several commands for creating such trees, all these commands can be accessed through a dispatcher:

<code>C-c /</code>	<code>org-sparse-tree</code> This prompts for an extra key to select a sparse-tree creating command.
--------------------	---

---

<sup>7</sup> See also the variable `org-show-context-detail` to decide how much context is shown around each match.

<code>C-c / r</code> or <code>C-c / /</code>	<code>org-occur</code>
Prompts for a regexp and shows a sparse tree with all matches. If the match is in a headline, the headline is made visible. If the match is in the body of an entry, headline and body are made visible. In order to provide minimal context, also the full hierarchy of headlines above the match is shown, as well as the headline following the match. Each match is also highlighted; the highlights disappear when the buffer is changed by an editing command <sup>8</sup> , or by pressing <code>C-c C-c</code> . When called with a <code>C-u</code> prefix argument, previous highlights are kept, so several calls to this command can be stacked.	
<code>M-g n</code> or <code>M-g M-n</code>	<code>next-error</code>
Jump to the next sparse tree match in this buffer.	
<code>M-g p</code> or <code>M-g M-p</code>	<code>previous-error</code>
Jump to the previous sparse tree match in this buffer.	

For frequently used sparse trees of specific search strings, you can use the option `org-agenda-custom-commands` to define fast keyboard access to specific sparse trees. These commands will then be accessible through the agenda dispatcher (see [Section 10.2 \[Agenda dispatcher\]](#), page 101). For example:

```
(setq org-agenda-custom-commands
      '(("f" occur-tree "FIXME")))
```

will define the key `C-c a f` as a shortcut for creating a sparse tree matching the string ‘FIXME’.

The other sparse tree commands select headings based on TODO keywords, tags, or properties and will be discussed later in this manual.

To print a sparse tree, you can use the Emacs command `ps-print-buffer-with-faces` which does not print invisible parts of the document. Or you can use `C-c C-e C-v` to export only the visible part of the document and print the resulting file.

## 2.7 Plain lists

Within an entry of the outline tree, hand-formatted lists can provide additional structure. They also provide a way to create lists of checkboxes (see [Section 5.6 \[Checkboxes\]](#), page 56). Org supports editing such lists, and every exporter (see [Chapter 12 \[Exporting\]](#), page 135) can parse and format them.

Org knows ordered lists, unordered lists, and description lists.

- *Unordered* list items start with ‘-’, ‘+’, or ‘\*’<sup>9</sup> as bullets.
- *Ordered* list items start with a numeral followed by either a period or a right parenthesis<sup>10</sup>, such as ‘1.’ or ‘1)’<sup>11</sup>. If you want a list to start with a different value (e.g.,

<sup>8</sup> This depends on the option `org-remove-highlights-with-change`

<sup>9</sup> When using ‘\*’ as a bullet, lines must be indented or they will be seen as top-level headlines. Also, when you are hiding leading stars to get a clean outline view, plain list items starting with a star may be hard to distinguish from true headlines. In short: even though ‘\*’ is supported, it may be better to not use it for plain list items.

<sup>10</sup> You can filter out any of them by configuring `org-plain-list-ordered-item-terminator`.

<sup>11</sup> You can also get ‘a.’, ‘A.’, ‘a)’ and ‘A)’ by configuring `org-list-allow-alphabetical`. To minimize confusion with normal text, those are limited to one character only. Beyond that limit, bullets will automatically fallback to numbers.

20), start the text of the item with [020]<sup>12</sup>. Those constructs can be used in any item of the list in order to enforce a particular numbering.

- *Description* list items are unordered list items, and contain the separator ‘ :: ’ to distinguish the description *term* from the description.

Items belonging to the same list must have the same indentation on the first line. In particular, if an ordered list reaches number ‘10.’, then the 2-digit numbers must be written left-aligned with the other numbers in the list. An item ends before the next line that is less or equally indented than its bullet/number.

A list ends whenever every item has ended, which means before any line less or equally indented than items at top level. It also ends before two blank lines<sup>13</sup>. In that case, all items are closed. Here is an example:

```
** Lord of the Rings
  My favorite scenes are (in this order)
  1. The attack of the Rohirrim
  2. Eowyn's fight with the witch king
    + this was already my favorite scene in the book
    + I really like Miranda Otto.
  3. Peter Jackson being shot by Legolas
    - on DVD only
      He makes a really funny face when it happens.
  But in the end, no individual scenes matter but the film as a whole.
  Important actors in this film are:
  - Elijah Wood :: He plays Frodo
  - Sean Astin :: He plays Sam, Frodo's friend. I still remember
    him very well from his role as Mikey Walsh in The Goonies.
```

Org supports these lists by tuning filling and wrapping commands to deal with them correctly, and by exporting them properly (see [Chapter 12 \[Exporting\]](#), page 135). Since indentation is what governs the structure of these lists, many structural constructs like `#+BEGIN_...` blocks can be indented to signal that they belong to a particular item.

If you find that using a different bullet for a sub-list (than that used for the current list-level) improves readability, customize the variable `org-list-demote-modify-bullet`. To get a greater difference of indentation between items and their sub-items, customize `org-list-indent-offset`.

The following commands act on items when the cursor is in the first line of an item (the line with the bullet or number). Some of them imply the application of automatic rules to keep list structure intact. If some of these actions get in your way, configure `org-list-automatic-rules` to disable them individually.

TAB	<code>org-cycle</code>
Items can be folded just like headline levels. Normally this works only if the cursor is on a plain list item. For more details, see the variable <code>org-cycle-include-plain-lists</code> . If this variable is set to <code>integrate</code> , plain list items	

<sup>12</sup> If there's a checkbox in the item, the cookie must be put *before* the checkbox. If you have activated alphabetical lists, you can also use counters like [0b].

<sup>13</sup> See also `org-list-empty-line-terminates-plain-lists`.



will be treated like low-level headlines. The level of an item is then given by the indentation of the bullet/number. Items are always subordinate to real headlines, however; the hierarchies remain completely separated. In a new item with no text yet, the first TAB demotes the item to become a child of the previous one. Subsequent TABs move the item to meaningful levels in the list and eventually get it back to its initial position.

<b>M-RET</b>	<b>org-insert-heading</b> Insert new item at current level. With a prefix argument, force a new heading (see <a href="#">Section 2.5 [Structure editing]</a> , page 9). If this command is used in the middle of an item, that item is <i>split</i> in two, and the second part becomes the new item <sup>14</sup> . If this command is executed <i>before item's body</i> , the new item is created <i>before</i> the current one.
<b>M-S-RET</b>	Insert a new item with a checkbox (see <a href="#">Section 5.6 [Checkboxes]</a> , page 56).
<b>S-up</b>	
<b>S-down</b>	Jump to the previous/next item in the current list <sup>15</sup> , but only if <b>org-support-shift-select</b> is off. If not, you can still use paragraph jumping commands like <b>C-up</b> and <b>C-down</b> to quite similar effect.
<b>M-up</b>	
<b>M-down</b>	Move the item including subitems up/down <sup>16</sup> (swap with previous/next item of same indentation). If the list is ordered, renumbering is automatic.
<b>M-left</b>	
<b>M-right</b>	Decrease/increase the indentation of an item, leaving children alone.
<b>M-S-left</b>	
<b>M-S-right</b>	Decrease/increase the indentation of the item, including subitems. Initially, the item tree is selected based on current indentation. When these commands are executed several times in direct succession, the initially selected region is used, even if the new indentation would imply a different hierarchy. To use the new hierarchy, break the command chain with a cursor motion or so.  As a special case, using this command on the very first item of a list will move the whole list. This behavior can be disabled by configuring <b>org-list-automatic-rules</b> . The global indentation of a list has no influence on the text <i>after</i> the list.
<b>C-c C-c</b>	If there is a checkbox (see <a href="#">Section 5.6 [Checkboxes]</a> , page 56) in the item line, toggle the state of the checkbox. In any case, verify bullets and indentation consistency in the whole list.
<b>C-c -</b>	Cycle the entire list level through the different itemize/enumerate bullets ('-', '+', '*', '1.', '1') or a subset of them, depending on <b>org-plain-list-ordered-item-terminator</b> , the type of list, and its indentation. With a numeric prefix

<sup>14</sup> If you do not want the item to be split, customize the variable **org-M-RET-may-split-line**.

<sup>15</sup> If you want to cycle around items that way, you may customize **org-list-use-circular-motion**.

<sup>16</sup> See **org-list-use-circular-motion** for a cyclic behavior.

argument N, select the Nth bullet from this list. If there is an active region when calling this, all selected lines are converted to list items. With a prefix argument, selected text is changed into a single item. If the first line already was a list item, any item marker will be removed from the list. Finally, even without an active region, a normal line will be converted into a list item.

**C-c \*** Turn a plain list item into a headline (so that it becomes a subheading at its location). See [Section 2.5 \[Structure editing\]](#), page 9, for a detailed explanation.

**C-c C-\*** Turn the whole plain list into a subtree of the current heading. Checkboxes (see [Section 5.6 \[Checkboxes\]](#), page 56) will become TODO (resp. DONE) keywords when unchecked (resp. checked).

### *S-left/right*

This command also cycles bullet styles when the cursor is on the bullet or anywhere in an item line, details depending on `org-support-shift-select`.

**C-c ^** Sort the plain list. You will be prompted for the sorting method: numerically, alphabetically, by time, by checked status for check lists, or by a custom function.

## 2.8 Drawers

Sometimes you want to keep information associated with an entry, but you normally don't want to see it. For this, Org mode has *drawers*. They can contain anything but a headline and another drawer. Drawers look like this:

```
** This is a headline
Still outside the drawer
:DRAWERNAME:
This is inside the drawer.
:END:
After the drawer.
```

You can interactively insert drawers at point by calling `org-insert-drawer`, which is bound to **C-c C-x d**. With an active region, this command will put the region inside the drawer. With a prefix argument, this command calls `org-insert-property-drawer` and add a property drawer right below the current headline. Completion over drawer keywords is also possible using **M-TAB**.

Visibility cycling (see [Section 2.3 \[Visibility cycling\]](#), page 6) on the headline will hide and show the entry, but keep the drawer collapsed to a single line. In order to look inside the drawer, you need to move the cursor to the drawer line and press **TAB** there. Org mode uses the `PROPERTIES` drawer for storing properties (see [Chapter 7 \[Properties and columns\]](#), page 64), and you can also arrange for state change notes (see [Section 5.3.2 \[Tracking TODO state changes\]](#), page 52) and clock times (see [Section 8.4 \[Clocking work time\]](#), page 80) to be stored in a drawer `LOGBOOK`. If you want to store a quick note in the `LOGBOOK` drawer, in a similar way to state changes, use

**C-c C-z** Add a time-stamped note to the `LOGBOOK` drawer.

You can select the name of the drawers which should be exported with `org-export-with-drawers`. In that case, drawer contents will appear in export output. Property drawers are not affected by this variable: configure `org-export-with-properties` instead.

## 2.9 Blocks

Org mode uses begin...end blocks for various purposes from including source code examples (see [Section 11.5 \[Literal examples\]](#), page 129) to capturing time logging information (see [Section 8.4 \[Clocking work time\]](#), page 80). These blocks can be folded and unfolded by pressing TAB in the begin line. You can also get all blocks folded at startup by configuring the option `org-hide-block-startup` or on a per-file basis by using

```
#+STARTUP: hideblocks
#+STARTUP: nohideblocks
```

## 2.10 Footnotes

Org mode supports the creation of footnotes.

A footnote is started by a footnote marker in square brackets in column 0, no indentation allowed. It ends at the next footnote definition, headline, or after two consecutive empty lines. The footnote reference is simply the marker in square brackets, inside text. Markers always start with `fn:`. For example:

```
The Org homepage[fn:1] now looks a lot better than it used to.
...
[fn:1] The link is: http://orgmode.org
```

Org mode extends the number-based syntax to *named* footnotes and optional inline definition. Here are the valid references:

- `[fn:name]`  
A named footnote reference, where `name` is a unique label word, or, for simplicity of automatic creation, a number.
- `[fn::This is the inline definition of this footnote]`  
A L<sup>A</sup>T<sub>E</sub>X-like anonymous footnote where the definition is given directly at the reference point.
- `[fn:name:a definition]`  
An inline definition of a footnote, which also specifies a name for the note. Since Org allows multiple references to the same note, you can then use `[fn:name]` to create additional references.

Footnote labels can be created automatically, or you can create names yourself. This is handled by the variable `org-footnote-auto-label` and its corresponding `#+STARTUP` keywords. See the docstring of that variable for details.

The following command handles footnotes:

`C-c C-x f` The footnote action command.

When the cursor is on a footnote reference, jump to the definition. When it is at a definition, jump to the (first) reference.

Otherwise, create a new footnote. Depending on the option `org-footnote-define-inline`<sup>17</sup>, the definition will be placed right into the text as part of the reference, or separately into the location determined by the option `org-footnote-section`.

When this command is called with a prefix argument, a menu of additional options is offered:

- s** Sort the footnote definitions by reference sequence. During editing, Org makes no effort to sort footnote definitions into a particular sequence. If you want them sorted, use this command, which will also move entries according to `org-footnote-section`. Automatic sorting after each insertion/deletion can be configured using the option `org-footnote-auto-adjust`.
- r** Renumber the simple `fn:N` footnotes. Automatic renumbering after each insertion/deletion can be configured using the option `org-footnote-auto-adjust`.
- S** Short for first **r**, then **s** action.
- n** Normalize the footnotes by collecting all definitions (including inline definitions) into a special section, and then numbering them in sequence. The references will then also be numbers.
- d** Delete the footnote at point, and all definitions of and references to it.

Depending on the variable `org-footnote-auto-adjust`<sup>18</sup>, renumbering and sorting footnotes can be automatic after each insertion or deletion.

**C-c C-c** If the cursor is on a footnote reference, jump to the definition. If it is a the definition, jump back to the reference. When called at a footnote location with a prefix argument, offer the same menu as **C-c C-x f**.

**C-c C-o** or *mouse-1/2*

Footnote labels are also links to the corresponding definition/reference, and you can use the usual commands to follow these links.

**C-c '**

**C-c '** Edit the footnote definition corresponding to the reference at point in a separate window. The window can be closed by pressing **C-c '**.

## 2.11 The Orgstruct minor mode

If you like the intuitive way the Org mode structure editing and list formatting works, you might want to use these commands in other modes like Text mode or Mail mode as well. The minor mode `orgstruct-mode` makes this possible. Toggle the mode with `M-x orgstruct-mode RET`, or turn it on by default, for example in Message mode, with one of:

```
(add-hook 'message-mode-hook 'turn-on-orgstruct)
(add-hook 'message-mode-hook 'turn-on-orgstruct++)
```

<sup>17</sup> The corresponding in-buffer setting is: `#+STARTUP: fninline` or `#+STARTUP: nofninline`

<sup>18</sup> the corresponding in-buffer options are `fnadjust` and `nofnadjust`.

When this mode is active and the cursor is on a line that looks to Org like a headline or the first line of a list item, most structure editing commands will work, even if the same keys normally have different functionality in the major mode you are using. If the cursor is not in one of those special lines, Orgstruct mode lurks silently in the shadows.

When you use `orgstruct++-mode`, Org will also export indentation and autofill settings into that mode, and detect item context after the first line of an item.

You can also use Org structure editing to fold and unfold headlines in *any* file, provided you defined `orgstruct-heading-prefix-regexp`: the regular expression must match the local prefix to use before Org's headlines. For example, if you set this variable to `";; "` in Emacs Lisp files, you will be able to fold and unfold headlines in Emacs Lisp commented lines. Some commands like `org-demote` are disabled when the prefix is set, but folding/unfolding will work correctly.

## 2.12 Org syntax

A reference document providing a formal description of Org's syntax is available as [a draft on Worg](#), written and maintained by Nicolas Goaziou. It defines Org's core internal concepts such as `headlines`, `sections`, `affiliated keywords`, `(greater) elements` and `objects`. Each part of an Org file falls into one of the categories above.

To explore the abstract structure of an Org buffer, run this in a buffer:

```
M-: (org-element-parse-buffer) RET
```

It will output a list containing the buffer's content represented as an abstract structure. The export engine relies on the information stored in this list. Most interactive commands (e.g., for structure editing) also rely on the syntactic meaning of the surrounding context.

You can check syntax in your documents using `org-lint` command.

## 3 Tables

Org comes with a fast and intuitive table editor. Spreadsheet-like calculations are supported using the Emacs `calc` package (see *Gnu Emacs Calculator Manual*).

### 3.1 The built-in table editor

Org makes it easy to format tables in plain ASCII. Any line with ‘|’ as the first non-whitespace character is considered part of a table. ‘|’ is also the column separator<sup>1</sup>. A table might look like this:

```
| Name | Phone | Age |
|-----+-----+-----|
| Peter | 1234 | 17 |
| Anna | 4321 | 25 |
```

A table is re-aligned automatically each time you press `TAB` or `RET` or `C-c C-c` inside the table. `TAB` also moves to the next field (`RET` to the next row) and creates new table rows at the end of the table or before horizontal lines. The indentation of the table is set by the first line. Any line starting with ‘|–’ is considered as a horizontal separator line and will be expanded on the next re-align to span the whole table width. So, to create the above table, you would only type

```
|Name|Phone|Age|
|–
```

and then press `TAB` to align the table and start filling in fields. Even faster would be to type `|Name|Phone|Age` followed by `C-c RET`.

When typing text into a field, Org treats `DEL`, `Backspace`, and all character keys in a special way, so that inserting and deleting avoids shifting other fields. Also, when typing *immediately after the cursor was moved into a new field with `TAB`, `S-TAB` or `RET`*, the field is automatically made blank. If this behavior is too unpredictable for you, configure the options `org-enable-table-editor` and `org-table-auto-blank-field`.

#### Creation and conversion

`C-c |` `org-table-create-or-convert-from-region`  
 Convert the active region to a table. If every line contains at least one `TAB` character, the function assumes that the material is tab separated. If every line contains a comma, comma-separated values (CSV) are assumed. If not, lines are split at whitespace into fields. You can use a prefix argument to force a specific separator: `C-u` forces CSV, `C-u C-u` forces TAB, `C-u C-u C-u` will prompt for a regular expression to match the separator, and a numeric argument `N` indicates that at least `N` consecutive spaces, or alternatively a TAB will be the separator. If there is no active region, this command creates an empty Org table. But it is easier just to start typing, like `|Name|Phone|Age RET |– TAB`.

#### Re-aligning and field motion

`C-c C-c` `org-table-align`  
 Re-align the table and don’t move to another field.

<sup>1</sup> To insert a vertical bar into a table field, use `\vert` or, inside a word `abc\vert{}def`.

<i>C-c SPC</i>	<code>org-table-blank-field</code>
	Blank the field at point.
<i>&lt;TAB&gt;</i>	<code>org-table-next-field</code>
	Re-align the table, move to the next field. Creates a new row if necessary.
<i>S-TAB</i>	<code>org-table-previous-field</code>
	Re-align, move to previous field.
<i>RET</i>	<code>org-table-next-row</code>
	Re-align the table and move down to next row. Creates a new row if necessary. At the beginning or end of a line, <code>RET</code> still does <code>NEWLINE</code> , so it can be used to split a table.
<i>M-a</i>	<code>org-table-beginning-of-field</code>
	Move to beginning of the current table field, or on to the previous field.
<i>M-e</i>	<code>org-table-end-of-field</code>
	Move to end of the current table field, or on to the next field.
<b>Column and row editing</b>	
<i>M-left</i>	<code>org-table-move-column-left</code>
<i>M-right</i>	<code>org-table-move-column-right</code>
	Move the current column left/right.
<i>M-S-left</i>	<code>org-table-delete-column</code>
	Kill the current column.
<i>M-S-right</i>	<code>org-table-insert-column</code>
	Insert a new column to the left of the cursor position.
<i>M-up</i>	<code>org-table-move-row-up</code>
<i>M-down</i>	<code>org-table-move-row-down</code>
	Move the current row up/down.
<i>M-S-up</i>	<code>org-table-kill-row</code>
	Kill the current row or horizontal line.
<i>M-S-down</i>	<code>org-table-insert-row</code>
	Insert a new row above the current row. With a prefix argument, the line is created below the current one.
<i>C-c -</i>	<code>org-table-insert-hline</code>
	Insert a horizontal line below current row. With a prefix argument, the line is created above the current line.
<i>C-c RET</i>	<code>org-table-hline-and-move</code>
	Insert a horizontal line below current row, and move the cursor into the row below that line.
<i>C-c ^</i>	<code>org-table-sort-lines</code>
	Sort the table lines in the region. The position of point indicates the column to be used for sorting, and the range of lines is the range between the nearest horizontal separator lines, or the entire table. If point is before the first column, you will be prompted for the sorting column. If there is an active region, the

mark specifies the first line and the sorting column, while point should be in the last line to be included into the sorting. The command prompts for the sorting type (alphabetically, numerically, or by time). You can sort in normal or reverse order. You can also supply your own key extraction and comparison functions. When called with a prefix argument, alphabetic sorting will be case-sensitive.

## Regions

*C-c C-x M-w* **org-table-copy-region**

Copy a rectangular region from a table to a special clipboard. Point and mark determine edge fields of the rectangle. If there is no active region, copy just the current field. The process ignores horizontal separator lines.

*C-c C-x C-w* **org-table-cut-region**

Copy a rectangular region from a table to a special clipboard, and blank all fields in the rectangle. So this is the “cut” operation.

*C-c C-x C-y* **org-table-paste-rectangle**

Paste a rectangular region into a table. The upper left corner ends up in the current field. All involved fields will be overwritten. If the rectangle does not fit into the present table, the table is enlarged as needed. The process ignores horizontal separator lines.

*M-RET* **org-table-wrap-region**

Split the current field at the cursor position and move the rest to the line below. If there is an active region, and both point and mark are in the same column, the text in the column is wrapped to minimum width for the given number of lines. A numeric prefix argument may be used to change the number of desired lines. If there is no region, but you specify a prefix argument, the current field is made blank, and the content is appended to the field above.

## Calculations

*C-c +* **org-table-sum**

Sum the numbers in the current column, or in the rectangle defined by the active region. The result is shown in the echo area and can be inserted with *C-y*.

*S-RET* **org-table-copy-down**

When current field is empty, copy from first non-empty field above. When not empty, copy current field down to next row and move cursor along with it. Depending on the option **org-table-copy-increment**, integer field values will be incremented during copy. Integers that are too large will not be incremented. Also, a 0 prefix argument temporarily disables the increment. This key is also used by shift-selection and related modes (see [Section 15.10.2 \[Conflicts\]](#), [page 234](#)).

## Miscellaneous

*C-c `* **org-table-edit-field**

Edit the current field in a separate window. This is useful for fields that are not fully visible (see [Section 3.2 \[Column width and alignment\]](#), [page 22](#)). When called with a *C-u* prefix, just make the full field visible, so that it can be edited



in place. When called with two `C-u` prefixes, make the editor window follow the cursor through the table and always show the current field. The follow mode exits automatically when the cursor leaves the table, or when you repeat this command with `C-u C-u C-c ``.

***M-x org-table-import RET***

Import a file as a table. The table should be TAB or whitespace separated. Use, for example, to import a spreadsheet table or data from a database, because these programs generally can write TAB-separated text files. This command works by inserting the file into the buffer and then converting the region to a table. Any prefix argument is passed on to the converter, which uses it to determine the separator.

***C-c | org-table-create-or-convert-from-region***

Tables can also be imported by pasting tabular text into the Org buffer, selecting the pasted text with `C-x C-x` and then using the `C-c |` command (see above under *Creation and conversion*).

***M-x org-table-export RET***

Export the table, by default as a TAB-separated file. Use for data exchange with, for example, spreadsheet or database programs. The format used to export the file can be configured in the option `org-table-export-default-format`. You may also use properties `TABLE_EXPORT_FILE` and `TABLE_EXPORT_FORMAT` to specify the file name and the format for table export in a subtree. Org supports quite general formats for exported tables. The exporter format is the same as the format used by Orgtbl radio tables, see [Section A.6.3 \[Translator functions\]](#), page 242, for a detailed description.

If you don't like the automatic table editor because it gets in your way on lines which you would like to start with `'|'`, you can turn it off with

```
(setq org-enable-table-editor nil)
```

Then the only table command that still works is `C-c C-c` to do a manual re-align.

## 3.2 Column width and alignment

The width of columns is automatically determined by the table editor. And also the alignment of a column is determined automatically from the fraction of number-like versus non-number fields in the column.

Sometimes a single field or a few fields need to carry more text, leading to inconveniently wide columns. Or maybe you want to make a table with several columns having a fixed width, regardless of content. To set the width of a column, one field anywhere in the column may contain just the string `<N>` where `'N'` is an integer specifying the width of the column in characters. The next re-align will then set the width of this column to this value.

	----				----	
	1		one			
	2		two		----	
	3		This is a long chunk of text		----	
	4		four			
	----				----	

Fields that are wider become clipped and end in the string ‘=>’. Note that the full text is still in the buffer but is hidden. To see the full text, hold the mouse over the field—a tool-tip window will show the full content. To edit such a field, use the command `C-c `` (that is `C-c` followed by the grave accent). This will open a new window with the full field. Edit it and finish with `C-c C-c`.

When visiting a file containing a table with narrowed columns, the necessary character hiding has not yet happened, and the table needs to be aligned before it looks nice. Setting the option `org-startup-align-all-tables` will realign all tables in a file upon visiting, but also slow down startup. You can also set this option on a per-file basis with:

```
#+STARTUP: align
#+STARTUP: noalign
```

If you would like to overrule the automatic alignment of number-rich columns to the right and of string-rich columns to the left, you can use ‘<r>’, ‘<c>’<sup>2</sup> or ‘<l>’ in a similar fashion. You may also combine alignment and field width like this: ‘<r10>’.

Lines which only contain these formatting cookies will be removed automatically when exporting the document.

### 3.3 Column groups

When Org exports tables, it does so by default without vertical lines because that is visually more satisfying in general. Occasionally however, vertical lines can be useful to structure a table into groups of columns, much like horizontal lines can do for groups of rows. In order to specify column groups, you can use a special row where the first field contains only ‘/’. The further fields can either contain ‘<’ to indicate that this column should start a group, ‘>’ to indicate the end of a group, or ‘<>’ (no space between ‘<’ and ‘>’) to make a column a group of its own. Boundaries between column groups will upon export be marked with vertical lines. Here is an example:

	N		N <sup>2</sup>		N <sup>3</sup>		N <sup>4</sup>		~sqrt(n)~		~sqrt[4](N)~	
	/		<				>		<		>	
	1		1		1		1		1		1	
	2		4		8		16		1.4142		1.1892	
	3		9		27		81		1.7321		1.3161	
	----		----		----		----		----		----	

```
#+TBLFM: $2=$1^2::$3=$1^3::$4=$1^4::$5=sqrt($1)::6=sqrt(sqrt(($1)))
```

It is also sufficient to just insert the column group starters after every vertical line you would like to have:

<sup>2</sup> Centering does not work inside Emacs, but it does have an effect when exporting to HTML.

	N		N^2		N^3		N^4		sqrt(n)		sqrt[4](N)	
	----		-----		-----		-----		-----		-----	
	/		<						<			

### 3.4 The Orgtbl minor mode

If you like the intuitive way the Org table editor works, you might also want to use it in other modes like Text mode or Mail mode. The minor mode Orgtbl mode makes this possible. You can always toggle the mode with *M-x orgtbl-mode RET*. To turn it on by default, for example in Message mode, use

```
(add-hook 'message-mode-hook 'turn-on-orgtbl)
```

Furthermore, with some special setup, it is possible to maintain tables in arbitrary syntax with Orgtbl mode. For example, it is possible to construct L<sup>A</sup>T<sub>E</sub>X tables with the underlying ease and power of Orgtbl mode, including spreadsheet capabilities. For details, see [Section A.6 \[Tables in arbitrary syntax\]](#), page 239.

### 3.5 The spreadsheet

The table editor makes use of the Emacs `calc` package to implement spreadsheet-like capabilities. It can also evaluate Emacs Lisp forms to derive fields from other fields. While fully featured, Org's implementation is not identical to other spreadsheets. For example, Org knows the concept of a *column formula* that will be applied to all non-header fields in a column without having to copy the formula to each relevant field. There is also a formula debugger, and a formula editor with features for highlighting fields in the table corresponding to the references at the point in the formula, moving these references by arrow keys

#### 3.5.1 References

To compute fields in the table from other fields, formulas must reference other fields or ranges. In Org, fields can be referenced by name, by absolute coordinates, and by relative coordinates. To find out what the coordinates of a field are, press *C-c ?* in that field, or press *C-c }* to toggle the display of a grid.

#### Field references

Formulas can reference the value of another field in two ways. Like in any other spreadsheet, you may reference fields with a letter/number combination like B3, meaning the 2nd field in the 3rd row. However, Org prefers<sup>3</sup> to use another, more general representation that looks like this:

`@row$column`

Column specifications can be absolute like \$1, \$2,...\$N, or relative to the current column (i.e., the column of the field which is being computed) like \$+1 or \$-2. \$< and \$> are immutable references to the first and last column, respectively, and you can use \$>>> to indicate the third column from the right.

<sup>3</sup> Org will understand references typed by the user as 'B4', but it will not use this syntax when offering a formula for editing. You can customize this behavior using the option `org-table-use-standard-references`.

The row specification only counts data lines and ignores horizontal separator lines (hlines). Like with columns, you can use absolute row numbers `@1`, `@2`,...`@N`, and row numbers relative to the current row like `@+3` or `@-1`. `@<` and `@>` are immutable references the first and last<sup>4</sup> row in the table, respectively. You may also specify the row relative to one of the hlines: `@I` refers to the first hline, `@II` to the second, etc. `@-I` refers to the first such line above the current line, `@+I` to the first such line below the current line. You can also write `@III+2` which is the second data line after the third hline in the table.

`@0` and `$0` refer to the current row and column, respectively, i.e., to the row/column for the field being computed. Also, if you omit either the column or the row part of the reference, the current row/column is implied.

Org's references with *unsigned* numbers are fixed references in the sense that if you use the same reference in the formula for two different fields, the same field will be referenced each time. Org's references with *signed* numbers are floating references because the same reference operator can reference different fields depending on the field being calculated by the formula.

Here are a few examples:

<code>@2\$3</code>	2nd row, 3rd column (same as <code>C2</code> )
<code>\$5</code>	column 5 in the current row (same as <code>E&amp;</code> )
<code>@2</code>	current column, row 2
<code>@-1\$-3</code>	the field one row up, three columns to the left
<code>@-I\$2</code>	field just under hline above current row, column 2
<code>@&gt;\$5</code>	field in the last row, in column 5

## Range references

You may reference a rectangular range of fields by specifying two field references connected by two dots `..`. If both fields are in the current row, you may simply use `$2..$7`, but if at least one field is in a different row, you need to use the general `@row$column` format at least for the first field (i.e the reference must start with `@` in order to be interpreted correctly). Examples:

<code>\$1..\$3</code>	first three fields in the current row
<code>\$P..\$Q</code>	range, using column names (see under Advanced)
<code>\$&lt;&lt;&lt;..\$&gt;&gt;</code>	start in third column, continue to the last but one
<code>@2\$1..@4\$3</code>	6 fields between these two fields (same as <code>A2..C4</code> )
<code>@-1\$-2..@-1</code>	3 fields in the row above, starting from 2 columns on the left
<code>@I..II</code>	between first and second hline, short for <code>@I..@II</code>

Range references return a vector of values that can be fed into Calc vector functions. Empty fields in ranges are normally suppressed, so that the vector contains only the non-empty fields. For other options with the mode switches `'E'`, `'N'` and examples see [Section 3.5.2 \[Formula syntax for Calc\]](#), page 27.

---

<sup>4</sup> For backward compatibility you can also use special names like `$LR5` and `$LR12` to refer in a stable way to the 5th and 12th field in the last row of the table. However, this syntax is deprecated, it should not be used for new documents. Use `@>$` instead.

## Field coordinates in formulas

One of the very first actions during evaluation of Calc formulas and Lisp formulas is to substitute `@#` and `$#` in the formula with the row or column number of the field where the current result will go to. The traditional Lisp formula equivalents are `org-table-current-dline` and `org-table-current-column`. Examples:

```
if(@# % 2, $#, string(""))
```

Insert column number on odd rows, set field to empty on even rows.

```
$2 = '(identity remote(F00, @@#$1))
```

Copy text or values of each row of column 1 of the table named F00 into column 2 of the current table.

```
@3 = 2 * remote(F00, @1$$#)
```

Insert the doubled value of each column of row 1 of the table named F00 into row 3 of the current table.

For the second/third example, the table named F00 must have at least as many rows/columns as the current table. Note that this is inefficient<sup>5</sup> for large number of rows/columns.

## Named references

`'$name'` is interpreted as the name of a column, parameter or constant. Constants are defined globally through the option `org-table-formula-constants`, and locally (for the file) through a line like

```
#+CONSTANTS: c=299792458. pi=3.14 eps=2.4e-6
```

Also properties (see [Chapter 7 \[Properties and columns\]](#), page 64) can be used as constants in table formulas: for a property `':Xyz:'` use the name `'$PROP_Xyz'`, and the property will be searched in the current outline entry and in the hierarchy above it. If you have the `constants.el` package, it will also be used to resolve constants, including natural constants like `'$h'` for Planck's constant, and units like `'$km'` for kilometers<sup>6</sup>. Column names and parameters can be specified in special table lines. These are described below, see [Section 3.5.10 \[Advanced features\]](#), page 34. All names must start with a letter, and further consist of letters and numbers.

## Remote references

You may also reference constants, fields and ranges from a different table, either in the current file or even in a different file. The syntax is

```
remote(NAME-OR-ID,REF)
```

where NAME can be the name of a table in the current file as set by a `#+NAME: Name` line before the table. It can also be the ID of an entry, even in a different file, and the reference then refers to the first table in that entry. REF is an absolute field or range reference as described above for example `@3$3` or `$somename`, valid in the referenced table.

<sup>5</sup> The computation time scales as  $O(N^2)$  because the table named F00 is parsed for each field to be read.

<sup>6</sup> `constants.el` can supply the values of constants in two different unit systems, SI and cgs. Which one is used depends on the value of the variable `constants-unit-system`. You can use the `#+STARTUP` options `constSI` and `constcgs` to set this value for the current buffer.

Indirection of NAME-OR-ID: When NAME-OR-ID has the format @ROW\$COLUMN it will be substituted with the name or ID found in this field of the current table. For example `remote($1, @>$2) => remote(year_2013, @>$1)`. The format B3 is not supported because it can not be distinguished from a plain table name or ID.

### 3.5.2 Formula syntax for Calc

A formula can be any algebraic expression understood by the Emacs `Calc` package. Note that `calc` has the non-standard convention that `/` has lower precedence than `*`, so that `'a/b*c'` is interpreted as `'a/(b*c)'`. Before evaluation by `calc-eval` (see [Section “Calling Calc from Your Lisp Programs” in GNU Emacs Calc Manual](#)), variable substitution takes place according to the rules described above. The range vectors can be directly fed into the Calc vector functions like `'vmean'` and `'vsum'`.

A formula can contain an optional mode string after a semicolon. This string consists of flags to influence Calc and other modes during execution. By default, Org uses the standard Calc modes (precision 12, angular units degrees, fraction and symbolic modes off). The display format, however, has been changed to (float 8) to keep tables compact. The default settings can be configured using the option `org-calc-default-modes`.

List of modes:

p20	Set the internal Calc calculation precision to 20 digits.
n3, s3, e2, f4	Normal, scientific, engineering or fixed format of the result of Calc passed back to Org. Calc formatting is unlimited in precision as long as the Calc calculation precision is greater.
D, R	Degree and radian angle modes of Calc.
F, S	Fraction and symbolic modes of Calc.
T, t	Duration computations in Calc or Lisp, see <a href="#">Section 3.5.4 [Durations and time values]</a> , page 29.
E	If and how to consider empty fields. Without 'E' empty fields in range references are suppressed so that the Calc vector or Lisp list contains only the non-empty fields. With 'E' the empty fields are kept. For empty fields in ranges or empty field references the value <code>'nan'</code> (not a number) is used in Calc formulas and the empty string is used for Lisp formulas. Add 'N' to use 0 instead for both formula types. For the value of a field the mode 'N' has higher precedence than 'E'.
N	Interpret all fields as numbers, use 0 for non-numbers. See the next section to see how this is essential for computations with Lisp formulas. In Calc formulas it is used only occasionally because there number strings are already interpreted as numbers without 'N'.
L	Literal, for Lisp formulas only. See the next section.

Unless you use large integer numbers or high-precision-calculation and -display for floating point numbers you may alternatively provide a `'printf'` format specifier to reformat the

Calc result after it has been passed back to Org instead of letting Calc already do the formatting<sup>7</sup>. A few examples:

<code>\$1+\$2</code>	Sum of first and second field
<code>\$1+\$2;%.2f</code>	Same, format result to two decimals
<code>exp(\$2)+exp(\$1)</code>	Math functions can be used
<code>\$0;%.1f</code>	Reformat current cell to 1 decimal
<code>(\$3-32)*5/9</code>	Degrees F -> C conversion
<code>\$c/\$1/\$cm</code>	Hz -> cm conversion, using <code>constants.el</code>
<code>tan(\$1);Dp3s1</code>	Compute in degrees, precision 3, display SCI 1
<code>sin(\$1);Dp3%.1e</code>	Same, but use printf specifier for display
<code>taylor(\$3,x=7,2)</code>	Taylor series of \$3, at x=7, second degree

Calc also contains a complete set of logical operations, (see [Section “Logical Operations”](#) in *GNU Emacs Calc Manual*). For example

```
if($1 < 20, teen, string(""))
    "teen" if age $1 is less than 20, else the Org table result field is set to empty
    with the empty string.
```

```
if("$1" == "nan" || "$2" == "nan", string(""), $1 + $2); E f-1
    Sum of the first two columns. When at least one of the input fields is empty
    the Org table result field is set to empty. ‘E’ is required to not convert empty
    fields to 0. ‘f-1’ is an optional Calc format string similar to ‘%.1f’ but leaves
    empty results empty.
```

```
if(typeof(vmean($1..$7)) == 12, string(""), vmean($1..$7); E
    Mean value of a range unless there is any empty field. Every field in the range
    that is empty is replaced by ‘nan’ which lets ‘vmean’ result in ‘nan’. Then
    ‘typeof == 12’ detects the ‘nan’ from ‘vmean’ and the Org table result field is
    set to empty. Use this when the sample set is expected to never have missing
    values.
```

```
if("$1..$7" == "[]", string(""), vmean($1..$7))
    Mean value of a range with empty fields skipped. Every field in the range that
    is empty is skipped. When all fields in the range are empty the mean value is
    not defined and the Org table result field is set to empty. Use this when the
    sample set can have a variable size.
```

```
vmean($1..$7); EN
    To complete the example before: Mean value of a range with empty fields
    counting as samples with value 0. Use this only when incomplete sample sets
    should be padded with 0 to the full size.
```

You can add your own Calc functions defined in Emacs Lisp with `defmath` and use them in formula syntax for Calc.

---

<sup>7</sup> The ‘printf’ reformatting is limited in precision because the value passed to it is converted into an ‘integer’ or ‘double’. The ‘integer’ is limited in size by truncating the signed value to 32 bits. The ‘double’ is limited in precision to 64 bits overall which leaves approximately 16 significant decimal digits.

### 3.5.3 Emacs Lisp forms as formulas

It is also possible to write a formula in Emacs Lisp. This can be useful for string manipulation and control structures, if Calc's functionality is not enough.

If a formula starts with an apostrophe followed by an opening parenthesis, then it is evaluated as a Lisp form. The evaluation should return either a string or a number. Just as with `calc` formulas, you can specify modes and a `printf` format after a semicolon.

With Emacs Lisp forms, you need to be conscious about the way field references are interpolated into the form. By default, a reference will be interpolated as a Lisp string (in double-quotes) containing the field. If you provide the 'N' mode switch, all referenced elements will be numbers (non-number fields will be zero) and interpolated as Lisp numbers, without quotes. If you provide the 'L' flag, all fields will be interpolated literally, without quotes. I.e., if you want a reference to be interpreted as a string by the Lisp form, enclose the reference operator itself in double-quotes, like "\$3". Ranges are inserted as space-separated fields, so you can embed them in list or vector syntax.

Here are a few examples—note how the 'N' mode is used when we do computations in Lisp:

```
'(concat (substring $1 1 2) (substring $1 0 1) (substring $1 2))
```

Swap the first two characters of the content of column 1.

```
'(+ $1 $2);N
```

Add columns 1 and 2, equivalent to Calc's `$1+$2`.

```
'(apply '+ '($1..$4));N
```

Compute the sum of columns 1 to 4, like Calc's `vsum($1..$4)`.

### 3.5.4 Durations and time values

If you want to compute time values use the T flag, either in Calc formulas or Elisp formulas:

Task 1	Task 2	Total
2:12	1:47	03:59:00
3:02:20	-2:07:00	0.92

```
#+TBLFM: @2$3=$1+$2;T::@3$3=$1+$2;t
```

Input duration values must be of the form `HH:MM[:SS]`, where seconds are optional. With the T flag, computed durations will be displayed as `HH:MM:SS` (see the first formula above). With the t flag, computed durations will be displayed according to the value of the option `org-table-duration-custom-format`, which defaults to 'hours and will display the result as a fraction of hours (see the second formula in the example above).

Negative duration values can be manipulated as well, and integers will be considered as seconds in addition and subtraction.

### 3.5.5 Field and range formulas

To assign a formula to a particular field, type it directly into the field, preceded by '=: ', for example `:=vsum(@II..III)`. When you press `TAB` or `RET` or `C-c C-c` with the cursor still in the field, the formula will be stored as the formula for this field, evaluated, and the current field will be replaced with the result.



Formulas are stored in a special line starting with ‘#+TBLFM:’ directly below the table. If you type the equation in the 4th field of the 3rd data line in the table, the formula will look like ‘@3\$4=\$1+\$2’. When inserting/deleting/swapping columns and rows with the appropriate commands, *absolute references* (but not relative ones) in stored formulas are modified in order to still reference the same field. To avoid this, in particular in range references, anchor ranges at the table borders (using @<, @>, \$<, \$>), or at hlines using the @I notation. Automatic adaptation of field references does of course not happen if you edit the table structure with normal editing commands—then you must fix the equations yourself.

Instead of typing an equation into the field, you may also use the following command

<b>C-u C-c =</b>	<b>org-table-eval-formula</b>
Install a new formula for the current field. The command prompts for a formula with default taken from the ‘#+TBLFM:’ line, applies it to the current field, and stores it.	

The left-hand side of a formula can also be a special expression in order to assign the formula to a number of different fields. There is no keyboard shortcut to enter such range formulas. To add them, use the formula editor (see [Section 3.5.8 \[Editing and debugging formulas\]](#), page 31) or edit the #+TBLFM: line directly.

<b>\$2=</b>	Column formula, valid for the entire column. This is so common that Org treats these formulas in a special way, see <a href="#">Section 3.5.6 [Column formulas]</a> , page 30.
<b>@3=</b>	Row formula, applies to all fields in the specified row. @>= means the last row.
<b>@1\$2..@4\$3=</b>	Range formula, applies to all fields in the given rectangular range. This can also be used to assign a formula to some but not all fields in a row.
<b>\$name=</b>	Named field, see <a href="#">Section 3.5.10 [Advanced features]</a> , page 34.

### 3.5.6 Column formulas

When you assign a formula to a simple column reference like \$3=, the same formula will be used in all fields of that column, with the following very convenient exceptions: (i) If the table contains horizontal separator hlines with rows above and below, everything before the first such hline is considered part of the table *header* and will not be modified by column formulas. Therefore a header is mandatory when you use column formulas and want to add hlines to group rows, like for example to separate a total row at the bottom from the summand rows above. (ii) Fields that already get a value from a field/range formula will be left alone by column formulas. These conditions make column formulas very easy to use.

To assign a formula to a column, type it directly into any field in the column, preceded by an equal sign, like ‘=\$1+\$2’. When you press TAB or RET or C-c C-c with the cursor still in the field, the formula will be stored as the formula for the current column, evaluated and the current field replaced with the result. If the field contains only ‘=’, the previously stored formula for this column is used. For each column, Org will only remember the most recently used formula. In the ‘#+TBLFM:’ line, column formulas will look like ‘\$4=\$1+\$2’. The left-hand side of a column formula cannot be the name of column, it must be the numeric column reference or \$>.

Instead of typing an equation into the field, you may also use the following command:

`C-c =` `org-table-eval-formula`  
 Install a new formula for the current column and replace current field with the result of the formula. The command prompts for a formula, with default taken from the ‘#+TBLFM’ line, applies it to the current field and stores it. With a numeric prefix argument (e.g., `C-5 C-c =`) the command will apply it to that many consecutive fields in the current column.

### 3.5.7 Lookup functions

Org has three predefined Emacs Lisp functions for lookups in tables.

`(org-lookup-first VAL S-LIST R-LIST &optional PREDICATE)`

Searches for the first element *S* in list *S-LIST* for which

`(PREDICATE VAL S)`

is *t*; returns the value from the corresponding position in list *R-LIST*. The default *PREDICATE* is `equal`. Note that the parameters *VAL* and *S* are passed to *PREDICATE* in the same order as the corresponding parameters are in the call to `org-lookup-first`, where *VAL* precedes *S-LIST*. If *R-LIST* is `nil`, the matching element *S* of *S-LIST* is returned.

`(org-lookup-last VAL S-LIST R-LIST &optional PREDICATE)`

Similar to `org-lookup-first` above, but searches for the *last* element for which *PREDICATE* is *t*.

`(org-lookup-all VAL S-LIST R-LIST &optional PREDICATE)`

Similar to `org-lookup-first`, but searches for *all* elements for which *PREDICATE* is *t*, and returns *all* corresponding values. This function can not be used by itself in a formula, because it returns a list of values. However, powerful lookups can be built when this function is combined with other Emacs Lisp functions.

If the ranges used in these functions contain empty fields, the *E* mode for the formula should usually be specified: otherwise empty fields will not be included in *S-LIST* and/or *R-LIST* which can, for example, result in an incorrect mapping from an element of *S-LIST* to the corresponding element of *R-LIST*.

These three functions can be used to implement associative arrays, count matching cells, rank results, group data etc. For practical examples see [this tutorial on Worg](#).

### 3.5.8 Editing and debugging formulas

You can edit individual formulas in the minibuffer or directly in the field. Org can also prepare a special buffer with all active formulas of a table. When offering a formula for editing, Org converts references to the standard format (like *B3* or *D&*) if possible. If you prefer to only work with the internal format (like *@3\$2* or *\$4*), configure the option `org-table-use-standard-references`.

`C-c =` or `C-u C-c =` `org-table-eval-formula`  
 Edit the formula associated with the current column/field in the minibuffer. See [Section 3.5.6 \[Column formulas\]](#), page 30, and [Section 3.5.5 \[Field and range formulas\]](#), page 29.

<i>C-u C-u C-c =</i>	<code>org-table-eval-formula</code> Re-insert the active formula (either a field formula, or a column formula) into the current field, so that you can edit it directly in the field. The advantage over editing in the minibuffer is that you can use the command <i>C-c ?</i> .
<i>C-c ?</i>	<code>org-table-field-info</code> While editing a formula in a table field, highlight the field(s) referenced by the reference at the cursor position in the formula.
<i>C-c }</i>	Toggle the display of row and column numbers for a table, using overlays ( <code>org-table-toggle-coordinate-overlays</code> ). These are updated each time the table is aligned; you can force it with <i>C-c C-c</i> .
<i>C-c {</i>	Toggle the formula debugger on and off ( <code>org-table-toggle-formula-debugger</code> ). See below.
<i>C-c '</i>	<code>org-table-edit-formulas</code> Edit all formulas for the current table in a special buffer, where the formulas will be displayed one per line. If the current field has an active formula, the cursor in the formula editor will mark it. While inside the special buffer, Org will automatically highlight any field or range reference at the cursor position. You may edit, remove and add formulas, and use the following commands:
<i>C-c C-c</i> or <i>C-x C-s</i>	<code>org-table-fedit-finish</code> Exit the formula editor and store the modified formulas. With <i>C-u</i> prefix, also apply the new formulas to the entire table.
<i>C-c C-q</i>	<code>org-table-fedit-abort</code> Exit the formula editor without installing changes.
<i>C-c C-r</i>	<code>org-table-fedit-toggle-ref-type</code> Toggle all references in the formula editor between standard (like B3) and internal (like @3\$2).
<i>TAB</i>	<code>org-table-fedit-lisp-indent</code> Pretty-print or indent Lisp formula at point. When in a line containing a Lisp formula, format the formula according to Emacs Lisp rules. Another <i>TAB</i> collapses the formula back again. In the open formula, <i>TAB</i> re-indents just like in Emacs Lisp mode.
<i>M-TAB</i>	<code>lisp-complete-symbol</code> Complete Lisp symbols, just like in Emacs Lisp mode.
<i>S-up/down/left/right</i>	Shift the reference at point. For example, if the reference is B3 and you press <i>S-right</i> , it will become C3. This also works for relative references and for hline references.
<i>M-S-up</i>	<code>org-table-fedit-line-up</code>
<i>M-S-down</i>	<code>org-table-fedit-line-down</code> Move the test line for column formulas in the Org buffer up and down.

<i>M-up</i>	<code>org-table-fedit-scroll-down</code>
<i>M-down</i>	<code>org-table-fedit-scroll-up</code>
Scroll the window displaying the table.	
<i>C-c }</i>	Turn the coordinate grid in the table on and off.

Making a table field blank does not remove the formula associated with the field, because that is stored in a different line (the ‘#+TBLFM’ line)—during the next recalculation the field will be filled again. To remove a formula from a field, you have to give an empty reply when prompted for the formula, or to edit the ‘#+TBLFM’ line.

You may edit the ‘#+TBLFM’ directly and re-apply the changed equations with *C-c C-c* in that line or with the normal recalculation commands in the table.

## Using multiple #+TBLFM lines

You may apply the formula temporarily. This is useful when you switch the formula. Place multiple ‘#+TBLFM’ lines right after the table, and then press *C-c C-c* on the formula to apply. Here is an example:

```
| x | y |
|---+---|
| 1 |   |
| 2 |   |
#+TBLFM: $2=$1*1
#+TBLFM: $2=$1*2
```

Pressing *C-c C-c* in the line of ‘#+TBLFM: \$2=\$1\*2’ yields:

```
| x | y |
|---+---|
| 1 | 2 |
| 2 | 4 |
#+TBLFM: $2=$1*1
#+TBLFM: $2=$1*2
```

Note: If you recalculate this table (with *C-u C-c \**, for example), you will get the following result of applying only the first ‘#+TBLFM’ line.

```
| x | y |
|---+---|
| 1 | 1 |
| 2 | 2 |
#+TBLFM: $2=$1*1
#+TBLFM: $2=$1*2
```

## Debugging formulas

When the evaluation of a formula leads to an error, the field content becomes the string ‘#ERROR’. If you would like see what is going on during variable substitution and calculation in order to find a bug, turn on formula debugging in the **Tbl** menu and repeat the calculation, for example by pressing *C-u C-u C-c = RET* in a field. Detailed information will be displayed.

### 3.5.9 Updating the table

Recalculation of a table is normally not automatic, but needs to be triggered by a command. See [Section 3.5.10 \[Advanced features\]](#), [page 34](#), for a way to make recalculation at least semi-automatic.

In order to recalculate a line of a table or the entire table, use the following commands:

`C-c *` `org-table-recalculate`  
 Recalculate the current row by first applying the stored column formulas from left to right, and all field/range formulas in the current row.

`C-u C-c *`  
`C-u C-c C-c`  
 Recompute the entire table, line by line. Any lines before the first hline are left alone, assuming that these are part of the table header.

`C-u C-u C-c *` or `C-u C-u C-c C-c` `org-table-iterate`  
 Iterate the table by recomputing it until no further changes occur. This may be necessary if some computed fields use the value of other fields that are computed *later* in the calculation sequence.

`M-x org-table-recalculate-buffer-tables RET`  
 Recompute all tables in the current buffer.

`M-x org-table-iterate-buffer-tables RET`  
 Iterate all tables in the current buffer, in order to converge table-to-table dependencies.

### 3.5.10 Advanced features

If you want the recalculation of fields to happen automatically, or if you want to be able to assign *names*<sup>8</sup> to fields and columns, you need to reserve the first column of the table for special marking characters.

`C-#` `org-table-rotate-recalc-marks`  
 Rotate the calculation mark in first column through the states ‘ ’, ‘#’, ‘\*’, ‘!’, ‘\$’. When there is an active region, change all marks in the region.

Here is an example of a table that collects exam results of students and makes use of these features:

---

<sup>8</sup> Such names must start by an alphabetic character and use only alphanumeric/underscore characters.

	Student	Prob 1	Prob 2	Prob 3	Total	Note		
!		P1	P2	P3	Tot			
#	Maximum	10	15	25	50	10.0		
^		m1	m2	m3	mt			
#	Peter	10	8	23	41	8.2		
#	Sam	2	4	3	9	1.8		
	Average				25.0			
^					at			
\$	max=50							

```
#+tblfm: $6=vsum($P1..$P3):: $7=10*$Tot/$max;%.1f:: $at=vmean(@-II..@-I);%.1f
```

**Important:** please note that for these special tables, recalculating the table with `C-u C-c *` will only affect rows that are marked ‘#’ or ‘\*’, and fields that have a formula assigned to the field itself. The column formulas are not applied in rows with empty first field.

The marking characters have the following meaning:

- ‘!’ The fields in this line define names for the columns, so that you may refer to a column as ‘\$Tot’ instead of ‘\$6’.
- ‘^’ This row defines names for the fields *above* the row. With such a definition, any formula in the table may use ‘\$m1’ to refer to the value ‘10’. Also, if you assign a formula to a names field, it will be stored as ‘\$name=...’.
- ‘\_’ Similar to ‘^’, but defines names for the fields in the row *below*.
- ‘\$’ Fields in this row can define *parameters* for formulas. For example, if a field in a ‘\$’ row contains ‘max=50’, then formulas in this table can refer to the value 50 using ‘\$max’. Parameters work exactly like constants, only that they can be defined on a per-table basis.
- ‘#’ Fields in this row are automatically recalculated when pressing TAB or RET or `S-TAB` in this row. Also, this row is selected for a global recalculation with `C-u C-c *`. Unmarked lines will be left alone by this command.
- ‘\*’ Selects this line for global recalculation with `C-u C-c *`, but not for automatic recalculation. Use this when automatic recalculation slows down editing too much.
- ‘ ’ Unmarked lines are exempt from recalculation with `C-u C-c *`. All lines that should be recalculated should be marked with ‘#’ or ‘\*’.
- ‘/’ Do not export this line. Useful for lines that contain the narrowing ‘<N>’ markers or column group markers.

Finally, just to whet your appetite for what can be done with the fantastic `calc.el` package, here is a table that computes the Taylor series of degree `n` at location `x` for a couple of functions.

```

|---+-----+---+-----+-----|
|  | Func      | n | x  | Result      |
|---+-----+---+-----+-----|
| # | exp(x)      | 1 | x  | 1 + x       |
| # | exp(x)      | 2 | x  | 1 + x + x^2 / 2 |
| # | exp(x)      | 3 | x  | 1 + x + x^2 / 2 + x^3 / 6 |
| # | x^2+sqrt(x) | 2 | x=0 | x*(0.5 / 0) + x^2 (2 - 0.25 / 0) / 2 |
| # | x^2+sqrt(x) | 2 | x=1 | 2 + 2.5 x - 2.5 + 0.875 (x - 1)^2 |
| * | tan(x)      | 3 | x  | 0.0175 x + 1.77e-6 x^3 |
|---+-----+---+-----+-----|
#+TBLFM: $5=taylor($2,$4,$3);n3

```

## 3.6 Org-Plot

Org-Plot can produce graphs of information stored in org tables, either graphically or in ASCII-art.

### Graphical plots using Gnuplot

Org-Plot produces 2D and 3D graphs using Gnuplot <http://www.gnuplot.info/> and gnuplot-mode <http://xafs.org/BruceRavel/GnuplotMode>. To see this in action, ensure that you have both Gnuplot and Gnuplot mode installed on your system, then call `C-c " g` or `M-x org-plot/gnuplot RET` on the following table.

```

#+PLOT: title:"Citas" ind:1 deps:(3) type:2d with:histograms set:"yrange [0:]"
| Sede      | Max cites | H-index |
|-----+-----+-----|
| Chile     | 257.72   | 21.39   |
| Leeds     | 165.77   | 19.68   |
| Sao Paulo | 71.00    | 11.50   |
| Stockholm | 134.19   | 14.33   |
| Morelia   | 257.56   | 17.67   |

```

Notice that Org Plot is smart enough to apply the table's headers as labels. Further control over the labels, type, content, and appearance of plots can be exercised through the `#+PLOT:` lines preceding a table. See below for a complete list of Org-plot options. The `#+PLOT:` lines are optional. For more information and examples see the Org-plot tutorial at <http://orgmode.org/worg/org-tutorials/org-plot.html>.

### Plot Options

<code>set</code>	Specify any <code>gnuplot</code> option to be set when graphing.
<code>title</code>	Specify the title of the plot.
<code>ind</code>	Specify which column of the table to use as the <code>x</code> axis.
<code>deps</code>	Specify the columns to graph as a Lisp style list, surrounded by parentheses and separated by spaces for example <code>dep: (3 4)</code> to graph the third and fourth columns (defaults to graphing all other columns aside from the <code>ind</code> column).
<code>type</code>	Specify whether the plot will be <code>2d</code> , <code>3d</code> , or <code>grid</code> .

<b>with</b>	Specify a <b>with</b> option to be inserted for every col being plotted (e.g., <b>lines</b> , <b>points</b> , <b>boxes</b> , <b>impulses</b> , etc...). Defaults to <b>lines</b> .
<b>file</b>	If you want to plot to a file, specify " <i>path/to/desired/output-file</i> ".
<b>labels</b>	List of labels to be used for the <b>deps</b> (defaults to the column headers if they exist).
<b>line</b>	Specify an entire line to be inserted in the Gnuplot script.
<b>map</b>	When plotting 3d or <b>grid</b> types, set this to <b>t</b> to graph a flat mapping rather than a 3d slope.
<b>timefmt</b>	Specify format of Org mode timestamps as they will be parsed by Gnuplot. Defaults to '%Y-%m-%d-%H:%M:%S'.
<b>script</b>	If you want total control, you can specify a script file (place the file name between double-quotes) which will be used to plot. Before plotting, every instance of <b>\$datafile</b> in the specified script will be replaced with the path to the generated data file. Note: even if you set this option, you may still want to specify the plot type, as that can impact the content of the data file.

## ASCII bar plots

While the cursor is on a column, typing *C-c " a* or *M-x orgtbl-ascii-plot RET* create a new column containing an ASCII-art bars plot. The plot is implemented through a regular column formula. When the source column changes, the bar plot may be updated by refreshing the table, for example typing *C-u C-c \**.

Sede	Max cites	
-----+-----+-----		
Chile	257.72	WWWWWWWWWWW
Leeds	165.77	WWWWWWWh
Sao Paolo	71.00	WWW;
Stockholm	134.19	WWWWWW:
Morelia	257.56	WWWWWWWWWWH
Rochefourchat	0.00	

```
#+TBLFM: $3='(orgtbl-ascii-draw $2 0.0 257.72 12)
```

The formula is an elisp call:

```
(orgtbl-ascii-draw COLUMN MIN MAX WIDTH)
```

<b>COLUMN</b>	is a reference to the source column.
<b>MIN MAX</b>	are the minimal and maximal values displayed. Sources values outside this range are displayed as 'too small' or 'too large'.
<b>WIDTH</b>	is the width in characters of the bar-plot. It defaults to '12'.



## 4 Hyperlinks

Like HTML, Org provides links inside a file, external links to other files, Usenet articles, emails, and much more.

### 4.1 Link format

Org will recognize plain URL-like links and activate them as clickable links. The general link format, however, looks like this:

`[[link][description]]` or alternatively `[[link]]`

Once a link in the buffer is complete (all brackets present), Org will change the display so that ‘description’ is displayed instead of ‘[[link][description]]’ and ‘link’ is displayed instead of ‘[[link]]’. Links will be highlighted in the face `org-link`, which by default is an underlined face. You can directly edit the visible part of a link. Note that this can be either the ‘link’ part (if there is no description) or the ‘description’ part. To edit also the invisible ‘link’ part, use `C-c C-l` with the cursor on the link.

If you place the cursor at the beginning or just behind the end of the displayed text and press `BACKSPACE`, you will remove the (invisible) bracket at that location. This makes the link incomplete and the internals are again displayed as plain text. Inserting the missing bracket hides the link internals again. To show the internal structure of all links, use the menu entry `Org->Hyperlinks->Literal links`.

### 4.2 Internal links

If the link does not look like a URL, it is considered to be internal in the current file. The most important case is a link like ‘[[#my-custom-id]]’ which will link to the entry with the `CUSTOM_ID` property ‘my-custom-id’. You are responsible yourself to make sure these custom IDs are unique in a file.

Links such as ‘[[My Target]]’ or ‘[[My Target][Find my target]]’ lead to a text search in the current file.

The link can be followed with `C-c C-o` when the cursor is on the link, or with a mouse click (see [Section 4.4 \[Handling links\]](#), page 41). Links to custom IDs will point to the corresponding headline. The preferred match for a text link is a *dedicated target*: the same string in double angular brackets, like ‘<<My Target>>’.

If no dedicated target exists, the link will then try to match the exact name of an element within the buffer. Naming is done with the `#+NAME` keyword, which has to be put in the line before the element it refers to, as in the following example

```
#+NAME: My Target
| a | table |
|----+-----|
| of | four cells |
```

If none of the above succeeds, Org will search for a headline that is exactly the link text but may also include a `TODO` keyword and tags<sup>1</sup>.

<sup>1</sup> To insert a link targeting a headline, in-buffer completion can be used. Just type a star followed by a few optional letters into the buffer and press `M-TAB`. All headlines in the current buffer will be offered as completions.

During export, internal links will be used to mark objects and assign them a number. Marked objects will then be referenced by links pointing to them. In particular, links without a description will appear as the number assigned to the marked object<sup>2</sup>. In the following excerpt from an Org buffer

```
- one item
- <<target>>another item
Here we refer to item [[target]].
```

The last sentence will appear as ‘Here we refer to item 2’ when exported.

In non-Org files, the search will look for the words in the link text. In the above example the search would be for ‘my target’.

Following a link pushes a mark onto Org’s own mark ring. You can return to the previous position with `C-c &`. Using this command several times in direct succession goes back to positions recorded earlier.

### 4.2.1 Radio targets

Org can automatically turn any occurrences of certain target names in normal text into a link. So without explicitly creating a link, the text connects to the target radioing its position. Radio targets are enclosed by triple angular brackets. For example, a target ‘<<<My Target>>>’ causes each occurrence of ‘my target’ in normal text to become activated as a link. The Org file is scanned automatically for radio targets only when the file is first loaded into Emacs. To update the target list during editing, press `C-c C-c` with the cursor on or at a target.

## 4.3 External links

Org supports links to files, websites, Usenet and email messages, BBDB database entries and links to both IRC conversations and their logs. External links are URL-like locators. They start with a short identifying string followed by a colon. There can be no space after the colon. The following list shows examples for each link type.

<code>http://www.astro.uva.nl/~dominik</code>	on the web
<code>doi:10.1000/182</code>	DOI for an electronic resource
<code>file:/home/dominik/images/jupiter.jpg</code>	file, absolute path
<code>/home/dominik/images/jupiter.jpg</code>	same as above
<code>file:papers/last.pdf</code>	file, relative path
<code>./papers/last.pdf</code>	same as above
<code>file:/myself@some.where:papers/last.pdf</code>	file, path on remote machine
<code>/myself@some.where:papers/last.pdf</code>	same as above
<code>file:sometextfile::NNN</code>	file, jump to line number
<code>file:projects.org</code>	another Org file
<code>file:projects.org::some words</code>	text search in Org file <sup>3</sup>

<sup>2</sup> When targeting a `#+NAME` keyword, `#+CAPTION` keyword is mandatory in order to get proper numbering (see Section 11.4 [Images and tables], page 129).

<sup>3</sup>

The actual behavior of the search will depend on the value of the option `org-link-search-must-match-exact-headline`. If its value is `nil`, then a fuzzy text search will be done. If it is `t`, then only the

<code>file:projects.org::*task title heading search in Org</code>	
<code>file<sup>4</sup></code>	
<code>docview:papers/last.pdf::NNN</code>	open in doc-view mode at page
<code>id:B7423F4D-2E8A-471B-8810-C40F074717E9</code>	Link to heading by ID
<code>news:comp.emacs</code>	Usenet link
<code>mailto:adent@galaxy.net</code>	Mail link
<code>mhe:folder</code>	MH-E folder link
<code>mhe:folder#id</code>	MH-E message link
<code>rmail:folder</code>	RMAIL folder link
<code>rmail:folder#id</code>	RMAIL message link
<code>gnus:group</code>	Gnus group link
<code>gnus:group#id</code>	Gnus article link
<code>bbdb:R.*Stallman</code>	BBDB link (with regexp)
<code>irc:/irc.com/#emacs/bob</code>	IRC link
<code>info:org#External links</code>	Info node or index link
<code>shell:ls *.org</code>	A shell command
<code>elisp:org-agenda</code>	Interactive Elisp command
<code>elisp:(find-file-other-frame "Elisp.org")</code>	Elisp form to evaluate

On top of these built-in link types, some are available through the `contrib/` directory (see [Section 1.2 \[Installation\]](#), page 2). For example, these links to VM or Wanderlust messages are available when you load the corresponding libraries from the `contrib/` directory:

<code>vm:folder</code>	VM folder link
<code>vm:folder#id</code>	VM message link
<code>vm://myself@some.where.org/folder#id</code>	VM on remote machine
<code>vm-imap:account:folder</code>	VM IMAP folder link
<code>vm-imap:account:folder#id</code>	VM IMAP message link
<code>wl:folder</code>	WANDERLUST folder link
<code>wl:folder#id</code>	WANDERLUST message link

For customizing Org to add new link types [Section A.3 \[Adding hyperlink types\]](#), page 237.

A link should be enclosed in double brackets and may contain a descriptive text to be displayed instead of the URL (see [Section 4.1 \[Link format\]](#), page 38), for example:

```
[[http://www.gnu.org/software/emacs/] [GNU Emacs]]
```

If the description is a file name or URL that points to an image, HTML export (see [Section 12.9 \[HTML export\]](#), page 147) will inline the image as a clickable button. If there is no description at all and the link points to an image, that image will be inlined into the exported HTML file.

---

exact headline will be matched, ignoring spaces and cookies. If the value is `query-to-create`, then an exact headline will be searched; if it is not found, then the user will be queried to create it.

<sup>4</sup> Headline searches always match the exact headline, ignoring spaces and cookies. If the headline is not found and the value of the option `org-link-search-must-match-exact-headline` is `query-to-create`, then the user will be queried to create it.

Org also finds external links in the normal text and activates them as links. If spaces must be part of the link (for example in ‘`bbdb:Richard Stallman`’), or if you need to remove ambiguities about the end of the link, enclose them in square brackets.

## 4.4 Handling links

Org provides methods to create a link in the correct syntax, to insert it into an Org file, and to follow the link.

**C-c l** **org-store-link**

Store a link to the current location. This is a *global* command (you must create the key binding yourself) which can be used in any buffer to create a link. The link will be stored for later insertion into an Org buffer (see below). What kind of link will be created depends on the current buffer:

### Org mode buffers

For Org files, if there is a ‘<<target>>’ at the cursor, the link points to the target. Otherwise it points to the current headline, which will also be the description<sup>5</sup>.

If the headline has a `CUSTOM_ID` property, a link to this custom ID will be stored. In addition or alternatively (depending on the value of `org-id-link-to-org-use-id`), a globally unique ID property will be created and/or used to construct a link<sup>6</sup>. So using this command in Org buffers will potentially create two links: a human-readable from the custom ID, and one that is globally unique and works even if the entry is moved from file to file. Later, when inserting the link, you need to decide which one to use.

### Email/News clients: VM, Rmail, Wanderlust, MH-E, Gnus

Pretty much all Emacs mail clients are supported. The link will point to the current article, or, in some GNUS buffers, to the group. The description is constructed from the author and the subject.

### Web browsers: Eww, W3 and W3M

Here the link will be the current URL, with the page title as description.

### Contacts: BBDB

Links created in a BBDB buffer will point to the current entry.

### Chat: IRC

For IRC links, if you set the option `org-irc-link-to-logs` to `t`, a ‘file:/’ style link to the relevant point in the logs for the current conversation is created. Otherwise an ‘irc:/’ style link to the user/channel/server under the point will be stored.

### Other files

For any other files, the link will point to the file, with a search string (see [Section 4.7 \[Search options\]](#), page 45) pointing to the contents of the current line. If there is an active region, the selected words will form the basis of the search

<sup>5</sup> If the headline contains a timestamp, it will be removed from the link and result in a wrong link—you should avoid putting timestamp in the headline.

<sup>6</sup> The library `org-id.el` must first be loaded, either through `org-customize` by enabling `org-id` in `org-modules`, or by adding `(require 'org-id)` in your `.emacs`.

string. If the automatically created link is not working correctly or accurately enough, you can write custom functions to select the search string and to do the search for particular file types—see [Section 4.8 \[Custom searches\]](#), page 45. The key binding `C-c l` is only a suggestion—see [Section 1.2 \[Installation\]](#), page 2.

### Agenda view

When the cursor is in an agenda view, the created link points to the entry referenced by the current line.

`C-c C-l` `org-insert-link`

Insert a link<sup>7</sup>. This prompts for a link to be inserted into the buffer. You can just type a link, using text for an internal link, or one of the link type prefixes mentioned in the examples above. The link will be inserted into the buffer<sup>8</sup>, along with a descriptive text. If some text was selected when this command is called, the selected text becomes the default description.

### Inserting stored links

All links stored during the current session are part of the history for this prompt, so you can access them with `up` and `down` (or `M-p/n`).

### Completion support

Completion with `TAB` will help you to insert valid link prefixes like `'http:'` or `'ftp:'`, including the prefixes defined through link abbreviations (see [Section 4.6 \[Link abbreviations\]](#), page 44). If you press `RET` after inserting only the *prefix*, Org will offer specific completion support for some link types<sup>9</sup>. For example, if you type `file RET`, file name completion (alternative access: `C-u C-c C-l`, see below) will be offered, and after `bbdb RET` you can complete contact names.

`C-u C-c C-l`

When `C-c C-l` is called with a `C-u` prefix argument, a link to a file will be inserted and you may use file name completion to select the name of the file. The path to the file is inserted relative to the directory of the current Org file, if the linked file is in the current directory or in a sub-directory of it, or if the path is written relative to the current directory using `'../'`. Otherwise an absolute path is used, if possible with `'~/'` for your home directory. You can force an absolute path with two `C-u` prefixes.

`C-c C-l` (with cursor on existing link)

When the cursor is on an existing link, `C-c C-l` allows you to edit the link and description parts of the link.

`C-c C-o` `org-open-at-point`

Open link at point. This will launch a web browser for URLs (using `browse-url-at-point`), run VM/MH-E/Wanderlust/Rmail/Gnus/BBDB for

<sup>7</sup> Note that you don't have to use this command to insert a link. Links in Org are plain text, and you can type or paste them straight into the buffer. By using this command, the links are automatically enclosed in double brackets, and you will be asked for the optional descriptive text.

<sup>8</sup> After insertion of a stored link, the link will be removed from the list of stored links. To keep it in the list later use, use a triple `C-u` prefix argument to `C-c C-l`, or configure the option `org-keep-stored-link-after-insertion`.

<sup>9</sup> This works if a completion function is defined in the `:complete` property of a link in `org-link-parameters`.

the corresponding links, and execute the command in a shell link. When the cursor is on an internal link, this command runs the corresponding search. When the cursor is on a TAG list in a headline, it creates the corresponding TAGS view. If the cursor is on a timestamp, it compiles the agenda for that date. Furthermore, it will visit text and remote files in ‘file:’ links with Emacs and select a suitable application for local non-text files. Classification of files is based on file extension only. See option `org-file-apps`. If you want to override the default application and visit the file with Emacs, use a `C-u` prefix. If you want to avoid opening in Emacs, use a `C-u C-u` prefix. If the cursor is on a headline, but not on a link, offer all links in the headline and entry text. If you want to setup the frame configuration for following links, customize `org-link-frame-setup`.

**RET** When `org-return-follows-link` is set, RET will also follow the link at point.

*mouse-2*

*mouse-1* On links, *mouse-1* and *mouse-2* will open the link just as `C-c C-o` would.

*mouse-3* Like *mouse-2*, but force file links to be opened with Emacs, and internal links to be displayed in another window<sup>10</sup>.

`C-c C-x C-v` `org-toggle-inline-images`  
Toggle the inline display of linked images. Normally this will only inline images that have no description part in the link, i.e., images that will also be inlined during export. When called with a prefix argument, also display images that do have a link description. You can ask for inline images to be displayed at startup by configuring the variable `org-startup-with-inline-images`<sup>11</sup>.

`C-c %` `org-mark-ring-push`  
Push the current position onto the mark ring, to be able to return easily. Commands following an internal link do this automatically.

`C-c &` `org-mark-ring-goto`  
Jump back to a recorded position. A position is recorded by the commands following internal links, and by `C-c %`. Using this command several times in direct succession moves through a ring of previously recorded positions.

`C-c C-x C-n` `org-next-link`

`C-c C-x C-p` `org-previous-link`  
Move forward/backward to the next link in the buffer. At the limit of the buffer, the search fails once, and then wraps around. The key bindings for this are really too long; you might want to bind this also to `C-n` and `C-p`

```
(add-hook 'org-load-hook
  (lambda ()
    (define-key org-mode-map "\C-n" 'org-next-link)
    (define-key org-mode-map "\C-p" 'org-previous-link)))
```

<sup>10</sup> See the option `org-display-internal-link-with-indirect-buffer`

<sup>11</sup> with corresponding `#+STARTUP` keywords `inlineimages` and `noinlineimages`

## 4.5 Using links outside Org

You can insert and follow links that have Org syntax not only in Org, but in any Emacs buffer. For this, you should create two global commands, like this (please select suitable global keys yourself):

```
(global-set-key "\C-c L" 'org-insert-link-global)
(global-set-key "\C-c o" 'org-open-at-point-global)
```

## 4.6 Link abbreviations

Long URLs can be cumbersome to type, and often many similar links are needed in a document. For this you can use link abbreviations. An abbreviated link looks like this

```
[[linkword:tag] [description]]
```

where the tag is optional. The *linkword* must be a word, starting with a letter, followed by letters, numbers, ‘-’, and ‘\_’. Abbreviations are resolved according to the information in the variable `org-link-abbrev-alist` that relates the linkwords to replacement text. Here is an example:

```
(setq org-link-abbrev-alist
  '(("bugzilla" . "http://10.1.2.9/bugzilla/show_bug.cgi?id=")
    ("url-to-ja" . "http://translate.google.fr/translate?sl=en&tl=ja&u=%h")
    ("google" . "http://www.google.com/search?q=")
    ("gmap" . "http://maps.google.com/maps?q=%s")
    ("omap" . "http://nominatim.openstreetmap.org/search?q=%s&polygon=1")
    ("ads" . "http://adsabs.harvard.edu/cgi-bin/nph-abs_connect?author=%s&db_key=AST")))
```

If the replacement text contains the string ‘%s’, it will be replaced with the tag. Using ‘%h’ instead of ‘%s’ will url-encode the tag (see the example above, where we need to encode the URL parameter.) Using ‘%(my-function)’ will pass the tag to a custom function, and replace it by the resulting string.

If the replacement text doesn’t contain any specifier, the tag will simply be appended in order to create the link.

Instead of a string, you may also specify a function that will be called with the tag as the only argument to create the link.

With the above setting, you could link to a specific bug with `[[bugzilla:129]]`, search the web for ‘OrgMode’ with `[[google:OrgMode]]`, show the map location of the Free Software Foundation `[[gmap:51 Franklin Street, Boston]]` or of Carsten office `[[omap:Science Park 904, Amsterdam, The Netherlands]]` and find out what the Org author is doing besides Emacs hacking with `[[ads:Dominik,C]]`.

If you need special abbreviations just for a single Org buffer, you can define them in the file with

```
#+LINK: bugzilla http://10.1.2.9/bugzilla/show_bug.cgi?id=
#+LINK: google http://www.google.com/search?q=%s
```

In-buffer completion (see [Section 15.1 \[Completion\]](#), [page 224](#)) can be used after ‘[’ to complete link abbreviations. You may also define a function that implements special (e.g., completion) support for inserting such a link with `C-c C-l`. Such a function should not accept any arguments, and return the full link with prefix. You can add a completion function to a link like this:

```
(org-link-set-parameters ``type'' :complete #'some-function)
```

## 4.7 Search options in file links

File links can contain additional information to make Emacs jump to a particular location in the file when following a link. This can be a line number or a search option after a double<sup>12</sup> colon. For example, when the command `C-c l` creates a link (see [Section 4.4 \[Handling links\], page 41](#)) to a file, it encodes the words in the current line as a search string that can be used to find this line back later when following the link with `C-c C-o`.

Here is the syntax of the different ways to attach a search to a file link, together with an explanation:

	<code>[[file:~/code/main.c::255]]</code>
	<code>[[file:~/xx.org::My Target]]</code>
	<code>[[file:~/xx.org::*My Target]]</code>
	<code>[[file:~/xx.org::#my-custom-id]]</code>
	<code>[[file:~/xx.org::/regexp/]]</code>
255	Jump to line 255.
My Target	Search for a link target ‘<<My Target>>’, or do a text search for ‘my target’, similar to the search in internal links, see <a href="#">Section 4.2 [Internal links], page 38</a> . In HTML export (see <a href="#">Section 12.9 [HTML export], page 147</a> ), such a file link will become an HTML reference to the corresponding named anchor in the linked file.
*My Target	In an Org file, restrict search to headlines.
#my-custom-id	Link to a heading with a <code>CUSTOM_ID</code> property
/regexp/	Do a regular expression search for <code>regexp</code> . This uses the Emacs command <code>occur</code> to list all matches in a separate window. If the target file is in Org mode, <code>org-occur</code> is used to create a sparse tree with the matches.

As a degenerate case, a file link with an empty file name can be used to search the current file. For example, `[[file::find me]]` does a search for ‘find me’ in the current file, just as ‘`[[find me]]`’ would.

## 4.8 Custom Searches

The default mechanism for creating search strings and for doing the actual search related to a file link may not work correctly in all cases. For example, BibTeX database files have many entries like ‘`year="1993"`’ which would not result in good search strings, because the only unique identification for a BibTeX entry is the citation key.

If you come across such a problem, you can write custom functions to set the right search string for a particular file type, and to do the search for the string in the file. Using `add-hook`, these functions need to be added to the hook variables `org-create-file-search-functions` and `org-execute-file-search-functions`. See the docstring for these variables for more information. Org actually uses this mechanism for BibTeX database files, and you can use the corresponding code as an implementation example. See the file `org-bibtex.el`.

<sup>12</sup> For backward compatibility, line numbers can also follow a single colon.



## 5 TODO items

Org mode does not maintain TODO lists as separate documents<sup>1</sup>. Instead, TODO items are an integral part of the notes file, because TODO items usually come up while taking notes! With Org mode, simply mark any entry in a tree as being a TODO item. In this way, information is not duplicated, and the entire context from which the TODO item emerged is always present.

Of course, this technique for managing TODO items scatters them throughout your notes file. Org mode compensates for this by providing methods to give you an overview of all the things that you have to do.

### 5.1 Basic TODO functionality

Any headline becomes a TODO item when it starts with the word ‘TODO’, for example:

```
*** TODO Write letter to Sam Fortune
```

The most important commands to work with TODO entries are:

`C-c C-t` `org-todo`

Rotate the TODO state of the current item among

```
,-> (unmarked) -> TODO -> DONE --.
'-----'
```

If TODO keywords have fast access keys (see [Section 5.2.4 \[Fast access to TODO states\]](#), [page 49](#)), you will be prompted for a TODO keyword through the fast selection interface; this is the default behavior when `org-use-fast-todo-selection` is non-`nil`.

The same rotation can also be done “remotely” from the timeline and agenda buffers with the `t` command key (see [Section 10.5 \[Agenda commands\]](#), [page 113](#)).

`C-u C-c C-t`

When TODO keywords have no selection keys, select a specific keyword using completion; otherwise force cycling through TODO states with no prompt. When `org-use-fast-todo-selection` is set to `prefix`, use the fast selection interface.

`S-right` / `S-left`

Select the following/preceding TODO state, similar to cycling. Useful mostly if more than two TODO states are possible (see [Section 5.2 \[TODO extensions\]](#), [page 47](#)). See also [Section 15.10.2 \[Conflicts\]](#), [page 234](#), for a discussion of the interaction with `shift-selection-mode`. See also the variable `org-treat-S-cursor-todo-selection-as-state-change`.

`C-c / t`

`org-show-todo-tree`

View TODO items in a *sparse tree* (see [Section 2.6 \[Sparse trees\]](#), [page 11](#)). Folds the entire buffer, but shows all TODO items (with not-DONE state) and

---

<sup>1</sup> Of course, you can make a document that contains only long lists of TODO items, but this is not required.

the headings hierarchy above them. With a prefix argument (or by using `C-c / T`), search for a specific TODO. You will be prompted for the keyword, and you can also give a list of keywords like `KWD1|KWD2|...` to list entries that match any one of these keywords. With a numeric prefix argument `N`, show the tree for the `N`th keyword in the option `org-todo-keywords`. With two prefix arguments, find all TODO states, both un-done and done.

**C-c a t** **org-todo-list**  
 Show the global TODO list. Collects the TODO items (with not-DONE states) from all agenda files (see [Chapter 10 \[Agenda views\]](#), page 100) into a single buffer. The new buffer will be in `agenda-mode`, which provides commands to examine and manipulate the TODO entries from the new buffer (see [Section 10.5 \[Agenda commands\]](#), page 113). See [Section 10.3.2 \[Global TODO list\]](#), page 104, for more information.

**S-M-RET** **org-insert-todo-heading**  
 Insert a new TODO entry below the current one.

Changing a TODO state can also trigger tag changes. See the docstring of the option `org-todo-state-tags-triggers` for details.

## 5.2 Extended use of TODO keywords

By default, marked TODO entries have one of only two states: TODO and DONE. Org mode allows you to classify TODO items in more complex ways with *TODO keywords* (stored in `org-todo-keywords`). With special setup, the TODO keyword system can work differently in different files.

Note that *tags* are another way to classify headlines in general and TODO items in particular (see [Chapter 6 \[Tags\]](#), page 59).

### 5.2.1 TODO keywords as workflow states

You can use TODO keywords to indicate different *sequential* states in the process of working on an item, for example<sup>2</sup>:

```
(setq org-todo-keywords
  '((sequence "TODO" "FEEDBACK" "VERIFY" "|" "DONE" "DELEGATED")))
```

The vertical bar separates the TODO keywords (states that *need action*) from the DONE states (which need *no further action*). If you don't provide the separator bar, the last state is used as the DONE state. With this setup, the command `C-c C-t` will cycle an entry from TODO to FEEDBACK, then to VERIFY, and finally to DONE and DELEGATED. You may also use a numeric prefix argument to quickly select a specific state. For example `C-3 C-c C-t` will change the state immediately to VERIFY. Or you can use `S-left` to go backward through the sequence. If you define many keywords, you can use in-buffer completion (see [Section 15.1 \[Completion\]](#), page 224) or even a special one-key selection scheme (see [Section 5.2.4 \[Fast access to TODO states\]](#), page 49) to insert these words into the buffer. Changing a TODO state can be logged with a timestamp, see [Section 5.3.2 \[Tracking TODO state changes\]](#), page 52, for more information.

<sup>2</sup> Changing this variable only becomes effective after restarting Org mode in a buffer.

### 5.2.2 TODO keywords as types

The second possibility is to use TODO keywords to indicate different *types* of action items. For example, you might want to indicate that items are for “work” or “home”. Or, when you work with several people on a single project, you might want to assign action items directly to persons, by using their names as TODO keywords. This would be set up like this:

```
(setq org-todo-keywords '((type "Fred" "Sara" "Lucy" "|" "DONE")))
```

In this case, different keywords do not indicate a sequence, but rather different types. So the normal work flow would be to assign a task to a person, and later to mark it DONE. Org mode supports this style by adapting the workings of the command `C-c C-t`<sup>3</sup>. When used several times in succession, it will still cycle through all names, in order to first select the right type for a task. But when you return to the item after some time and execute `C-c C-t` again, it will switch from any name directly to DONE. Use prefix arguments or completion to quickly select a specific name. You can also review the items of a specific TODO type in a sparse tree by using a numeric prefix to `C-c / t`. For example, to see all things Lucy has to do, you would use `C-3 C-c / t`. To collect Lucy’s items from all agenda files into a single buffer, you would use the numeric prefix argument as well when creating the global TODO list: `C-3 C-c a t`.

### 5.2.3 Multiple keyword sets in one file

Sometimes you may want to use different sets of TODO keywords in parallel. For example, you may want to have the basic TODO/DONE, but also a workflow for bug fixing, and a separate state indicating that an item has been canceled (so it is not DONE, but also does not require action). Your setup would then look like this:

```
(setq org-todo-keywords
      '((sequence "TODO" "|" "DONE")
        (sequence "REPORT" "BUG" "KNOWNCAUSE" "|" "FIXED")
        (sequence "|" "CANCELED")))
```

The keywords should all be different, this helps Org mode to keep track of which subsequence should be used for a given entry. In this setup, `C-c C-t` only operates within a subsequence, so it switches from DONE to (nothing) to TODO, and from FIXED to (nothing) to REPORT. Therefore you need a mechanism to initially select the correct sequence. Besides the obvious ways like typing a keyword or using completion, you may also apply the following commands:

`C-u C-u C-c C-t`

`C-S-right`

`C-S-left` These keys jump from one TODO subset to the next. In the above example, `C-u C-u C-c C-t` or `C-S-right` would jump from TODO or DONE to REPORT, and any of the words in the second row to CANCELED. Note that the `C-S-` key binding conflict with `shift-selection-mode` (see [Section 15.10.2 \[Conflicts\]](#), [page 234](#)).

---

<sup>3</sup> This is also true for the `t` command in the timeline and agenda buffers.

*S-right*

*S-left*     *S-left* and *S-right* and walk through *all* keywords from all sets, so for example *S-right* would switch from DONE to REPORT in the example above. See also [Section 15.10.2 \[Conflicts\]](#), page 234, for a discussion of the interaction with `shift-selection-mode`.

## 5.2.4 Fast access to TODO states

If you would like to quickly change an entry to an arbitrary TODO state instead of cycling through the states, you can set up keys for single-letter access to the states. This is done by adding the selection character after each keyword, in parentheses<sup>4</sup>. For example:

```
(setq org-todo-keywords
  '((sequence "TODO(t)" "|" "DONE(d)")
    (sequence "REPORT(r)" "BUG(b)" "KNOWNCAUSE(k)" "|" "FIXED(f)")
    (sequence "|" "CANCELED(c)")))
```

If you then press `C-c C-t` followed by the selection key, the entry will be switched to this state. `SPC` can be used to remove any TODO keyword from an entry.<sup>5</sup>

## 5.2.5 Setting up keywords for individual files

It can be very useful to use different aspects of the TODO mechanism in different files. For file-local settings, you need to add special lines to the file which set the keywords and interpretation for that file only. For example, to set one of the two examples discussed above, you need one of the following lines anywhere in the file:

```
#+TODO: TODO FEEDBACK VERIFY | DONE CANCELED
```

(you may also write `#+SEQ_TODO` to be explicit about the interpretation, but it means the same as `#+TODO`), or

```
#+TYP_TODO: Fred Sara Lucy Mike | DONE
```

A setup for using several sets in parallel would be:

```
#+TODO: TODO | DONE
#+TODO: REPORT BUG KNOWNCAUSE | FIXED
#+TODO: | CANCELED
```

To make sure you are using the correct keyword, type `#+` into the buffer and then use `M-TAB` completion.

Remember that the keywords after the vertical bar (or the last keyword if no bar is there) must always mean that the item is DONE (although you may use a different word). After changing one of these lines, use `C-c C-c` with the cursor still in the line to make the changes known to Org mode<sup>6</sup>.

<sup>4</sup> All characters are allowed except `@^!`, which have a special meaning here.

<sup>5</sup> Check also the option `org-fast-tag-selection-include-todo`, it allows you to change the TODO state through the tags interface (see [Section 6.2 \[Setting tags\]](#), page 59), in case you like to mingle the two concepts. Note that this means you need to come up with unique keys across both sets of keywords.

<sup>6</sup> Org mode parses these lines only when Org mode is activated after visiting a file. `C-c C-c` with the cursor in a line starting with `#+` is simply restarting Org mode for the current buffer.

### 5.2.6 Faces for TODO keywords

Org mode highlights TODO keywords with special faces: `org-todo` for keywords indicating that an item still has to be acted upon, and `org-done` for keywords indicating that an item is finished. If you are using more than 2 different states, you might want to use special faces for some of them. This can be done using the option `org-todo-keyword-faces`. For example:

```
(setq org-todo-keyword-faces
      '(("TODO" . org-warning) ("STARTED" . "yellow")
        ("CANCELED" . (:foreground "blue" :weight bold))))
```

While using a list with face properties as shown for CANCELED *should* work, this does not always seem to be the case. If necessary, define a special face and use that. A string is interpreted as a color. The option `org-faces-easy-properties` determines if that color is interpreted as a foreground or a background color.

### 5.2.7 TODO dependencies

The structure of Org files (hierarchy and lists) makes it easy to define TODO dependencies. Usually, a parent TODO task should not be marked DONE until all subtasks (defined as children tasks) are marked as DONE. And sometimes there is a logical sequence to a number of (sub)tasks, so that one task cannot be acted upon before all siblings above it are done. If you customize the option `org-enforce-todo-dependencies`, Org will block entries from changing state to DONE while they have children that are not DONE. Furthermore, if an entry has a property `ORDERED`, each of its children will be blocked until all earlier siblings are marked DONE. Here is an example:

```
* TODO Blocked until (two) is done
** DONE one
** TODO two

* Parent
:PROPERTIES:
:ORDERED: t
:END:
** TODO a
** TODO b, needs to wait for (a)
** TODO c, needs to wait for (a) and (b)
```

You can ensure an entry is never blocked by using the `NOBLOCKING` property:

```
* This entry is never blocked
:PROPERTIES:
:NOBLOCKING: t
:END:
```

`C-c C-x o` `org-toggle-ordered-property`  
 Toggle the `ORDERED` property of the current entry. A property is used for this behavior because this should be local to the current entry, not inherited like a tag. However, if you would like to *track* the value of this property with a tag for better visibility, customize the option `org-track-ordered-property-with-tag`.

*C-u C-u C-u C-c C-t*

Change TODO state, circumventing any state blocking.

If you set the option `org-agenda-dim-blocked-tasks`, TODO entries that cannot be closed because of such dependencies will be shown in a dimmed font or even made invisible in agenda views (see [Chapter 10 \[Agenda views\]](#), page 100).

You can also block changes of TODO states by looking at checkboxes (see [Section 5.6 \[Checkboxes\]](#), page 56). If you set the option `org-enforce-todo-checkbox-dependencies`, an entry that has unchecked checkboxes will be blocked from switching to DONE.

If you need more complex dependency structures, for example dependencies between entries in different trees or files, check out the contributed module `org-depend.el`.

## 5.3 Progress logging

Org mode can automatically record a timestamp and possibly a note when you mark a TODO item as DONE, or even each time you change the state of a TODO item. This system is highly configurable; settings can be on a per-keyword basis and can be localized to a file or even a subtree. For information on how to clock working time for a task, see [Section 8.4 \[Clocking work time\]](#), page 80.

### 5.3.1 Closing items

The most basic logging is to keep track of *when* a certain TODO item was finished. This is achieved with<sup>1</sup>

```
(setq org-log-done 'time)
```

Then each time you turn an entry from a TODO (not-done) state into any of the DONE states, a line `CLOSED: [timestamp]` will be inserted just after the headline. If you turn the entry back into a TODO item through further state cycling, that line will be removed again. If you turn the entry back to a non-TODO state (by pressing `C-c C-t SPC` for example), that line will also be removed, unless you set `org-closed-keep-when-no-todo` to `non-nil`. If you want to record a note along with the timestamp, use<sup>2</sup>

```
(setq org-log-done 'note)
```

You will then be prompted for a note, and that note will be stored below the entry with a `Closing Note` heading.

In the timeline (see [Section 10.3.4 \[Timeline\]](#), page 108) and in the agenda (see [Section 10.3.1 \[Weekly/daily agenda\]](#), page 102), you can then use the `l` key to display the TODO items with a `CLOSED` timestamp on each day, giving you an overview of what has been done.

### 5.3.2 Tracking TODO state changes

When TODO keywords are used as workflow states (see [Section 5.2.1 \[Workflow states\]](#), page 47), you might want to keep track of when a state change occurred and maybe take a note about this change. You can either record just a timestamp, or a time-stamped note for a change. These records will be inserted after the headline as an itemized list, newest first<sup>3</sup>. When taking a lot of notes, you might want to get the notes out of the way into a drawer (see [Section 2.8 \[Drawers\]](#), page 15). Customize `org-log-into-drawer` to get this behavior—the recommended drawer for this is called `LOGBOOK`<sup>4</sup>. You can also overrule the setting of this variable for a subtree by setting a `LOG_INTRO_DRAWER` property.

Since it is normally too much to record a note for every state, Org mode expects configuration on a per-keyword basis for this. This is achieved by adding special markers `!` (for a timestamp) or `@` (for a note with timestamp) in parentheses after each keyword. For example, with the setting

```
(setq org-todo-keywords
```

<sup>1</sup> The corresponding in-buffer setting is: `#+STARTUP: logdone`

<sup>2</sup> The corresponding in-buffer setting is: `#+STARTUP: lognotedone`.

<sup>3</sup> See the option `org-log-states-order-reversed`

<sup>4</sup> Note that the `LOGBOOK` drawer is unfolded when pressing `SPC` in the agenda to show an entry—use `C-u SPC` to keep it folded here

```
'((sequence "TODO(t)" "WAIT(w@/!)" "|" "DONE(d!)" "CANCELED(c@)"))'
```

To record a timestamp without a note for TODO keywords configured with '@', just type `C-c C-c` to enter a blank note when prompted.

You not only define global TODO keywords and fast access keys, but also request that a time is recorded when the entry is set to DONE<sup>5</sup>, and that a note is recorded when switching to WAIT or CANCELED. The setting for WAIT is even more special: the '!' after the slash means that in addition to the note taken when entering the state, a timestamp should be recorded when *leaving* the WAIT state, if and only if the *target* state does not configure logging for entering it. So it has no effect when switching from WAIT to DONE, because DONE is configured to record a timestamp only. But when switching from WAIT back to TODO, the '/!' in the WAIT setting now triggers a timestamp even though TODO has no logging configured.

You can use the exact same syntax for setting logging preferences local to a buffer:

```
#+TODO: TODO(t) WAIT(w@/!) | DONE(d!) CANCELED(c@)
```

In order to define logging settings that are local to a subtree or a single item, define a LOGGING property in this entry. Any non-empty LOGGING property resets all logging settings to nil. You may then turn on logging for this specific tree using STARTUP keywords like `lognotedone` or `logrepeat`, as well as adding state specific settings like `TODO(!)`. For example

```
* TODO Log each state with only a time
:PROPERTIES:
:LOGGING: TODO(!) WAIT(!) DONE(!) CANCELED(!)
:END:
* TODO Only log when switching to WAIT, and when repeating
:PROPERTIES:
:LOGGING: WAIT(@) logrepeat
:END:
* TODO No logging at all
:PROPERTIES:
:LOGGING: nil
:END:
```

### 5.3.3 Tracking your habits

Org has the ability to track the consistency of a special category of TODOs, called “habits”. A habit has the following properties:

1. You have enabled the `habits` module by customizing `org-modules`.
2. The habit is a TODO item, with a TODO keyword representing an open state.
3. The property `STYLE` is set to the value `habit`.
4. The TODO has a scheduled date, usually with a `.+` style repeat interval. A `++` style may be appropriate for habits with time constraints, e.g., must be done on weekends, or a `+` style for an unusual habit that can have a backlog, e.g., weekly reports.

---

<sup>5</sup> It is possible that Org mode will record two timestamps when you are using both `org-log-done` and state change logging. However, it will never prompt for two notes—if you have configured both, the state change recording note will take precedence and cancel the ‘Closing Note’.



5. The TODO may also have minimum and maximum ranges specified by using the syntax `‘.+2d/3d’`, which says that you want to do the task at least every three days, but at most every two days.
6. You must also have state logging for the DONE state enabled (see [Section 5.3.2 \[Tracking TODO state changes\]](#), page 52), in order for historical data to be represented in the consistency graph. If it is not enabled it is not an error, but the consistency graphs will be largely meaningless.

To give you an idea of what the above rules look like in action, here’s an actual habit with some history:

```

** TODO Shave
SCHEDULED: <2009-10-17 Sat .+2d/4d>
:PROPERTIES:
:STYLE:      habit
:LAST_REPEAT: [2009-10-19 Mon 00:36]
:END:
- State "DONE"      from "TODO"      [2009-10-15 Thu]
- State "DONE"      from "TODO"      [2009-10-12 Mon]
- State "DONE"      from "TODO"      [2009-10-10 Sat]
- State "DONE"      from "TODO"      [2009-10-04 Sun]
- State "DONE"      from "TODO"      [2009-10-02 Fri]
- State "DONE"      from "TODO"      [2009-09-29 Tue]
- State "DONE"      from "TODO"      [2009-09-25 Fri]
- State "DONE"      from "TODO"      [2009-09-19 Sat]
- State "DONE"      from "TODO"      [2009-09-16 Wed]
- State "DONE"      from "TODO"      [2009-09-12 Sat]

```

What this habit says is: I want to shave at most every 2 days (given by the `SCHEDULED` date and repeat interval) and at least every 4 days. If today is the 15th, then the habit first appears in the agenda on Oct 17, after the minimum of 2 days has elapsed, and will appear overdue on Oct 19, after four days have elapsed.

What’s really useful about habits is that they are displayed along with a consistency graph, to show how consistent you’ve been at getting that task done in the past. This graph shows every day that the task was done over the past three weeks, with colors for each day. The colors used are:

Blue	If the task wasn’t to be done yet on that day.
Green	If the task could have been done on that day.
Yellow	If the task was going to be overdue the next day.
Red	If the task was overdue on that day.

In addition to coloring each day, the day is also marked with an asterisk if the task was actually done that day, and an exclamation mark to show where the current day falls in the graph.

There are several configuration variables that can be used to change the way habits are displayed in the agenda.

**org-habit-graph-column**

The buffer column at which the consistency graph should be drawn. This will overwrite any text in that column, so it is a good idea to keep your habits' titles brief and to the point.

**org-habit-preceding-days**

The amount of history, in days before today, to appear in consistency graphs.

**org-habit-following-days**

The number of days after today that will appear in consistency graphs.

**org-habit-show-habits-only-for-today**

If non-*nil*, only show habits in today's agenda view. This is set to true by default.

Lastly, pressing *K* in the agenda buffer will cause habits to temporarily be disabled and they won't appear at all. Press *K* again to bring them back. They are also subject to tag filtering, if you have habits which should only be done in certain contexts, for example.

## 5.4 Priorities

If you use Org mode extensively, you may end up with enough TODO items that it starts to make sense to prioritize them. Prioritizing can be done by placing a *priority cookie* into the headline of a TODO item, like this

```
*** TODO [#A] Write letter to Sam Fortune
```

By default, Org mode supports three priorities: 'A', 'B', and 'C'. 'A' is the highest priority. An entry without a cookie is treated just like priority 'B'. Priorities make a difference only for sorting in the agenda (see [Section 10.3.1 \[Weekly/daily agenda\]](#), page 102); outside the agenda, they have no inherent meaning to Org mode. The cookies can be highlighted with special faces by customizing **org-priority-faces**.

Priorities can be attached to any outline node; they do not need to be TODO items.

**C-c ,** Set the priority of the current headline (**org-priority**). The command prompts for a priority character 'A', 'B' or 'C'. When you press SPC instead, the priority cookie is removed from the headline. The priorities can also be changed "remotely" from the timeline and agenda buffer with the **,** command (see [Section 10.5 \[Agenda commands\]](#), page 113).

**S-up**

**org-priority-up**

**S-down**

**org-priority-down**

Increase/decrease priority of current headline<sup>6</sup>. Note that these keys are also used to modify timestamps (see [Section 8.2 \[Creating timestamps\]](#), page 74). See also [Section 15.10.2 \[Conflicts\]](#), page 234, for a discussion of the interaction with **shift-selection-mode**.

You can change the range of allowed priorities by setting the options **org-highest-priority**, **org-lowest-priority**, and **org-default-priority**. For an individual buffer, you may set these values (highest, lowest, default) like this (please make sure that the highest priority is earlier in the alphabet than the lowest priority):

```
#+PRIORITIES: A C B
```

<sup>6</sup> See also the option **org-priority-start-cycle-with-default**.

## 5.5 Breaking tasks down into subtasks

It is often advisable to break down large tasks into smaller, manageable subtasks. You can do this by creating an outline tree below a TODO item, with detailed subtasks on the tree<sup>7</sup>. To keep the overview over the fraction of subtasks that are already completed, insert either ‘[/]’ or ‘[%]’ anywhere in the headline. These cookies will be updated each time the TODO status of a child changes, or when pressing `C-c C-c` on the cookie. For example:

```
* Organize Party [33%]
** TODO Call people [1/2]
*** TODO Peter
*** DONE Sarah
** TODO Buy food
** DONE Talk to neighbor
```

If a heading has both checkboxes and TODO children below it, the meaning of the statistics cookie become ambiguous. Set the property `COOKIE_DATA` to either ‘checkbox’ or ‘todo’ to resolve this issue.

If you would like to have the statistics cookie count any TODO entries in the subtree (not just direct children), configure `org-hierarchical-todo-statistics`. To do this for a single subtree, include the word ‘recursive’ into the value of the `COOKIE_DATA` property.

```
* Parent capturing statistics [2/20]
:PROPERTIES:
:COOKIE_DATA: todo recursive
:END:
```

If you would like a TODO entry to automatically change to DONE when all children are done, you can use the following setup:

```
(defun org-summary-todo (n-done n-not-done)
  "Switch entry to DONE when all subentries are done, to TODO otherwise."
  (let (org-log-done org-log-states)    ; turn off logging
    (org-todo (if (= n-not-done 0) "DONE" "TODO"))))

(add-hook 'org-after-todo-statistics-hook 'org-summary-todo)
```

Another possibility is the use of checkboxes to identify (a hierarchy of) a large number of subtasks (see [Section 5.6 \[Checkboxes\]](#), page 56).

## 5.6 Checkboxes

Every item in a plain list<sup>8</sup> (see [Section 2.7 \[Plain lists\]](#), page 12) can be made into a checkbox by starting it with the string ‘[ ]’. This feature is similar to TODO items (see [Chapter 5 \[TODO items\]](#), page 46), but is more lightweight. Checkboxes are not included in the global TODO list, so they are often great to split a task into a number of simple steps. Or you can use them in a shopping list. To toggle a checkbox, use `C-c C-c`, or use the mouse (thanks to Piotr Zielinski’s `org-mouse.el`).

Here is an example of a checkbox list.

<sup>7</sup> To keep subtasks out of the global TODO list, see the `org-agenda-todo-list-sublevels`.

<sup>8</sup> With the exception of description lists. But you can allow it by modifying `org-list-automatic-rules` accordingly.

- ```
* TODO Organize party [2/4]
- [-] call people [1/3]
  - [ ] Peter
  - [X] Sarah
  - [ ] Sam
- [X] order food
- [ ] think about what music to play
- [X] talk to the neighbors
```

Checkboxes work hierarchically, so if a checkbox item has children that are checkboxes, toggling one of the children checkboxes will make the parent checkbox reflect if none, some, or all of the children are checked.

The ‘[2/4]’ and ‘[1/3]’ in the first and second line are cookies indicating how many checkboxes present in this entry have been checked off, and the total number of checkboxes present. This can give you an idea on how many checkboxes remain, even without opening a folded entry. The cookies can be placed into a headline or into (the first line of) a plain list item. Each cookie covers checkboxes of direct children structurally below the headline/item on which the cookie appears<sup>9</sup>. You have to insert the cookie yourself by typing either ‘[/]’ or ‘[%]’. With ‘[/]’ you get an ‘n out of m’ result, as in the examples above. With ‘[%]’ you get information about the percentage of checkboxes checked (in the above example, this would be ‘[50%]’ and ‘[33%]’, respectively). In a headline, a cookie can count either checkboxes below the heading or TODO states of children, and it will display whatever was changed last. Set the property `COOKIE_DATA` to either ‘checkbox’ or ‘todo’ to resolve this issue.

If the current outline node has an `ORDERED` property, checkboxes must be checked off in sequence, and an error will be thrown if you try to check off a box while there are unchecked boxes above it.

The following commands work with checkboxes:

**C-c C-c** **org-toggle-checkbox**

Toggle checkbox status or (with prefix arg) checkbox presence at point. With a single prefix argument, add an empty checkbox or remove the current one<sup>10</sup>. With a double prefix argument, set it to ‘[-]’, which is considered to be an intermediate state.

**C-c C-x C-b** **org-toggle-checkbox**

Toggle checkbox status or (with prefix arg) checkbox presence at point. With double prefix argument, set it to ‘[-]’, which is considered to be an intermediate state.

- If there is an active region, toggle the first checkbox in the region and set all remaining boxes to the same status as the first. With a prefix arg, add or remove the checkbox for all items in the region.
- If the cursor is in a headline, toggle the state of the first checkbox in the region between this headline and the next—so *not* the entire subtree—and propagate this new state to all other checkboxes in the same area.

<sup>9</sup> Set the option `org-checkbox-hierarchical-statistics` if you want such cookies to count all checkboxes below the cookie, not just those belonging to direct children.

<sup>10</sup> `C-u C-c C-c` before the *first* bullet in a list with no checkbox will add checkboxes to the rest of the list.

- If there is no active region, just toggle the checkbox at point.

|                  |                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>M-S-RET</i>   | <code>org-insert-todo-heading</code>                                                                                                                                                                                                                                                                                                                                                                                                |
|                  | Insert a new item with a checkbox. This works only if the cursor is already in a plain list item (see <a href="#">Section 2.7 [Plain lists]</a> , page 12).                                                                                                                                                                                                                                                                         |
| <i>C-c C-x o</i> | <code>org-toggle-ordered-property</code>                                                                                                                                                                                                                                                                                                                                                                                            |
|                  | Toggle the <code>ORDERED</code> property of the entry, to toggle if checkboxes must be checked off in sequence. A property is used for this behavior because this should be local to the current entry, not inherited like a tag. However, if you would like to <i>track</i> the value of this property with a tag for better visibility, customize <code>org-track-ordered-property-with-tag</code> .                              |
| <i>C-c #</i>     | <code>org-update-statistics-cookies</code>                                                                                                                                                                                                                                                                                                                                                                                          |
|                  | Update the statistics cookie in the current outline entry. When called with a <i>C-u</i> prefix, update the entire file. Checkbox statistic cookies are updated automatically if you toggle checkboxes with <i>C-c C-c</i> and make new ones with <i>M-S-RET</i> . TODO statistics cookies update when changing TODO states. If you delete boxes/entries or add/change them by hand, use this command to get things back into sync. |

## 6 Tags

An excellent way to implement labels and contexts for cross-correlating information is to assign *tags* to headlines. Org mode has extensive support for tags.

Every headline can contain a list of tags; they occur at the end of the headline. Tags are normal words containing letters, numbers, ‘\_’, and ‘@’. Tags must be preceded and followed by a single colon, e.g., ‘:work:’. Several tags can be specified, as in ‘:work:urgent:’. Tags will by default be in bold face with the same color as the headline. You may specify special faces for specific tags using the option `org-tag-faces`, in much the same way as you can for TODO keywords (see [Section 5.2.6 \[Faces for TODO keywords\]](#), page 50).

### 6.1 Tag inheritance

*Tags* make use of the hierarchical structure of outline trees. If a heading has a certain tag, all subheadings will inherit the tag as well. For example, in the list

```
* Meeting with the French group      :work:
** Summary by Frank                  :boss:notes:
*** TODO Prepare slides for him      :action:
```

the final heading will have the tags ‘:work:’, ‘:boss:’, ‘:notes:’, and ‘:action:’ even though the final heading is not explicitly marked with all those tags. You can also set tags that all entries in a file should inherit just as if these tags were defined in a hypothetical level zero that surrounds the entire file. Use a line like this<sup>1</sup>:

```
#+FILETAGS: :Peter:Boss:Secret:
```

To limit tag inheritance to specific tags, use `org-tags-exclude-from-inheritance`. To turn it off entirely, use `org-use-tag-inheritance`.

When a headline matches during a tags search while tag inheritance is turned on, all the sublevels in the same tree will (for a simple match form) match as well<sup>2</sup>. The list of matches may then become very long. If you only want to see the first tags match in a subtree, configure `org-tags-match-list-sublevels` (not recommended).

Tag inheritance is relevant when the agenda search tries to match a tag, either in the `tags` or `tags-todo` agenda types. In other agenda types, `org-use-tag-inheritance` has no effect. Still, you may want to have your tags correctly set in the agenda, so that tag filtering works fine, with inherited tags. Set `org-agenda-use-tag-inheritance` to control this: the default value includes all agenda types, but setting this to `nil` can really speed up agenda generation.

### 6.2 Setting tags

Tags can simply be typed into the buffer at the end of a headline. After a colon, `M-TAB` offers completion on tags. There is also a special command for inserting tags:

|                                                                                                                                                                   |                                   |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------|
| <code>C-c C-q</code>                                                                                                                                              | <code>org-set-tags-command</code> |
| Enter new tags for the current headline. Org mode will either offer completion or a special single-key interface for setting tags, see below. After pressing RET, |                                   |

<sup>1</sup> As with all these in-buffer settings, pressing `C-c C-c` activates any changes in the line.

<sup>2</sup> This is only true if the search does not involve more complex tests including properties (see [Section 7.3 \[Property searches\]](#), page 66).

the tags will be inserted and aligned to `org-tags-column`. When called with a `C-u` prefix, all tags in the current buffer will be aligned to that column, just to make things look nice. TAGS are automatically realigned after promotion, demotion, and TODO state changes (see [Section 5.1 \[TODO basics\]](#), page 46).

`C-c C-c` `org-set-tags-command`  
 When the cursor is in a headline, this does the same as `C-c C-q`.

Org supports tag insertion based on a *list of tags*. By default this list is constructed dynamically, containing all tags currently used in the buffer. You may also globally specify a hard list of tags with the variable `org-tag-alist`. Finally you can set the default tags for a given file with lines like

```
#+TAGS: @work @home @tennisclub
#+TAGS: laptop car pc sailboat
```

If you have globally defined your preferred set of tags using the variable `org-tag-alist`, but would like to use a dynamic tag list in a specific file, add an empty TAGS option line to that file:

```
#+TAGS:
```

If you have a preferred set of tags that you would like to use in every file, in addition to those defined on a per-file basis by TAGS option lines, then you may specify a list of tags with the variable `org-tag-persistent-alist`. You may turn this off on a per-file basis by adding a STARTUP option line to that file:

```
#+STARTUP: noptag
```

By default Org mode uses the standard minibuffer completion facilities for entering tags. However, it also implements another, quicker, tag selection method called *fast tag selection*. This allows you to select and deselect tags with just a single key press. For this to work well you should assign unique letters to most of your commonly used tags. You can do this globally by configuring the variable `org-tag-alist` in your `.emacs` file. For example, you may find the need to tag many items in different files with `:@home:`. In this case you can set something like:

```
(setq org-tag-alist '(("@work" . ?w) ("@home" . ?h) ("laptop" . ?l)))
```

If the tag is only relevant to the file you are working on, then you can instead set the TAGS option line as:

```
#+TAGS: @work(w) @home(h) @tennisclub(t) laptop(l) pc(p)
```

The tags interface will show the available tags in a splash window. If you want to start a new line after a specific tag, insert `\n` into the tag list

```
#+TAGS: @work(w) @home(h) @tennisclub(t) \n laptop(l) pc(p)
```

or write them in two lines:

```
#+TAGS: @work(w) @home(h) @tennisclub(t)
#+TAGS: laptop(l) pc(p)
```

You can also group together tags that are mutually exclusive by using braces, as in:

```
#+TAGS: { @work(w) @home(h) @tennisclub(t) } laptop(l) pc(p)
```

you indicate that at most one of `@work`, `@home`, and `@tennisclub` should be selected. Multiple such groups are allowed.

Don't forget to press `C-c C-c` with the cursor in one of these lines to activate any changes. To set these mutually exclusive groups in the variable `org-tag-alist`, you must use the dummy tags `:startgroup` and `:endgroup` instead of the braces. Similarly, you can use `:newline` to indicate a line break. The previous example would be set globally by the following configuration:

```
(setq org-tag-alist '(:startgroup . nil)
                     ("@work" . ?w) ("@home" . ?h)
                     ("@tennisclub" . ?t)
                     (:endgroup . nil)
                     ("laptop" . ?l) ("pc" . ?p)))
```

If at least one tag has a selection key then pressing `C-c C-c` will automatically present you with a special interface, listing inherited tags, the tags of the current headline, and a list of all valid tags with corresponding keys<sup>3</sup>. In this interface, you can use the following keys:

|                     |                                                                                                                                                                                                               |
|---------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>a-z...</code> | Pressing keys assigned to tags will add or remove them from the list of tags in the current line. Selecting a tag in a group of mutually exclusive tags will turn off any other tags from that group.         |
| <code>TAB</code>    | Enter a tag in the minibuffer, even if the tag is not in the predefined list. You will be able to complete on all tags present in the buffer. You can also add several tags: just separate them with a comma. |
| <code>SPC</code>    | Clear all tags for this line.                                                                                                                                                                                 |
| <code>RET</code>    | Accept the modified set.                                                                                                                                                                                      |
| <code>C-g</code>    | Abort without installing changes.                                                                                                                                                                             |
| <code>q</code>      | If <code>q</code> is not assigned to a tag, it aborts like <code>C-g</code> .                                                                                                                                 |
| <code>!</code>      | Turn off groups of mutually exclusive tags. Use this to (as an exception) assign several tags from such a group.                                                                                              |
| <code>C-c</code>    | Toggle auto-exit after the next change (see below). If you are using expert mode, the first <code>C-c</code> will display the selection window.                                                               |

This method lets you assign tags to a headline with very few keys. With the above setup, you could clear the current tags and set `@home`, `laptop` and `pc` tags with just the following keys: `C-c C-c SPC h l p RET`. Switching from `@home` to `@work` would be done with `C-c C-c w RET` or alternatively with `C-c C-c C-c w`. Adding the non-predefined tag `Sarah` could be done with `C-c C-c TAB S a r a h RET RET`.

If you find that most of the time you need only a single key press to modify your list of tags, set `org-fast-tag-selection-single-key`. Then you no longer have to press `RET` to exit fast tag selection—it will immediately exit after the first change. If you then occasionally need more keys, press `C-c` to turn off auto-exit for the current tag selection process (in effect: start selection with `C-c C-c C-c` instead of `C-c C-c`). If you set the variable to the value `expert`, the special window is not even shown for single-key tag selection, it comes up only when you press an extra `C-c`.

---

<sup>3</sup> Keys will automatically be assigned to tags which have no configured keys.



## 6.3 Tag hierarchy

Tags can be defined in hierarchies. A tag can be defined as a *group tag* for a set of other tags. The group tag can be seen as the “broader term” for its set of tags. Defining multiple *group tags* and nesting them creates a tag hierarchy.

One use-case is to create a taxonomy of terms (tags) that can be used to classify nodes in a document or set of documents.

When you search for a group tag, it will return matches for all members in the group and its subgroups. In an agenda view, filtering by a group tag will display or hide headlines tagged with at least one of the members of the group or any of its subgroups. This makes tag searches and filters even more flexible.

You can set group tags by using brackets and inserting a colon between the group tag and its related tags—beware that all whitespaces are mandatory so that Org can parse this line correctly:

```
#+TAGS: [ GTD : Control Persp ]
```

In this example, ‘GTD’ is the *group tag* and it is related to two other tags: ‘Control’, ‘Persp’. Defining ‘Control’ and ‘Persp’ as group tags creates an hierarchy of tags:

```
#+TAGS: [ Control : Context Task ]
```

```
#+TAGS: [ Persp : Vision Goal AOF Project ]
```

That can conceptually be seen as a hierarchy of tags:

- GTD
  - Persp
    - Vision
    - Goal
    - AOF
    - Project
  - Control
    - Context
    - Task

You can use the `:startgroup tag`, `:group tags` and `:endgroup tag` keyword directly when setting `org-tag-alist` directly:

```
(setq org-tag-alist '(:startgroup tag
  ("GTD")
  (:group tags
    ("Control")
    ("Persp")
  (:endgroup tag
    (:startgroup tag
      ("Control")
      (:group tags
        ("Context")
        ("Task")
      (:endgroup tag)))
  )
  )
  )
  )
```

The tags in a group can be mutually exclusive if using the same group syntax as is used for grouping mutually exclusive tags together; using curly brackets.

```
#+TAGS: { Context : @Home @Work @Call }
```

When setting `org-tag-alist` you can use `:startgroup & :endgroup` instead of `:startgroup tag & :endgroup tag` to make the tags mutually exclusive.

Furthermore, the members of a *group tag* can also be regular expressions, creating the possibility of a more dynamic and rule-based tag structure. The regular expressions in the group must be specified within `{ }`. Here is an expanded example:

```
#+TAGS: [ Vision : {V@.+} ]
#+TAGS: [ Goal : {G@.+} ]
#+TAGS: [ AOF : {AOF@.+} ]
#+TAGS: [ Project : {P@.+} ]
```

Searching for the tag ‘Project’ will now list all tags also including regular expression matches for ‘P@.+’, and similarly for tag searches on ‘Vision’, ‘Goal’ and ‘AOF’. For example, this would work well for a project tagged with a common project-identifier, e.g. ‘P@2014\_OrgTags’.

If you want to ignore group tags temporarily, toggle group tags support with `org-toggle-tags-groups`, bound to `C-c C-x q`. If you want to disable tag groups completely, set `org-group-tags` to `nil`.

## 6.4 Tag searches

Once a system of tags has been set up, it can be used to collect related information into special lists.

`C-c / m` or `C-c \` `org-match-sparse-tree`  
 Create a sparse tree with all headlines matching a tags/property/TODO search. With a `C-u` prefix argument, ignore headlines that are not a TODO line. See [Section 10.3.3 \[Matching tags and properties\]](#), page 105.

`C-c a m` `org-tags-view`  
 Create a global list of tag matches from all agenda files. See [Section 10.3.3 \[Matching tags and properties\]](#), page 105.

`C-c a M` `org-tags-view`  
 Create a global list of tag matches from all agenda files, but check only TODO items and force checking subitems (see the option `org-tags-match-list-sublevels`).

These commands all prompt for a match string which allows basic Boolean logic like ‘+boss+urgent-project1’, to find entries with tags ‘boss’ and ‘urgent’, but not ‘project1’, or ‘Kathy|Sally’ to find entries tagged as ‘Kathy’ or ‘Sally’. The full syntax of the search string is rich and allows also matching against TODO keywords, entry levels and properties. For a complete description with many examples, see [Section 10.3.3 \[Matching tags and properties\]](#), page 105.

## 7 Properties and columns

A property is a key-value pair associated with an entry. Properties can be set so they are associated with a single entry, with every entry in a tree, or with every entry in an Org mode file.

There are two main applications for properties in Org mode. First, properties are like tags, but with a value. Imagine maintaining a file where you document bugs and plan releases for a piece of software. Instead of using tags like `:release_1:`, `:release_2:`, you can use a property, say `:Release:`, that in different subtrees has different values, such as 1.0 or 2.0. Second, you can use properties to implement (very basic) database capabilities in an Org buffer. Imagine keeping track of your music CDs, where properties could be things such as the album, artist, date of release, number of tracks, and so on.

Properties can be conveniently edited and viewed in column view (see [Section 7.5 \[Column view\]](#), page 67).

### 7.1 Property syntax

Properties are key-value pairs. When they are associated with a single entry or with a tree they need to be inserted into a special drawer (see [Section 2.8 \[Drawers\]](#), page 15) with the name `PROPERTIES`, which has to be located right below a headline, and its planning line (see [Section 8.3 \[Deadlines and scheduling\]](#), page 77) when applicable. Each property is specified on a single line, with the key (surrounded by colons) first, and the value after it. Keys are case-insensitives. Here is an example:

```
* CD collection
** Classic
*** Goldberg Variations
    :PROPERTIES:
    :Title:      Goldberg Variations
    :Composer:   J.S. Bach
    :Artist:     Glen Gould
    :Publisher:  Deutsche Grammophon
    :NDisks:     1
    :END:
```

Depending on the value of `org-use-property-inheritance`, a property set this way will either be associated with a single entry, or the subtree defined by the entry, see [Section 7.4 \[Property inheritance\]](#), page 67.

You may define the allowed values for a particular property `:Xyz:` by setting a property `:Xyz_ALL:`. This special property is *inherited*, so if you set it in a level 1 entry, it will apply to the entire tree. When allowed values are defined, setting the corresponding property becomes easier and is less prone to typing errors. For the example with the CD collection, we can predefine publishers and the number of disks in a box like this:

```
* CD collection
    :PROPERTIES:
    :NDisks_ALL:  1 2 3 4
    :Publisher_ALL: "Deutsche Grammophon" Philips EMI
    :END:
```

If you want to set properties that can be inherited by any entry in a file, use a line like

```
#+PROPERTY: NDisks_ALL 1 2 3 4
```

Contrary to properties set from a special drawer, you have to refresh the buffer with `C-c C-c` to activate this change.

If you want to add to the value of an existing property, append a `+` to the property name. The following results in the property `var` having the value “foo=1 bar=2”.

```
#+PROPERTY: var foo=1
#+PROPERTY: var+ bar=2
```

It is also possible to add to the values of inherited properties. The following results in the `genres` property having the value “Classic Baroque” under the `Goldberg Variations` subtree.

```
* CD collection
** Classic
   :PROPERTIES:
   :GENRES: Classic
   :END:
*** Goldberg Variations
   :PROPERTIES:
   :Title:    Goldberg Variations
   :Composer: J.S. Bach
   :Artist:   Glen Gould
   :Publisher: Deutsche Grammophon
   :NDisks:   1
   :GENRES+:  Baroque
   :END:
```

Note that a property can only have one entry per Drawer.

Property values set with the global variable `org-global-properties` can be inherited by all entries in all Org files.

The following commands help to work with properties:

|                                                                                                                                                                |                                  |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------|
| <i>M-TAB</i>                                                                                                                                                   | <code>pcomplete</code>           |
| After an initial colon in a line, complete property keys. All keys used in the current file will be offered as possible completions.                           |                                  |
| <i>C-c C-x p</i>                                                                                                                                               | <code>org-set-property</code>    |
| Set a property. This prompts for a property name and a value. If necessary, the property drawer is created as well.                                            |                                  |
| <i>C-u M-x org-insert-drawer RET</i>                                                                                                                           |                                  |
| Insert a property drawer into the current entry. The drawer will be inserted early in the entry, but after the lines with planning information like deadlines. |                                  |
| <i>C-c C-c</i>                                                                                                                                                 | <code>org-property-action</code> |
| With the cursor in a property drawer, this executes property commands.                                                                                         |                                  |
| <i>C-c C-c s</i>                                                                                                                                               | <code>org-set-property</code>    |
| Set a property in the current entry. Both the property and the value can be inserted using completion.                                                         |                                  |

|                                                                                                        |                                                  |
|--------------------------------------------------------------------------------------------------------|--------------------------------------------------|
| <i>S-right</i>                                                                                         | <code>org-property-next-allowed-value</code>     |
| <i>S-left</i>                                                                                          | <code>org-property-previous-allowed-value</code> |
| Switch property at point to the next/previous allowed value.                                           |                                                  |
| <i>C-c C-c d</i>                                                                                       | <code>org-delete-property</code>                 |
| Remove a property from the current entry.                                                              |                                                  |
| <i>C-c C-c D</i>                                                                                       | <code>org-delete-property-globally</code>        |
| Globally remove a property, from all entries in the current file.                                      |                                                  |
| <i>C-c C-c c</i>                                                                                       | <code>org-compute-property-at-point</code>       |
| Compute the property at point, using the operator and scope from the nearest column format definition. |                                                  |

## 7.2 Special properties

Special properties provide an alternative access method to Org mode features, like the TODO state or the priority of an entry, discussed in the previous chapters. This interface exists so that you can include these states in a column view (see [Section 7.5 \[Column view\]](#), [page 67](#)), or to use them in queries. The following property names are special and should not be used as keys in the properties drawer:

|              |                                                                                                                                                      |
|--------------|------------------------------------------------------------------------------------------------------------------------------------------------------|
| ALLTAGS      | All tags, including inherited ones.                                                                                                                  |
| BLOCKED      | "t" if task is currently blocked by children or siblings.                                                                                            |
| CLOCKSUM     | The sum of CLOCK intervals in the subtree. <code>org-clock-sum</code> must be run first to compute the values in the current buffer.                 |
| CLOCKSUM_T   | The sum of CLOCK intervals in the subtree for today. <code>org-clock-sum-today</code> must be run first to compute the values in the current buffer. |
| CLOSED       | When was this entry closed?                                                                                                                          |
| DEADLINE     | The deadline time string, without the angular brackets.                                                                                              |
| FILE         | The filename the entry is located in.                                                                                                                |
| ITEM         | The headline of the entry.                                                                                                                           |
| PRIORITY     | The priority of the entry, a string with a single letter.                                                                                            |
| SCHEDULED    | The scheduling timestamp, without the angular brackets.                                                                                              |
| TAGS         | The tags defined directly in the headline.                                                                                                           |
| TIMESTAMP    | The first keyword-less timestamp in the entry.                                                                                                       |
| TIMESTAMP_IA | The first inactive timestamp in the entry.                                                                                                           |
| TODO         | The TODO keyword of the entry.                                                                                                                       |

## 7.3 Property searches

To create sparse trees and special lists with selection based on properties, the same commands are used as for tag searches (see [Section 6.4 \[Tag searches\]](#), [page 63](#)).

|                                                                                                                                                                    |                                    |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------|
| <i>C-c / m</i> or <i>C-c \</i>                                                                                                                                     | <code>org-match-sparse-tree</code> |
| Create a sparse tree with all matching entries. With a <i>C-u</i> prefix argument, ignore headlines that are not a TODO line.                                      |                                    |
| <i>C-c a m</i>                                                                                                                                                     | <code>org-tags-view</code>         |
| Create a global list of tag/property matches from all agenda files. See <a href="#">Section 10.3.3 [Matching tags and properties]</a> , <a href="#">page 105</a> . |                                    |

**C-c a M** **org-tags-view**  
 Create a global list of tag matches from all agenda files, but check only TODO items and force checking of subitems (see the option **org-tags-match-list-sublevels**).

The syntax for the search string is described in [Section 10.3.3 \[Matching tags and properties\]](#), page 105.

There is also a special command for creating sparse trees based on a single property:

**C-c / p** Create a sparse tree based on the value of a property. This first prompts for the name of a property, and then for a value. A sparse tree is created with all entries that define this property with the given value. If you enclose the value in curly braces, it is interpreted as a regular expression and matched against the property values.

## 7.4 Property Inheritance

The outline structure of Org mode documents lends itself to an inheritance model of properties: if the parent in a tree has a certain property, the children can inherit this property. Org mode does not turn this on by default, because it can slow down property searches significantly and is often not needed. However, if you find inheritance useful, you can turn it on by setting the variable **org-use-property-inheritance**. It may be set to **t** to make all properties inherited from the parent, to a list of properties that should be inherited, or to a regular expression that matches inherited properties. If a property has the value **nil**, this is interpreted as an explicit undefine of the property, so that inheritance search will stop at this value and return **nil**.

Org mode has a few properties for which inheritance is hard-coded, at least for the special applications for which they are used:

**COLUMNS** The **:COLUMNS:** property defines the format of column view (see [Section 7.5 \[Column view\]](#), page 67). It is inherited in the sense that the level where a **:COLUMNS:** property is defined is used as the starting point for a column view table, independently of the location in the subtree from where columns view is turned on.

**CATEGORY** For agenda view, a category set through a **:CATEGORY:** property applies to the entire subtree.

**ARCHIVE** For archiving, the **:ARCHIVE:** property may define the archive location for the entire subtree (see [Section 9.6.1 \[Moving subtrees\]](#), page 98).

**LOGGING** The **LOGGING** property may define logging settings for an entry or a subtree (see [Section 5.3.2 \[Tracking TODO state changes\]](#), page 52).

## 7.5 Column view

A great way to view and edit properties in an outline tree is *column view*. In column view, each outline node is turned into a table row. Columns in this table provide access to properties of the entries. Org mode implements columns by overlaying a tabular structure over the headline of each item. While the headlines have been turned into a table row, you can still change the visibility of the outline tree. For example, you get a compact table

by switching to CONTENTS view (*S-TAB S-TAB*, or simply *c* while column view is active), but you can still open, read, and edit the entry below each headline. Or, you can switch to column view after executing a sparse tree command and in this way get a table only for the selected items. Column view also works in agenda buffers (see [Chapter 10 \[Agenda views\]](#), [page 100](#)) where queries have collected selected items, possibly from a number of files.

### 7.5.1 Defining columns

Setting up a column view first requires defining the columns. This is done by defining a column format line.

#### 7.5.1.1 Scope of column definitions

To define a column format for an entire file, use a line like

```
#+COLUMNS: %25ITEM %TAGS %PRIORITY %TODO
```

To specify a format that only applies to a specific tree, add a `:COLUMNS:` property to the top node of that tree, for example:

```
** Top node for columns view
   :PROPERTIES:
   :COLUMNS: %25ITEM %TAGS %PRIORITY %TODO
   :END:
```

If a `:COLUMNS:` property is present in an entry, it defines columns for the entry itself, and for the entire subtree below it. Since the column definition is part of the hierarchical structure of the document, you can define columns on level 1 that are general enough for all sublevels, and more specific columns further down, when you edit a deeper part of the tree.

#### 7.5.1.2 Column attributes

A column definition sets the attributes of a column. The general definition looks like this:

```
%[width]property[(title)] [{summary-type}]
```

Except for the percent sign and the property name, all items are optional. The individual parts have the following meaning:

|                       |                                                                                                                                                                                                            |
|-----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>width</i>          | An integer specifying the width of the column in characters.<br>If omitted, the width will be determined automatically.                                                                                    |
| <i>property</i>       | The property that should be edited in this column.<br>Special properties representing meta data are allowed here as well (see <a href="#">Section 7.2 [Special properties]</a> , <a href="#">page 66</a> ) |
| <i>title</i>          | The header text for the column. If omitted, the property name is used.                                                                                                                                     |
| <i>{summary-type}</i> | The summary type. If specified, the column values for parent nodes are computed from the children <sup>1</sup> .<br>Supported summary types are:<br><code>{+}</code> Sum numbers in this column.           |

---

<sup>1</sup> If

more than one summary type apply to the property, the parent values are computed according to the first of them.

|                        |                                                          |
|------------------------|----------------------------------------------------------|
| <code>{+;% .1f}</code> | Like '+', but format result with '%.1f'.                 |
| <code>{ \$ }</code>    | Currency, short for '+;% .2f'.                           |
| <code>{min}</code>     | Smallest number in column.                               |
| <code>{max}</code>     | Largest number.                                          |
| <code>{mean}</code>    | Arithmetic mean of numbers.                              |
| <code>{X}</code>       | Checkbox status, '[X]' if all children are '[X]'.        |
| <code>{X/}</code>      | Checkbox status, '[n/m]'.                                |
| <code>{X%}</code>      | Checkbox status, '[n%]'.                                 |
| <code>{:}</code>       | Sum times, HH:MM, plain numbers are hours <sup>2</sup> . |
| <code>{:min}</code>    | Smallest time value in column.                           |
| <code>{:max}</code>    | Largest time value.                                      |
| <code>{:mean}</code>   | Arithmetic mean of time values.                          |
| <code>{@min}</code>    | Minimum age <sup>3</sup> (in days/hours/mins/seconds).   |
| <code>{@max}</code>    | Maximum age (in days/hours/mins/seconds).                |
| <code>{@mean}</code>   | Arithmetic mean of ages (in days/hours/mins/seconds).    |
| <code>{est+}</code>    | Add 'low-high' estimates.                                |

The **est+** summary type requires further explanation. It is used for combining estimates, expressed as 'low-high' ranges or plain numbers. For example, instead of estimating a particular task will take 5 days, you might estimate it as 5–6 days if you're fairly confident you know how much work is required, or 1–10 days if you don't really know what needs to be done. Both ranges average at 5.5 days, but the first represents a more predictable delivery.

When combining a set of such estimates, simply adding the lows and highs produces an unrealistically wide result. Instead, **est+** adds the statistical mean and variance of the sub-tasks, generating a final estimate from the sum. For example, suppose you had ten tasks, each of which was estimated at 0.5 to 2 days of work. Straight addition produces an estimate of 5 to 20 days, representing what to expect if everything goes either extremely well or extremely poorly. In contrast, **est+** estimates the full job more realistically, at 10–15 days.

Numbers are right-aligned when a format specifier with an explicit width like `%5d` or `%5.1f` is used.

You can also define custom summary types by setting `org-columns-summary-types`, which see.

Here is an example for a complete columns definition, along with allowed values.

---

<sup>2</sup> A time can also be a duration, using effort modifiers defined in `org-effort-durations`, e.g., `'3d 1h'`. If any value in the column is as such, the summary will also be an effort duration.

<sup>3</sup> An age is defined as a duration since a given time-stamp (see [Section 8.1 \[Timestamps\]](#), page 73). It can also be expressed as days, hours, minutes and seconds, identified by 'd', 'h', 'm' and 's' suffixes, all mandatory, e.g., `'0d 13h 0m 10s'`.



```

:COLUMNS:  %25ITEM %9Approved(Approved?){X} %Owner %11Status \^4
              %10Time_Estimate{:} %CLOCKSUM %CLOCKSUM_T
:Owner_ALL:  Tammy Mark Karl Lisa Don
:Status_ALL:  "In progress" "Not started yet" "Finished" ""
:Approved_ALL:  "[ ]" "[X]"

```

The first column, ‘%25ITEM’, means the first 25 characters of the item itself, i.e., of the headline. You probably always should start the column definition with the ‘ITEM’ specifier. The other specifiers create columns ‘Owner’ with a list of names as allowed values, for ‘Status’ with four different possible values, and for a checkbox field ‘Approved’. When no width is given after the ‘%’ character, the column will be exactly as wide as it needs to be in order to fully display all values. The ‘Approved’ column does have a modified title (‘Approved?’, with a question mark). Summaries will be created for the ‘Time\_Estimate’ column by adding time duration expressions like HH:MM, and for the ‘Approved’ column, by providing an ‘[X]’ status if all children have been checked. The ‘CLOCKSUM’ and ‘CLOCKSUM\_T’ columns are special, they lists the sums of CLOCK intervals in the subtree, either for all clocks or just for today.

## 7.5.2 Using column view

### Turning column view on and off

*C-c C-x C-c*

*org-columns*

Turn on column view. If the cursor is before the first headline in the file, or the function called with the universal prefix argument, column view is turned on for the entire file, using the `#+COLUMNS` definition. If the cursor is somewhere inside the outline, this command searches the hierarchy, up from point, for a `:COLUMNS:` property that defines a format. When one is found, the column view table is established for the tree starting at the entry that contains the `:COLUMNS:` property. If no such property is found, the format is taken from the `#+COLUMNS` line or from the variable `org-columns-default-format`, and column view is established for the current entry and its subtree.

|          |                                                                         |                         |
|----------|-------------------------------------------------------------------------|-------------------------|
| <i>r</i> |                                                                         | <i>org-columns-redo</i> |
|          | Recreate the column view, to include recent changes made in the buffer. |                         |
| <i>g</i> |                                                                         | <i>org-columns-redo</i> |
|          | Same as <i>r</i> .                                                      |                         |
| <i>q</i> |                                                                         | <i>org-columns-quit</i> |
|          | Exit column view.                                                       |                         |

### Editing values

*left right up down*

Move through the column view from field to field.

*S-left/right*

Switch to the next/previous allowed value of the field. For this, you have to have specified allowed values for a property.

---

<sup>4</sup> Please note that the COLUMNS definition must be on a single line—it is wrapped here only because of formatting constraints.

|                |                                                                                                                                                                                                                                                   |
|----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>1..9,0</i>  | Directly select the Nth allowed value, 0 selects the 10th value.                                                                                                                                                                                  |
| <i>n</i>       | <code>org-columns-next-allowed-value</code>                                                                                                                                                                                                       |
| <i>p</i>       | <code>org-columns-previous-allowed-value</code>                                                                                                                                                                                                   |
|                | Same as <i>S-left/right</i>                                                                                                                                                                                                                       |
| <i>e</i>       | <code>org-columns-edit-value</code>                                                                                                                                                                                                               |
|                | Edit the property at point. For the special properties, this will invoke the same interface that you normally use to change that property. For example, when editing a TAGS property, the tag completion or fast selection interface will pop up. |
| <i>C-c C-c</i> | <code>org-columns-set-tags-or-toggle</code>                                                                                                                                                                                                       |
|                | When there is a checkbox at point, toggle it.                                                                                                                                                                                                     |
| <i>v</i>       | <code>org-columns-show-value</code>                                                                                                                                                                                                               |
|                | View the full value of this property. This is useful if the width of the column is smaller than that of the value.                                                                                                                                |
| <i>a</i>       | <code>org-columns-edit-allowed</code>                                                                                                                                                                                                             |
|                | Edit the list of allowed values for this property. If the list is found in the hierarchy, the modified value is stored there. If no list is found, the new value is stored in the first entry that is part of the current column view.            |

### Modifying the table structure

|                  |                                                         |
|------------------|---------------------------------------------------------|
| <i>&lt;</i>      | <code>org-columns-narrow</code>                         |
| <i>&gt;</i>      | <code>org-columns-widen</code>                          |
|                  | Make the column narrower/wider by one character.        |
| <i>S-M-right</i> | <code>org-columns-new</code>                            |
|                  | Insert a new column, to the left of the current column. |
| <i>S-M-left</i>  | <code>org-columns-delete</code>                         |
|                  | Delete the current column.                              |

### 7.5.3 Capturing column view

Since column view is just an overlay over a buffer, it cannot be exported or printed directly. If you want to capture a column view, use a `columnview` dynamic block (see [Section A.7 \[Dynamic blocks\]](#), page 244). The frame of this block looks like this:

```
* The column view
#+BEGIN: columnview :hlines 1 :id "label"

#+END:
```

This dynamic block has the following parameters:

|               |                                                                                                                                                                                                                                                      |
|---------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>:id</i>    | This is the most important parameter. Column view is a feature that is often localized to a certain (sub)tree, and the capture block might be at a different location in the file. To identify the tree whose view to capture, you can use 4 values: |
| <i>local</i>  | use the tree in which the capture block is located                                                                                                                                                                                                   |
| <i>global</i> | make a global view, including all headings in the file                                                                                                                                                                                               |

- `"file:path-to-file"`  
run column view at the top of this file
- `"ID"`  
call column view in the tree that has an `:ID:` property with the value *label*. You can use `M-x org-id-copy RET` to create a globally unique ID for the current entry and copy it to the kill-ring.
- `:hlines` When `t`, insert an hline after every line. When a number *N*, insert an hline before each headline with level  $\leq N$ .
- `:vlines` When set to `t`, force column groups to get vertical lines.
- `:maxlevel`  
When set to a number, don't capture entries below this level.
- `:skip-empty-rows`  
When set to `t`, skip rows where the only non-empty specifier of the column view is `ITEM`.
- `:indent` When non-`nil`, indent each `ITEM` field according to its level.

The following commands insert or update the dynamic block:

- `C-c C-x i` `org-insert-columns-dblock`  
Insert a dynamic block capturing a column view. You will be prompted for the scope or ID of the view.
- `C-c C-c` or `C-c C-x C-u` `org-dblock-update`  
Update dynamic block at point. The cursor needs to be in the `#+BEGIN` line of the dynamic block.
- `C-u C-c C-x C-u` `org-update-all-dblocks`  
Update all dynamic blocks (see [Section A.7 \[Dynamic blocks\]](#), page 244). This is useful if you have several clock table blocks, column-capturing blocks or other dynamic blocks in a buffer.

You can add formulas to the column view table and you may add plotting instructions in front of the table—these will survive an update of the block. If there is a `#+TBLFM:` after the table, the table will actually be recalculated automatically after an update.

An alternative way to capture and process property values into a table is provided by Eric Schulte's `org-collector.el` which is a contributed package<sup>5</sup>. It provides a general API to collect properties from entries in a certain scope, and arbitrary Lisp expressions to process these values before inserting them into a table or a dynamic block.

## 7.6 The Property API

There is a full API for accessing and changing properties. This API can be used by Emacs Lisp programs to work with properties and to implement features based on them. For more information see [Section A.11 \[Using the property API\]](#), page 248.

---

<sup>5</sup> Contributed packages are not part of Emacs, but are distributed with the main distribution of Org (visit <http://orgmode.org>).

## 8 Dates and times

To assist project planning, TODO items can be labeled with a date and/or a time. The specially formatted string carrying the date and time information is called a *timestamp* in Org mode. This may be a little confusing because timestamp is often used to indicate when something was created or last changed. However, in Org mode this term is used in a much wider sense.

### 8.1 Timestamps, deadlines, and scheduling

A timestamp is a specification of a date (possibly with a time or a range of times) in a special format, either ‘<2003-09-16 Tue>’<sup>1</sup> or ‘<2003-09-16 Tue 09:39>’ or ‘<2003-09-16 Tue 12:00-12:30>’<sup>2</sup>. A timestamp can appear anywhere in the headline or body of an Org tree entry. Its presence causes entries to be shown on specific dates in the agenda (see [Section 10.3.1 \[Weekly/daily agenda\], page 102](#)). We distinguish:

#### *Plain timestamp; Event; Appointment*

A simple timestamp just assigns a date/time to an item. This is just like writing down an appointment or event in a paper agenda. In the timeline and agenda displays, the headline of an entry associated with a plain timestamp will be shown exactly on that date.

```
* Meet Peter at the movies
  <2006-11-01 Wed 19:15>
* Discussion on climate change
  <2006-11-02 Thu 20:00-22:00>
```

#### *Timestamp with repeater interval*

A timestamp may contain a *repeater interval*, indicating that it applies not only on the given date, but again and again after a certain interval of N days (d), weeks (w), months (m), or years (y). The following will show up in the agenda every Wednesday:

```
* Pick up Sam at school
  <2007-05-16 Wed 12:30 +1w>
```

#### *Diary-style sexp entries*

For more complex date specifications, Org mode supports using the special sexp diary entries implemented in the Emacs calendar/diary package<sup>3</sup>. For example with optional time

<sup>1</sup> In this simplest form, the day name is optional when you type the date yourself. However, any dates inserted or modified by Org will add that day name, for reading convenience.

<sup>2</sup> This is inspired by the standard ISO 8601 date/time format. To use an alternative format, see [Section 8.2.2 \[Custom time format\], page 77](#).

<sup>3</sup> When working with the standard diary sexp functions, you need to be very careful with the order of the arguments. That order depends evilly on the variable `calendar-date-style` (or, for older Emacs versions, `european-calendar-style`). For example, to specify a date December 1, 2005, the call might look like `(diary-date 12 1 2005)` or `(diary-date 1 12 2005)` or `(diary-date 2005 12 1)`, depending on the settings. This has been the source of much confusion. Org mode users can resort to special versions of these functions like `org-date` or `org-anniversary`. These work just like the corresponding `diary-` functions, but with stable ISO order of arguments (year, month, day) wherever applicable, independent of the value of `calendar-date-style`.

```
* 22:00-23:00 The nerd meeting on every 2nd Thursday of the month
<%%(diary-float t 4 2)>
```

### *Time/Date range*

Two timestamps connected by ‘--’ denote a range. The headline will be shown on the first and last day of the range, and on any dates that are displayed and fall in the range. Here is an example:

```
** Meeting in Amsterdam
<2004-08-23 Mon>--<2004-08-26 Thu>
```

### *Inactive timestamp*

Just like a plain timestamp, but with square brackets instead of angular ones. These timestamps are inactive in the sense that they do *not* trigger an entry to show up in the agenda.

```
* Gillian comes late for the fifth time
[2006-11-01 Wed]
```

## 8.2 Creating timestamps

For Org mode to recognize timestamps, they need to be in the specific format. All commands listed below produce timestamps in the correct format.

|                        |                                                                                                                                                                                                                                                                          |
|------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>C-c .</code>     | <code>org-time-stamp</code>                                                                                                                                                                                                                                              |
|                        | Prompt for a date and insert a corresponding timestamp. When the cursor is at an existing timestamp in the buffer, the command is used to modify this timestamp instead of inserting a new one. When this command is used twice in succession, a time range is inserted. |
| <code>C-c !</code>     | <code>org-time-stamp-inactive</code>                                                                                                                                                                                                                                     |
|                        | Like <code>C-c .</code> , but insert an inactive timestamp that will not cause an agenda entry.                                                                                                                                                                          |
| <code>C-u C-c .</code> |                                                                                                                                                                                                                                                                          |
| <code>C-u C-c !</code> | Like <code>C-c .</code> and <code>C-c !</code> , but use the alternative format which contains date and time. The default time can be rounded to multiples of 5 minutes, see the option <code>org-time-stamp-rounding-minutes</code> .                                   |
| <code>C-c C-c</code>   | Normalize timestamp, insert/fix day name if missing or wrong.                                                                                                                                                                                                            |
| <code>C-c &lt;</code>  | <code>org-date-from-calendar</code>                                                                                                                                                                                                                                      |
|                        | Insert a timestamp corresponding to the cursor date in the Calendar.                                                                                                                                                                                                     |
| <code>C-c &gt;</code>  | <code>org-goto-calendar</code>                                                                                                                                                                                                                                           |
|                        | Access the Emacs calendar for the current date. If there is a timestamp in the current line, go to the corresponding date instead.                                                                                                                                       |
| <code>C-c C-o</code>   | <code>org-open-at-point</code>                                                                                                                                                                                                                                           |
|                        | Access the agenda for the date given by the timestamp or -range at point (see <a href="#">Section 10.3.1 [Weekly/daily agenda]</a> , page 102).                                                                                                                          |
| <code>S-left</code>    | <code>org-timestamp-down-day</code>                                                                                                                                                                                                                                      |
| <code>S-right</code>   | <code>org-timestamp-up-day</code>                                                                                                                                                                                                                                        |
|                        | Change date at cursor by one day. These key bindings conflict with shift-selection and related modes (see <a href="#">Section 15.10.2 [Conflicts]</a> , page 234).                                                                                                       |

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                         |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|
| <i>S</i> -up                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | org-timestamp-up        |
| <i>S</i> -down                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | org-timestamp-down-down |
| <p>Change the item under the cursor in a timestamp. The cursor can be on a year, month, day, hour or minute. When the timestamp contains a time range like ‘15:30-16:30’, modifying the first time will also shift the second, shifting the time block with constant length. To change the length, modify the second time. Note that if the cursor is in a headline and not at a timestamp, these same keys modify the priority of an item. (see <a href="#">Section 5.4 [Priorities]</a>, page 55). The key bindings also conflict with shift-selection and related modes (see <a href="#">Section 15.10.2 [Conflicts]</a>, page 234).</p> |                         |
| <i>C</i> -c <i>C</i> -y                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | org-evaluate-time-range |
| <p>Evaluate a time range by computing the difference between start and end. With a prefix argument, insert result after the time range (in a table: into the following column).</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                         |

### 8.2.1 The date/time prompt

When Org mode prompts for a date/time, the default is shown in default date/time format, and the prompt therefore seems to ask for a specific format. But it will in fact accept date/time information in a variety of formats. Generally, the information should start at the beginning of the string. Org mode will find whatever information is in there and derive anything you have not specified from the *default date and time*. The default is usually the current date and time, but when modifying an existing timestamp, or when entering the second stamp of a range, it is taken from the stamp in the buffer. When filling in information, Org mode assumes that most of the time you will want to enter a date in the future: if you omit the month/year and the given day/month is *before* today, it will assume that you mean a future date<sup>4</sup>. If the date has been automatically shifted into the future, the time prompt will show this with ‘(=>F).’

For example, let’s assume that today is **June 13, 2006**. Here is how various inputs will be interpreted, the items filled in by Org mode are in **bold**.

|              |                                                 |
|--------------|-------------------------------------------------|
| 3-2-5        | ⇒ 2003-02-05                                    |
| 2/5/3        | ⇒ 2003-02-05                                    |
| 14           | ⇒ <b>2006-06-14</b>                             |
| 12           | ⇒ <b>2006-07-12</b>                             |
| 2/5          | ⇒ <b>2007-02-05</b>                             |
| Fri          | ⇒ nearest Friday after the default date         |
| sep 15       | ⇒ <b>2006-09-15</b>                             |
| feb 15       | ⇒ <b>2007-02-15</b>                             |
| sep 12 9     | ⇒ 2009-09-12                                    |
| 12:45        | ⇒ <b>2006-06-13</b> 12:45                       |
| 22 sept 0:34 | ⇒ <b>2006-09-22</b> 00:34                       |
| w4           | ⇒ ISO week four of the current year <b>2006</b> |
| 2012 w4 fri  | ⇒ Friday of ISO week 4 in 2012                  |
| 2012-w04-5   | ⇒ Same as above                                 |

<sup>4</sup> See the variable `org-read-date-prefer-future`. You may set that variable to the symbol `time` to even make a time before now shift the date to tomorrow.

Furthermore you can specify a relative date by giving, as the *first* thing in the input: a plus/minus sign, a number and a letter ([hdwmy]) to indicate change in hours, days, weeks, months, or years. With a single plus or minus, the date is always relative to today. With a double plus or minus, it is relative to the default date. If instead of a single letter, you use the abbreviation of day name, the date will be the Nth such day, e.g.:

```
+0           ⇒ today
.            ⇒ today
+4d          ⇒ four days from today
+4           ⇒ same as above
+2w          ⇒ two weeks from today
++5          ⇒ five days from default date
+2tue        ⇒ second Tuesday from now
-wed         ⇒ last Wednesday
```

The function understands English month and weekday abbreviations. If you want to use unabbreviated names and/or other languages, configure the variables `parse-time-months` and `parse-time-weekdays`.

Not all dates can be represented in a given Emacs implementation. By default Org mode forces dates into the compatibility range 1970–2037 which works on all Emacs implementations. If you want to use dates outside of this range, read the docstring of the variable `org-read-date-force-compatible-dates`.

You can specify a time range by giving start and end times or by giving a start time and a duration (in HH:MM format). Use one or two dash(es) as the separator in the former case and use '+' as the separator in the latter case, e.g.:

```
11am-1:15pm   ⇒ 11:00-13:15
11am--1:15pm  ⇒ same as above
11am+2:15     ⇒ same as above
```

Parallel to the minibuffer prompt, a calendar is popped up<sup>5</sup>. When you exit the date prompt, either by clicking on a date in the calendar, or by pressing RET, the date selected in the calendar will be combined with the information entered at the prompt. You can control the calendar fully from the minibuffer:

```
RET           Choose date at cursor in calendar.
mouse-1       Select date by clicking on it.
S-right/left  One day forward/backward.
S-down/up     One week forward/backward.
M-S-right/left One month forward/backward.
> / <         Scroll calendar forward/backward by one month.
M-v / C-v     Scroll calendar forward/backward by 3 months.
M-S-down/up   Scroll calendar forward/backward by one year.
```

The actions of the date/time prompt may seem complex, but I assure you they will grow on you, and you will start getting annoyed by pretty much any other way of entering a date/time out there. To help you understand what is going on, the current interpretation of your input will be displayed live in the minibuffer<sup>6</sup>.

<sup>5</sup> If you don't need/want the calendar, configure the variable `org-popup-calendar-for-date-prompt`.

<sup>6</sup> If you find this distracting, turn the display off with `org-read-date-display-live`.

### 8.2.2 Custom time format

Org mode uses the standard ISO notation for dates and times as it is defined in ISO 8601. If you cannot get used to this and require another representation of date and time to keep you happy, you can get it by customizing the options `org-display-custom-times` and `org-time-stamp-custom-formats`.

`C-c C-x C-t` `org-toggle-time-stamp-overlays`  
Toggle the display of custom formats for dates and times.

Org mode needs the default format for scanning, so the custom date/time format does not *replace* the default format—instead it is put *over* the default format using text properties. This has the following consequences:

- You cannot place the cursor onto a timestamp anymore, only before or after.
- The *S-up/down* keys can no longer be used to adjust each component of a timestamp. If the cursor is at the beginning of the stamp, *S-up/down* will change the stamp by one day, just like *S-left/right*. At the end of the stamp, the time will be changed by one minute.
- If the timestamp contains a range of clock times or a repeater, these will not be overlaid, but remain in the buffer as they were.
- When you delete a timestamp character-by-character, it will only disappear from the buffer after *all* (invisible) characters belonging to the ISO timestamp have been removed.
- If the custom timestamp format is longer than the default and you are using dates in tables, table alignment will be messed up. If the custom format is shorter, things do work as expected.

## 8.3 Deadlines and scheduling

A timestamp may be preceded by special keywords to facilitate planning:

### *DEADLINE*

Meaning: the task (most likely a TODO item, though not necessarily) is supposed to be finished on that date.

On the deadline date, the task will be listed in the agenda. In addition, the agenda for *today* will carry a warning about the approaching or missed deadline, starting `org-deadline-warning-days` before the due date, and continuing until the entry is marked DONE. An example:

```
*** TODO write article about the Earth for the Guide
    DEADLINE: <2004-02-29 Sun>
    The editor in charge is [[bldb:Ford Prefect]]
```

You can specify a different lead time for warnings for a specific deadline using the following syntax. Here is an example with a warning period of 5 days `DEADLINE: <2004-02-29 Sun -5d>`. This warning is deactivated if the task gets scheduled and you set `org-agenda-skip-deadline-prewarning-if-scheduled` to `t`.

### *SCHEDULED*

Meaning: you are planning to start working on that task on the given date.



The headline will be listed under the given date<sup>7</sup>. In addition, a reminder that the scheduled date has passed will be present in the compilation for *today*, until the entry is marked DONE, i.e., the task will automatically be forwarded until completed.

```
*** TODO Call Trillian for a date on New Years Eve.
    SCHEDULED: <2004-12-25 Sat>
```

If you want to *delay* the display of this task in the agenda, use `SCHEDULED: <2004-12-25 Sat -2d>`: the task is still scheduled on the 25th but will appear two days later. In case the task contains a repeater, the delay is considered to affect all occurrences; if you want the delay to only affect the first scheduled occurrence of the task, use `--2d` instead. See `org-scheduled-delay-days` and `org-agenda-skip-scheduled-delay-if-deadline` for details on how to control this globally or per agenda.

**Important:** Scheduling an item in Org mode should *not* be understood in the same way that we understand *scheduling a meeting*. Setting a date for a meeting is just a simple appointment, you should mark this entry with a simple plain timestamp, to get this item shown on the date where it applies. This is a frequent misunderstanding by Org users. In Org mode, *scheduling* means setting a date when you want to start working on an action item.

You may use timestamps with repeaters in scheduling and deadline entries. Org mode will issue early and late warnings based on the assumption that the timestamp represents the *nearest instance* of the repeater. However, the use of diary sexp entries like `<%(diary-float t 42)>` in scheduling and deadline timestamps is limited. Org mode does not know enough about the internals of each sexp function to issue early and late warnings. However, it will show the item on each day where the sexp entry matches.

### 8.3.1 Inserting deadlines or schedules

The following commands allow you to quickly insert<sup>8</sup> a deadline or to schedule an item:

|                                                                                                                                                                                                                                                                                                                                                                                  |                           |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------|
| <code>C-c C-d</code>                                                                                                                                                                                                                                                                                                                                                             | <code>org-deadline</code> |
| Insert ‘DEADLINE’ keyword along with a stamp. The insertion will happen in the line directly following the headline. Any CLOSED timestamp will be removed. When called with a prefix arg, an existing deadline will be removed from the entry. Depending on the variable <code>org-log-redeadline</code> <sup>9</sup> , a note will be taken when changing an existing deadline. |                           |
| <code>C-c C-s</code>                                                                                                                                                                                                                                                                                                                                                             | <code>org-schedule</code> |
| Insert ‘SCHEDULED’ keyword along with a stamp. The insertion will happen in the line directly following the headline. Any CLOSED timestamp will be removed. When called with a prefix argument, remove the scheduling date                                                                                                                                                       |                           |

<sup>7</sup> It will still be listed on that date after it has been marked DONE. If you don’t like this, set the variable `org-agenda-skip-scheduled-if-done`.

<sup>8</sup> The ‘SCHEDULED’ and ‘DEADLINE’ dates are inserted on the line right below the headline. Don’t put any text between this line and the headline.

<sup>9</sup> with corresponding `#+STARTUP` keywords `logredeadline`, `lognoteredecline`, and `nologredeadline`

from the entry. Depending on the variable `org-log-reschedule`<sup>10</sup>, a note will be taken when changing an existing scheduling time.

**C-c / d** **org-check-deadlines**  
 Create a sparse tree with all deadlines that are either past-due, or which will become due within `org-deadline-warning-days`. With **C-u** prefix, show all deadlines in the file. With a numeric prefix, check that many days. For example, **C-1 C-c / d** shows all deadlines due tomorrow.

**C-c / b** **org-check-before-date**  
 Sparse tree for deadlines and scheduled items before a given date.

**C-c / a** **org-check-after-date**  
 Sparse tree for deadlines and scheduled items after a given date.

Note that `org-schedule` and `org-deadline` supports setting the date by indicating a relative time: e.g., `+1d` will set the date to the next day after today, and `-1w` will set the date to the previous week before any current timestamp.

### 8.3.2 Repeated tasks

Some tasks need to be repeated again and again. Org mode helps to organize such tasks using a so-called repeater in a DEADLINE, SCHEDULED, or plain timestamp. In the following example

```
** TODO Pay the rent
   DEADLINE: <2005-10-01 Sat +1m>
```

the `+1m` is a repeater; the intended interpretation is that the task has a deadline on `<2005-10-01>` and repeats itself every (one) month starting from that time. You can use yearly, monthly, weekly, daily and hourly repeat cookies by using the `y/w/m/d/h` letters. If you need both a repeater and a special warning period in a deadline entry, the repeater should come first and the warning period last: `DEADLINE: <2005-10-01 Sat +1m -3d>`.

Deadlines and scheduled items produce entries in the agenda when they are over-due, so it is important to be able to mark such an entry as completed once you have done so. When you mark a DEADLINE or a SCHEDULE with the TODO keyword DONE, it will no longer produce entries in the agenda. The problem with this is, however, that then also the *next* instance of the repeated entry will not be active. Org mode deals with this in the following way: When you try to mark such an entry DONE (using **C-c C-t**), it will shift the base date of the repeating timestamp by the repeater interval, and immediately set the entry state back to TODO<sup>11</sup>. In the example above, setting the state to DONE would actually switch the date like this:

```
** TODO Pay the rent
   DEADLINE: <2005-11-01 Tue +1m>
```

To mark a task with a repeater as DONE, use **C-- 1 C-c C-t** (i.e., `org-todo` with a numeric prefix argument of -1.)

<sup>10</sup> with corresponding `#+STARTUP` keywords `logreschedule`, `lognotereschedule`, and `nologreschedule`

<sup>11</sup> In fact, the target state is taken from, in this sequence, the `REPEAT_TO_STATE` property or the variable `org-todo-repeat-to-state`. If neither of these is specified, the target state defaults to the first state of the TODO state sequence.

A timestamp<sup>12</sup> will be added under the deadline, to keep a record that you actually acted on the previous instance of this deadline.

As a consequence of shifting the base date, this entry will no longer be visible in the agenda when checking past dates, but all future instances will be visible.

With the ‘+1m’ cookie, the date shift will always be exactly one month. So if you have not paid the rent for three months, marking this entry DONE will still keep it as an overdue deadline. Depending on the task, this may not be the best way to handle it. For example, if you forgot to call your father for 3 weeks, it does not make sense to call him 3 times in a single day to make up for it. Finally, there are tasks like changing batteries which should always repeat a certain time *after* the last time you did it. For these tasks, Org mode has special repeaters ‘++’ and ‘.+’. For example:

```
** TODO Call Father
  DEADLINE: <2008-02-10 Sun ++1w>
  Marking this DONE will shift the date by at least one week,
  but also by as many weeks as it takes to get this date into
  the future. However, it stays on a Sunday, even if you called
  and marked it done on Saturday.
** TODO Empty kitchen trash
  DEADLINE: <2008-02-08 Fri 20:00 ++1d>
  Marking this DONE will shift the date by at least one day, and
  also by as many days as it takes to get the timestamp into the
  future. Since there is a time in the timestamp, the next
  deadline in the future will be on today's date if you
  complete the task before 20:00.
** TODO Check the batteries in the smoke detectors
  DEADLINE: <2005-11-01 Tue .+1m>
  Marking this DONE will shift the date to one month after
  today.
```

You may have both scheduling and deadline information for a specific task. If the repeater is set for the scheduling information only, you probably want the repeater to be ignored after the deadline. If so, set the variable `org-agenda-skip-scheduled-if-deadline-is-shown` to `repeated-after-deadline`. However, any scheduling information without a repeater is no longer relevant once the task is done, and thus, removed upon repeating the task. If you want both scheduling and deadline information to repeat after the same interval, set the same repeater for both timestamps.

An alternative to using a repeater is to create a number of copies of a task subtree, with dates shifted in each copy. The command `C-c C-x c` was created for this purpose, it is described in [Section 2.5 \[Structure editing\]](#), page 9.

## 8.4 Clocking work time

Org mode allows you to clock the time you spend on specific tasks in a project. When you start working on an item, you can start the clock. When you stop working on that task, or when you mark the task done, the clock is stopped and the corresponding time interval

<sup>12</sup> You can change this using the option `org-log-repeat`, or the `#+STARTUP` options `logrepeat`, `lognoterepeat`, and `nologrepeat`. With `lognoterepeat`, you will also be prompted for a note.

is recorded. It also computes the total time spent on each subtree<sup>13</sup> of a project. And it remembers a history of tasks recently clocked, so that you can jump quickly between a number of tasks absorbing your time.

To save the clock history across Emacs sessions, use

```
(setq org-clock-persist 'history)
(org-clock-persistence-insinuate)
```

When you clock into a new task after resuming Emacs, the incomplete clock<sup>14</sup> will be found (see [Section 8.4.3 \[Resolving idle time\]](#), page 85) and you will be prompted about what to do with it.

### 8.4.1 Clocking commands

**C-c C-x C-i** **org-clock-in**

Start the clock on the current item (clock-in). This inserts the **CLOCK** keyword together with a timestamp. If this is not the first clocking of this item, the multiple **CLOCK** lines will be wrapped into a **:LOGBOOK:** drawer (see also the variable **org-clock-into-drawer**). You can also overrule the setting of this variable for a subtree by setting a **CLOCK\_INTO\_DRAWER** or **LOG\_INTO\_DRAWER** property. When called with a **C-u** prefix argument, select the task from a list of recently clocked tasks. With two **C-u C-u** prefixes, clock into the task at point and mark it as the default task; the default task will then always be available with letter **d** when selecting a clocking task. With three **C-u C-u C-u** prefixes, force continuous clocking by starting the clock when the last clock stopped.

While the clock is running, the current clocking time is shown in the mode line, along with the title of the task. The clock time shown will be all time ever clocked for this task and its children. If the task has an effort estimate (see [Section 8.5 \[Effort estimates\]](#), page 86), the mode line displays the current clocking time against it<sup>15</sup> If the task is a repeating one (see [Section 8.3.2 \[Repeated tasks\]](#), page 79), only the time since the last reset of the task<sup>16</sup> will be shown. More control over what time is shown can be exercised with the **CLOCK\_MODELINE\_TOTAL** property. It may have the values **current** to show only the current clocking instance, **today** to show all time clocked on this task today (see also the variable **org-extend-today-until**), **all** to include all time, or **auto** which is the default<sup>17</sup>.

Clicking with **mouse-1** onto the mode line entry will pop up a menu with clocking options.

**C-c C-x C-o** **org-clock-out**

Stop the clock (clock-out). This inserts another timestamp at the same location where the clock was last started. It also directly computes the resulting time

<sup>13</sup> Clocking only works if all headings are indented with less than 30 stars. This is a hardcoded limitation of **lmax** in **org-clock-sum**.

<sup>14</sup> To resume the clock under the assumption that you have worked on this task while outside Emacs, use **(setq org-clock-persist t)**.

<sup>15</sup> To add an effort estimate “on the fly”, hook a function doing this to **org-clock-in-prepare-hook**.

<sup>16</sup> as recorded by the **LAST\_REPEAT** property

<sup>17</sup> See also the variable **org-clock-modeline-total**.

and inserts it after the time range as ‘=> HH:MM’. See the variable `org-log-note-clock-out` for the possibility to record an additional note together with the clock-out timestamp<sup>18</sup>.

- `C-c C-x C-x` `org-clock-in-last`  
 Reclock the last clocked task. With one `C-u` prefix argument, select the task from the clock history. With two `C-u` prefixes, force continuous clocking by starting the clock when the last clock stopped.
- `C-c C-x C-e` `org-clock-modify-effort-estimate`  
 Update the effort estimate for the current clock task.
- `C-c C-c` or `C-c C-y` `org-evaluate-time-range`  
 Recompute the time interval after changing one of the timestamps. This is only necessary if you edit the timestamps directly. If you change them with `S-cursor` keys, the update is automatic.
- `C-S-up/down` `org-clock-timestamps-up/down`  
 On `CLOCK` log lines, increase/decrease both timestamps so that the clock duration keeps the same.
- `S-M-up/down` `org-timestamp-up/down`  
 On `CLOCK` log lines, increase/decrease the timestamp at point and the one of the previous (or the next clock) timestamp by the same duration. For example, if you hit `S-M-up` to increase a clocked-out timestamp by five minutes, then the clocked-in timestamp of the next clock will be increased by five minutes.
- `C-c C-t` `org-todo`  
 Changing the TODO state of an item to DONE automatically stops the clock if it is running in this same item.
- `C-c C-x C-q` `org-clock-cancel`  
 Cancel the current clock. This is useful if a clock was started by mistake, or if you ended up working on something else.
- `C-c C-x C-j` `org-clock-goto`  
 Jump to the headline of the currently clocked in task. With a `C-u` prefix arg, select the target task from a list of recently clocked tasks.
- `C-c C-x C-d` `org-clock-display`  
 Display time summaries for each subtree in the current buffer. This puts overlays at the end of each headline, showing the total time recorded under that heading, including the time of any subheadings. You can use visibility cycling to study the tree, but the overlays disappear when you change the buffer (see variable `org-remove-highlights-with-change`) or press `C-c C-c`.

The `l` key may be used in the timeline (see [Section 10.3.4 \[Timeline\]](#), page 108) and in the agenda (see [Section 10.3.1 \[Weekly/daily agenda\]](#), page 102) to show which tasks have been worked on or closed during a day.

**Important:** note that both `org-clock-out` and `org-clock-in-last` can have a global key binding and will not modify the window disposition.

<sup>18</sup> The corresponding in-buffer setting is: `#+STARTUP: lognoteclock-out`

### 8.4.2 The clock table

Org mode can produce quite complex reports based on the time clocking information. Such a report is called a *clock table*, because it is formatted as one or several Org tables.

**C-c C-x C-r** **org-clock-report**  
 Insert a dynamic block (see [Section A.7 \[Dynamic blocks\], page 244](#)) containing a clock report as an Org mode table into the current file. When the cursor is at an existing clock table, just update it. When called with a prefix argument, jump to the first clock report in the current document and update it. The clock table always includes also trees with **:ARCHIVE:** tag.

**C-c C-c** or **C-c C-x C-u** **org-dblock-update**  
 Update dynamic block at point. The cursor needs to be in the **#+BEGIN** line of the dynamic block.

**C-u C-c C-x C-u**  
 Update all dynamic blocks (see [Section A.7 \[Dynamic blocks\], page 244](#)). This is useful if you have several clock table blocks in a buffer.

**S-left**

**S-right** **org-clocktable-try-shift**  
 Shift the current **:block** interval and update the table. The cursor needs to be in the **#+BEGIN: clocktable** line for this command. If **:block** is **today**, it will be shifted to **today-1** etc.

Here is an example of the frame for a clock table as it is inserted into the buffer with the **C-c C-x C-r** command:

```
#+BEGIN: clocktable :maxlevel 2 :emphasize nil :scope file
#+END: clocktable
```

The ‘BEGIN’ line specifies a number of options to define the scope, structure, and formatting of the report. Defaults for all these options can be configured in the variable **org-clocktable-defaults**.

First there are options that determine which clock entries are to be selected:

|                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>:maxlevel</b> | Maximum level depth to which times are listed in the table. Clocks at deeper levels will be summed into the upper level.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| <b>:scope</b>    | The scope to consider. This can be any of the following: <ul style="list-style-type: none"> <li><b>nil</b> the current buffer or narrowed region</li> <li><b>file</b> the full current buffer</li> <li><b>subtree</b> the subtree where the clocktable is located</li> <li><b>treeN</b> the surrounding level <i>N</i> tree, for example <b>tree3</b></li> <li><b>tree</b> the surrounding level 1 tree</li> <li><b>agenda</b> all agenda files</li> <li><b>("file"..)</b> scan these files</li> <li><b>file-with-archives</b> current file and its archives</li> <li><b>agenda-with-archives</b> all agenda files, including archives</li> </ul> |
| <b>:block</b>    | The time block to consider. This block is specified either absolutely, or relative to the current time and may be any of these formats:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |

|            |                                                                                                                                                                                                                     |                     |
|------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------|
|            | 2007-12-31                                                                                                                                                                                                          | New year eve 2007   |
|            | 2007-12                                                                                                                                                                                                             | December 2007       |
|            | 2007-W50                                                                                                                                                                                                            | ISO-week 50 in 2007 |
|            | 2007-Q2                                                                                                                                                                                                             | 2nd quarter in 2007 |
|            | 2007                                                                                                                                                                                                                | the year 2007       |
|            | today, yesterday, today- <i>N</i>                                                                                                                                                                                   | a relative day      |
|            | thisweek, lastweek, thisweek- <i>N</i>                                                                                                                                                                              | a relative week     |
|            | thismonth, lastmonth, thismonth- <i>N</i>                                                                                                                                                                           | a relative month    |
|            | thisyear, lastyear, thisyear- <i>N</i>                                                                                                                                                                              | a relative year     |
|            | untilnow                                                                                                                                                                                                            |                     |
|            | Use <i>S-left/right</i> keys to shift the time interval.                                                                                                                                                            |                     |
| :tstart    | A time string specifying when to start considering times.<br>Relative times like "<-2w>" can also be used. See<br><a href="#">Section 10.3.3 [Matching tags and properties], page 105</a> for relative time syntax. |                     |
| :tend      | A time string specifying when to stop considering times.<br>Relative times like "<now>" can also be used. See<br><a href="#">Section 10.3.3 [Matching tags and properties], page 105</a> for relative time syntax.  |                     |
| :wstart    | The starting day of the week. The default is 1 for monday.                                                                                                                                                          |                     |
| :mstart    | The starting day of the month. The default 1 is for the first<br>day of the month.                                                                                                                                  |                     |
| :step      | week or day, to split the table into chunks.<br>To use this, :block or :tstart, :tend are needed.                                                                                                                   |                     |
| :stepskip0 | Do not show steps that have zero time.                                                                                                                                                                              |                     |
| :fileskip0 | Do not show table sections from files which did not contribute.                                                                                                                                                     |                     |
| :tags      | A tags match to select entries that should contribute. See<br><a href="#">Section 10.3.3 [Matching tags and properties], page 105</a> for the match syntax.                                                         |                     |

Then there are options which determine the formatting of the table. These options are interpreted by the function `org-clocktable-write-default`, but you can specify your own function using the `:formatter` parameter.

|            |                                                                                                                                                              |
|------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|
| :emphasize | When t, emphasize level one and level two items.                                                                                                             |
| :lang      | Language <sup>19</sup> to use for descriptive cells like "Task".                                                                                             |
| :link      | Link the item headlines in the table to their origins.                                                                                                       |
| :narrow    | An integer to limit the width of the headline column in<br>the org table. If you write it like '50!', then the<br>headline will also be shortened in export. |
| :indent    | Indent each headline field according to its level.                                                                                                           |
| :tcolumns  | Number of columns to be used for times. If this is smaller<br>than :maxlevel, lower levels will be lumped into one column.                                   |
| :level     | Should a level number column be included?                                                                                                                    |
| :sort      | A cons cell like containing the column to sort and a sorting type.<br>E.g., :sort (1 . ?a) sorts the first column alphabetically.                            |
| :compact   | Abbreviation for :level nil :indent t :narrow 40! :tcolumns 1<br>All are overwritten except if there is an explicit :narrow                                  |
| :timestamp | A timestamp for the entry, when available. Look for SCHEDULED,<br>DEADLINE, TIMESTAMP and TIMESTAMP_IA, in this order.                                       |

<sup>19</sup> Language terms can be set through the variable `org-clock-clocktable-language-setup`.

**:properties** List of properties that should be shown in the table. Each property will get its own column.

**:inherit-props** When this flag is **t**, the values for **:properties** will be inherited.

**:formula** Content of a **#+TBLFM** line to be added and evaluated. As a special case, **:formula %** adds a column with % time. If you do not specify a formula here, any existing formula below the clock table will survive updates and be evaluated.

**:formatter** A function to format clock data and insert it into the buffer.

To get a clock summary of the current level 1 tree, for the current day, you could write

```
#+BEGIN: clocktable :maxlevel 2 :block today :scope tree1 :link t
#+END: clocktable
```

and to use a specific time range you could write<sup>20</sup>

```
#+BEGIN: clocktable :tstart "<2006-08-10 Thu 10:00>"
                        :tend "<2006-08-10 Thu 12:00>"
#+END: clocktable
```

A range starting a week ago and ending right now could be written as

```
#+BEGIN: clocktable :tstart "<-1w>" :tend "<now>"
#+END: clocktable
```

A summary of the current subtree with % times would be

```
#+BEGIN: clocktable :scope subtree :link t :formula %
#+END: clocktable
```

A horizontally compact representation of everything clocked during last week would be

```
#+BEGIN: clocktable :scope agenda :block lastweek :compact t
#+END: clocktable
```

### 8.4.3 Resolving idle time and continuous clocking

#### Resolving idle time

If you clock in on a work item, and then walk away from your computer—perhaps to take a phone call—you often need to “resolve” the time you were away by either subtracting it from the current clock, or applying it to another one.

By customizing the variable **org-clock-idle-time** to some integer, such as 10 or 15, Emacs can alert you when you get back to your computer after being idle for that many minutes<sup>21</sup>, and ask what you want to do with the idle time. There will be a question waiting for you when you get back, indicating how much idle time has passed (constantly updated with the current amount), as well as a set of choices to correct the discrepancy:

<sup>20</sup> Note that all parameters must be specified in a single line—the line is broken here only to fit it into the manual.

<sup>21</sup> On computers using Mac OS X, idleness is based on actual user idleness, not just Emacs’ idle time. For X11, you can install a utility program **x11idle.c**, available in the **contrib/scripts** directory of the Org git distribution, or install the **xprintidle** package and set it to the variable **org-clock-x11idle-program-name** if you are running Debian, to get the same general treatment of idleness. On other systems, idle time refers to Emacs idle time only.



|          |                                                                                                                                                                                                                                                         |
|----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>k</i> | To keep some or all of the minutes and stay clocked in, press <i>k</i> . Org will ask how many of the minutes to keep. Press RET to keep them all, effectively changing nothing, or enter a number to keep that many minutes.                           |
| <i>K</i> | If you use the shift key and press <i>K</i> , it will keep however many minutes you request and then immediately clock out of that task. If you keep all of the minutes, this is the same as just clocking out of the current task.                     |
| <i>s</i> | To keep none of the minutes, use <i>s</i> to subtract all the away time from the clock, and then check back in from the moment you returned.                                                                                                            |
| <i>S</i> | To keep none of the minutes and just clock out at the start of the away time, use the shift key and press <i>S</i> . Remember that using shift will always leave you clocked out, no matter which option you choose.                                    |
| <i>C</i> | To cancel the clock altogether, use <i>C</i> . Note that if instead of canceling you subtract the away time, and the resulting clock amount is less than a minute, the clock will still be canceled rather than clutter up the log with an empty entry. |

What if you subtracted those away minutes from the current clock, and now want to apply them to a new clock? Simply clock in to any task immediately after the subtraction. Org will notice that you have subtracted time “on the books”, so to speak, and will ask if you want to apply those minutes to the next task you clock in on.

There is one other instance when this clock resolution magic occurs. Say you were clocked in and hacking away, and suddenly your cat chased a mouse who scared a hamster that crashed into your UPS’s power button! You suddenly lose all your buffers, but thanks to auto-save you still have your recent Org mode changes, including your last clock in.

If you restart Emacs and clock into any task, Org will notice that you have a dangling clock which was never clocked out from your last session. Using that clock’s starting time as the beginning of the unaccounted-for period, Org will ask how you want to resolve that time. The logic and behavior is identical to dealing with away time due to idleness; it is just happening due to a recovery event rather than a set amount of idle time.

You can also check all the files visited by your Org agenda for dangling clocks at any time using *M-x org-resolve-clocks RET* (or *C-c C-x C-z*).

## Continuous clocking

You may want to start clocking from the time when you clocked out the previous task. To enable this systematically, set `org-clock-continuously` to `t`. Each time you clock in, Org retrieves the clock-out time of the last clocked entry for this session, and start the new clock from there.

If you only want this from time to time, use three universal prefix arguments with `org-clock-in` and two *C-u C-u* with `org-clock-in-last`.

## 8.5 Effort estimates

If you want to plan your work in a very detailed way, or if you need to produce offers with quotations of the estimated work effort, you may want to assign effort estimates to entries. If you are also clocking your work, you may later want to compare the planned effort with

the actual working time, a great way to improve planning estimates. Effort estimates are stored in a special property `EFFORT`. You can set the effort for an entry with the following commands:

`C-c C-x e` `org-set-effort`  
 Set the effort estimate for the current entry. With a numeric prefix argument, set it to the Nth allowed value (see below). This command is also accessible from the agenda with the `e` key.

`C-c C-x C-e` `org-clock-modify-effort-estimate`  
 Modify the effort estimate of the item currently being clocked.

Clearly the best way to work with effort estimates is through column view (see [Section 7.5 \[Column view\]](#), page 67). You should start by setting up discrete values for effort estimates, and a `COLUMNS` format that displays these values together with clock sums (if you want to clock your time). For a specific buffer you can use

```
#+PROPERTY: Effort_ALL 0 0:10 0:30 1:00 2:00 3:00 4:00 5:00 6:00 7:00
#+COLUMNS: %40ITEM(Task) %17Effort(Estimated Effort){:} %CLOCKSUM
```

or, even better, you can set up these values globally by customizing the variables `org-global-properties` and `org-columns-default-format`. In particular if you want to use this setup also in the agenda, a global setup may be advised.

The way to assign estimates to individual items is then to switch to column mode, and to use `S-right` and `S-left` to change the value. The values you enter will immediately be summed up in the hierarchy. In the column next to it, any clocked time will be displayed.

If you switch to column view in the daily/weekly agenda, the effort column will summarize the estimated work effort for each day<sup>22</sup>, and you can use this to find space in your schedule. To get an overview of the entire part of the day that is committed, you can set the option `org-agenda-columns-add-appointments-to-effort-sum`. The appointments on a day that take place over a specified time interval will then also be added to the load estimate of the day.

Effort estimates can be used in secondary agenda filtering that is triggered with the `/` key in the agenda (see [Section 10.5 \[Agenda commands\]](#), page 113). If you have these estimates defined consistently, two or three key presses will narrow down the list to stuff that fits into an available time slot.

## 8.6 Taking notes with a timer

Org provides two types of timers. There is a relative timer that counts up, which can be useful when taking notes during, for example, a meeting or a video viewing. There is also a countdown timer.

The relative and countdown are started with separate commands.

`C-c C-x 0` `org-timer-start`  
 Start or reset the relative timer. By default, the timer is set to 0. When called with a `C-u` prefix, prompt the user for a starting offset. If there is a timer string at point, this is taken as the default, providing a convenient way

<sup>22</sup> Please note the pitfalls of summing hierarchical data in a flat list (see [Section 10.8 \[Agenda column view\]](#), page 126).

to restart taking notes after a break in the process. When called with a double prefix argument *C-u C-u*, change all timer strings in the active region by a certain amount. This can be used to fix timer strings if the timer was not started at exactly the right moment.

*C-c C-x ;* **org-timer-set-timer**  
 Start a countdown timer. The user is prompted for a duration. **org-timer-default-timer** sets the default countdown value. Giving a numeric prefix argument overrides this default value. This command is available as *; in agenda buffers*.

Once started, relative and countdown timers are controlled with the same commands.

*C-c C-x .* **org-timer**  
 Insert the value of the current relative or countdown timer into the buffer. If no timer is running, the relative timer will be started. When called with a prefix argument, the relative timer is restarted.

*C-c C-x -* **org-timer-item**  
 Insert a description list item with the value of the current relative or countdown timer. With a prefix argument, first reset the relative timer to 0.

*M-RET* **org-insert-heading**  
 Once the timer list is started, you can also use *M-RET* to insert new timer items.

*C-c C-x ,* **org-timer-pause-or-continue**  
 Pause the timer, or continue it if it is already paused.

*C-c C-x \_* **org-timer-stop**  
 Stop the timer. After this, you can only start a new timer, not continue the old one. This command also removes the timer from the mode line.

## 9 Capture - Refile - Archive

An important part of any organization system is the ability to quickly capture new ideas and tasks, and to associate reference material with them. Org does this using a process called *capture*. It also can store files related to a task (*attachments*) in a special directory. Once in the system, tasks and projects need to be moved around. Moving completed project trees to an archive file keeps the system compact and fast.

### 9.1 Capture

Capture lets you quickly store notes with little interruption of your work flow. Org's method for capturing new items is heavily inspired by John Wiegley excellent `remember.el` package. Up to version 6.36, Org used a special setup for `remember.el`, then replaced it with `org-remember.el`. As of version 8.0, `org-remember.el` has been completely replaced by `org-capture.el`.

If your configuration depends on `org-remember.el`, you need to update it and use the setup described below. To convert your `org-remember-templates`, run the command

```
M-x org-capture-import-remember-templates RET
```

and then customize the new variable with `M-x customize-variable org-capture-templates`, check the result, and save the customization.

#### 9.1.1 Setting up capture

The following customization sets a default target file for notes, and defines a global key<sup>1</sup> for capturing new material.

```
(setq org-default-notes-file (concat org-directory "/notes.org"))
(define-key global-map "\C-c" 'org-capture)
```

#### 9.1.2 Using capture

`C-c c` `org-capture`

Call the command `org-capture`. Note that this key binding is global and not active by default: you need to install it. If you have templates defined see [Section 9.1.3 \[Capture templates\]](#), [page 90](#), it will offer these templates for selection or use a new Org outline node as the default template. It will insert the template into the target file and switch to an indirect buffer narrowed to this new node. You may then insert the information you want.

`C-c C-c` `org-capture-finalize`

Once you have finished entering information into the capture buffer, `C-c C-c` will return you to the window configuration before the capture process, so that you can resume your work without further distraction. When called with a prefix arg, finalize and then jump to the captured item.

`C-c C-w` `org-capture-refile`

Finalize the capture process by refileing (see [Section 9.5 \[Refile and copy\]](#), [page 97](#)) the note to a different place. Please realize that this is a normal

---

<sup>1</sup> Please select your own key, `C-c c` is only a suggestion.

refiling command that will be executed—so the cursor position at the moment you run this command is important. If you have inserted a tree with a parent and children, first move the cursor back to the parent. Any prefix argument given to this command will be passed on to the `org-refile` command.

**C-c C-k** **org-capture-kill**

Abort the capture process and return to the previous state.

You can also call `org-capture` in a special way from the agenda, using the `k c` key combination. With this access, any timestamps inserted by the selected capture template will default to the cursor date in the agenda, rather than to the current date.

To find the locations of the last stored capture, use `org-capture` with prefix commands:

**C-u C-c c**

Visit the target location of a capture template. You get to select the template in the usual way.

**C-u C-u C-c c**

Visit the last stored capture item in its buffer.

You can also jump to the bookmark `org-capture-last-stored`, which will automatically be created unless you set `org-capture-bookmark` to `nil`.

To insert the capture at point in an Org buffer, call `org-capture` with a `C-0` prefix argument.

### 9.1.3 Capture templates

You can use templates for different types of capture items, and for different target locations. The easiest way to create such templates is through the customize interface.

**C-c c C** Customize the variable `org-capture-templates`.

Before we give the formal description of template definitions, let's look at an example. Say you would like to use one template to create general TODO entries, and you want to put these entries under the heading 'Tasks' in your file `~/org/gtd.org`. Also, a date tree in the file `journal.org` should capture journal entries. A possible configuration would look like:

```
(setq org-capture-templates
  '(("t" "Todo" entry (file+headline "~/org/gtd.org" "Tasks")
    "* TODO %?\n %i\n %a")
    ("j" "Journal" entry (file+datetree "~/org/journal.org")
    "* %?\nEntered on %U\n %i\n %a")))
```

If you then press **C-c c t**, Org will prepare the template for you like this:

```
* TODO
[[file:link to where you initiated capture]]
```

During expansion of the template, `%a` has been replaced by a link to the location from where you called the capture command. This can be extremely useful for deriving tasks from emails, for example. You fill in the task definition, press **C-c C-c** and Org returns you to the same place where you started the capture process.

To define special keys to capture to a particular template without going through the interactive template selection, you can create your key binding like this:

```
(define-key global-map "\C-cx"
  (lambda () (interactive) (org-capture nil "x")))
```

### 9.1.3.1 Template elements

Now let's look at the elements of a template definition. Each entry in `org-capture-templates` is a list with the following items:

*keys*        The keys that will select the template, as a string, characters only, for example "a" for a template to be selected with a single key, or "bt" for selection with two keys. When using several keys, keys using the same prefix key must be sequential in the list and preceded by a 2-element entry explaining the prefix key, for example

```
("b" "Templates for marking stuff to buy")
```

If you do not define a template for the `C` key, this key will be used to open the customize buffer for this complex variable.

*description*

A short string describing the template, which will be shown during selection.

*type*

The type of entry, a symbol. Valid values are:

*entry*        An Org mode node, with a headline. Will be filed as the child of the target entry or as a top-level entry. The target file should be an Org mode file.

*item*         A plain list item, placed in the first plain list at the target location. Again the target file should be an Org file.

*checkitem*    A checkbox item. This only differs from the plain list item by the default template.

*table-line*    a new line in the first table at the target location. Where exactly the line will be inserted depends on the properties `:prepend` and `:table-line-pos` (see below).

*plain*        Text to be inserted as it is.

*target*       Specification of where the captured item should be placed. In Org mode files, targets usually define a node. Entries will become children of this node. Other types will be added to the table or list in the body of this node. Most target specifications contain a file name. If that file name is the empty string, it defaults to `org-default-notes-file`. A file can also be given as a variable, function, or Emacs Lisp form. When an absolute path is not specified for a target, it is taken as relative to `org-directory`.

Valid values are:

```
(file "path/to/file")
```

Text will be placed at the beginning or end of that file.

```
(id "id of existing org entry")
```

Filing as child of this entry, or in the body of the entry.

|                   |                                                                                                                                                                                                                                                                                                                                                                                                      |                                                                                                                                                                         |
|-------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                   | <code>(file+headline "path/to/file" "node headline")</code>                                                                                                                                                                                                                                                                                                                                          | Fast configuration if the target heading is unique in the file.                                                                                                         |
|                   | <code>(file+olp "path/to/file" "Level 1 heading" "Level 2" ...)</code>                                                                                                                                                                                                                                                                                                                               | For non-unique headings, the full path is safer.                                                                                                                        |
|                   | <code>(file+regexp "path/to/file" "regexp to find location")</code>                                                                                                                                                                                                                                                                                                                                  | Use a regular expression to position the cursor.                                                                                                                        |
|                   | <code>(file+datetree "path/to/file")</code>                                                                                                                                                                                                                                                                                                                                                          | Will create a heading in a date tree for today's date <sup>2</sup> .                                                                                                    |
|                   | <code>(file+datetree+prompt "path/to/file")</code>                                                                                                                                                                                                                                                                                                                                                   | Will create a heading in a date tree, but will prompt for the date.                                                                                                     |
|                   | <code>(file+weektree "path/to/file")</code>                                                                                                                                                                                                                                                                                                                                                          | Will create a heading in a week tree for today's date. Week trees are sorted by week and not by month unlike datetrees.                                                 |
|                   | <code>(file+weektree+prompt "path/to/file")</code>                                                                                                                                                                                                                                                                                                                                                   | Will create a heading in a week tree, but will prompt for the date.                                                                                                     |
|                   | <code>(file+function "path/to/file" function-finding-location)</code>                                                                                                                                                                                                                                                                                                                                | A function to find the right location in the file.                                                                                                                      |
|                   | <code>(clock)</code>                                                                                                                                                                                                                                                                                                                                                                                 | File to the entry that is currently being clocked.                                                                                                                      |
|                   | <code>(function function-finding-location)</code>                                                                                                                                                                                                                                                                                                                                                    | Most general way: write your own function which both visits the file and moves point to the right location.                                                             |
| <i>template</i>   | The template for creating the capture item. If you leave this empty, an appropriate default template will be used. Otherwise this is a string with escape codes, which will be replaced depending on time and context of the capture call. The string with escapes may be loaded from a template file, using the special syntax <code>(file "path/to/template")</code> . See below for more details. |                                                                                                                                                                         |
| <i>properties</i> | The rest of the entry is a property list of additional options. Recognized properties are:                                                                                                                                                                                                                                                                                                           |                                                                                                                                                                         |
|                   | <code>:prepend</code>                                                                                                                                                                                                                                                                                                                                                                                | Normally new captured information will be appended at the target location (last child, last table line, last list item...). Setting this property will change that.     |
|                   | <code>:immediate-finish</code>                                                                                                                                                                                                                                                                                                                                                                       | When set, do not offer to edit the information, just file it away immediately. This makes sense if the template only needs information that can be added automatically. |
|                   | <code>:empty-lines</code>                                                                                                                                                                                                                                                                                                                                                                            | Set this to the number of lines to insert before and after the new item. Default 0, only common other value is 1.                                                       |

---

<sup>2</sup> Datetree headlines for years accept tags, so if you use both `* 2013 :noexport:` and `* 2013` in your file, the capture will refile the note to the first one matched.

|                              |                                                                                                                                                                                                                                                                                                            |
|------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>:clock-in</code>       | Start the clock in this item.                                                                                                                                                                                                                                                                              |
| <code>:clock-keep</code>     | Keep the clock running when filing the captured entry.                                                                                                                                                                                                                                                     |
| <code>:clock-resume</code>   | If starting the capture interrupted a clock, restart that clock when finished with the capture. Note that <code>:clock-keep</code> has precedence over <code>:clock-resume</code> . When setting both to <code>t</code> , the current clock will run and the previous one will not be resumed.             |
| <code>:unnarrowed</code>     | Do not narrow the target buffer, simply show the full buffer. Default is to narrow it so that you only see the new material.                                                                                                                                                                               |
| <code>:table-line-pos</code> | Specification of the location in the table where the new line should be inserted. It can be a string, a variable holding a string or a function returning a string. The string should look like "II-3" meaning that the new line should become the third line before the second horizontal separator line. |
| <code>:kill-buffer</code>    | If the target file was not yet visited when capture was invoked, kill the buffer again after capture is completed.                                                                                                                                                                                         |

### 9.1.3.2 Template expansion

In the template itself, special %-escapes<sup>3</sup> allow dynamic insertion of content. The templates are expanded in the order given here:

|                           |                                                                                                                                                                                                                         |
|---------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>%[file]</code>      | Insert the contents of the file given by <i>file</i> .                                                                                                                                                                  |
| <code>%(sexp)</code>      | Evaluate Elisp <i>sexp</i> and replace with the result.<br>For convenience, <code>%:keyword</code> (see below) placeholders within the expression will be expanded prior to this. The <i>sexp</i> must return a string. |
| <code>%&lt;...&gt;</code> | The result of format-time-string on the ... format specification.                                                                                                                                                       |
| <code>%t</code>           | Timestamp, date only.                                                                                                                                                                                                   |
| <code>%T</code>           | Timestamp, with date and time.                                                                                                                                                                                          |
| <code>%u, %U</code>       | Like the above, but inactive timestamps.                                                                                                                                                                                |
| <code>%i</code>           | Initial content, the region when capture is called while the region is active.<br>The entire text will be indented like <code>%i</code> itself.                                                                         |
| <code>%a</code>           | Annotation, normally the link created with <code>org-store-link</code> .                                                                                                                                                |
| <code>%A</code>           | Like <code>%a</code> , but prompt for the description part.                                                                                                                                                             |
| <code>%l</code>           | Like <code>%a</code> , but only insert the literal link.                                                                                                                                                                |
| <code>%c</code>           | Current kill ring head.                                                                                                                                                                                                 |
| <code>%x</code>           | Content of the X clipboard.                                                                                                                                                                                             |
| <code>%k</code>           | Title of the currently clocked task.                                                                                                                                                                                    |
| <code>%K</code>           | Link to the currently clocked task.                                                                                                                                                                                     |
| <code>%n</code>           | User name (taken from <code>user-full-name</code> ).                                                                                                                                                                    |
| <code>%f</code>           | File visited by current buffer when org-capture was called.                                                                                                                                                             |
| <code>%F</code>           | Full path of the file or directory visited by current buffer.                                                                                                                                                           |

<sup>3</sup> If you need one of these sequences literally, escape the % with a backslash.



|                          |                                                                                                                                                                                                                                                    |
|--------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>%.keyword</code>   | Specific information for certain link types, see below.                                                                                                                                                                                            |
| <code>%^g</code>         | Prompt for tags, with completion on tags in target file.                                                                                                                                                                                           |
| <code>%^G</code>         | Prompt for tags, with completion all tags in all agenda files.                                                                                                                                                                                     |
| <code>%^t</code>         | Like <code>%t</code> , but prompt for date. Similarly <code>%^T</code> , <code>%^u</code> , <code>%^U</code> .<br>You may define a prompt like <code>%^{Birthday}t</code> .                                                                        |
| <code>%^C</code>         | Interactive selection of which kill or clip to use.                                                                                                                                                                                                |
| <code>%^L</code>         | Like <code>%^C</code> , but insert as link.                                                                                                                                                                                                        |
| <code>%^{prop}p</code>   | Prompt the user for a value for property <i>prop</i> .                                                                                                                                                                                             |
| <code>%^{prompt}</code>  | prompt the user for a string and replace this sequence with it.<br>You may specify a default value and a completion table with<br><code>%^{prompt default completion2 completion3...}</code> .<br>The arrow keys access a prompt-specific history. |
| <code>%\1 ... %\N</code> | Insert the text entered at the Nth <code>%^{prompt}</code> , where N is<br>a number, starting from 1.                                                                                                                                              |
| <code>%?</code>          | After completing the template, position cursor here.                                                                                                                                                                                               |

For specific link types, the following keywords will be defined<sup>4</sup>:

| Link type                        | Available keywords                                                                                                                                                                                                                                                                                                               |
|----------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| bbdb                             | <code>%.name</code> <code>%.company</code>                                                                                                                                                                                                                                                                                       |
| irc                              | <code>%.server</code> <code>%.port</code> <code>%.nick</code>                                                                                                                                                                                                                                                                    |
| vm, vm-imap, wl, mh, mew, rmail, | <code>%.type</code> <code>%.subject</code> <code>%.message-id</code>                                                                                                                                                                                                                                                             |
| gnus, notmuch                    | <code>%.from</code> <code>%.fromname</code> <code>%.fromaddress</code><br><code>%.to</code> <code>%.toname</code> <code>%.toaddress</code><br><code>%.date</code> (message date header field)<br><code>%.date-timestamp</code> (date as active timestamp)<br><code>%.date-timestamp-inactive</code> (date as inactive timestamp) |
| gnus                             | <code>%.fromto</code> (either "to NAME" or "from NAME") <sup>5</sup>                                                                                                                                                                                                                                                             |
| eww, w3, w3m                     | <code>%.group</code> , for messages also all email fields                                                                                                                                                                                                                                                                        |
| info                             | <code>%.url</code>                                                                                                                                                                                                                                                                                                               |
| calendar                         | <code>%.file</code> <code>%.node</code><br><code>%.date</code>                                                                                                                                                                                                                                                                   |

To place the cursor after template expansion use:

`%?` After completing the template, position cursor here.

### 9.1.3.3 Templates in contexts

To control whether a capture template should be accessible from a specific context, you can customize `org-capture-templates-contexts`. Let's say for example that you have a capture template "p" for storing Gnus emails containing patches. Then you would configure this option like this:

```
(setq org-capture-templates-contexts
      '(("p" (in-mode . "message-mode"))))
```

You can also tell that the command key "p" should refer to another template. In that case, add this command key like this:

```
(setq org-capture-templates-contexts
      '(("p" "q" (in-mode . "message-mode"))))
```

See the docstring of the variable for more information.

<sup>4</sup> If you define your own link types (see [Section A.3 \[Adding hyperlink types\]](#), page 237), any property you store with `org-store-link-props` can be accessed in capture templates in a similar way.

<sup>5</sup> This will always be the other, not the user. See the variable `org-from-is-user-regexp`.

## 9.2 Attachments

It is often useful to associate reference material with an outline node/task. Small chunks of plain text can simply be stored in the subtree of a project. Hyperlinks (see [Chapter 4 \[Hyperlinks\]](#), [page 38](#)) can establish associations with files that live elsewhere on your computer or in the cloud, like emails or source code files belonging to a project. Another method is *attachments*, which are files located in a directory belonging to an outline node. Org uses directories named by the unique ID of each entry. These directories are located in the `data` directory which lives in the same directory where your Org file lives<sup>6</sup>. If you initialize this directory with `git init`, Org will automatically commit changes when it sees them. The attachment system has been contributed to Org by John Wiegley.

In cases where it seems better to do so, you can also attach a directory of your choice to an entry. You can also make children inherit the attachment directory from a parent, so that an entire subtree uses the same attached directory.

The following commands deal with attachments:

|                      |                                                                                                                                                                                                                                                                                                         |
|----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>C-c C-a</code> | <code>org-attach</code>                                                                                                                                                                                                                                                                                 |
|                      | The dispatcher for commands related to the attachment system. After these keys, a list of commands is displayed and you must press an additional key to select a command:                                                                                                                               |
| <code>a</code>       | <code>org-attach-attach</code>                                                                                                                                                                                                                                                                          |
|                      | Select a file and move it into the task's attachment directory. The file will be copied, moved, or linked, depending on <code>org-attach-method</code> . Note that hard links are not supported on all systems.                                                                                         |
| <code>c/m/l</code>   | Attach a file using the copy/move/link method. Note that hard links are not supported on all systems.                                                                                                                                                                                                   |
| <code>n</code>       | <code>org-attach-new</code>                                                                                                                                                                                                                                                                             |
|                      | Create a new attachment as an Emacs buffer.                                                                                                                                                                                                                                                             |
| <code>z</code>       | <code>org-attach-sync</code>                                                                                                                                                                                                                                                                            |
|                      | Synchronize the current task with its attachment directory, in case you added attachments yourself.                                                                                                                                                                                                     |
| <code>o</code>       | <code>org-attach-open</code>                                                                                                                                                                                                                                                                            |
|                      | Open current task's attachment. If there is more than one, prompt for a file name first. Opening will follow the rules set by <code>org-file-apps</code> . For more details, see the information on following hyperlinks (see <a href="#">Section 4.4 [Handling links]</a> , <a href="#">page 41</a> ). |
| <code>O</code>       | <code>org-attach-open-in-emacs</code>                                                                                                                                                                                                                                                                   |
|                      | Also open the attachment, but force opening the file in Emacs.                                                                                                                                                                                                                                          |
| <code>f</code>       | <code>org-attach-reveal</code>                                                                                                                                                                                                                                                                          |
|                      | Open the current task's attachment directory.                                                                                                                                                                                                                                                           |
| <code>F</code>       | <code>org-attach-reveal-in-emacs</code>                                                                                                                                                                                                                                                                 |
|                      | Also open the directory, but force using <code>dired</code> in Emacs.                                                                                                                                                                                                                                   |

---

<sup>6</sup> If you move entries or Org files from one directory to another, you may want to configure `org-attach-directory` to contain an absolute path.

|          |                                                                                                                                                                                |
|----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>d</i> | <b>org-attach-delete-one</b><br>Select and delete a single attachment.                                                                                                         |
| <i>D</i> | <b>org-attach-delete-all</b><br>Delete all of a task's attachments. A safer way is to open the directory in <b>dired</b> and delete from there.                                |
| <i>s</i> | <b>org-attach-set-directory</b><br>Set a specific directory as the entry's attachment directory. This works by putting the directory path into the <b>ATTACH_DIR</b> property. |
| <i>i</i> | <b>org-attach-set-inherit</b><br>Set the <b>ATTACH_DIR_INHERIT</b> property, so that children will use the same directory for attachments as the parent does.                  |

### 9.3 RSS feeds

Org can add and change entries based on information found in RSS feeds and Atom feeds. You could use this to make a task out of each new podcast in a podcast feed. Or you could use a phone-based note-creating service on the web to import tasks into Org. To access feeds, configure the variable **org-feed-alist**. The docstring of this variable has detailed information. Here is just an example:

```
(setq org-feed-alist
  '(("Slashdot"
    "http://rss.slashdot.org/Slashdot/slashdot"
    "~/txt/org/feeds.org" "Slashdot Entries")))
```

will configure that new items from the feed provided by **rss.slashdot.org** will result in new entries in the file **~/org/feeds.org** under the heading 'Slashdot Entries', whenever the following command is used:

**C-c C-x g** **org-feed-update-all**  
**C-c C-x g** Collect items from the feeds configured in **org-feed-alist** and act upon them.

**C-c C-x G** **org-feed-goto-inbox**  
 Prompt for a feed name and go to the inbox configured for this feed.

Under the same headline, Org will create a drawer 'FEEDSTATUS' in which it will store information about the status of items in the feed, to avoid adding the same item several times.

For more information, including how to read atom feeds, see **org-feed.el** and the docstring of **org-feed-alist**.

### 9.4 Protocols for external access

You can set up Org for handling protocol calls from outside applications that are passed to Emacs through the **emacsserver**. For example, you can configure bookmarks in your web browser to send a link to the current page to Org and create a note from it using capture (see [Section 9.1 \[Capture\]](#), page 89). Or you could create a bookmark that will tell Emacs to open the local source file of a remote website you are looking at with the browser. See <http://orgmode.org/worg/org-contrib/org-protocol.php> for detailed documentation and setup instructions.

## 9.5 Refile and copy

When reviewing the captured data, you may want to refile or to copy some of the entries into a different list, for example into a project. Cutting, finding the right location, and then pasting the note is cumbersome. To simplify this process, you can use the following special command:

**C-c M-w** **org-copy**  
 Copying works like refiling, except that the original note is not deleted.

**C-c C-w** **org-refile**  
 Refile the entry or region at point. This command offers possible locations for refiling the entry and lets you select one with completion. The item (or all items in the region) is filed below the target heading as a subitem. Depending on **org-reverse-note-order**, it will be either the first or last subitem. By default, all level 1 headlines in the current buffer are considered to be targets, but you can have more complex definitions across a number of files. See the variable **org-refile-targets** for details. If you would like to select a location via a file-path-like completion along the outline path, see the variables **org-refile-use-outline-path** and **org-outline-path-complete-in-steps**. If you would like to be able to create new nodes as new parents for refiling on the fly, check the variable **org-refile-allow-creating-parent-nodes**. When the variable **org-log-refile**<sup>7</sup> is set, a timestamp or a note will be recorded when an entry has been refiled.

**C-u C-c C-w**  
 Use the refile interface to jump to a heading.

**C-u C-u C-c C-w** **org-refile-goto-last-stored**  
 Jump to the location where **org-refile** last moved a tree to.

**C-2 C-c C-w**  
 Refile as the child of the item currently being clocked.

**C-3 C-c C-w**  
 Refile and keep the entry in place. Also see **org-refile-keep** to make this the default behavior, and beware that this may result in duplicated ID properties.

**C-0 C-c C-w** or **C-u C-u C-u C-c C-w** **org-refile-cache-clear**  
 Clear the target cache. Caching of refile targets can be turned on by setting **org-refile-use-cache**. To make the command see new possible targets, you have to clear the cache with this command.

## 9.6 Archiving

When a project represented by a (sub)tree is finished, you may want to move the tree out of the way and to stop it from contributing to the agenda. Archiving is important to keep your working files compact and global searches like the construction of agenda views fast.

**C-c C-x C-a** **org-archive-subtree-default**  
 Archive the current entry using the command specified in the variable **org-archive-default-command**.

<sup>7</sup> with corresponding **#+STARTUP** keywords **logrefile**, **lognoterefile**, and **nologrefile**

### 9.6.1 Moving a tree to the archive file

The most common archiving action is to move a project tree to another file, the archive file.

`C-c C-x C-s` or short `C-c $` `org-archive-subtree`  
 Archive the subtree starting at the cursor position to the location given by `org-archive-location`.

`C-u C-c C-x C-s`  
 Check if any direct children of the current headline could be moved to the archive. To do this, each subtree is checked for open TODO entries. If none are found, the command offers to move it to the archive location. If the cursor is *not* on a headline when this command is invoked, the level 1 trees will be checked.

`C-u C-u C-c C-x C-s`  
 As above, but check subtree for timestamps instead of TODO entries. The command will offer to archive the subtree if it *does* contain a timestamp, and that timestamp is in the past.

The default archive location is a file in the same directory as the current file, with the name derived by appending `_archive` to the current file name. You can also choose what heading to file archived items under, with the possibility to add them to a datetree in a file. For information and examples on how to specify the file and the heading, see the documentation string of the variable `org-archive-location`.

There is also an in-buffer option for setting this variable, for example:

```
#+ARCHIVE: %s_done::
```

If you would like to have a special ARCHIVE location for a single entry or a (sub)tree, give the entry an `:ARCHIVE:` property with the location as the value (see [Chapter 7 \[Properties and columns\]](#), page 64).

When a subtree is moved, it receives a number of special properties that record context information like the file from where the entry came, its outline path the archiving time etc. Configure the variable `org-archive-save-context-info` to adjust the amount of information added.

### 9.6.2 Internal archiving

If you want to just switch off (for agenda views) certain subtrees without moving them to a different file, you can use the **ARCHIVE** tag.

A headline that is marked with the ARCHIVE tag (see [Chapter 6 \[Tags\]](#), page 59) stays at its location in the outline tree, but behaves in the following way:

- It does not open when you attempt to do so with a visibility cycling command (see [Section 2.3 \[Visibility cycling\]](#), page 6). You can force cycling archived subtrees with `C-TAB`, or by setting the option `org-cycle-open-archived-trees`. Also normal outline commands like `show-all` will open archived subtrees.
- During sparse tree construction (see [Section 2.6 \[Sparse trees\]](#), page 11), matches in archived subtrees are not exposed, unless you configure the option `org-sparse-tree-open-archived-trees`.

- During agenda view construction (see [Chapter 10 \[Agenda views\]](#), page 100), the content of archived trees is ignored unless you configure the option `org-agenda-skip-archived-trees`, in which case these trees will always be included. In the agenda you can press `v a` to get archives temporarily included.
- Archived trees are not exported (see [Chapter 12 \[Exporting\]](#), page 135), only the headline is. Configure the details using the variable `org-export-with-archived-trees`.
- Archived trees are excluded from column view unless the variable `org-columns-skip-archived-trees` is configured to `nil`.

The following commands help manage the ARCHIVE tag:

- `C-c C-x a` `org-toggle-archive-tag`  
 Toggle the ARCHIVE tag for the current headline. When the tag is set, the headline changes to a shadowed face, and the subtree below it is hidden.
- `C-u C-c C-x a`  
 Check if any direct children of the current headline should be archived. To do this, each subtree is checked for open TODO entries. If none are found, the command offers to set the ARCHIVE tag for the child. If the cursor is *not* on a headline when this command is invoked, the level 1 trees will be checked.
- `C-TAB` `org-force-cycle-archived`  
 Cycle a tree even if it is tagged with ARCHIVE.
- `C-c C-x A` `org-archive-to-archive-sibling`  
 Move the current entry to the *Archive Sibling*. This is a sibling of the entry with the heading ‘Archive’ and the tag ‘ARCHIVE’. The entry becomes a child of that sibling and in this way retains a lot of its original context, including inherited tags and approximate position in the outline.

## 10 Agenda views

Due to the way Org works, TODO items, time-stamped items, and tagged headlines can be scattered throughout a file or even a number of files. To get an overview of open action items, or of events that are important for a particular date, this information must be collected, sorted and displayed in an organized way.

Org can select items based on various criteria and display them in a separate buffer. Seven different view types are provided:

- an *agenda* that is like a calendar and shows information for specific dates,
- a *TODO list* that covers all unfinished action items,
- a *match view*, showing headlines based on the tags, properties, and TODO state associated with them,
- a *timeline view* that shows all events in a single Org file, in time-sorted view,
- a *text search view* that shows all entries from multiple files that contain specified keywords,
- a *stuck projects view* showing projects that currently don't move along, and
- *custom views* that are special searches and combinations of different views.

The extracted information is displayed in a special *agenda buffer*. This buffer is read-only, but provides commands to visit the corresponding locations in the original Org files, and even to edit these files remotely.

Two variables control how the agenda buffer is displayed and whether the window configuration is restored when the agenda exits: `org-agenda-window-setup` and `org-agenda-restore-windows-after-quit`.

### 10.1 Agenda files

The information to be shown is normally collected from all *agenda files*, the files listed in the variable `org-agenda-files`<sup>1</sup>. If a directory is part of this list, all files with the extension `.org` in this directory will be part of the list.

Thus, even if you only work with a single Org file, that file should be put into the list<sup>2</sup>. You can customize `org-agenda-files`, but the easiest way to maintain it is through the following commands

|                                                                                                                                                                                                            |                                       |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------|
| <code>C-c [</code>                                                                                                                                                                                         | <code>org-agenda-file-to-front</code> |
| Add current file to the list of agenda files. The file is added to the front of the list. If it was already in the list, it is moved to the front. With a prefix argument, file is added/moved to the end. |                                       |
| <code>C-c ]</code>                                                                                                                                                                                         | <code>org-remove-file</code>          |
| Remove current file from the list of agenda files.                                                                                                                                                         |                                       |

<sup>1</sup> If the value of that variable is not a list, but a single file name, then the list of agenda files will be maintained in that external file.

<sup>2</sup> When using the dispatcher, pressing `<` before selecting a command will actually limit the command to the current file, and ignore `org-agenda-files` until the next dispatcher command.

`C-'` `org-cycle-agenda-files`  
`C-,` Cycle through agenda file list, visiting one file after the other.

`M-x org-iswitchb RET`  
 Command to use an `iswitchb`-like interface to switch to and between Org buffers.

The Org menu contains the current list of files and can be used to visit any of them.

If you would like to focus the agenda temporarily on a file not in this list, or on just one file in the list, or even on only a subtree in a file, then this can be done in different ways. For a single agenda command, you may press `<` once or several times in the dispatcher (see [Section 10.2 \[Agenda dispatcher\], page 101](#)). To restrict the agenda scope for an extended period, use the following commands:

`C-c C-x <` `org-agenda-set-restriction-lock`  
 Permanently restrict the agenda to the current subtree. When with a prefix argument, or with the cursor before the first headline in a file, the agenda scope is set to the entire file. This restriction remains in effect until removed with `C-c C-x >`, or by typing either `<` or `>` in the agenda dispatcher. If there is a window displaying an agenda view, the new restriction takes effect immediately.

`C-c C-x >` `org-agenda-remove-restriction-lock`  
 Remove the permanent restriction created by `C-c C-x <`.

When working with `speedbar.el`, you can use the following commands in the Speedbar frame:

`<` in the speedbar frame `org-speedbar-set-agenda-restriction`  
 Permanently restrict the agenda to the item—either an Org file or a subtree in such a file—at the cursor in the Speedbar frame. If there is a window displaying an agenda view, the new restriction takes effect immediately.

`>` in the speedbar frame `org-agenda-remove-restriction-lock`  
 Lift the restriction.

## 10.2 The agenda dispatcher

The views are created through a dispatcher, which should be bound to a global key—for example `C-c a` (see [Section 1.3 \[Activation\], page 3](#)). In the following we will assume that `C-c a` is indeed how the dispatcher is accessed and list keyboard access to commands accordingly. After pressing `C-c a`, an additional letter is required to execute a command. The dispatcher offers the following default commands:

`a` Create the calendar-like agenda (see [Section 10.3.1 \[Weekly/daily agenda\], page 102](#)).

`t / T` Create a list of all TODO items (see [Section 10.3.2 \[Global TODO list\], page 104](#)).

`m / M` Create a list of headlines matching a TAGS expression (see [Section 10.3.3 \[Matching tags and properties\], page 105](#)).

`L` Create the timeline view for the current buffer (see [Section 10.3.4 \[Timeline\], page 108](#)).



- `s` Create a list of entries selected by a boolean expression of keywords and/or regular expressions that must or must not occur in the entry.
- `/` Search for a regular expression in all agenda files and additionally in the files listed in `org-agenda-text-search-extra-files`. This uses the Emacs command `multi-occur`. A prefix argument can be used to specify the number of context lines for each match, default is 1.
- `# / !` Create a list of stuck projects (see [Section 10.3.6 \[Stuck projects\]](#), page 108).
- `<` Restrict an agenda command to the current buffer<sup>3</sup>. After pressing `<`, you still need to press the character selecting the command.
- `< <` If there is an active region, restrict the following agenda command to the region. Otherwise, restrict it to the current subtree<sup>4</sup>. After pressing `< <`, you still need to press the character selecting the command.
- `*` Toggle sticky agenda views. By default, Org maintains only a single agenda buffer and rebuilds it each time you change the view, to make sure everything is always up to date. If you often switch between agenda views and the build time bothers you, you can turn on sticky agenda buffers or make this the default by customizing the variable `org-agenda-sticky`. With sticky agendas, the agenda dispatcher will not recreate agenda views from scratch, it will only switch to the selected one, and you need to update the agenda by hand with `r` or `g` when needed. You can toggle sticky agenda view any time with `org-toggle-sticky-agenda`.

You can also define custom commands that will be accessible through the dispatcher, just like the default commands. This includes the possibility to create extended agenda buffers that contain several blocks together, for example the weekly agenda, the global TODO list and a number of special tags matches. See [Section 10.6 \[Custom agenda views\]](#), page 121.

## 10.3 The built-in agenda views

In this section we describe the built-in views.

### 10.3.1 The weekly/daily agenda

The purpose of the weekly/daily *agenda* is to act like a page of a paper agenda, showing all the tasks for the current week or day.

`C-c a a` `org-agenda-list`  
 Compile an agenda for the current week from a list of Org files. The agenda shows the entries for each day. With a numeric prefix<sup>5</sup> (like `C-u 2 1 C-c a a`) you may set the number of days to be displayed.

The default number of days displayed in the agenda is set by the variable `org-agenda-span` (or the obsolete `org-agenda-ndays`). This variable can be set to any number of

<sup>3</sup> For backward compatibility, you can also press `1` to restrict to the current buffer.

<sup>4</sup> For backward compatibility, you can also press `0` to restrict to the current region/subtree.

<sup>5</sup> For backward compatibility, the universal prefix `C-u` causes all TODO entries to be listed before the agenda. This feature is deprecated, use the dedicated TODO list, or a block agenda instead (see [Section 10.6.2 \[Block agenda\]](#), page 123).

days you want to see by default in the agenda, or to a span name, such as `day`, `week`, `month` or `year`. For weekly agendas, the default is to start on the previous monday (see `org-agenda-start-on-weekday`). You can also set the start date using a date shift: `(setq org-agenda-start-day "+10d")` will start the agenda ten days from today in the future.

Remote editing from the agenda buffer means, for example, that you can change the dates of deadlines and appointments from the agenda buffer. The commands available in the Agenda buffer are listed in [Section 10.5 \[Agenda commands\]](#), page 113.

## Calendar/Diary integration

Emacs contains the calendar and diary by Edward M. Reingold. The calendar displays a three-month calendar with holidays from different countries and cultures. The diary allows you to keep track of anniversaries, lunar phases, sunrise/set, recurrent appointments (weekly, monthly) and more. In this way, it is quite complementary to Org. It can be very useful to combine output from Org with the diary.

In order to include entries from the Emacs diary into Org mode's agenda, you only need to customize the variable

```
(setq org-agenda-include-diary t)
```

After that, everything will happen automatically. All diary entries including holidays, anniversaries, etc., will be included in the agenda buffer created by Org mode. `SPC`, `TAB`, and `RET` can be used from the agenda buffer to jump to the diary file in order to edit existing diary entries. The `i` command to insert new entries for the current date works in the agenda buffer, as well as the commands `S`, `M`, and `C` to display Sunrise/Sunset times, show lunar phases and to convert to other calendars, respectively. `c` can be used to switch back and forth between calendar and agenda.

If you are using the diary only for sexp entries and holidays, it is faster to not use the above setting, but instead to copy or even move the entries into an Org file. Org mode evaluates diary-style sexp entries, and does it faster because there is no overhead for first creating the diary display. Note that the sexp entries must start at the left margin, no whitespace is allowed before them. For example, the following segment of an Org file will be processed and entries will be made in the agenda:

```
* Holidays
:PROPERTIES:
:CATEGORY: Holiday
:END:
%%(org-calendar-holiday)    ; special function for holiday names

* Birthdays
:PROPERTIES:
:CATEGORY: Ann
:END:
%%(org-anniversary 1956  5 14)6 Arthur Dent is %d years old
%%(org-anniversary 1869 10  2) Mahatma Gandhi would be %d years old
```

---

<sup>6</sup> `org-anniversary` is just like `diary-anniversary`, but the argument order is always according to ISO and therefore independent of the value of `calendar-date-style`.

## Anniversaries from BBDB

If you are using the Big Brothers Database to store your contacts, you will very likely prefer to store anniversaries in BBDB rather than in a separate Org or diary file. Org supports this and will show BBDB anniversaries as part of the agenda. All you need to do is to add the following to one of your agenda files:

```
* Anniversaries
:PROPERTIES:
:CATEGORY: Anniv
:END:
%%(org-bbdb-anniversaries)
```

You can then go ahead and define anniversaries for a BBDB record. Basically, you need to press `C-o anniversary RET` with the cursor in a BBDB record and then add the date in the format `YYYY-MM-DD` or `MM-DD`, followed by a space and the class of the anniversary (`'birthday'` or `'wedding'`, or a format string). If you omit the class, it will default to `'birthday'`. Here are a few examples, the header for the file `org-bbdb.el` contains more detailed information.

```
1973-06-22
06-22
1955-08-02 wedding
2008-04-14 %s released version 6.01 of org mode, %d years ago
```

After a change to BBDB, or for the first agenda display during an Emacs session, the agenda display will suffer a short delay as Org updates its hash with anniversaries. However, from then on things will be very fast—much faster in fact than a long list of `'%(diary-anniversary)'` entries in an Org or Diary file.

If you would like to see upcoming anniversaries with a bit of forewarning, you can use the following instead:

```
* Anniversaries
:PROPERTIES:
:CATEGORY: Anniv
:END:
%%(org-bbdb-anniversaries-future 3)
```

That will give you three days' warning: on the anniversary date itself and the two days prior. The argument is optional: if omitted, it defaults to 7.

## Appointment reminders

Org can interact with Emacs appointments notification facility. To add the appointments of your agenda files, use the command `org-agenda-to-appt`. This command lets you filter through the list of your appointments and add only those belonging to a specific category or matching a regular expression. It also reads a `APPT_WARNTIME` property which will then override the value of `appt-message-warning-time` for this appointment. See the docstring for details.

### 10.3.2 The global TODO list

The global TODO list contains all unfinished TODO items formatted and collected into a single place.

**C-c a t** org-todo-list  
 Show the global TODO list. This collects the TODO items from all agenda files (see [Chapter 10 \[Agenda views\]](#), page 100) into a single buffer. By default, this lists items with a state that is not a DONE state. The buffer is in **agenda-mode**, so there are commands to examine and manipulate the TODO entries directly from that buffer (see [Section 10.5 \[Agenda commands\]](#), page 113).

**C-c a T** org-todo-list  
 Like the above, but allows selection of a specific TODO keyword. You can also do this by specifying a prefix argument to **C-c a t**. You are prompted for a keyword, and you may also specify several keywords by separating them with ‘|’ as the boolean OR operator. With a numeric prefix, the Nth keyword in **org-todo-keywords** is selected. The **r** key in the agenda buffer regenerates it, and you can give a prefix argument to this command to change the selected TODO keyword, for example **3 r**. If you often need a search for a specific keyword, define a custom command for it (see [Section 10.2 \[Agenda dispatcher\]](#), page 101).  
 Matching specific TODO keywords can also be done as part of a tags search (see [Section 6.4 \[Tag searches\]](#), page 63).

Remote editing of TODO items means that you can change the state of a TODO entry with a single key press. The commands available in the TODO list are described in [Section 10.5 \[Agenda commands\]](#), page 113.

Normally the global TODO list simply shows all headlines with TODO keywords. This list can become very long. There are two ways to keep it more compact:

- Some people view a TODO item that has been *scheduled* for execution or have a *deadline* (see [Section 8.1 \[Timestamps\]](#), page 73) as no longer *open*. Configure the variables **org-agenda-todo-ignore-scheduled**, **org-agenda-todo-ignore-deadlines**, **org-agenda-todo-ignore-timestamp** and/or **org-agenda-todo-ignore-with-date** to exclude such items from the global TODO list.
- TODO items may have sublevels to break up the task into subtasks. In such cases it may be enough to list only the highest level TODO headline and omit the sublevels from the global list. Configure the variable **org-agenda-todo-list-sublevels** to get this behavior.

### 10.3.3 Matching tags and properties

If headlines in the agenda files are marked with *tags* (see [Chapter 6 \[Tags\]](#), page 59), or have properties (see [Chapter 7 \[Properties and columns\]](#), page 64), you can select headlines based on this metadata and collect them into an agenda buffer. The match syntax described here also applies when creating sparse trees with **C-c / m**.

**C-c a m** org-tags-view  
 Produce a list of all headlines that match a given set of tags. The command prompts for a selection criterion, which is a boolean logic expression with tags, like ‘+work+urgent-withboss’ or ‘work|home’ (see [Chapter 6 \[Tags\]](#), page 59). If you often need a specific search, define a custom command for it (see [Section 10.2 \[Agenda dispatcher\]](#), page 101).

**C-c a M****org-tags-view**

Like **C-c a m**, but only select headlines that are also TODO items in a not-DONE state and force checking subitems (see variable **org-tags-match-list-sublevels**). To exclude scheduled/deadline items, see the variable **org-agenda-tags-todo-honor-ignore-options**. Matching specific TODO keywords together with a tags match is also possible, see [Section 6.4 \[Tag searches\]](#), page 63.

The commands available in the tags list are described in [Section 10.5 \[Agenda commands\]](#), page 113.

## Match syntax

A search string can use Boolean operators ‘&’ for AND and ‘|’ for OR. ‘&’ binds more strongly than ‘|’. Parentheses are not implemented. Each element in the search is either a tag, a regular expression matching tags, or an expression like **PROPERTY OPERATOR VALUE** with a comparison operator, accessing a property value. Each element may be preceded by ‘-’, to select against it, and ‘+’ is syntactic sugar for positive selection. The AND operator ‘&’ is optional when ‘+’ or ‘-’ is present. Here are some examples, using only tags.

‘work’        Select headlines tagged ‘:work:’.

‘work&boss’

Select headlines tagged ‘:work:’ and ‘:boss:’.

‘+work-boss’

Select headlines tagged ‘:work:’, but discard those also tagged ‘:boss:’.

‘work|laptop’

Selects lines tagged ‘:work:’ or ‘:laptop:’.

‘work|laptop+night’

Like before, but require the ‘:laptop:’ lines to be tagged also ‘:night:’.

Instead of a tag, you may also specify a regular expression enclosed in curly braces. For example, ‘work+{~boss.\*}’ matches headlines that contain the tag ‘:work:’ and any tag *starting* with ‘boss’.

Group tags (see [Section 6.3 \[Tag hierarchy\]](#), page 62) are expanded as regular expressions. E.g., if ‘:work:’ is a group tag for the group ‘:work:lab:conf:’, then searching for ‘work’ will search for ‘{\\(?:work\\|lab\\|conf\\)}’ and searching for ‘-work’ will search for all headlines but those with one of the tags in the group (i.e., ‘-{\\(?:work\\|lab\\|conf\\)}’).

You may also test for properties (see [Chapter 7 \[Properties and columns\]](#), page 64) at the same time as matching tags. The properties may be real properties, or special properties that represent other metadata (see [Section 7.2 \[Special properties\]](#), page 66). For example, the “property” **TODO** represents the TODO keyword of the entry and the “property” **PRIORITY** represents the PRIORITY keyword of the entry.

In addition to the [Section 7.2 \[Special properties\]](#), page 66, one other “property” can also be used. **LEVEL** represents the level of an entry. So a search ‘+LEVEL=3+boss-TODO="DONE"’ lists all level three headlines that have the tag ‘boss’ and are *not* marked with the TODO keyword DONE. In buffers with **org-odd-levels-only** set, ‘LEVEL’ does not count the number of stars, but ‘LEVEL=2’ will correspond to 3 stars etc.

Here are more examples:

```
'work+TODO="WAITING"'
```

Select `:work:`-tagged TODO lines with the specific TODO keyword `'WAITING'`.

```
'work+TODO="WAITING"|home+TODO="WAITING"'
```

Waiting tasks both at work and at home.

When matching properties, a number of different operators can be used to test the value of a property. Here is a complex example:

```
+work-boss+PRIORITY="A"+Coffee="unlimited"+Effort<2 \
+With={Sarah\|Denny}+SCHEDULED>="<2008-10-11>"
```

The type of comparison will depend on how the comparison value is written:

- If the comparison value is a plain number, a numerical comparison is done, and the allowed operators are `'<'`, `'='`, `'>'`, `'<='`, `'>='`, and `'<>'`.
- If the comparison value is enclosed in double-quotes, a string comparison is done, and the same operators are allowed.
- If the comparison value is enclosed in double-quotes *and* angular brackets (like `'DEADLINE<="<2008-12-24 18:30>"'`), both values are assumed to be date/time specifications in the standard Org way, and the comparison will be done accordingly. Special values that will be recognized are `"<now>"` for now (including time), and `"<today>"`, and `"<tomorrow>"` for these days at 00:00 hours, i.e., without a time specification. Also strings like `"<+5d>"` or `"<-2m>"` with units `d`, `w`, `m`, and `y` for day, week, month, and year, respectively, can be used.
- If the comparison value is enclosed in curly braces, a regexp match is performed, with `'='` meaning that the regexp matches the property value, and `'<>'` meaning that it does not match.

So the search string in the example finds entries tagged `:work:` but not `:boss:`, which also have a priority value `'A'`, a `:Coffee:` property with the value `'unlimited'`, an `'Effort'` property that is numerically smaller than 2, a `:With:` property that is matched by the regular expression `'Sarah\|Denny'`, and that are scheduled on or after October 11, 2008.

You can configure Org mode to use property inheritance during a search, but beware that this can slow down searches considerably. See [Section 7.4 \[Property inheritance\]](#), page 67, for details.

For backward compatibility, and also for typing speed, there is also a different way to test TODO states in a search. For this, terminate the tags/property part of the search string (which may include several terms connected with `'|'`) with a `'/'` and then specify a Boolean expression just for TODO keywords. The syntax is then similar to that for tags, but should be applied with care: for example, a positive selection on several TODO keywords cannot meaningfully be combined with boolean AND. However, *negative selection* combined with AND can be meaningful. To make sure that only lines are checked that actually have any TODO keyword (resulting in a speed-up), use `C-c a M`, or equivalently start the TODO part after the slash with `'!'`. Using `C-c a M` or `'/!'` will not match TODO keywords in a DONE state. Examples:

```
'work/WAITING'
```

Same as `'work+TODO="WAITING"'`

`'work/!-WAITING-NEXT'`

Select `'work:'`-tagged TODO lines that are neither `'WAITING'` nor `'NEXT'`

`'work/!+WAITING|+NEXT'`

Select `'work:'`-tagged TODO lines that are either `'WAITING'` or `'NEXT'`.

### 10.3.4 Timeline for a single file

The timeline summarizes all time-stamped items from a single Org mode file in a *time-sorted view*. The main purpose of this command is to give an overview over events in a project.

`C-c a L`

`org-timeline`

Show a time-sorted view of the Org file, with all time-stamped items. When called with a `C-u` prefix, all unfinished TODO entries (scheduled or not) are also listed under the current date.

The commands available in the timeline buffer are listed in [Section 10.5 \[Agenda commands\]](#), [page 113](#).

### 10.3.5 Search view

This agenda view is a general text search facility for Org mode entries. It is particularly useful to find notes.

`C-c a s`

`org-search-view`

This is a special search that lets you select entries by matching a substring or specific words using a boolean logic.

For example, the search string `'computer equipment'` will find entries that contain `'computer equipment'` as a substring. If the two words are separated by more space or a line break, the search will still match. Search view can also search for specific keywords in the entry, using Boolean logic. The search string `'+computer +wifi -ethernet -{8\11[bg]}'` will search for note entries that contain the keywords `computer` and `wifi`, but not the keyword `ethernet`, and which are also not matched by the regular expression `8\11[bg]`, meaning to exclude both `8.11b` and `8.11g`. The first `+` is necessary to turn on word search, other `+` characters are optional. For more details, see the docstring of the command `org-search-view`.

Note that in addition to the agenda files, this command will also search the files listed in `org-agenda-text-search-extra-files`.

### 10.3.6 Stuck projects

If you are following a system like David Allen's GTD to organize your work, one of the "duties" you have is a regular review to make sure that all projects move along. A *stuck* project is a project that has no defined next actions, so it will never show up in the TODO lists Org mode produces. During the review, you need to identify such projects and define next actions for them.

`C-c a #`

`org-agenda-list-stuck-projects`

List projects that are stuck.

`C-c a !`

Customize the variable `org-stuck-projects` to define what a stuck project is and how to find it.



You almost certainly will have to configure this view before it will work for you. The built-in default assumes that all your projects are level-2 headlines, and that a project is not stuck if it has at least one entry marked with a TODO keyword TODO or NEXT or NEXTACTION.

Let's assume that you, in your own way of using Org mode, identify projects with a tag PROJECT, and that you use a TODO keyword MAYBE to indicate a project that should not be considered yet. Let's further assume that the TODO keyword DONE marks finished projects, and that NEXT and TODO indicate next actions. The tag @SHOP indicates shopping and is a next action even without the NEXT tag. Finally, if the project contains the special word IGNORE anywhere, it should not be listed either. In this case you would start by identifying eligible projects with a tags/todo match<sup>7</sup> '+PROJECT/-MAYBE-DONE', and then check for TODO, NEXT, @SHOP, and IGNORE in the subtree to identify projects that are not stuck. The correct customization for this is

```
(setq org-stuck-projects
  '("+PROJECT/-MAYBE-DONE" ("NEXT" "TODO") ("@SHOP")
    "\\<IGNORE\\>"))
```

Note that if a project is identified as non-stuck, the subtree of this entry will still be searched for stuck projects.

## 10.4 Presentation and sorting

Before displaying items in an agenda view, Org mode visually prepares the items and sorts them. Each item occupies a single line. The line starts with a *prefix* that contains the *category* (see [Section 10.4.1 \[Categories\]](#), page 109) of the item and other important information. You can customize in which column tags will be displayed through `org-agenda-tags-column`. You can also customize the prefix using the option `org-agenda-prefix-format`. This prefix is followed by a cleaned-up version of the outline headline associated with the item.

### 10.4.1 Categories

The category is a broad label assigned to each agenda item. By default, the category is simply derived from the file name, but you can also specify it with a special line in the buffer, like this:

```
#+CATEGORY: Thesis
```

If you would like to have a special CATEGORY for a single entry or a (sub)tree, give the entry a `:CATEGORY:` property with the special category you want to apply as the value.

The display in the agenda buffer looks best if the category is not longer than 10 characters. You can set up icons for category by customizing the `org-agenda-category-icon-alist` variable.

### 10.4.2 Time-of-day specifications

Org mode checks each agenda item for a time-of-day specification. The time can be part of the timestamp that triggered inclusion into the agenda, for example as in

<sup>7</sup> See [Section 6.4 \[Tag searches\]](#), page 63.



‘<2005-05-10 Tue 19:00>’. Time ranges can be specified with two timestamps, like ‘<2005-05-10 Tue 20:30>--<2005-05-10 Tue 22:15>’.

In the headline of the entry itself, a time(range) may also appear as plain text (like ‘12:45’ or a ‘8:30-1pm’). If the agenda integrates the Emacs diary (see [Section 10.3.1 \[Weekly/daily agenda\]](#), [page 102](#)), time specifications in diary entries are recognized as well.

For agenda display, Org mode extracts the time and displays it in a standard 24 hour format as part of the prefix. The example times in the previous paragraphs would end up in the agenda like this:

```
8:30-13:00 Arthur Dent lies in front of the bulldozer
12:45..... Ford Prefect arrives and takes Arthur to the pub
19:00..... The Vogon reads his poem
20:30-22:15 Marvin escorts the Hitchhikers to the bridge
```

If the agenda is in single-day mode, or for the display of today, the timed entries are embedded in a time grid, like

```
8:00..... -----
8:30-13:00 Arthur Dent lies in front of the bulldozer
10:00..... -----
12:00..... -----
12:45..... Ford Prefect arrives and takes Arthur to the pub
14:00..... -----
16:00..... -----
18:00..... -----
19:00..... The Vogon reads his poem
20:00..... -----
20:30-22:15 Marvin escorts the Hitchhikers to the bridge
```

The time grid can be turned on and off with the variable `org-agenda-use-time-grid`, and can be configured with `org-agenda-time-grid`.

### 10.4.3 Sorting agenda items

Before being inserted into a view, the items are sorted. How this is done depends on the type of view.

- For the daily/weekly agenda, the items for each day are sorted. The default order is to first collect all items containing an explicit time-of-day specification. These entries will be shown at the beginning of the list, as a *schedule* for the day. After that, items remain grouped in categories, in the sequence given by `org-agenda-files`. Within each category, items are sorted by priority (see [Section 5.4 \[Priorities\]](#), [page 55](#)), which is composed of the base priority (2000 for priority ‘A’, 1000 for ‘B’, and 0 for ‘C’), plus additional increments for overdue scheduled or deadline items.
- For the TODO list, items remain in the order of categories, but within each category, sorting takes place according to priority (see [Section 5.4 \[Priorities\]](#), [page 55](#)). The priority used for sorting derives from the priority cookie, with additions depending on how close an item is to its due or scheduled date.
- For tags matches, items are not sorted at all, but just appear in the sequence in which they are found in the agenda files.

Sorting can be customized using the variable `org-agenda-sorting-strategy`, and may also include criteria based on the estimated effort of an entry (see [Section 8.5 \[Effort estimates\]](#), page 86).

#### 10.4.4 Filtering/limiting agenda items

Agenda built-in or customized commands are statically defined. Agenda filters and limits provide two ways of dynamically narrowing down the list of agenda entries: *filters* and *limits*. Filters only act on the display of the items, while limits take effect before the list of agenda entries is built. Filters are more often used interactively, while limits are mostly useful when defined as local variables within custom agenda commands.

#### Filtering in the agenda

/ `org-agenda-filter-by-tag`

Filter the agenda view with respect to a tag and/or effort estimates. The difference between this and a custom agenda command is that filtering is very fast, so that you can switch quickly between different filters without having to recreate the agenda.<sup>8</sup>

You will be prompted for a tag selection letter; `SPC` will mean any tag at all. Pressing `TAB` at that prompt will offer use completion to select a tag (including any tags that do not have a selection character). The command then hides all entries that do not contain or inherit this tag. When called with prefix arg, remove the entries that *do* have the tag. A second `/` at the prompt will turn off the filter and unhide any hidden entries. Pressing `+` or `-` switches between filtering and excluding the next tag.

Org also supports automatic, context-aware tag filtering. If the variable `org-agenda-auto-exclude-function` is set to a user-defined function, that function can decide which tags should be excluded from the agenda automatically. Once this is set, the `/` command then accepts `RET` as a sub-option key and runs the auto exclusion logic. For example, let's say you use a `Net` tag to identify tasks which need network access, an `Errand` tag for errands in town, and a `Call` tag for making phone calls. You could auto-exclude these tags based on the availability of the Internet, and outside of business hours, with something like this:

```
(defun org-my-auto-exclude-function (tag)
  (and (cond
        ((string= tag "Net")
         (/= 0 (call-process "/sbin/ping" nil nil nil
                             "-c1" "-q" "-t1" "mail.gnu.org")))
        ((or (string= tag "Errand") (string= tag "Call"))
         (let ((hour (nth 2 (decode-time))))
           (or (< hour 8) (> hour 21))))))
    (concat "-" tag)))

(setq org-agenda-auto-exclude-function 'org-my-auto-exclude-function)
```

<sup>8</sup> Custom commands can preset a filter by binding the variable `org-agenda-tag-filter-preset` as an option. This filter will then be applied to the view and persist as a basic filter through refreshes and more secondary filtering. The filter is a global property of the entire agenda view—in a block agenda, you should only set this in the global options section, not in the section of an individual block.

[ ] { }

in *search view*

add new search words ( [ and ] ) or new regular expressions ( { and } ) to the query string. The opening bracket/brace will add a positive search term prefixed by '+', indicating that this search term *must* occur/match in the entry. The closing bracket/brace will add a negative search term which *must not* occur/match in the entry for it to be selected.

<

**org-agenda-filter-by-category**

Filter the current agenda view with respect to the category of the item at point. Pressing < another time will remove this filter. When called with a prefix argument exclude the category of the item at point from the agenda. You can add a filter preset through the option **org-agenda-category-filter-preset** (see below.)

^

**org-agenda-filter-by-top-headline**

Filter the current agenda view and only display the siblings and the parent headline of the one at point.

=

**org-agenda-filter-by-regexp**

Filter the agenda view by a regular expression: only show agenda entries matching the regular expression the user entered. When called with a prefix argument, it will filter *out* entries matching the regexp. With two universal prefix arguments, it will remove all the regexp filters, which can be accumulated. You can add a filter preset through the option **org-agenda-category-filter-preset** (see below.)

-

**org-agenda-filter-by-effort**

Filter the agenda view with respect to effort estimates. You first need to set up allowed efforts globally, for example

```
(setq org-global-properties
      '(("Effort_ALL". "0 0:10 0:30 1:00 2:00 3:00 4:00")))
```

You can then filter for an effort by first typing an operator, one of <, >, and =, and then the one-digit index of an effort estimate in your array of allowed values, where 0 means the 10th value. The filter will then restrict to entries with effort smaller-or-equal, equal, or larger-or-equal than the selected value. For application of the operator, entries without a defined effort will be treated according to the value of **org-sort-agenda-noeffort-is-high**.

|

**org-agenda-filter-remove-all**

Remove all filters in the current agenda view.

## Setting limits for the agenda

Here is a list of options that you can set, either globally, or locally in your custom agenda views (see [Section 10.6 \[Custom agenda views\]](#), page 121).

**org-agenda-max-entries**

Limit the number of entries.

**org-agenda-max-effort**

Limit the duration of accumulated efforts (as minutes).

**org-agenda-max-todos**

Limit the number of entries with TODO keywords.

**org-agenda-max-tags**

Limit the number of tagged entries.

When set to a positive integer, each option will exclude entries from other categories: for example, `(setq org-agenda-max-effort 100)` will limit the agenda to 100 minutes of effort and exclude any entry that has no effort property. If you want to include entries with no effort property, use a negative value for **org-agenda-max-effort**.

One useful setup is to use **org-agenda-max-entries** locally in a custom command. For example, this custom command will display the next five entries with a **NEXT** TODO keyword.

```
(setq org-agenda-custom-commands
      '(("n" todo "NEXT"
         ((org-agenda-max-entries 5)))))
```

Once you mark one of these five entry as **DONE**, rebuilding the agenda will again the next five entries again, including the first entry that was excluded so far.

You can also dynamically set temporary limits, which will be lost when rebuilding the agenda:

```
~                                     org-agenda-limit-interactively
This prompts for the type of limit to apply and its value.
```

## 10.5 Commands in the agenda buffer

Entries in the agenda buffer are linked back to the Org file or diary file where they originate. You are not allowed to edit the agenda buffer itself, but commands are provided to show and jump to the original entry location, and to edit the Org files “remotely” from the agenda buffer. In this way, all information is stored only once, removing the risk that your agenda and note files may diverge.

Some commands can be executed with mouse clicks on agenda lines. For the other commands, the cursor needs to be in the desired line.

### Motion

|          |                                                                |                                 |
|----------|----------------------------------------------------------------|---------------------------------|
| <b>n</b> | Next line (same as <b>down</b> and <b>C-n</b> ).               | <b>org-agenda-next-line</b>     |
| <b>p</b> | Previous line (same as <b>up</b> and <b>C-p</b> ).             | <b>org-agenda-previous-line</b> |
| <b>N</b> | Next item: same as next line, but only consider items.         | <b>org-agenda-next-item</b>     |
| <b>P</b> | Previous item: same as previous line, but only consider items. | <b>org-agenda-previous-item</b> |

**View/Go to Org file**

|                              |                                                                                                                                                                                                                                                                                                       |
|------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>SPC</i> or <i>mouse-3</i> | <code>org-agenda-show-and-scroll-up</code>                                                                                                                                                                                                                                                            |
|                              | Display the original location of the item in another window. With prefix arg, make sure that drawers stay folded.                                                                                                                                                                                     |
| <i>L</i>                     | <code>org-agenda-recenter</code>                                                                                                                                                                                                                                                                      |
|                              | Display original location and recenter that window.                                                                                                                                                                                                                                                   |
| <i>TAB</i> or <i>mouse-2</i> | <code>org-agenda-goto</code>                                                                                                                                                                                                                                                                          |
|                              | Go to the original location of the item in another window.                                                                                                                                                                                                                                            |
| <i>RET</i>                   | <code>org-agenda-switch-to</code>                                                                                                                                                                                                                                                                     |
|                              | Go to the original location of the item and delete other windows.                                                                                                                                                                                                                                     |
| <i>F</i>                     | <code>org-agenda-follow-mode</code>                                                                                                                                                                                                                                                                   |
|                              | Toggle Follow mode. In Follow mode, as you move the cursor through the agenda buffer, the other window always shows the corresponding location in the Org file. The initial setting for this mode in new agenda buffers can be set with the variable <code>org-agenda-start-with-follow-mode</code> . |
| <i>C-c C-x b</i>             | <code>org-agenda-tree-to-indirect-buffer</code>                                                                                                                                                                                                                                                       |
|                              | Display the entire subtree of the current item in an indirect buffer. With a numeric prefix argument N, go up to level N and then take that tree. If N is negative, go up that many levels. With a <i>C-u</i> prefix, do not remove the previously used indirect buffer.                              |
| <i>C-c C-o</i>               | <code>org-agenda-open-link</code>                                                                                                                                                                                                                                                                     |
|                              | Follow a link in the entry. This will offer a selection of any links in the text belonging to the referenced Org node. If there is only one link, it will be followed without a selection prompt.                                                                                                     |

**Change display**

|                              |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>A</i>                     | Interactively select another agenda view and append it to the current view.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <i>o</i>                     | Delete other windows.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| <i>v d</i> or short <i>d</i> | <code>org-agenda-day-view</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <i>v w</i> or short <i>w</i> | <code>org-agenda-week-view</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <i>v t</i>                   | <code>org-agenda-fortnight-view</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <i>v m</i>                   | <code>org-agenda-month-view</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <i>v y</i>                   | <code>org-agenda-year-view</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <i>v SPC</i>                 | <code>org-agenda-reset-view</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|                              | Switch to day/week/month/year view. When switching to day or week view, this setting becomes the default for subsequent agenda refreshes. Since month and year views are slow to create, they do not become the default. A numeric prefix argument may be used to jump directly to a specific day of the year, ISO week, month, or year, respectively. For example, <i>32 d</i> jumps to February 1st, <i>9 w</i> to ISO week number 9. When setting day, week, or month view, a year may be encoded in the prefix argument as well. For example, <i>200712 w</i> will jump to week 12 in 2007. If such a year specification has only one or two digits, it will be mapped to the interval 1938–2037. <i>v SPC</i> will reset to what is set in <code>org-agenda-span</code> . |

|                              |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>f</i>                     | <code>org-agenda-later</code><br>Go forward in time to display the following <code>org-agenda-current-span</code> days. For example, if the display covers a week, switch to the following week. With prefix arg, go forward that many times <code>org-agenda-current-span</code> days.                                                                                                                                                                                                                                                                                                                                                             |
| <i>b</i>                     | <code>org-agenda-earlier</code><br>Go backward in time to display earlier dates.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <i>.</i>                     | <code>org-agenda-goto-today</code><br>Go to today.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <i>j</i>                     | <code>org-agenda-goto-date</code><br>Prompt for a date and go there.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <i>J</i>                     | <code>org-agenda-clock-goto</code><br>Go to the currently clocked-in task <i>in the agenda buffer</i> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <i>D</i>                     | <code>org-agenda-toggle-diary</code><br>Toggle the inclusion of diary entries. See <a href="#">Section 10.3.1 [Weekly/daily agenda]</a> , <a href="#">page 102</a> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <i>v l</i> or short <i>l</i> | <code>org-agenda-log-mode</code><br>Toggle Logbook mode. In Logbook mode, entries that were marked DONE while logging was on (variable <code>org-log-done</code> ) are shown in the agenda, as are entries that have been clocked on that day. You can configure the entry types that should be included in log mode using the variable <code>org-agenda-log-mode-items</code> . When called with a <i>C-u</i> prefix, show all possible logbook entries, including state changes. When called with two prefix arguments <i>C-u C-u</i> , show only logging information, nothing else. <i>v L</i> is equivalent to <i>C-u v l</i> .                 |
| <i>v [</i> or short <i>[</i> | <code>org-agenda-manipulate-query-add</code><br>Include inactive timestamps into the current view. Only for weekly/daily agenda and timeline views.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| <i>v a</i>                   | <code>org-agenda-archives-mode</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <i>v A</i>                   | <code>org-agenda-archives-mode 'files</code><br>Toggle Archives mode. In Archives mode, trees that are marked ARCHIVED are also scanned when producing the agenda. When you use the capital <i>A</i> , even all archive files are included. To exit archives mode, press <i>v a</i> again.                                                                                                                                                                                                                                                                                                                                                          |
| <i>v R</i> or short <i>R</i> | <code>org-agenda-clockreport-mode</code><br>Toggle Clockreport mode. In Clockreport mode, the daily/weekly agenda will always show a table with the clocked times for the time span and file scope covered by the current agenda view. The initial setting for this mode in new agenda buffers can be set with the variable <code>org-agenda-start-with-clockreport-mode</code> . By using a prefix argument when toggling this mode (i.e., <i>C-u R</i> ), the clock table will not show contributions from entries that are hidden by agenda filtering <sup>9</sup> . See also the variable <code>org-clock-report-include-clocking-task</code> . |
| <i>v c</i>                   | Show overlapping clock entries, clocking gaps, and other clocking problems in the current agenda range. You can then visit clocking lines and fix them manually. See the variable <code>org-agenda-clock-consistency-checks</code> for information                                                                                                                                                                                                                                                                                                                                                                                                  |

---

<sup>9</sup> Only tags filtering will be respected here, effort filtering is ignored.

on how to customize the definition of what constituted a clocking problem. To return to normal agenda display, press *l* to exit Logbook mode.

*v E* or short *E* `org-agenda-entry-text-mode`  
 Toggle entry text mode. In entry text mode, a number of lines from the Org outline node referenced by an agenda line will be displayed below the line. The maximum number of lines is given by the variable `org-agenda-entry-text-maxlines`. Calling this command with a numeric prefix argument will temporarily modify that number to the prefix value.

*G* `org-agenda-toggle-time-grid`  
 Toggle the time grid on and off. See also the variables `org-agenda-use-time-grid` and `org-agenda-time-grid`.

*r* `org-agenda-redo`  
 Recreate the agenda buffer, for example to reflect the changes after modification of the timestamps of items with *S-left* and *S-right*. When the buffer is the global TODO list, a prefix argument is interpreted to create a selective list for a specific TODO keyword.

*g* `org-agenda-redo`  
 Same as *r*.

*C-x C-s* or short *s* `org-save-all-org-buffers`  
 Save all Org buffers in the current Emacs session, and also the locations of IDs.

*C-c C-x C-c* `org-agenda-columns`  
 Invoke column view (see [Section 7.5 \[Column view\]](#), page 67) in the agenda buffer. The column view format is taken from the entry at point, or (if there is no entry at point), from the first entry in the agenda view. So whatever the format for that entry would be in the original buffer (taken from a property, from a `#+COLUMNS` line, or from the default variable `org-columns-default-format`), will be used in the agenda.

*C-c C-x >* `org-agenda-remove-restriction-lock`  
 Remove the restriction lock on the agenda, if it is currently restricted to a file or subtree (see [Section 10.1 \[Agenda files\]](#), page 100).

### Secondary filtering and query editing

For a detailed description of these commands, see [Section 10.4.4 \[Filtering/limiting agenda items\]](#), page 111.

*/* `org-agenda-filter-by-tag`  
 Filter the agenda view with respect to a tag and/or effort estimates.

*<* `org-agenda-filter-by-category`  
 Filter the current agenda view with respect to the category of the item at point. Pressing *<* another time will remove this filter.

*^* `org-agenda-filter-by-top-headline`  
 Filter the current agenda view and only display the siblings and the parent headline of the one at point.

|                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|---------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>=</b>                              | <b>org-agenda-filter-by-regexp</b>                                                                                                                                                                                                                                                                                                                                                                                               |
|                                       | Filter the agenda view by a regular expression: only show agenda entries matching the regular expression the user entered. When called with a prefix argument, it will filter <i>out</i> entries matching the regexp. With two universal prefix arguments, it will remove all the regexp filters, which can be accumulated. You can add a filter preset through the option <b>org-agenda-category-filter-preset</b> (see below.) |
| <b> </b>                              | <b>org-agenda-filter-remove-all</b>                                                                                                                                                                                                                                                                                                                                                                                              |
|                                       | Remove all filters in the current agenda view.                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>Remote editing</b>                 |                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>0--9</b>                           | Digit argument.                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>C-_</b>                            | <b>org-agenda-undo</b>                                                                                                                                                                                                                                                                                                                                                                                                           |
|                                       | Undo a change due to a remote editing command. The change is undone both in the agenda buffer and in the remote buffer.                                                                                                                                                                                                                                                                                                          |
| <b>t</b>                              | <b>org-agenda-todo</b>                                                                                                                                                                                                                                                                                                                                                                                                           |
|                                       | Change the TODO state of the item, both in the agenda and in the original org file.                                                                                                                                                                                                                                                                                                                                              |
| <b>C-S-right</b>                      | <b>org-agenda-todo-nextset</b>                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>C-S-left</b>                       | <b>org-agenda-todo-previousset</b>                                                                                                                                                                                                                                                                                                                                                                                               |
|                                       | Switch to the next/previous set of TODO keywords.                                                                                                                                                                                                                                                                                                                                                                                |
| <b>C-k</b>                            | <b>org-agenda-kill</b>                                                                                                                                                                                                                                                                                                                                                                                                           |
|                                       | Delete the current agenda item along with the entire subtree belonging to it in the original Org file. If the text to be deleted remotely is longer than one line, the kill needs to be confirmed by the user. See variable <b>org-agenda-confirm-kill</b> .                                                                                                                                                                     |
| <b>C-c C-w</b>                        | <b>org-agenda-refile</b>                                                                                                                                                                                                                                                                                                                                                                                                         |
|                                       | Refile the entry at point.                                                                                                                                                                                                                                                                                                                                                                                                       |
| <b>C-c C-x C-a</b> or short <b>a</b>  | <b>org-agenda-archive-default-with-confirmation</b>                                                                                                                                                                                                                                                                                                                                                                              |
|                                       | Archive the subtree corresponding to the entry at point using the default archiving command set in <b>org-archive-default-command</b> . When using the <b>a</b> key, confirmation will be required.                                                                                                                                                                                                                              |
| <b>C-c C-x a</b>                      | <b>org-agenda-toggle-archive-tag</b>                                                                                                                                                                                                                                                                                                                                                                                             |
|                                       | Toggle the ARCHIVE tag for the current headline.                                                                                                                                                                                                                                                                                                                                                                                 |
| <b>C-c C-x A</b>                      | <b>org-agenda-archive-to-archive-sibling</b>                                                                                                                                                                                                                                                                                                                                                                                     |
|                                       | Move the subtree corresponding to the current entry to its <i>archive sibling</i> .                                                                                                                                                                                                                                                                                                                                              |
| <b>C-c C-x C-s</b> or short <b>\$</b> | <b>org-agenda-archive</b>                                                                                                                                                                                                                                                                                                                                                                                                        |
|                                       | Archive the subtree corresponding to the current headline. This means the entry will be moved to the configured archive location, most likely a different file.                                                                                                                                                                                                                                                                  |
| <b>T</b>                              | <b>org-agenda-show-tags</b>                                                                                                                                                                                                                                                                                                                                                                                                      |
|                                       | Show all tags associated with the current item. This is useful if you have turned off <b>org-agenda-show-inherited-tags</b> , but still want to see all tags of a headline occasionally.                                                                                                                                                                                                                                         |



|                           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|---------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>:</code>            | <code>org-agenda-set-tags</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|                           | Set tags for the current headline. If there is an active region in the agenda, change a tag for all headings in the region.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| <code>,</code>            | <code>org-agenda-priority</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|                           | Set the priority for the current item ( <code>org-agenda-priority</code> ). Org mode prompts for the priority character. If you reply with <code>SPC</code> , the priority cookie is removed from the entry.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <code>P</code>            | <code>org-agenda-show-priority</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|                           | Display weighted priority of current item.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <code>+ or S-up</code>    | <code>org-agenda-priority-up</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|                           | Increase the priority of the current item. The priority is changed in the original buffer, but the agenda is not resorted. Use the <code>r</code> key for this.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <code>- or S-down</code>  | <code>org-agenda-priority-down</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|                           | Decrease the priority of the current item.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <code>z or C-c C-z</code> | <code>org-agenda-add-note</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|                           | Add a note to the entry. This note will be recorded, and then filed to the same location where state change notes are put. Depending on <code>org-log-into-drawer</code> , this may be inside a drawer.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| <code>C-c C-a</code>      | <code>org-attach</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|                           | Dispatcher for all command related to attachments.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <code>C-c C-s</code>      | <code>org-agenda-schedule</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|                           | Schedule this item. With prefix arg remove the scheduling timestamp                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <code>C-c C-d</code>      | <code>org-agenda-deadline</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|                           | Set a deadline for this item. With prefix arg remove the deadline.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <code>S-right</code>      | <code>org-agenda-do-date-later</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|                           | Change the timestamp associated with the current line by one day into the future. If the date is in the past, the first call to this command will move it to today.<br>With a numeric prefix argument, change it by that many days. For example, <code>3 6 5 S-right</code> will change it by a year. With a <code>C-u</code> prefix, change the time by one hour. If you immediately repeat the command, it will continue to change hours even without the prefix arg. With a double <code>C-u C-u</code> prefix, do the same for changing minutes.<br>The stamp is changed in the original Org file, but the change is not directly reflected in the agenda buffer. Use <code>r</code> or <code>g</code> to update the buffer. |
| <code>S-left</code>       | <code>org-agenda-do-date-earlier</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|                           | Change the timestamp associated with the current line by one day into the past.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <code>&gt;</code>         | <code>org-agenda-date-prompt</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|                           | Change the timestamp associated with the current line. The key <code>&gt;</code> has been chosen, because it is the same as <code>S-</code> on my keyboard.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| <code>I</code>            | <code>org-agenda-clock-in</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|                           | Start the clock on the current item. If a clock is running already, it is stopped first.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |

|                                               |                                                                                                                                                                                                                                                                                                                                                                                                                                 |                                               |
|-----------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------|
| <i>O</i>                                      |                                                                                                                                                                                                                                                                                                                                                                                                                                 | <code>org-agenda-clock-out</code>             |
|                                               | Stop the previously started clock.                                                                                                                                                                                                                                                                                                                                                                                              |                                               |
| <i>X</i>                                      |                                                                                                                                                                                                                                                                                                                                                                                                                                 | <code>org-agenda-clock-cancel</code>          |
|                                               | Cancel the currently running clock.                                                                                                                                                                                                                                                                                                                                                                                             |                                               |
| <i>J</i>                                      |                                                                                                                                                                                                                                                                                                                                                                                                                                 | <code>org-agenda-clock-goto</code>            |
|                                               | Jump to the running clock in another window.                                                                                                                                                                                                                                                                                                                                                                                    |                                               |
| <i>k</i>                                      |                                                                                                                                                                                                                                                                                                                                                                                                                                 | <code>org-agenda-capture</code>               |
|                                               | Like <code>org-capture</code> , but use the date at point as the default date for the capture template. See <code>org-capture-use-agenda-date</code> to make this the default behavior of <code>org-capture</code> .                                                                                                                                                                                                            |                                               |
| <b>Dragging agenda lines forward/backward</b> |                                                                                                                                                                                                                                                                                                                                                                                                                                 |                                               |
| <i>M-&lt;up&gt;</i>                           |                                                                                                                                                                                                                                                                                                                                                                                                                                 | <code>org-agenda-drag-line-backward</code>    |
|                                               | Drag the line at point backward one line <sup>10</sup> . With a numeric prefix argument, drag backward by that many lines.                                                                                                                                                                                                                                                                                                      |                                               |
| <i>M-&lt;down&gt;</i>                         |                                                                                                                                                                                                                                                                                                                                                                                                                                 | <code>org-agenda-drag-line-forward</code>     |
|                                               | Drag the line at point forward one line. With a numeric prefix argument, drag forward by that many lines.                                                                                                                                                                                                                                                                                                                       |                                               |
| <b>Bulk remote editing selected entries</b>   |                                                                                                                                                                                                                                                                                                                                                                                                                                 |                                               |
| <i>m</i>                                      |                                                                                                                                                                                                                                                                                                                                                                                                                                 | <code>org-agenda-bulk-mark</code>             |
|                                               | Mark the entry at point for bulk action. With numeric prefix argument, mark that many successive entries.                                                                                                                                                                                                                                                                                                                       |                                               |
| <i>*</i>                                      |                                                                                                                                                                                                                                                                                                                                                                                                                                 | <code>org-agenda-bulk-mark-all</code>         |
|                                               | Mark all visible agenda entries for bulk action.                                                                                                                                                                                                                                                                                                                                                                                |                                               |
| <i>u</i>                                      |                                                                                                                                                                                                                                                                                                                                                                                                                                 | <code>org-agenda-bulk-unmark</code>           |
|                                               | Unmark entry at point for bulk action.                                                                                                                                                                                                                                                                                                                                                                                          |                                               |
| <i>U</i>                                      |                                                                                                                                                                                                                                                                                                                                                                                                                                 | <code>org-agenda-bulk-remove-all-marks</code> |
|                                               | Unmark all marked entries for bulk action.                                                                                                                                                                                                                                                                                                                                                                                      |                                               |
| <i>M-m</i>                                    |                                                                                                                                                                                                                                                                                                                                                                                                                                 | <code>org-agenda-bulk-toggle</code>           |
|                                               | Toggle mark of the entry at point for bulk action.                                                                                                                                                                                                                                                                                                                                                                              |                                               |
| <i>M-*</i>                                    |                                                                                                                                                                                                                                                                                                                                                                                                                                 | <code>org-agenda-bulk-toggle-all</code>       |
|                                               | Toggle marks of all visible entries for bulk action.                                                                                                                                                                                                                                                                                                                                                                            |                                               |
| <i>%</i>                                      |                                                                                                                                                                                                                                                                                                                                                                                                                                 | <code>org-agenda-bulk-mark-regexp</code>      |
|                                               | Mark entries matching a regular expression for bulk action.                                                                                                                                                                                                                                                                                                                                                                     |                                               |
| <i>B</i>                                      |                                                                                                                                                                                                                                                                                                                                                                                                                                 | <code>org-agenda-bulk-action</code>           |
|                                               | Bulk action: act on all marked entries in the agenda. This will prompt for another key to select the action to be applied. The prefix arg to <i>B</i> will be passed through to the <i>s</i> and <i>d</i> commands, to bulk-remove these special timestamps. By default, marks are removed after the bulk. If you want them to persist, set <code>org-agenda-persistent-marks</code> to <i>t</i> or hit <i>p</i> at the prompt. |                                               |

<sup>10</sup> Moving agenda lines does not persist after an agenda refresh and does not modify the contributing `.org` files

|           |                                                                                                                                                                                    |
|-----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>*</b>  | Toggle persistent marks.                                                                                                                                                           |
| <b>\$</b> | Archive all selected entries.                                                                                                                                                      |
| <b>A</b>  | Archive entries by moving them to their respective archive siblings.                                                                                                               |
| <b>t</b>  | Change TODO state. This prompts for a single TODO keyword and changes the state of all selected entries, bypassing blocking and suppressing logging notes (but not timestamps).    |
| <b>+</b>  | Add a tag to all selected entries.                                                                                                                                                 |
| <b>-</b>  | Remove a tag from all selected entries.                                                                                                                                            |
| <b>s</b>  | Schedule all items to a new date. To shift existing schedule dates by a fixed number of days, use something starting with double plus at the prompt, for example ‘++8d’ or ‘++2w’. |
| <b>d</b>  | Set deadline to a specific date.                                                                                                                                                   |
| <b>r</b>  | Prompt for a single refile target and move all entries. The entries will no longer be in the agenda; refresh ( <i>g</i> ) to bring them back.                                      |
| <b>S</b>  | Reschedule randomly into the coming N days. N will be prompted for. With prefix arg ( <i>C-u B S</i> ), scatter only across weekdays.                                              |
| <b>f</b>  | Apply a function <sup>11</sup> to marked entries. For example, the function below sets the CATEGORY property of the entries to web.                                                |

```

(defun set-category ()
  (interactive "P")
  (let* ((marker (or (org-get-at-bol 'org-hd-marker)
                     (org-agenda-error)))
        (buffer (marker-buffer marker)))
    (with-current-buffer buffer
      (save-excursion
        (save-restriction
          (widen)
          (goto-char marker)
          (org-back-to-heading t)
          (org-set-property "CATEGORY" "web"))))))

```

### Calendar commands

|          |                                                                                                                                                                                                               |
|----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>c</b> | <b>org-agenda-goto-calendar</b><br>Open the Emacs calendar and move to the date at the agenda cursor.                                                                                                         |
| <b>c</b> | <b>org-calendar-goto-agenda</b><br>When in the calendar, compute and show the Org mode agenda for the date at the cursor.                                                                                     |
| <b>i</b> | <b>org-agenda-diary-entry</b><br>Insert a new entry into the diary, using the date at the cursor and (for block entries) the date at the mark. This will add to the Emacs diary file <sup>12</sup> , in a way |

<sup>11</sup> You can also create persistent custom functions through `org-agenda-bulk-custom-functions`.

<sup>12</sup> This file is parsed for the agenda when `org-agenda-include-diary` is set.

similar to the *i* command in the calendar. The diary file will pop up in another window, where you can add the entry.

If you configure `org-agenda-diary-file` to point to an Org mode file, Org will create entries (in Org mode syntax) in that file instead. Most entries will be stored in a date-based outline tree that will later make it easy to archive appointments from previous months/years. The tree will be built under an entry with a `DATE_TREE` property, or else with years as top-level entries. Emacs will prompt you for the entry text—if you specify it, the entry will be created in `org-agenda-diary-file` without further interaction. If you directly press `RET` at the prompt without typing text, the target file will be shown in another window for you to finish the entry there. See also the *k r* command.

*M* `org-agenda-phases-of-moon`  
Show the phases of the moon for the three months around current date.

*S* `org-agenda-sunrise-sunset`  
Show sunrise and sunset times. The geographical location must be set with calendar variables, see the documentation for the Emacs calendar.

*C* `org-agenda-convert-date`  
Convert the date at cursor into many other cultural and historic calendars.

*H* `org-agenda-holidays`  
Show holidays for three months around the cursor date.

*M-x org-icalendar-combine-agenda-files RET*

Export a single iCalendar file containing entries from all agenda files. This is a globally available command, and also available in the agenda menu.

### Exporting to a file

*C-x C-w* `org-agenda-write`  
Write the agenda view to a file. Depending on the extension of the selected file name, the view will be exported as HTML (`.html` or `.htm`), Postscript (`.ps`), PDF (`.pdf`), Org (`.org`) and plain text (any other extension). When exporting to Org, only the body of original headlines are exported, not subtrees or inherited tags. When called with a *C-u* prefix argument, immediately open the newly created file. Use the variable `org-agenda-exporter-settings` to set options for `ps-print` and for `htmlize` to be used during export.

### Quit and Exit

*q* `org-agenda-quit`  
Quit agenda, remove the agenda buffer.

*x* `org-agenda-exit`  
Exit agenda, remove the agenda buffer and all buffers loaded by Emacs for the compilation of the agenda. Buffers created by the user to visit Org files will not be removed.

## 10.6 Custom agenda views

Custom agenda commands serve two purposes: to store and quickly access frequently used TODO and tags searches, and to create special composite agenda buffers. Custom agenda

commands will be accessible through the dispatcher (see [Section 10.2 \[Agenda dispatcher\]](#), [page 101](#)), just like the default commands.

### 10.6.1 Storing searches

The first application of custom searches is the definition of keyboard shortcuts for frequently used searches, either creating an agenda buffer, or a sparse tree (the latter covering of course only the current buffer).

Custom commands are configured in the variable `org-agenda-custom-commands`. You can customize this variable, for example by pressing `C-c a C`. You can also directly set it with Emacs Lisp in `.emacs`. The following example contains all valid agenda views:

```
(setq org-agenda-custom-commands
      '(("x" agenda)
        ("y" agenda*)
        ("w" todo "WAITING")
        ("W" todo-tree "WAITING")
        ("u" tags "+boss-urgent")
        ("v" tags-todo "+boss-urgent")
        ("U" tags-tree "+boss-urgent")
        ("f" occur-tree "\\<FIXME\\>")
        ("h" . "HOME+Name tags searches") ; description for "h" prefix
        ("hl" tags "+home+Lisa")
        ("hp" tags "+home+Peter")
        ("hk" tags "+home+Kim")))
```

The initial string in each entry defines the keys you have to press after the dispatcher command `C-c a` in order to access the command. Usually this will be just a single character, but if you have many similar commands, you can also define two-letter combinations where the first character is the same in several combinations and serves as a prefix key<sup>13</sup>. The second parameter is the search type, followed by the string or regular expression to be used for the matching. The example above will therefore define:

|                      |                                                                                                                                                                  |
|----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>C-c a x</code> | as a global search for agenda entries planned <sup>14</sup> this week/day.                                                                                       |
| <code>C-c a y</code> | as a global search for agenda entries planned this week/day, but only those with an hour specification like <code>[h]h:mm</code> —think of them as appointments. |
| <code>C-c a w</code> | as a global search for TODO entries with ‘WAITING’ as the TODO keyword                                                                                           |
| <code>C-c a W</code> | as the same search, but only in the current buffer and displaying the results as a sparse tree                                                                   |
| <code>C-c a u</code> | as a global tags search for headlines marked ‘:boss:’ but not ‘:urgent:’                                                                                         |
| <code>C-c a v</code> | as the same search as <code>C-c a u</code> , but limiting the search to headlines that are also TODO items                                                       |

<sup>13</sup> You can provide a description for a prefix key by inserting a cons cell with the prefix and the description.

<sup>14</sup> *Planned* means here that these entries have some planning information attached to them, like a time-stamp, a scheduled or a deadline string. See `org-agenda-entry-types` on how to set what planning information will be taken into account.

- C-c a U** as the same search as **C-c a u**, but only in the current buffer and displaying the result as a sparse tree
- C-c a f** to create a sparse tree (again: current buffer only) with all entries containing the word ‘FIXME’
- C-c a h** as a prefix command for a HOME tags search where you have to press an additional key (*l*, *p* or *k*) to select a name (Lisa, Peter, or Kim) as additional tag to match.

Note that the **\*-tree** agenda views need to be called from an Org buffer as they operate on the current buffer only.

### 10.6.2 Block agenda

Another possibility is the construction of agenda views that comprise the results of *several* commands, each of which creates a block in the agenda buffer. The available commands include **agenda** for the daily or weekly agenda (as created with **C-c a a**), **alltodo** for the global TODO list (as constructed with **C-c a t**), and the matching commands discussed above: **todo**, **tags**, and **tags-todo**. Here are two examples:

```
(setq org-agenda-custom-commands
  '(("h" "Agenda and Home-related tasks"
    ((agenda "")
     (tags-todo "home")
     (tags "garden"))))
  ("o" "Agenda and Office-related tasks"
    ((agenda "")
     (tags-todo "work")
     (tags "office")))))
```

This will define **C-c a h** to create a multi-block view for stuff you need to attend to at home. The resulting agenda buffer will contain your agenda for the current week, all TODO items that carry the tag ‘home’, and also all lines tagged with ‘garden’. Finally the command **C-c a o** provides a similar view for office tasks.

### 10.6.3 Setting options for custom commands

Org mode contains a number of variables regulating agenda construction and display. The global variables define the behavior for all agenda commands, including the custom commands. However, if you want to change some settings just for a single custom view, you can do so. Setting options requires inserting a list of variable names and values at the right spot in **org-agenda-custom-commands**. For example:

```
(setq org-agenda-custom-commands
  '(("w" todo "WAITING"
    ((org-agenda-sorting-strategy '(priority-down))
     (org-agenda-prefix-format " Mixed: "))
    ("U" tags-tree "+boss-urgent"
     ((org-show-context-detail 'minimal)))
    ("N" search ""
     ((org-agenda-files '("~/org/notes.org"))
      (org-agenda-text-search-extra-files nil)))))
```

Now the `C-c a w` command will sort the collected entries only by priority, and the prefix format is modified to just say ‘Mixed:’ instead of giving the category of the entry. The sparse tags tree of `C-c a U` will now turn out ultra-compact, because neither the headline hierarchy above the match, nor the headline following the match will be shown. The command `C-c a N` will do a text search limited to only a single file.

For command sets creating a block agenda, `org-agenda-custom-commands` has two separate spots for setting options. You can add options that should be valid for just a single command in the set, and options that should be valid for all commands in the set. The former are just added to the command entry; the latter must come after the list of command entries. Going back to the block agenda example (see [Section 10.6.2 \[Block agenda\]](#), [page 123](#)), let’s change the sorting strategy for the `C-c a h` commands to `priority-down`, but let’s sort the results for GARDEN tags query in the opposite order, `priority-up`. This would look like this:

```
(setq org-agenda-custom-commands
      '(("h" "Agenda and Home-related tasks"
         ((agenda)
          (tags-todo "home")
          (tags "garden"
               ((org-agenda-sorting-strategy '(priority-up))))))
        ((org-agenda-sorting-strategy '(priority-down))))
      ("o" "Agenda and Office-related tasks"
         ((agenda)
          (tags-todo "work")
          (tags "office")))))
```

As you see, the values and parentheses setting is a little complex. When in doubt, use the customize interface to set this variable—it fully supports its structure. Just one caveat: when setting options in this interface, the *values* are just Lisp expressions. So if the value is a string, you need to add the double-quotes around the value yourself.

To control whether an agenda command should be accessible from a specific context, you can customize `org-agenda-custom-commands-contexts`. Let’s say for example that you have an agenda command “o” displaying a view that you only need when reading emails. Then you would configure this option like this:

```
(setq org-agenda-custom-commands-contexts
      '(("o" (in-mode . "message-mode"))))
```

You can also tell that the command key “o” should refer to another command key “r”. In that case, add this command key like this:

```
(setq org-agenda-custom-commands-contexts
      '(("o" "r" (in-mode . "message-mode"))))
```

See the docstring of the variable for more information.

## 10.7 Exporting agenda views

If you are away from your computer, it can be very useful to have a printed version of some agenda views to carry around. Org mode can export custom agenda views as plain text,

HTML<sup>15</sup>, Postscript, PDF<sup>16</sup>, and iCalendar files. If you want to do this only occasionally, use the command

```
C-x C-w                                     org-agenda-write

Write the agenda view to a file. Depending on the extension of the selected file
name, the view will be exported as HTML (extension .html or .htm), Postscript
(extension .ps), iCalendar (extension .ics), or plain text (any other extension).
Use the variable org-agenda-exporter-settings to set options for ps-print
and for htmlize to be used during export, for example

(setq org-agenda-exporter-settings
      '((ps-number-of-columns 2)
        (ps-landscape-mode t)
        (org-agenda-add-entry-text-maxlines 5)
        (htmlize-output-type 'css)))
```

If you need to export certain agenda views frequently, you can associate any custom agenda command with a list of output file names<sup>17</sup>. Here is an example that first defines custom commands for the agenda and the global TODO list, together with a number of files to which to export them. Then we define two block agenda commands and specify file names for them as well. File names can be relative to the current working directory, or absolute.

```
(setq org-agenda-custom-commands
      '(("X" agenda "" nil ("agenda.html" "agenda.ps"))
        ("Y" alltodo "" nil ("todo.html" "todo.txt" "todo.ps"))
        ("h" "Agenda and Home-related tasks"
          ((agenda "")
            (tags-todo "home")
            (tags "garden")))
          nil
          ("~/views/home.html"))
        ("o" "Agenda and Office-related tasks"
          ((agenda)
            (tags-todo "work")
            (tags "office")))
          nil
          ("~/views/office.ps" "~/calendars/office.ics")))))
```

The extension of the file name determines the type of export. If it is `.html`, Org mode will use the `htmlize.el` package to convert the buffer to HTML and save it to this file name. If the extension is `.ps`, `ps-print-buffer-with-faces` is used to produce Postscript output. If the extension is `.ics`, iCalendar export is run export over all files that were used to construct the agenda, and limit the export to entries listed in the agenda. Any other extension produces a plain ASCII file.

<sup>15</sup> You need to install Hrvoje Niksic's `htmlize.el`.

<sup>16</sup> To create PDF output, the ghostscript `ps2pdf` utility must be installed on the system. Selecting a PDF file will also create the postscript file.

<sup>17</sup> If you want to store standard views like the weekly agenda or the global TODO list as well, you need to define custom commands for them in order to be able to specify file names.



The export files are *not* created when you use one of those commands interactively because this might use too much overhead. Instead, there is a special command to produce *all* specified files in one step:

**C-c a e** **org-store-agenda-views**  
 Export all agenda views that have export file names associated with them.

You can use the options section of the custom agenda commands to also set options for the export commands. For example:

```
(setq org-agenda-custom-commands
      '(("X" agenda ""
          ((ps-number-of-columns 2)
           (ps-landscape-mode t)
           (org-agenda-prefix-format " [ ] ")
           (org-agenda-with-colors nil)
           (org-agenda-remove-tags t))
          ("theagenda.ps"))))
```

This command sets two options for the Postscript exporter, to make it print in two columns in landscape format—the resulting page can be cut in two and then used in a paper agenda. The remaining settings modify the agenda prefix to omit category and scheduling information, and instead include a checkbox to check off items. We also remove the tags to make the lines compact, and we don't want to use colors for the black-and-white printer. Settings specified in `org-agenda-exporter-settings` will also apply, but the settings in `org-agenda-custom-commands` take precedence.

From the command line you may also use

```
emacs -eval (org-batch-store-agenda-views) -kill
```

or, if you need to modify some parameters<sup>18</sup>

```
emacs -eval '(org-batch-store-agenda-views \
              org-agenda-span (quote month) \
              org-agenda-start-day "2007-11-01" \
              org-agenda-include-diary nil \
              org-agenda-files (quote ("~/org/project.org")))' \
  -kill
```

which will create the agenda views restricted to the file `~/org/project.org`, without diary entries and with a 30-day extent.

You can also extract agenda information in a way that allows further processing by other programs. See [Section A.10 \[Extracting agenda information\]](#), page 247, for more information.

## 10.8 Using column view in the agenda

Column view (see [Section 7.5 \[Column view\]](#), page 67) is normally used to view and edit properties embedded in the hierarchical structure of an Org file. It can be quite useful to use column view also from the agenda, where entries are collected by certain criteria.

<sup>18</sup> Quoting depends on the system you use, please check the FAQ for examples.

`C-c C-x C-c`

`org-agenda-columns`

Turn on column view in the agenda.

To understand how to use this properly, it is important to realize that the entries in the agenda are no longer in their proper outline environment. This causes the following issues:

1. Org needs to make a decision which `COLUMNS` format to use. Since the entries in the agenda are collected from different files, and different files may have different `COLUMNS` formats, this is a non-trivial problem. Org first checks if the variable `org-agenda-overriding-columns-format` is currently set, and if so, takes the format from there. Otherwise it takes the format associated with the first item in the agenda, or, if that item does not have a specific format (defined in a property, or in its file), it uses `org-columns-default-format`.
2. If any of the columns has a summary type defined (see [Section 7.5.1.2 \[Column attributes\]](#), page 68), turning on column view in the agenda will visit all relevant agenda files and make sure that the computations of this property are up to date. This is also true for the special `CLOCKSUM` property. Org will then sum the values displayed in the agenda. In the daily/weekly agenda, the sums will cover a single day; in all other views they cover the entire block. It is vital to realize that the agenda may show the same entry *twice* (for example as scheduled and as a deadline), and it may show two entries from the same hierarchy (for example a *parent* and its *child*). In these cases, the summation in the agenda will lead to incorrect results because some values will count double.
3. When the column view in the agenda shows the `CLOCKSUM`, that is always the entire clocked time for this item. So even in the daily/weekly agenda, the clocksum listed in column view may originate from times outside the current view. This has the advantage that you can compare these values with a column listing the planned total effort for a task—one of the major applications for column view in the agenda. If you want information about clocked time in the displayed period use clock table mode (press `R` in the agenda).
4. When the column view in the agenda shows the `CLOCKSUM_T`, that is always today's clocked time for this item. So even in the weekly agenda, the clocksum listed in column view only originates from today. This lets you compare the time you spent on a task for today, with the time already spent (via `CLOCKSUM`) and with the planned total effort for it.

## 11 Markup for rich export

When exporting Org mode documents, the exporter tries to reflect the structure of the document as accurately as possible in the back-end. Since export targets like HTML and L<sup>A</sup>T<sub>E</sub>X allow much richer formatting, Org mode has rules on how to prepare text for rich export. This section summarizes the markup rules used in an Org mode buffer.

### 11.1 Paragraphs, line breaks, and quoting

Paragraphs are separated by at least one empty line. If you need to enforce a line break within a paragraph, use ‘\\’ at the end of a line.

To preserve the line breaks, indentation and blank lines in a region, but otherwise use normal formatting, you can use this construct, which can also be used to format poetry.

```
#+BEGIN_VERSE
Great clouds overhead
Tiny black birds rise and fall
Snow covers Emacs

-- AlexSchroeder
#+END_VERSE
```

When quoting a passage from another document, it is customary to format this as a paragraph that is indented on both the left and the right margin. You can include quotations in Org mode documents like this:

```
#+BEGIN_QUOTE
Everything should be made as simple as possible,
but not any simpler -- Albert Einstein
#+END_QUOTE
```

If you would like to center some text, do it like this:

```
#+BEGIN_CENTER
Everything should be made as simple as possible, \\
but not any simpler
#+END_CENTER
```

### 11.2 Emphasis and monospace

You can make words ***=verbatim=*** and `~code~`, and, if you must, ~~+strike-through+~~. Text in the code and verbatim string is not processed for Org mode specific syntax, it is exported verbatim.

To turn off fontification for marked up text, you can set `org-fontify-emphasized-text` to `nil`. To narrow down the list of available markup syntax, you can customize `org-emphasis-alist`. To fine tune what characters are allowed before and after the markup characters, you can tweak `org-emphasis-regexp-components`. Beware that changing one of the above variables will no take effect until you reload Org, for which you may need to restart Emacs.

## 11.3 Horizontal rules

A line consisting of only dashes, and at least 5 of them, will be exported as a horizontal line.

## 11.4 Images and Tables

Both the native Org mode tables (see [Chapter 3 \[Tables\]](#), page 19) and tables formatted with the `table.el` package will be exported properly. For Org mode tables, the lines before the first horizontal separator line will become table header lines. You can use the following lines somewhere before the table to assign a caption and a label for cross references, and in the text you can refer to the object with `[[tab:basic-data]]` (see [Section 4.2 \[Internal links\]](#), page 38):

```
#+CAPTION: This is the caption for the next table (or link)
#+NAME:    tab:basic-data
...	...
```

Optionally, the caption can take the form:

```
#+CAPTION[Caption for list of tables]: Caption for table.
```

Some back-ends allow you to directly include images into the exported document. Org does this, if a link to an image files does not have a description part, for example `[[./img/a.jpg]]`. If you wish to define a caption for the image and maybe a label for internal cross references, make sure that the link is on a line by itself and precede it with `#+CAPTION` and `#+NAME` as follows:

```
#+CAPTION: This is the caption for the next figure link (or table)
#+NAME:    fig:SED-HR4049
[[./img/a.jpg]]
```

Such images can be displayed within the buffer. See [Section 4.4 \[Handling links\]](#), page 41.

Even though images and tables are prominent examples of captioned structures, the same caption mechanism can apply to many others (e.g.,  $\text{\LaTeX}$  equations, source code blocks). Depending on the export back-end, those may or may not be handled.

## 11.5 Literal examples

You can include literal examples that should not be subjected to markup. Such examples will be typeset in monospace, so this is well suited for source code and similar examples.

```
#+BEGIN_EXAMPLE
Some example from a text file.
#+END_EXAMPLE
```

Note that such blocks may be *indented* in order to align nicely with indented text and in particular with plain list structure (see [Section 2.7 \[Plain lists\]](#), page 12). For simplicity when using small examples, you can also start the example lines with a colon followed by a space. There may also be additional whitespace before the colon:

```
Here is an example
  : Some example from a text file.
```

If the example is source code from a programming language, or any other text that can be marked up by font-lock in Emacs, you can ask for the example to look like the fontified Emacs buffer<sup>1</sup>. This is done with the ‘src’ block, where you also need to specify the name of the major mode that should be used to fontify the example<sup>2</sup>, see [Section 15.2 \[Easy templates\]](#), page 224 for shortcuts to easily insert code blocks.

```
#+BEGIN_SRC emacs-lisp
  (defun org-xor (a b)
    "Exclusive or."
    (if a (not b) b))
#+END_SRC
```

Both in `example` and in `src` snippets, you can add a `-n` switch to the end of the `BEGIN` line, to get the lines of the example numbered. The `-n` takes an optional numeric argument specifying the starting line number of the block. If you use a `+n` switch, the numbering from the previous numbered snippet will be continued in the current one. The `+n` can also take a numeric argument. The value of the argument will be added to the last line of the previous block to determine the starting line number.

```
#+BEGIN_SRC emacs-lisp -n 20
  ;; this will export with line number 20
  (message "This is line 21")
#+END_SRC
#+BEGIN_SRC emacs-lisp +n 10
  ;; This will be listed as line 31
  (message "This is line 32")
#+END_SRC
```

In literal examples, Org will interpret strings like ‘(ref:name)’ as labels, and use them as targets for special hyperlinks like `[[name]]` (i.e., the reference name enclosed in single parenthesis). In HTML, hovering the mouse over such a link will remote-highlight the corresponding code line, which is kind of cool.

You can also add a `-r` switch which *removes* the labels from the source code<sup>3</sup>. With the `-n` switch, links to these references will be labeled by the line numbers from the code listing, otherwise links will use the labels with no parentheses. Here is an example:

```
#+BEGIN_SRC emacs-lisp -n -r
  (save-excursion                                (ref:sc)
    (goto-char (point-min)))                      (ref:jump)
#+END_SRC
In line [[sc]] we remember the current position. [[jump]] [Line (jump)]
jumps to point-min.
```

<sup>1</sup> This works automatically for the HTML back-end (it requires version 1.34 of the `htmlize.el` package, which is distributed with Org). Fontified code chunks in L<sup>A</sup>T<sub>E</sub>X can be achieved using either the `listings` or the `minted` package. If you use `minted` or `listings`, you must load the packages manually, for example by adding the desired package to `org-latex-packages-alist`. Refer to `org-latex-listings` for details.

<sup>2</sup> Code in ‘src’ blocks may also be evaluated either interactively or on export. See [Chapter 14 \[Working with source code\]](#), page 194 for more information on evaluating code blocks.

<sup>3</sup> Adding `-k` to `-n -r` will *keep* the labels in the source code while using line numbers for the links, which might be useful to explain those in an Org mode example code.

Finally, you can use `-i` to preserve the indentation of a specific code block (see [Section 14.2 \[Editing source code\]](#), page 195).

If the syntax for the label format conflicts with the language syntax, use a `-l` switch to change the format, for example `#+BEGIN_SRC pascal -n -r -l "((%s))"`. See also the variable `org-coderef-label-format`.

HTML export also allows examples to be published as text areas (see [Section 12.9.10 \[Text areas in HTML export\]](#), page 152).

Because the `#+BEGIN_...` and `#+END_...` patterns need to be added so often, shortcuts are provided using the Easy templates facility (see [Section 15.2 \[Easy templates\]](#), page 224).

- `C-c '`      Edit the source code example at point in its native mode. This works by switching to a temporary buffer with the source code. You need to exit by pressing `C-c '` again<sup>4</sup>. The edited version will then replace the old version in the Org buffer. Fixed-width regions (where each line starts with a colon followed by a space) will be edited using `artist-mode`<sup>5</sup> to allow creating ASCII drawings easily. Using this command in an empty line will create a new fixed-width region.
- `C-c l`      Calling `org-store-link` while editing a source code example in a temporary buffer created with `C-c '` will prompt for a label. Make sure that it is unique in the current buffer, and insert it with the proper formatting like `(ref:label)` at the end of the current line. Then the label is stored as a link `(label)`, for retrieval with `C-c C-l`.

## 11.6 Special symbols

You can use  $\text{\LaTeX}$ -like syntax to insert special symbols—named entities—like `\alpha` to indicate the Greek letter, or `\to` to indicate an arrow. Completion for these symbols is available, just type `\` and maybe a few letters, and press `M-TAB` to see possible completions. If you need such a symbol inside a word, terminate it with a pair of curly brackets. For example

Protip: Given a circle `\Gamma` of diameter `d`, the length of its circumference is `\pi{d}`.

A large number of entities is provided, with names taken from both HTML and  $\text{\LaTeX}$ ; you can comfortably browse the complete list from a dedicated buffer using the command `org-entities-help`. It is also possible to provide your own special symbols in the variable `org-entities-user`.

During export, these symbols are transformed into the native format of the exporter back-end. Strings like `\alpha` are exported as `&alpha;` in the HTML output, and as `\(\alpha\)` in the  $\text{\LaTeX}$  output. Similarly, `\nbsp` becomes `&nbsp;` in HTML and `~` in  $\text{\LaTeX}$ .

Entities may also be used as a way to escape markup in an Org document, e.g., `\under{}not underlined\under` exports as `_not underlined_`.

<sup>4</sup> Upon exit, lines starting with `'*`, `*,*`, `#+` and `*,#+` will get a comma prepended, to keep them from being interpreted by Org as outline nodes or special syntax. These commas will be stripped for editing with `C-c '`, and also for export.

<sup>5</sup> You may select a different mode with the variable `org-edit-fixed-width-region-mode`.

If you would like to see entities displayed as UTF-8 characters, use the following command<sup>6</sup>:

**C-c C-x \** Toggle display of entities as UTF-8 characters. This does not change the buffer content which remains plain ASCII, but it overlays the UTF-8 character for display purposes only.

In addition to regular entities defined above, Org exports in a special way<sup>7</sup> the following commonly used character combinations: ‘\-’ is treated as a shy hyphen, ‘--’ and ‘---’ are converted into dashes, and ‘...’ becomes a compact set of dots.

## 11.7 Subscripts and superscripts

‘^’ and ‘\_’ are used to indicate super- and subscripts. To increase the readability of ASCII text, it is not necessary—but OK—to surround multi-character sub- and superscripts with curly braces. Those are, however, mandatory, when more than one word is involved. For example

The radius of the sun is  $R_{\text{sun}} = 6.96 \times 10^8 \text{ m}$ . On the other hand, the radius of Alpha Centauri is  $R_{\{\text{Alpha Centauri}\}} = 1.28 \times R_{\{\text{sun}\}}$ .

If you write a text where the underscore is often used in a different context, Org’s convention to always interpret these as subscripts can get in your way. Configure the variable `org-use-sub-superscripts` to change this convention. For example, when setting this variable to `{}`, ‘a\_b’ will not be interpreted as a subscript, but ‘a\_{b}’ will.

**C-c C-x \** In addition to showing entities as UTF-8 characters, this command will also format sub- and superscripts in a WYSIWYM way.

## 11.8 Embedded L<sup>A</sup>T<sub>E</sub>X

Plain ASCII is normally sufficient for almost all note taking. Exceptions include scientific notes, which often require mathematical symbols and the occasional formula. L<sup>A</sup>T<sub>E</sub>X<sup>8</sup> is widely used to typeset scientific documents. Org mode supports embedding L<sup>A</sup>T<sub>E</sub>X code into its files, because many academics are used to writing and reading L<sup>A</sup>T<sub>E</sub>X source code, and because it can be readily processed to produce pretty output for a number of export back-ends.

### 11.8.1 L<sup>A</sup>T<sub>E</sub>X fragments

Org mode can contain L<sup>A</sup>T<sub>E</sub>X math fragments, and it supports ways to process these for several export back-ends. When exporting to L<sup>A</sup>T<sub>E</sub>X, the code is left as it is. When exporting to HTML, Org can use either **MathJax** (see [Section 12.9.9 \[Math formatting in HTML export\]](#), page 151) or transcode the math into images (see [Section 11.8.2 \[Previewing L<sup>A</sup>T<sub>E</sub>X fragments\]](#), page 133).

L<sup>A</sup>T<sub>E</sub>X fragments don’t need any special marking at all. The following snippets will be identified as L<sup>A</sup>T<sub>E</sub>X source code:

<sup>6</sup> You can turn this on by default by setting the variable `org-pretty-entities`, or on a per-file base with the `#+STARTUP` option `entitiespretty`.

<sup>7</sup> This behaviour can be disabled with `- export` setting (see [Section 12.2 \[Export settings\]](#), page 136).

<sup>8</sup> L<sup>A</sup>T<sub>E</sub>X is a macro system based on Donald E. Knuth’s T<sub>E</sub>X system. Many of the features described here as “L<sup>A</sup>T<sub>E</sub>X” are really from T<sub>E</sub>X, but for simplicity I am blurring this distinction.

- Environments of any kind<sup>9</sup>. The only requirement is that the `\begin` statement appears on a new line, at the beginning of the line or after whitespaces only.
- Text within the usual  $\LaTeX$  math delimiters. To avoid conflicts with currency specifications, single ‘\$’ characters are only recognized as math delimiters if the enclosed text contains at most two line breaks, is directly attached to the ‘\$’ characters with no whitespace in between, and if the closing ‘\$’ is followed by whitespace or punctuation (parentheses and quotes are considered to be punctuation in this context). For the other delimiters, there is no such restriction, so when in doubt, use ‘`\(...\)`’ as inline math delimiters.

For example:

```
\begin{equation}
x=\sqrt{b}
\end{equation}
```

If  $a^2=b$  and  $(b=2)$ , then the solution must be either  $a=+\sqrt{2}$  or  $a=-\sqrt{2}$ .

$\LaTeX$  processing can be configured with the variable `org-export-with-latex`. The default setting is `t` which means MathJax for HTML, and no processing for ASCII and  $\LaTeX$  back-ends. You can also set this variable on a per-file basis using one of these lines:

```
#+OPTIONS: tex:t           Do the right thing automatically (MathJax)
#+OPTIONS: tex:nil        Do not process  $\LaTeX$  fragments at all
#+OPTIONS: tex:verbatim   Verbatim export, for jsMath or so
```

### 11.8.2 Previewing $\LaTeX$ fragments

If you have a working  $\LaTeX$  installation and `dvipng`, `dvisvgm` or `convert` installed<sup>10</sup>,  $\LaTeX$  fragments can be processed to produce images of the typeset expressions to be used for inclusion while exporting to HTML (see see [Section 11.8.1 \[ \$\LaTeX\$  fragments\]](#), page 132), or for inline previewing within Org mode.

You can customize the variables `org-format-latex-options` and `org-format-latex-header` to influence some aspects of the preview. In particular, the `:scale` (and for HTML export, `:html-scale`) property of the former can be used to adjust the size of the preview images.

**`C-c C-x C-l`**

Produce a preview image of the  $\LaTeX$  fragment at point and overlay it over the source code. If there is no fragment at point, process all fragments in the current entry (between two headlines). When called with a prefix argument, process the entire subtree. When called with two prefix arguments, or when the cursor is before the first headline, process the entire buffer.

**`C-c C-c`** Remove the overlay preview images.

<sup>9</sup> When MathJax is used, only the environments recognized by MathJax will be processed. When `dvipng` program, `dvisvgm` program or `imagemagick` suite is used to create images, any  $\LaTeX$  environment will be handled.

<sup>10</sup> These are respectively available at <http://sourceforge.net/projects/dvipng/>, <http://dvisvgm.bplaced.net/> and from the `imagemagick` suite. Choose the converter by setting the variable `org-preview-latex-default-process` accordingly.



You can turn on the previewing of all  $\text{\LaTeX}$  fragments in a file with

```
#+STARTUP: latexpreview
```

To disable it, simply use

```
#+STARTUP: nolatexpreview
```

### 11.8.3 Using $\text{CD}\text{\LaTeX}$ to enter math

$\text{CD}\text{\LaTeX}$  mode is a minor mode that is normally used in combination with a major  $\text{\LaTeX}$  mode like  $\text{AUC}\text{\LaTeX}$  in order to speed-up insertion of environments and math templates. Inside Org mode, you can make use of some of the features of  $\text{CD}\text{\LaTeX}$  mode. You need to install `cdlatex.el` and `texmathp.el` (the latter comes also with  $\text{AUC}\text{\LaTeX}$ ) from <http://www.astro.uva.nl/~dominik/Tools/cdlatex>. Don't use  $\text{CD}\text{\LaTeX}$  mode itself under Org mode, but use the light version `org-cdlatex-mode` that comes as part of Org mode. Turn it on for the current buffer with *M-x org-cdlatex-mode RET*, or for all Org files with

```
(add-hook 'org-mode-hook 'turn-on-org-cdlatex)
```

When this mode is enabled, the following features are present (for more details see the documentation of  $\text{CD}\text{\LaTeX}$  mode):

- Environment templates can be inserted with *C-c {*.
- The **TAB** key will do template expansion if the cursor is inside a  $\text{\LaTeX}$  fragment<sup>11</sup>. For example, **TAB** will expand `fr` to `\frac{}{}` and position the cursor correctly inside the first brace. Another **TAB** will get you into the second brace. Even outside fragments, **TAB** will expand environment abbreviations at the beginning of a line. For example, if you write 'equ' at the beginning of a line and press **TAB**, this abbreviation will be expanded to an `equation` environment. To get a list of all abbreviations, type *M-x cdlatex-command-help RET*.
- Pressing `_` and `^` inside a  $\text{\LaTeX}$  fragment will insert these characters together with a pair of braces. If you use **TAB** to move out of the braces, and if the braces surround only a single character or macro, they are removed again (depending on the variable `cdlatex-simplify-sub-super-scripts`).
- Pressing the grave accent ``` followed by a character inserts math macros, also outside  $\text{\LaTeX}$  fragments. If you wait more than 1.5 seconds after the grave accent, a help window will pop up.
- Pressing the apostrophe `'` followed by another character modifies the symbol before point with an accent or a font. If you wait more than 1.5 seconds after the apostrophe, a help window will pop up. Character modification will work only inside  $\text{\LaTeX}$  fragments; outside the quote is normal.

<sup>11</sup> Org mode has a method to test if the cursor is inside such a fragment, see the documentation of the function `org-inside-LaTeX-fragment-p`.

## 12 Exporting

Sometimes, you may want to pretty print your notes, publish them on the web or even share them with people not using Org. In these cases, the Org export facilities can be used to convert your documents to a variety of other formats, while retaining as much structure (see [Chapter 2 \[Document structure\]](#), page 6) and markup (see [Chapter 11 \[Markup\]](#), page 128) as possible.

Libraries responsible for such translation are called back-ends. Org ships with the following ones

- `ascii` (ASCII format)
- `beamer` (L<sup>A</sup>T<sub>E</sub>X Beamer format)
- `html` (HTML format)
- `icalendar` (iCalendar format)
- `latex` (L<sup>A</sup>T<sub>E</sub>X format)
- `md` (Markdown format)
- `odt` (OpenDocument Text format)
- `org` (Org format)
- `texinfo` (Texinfo format)
- `man` (Man page format)

More of them can be found in the `contrib/` directory (see [Section 1.2 \[Installation\]](#), page 2) or through the Emacs packaging system<sup>1</sup>.

By default, the following five back-ends are loaded: `ascii`, `html`, `icalendar`, `latex` and `odt`. Others need to be specifically loaded, either by customizing `org-export-backends`, or by requiring the associated library, e.g.,

```
(require 'ox-md)
```

Eventually, you can these facilities can be used with `orgtbl-mode` or `orgstruct-mode` in foreign buffers so you can author tables and lists in Org syntax and convert them in place to the target language.

### 12.1 The export dispatcher

The main entry point for export related tasks is the dispatcher, a hierarchical menu from which it is possible to select an export format and toggle export options<sup>2</sup>.

|                                                                                                                                                                                                                                                                                                            |                                  |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------|
| <code>C-c C-e</code>                                                                                                                                                                                                                                                                                       | <code>org-export-dispatch</code> |
| Dispatch for export and publishing commands. When called with a <code>C-u</code> prefix argument, repeat the last export command on the current buffer while preserving toggled options. If the current buffer hasn't changed and subtree export was activated, the command will affect that same subtree. |                                  |

<sup>1</sup> These libraries traditionnaly appear as `ox-NAME`, e.g., `ox-koma-letter` for `koma-letter` back-end.

<sup>2</sup> It is also possible to use a less intrusive interface by setting `org-export-dispatch-use-expert-ui` to a non-`nil` value. In that case, only a prompt is visible from the minibuffer. From there one can still switch back to regular menu by pressing `?`.

Normally the entire buffer is exported, but if there is an active region only that part of the buffer will be exported.

Several export options (see [Section 12.2 \[Export settings\], page 136](#)) can be toggled from the export dispatcher with the following key combinations:

- C-a**      Toggle asynchronous export. Asynchronous export uses an external Emacs process that is configured with a specified initialization file.  
While exporting asynchronously, the output is not displayed, but stored in a place called “the export stack”. This stack can be displayed by calling the dispatcher with a double **C-u** prefix argument, or with **&** key from the dispatcher menu.  
To make this behavior the default, customize the variable `org-export-in-background`.
- C-b**      Toggle body-only export. Its effect depends on the back-end used. Typically, if the back-end has a header section (like `<head>...</head>` in the HTML back-end), a body-only export will not include this header.
- C-s**      Toggle subtree export. The top heading becomes the document title.  
You can change the default state of this option by setting `org-export-initial-scope`.
- C-v**      Toggle visible-only export. Only export the text that is currently visible, i.e., not hidden by outline visibility in the buffer.

## 12.2 Export settings

Export options can be set: globally with variables; for an individual file by making variables buffer-local with in-buffer settings (see [Section 15.6 \[In-buffer settings\], page 226](#)), by setting individual keywords, or by specifying them in a compact form with the `#+OPTIONS` keyword; or for a tree by setting properties (see [Chapter 7 \[Properties and columns\], page 64](#)). Options set at a specific level override options set at a more general level.

In-buffer settings may appear anywhere in the file, either directly or indirectly through a file included using `'#+SETUPFILE: filename'` syntax. Option keyword sets tailored to a particular back-end can be inserted from the export dispatcher (see [Section 12.1 \[The export dispatcher\], page 135](#)) using the `Insert template` command by pressing **#**. To insert keywords individually, a good way to make sure the keyword is correct is to type `#+` and then to use `M-<TAB>` for completion.

The export keywords available for every back-end, and their equivalent global variables, include:

- `'AUTHOR'`    The document author (`user-full-name`).
- `'CREATOR'`   Entity responsible for output generation (`org-export-creator-string`).
- `'DATE'`      A date or a time-stamp<sup>3</sup>.
- `'EMAIL'`     The email address (`user-mail-address`).

---

<sup>3</sup> The variable `org-export-date-timestamp-format` defines how this time-stamp will be exported.

**‘LANGUAGE’**

The language used for translating some strings (`org-export-default-language`). E.g., `#+LANGUAGE: fr` will tell Org to translate *File* (english) into *Fichier* (french) in the clocktable.

**‘SELECT\_TAGS’**

The tags that select a tree for export (`org-export-select-tags`). The default value is `:export:`. Within a subtree tagged with `:export:`, you can still exclude entries with `:noexport:` (see below). When headlines are selectively exported with `:export:` anywhere in a file, text before the first headline is ignored.

**‘EXCLUDE\_TAGS’**

The tags that exclude a tree from export (`org-export-exclude-tags`). The default value is `:noexport:`. Entries with the `:noexport:` tag will be unconditionally excluded from the export, even if they have an `:export:` tag. Code blocks contained in excluded subtrees will still be executed during export even though the subtree is not exported.

**‘TITLE’**      The title to be shown. You can use several such keywords for long titles.

The `#+OPTIONS` keyword is a compact<sup>4</sup> form that recognizes the following arguments:

- ‘:**            Toggle smart quotes (`org-export-with-smart-quotes`). When activated, pairs of double quotes become primary quotes according to the language used. Inside, pairs of single quotes become secondary quotes. Other single quotes are treated as apostrophes.
- \*:**            Toggle emphasized text (`org-export-with-emphasize`).
- :**            Toggle conversion of special strings (`org-export-with-special-strings`).
- ::**            Toggle fixed-width sections (`org-export-with-fixed-width`).
- <:**            Toggle inclusion of any time/date active/inactive stamps (`org-export-with-timestamps`).
- \n:**           Toggle line-break-preservation (`org-export-preserve-breaks`).
- ^:**            Toggle TeX-like syntax for sub- and superscripts. If you write `"^:{ }"`, `‘a_{b}’` will be interpreted, but the simple `‘a_b’` will be left as it is (`org-export-with-sub-superscripts`).
- arch:**        Configure export of archived trees. Can be set to `headline` to only process the headline, skipping its contents (`org-export-with-archived-trees`).
- author:**     Toggle inclusion of author name into exported file (`org-export-with-author`).
- broken-links:**  
                 Decide whether to raise an error or not when encountering a broken internal link. When set to `mark`, signal the problem clearly in the output (`org-export-with-broken-links`).
- c:**            Toggle inclusion of CLOCK keywords (`org-export-with-clocks`).

---

<sup>4</sup> If you want to configure many options this way, you can use several `#+OPTIONS` lines.

|                   |                                                                                                                                                                                                                                                                                                                                                                   |
|-------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>creator:</b>   | Toggle inclusion of creator info into exported file ( <code>org-export-with-creator</code> ).                                                                                                                                                                                                                                                                     |
| <b>d:</b>         | Toggle inclusion of drawers, or list drawers to include ( <code>org-export-with-drawers</code> ).                                                                                                                                                                                                                                                                 |
| <b>date:</b>      | Toggle inclusion of a date into exported file ( <code>org-export-with-date</code> ).                                                                                                                                                                                                                                                                              |
| <b>e:</b>         | Toggle inclusion of entities ( <code>org-export-with-entities</code> ).                                                                                                                                                                                                                                                                                           |
| <b>email:</b>     | Toggle inclusion of the author's e-mail into exported file ( <code>org-export-with-email</code> ).                                                                                                                                                                                                                                                                |
| <b>f:</b>         | Toggle the inclusion of footnotes ( <code>org-export-with-footnotes</code> ).                                                                                                                                                                                                                                                                                     |
| <b>H:</b>         | Set the number of headline levels for export ( <code>org-export-headline-levels</code> ). Below that level, headlines are treated differently. In most back-ends, they become list items.                                                                                                                                                                         |
| <b>inline:</b>    | Toggle inclusion of inlinetasks ( <code>org-export-with-inlinetasks</code> ).                                                                                                                                                                                                                                                                                     |
| <b>num:</b>       | Toggle section-numbers ( <code>org-export-with-section-numbers</code> ). It can also be set to a number 'n', so only headlines at that level or above will be numbered. Finally, irrespective of the level of a specific headline, the numbering of it can be disabled by setting the <code>UNNUMBERED</code> property to non-nil. This also affects subheadings. |
| <b>p:</b>         | Toggle export of planning information ( <code>org-export-with-planning</code> ). "Planning information" is the line containing the <code>SCHEDULED:</code> , the <code>DEADLINE:</code> or the <code>CLOSED:</code> cookies or a combination of them.                                                                                                             |
| <b>pri:</b>       | Toggle inclusion of priority cookies ( <code>org-export-with-priority</code> ).                                                                                                                                                                                                                                                                                   |
| <b>prop:</b>      | Toggle inclusion of property drawers, or list properties to include ( <code>org-export-with-properties</code> ).                                                                                                                                                                                                                                                  |
| <b>stat:</b>      | Toggle inclusion of statistics cookies ( <code>org-export-with-statistics-cookies</code> ).                                                                                                                                                                                                                                                                       |
| <b>tags:</b>      | Toggle inclusion of tags, may also be <code>not-in-toc</code> ( <code>org-export-with-tags</code> ).                                                                                                                                                                                                                                                              |
| <b>tasks:</b>     | Toggle inclusion of tasks (TODO items), can be <code>nil</code> to remove all tasks, <code>todo</code> to remove DONE tasks, or a list of keywords to keep ( <code>org-export-with-tasks</code> ).                                                                                                                                                                |
| <b>tex:</b>       | Configure export of $\text{\LaTeX}$ fragments and environments. It may be set to <code>verbatim</code> ( <code>org-export-with-latex</code> ).                                                                                                                                                                                                                    |
| <b>timestamp:</b> | Toggle inclusion of the creation time into exported file ( <code>org-export-time-stamp-file</code> ).                                                                                                                                                                                                                                                             |
| <b>title:</b>     | Toggle inclusion of title ( <code>org-export-with-title</code> ).                                                                                                                                                                                                                                                                                                 |
| <b>toc:</b>       | Toggle inclusion of the table of contents, or set the level limit ( <code>org-export-with-toc</code> ).                                                                                                                                                                                                                                                           |
| <b>todo:</b>      | Toggle inclusion of TODO keywords into exported text ( <code>org-export-with-todo-keywords</code> ).                                                                                                                                                                                                                                                              |

|:           Toggle inclusion of tables (`org-export-with-tables`).

When exporting only a subtree, each of the previous keywords<sup>5</sup> can be overridden locally by special node properties. These begin with ‘`EXPORT_`’, followed by the name of the keyword they supplant. For example, ‘`DATE`’ and ‘`OPTIONS`’ keywords become, respectively, ‘`EXPORT_DATE`’ and ‘`EXPORT_OPTIONS`’ properties.

If `org-export-allow-bind-keywords` is non-`nil`, Emacs variables can become buffer-local during export by using the `BIND` keyword. Its syntax is ‘`#+BIND: variable value`’. This is particularly useful for in-buffer settings that cannot be changed using specific keywords.

The name of the output file to be generated is taken from the file associated to the buffer, when possible, or asked to you otherwise. For subtree export, you can also set `EXPORT_FILE_NAME` property. In all cases, only the base name of the file is retained, and a back-end specific extension is added.

## 12.3 Table of contents

The table of contents is normally inserted directly before the first headline of the file. The depth of the table is by default the same as the number of headline levels, but you can choose a smaller number, or turn off the table of contents entirely, by configuring the variable `org-export-with-toc`, or on a per-file basis with a line like

```
#+OPTIONS: toc:2          only include two levels in TOC
#+OPTIONS: toc:nil        no default TOC at all
```

If you would like to move the table of contents to a different location, you should turn off the default table using `org-export-with-toc` or `#+OPTIONS` and insert `#+TOC: headlines N` at the desired location(s).

```
#+OPTIONS: toc:nil        no default TOC
...
#+TOC: headlines 2        insert TOC here, with two headline levels
```

Moreover, if you append ‘`local`’ parameter, the table contains only entries for the children of the current section<sup>6</sup>. In this case, any depth parameter becomes relative to the current level.

```
* Section
#+TOC: headlines 1 local  insert local TOC, with direct children only
```

The same TOC keyword can also generate a list of all tables (resp. all listings) with a caption in the document.

```
#+TOC: listings          build a list of listings
#+TOC: tables            build a list of tables
```

The headline’s title usually determines its corresponding entry in a table of contents. However, it is possible to specify an alternative title by setting `ALT_TITLE` property accordingly. It will then be used when building the table.

<sup>5</sup> With the exception of ‘`SETUPFILE`’.

<sup>6</sup> For `LATEX` export, this feature requires the `titletoc` package. Note that `titletoc` must be loaded *before* `hyperref`. Thus, you may have to customize `org-latex-default-packages-alist`.

## 12.4 Include files

During export, you can include the content of another file. For example, to include your `.emacs` file, you could use:

```
#+INCLUDE: "~/emacs" src emacs-lisp
```

The first parameter names the file to include. The optional second and third parameter specify the markup (i.e., ‘`example`’, ‘`export`’ or ‘`src`’), and, if the markup is either ‘`export`’ or ‘`src`’, the language for formatting the contents.

If markup is requested, the included content will be placed within an appropriate block<sup>7</sup>. No changes to the included content are made and it is the responsibility of the user to ensure that the result is valid Org syntax. For markup ‘`example`’ and ‘`src`’, which is requesting a literal example, the content will be code-escaped before inclusion.

If no markup is requested, the text will be assumed to be in Org mode format and will be processed normally. However, footnote labels (see [Section 2.10 \[Footnotes\]](#), page 16) in the file will be made local to that file. Contents of the included file will belong to the same structure (headline, item) containing the `INCLUDE` keyword. In particular, headlines within the file will become children of the current section. That behavior can be changed by providing an additional keyword parameter, `:minlevel`. In that case, all headlines in the included file will be shifted so the one with the lowest level reaches that specified level. For example, to make a file become a sibling of the current top-level headline, use

```
#+INCLUDE: "~/my-book/chapter2.org" :minlevel 1
```

You can also include a portion of a file by specifying a lines range using the `:lines` keyword parameter. The line at the upper end of the range will not be included. The start and/or the end of the range may be omitted to use the obvious defaults.

```
#+INCLUDE: "~/emacs" :lines "5-10"    Include lines 5 to 10, 10 excluded
#+INCLUDE: "~/emacs" :lines "-10"     Include lines 1 to 10, 10 excluded
#+INCLUDE: "~/emacs" :lines "10-"     Include lines from 10 to EOF
```

Finally, you may use a file-link to extract an object as matched by `org-link-search`<sup>8</sup> (see [Section 4.7 \[Search options\]](#), page 45). If the `:only-contents` property is non-`nil`, only the contents of the requested element will be included, omitting properties drawer and planning-line if present. The `:lines` keyword operates locally with respect to the requested element. Some examples:

```
#+INCLUDE: "./paper.org::#theory" :only-contents t
    Include the body of the heading with the custom id ‘theory’
#+INCLUDE: "./paper.org::mytable"  Include named element.
#+INCLUDE: "./paper.org::*conclusion" :lines 1-20
    Include the first 20 lines of the headline named ‘conclusion’.
```

**C-c '** Visit the include file at point.

<sup>7</sup> While you can request paragraphs (‘`verse`’, ‘`quote`’, ‘`center`’), but this places severe restrictions on the type of content that is permissible

<sup>8</sup> Note that `org-link-search-must-match-exact-headline` is locally bound to non-`nil`. Therefore, `org-link-search` only matches headlines and named elements.

## 12.5 Macro replacement

You can define text snippets with

```
#+MACRO: name replacement text $1, $2 are arguments
```

which can be referenced `{{{name(arg1, arg2)}}}`<sup>9</sup>.

These references, called macros, can be inserted anywhere Org markup is recognized: paragraphs, headlines, verse blocks, tables cells and lists. They can also be used in keywords accepting Org syntax, e.g., `#+CAPTION`, `#+TITLE`, `#+AUTHOR`, `#+DATE` and some others, export back-end specific, ones.

In addition to user-defined macros, a set of predefined macros can be used:

```
{{{title}}}
{{{author}}}
{{{email}}}
```

These macros are replaced with the information available at the time of export.

```
{{{date}}}
{{{date(FORMAT)}}}
```

This macro refers to the `#+DATE` keyword. *FORMAT* is an optional argument to the `{{{date}}}` macro that will be used only if `#+DATE` is a single timestamp. *FORMAT* should be a format string understood by `format-time-string`.

```
{{{time(FORMAT)}}}
{{{modification-time(FORMAT, VC)}}}
```

These macros refer to the date and time when the document is exported and to the modification date and time, respectively. *FORMAT* should be a format string understood by `format-time-string`. If the second argument to the `modification-time` macro is non-`nil`, Org retrieves the information from the version control system, using `vc.el`, instead of the file attributes.

```
{{{input-file}}}
```

This macro refers to the filename of the exported file, if any.

```
{{{property(PROPERTY-NAME)}}}
{{{property(PROPERTY-NAME, SEARCH-OPTION)}}}
```

This macro returns the value of property *PROPERTY-NAME* in current entry. If *SEARCH-OPTION* (see [Section 4.7 \[Search options\]](#), page 45) refers to a remote entry, it will be used instead.

The surrounding brackets can be made invisible by setting `org-hide-macro-markers` non-`nil`.

Macro expansion takes place during the very beginning of the export process.

---

<sup>9</sup> Since commas separate arguments, commas within arguments have to be escaped with a backslash character. Conversely, backslash characters before a comma, and only them, need to be escaped with another backslash character.



## 12.6 Comment lines

Lines starting with zero or more whitespace characters followed by one ‘#’ and a whitespace are treated as comments and, as such, are not exported.

Likewise, regions surrounded by ‘#+BEGIN\_COMMENT’ ... ‘#+END\_COMMENT’ are not exported.

Finally, a ‘COMMENT’ keyword at the beginning of an entry, but after any other keyword or priority cookie, comments out the entire subtree. In this case, the subtree is not exported and no code block within it is executed either<sup>10</sup>. The command below helps changing the comment status of a headline.

**C-c ;**      Toggle the ‘COMMENT’ keyword at the beginning of an entry.

## 12.7 ASCII/Latin-1/UTF-8 export

ASCII export produces a simple and very readable version of an Org mode file, containing only plain ASCII. Latin-1 and UTF-8 export augment the file with special characters and symbols available in these encodings.

Upon exporting, text is filled and justified, when appropriate, according the text width set in `org-ascii-text-width`.

Links are exported in a footnote-like style, with the descriptive part in the text and the link in a note before the next heading. See the variable `org-ascii-links-to-notes` for details and other options.

### ASCII export commands

**C-c C-e t a/l/u**      `org-ascii-export-to-ascii`  
Export as an ASCII file. For an Org file, `myfile.org`, the ASCII file will be `myfile.txt`. The file will be overwritten without warning. When the original file is `myfile.txt`, the resulting file becomes `myfile.txt.txt` in order to prevent data loss.

**C-c C-e t A/L/U**      `org-ascii-export-as-ascii`  
Export to a temporary buffer. Do not create a file.

### ASCII specific export settings

ASCII export introduces a single of keywords, similar to the general options settings described in [Section 12.2 \[Export settings\]](#), page 136.

‘SUBTITLE’

The document subtitle.

### Header and sectioning structure

In the exported version, the first three outline levels become headlines, defining a general document structure. Additional levels are exported as lists. The transition can also occur at a different level (see [Section 12.2 \[Export settings\]](#), page 136).

<sup>10</sup> For a less drastic behavior, consider using a select tag (see [Section 12.2 \[Export settings\]](#), page 136) instead.

## Quoting ASCII text

You can insert text that will only appear when using ASCII back-end with the following constructs:

```
Text @@ascii:and additional text@@ within a paragraph.

#+ASCII: Some text

#+BEGIN_EXPORT ascii
All lines in this block will appear only when using this back-end.
#+END_EXPORT
```

## ASCII specific attributes

ASCII back-end only understands one attribute, `:width`, which specifies the length, in characters, of a given horizontal rule. It must be specified using an `ATTR_ASCII` line, directly preceding the rule.

```
#+ATTR_ASCII: :width 10
-----
```

## ASCII special blocks

In addition to `#+BEGIN_CENTER` blocks (see [Section 11.1 \[Paragraphs\], page 128](#)), it is possible to justify contents to the left or the right of the page with the following dedicated blocks.

```
#+BEGIN_JUSTIFYLEFT
It's just a jump to the left...
#+END_JUSTIFYLEFT

#+BEGIN_JUSTIFYRIGHT
...and then a step to the right.
#+END_JUSTIFYRIGHT
```

## 12.8 Beamer export

The  $\text{\LaTeX}$  class *Beamer* allows production of high quality presentations using  $\text{\LaTeX}$  and PDF processing. Org mode has special support for turning an Org mode file or tree into a Beamer presentation.

### 12.8.1 Beamer export commands

|                                                                                                                                                                                      |                                         |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------|
| <code>C-c C-e l b</code>                                                                                                                                                             | <code>org-beamer-export-to-latex</code> |
| Export as a $\text{\LaTeX}$ file. For an Org file <code>myfile.org</code> , the $\text{\LaTeX}$ file will be <code>myfile.tex</code> . The file will be overwritten without warning. |                                         |
| <code>C-c C-e l B</code>                                                                                                                                                             | <code>org-beamer-export-as-latex</code> |
| Export to a temporary buffer. Do not create a file.                                                                                                                                  |                                         |
| <code>C-c C-e l P</code>                                                                                                                                                             | <code>org-beamer-export-to-pdf</code>   |
| Export as $\text{\LaTeX}$ and then process to PDF.                                                                                                                                   |                                         |

*C-c C-e l O*

Export as L<sup>A</sup>T<sub>E</sub>X and then process to PDF, then open the resulting PDF file.

### 12.8.2 Beamer specific export settings

Beamer export introduces a number of keywords, similar to the general options settings described in [Section 12.2 \[Export settings\]](#), page 136.

`'BEAMER_THEME'`

The Beamer theme (`org-beamer-theme`). Options can be specified via brackets, for example:

```
#+BEAMER_THEME: Rochester [height=20pt]
```

`'BEAMER_FONT_THEME'`

The Beamer font theme.

`'BEAMER_INNER_THEME'`

The Beamer inner theme.

`'BEAMER_OUTER_THEME'`

The Beamer outer theme.

`'BEAMER_HEADER'`

Arbitrary lines inserted into the preamble, just before the `'hyperref'` settings.

`'DESCRIPTION'`

The document description. By default these are inserted as metadata using `'hyperref'`. Document metadata can be configured via `org-latex-hyperref-template`. Description can also be typeset as part of the front matter via `org-latex-title-command`. You can use several `#+DESCRIPTION` keywords if the description is is long.

`'KEYWORDS'`

The keywords defining the contents of the document. By default these are inserted as metadata using `'hyperref'`. Document metadata can be configured via `org-latex-hyperref-template`. Description can also be typeset as part of the front matter via `org-latex-title-command`. You can use several `#+KEYWORDS` if the description is is long.

`'SUBTITLE'`

The document subtitle. This is typeset using the format string `org-beamer-subtitle-format`. It can also access via `org-latex-hyperref-template` or typeset as part of the front matter via `org-latex-title-command`.

### 12.8.3 Sectioning, Frames and Blocks in Beamer

Any tree with not-too-deep level nesting should in principle be exportable as a Beamer presentation. Headlines fall into three categories: sectioning elements, frames and blocks.

- Headlines become frames when their level is equal to `org-beamer-frame-level` or `H` value in an `OPTIONS` line (see [Section 12.2 \[Export settings\]](#), page 136).

Though, if a headline in the current tree has a `BEAMER_ENV` property set to either to `frame` or `fullframe`, its level overrides the variable. A `fullframe` is a frame with an empty (ignored) title.

- All frame’s children become **block** environments. Special block types can be enforced by setting headline’s `BEAMER_ENV` property<sup>11</sup> to an appropriate value (see `org-beamer-environments-default` for supported values and `org-beamer-environments-extra` for adding more).
- As a special case, if the `BEAMER_ENV` property is set to either **appendix**, **note**, **noteNH** or **againframe**, the headline will become, respectively, an appendix, a note (within frame or between frame, depending on its level), a note with its title ignored or an `\againframe` command. In the latter case, a `BEAMER_REF` property is mandatory in order to refer to the frame being resumed, and contents are ignored.

Also, a headline with an `ignoreheading` environment will have its contents only inserted in the output. This special value is useful to have data between frames, or to properly close a `column` environment.

Headlines also support `BEAMER_ACT` and `BEAMER_OPT` properties. The former is translated as an overlay/action specification, or a default overlay specification when enclosed within square brackets. The latter specifies options<sup>12</sup> for the current frame or block. The export back-end will automatically wrap properties within angular or square brackets when appropriate.

Moreover, headlines handle the `BEAMER_COL` property. Its value should be a decimal number representing the width of the column as a fraction of the total text width. If the headline has no specific environment, its title will be ignored and its contents will fill the column created. Otherwise, the block will fill the whole column and the title will be preserved. Two contiguous headlines with a non-`nil` `BEAMER_COL` value share the same `columns` `LATEX` environment. It will end before the next headline without such a property. This environment is generated automatically. Although, it can also be explicitly created, with a special `columns` value for `BEAMER_ENV` property (if it needs to be set up with some specific options, for example).

#### 12.8.4 Beamer specific syntax

The Beamer back-end is an extension of the `LATEX` back-end. As such, all `LATEX` specific syntax (e.g., `#+LATEX:` or `#+ATTR_LATEX:`) is recognized. See [Section 12.10 \[L<sup>A</sup>T<sub>E</sub>X export\]](#), [page 154](#) for more information.

Table of contents generated from `toc:t` `OPTION` keyword are wrapped within a **frame** environment. Those generated from a `TOC` keyword (see [Section 12.3 \[Table of contents\]](#), [page 139](#)) are not. In that case, it is also possible to specify options, enclosed within square brackets.

```
#+TOC: headlines [currentsection]
```

Beamer specific code can be inserted with the following constructs:

```
#+BEAMER: \pause
```

```
#+BEGIN_EXPORT beamer
```

<sup>11</sup> If this property is set, the entry will also get a `:B_environment:` tag to make this visible. This tag has no semantic meaning, it is only a visual aid.

<sup>12</sup> The `fragile` option is added automatically if it contains code that requires a verbatim environment, though.

```
All lines in this block will appear only when using this back-end.
#+END_BEAMER
```

```
Text @@beamer:some code@@ within a paragraph.
```

In particular, this last example can be used to add overlay specifications to objects whose type is among `bold`, `item`, `link`, `radio-target` and `target`, when the value is enclosed within angular brackets and put at the beginning the object.

```
A *@@beamer:<2->@@useful* feature
```

Eventually, every plain list has support for `:environment`, `:overlay` and `:options` attributes through `ATTR_BEAMER` affiliated keyword. The first one allows the use of a different environment, the second sets overlay specifications and the last one inserts optional arguments in current list environment.

```
#+ATTR_BEAMER: :overlay +-
- item 1
- item 2
```

### 12.8.5 Editing support

You can turn on a special minor mode `org-beamer-mode` for faster editing with:

```
#+STARTUP: beamer
```

*C-c C-b*

`org-beamer-select-environment`

In `org-beamer-mode`, this key offers fast selection of a Beamer environment or the `BEAMER_COL` property.

### 12.8.6 A Beamer example

Here is a simple example Org document that is intended for Beamer export.

```
#+TITLE: Example Presentation
#+AUTHOR: Carsten Dominik
#+OPTIONS: H:2 toc:t num:t
#+LATEX_CLASS: beamer
#+LATEX_CLASS_OPTIONS: [presentation]
#+BEAMER_THEME: Madrid
#+COLUMNS: %45ITEM %10BEAMER_ENV(Env) %10BEAMER_ACT(Act) %4BEAMER_COL(Col) %8BEAMER_OP

* This is the first structural section

** Frame 1
*** Thanks to Eric Fraga                                     :B_block:
    :PROPERTIES:
    :BEAMER_COL: 0.48
    :BEAMER_ENV: block
    :END:
    for the first viable Beamer setup in Org
*** Thanks to everyone else                                   :B_block:
    :PROPERTIES:
    :BEAMER_COL: 0.48
```

```

:BEAMER_ACT: <2->
:BEAMER_ENV: block
:END:
for contributing to the discussion
**** This will be formatted as a beamer note                                :B_note:
:PROPERTIES:
:BEAMER_env: note
:END:
** Frame 2 (where we will not use columns)
*** Request
    Please test this stuff!

```

## 12.9 HTML export

Org mode contains an HTML (XHTML 1.0 strict) exporter with extensive HTML formatting, in ways similar to John Gruber's *markdown* language, but with additional support for tables.

### 12.9.1 HTML export commands

```

C-c C-e h h                                org-html-export-to-html
Export as an HTML file. For an Org file myfile.org, the HTML file will
be myfile.html. The file will be overwritten without warning. C-c C-e h o
Export as an HTML file and immediately open it with a browser.

C-c C-e h H                                org-html-export-as-html
Export to a temporary buffer. Do not create a file.

```

### 12.9.2 HTML Specific export settings

HTML export introduces a number of keywords, similar to the general options settings described in [Section 12.2 \[Export settings\]](#), page 136.

'DESCRIPTION'

The document description. This description is inserted as a HTML meta tag. You can use several such keywords if the list is long.

'HTML\_DOCTYPE'

The document type, e.g. HTML5, (`org-html-doctype`).

'HTML\_CONTAINER'

The container, e.g. 'div', used to wrap sections and elements (`org-html-container-element`).

'HTML\_LINK\_HOME'

The home link URL (`org-html-link-home`).

'HTML\_LINK\_UP'

The up link URL (`org-html-link-up`).

'HTML\_MATHJAX'

Options for the MathJax (`org-html-mathjax-options`). MathJax is used to typeset L<sup>A</sup>T<sub>E</sub>X math in HTML documents. [Section 12.9.9 \[Math formatting in HTML export\]](#), page 151 contains an example.

- ‘HTML\_HEAD’**  
Arbitrary lines appended to the end of the head of the document (`org-html-head`).
- ‘HTML\_HEAD\_EXTRA’**  
Arbitrary lines appended to the end of the header of the document (`org-html-head-extra`).
- ‘KEYWORDS’**  
The keywords defining the contents of the document. This description is inserted as a HTML meta tag. You can use several such keywords if the list is long.
- ‘LATEX\_HEADER’**  
Arbitrary lines appended to the preamble used when transcoding  $\text{\LaTeX}$  fragments to images. See [Section 12.9.9 \[Math formatting in HTML export\]](#), [page 151](#) for details.
- ‘SUBTITLE’**  
The document subtitle. The formatting depends on whether HTML5 is used and on the `‘subtitle’` CSS class.

These keywords are treated in details in the following sections.

### 12.9.3 HTML doctypes

Org can export to various (X)HTML flavors.

Setting the variable `org-html-doctype` allows you to export to different (X)HTML variants. The exported HTML will be adjusted according to the syntax requirements of that variant. You can either set this variable to a doctype string directly, in which case the exporter will try to adjust the syntax automatically, or you can use a ready-made doctype. The ready-made options are:

- “html4-strict”
- “html4-transitional”
- “html4-frameset”
- “xhtml-strict”
- “xhtml-transitional”
- “xhtml-frameset”
- “xhtml-11”
- “html5”
- “xhtml5”

See the variable `org-html-doctype-alist` for details. The default is “xhtml-strict”.

HTML5 introduces several new element types. By default, Org will not make use of these element types, but you can set `org-html-html5-fancy` to `non-nil` (or set `html5-fancy` item in an `OPTIONS` line), to enable a few new block-level elements. These are created using arbitrary `#+BEGIN` and `#+END` blocks. For instance:

```
#+BEGIN_aside
Lorem ipsum
#+END_aside
```

Will export to:

```
<aside>
  <p>Lorem ipsum</p>
</aside>
```

While this:

```
#+ATTR_HTML: :controls controls :width 350
#+BEGIN_video
#+HTML: <source src="movie.mp4" type="video/mp4">
#+HTML: <source src="movie.ogg" type="video/ogg">
Your browser does not support the video tag.
#+END_video
```

Becomes:

```
<video controls="controls" width="350">
  <source src="movie.mp4" type="video/mp4">
  <source src="movie.ogg" type="video/ogg">
  <p>Your browser does not support the video tag.</p>
</video>
```

Special blocks that do not correspond to HTML5 elements (see `org-html-html5-elements`) will revert to the usual behavior, i.e., `#+BEGIN_lederhosen` will still export to `<div class="lederhosen">`.

Headlines cannot appear within special blocks. To wrap a headline and its contents in e.g., `<section>` or `<article>` tags, set the `HTML_CONTAINER` property on the headline itself.

### 12.9.4 HTML preamble and postamble

The HTML exporter lets you define a preamble and a postamble.

The default value for `org-html-preamble` is `t`, which means that the preamble is inserted depending on the relevant format string in `org-html-preamble-format`.

Setting `org-html-preamble` to a string will override the default format string. If you set it to a function, it will insert the output of the function, which must be a string. Setting to `nil` will not insert any preamble.

The default value for `org-html-postamble` is `'auto`, which means that the HTML exporter will look for information about the author, the email, the creator and the date, and build the postamble from these values. Setting `org-html-postamble` to `t` will insert the postamble from the relevant format string found in `org-html-postamble-format`. Setting it to `nil` will not insert any postamble.

### 12.9.5 Quoting HTML tags

Plain `<` and `>` are always transformed to `&lt;` and `&gt;` in HTML export. If you want to include raw HTML code, which should only appear in HTML export, mark it with `@html:` as in `@html:<b>@bold text@html:</b>@html:`. For more extensive HTML that should be copied verbatim to the exported file use either



```

#+HTML: Literal HTML code for export
or
#+BEGIN_EXPORT html
All lines between these markers are exported literally
#+END_EXPORT

```

### 12.9.6 Links in HTML export

Internal links (see [Section 4.2 \[Internal links\]](#), page 38) will continue to work in HTML. This includes automatic links created by radio targets (see [Section 4.2.1 \[Radio targets\]](#), page 39). Links to external files will still work if the target file is on the same *relative* path as the published Org file. Links to other `.org` files will be translated into HTML links under the assumption that an HTML version also exists of the linked file, at the same relative path; setting `org-html-link-org-files-as-html` to `nil` disables this translation. ‘`id:`’ links can then be used to jump to specific entries across files. For information related to linking files while publishing them to a publishing directory see [Section 13.1.6 \[Publishing links\]](#), page 189.

If you want to specify attributes for links, you can do so using a special `#+ATTR_HTML` line to define attributes that will be added to the `<a>` or `<img>` tags. Here is an example that sets `title` and `style` attributes for a link:

```

#+ATTR_HTML: :title The Org mode homepage :style color:red;
[[http://orgmode.org]]

```

### 12.9.7 Tables in HTML export

Org mode tables are exported to HTML using the table attributes defined in `org-html-table-default-attributes`. The default setting makes tables without cell borders and frame. If you would like to change this for individual tables, place something like the following before the table:

```

#+CAPTION: This is a table with lines around and between cells
#+ATTR_HTML: :border 2 :rules all :frame border

```

You can also group columns in the HTML output (see [Section 3.3 \[Column groups\]](#), page 23).

Below is a list of options for customizing tables HTML export.

`org-html-table-align-individual-fields`

Non-`nil` means attach style attributes for alignment to each table field.

`org-html-table-caption-above`

When non-`nil`, place caption string at the beginning of the table.

`org-html-table-data-tags`

The opening and ending tags for table data fields.

`org-html-table-default-attributes`

Default attributes and values which will be used in table tags.

`org-html-table-header-tags`

The opening and ending tags for table header fields.

`org-html-table-row-tags`

The opening and ending tags for table rows.

`org-html-table-use-header-tags-for-first-column`

Non-nil means format column one in tables with header tags.

### 12.9.8 Images in HTML export

HTML export can inline images given as links in the Org file, and it can make an image the clickable part of a link. By default<sup>13</sup>, images are inlined if a link does not have a description. So `'[[file:myimg.jpg]]'` will be inlined, while `'[[file:myimg.jpg][the image]]'` will just produce a link `'the image'` that points to the image. If the description part itself is a `file:` link or a `http:` URL pointing to an image, this image will be inlined and activated so that clicking on the image will activate the link. For example, to include a thumbnail that will link to a high resolution version of the image, you could use:

```
[[file:highres.jpg][file:thumb.jpg]]
```

If you need to add attributes to an inlined image, use a `#+ATTR_HTML`. In the example below we specify the `alt` and `title` attributes to support text viewers and accessibility, and align it to the right.

```
#+CAPTION: A black cat stalking a spider
#+ATTR_HTML: :alt cat/spider image :title Action! :align right
[[./img/a.jpg]]
```

You could use `http` addresses just as well.

### 12.9.9 Math formatting in HTML export

$\text{\LaTeX}$  math snippets (see [Section 11.8.1 \[ \$\text{\LaTeX}\$  fragments\]](#), page 132) can be displayed in two different ways on HTML pages. The default is to use [MathJax](#) which should work out of the box with Org<sup>14</sup>. Some MathJax display options can be configured via `org-html-mathjax-options`, or in the buffer. For example, with the following settings,

```
#+HTML_MATHJAX: align: left indent: 5em tagside: left font: Neo-Euler
```

equation labels will be displayed on the left margin and equations will be five ems from the left margin.

See the docstring of `org-html-mathjax-options` for all supported variables. The MathJax template can be configure via `org-html-mathjax-template`.

If you prefer, you can also request that  $\text{\LaTeX}$  fragments are processed into small images that will be inserted into the browser page. Before the availability of MathJax, this was the default method for Org files. This method requires that the `dvipng` program, `dvisvgm` or `imagemagick` suite is available on your system. You can still get this processing with

```
#+OPTIONS: tex:dvipng
#+OPTIONS: tex:dvisvgm
```

or:

```
#+OPTIONS: tex:imagemagick
```

<sup>13</sup> But see the variable `org-html-inline-images`.

<sup>14</sup> By default Org loads MathJax from [MathJax.org](#). A link to the terms of service of the MathJax CDN can be found in the docstring of `org-html-mathjax-options`.

### 12.9.10 Text areas in HTML export

An alternative way to publish literal code examples in HTML is to use text areas, where the example can even be edited before pasting it into an application. It is triggered by `:textarea` attribute at an `example` or `src` block.

You may also use `:height` and `:width` attributes to specify the height and width of the text area, which default to the number of lines in the example, and 80, respectively. For example

```
#+ATTR_HTML: :textarea t :width 40
#+BEGIN_EXAMPLE
  (defun org-xor (a b)
    "Exclusive or."
    (if a (not b) b))
#+END_EXAMPLE
```

### 12.9.11 CSS support

You can modify the CSS style definitions for the exported file. The HTML exporter assigns the following special CSS classes<sup>15</sup> to appropriate parts of the document—your style specifications may change these, in addition to any of the standard classes like for headlines, tables, etc.

<code>p.author</code>	author information, including email
<code>p.date</code>	publishing date
<code>p.creator</code>	creator info, about org mode version
<code>.title</code>	document title
<code>.subtitle</code>	document subtitle
<code>.todo</code>	TODO keywords, all not-done states
<code>.done</code>	the DONE keywords, all states that count as done
<code>.WAITING</code>	each TODO keyword also uses a class named after itself
<code>.timestamp</code>	timestamp
<code>.timestamp-kwd</code>	keyword associated with a timestamp, like SCHEDULED
<code>.timestamp-wrapper</code>	span around keyword plus timestamp
<code>.tag</code>	tag in a headline
<code>._HOME</code>	each tag uses itself as a class, "@" replaced by "_"
<code>.target</code>	target for links
<code>.linenr</code>	the line number in a code example
<code>.code-highlighted</code>	for highlighting referenced code lines
<code>div.outline-N</code>	div for outline level N (headline plus text))
<code>div.outline-text-N</code>	extra div for text at outline level N
<code>.section-number-N</code>	section number in headlines, different for each level
<code>.figure-number</code>	label like "Figure 1:"
<code>.table-number</code>	label like "Table 1:"
<code>.listing-number</code>	label like "Listing 1:"
<code>div.figure</code>	how to format an inlined image
<code>pre.src</code>	formatted source code

<sup>15</sup> If the classes on TODO keywords and tags lead to conflicts, use the variables `org-html-todo-kwd-class-prefix` and `org-html-tag-class-prefix` to make them unique.

<code>pre.example</code>	normal example
<code>p.verse</code>	verse paragraph
<code>div.footnotes</code>	footnote section headline
<code>p.footnote</code>	footnote definition paragraph, containing a footnote
<code>.footref</code>	a footnote reference number (always a <code>&lt;sup&gt;</code> )
<code>.footnum</code>	footnote number in footnote definition (always <code>&lt;sup&gt;</code> )
<code>.org-svg</code>	default class for a linked <code>.svg</code> image

Each exported file contains a compact default style that defines these classes in a basic way<sup>16</sup>. You may overwrite these settings, or add to them by using the variables `org-html-head` and `org-html-head-extra`. You can override the global values of these variables for each file by using these keywords:

```
#+HTML_HEAD: <link rel="stylesheet" type="text/css" href="style1.css" />
#+HTML_HEAD_EXTRA: <link rel="alternate stylesheet" type="text/css" href="style2.css"
```

For longer style definitions, you can use several such lines. You could also directly write a `<style> </style>` section in this way, without referring to an external file.

In order to add styles to a subtree, use the `:HTML_CONTAINER_CLASS:` property to assign a class to the tree. In order to specify CSS styles for a particular headline, you can use the id specified in a `:CUSTOM_ID:` property.

### 12.9.12 JavaScript supported display of web pages

Sebastian Rose has written a JavaScript program especially designed to enhance the web viewing experience of HTML files created with Org. This program allows you to view large files in two different ways. The first one is an *Info*-like mode where each section is displayed separately and navigation can be done with the `n` and `p` keys (and some other keys as well, press `?` for an overview of the available keys). The second view type is a *folding* view much like Org provides inside Emacs. The script is available at <http://orgmode.org/org-info.js> and you can find the documentation for it at <http://orgmode.org/worg/code/org-info-js/>. We host the script at our site, but if you use it a lot, you might not want to be dependent on <http://orgmode.org> and prefer to install a local copy on your own web server.

All it then takes to use this program is adding a single line to the Org file:

```
#+INFOJS_OPT: view:info toc:nil
```

If this line is found, the HTML header will automatically contain the code needed to invoke the script. Using the line above, you can set the following viewing options:

<b>path:</b>	The path to the script. The default is to grab the script from <a href="http://orgmode.org/org-info.js">http://orgmode.org/org-info.js</a> , but you might want to have a local copy and use a path like <code>../scripts/org-info.js</code> .
<b>view:</b>	Initial view when the website is first shown. Possible values are:
<b>info</b>	Info-like interface with one section per page.
<b>overview</b>	Folding interface, initially showing only top-level.
<b>content</b>	Folding interface, starting with all headlines visible.

<sup>16</sup> This style is defined in the constant `org-html-style-default`, which you should not modify. To turn inclusion of these defaults off, customize `org-html-head-include-default-style` or set `html-style` to `nil` in an `OPTIONS` line.

- `showall` Folding interface, all headlines and text visible.
- `sdepth:` Maximum headline level that will still become an independent section for info and folding modes. The default is taken from `org-export-headline-levels` (= the `H` switch in `#+OPTIONS`). If this is smaller than in `org-export-headline-levels`, each info/folding section can still contain child headlines.
- `toc:` Should the table of contents *initially* be visible? Even when `nil`, you can always get to the "toc" with `i`.
- `tdepth:` The depth of the table of contents. The defaults are taken from the variables `org-export-headline-levels` and `org-export-with-toc`.
- `ftoc:` Does the CSS of the page specify a fixed position for the "toc"? If yes, the toc will never be displayed as a section.
- `ltoc:` Should there be short contents (children) in each section? Make this `above` if the section should be above initial text.
- `mouse:` Headings are highlighted when the mouse is over them. Should be `'underline'` (default) or a background color like `'#cccccc'`.
- `buttons:` Should view-toggle buttons be everywhere? When `nil` (the default), only one such button will be present.

You can choose default values for these options by customizing the variable `org-html-infojs-options`. If you always want to apply the script to your pages, configure the variable `org-html-use-infojs`.

## 12.10 $\text{\LaTeX}$ export

The  $\text{\LaTeX}$  exporter can produce an arbitrarily complex  $\text{\LaTeX}$  document of any standard or custom document class<sup>17</sup>. The Org  $\text{\LaTeX}$  exporter is geared towards producing fully-linked PDF output.

As in  $\text{\LaTeX}$ , blank lines are meaningful for this back-end: a paragraph will not be started if two contiguous syntactical elements are not separated by an empty line.

### 12.10.1 $\text{\LaTeX}$ export commands

- `C-c C-e l l` `org-latex-export-to-latex`  
Export as a  $\text{\LaTeX}$  file. For an Org file `myfile.org`, the  $\text{\LaTeX}$  file will be `myfile.tex`. The file will be overwritten without warning.
- `C-c C-e l L` `org-latex-export-as-latex`  
Export to a temporary buffer. Do not create a file.
- `C-c C-e l p` `org-latex-export-to-pdf`  
Export as  $\text{\LaTeX}$  and then process to PDF.
- `C-c C-e l o`  
Export as  $\text{\LaTeX}$  and then process to PDF, then open the resulting PDF file.

The exporter supports several  $\text{\LaTeX}$  engines, namely `'pdflatex'`, `'xelatex'` and `'lualatex'`. The default  $\text{\LaTeX}$  compiler can be set via `org-latex-compiler` or the

<sup>17</sup> The  $\text{\LaTeX}$  exporter can be configured to support alternative  $\text{\LaTeX}$  engines (see `org-latex-compiler`), build sequences (see `org-latex-pdf-process`), and packages, (see `org-latex-default-packages-alist` and `org-latex-packages-alist`).

`#+LATEX_COMPILER` keyword. It is possible to only load some packages with certain compilers (see the docstring of `org-latex-default-packages-alist`). The bibliography compiler may also be set via `org-latex-bibtex-compiler`<sup>18</sup>.

### 12.10.2 L<sup>A</sup>T<sub>E</sub>X specific export settings

The L<sup>A</sup>T<sub>E</sub>X exporter introduces a number of keywords, similar to the general options settings described in [Section 12.2 \[Export settings\]](#), page 136.

**‘DESCRIPTION’**

The document description. By default these are inserted as metadata using ‘`hyperref`’. Document metadata can be configured via `org-latex-hyperref-template`. Description can also be typeset as part of the front matter via `org-latex-title-command`. You can use several `#+DESCRIPTION` keywords if the description is is long.

**‘LATEX\_CLASS’**

The predefined preamble and headline level mapping to use (`org-latex-default-class`). Must be an element in `org-latex-classes`.

**‘LATEX\_CLASS\_OPTIONS’**

Options given to the L<sup>A</sup>T<sub>E</sub>X document class.

**‘LATEX\_COMPILER’**

The compiler used to produce the PDF (`org-latex-compiler`).

**‘LATEX\_HEADER’**

Arbitrary lines added to the preamble of the document, before the ‘`hyperref`’ settings. The location can be controlled via `org-latex-classes`.

**‘LATEX\_HEADER\_EXTRA’**

Arbitrary lines added to the preamble of the document, before the ‘`hyperref`’ settings. The location can be controlled via `org-latex-classes`.

**‘KEYWORDS’**

The keywords defining the contents of the document. By default these are inserted as metadata using ‘`hyperref`’. Document metadata can be configured via `org-latex-hyperref-template`. Description can also be typeset as part of the front matter via `org-latex-title-command`. You can use several `#+KEYWORDS` if the description is is long.

**‘SUBTITLE’**

The document subtitle. This is typeset according to `org-latex-subtitle-format`. If `org-latex-subtitle-separate` is non-nil it is typed as part of the ‘`\title`’-macro. It can also access via `org-latex-hyperref-template` or typeset as part of the front matter via `org-latex-title-command`.

These keywords are treated in details in the following sections.

<sup>18</sup> You cannot set the bibliography compiler on a file basis via a keyword. However, “smart” L<sup>A</sup>T<sub>E</sub>X compilation systems, such as ‘`latexmk`’, are usually able to select the correct bibliography compiler.

### 12.10.3 L<sup>A</sup>T<sub>E</sub>X header and sectioning structure

By default, the first three outline levels become headlines, defining a general document structure. Additional levels are exported as `itemize` or `enumerate` lists. The transition can also occur at a different level (see [Section 12.2 \[Export settings\]](#), page 136).

By default, the L<sup>A</sup>T<sub>E</sub>X output uses the class `article`.

You can change this globally by setting a different value for `org-latex-default-class` or locally by adding an option like `#+LATEX_CLASS: myclass` in your file, or with a `EXPORT_LATEX_CLASS` property that applies when exporting a region containing only this (sub)tree. The class must be listed in `org-latex-classes`. This variable defines a header template for each class<sup>19</sup>, and allows you to define the sectioning structure for each class. You can also define your own classes there.

The `LATEX_CLASS_OPTIONS` keyword or `EXPORT_LATEX_CLASS_OPTIONS` property can specify the options for the `\documentclass` macro. These options have to be provided, as expected by L<sup>A</sup>T<sub>E</sub>X, within square brackets.

You can also use the `LATEX_HEADER` and `LATEX_HEADER_EXTRA`<sup>20</sup> keywords in order to add lines to the header. See the docstring of `org-latex-classes` for more information.

An example is shown below.

```
#+LATEX_CLASS: article
#+LATEX_CLASS_OPTIONS: [a4paper]
#+LATEX_HEADER: \usepackage{xyz}

* Headline 1
  some text
```

### 12.10.4 Quoting L<sup>A</sup>T<sub>E</sub>X code

Embedded L<sup>A</sup>T<sub>E</sub>X as described in [Section 11.8 \[Embedded L<sup>A</sup>T<sub>E</sub>X\]](#), page 132, will be correctly inserted into the L<sup>A</sup>T<sub>E</sub>X file. Furthermore, you can add special code that should only be present in L<sup>A</sup>T<sub>E</sub>X export with the following constructs:

Code within `@@latex:some code@@` a paragraph.

```
#+LATEX: Literal LATEX code for export
```

```
#+BEGIN_EXPORT latex
```

All lines between these markers are exported literally

```
#+END_EXPORT
```

### 12.10.5 Tables in L<sup>A</sup>T<sub>E</sub>X export

For L<sup>A</sup>T<sub>E</sub>X export of a table, you can specify a label and a caption (see [Section 11.4 \[Images and tables\]](#), page 129). You can also use attributes to control table layout and contents. Valid L<sup>A</sup>T<sub>E</sub>X attributes include:

<sup>19</sup> Into which the values of `org-latex-default-packages-alist` and `org-latex-packages-alist` are spliced.

<sup>20</sup> Unlike `LATEX_HEADER`, contents from `LATEX_HEADER_EXTRA` keywords will not be loaded when previewing L<sup>A</sup>T<sub>E</sub>X snippets (see [Section 11.8.2 \[Previewing L<sup>A</sup>T<sub>E</sub>X fragments\]](#), page 133).

<b>:mode</b>	Nature of table's contents. It can be set to <code>table</code> , <code>math</code> , <code>inline-math</code> or <code>verbatim</code> . In particular, when in <code>math</code> or <code>inline-math</code> mode, every cell is exported as-is, horizontal rules are ignored and the table will be wrapped in a math environment. Also, contiguous tables sharing the same math mode will be wrapped within the same environment. Default mode is determined in <code>org-latex-default-table-mode</code> .
<b>:environment</b>	Environment used for the table. It can be set to any L <sup>A</sup> T <sub>E</sub> X table environment, like <code>tabularx</code> <sup>21</sup> , <code>longtable</code> , <code>array</code> , <code>tabu</code> <sup>22</sup> , <code>bmatrix</code> ... It defaults to <code>org-latex-default-table-environment</code> value.
<b>:caption</b>	<code>#+CAPTION</code> keyword is the simplest way to set a caption for a table (see <a href="#">Section 11.4 [Images and tables], page 129</a> ). If you need more advanced commands for that task, you can use <code>:caption</code> attribute instead. Its value should be raw L <sup>A</sup> T <sub>E</sub> X code. It has precedence over <code>#+CAPTION</code> .
<b>:float</b>	
<b>:placement</b>	The <code>:float</code> specifies the float environment for the table. Possible values are <code>sideways</code> <sup>23</sup> , <code>multicolumn</code> , <code>t</code> and <code>nil</code> . When unspecified, a table with a caption will have a <code>table</code> environment. Moreover, the <code>:placement</code> attribute can specify the positioning of the float. Note: <code>:placement</code> is ignored for <code>:float sideways</code> tables.
<b>:align</b>	
<b>:font</b>	
<b>:width</b>	Set, respectively, the alignment string of the table, its font size and its width. They only apply on regular tables.
<b>:spread</b>	Boolean specific to the <code>tabu</code> and <code>longtabu</code> environments, and only takes effect when used in conjunction with the <code>:width</code> attribute. When <code>:spread</code> is non- <code>nil</code> , the table will be spread or shrunk by the value of <code>:width</code> .
<b>:booktabs</b>	
<b>:center</b>	
<b>:rmlines</b>	They toggle, respectively, <code>booktabs</code> usage (assuming the package is properly loaded), table centering and removal of every horizontal rule but the first one (in a "table.el" table only). In particular, <code>org-latex-tables-booktabs</code> (respectively <code>org-latex-tables-centered</code> ) activates the first (respectively second) attribute globally.
<b>:math-prefix</b>	
<b>:math-suffix</b>	
<b>:math-arguments</b>	A string that will be inserted, respectively, before the table within the math environment, after the table within the math environment, and between the macro

---

<sup>21</sup> Requires adding the `tabularx` package to `org-latex-packages-alist`.

<sup>22</sup> Requires adding the `tabu` package to `org-latex-packages-alist`.

<sup>23</sup> Formerly, the value was `sidewaystable`. This is deprecated since Org 8.3.



name and the contents of the table. The `:math-arguments` attribute is used for matrix macros that require more than one argument (e.g., `qbordermatrix`).

Thus, attributes can be used in a wide array of situations, like writing a table that will span over multiple pages, or a matrix product:

```
#+ATTR_LATEX: :environment longtable :align l|lp{3cm}r|l
| ..... | ..... |
| ..... | ..... |

#+ATTR_LATEX: :mode math :environment bmatrix :math-suffix \times
| a | b |
| c | d |
#+ATTR_LATEX: :mode math :environment bmatrix
| 1 | 2 |
| 3 | 4 |
```

In the example below,  $\text{\LaTeX}$  command `\bicaption{HeadingA}{HeadingB}` will set the caption.

```
#+ATTR_LATEX: :caption \bicaption{HeadingA}{HeadingB}
| ..... | ..... |
| ..... | ..... |
```

### 12.10.6 Images in $\text{\LaTeX}$ export

Images that are linked to without a description part in the link, like `'[[file:img.jpg]]'` or `'[[./img.jpg]]'` will be inserted into the PDF output file resulting from  $\text{\LaTeX}$  processing. Org will use an `\includegraphics` macro to insert the image<sup>24</sup>.

You can specify image width or height with, respectively, `:width` and `:height` attributes. It is also possible to add any other option with the `:options` attribute, as shown in the following example:

```
#+ATTR_LATEX: :width 5cm :options angle=90
[[./img/sed-hr4049.pdf]]
```

If you need a specific command for the caption, use `:caption` attribute. It will override standard `#+CAPTION` value, if any.

```
#+ATTR_LATEX: :caption \bicaption{HeadingA}{HeadingB}
[[./img/sed-hr4049.pdf]]
```

If you have specified a caption as described in [Section 11.4 \[Images and tables\]](#), [page 129](#), the picture will be wrapped into a `figure` environment and thus become a floating element. You can also ask Org to export an image as a float without specifying caption by setting the `:float` attribute. You may also set it to:

- `t`: if you want to use the standard `'figure'` environment. It is used by default if you provide a caption to the image.
- `multicolumn`: if you wish to include an image which spans multiple columns in a page. This will export the image wrapped in a `figure*` environment.

<sup>24</sup> In the case of TikZ (<http://sourceforge.net/projects/pgf/>) images, it will become an `\input` macro wrapped within a `tikzpicture` environment.

- **wrap**: if you would like to let text flow around the image. It will make the figure occupy the left half of the page.
- **sideways**: if you would like the image to appear alone on a separate page rotated ninety degrees using the `sidewaysfigure` environment. Setting this `:float` option will ignore the `:placement` setting.
- **nil**: if you need to avoid any floating environment, even when a caption is provided.

To modify the placement option of any floating environment, set the `placement` attribute.

```
#+ATTR_LATEX: :float wrap :width 0.38\textwidth :placement {r}{0.4\textwidth}
[[./img/hst.png]]
```

Images are centered by default. However, one can disable this behavior by setting `:center` attribute to `nil`. To prevent any image from being centered throughout a document, set `org-latex-images-centered` instead.

Eventually, if the `:comment-include` attribute is set to a non-`nil` value, the  $\LaTeX$  `\includegraphics` macro will be commented out.

### 12.10.7 Plain lists in $\LaTeX$ export

Plain lists accept two optional attributes: `:environment` and `:options`. The first can be used to specify the environment. The second can be used to specifies additional arguments to the environment. Both attributes are illustrated in the following example:

```
#+LATEX_HEADER: \usepackage[inline]{enumitem}
Some ways to say "Hello":
#+ATTR_LATEX: :environment itemize*
#+ATTR_LATEX: :options [label={}, itemjoin={,}, itemjoin*={, and}]
- Hola
- Bonjour
- Guten Tag.
```

By default,  $\LaTeX$  only supports four levels of nesting for lists. If deeper nesting is needed, the ‘`enumitem`’  $\LaTeX$  package can be employed, as shown in this example:

```
#+LATEX_HEADER: \usepackage{enumitem}
#+LATEX_HEADER: \renewlist{itemize}{itemize}{9}
#+LATEX_HEADER: \setlist[itemize]{label=$\circ$}
- One
  - Two
    - Three
      - Four
        - Five
```

### 12.10.8 Source blocks in $\LaTeX$ export

In addition to syntax defined in [Section 11.5 \[Literal examples\]](#), [page 129](#), names and captions (see [Section 11.4 \[Images and tables\]](#), [page 129](#)), source blocks also accept two additional attributes: `:float` and `:options`.

You may set the former to

- **t**: if you want to make the source block a float. It is the default value when a caption is provided.

- `multicolumn`: if you wish to include a source block which spans multiple columns in a page.
- `nil`: if you need to avoid any floating environment, even when a caption is provided. It is useful for source code that may not fit in a single page.

```
#+ATTR_LATEX: :float nil
#+BEGIN_SRC emacs-lisp
Code that may not fit in a single page.
#+END_SRC
```

The latter allows to specify options relative to the package used to highlight code in the output (e.g., `listings`). This is the local counterpart to `org-latex-listings-options` and `org-latex-minted-options` variables, which see.

```
#+ATTR_LATEX: :options commentstyle=\bfseries
#+BEGIN_SRC emacs-lisp
(defun Fib (n)
  (if (< n 2) n (+ (Fib (- n 1)) (Fib (- n 2)))))
; Count rabbits.
#+END_SRC
```

### 12.10.9 Example blocks in $\text{\LaTeX}$ export

By default, when exporting to  $\text{\LaTeX}$ , example blocks contents are wrapped in a ‘`verbatim`’ environment. It is possible to use a different environment globally using an appropriate export filter (see [Section 12.17 \[Advanced configuration\]](#), page 179). You can also change this per block using `:environment` parameter.

```
#+ATTR_LATEX: :environment myverbatim
#+BEGIN_EXAMPLE
This sentence is false.
#+END_EXAMPLE
```

### 12.10.10 Special blocks in $\text{\LaTeX}$ export

In  $\text{\LaTeX}$  back-end, special blocks become environments of the same name. Value of `:options` attribute will be appended as-is to that environment’s opening string. For example:

```
#+BEGIN_abstract
We demonstrate how to solve the Syracuse problem.
#+END_abstract

#+ATTR_LATEX: :options [Proof of important theorem]
#+BEGIN_proof
...
Therefore, any even number greater than 2 is the sum of two primes.
#+END_proof
```

becomes

```
\begin{abstract}
We demonstrate how to solve the Syracuse problem.
\end{abstract}
```

```

\begin{proof}[Proof of important theorem]
...
Therefore, any even number greater than 2 is the sum of two primes.
\end{proof}

```

If you need to insert a specific caption command, use `:caption` attribute. It will override standard `#+CAPTION` value, if any. For example:

```

#+ATTR_LATEX: :caption \MyCaption{HeadingA}
#+BEGIN_proof
...
#+END_proof

```

### 12.10.11 Horizontal rules in $\text{\LaTeX}$ export

Width and thickness of a given horizontal rule can be controlled with, respectively, `:width` and `:thickness` attributes:

```

#+ATTR_LATEX: :width .6\textwidth :thickness 0.8pt
-----

```

## 12.11 Markdown export

`md` export back-end generates Markdown syntax<sup>25</sup> for an Org mode buffer.

It is built over HTML back-end: any construct not supported by Markdown syntax (e.g., tables) will be controlled and translated by `html` back-end (see [Section 12.9 \[HTML export\]](#), [page 147](#)).

### Markdown export commands

`C-c C-e m m` `org-md-export-to-markdown`  
 Export as a text file written in Markdown syntax. For an Org file, `myfile.org`, the resulting file will be `myfile.md`. The file will be overwritten without warning.

`C-c C-e m M` `org-md-export-as-markdown`  
 Export to a temporary buffer. Do not create a file.

`C-c C-e m o`  
 Export as a text file with Markdown syntax, then open it.

### Header and sectioning structure

Markdown export can generate both `atx` and `setext` types for headlines, according to `org-md-headline-style`. The former introduces a hard limit of two levels, whereas the latter pushes it to six. Headlines below that limit are exported as lists. You can also set a soft limit before that one (see [Section 12.2 \[Export settings\]](#), [page 136](#)).

---

<sup>25</sup> Vanilla flavor, as defined at <http://daringfireball.net/projects/markdown/>.

## 12.12 OpenDocument Text export

Org mode supports export to OpenDocument Text (ODT) format. Documents created by this exporter use the *OpenDocument-v1.2 specification*<sup>26</sup> and are compatible with LibreOffice 3.4.

### 12.12.1 Pre-requisites for ODT export

The ODT exporter relies on the `zip` program to create the final output. Check the availability of this program before proceeding further.

### 12.12.2 ODT export commands

`C-c C-e o o` `org-odt-export-to-odt`  
Export as OpenDocument Text file.

If `org-odt-preferred-output-format` is specified, automatically convert the exported file to that format. See [\[Automatically exporting to other formats\]](#), page 163.

For an Org file `myfile.org`, the ODT file will be `myfile.odt`. The file will be overwritten without warning. If there is an active region,<sup>27</sup> only the region will be exported. If the selected region is a single tree,<sup>28</sup> the tree head will become the document title. If the tree head entry has, or inherits, an `EXPORT_FILE_NAME` property, that name will be used for the export.

`C-c C-e o O` Export as an OpenDocument Text file and open the resulting file. If `org-odt-preferred-output-format` is specified, open the converted file instead. See [\[Automatically exporting to other formats\]](#), page 163.

### 12.12.3 ODT specific export settings

The ODT exporter introduces a number of keywords, similar to the general options settings described in [Section 12.2 \[Export settings\]](#), page 136.

‘DESCRIPTION’

The document description. These are inserted as document metadata. You can use several such keywords if the list is long.

‘KEYWORDS’

The keywords defining the contents of the document. These are inserted as document metadata. You can use several such keywords if the list is long.

‘ODT\_STYLES\_FILE’

The style file of the document (`org-odt-styles-file`). See [Section 12.12.5 \[Applying custom styles\]](#), page 163 for details.

‘SUBTITLE’

The document subtitle.

<sup>26</sup> Open Document Format for Office Applications (OpenDocument) Version 1.2

<sup>27</sup> This requires `transient-mark-mode` to be turned on

<sup>28</sup> To select the current subtree, use `C-c @`

### 12.12.4 Extending ODT export

The ODT exporter can interface with a variety of document converters and supports popular converters out of the box. As a result, you can use it to export to formats like ‘doc’ or convert a document from one format (say ‘csv’) to another format (say ‘ods’ or ‘xls’).

If you have a working installation of LibreOffice, a document converter is pre-configured for you and you can use it right away. If you would like to use `unoconv` as your preferred converter, customize the variable `org-odt-convert-process` to point to `unoconv`. You can also use your own favorite converter or tweak the default settings of the LibreOffice and ‘unoconv’ converters. See [\[Configuring a document converter\]](#), page 168.

### Automatically exporting to other formats

Very often, you will find yourself exporting to ODT format, only to immediately save the exported document to other formats like ‘doc’, ‘docx’, ‘rtf’, ‘pdf’ etc. In such cases, you can specify your preferred output format by customizing the variable `org-odt-preferred-output-format`. This way, the export commands (see [\[Exporting to ODT\]](#), page 162) can be extended to export to a format that is of immediate interest to you.

### Converting between document formats

There are many document converters in the wild which support conversion to and from various file formats, including, but not limited to the ODT format. LibreOffice converter, mentioned above, is one such converter. Once a converter is configured, you can interact with it using the following command.

*M-x org-odt-convert RET*

Convert an existing document from one format to another. With a prefix argument, also open the newly produced file.

### 12.12.5 Applying custom styles

The ODT exporter ships with a set of OpenDocument styles (see [\[Working with OpenDocument style files\]](#), page 168) that ensure a well-formatted output. These factory styles, however, may not cater to your specific tastes. To customize the output, you can either modify the above styles files directly, or generate the required styles using an application like LibreOffice. The latter method is suitable for expert and non-expert users alike, and is described here.

### Applying custom styles: the easy way

1. Create a sample `example.org` file with the below settings and export it to ODT format.

```
#+OPTIONS: H:10 num:t
```

2. Open the above `example.odt` using LibreOffice. Use the `Stylist` to locate the target styles—these typically have the ‘Org’ prefix—and modify those to your taste. Save the modified file either as an OpenDocument Text (`.odt`) or OpenDocument Template (`.ott`) file.
3. Customize the variable `org-odt-styles-file` and point it to the newly created file. For additional configuration options see [\[Overriding factory styles\]](#), page 169.

If you would like to choose a style on a per-file basis, you can use the `#+ODT_STYLES_FILE` option. A typical setting will look like

```
#+ODT_STYLES_FILE: "/path/to/example.ott"
```

or

```
#+ODT_STYLES_FILE: ("/path/to/file.ott" ("styles.xml" "image/hdr.png"))
```

## Using third-party styles and templates

You can use third-party styles and templates for customizing your output. This will produce the desired output only if the template provides all style names that the ‘ODT’ exporter relies on. Unless this condition is met, the output is going to be less than satisfactory. So it is highly recommended that you only work with templates that are directly derived from the factory settings.

### 12.12.6 Links in ODT export

ODT exporter creates native cross-references for internal links. It creates Internet-style links for all other links.

A link with no description and destined to a regular (un-itemized) outline heading is replaced with a cross-reference and section number of the heading.

A ‘\ref{label}’-style reference to an image, table etc. is replaced with a cross-reference and sequence number of the labeled entity. See [Section 12.12.10 \[Labels and captions in ODT export\]](#), page 167.

### 12.12.7 Tables in ODT export

Export of native Org mode tables (see [Chapter 3 \[Tables\]](#), page 19) and simple `table.el` tables is supported. However, export of complex `table.el` tables—tables that have column or row spans—is not supported. Such tables are stripped from the exported document.

By default, a table is exported with top and bottom frames and with rules separating row and column groups (see [Section 3.3 \[Column groups\]](#), page 23). Furthermore, all tables are typeset to occupy the same width. If the table specifies alignment and relative width for its columns (see [Section 3.2 \[Column width and alignment\]](#), page 22) then these are honored on export.<sup>29</sup>

You can control the width of the table by specifying `:rel-width` property using an `#+ATTR_ODT` line.

For example, consider the following table which makes use of all the rules mentioned above.

```
#+ATTR_ODT: :rel-width 50
| Area/Month | Jan | Feb | Mar | Sum |
|-----+-----+-----+-----+-----|
| /          | <  |    |    | <  |
| <l13>      | <r5> | <r5> | <r5> | <r6> |
| North America | 1 | 21 | 926 | 948 |
| Middle East   | 6 | 75 | 844 | 925 |
| Asia Pacific  | 9 | 27 | 790 | 826 |
|-----+-----+-----+-----+-----|
| Sum          | 16 | 123 | 2560 | 2699 |
```

<sup>29</sup> The column widths are interpreted as weighted ratios with the default weight being 1

On export, the table will occupy 50% of text area. The columns will be sized (roughly) in the ratio of 13:5:5:5:6. The first column will be left-aligned and rest of the columns will be right-aligned. There will be vertical rules after separating the header and last columns from other columns. There will be horizontal rules separating the header and last rows from other rows.

If you are not satisfied with the above formatting options, you can create custom table styles and associate them with a table using the `#+ATTR_ODT` line. See [Customizing tables in ODT export], page 170.

## 12.12.8 Images in ODT export

### Embedding images

You can embed images within the exported document by providing a link to the desired image file with no link description. For example, to embed ‘img.png’ do either of the following:

```
[[file:img.png]]
[[./img.png]]
```

### Embedding clickable images

You can create clickable images by providing a link whose description is a link to an image file. For example, to embed a image `org-mode-unicorn.png` which when clicked jumps to <http://Orgmode.org> website, do the following

```
[[http://orgmode.org][./org-mode-unicorn.png]]
```

### Sizing and scaling of embedded images

You can control the size and scale of the embedded images using the `#+ATTR_ODT` attribute.

The exporter specifies the desired size of the image in the final document in units of centimeters. In order to scale the embedded images, the exporter queries for pixel dimensions of the images using one of a) ImageMagick’s `identify` program or b) Emacs `create-image` and `image-size` APIs<sup>30</sup>. The pixel dimensions are subsequently converted in to units of centimeters using `org-odt-pixels-per-inch`. The default value of this variable is set to `display-pixels-per-inch`. You can tweak this variable to achieve the best results.

The examples below illustrate the various possibilities.

Explicitly size the image

To embed `img.png` as a 10 cm x 10 cm image, do the following:

```
#+ATTR_ODT: :width 10 :height 10
[[./img.png]]
```

Scale the image

To embed `img.png` at half its size, do the following:

```
#+ATTR_ODT: :scale 0.5
[[./img.png]]
```

<sup>30</sup> Use of `ImageMagick` is only desirable. However, if you routinely produce documents that have large images or you export your Org files that has images using a Emacs batch script, then the use of `ImageMagick` is mandatory.



Scale the image to a specific width

To embed `img.png` with a width of 10 cm while retaining the original height:width ratio, do the following:

```
#+ATTR_ODT: :width 10
[[./img.png]]
```

Scale the image to a specific height

To embed `img.png` with a height of 10 cm while retaining the original height:width ratio, do the following

```
#+ATTR_ODT: :height 10
[[./img.png]]
```

## Anchoring of images

You can control the manner in which an image is anchored by setting the `:anchor` property of its `#+ATTR_ODT` line. You can specify one of the following three values for the `:anchor` property: `"as-char"`, `"paragraph"` and `"page"`.

To create an image that is anchored to a page, do the following:

```
#+ATTR_ODT: :anchor "page"
[[./img.png]]
```

### 12.12.9 Math formatting in ODT export

The ODT exporter has special support for handling math.

## Working with $\text{\LaTeX}$ math snippets

$\text{\LaTeX}$  math snippets (see [Section 11.8.1 \[ \$\text{\LaTeX}\$  fragments\]](#), page 132) can be embedded in the ODT document in one of the following ways:

### 1. MathML

This option is activated on a per-file basis with

```
#+OPTIONS: LaTeX:t
```

With this option,  $\text{\LaTeX}$  fragments are first converted into MathML fragments using an external  $\text{\LaTeX}$ -to-MathML converter program. The resulting MathML fragments are then embedded as an OpenDocument Formula in the exported document.

You can specify the  $\text{\LaTeX}$ -to-MathML converter by customizing the variables `org-latex-to-mathml-convert-command` and `org-latex-to-mathml-jar-file`.

To use MathToWeb<sup>31</sup> as your converter, you can configure the above variables as

```
(setq org-latex-to-mathml-convert-command
      "java -jar %j -unicode -force -df %o %I"
      org-latex-to-mathml-jar-file
      "/path/to/mathtoweb.jar")
```

To use  $\text{\LaTeX}$ XML<sup>32</sup> use

<sup>31</sup> See [MathToWeb](#).

<sup>32</sup> See <http://dlmf.nist.gov/LaTeXML/>.

```
(setq org-latex-to-mathml-convert-command
      "latexmlmath \"%i\" --presentationmathml=%o")
```

You can use the following commands to quickly verify the reliability of the L<sup>A</sup>T<sub>E</sub>X-to-MathML converter.

*M-x org-odt-export-as-odf RET*

Convert a L<sup>A</sup>T<sub>E</sub>X math snippet to an OpenDocument formula (.odf) file.

*M-x org-odt-export-as-odf-and-open RET*

Convert a L<sup>A</sup>T<sub>E</sub>X math snippet to an OpenDocument formula (.odf) file and open the formula file with the system-registered application.

## 2. PNG images

This option is activated on a per-file basis with

```
#+OPTIONS: tex:dvipng
#+OPTIONS: tex:dvisvgm
```

or:

```
#+OPTIONS: tex:imagemagick
```

With this option, L<sup>A</sup>T<sub>E</sub>X fragments are processed into PNG or SVG images and the resulting images are embedded in the exported document. This method requires that the `dvipng` program, `dvisvgm` or `imagemagick` suite be available on your system.

## Working with MathML or OpenDocument formula files

For various reasons, you may find embedding L<sup>A</sup>T<sub>E</sub>X math snippets in an ODT document less than reliable. In that case, you can embed a math equation by linking to its MathML (.mml) source or its OpenDocument formula (.odf) file as shown below:

```
[[./equation.mml]]
```

or

```
[[./equation.odf]]
```

### 12.12.10 Labels and captions in ODT export

You can label and caption various category of objects—an inline image, a table, a L<sup>A</sup>T<sub>E</sub>X fragment or a Math formula—using `#+LABEL` and `#+CAPTION` lines. See [Section 11.4 \[Images and tables\], page 129](#). ODT exporter enumerates each labeled or captioned object of a given category separately. As a result, each such object is assigned a sequence number based on order of its appearance in the Org file.

In the exported document, a user-provided caption is augmented with the category and sequence number. Consider the following inline image in an Org file.

```
#+CAPTION: Bell curve
#+LABEL:   fig:SED-HR4049
[[./img/a.png]]
```

It could be rendered as shown below in the exported document.

Figure 2: Bell curve

You can modify the category component of the caption by customizing the option `org-odt-category-map-alist`. For example, to tag all embedded images with the string ‘Illustration’ (instead of the default ‘Figure’) use the following setting:

```
(setq org-odt-category-map-alist
      (( "__Figure__" "Illustration" "value" "Figure" org-odt--enumerable-image-p)))
```

With this, previous image will be captioned as below in the exported document.

Illustration 2: Bell curve

### 12.12.11 Literal examples in ODT export

Export of literal examples (see [Section 11.5 \[Literal examples\]](#), page 129) with full fontification is supported. Internally, the exporter relies on `htmlfontify.el` to generate all style definitions needed for a fancy listing. The auto-generated styles have ‘`OrgSrc`’ as prefix and inherit their color from the faces used by Emacs `font-lock` library for the source language.

If you prefer to use your own custom styles for fontification, you can do so by customizing the option `org-odt-create-custom-styles-for-srcblocks`.

You can turn off fontification of literal examples by customizing the option `org-odt-fontify-srcblocks`.

### 12.12.12 Advanced topics in ODT export

If you rely heavily on ODT export, you may want to exploit the full set of features that the exporter offers. This section describes features that would be of interest to power users.

#### Configuring a document converter

The ODT exporter can work with popular converters with little or no extra configuration from your side. See [Section 12.12.4 \[Extending ODT export\]](#), page 163. If you are using a converter that is not supported by default or if you would like to tweak the default converter settings, proceed as below.

1. Register the converter

Name your converter and add it to the list of known converters by customizing the option `org-odt-convert-processes`. Also specify how the converter can be invoked via command-line to effect the conversion.

2. Configure its capabilities

Specify the set of formats the converter can handle by customizing the variable `org-odt-convert-capabilities`. Use the default value for this variable as a guide for configuring your converter. As suggested by the default setting, you can specify the full set of formats supported by the converter and not limit yourself to specifying formats that are related to just the OpenDocument Text format.

3. Choose the converter

Select the newly added converter as the preferred one by customizing the option `org-odt-convert-process`.

#### Working with OpenDocument style files

This section explores the internals of the ODT exporter and the means by which it produces styled documents. Read this section if you are interested in exploring the automatic and custom OpenDocument styles used by the exporter.

### a) Factory styles

The ODT exporter relies on two files for generating its output. These files are bundled with the distribution under the directory pointed to by the variable `org-odt-styles-dir`. The two files are:

- **OrgOdtStyles.xml**

This file contributes to the `styles.xml` file of the final ‘ODT’ document. This file gets modified for the following purposes:

1. To control outline numbering based on user settings.
2. To add styles generated by `htmlfontify.el` for fontification of code blocks.

- **OrgOdtContentTemplate.xml**

This file contributes to the `content.xml` file of the final ‘ODT’ document. The contents of the Org outline are inserted between the ‘`<office:text>`’...‘`</office:text>`’ elements of this file.

Apart from serving as a template file for the final `content.xml`, the file serves the following purposes:

1. It contains automatic styles for formatting of tables which are referenced by the exporter.
2. It contains ‘`<text:sequence-decl>`’...‘`</text:sequence-decl>`’ elements that control how various entities—tables, images, equations, etc.—are numbered.

### b) Overriding factory styles

The following two variables control the location from which the ODT exporter picks up the custom styles and content template files. You can customize these variables to override the factory styles used by the exporter.

- **org-odt-styles-file**

Use this variable to specify the `styles.xml` that will be used in the final output. You can specify one of the following values:

1. A `styles.xml` file  
Use this file instead of the default `styles.xml`
2. A `.odt` or `.ott` file  
Use the `styles.xml` contained in the specified OpenDocument Text or Template file
3. A `.odt` or `.ott` file and a subset of files contained within them  
Use the `styles.xml` contained in the specified OpenDocument Text or Template file. Additionally extract the specified member files and embed those within the final ‘ODT’ document.  
Use this option if the `styles.xml` file references additional files like header and footer images.

4. `nil`

Use the default `styles.xml`

- **org-odt-content-template-file**

Use this variable to specify the blank `content.xml` that will be used in the final output.

## Creating one-off styles

There are times when you would want one-off formatting in the exported document. You can achieve this by embedding raw OpenDocument XML in the Org file. The use of this feature is better illustrated with couple of examples.

### 1. Embedding ODT tags as part of regular text

You can inline OpenDocument syntax by enclosing it within ‘`@@odt:...@@`’ markup. For example, to highlight a region of text do the following:

```
@@odt:<text:span text:style-name="Highlight">This is a highlighted
text</text:span>@@. But this is a regular text.
```

**Hint:** To see the above example in action, edit your `styles.xml` (see [Factory styles], page 169) and add a custom ‘Highlight’ style as shown below.

```
<style:style style:name="Highlight" style:family="text">
  <style:text-properties fo:background-color="#ff0000"/>
</style:style>
```

### 2. Embedding a one-line OpenDocument XML

You can add a simple OpenDocument one-liner using the `#+ODT:` directive. For example, to force a page break do the following:

```
#+ODT: <text:p text:style-name="PageBreak"/>
```

**Hint:** To see the above example in action, edit your `styles.xml` (see [Factory styles], page 169) and add a custom ‘PageBreak’ style as shown below.

```
<style:style style:name="PageBreak" style:family="paragraph"
  style:parent-style-name="Text_20_body">
  <style:paragraph-properties fo:break-before="page"/>
</style:style>
```

### 3. Embedding a block of OpenDocument XML

You can add a large block of OpenDocument XML using the `#+BEGIN_EXPORT odt...#+END_EXPORT` construct.

For example, to create a one-off paragraph that uses bold text, do the following:

```
#+BEGIN_EXPORT odt
<text:p text:style-name="Text_20_body_20_bold">
This paragraph is specially formatted and uses bold text.
</text:p>
#+END_EXPORT
```

## Customizing tables in ODT export

You can override the default formatting of the table by specifying a custom table style with the `#+ATTR_ODT` line. For a discussion on default formatting of tables see [Section 12.12.7 \[Tables in ODT export\]](#), page 164.

This feature closely mimics the way table templates are defined in the OpenDocument-v1.2 specification.<sup>33</sup>

To have a quick preview of this feature, install the below setting and export the table that follows:

<sup>33</sup> [OpenDocument-v1.2 Specification](#)

```
(setq org-odt-table-styles
  (append org-odt-table-styles
    '(("TableWithHeaderRowAndColumn" "Custom"
      ((use-first-row-styles . t)
       (use-first-column-styles . t))))
    ("TableWithFirstRowandLastRow" "Custom"
      ((use-first-row-styles . t)
       (use-last-row-styles . t))))))

#+ATTR_ODT: :style TableWithHeaderRowAndColumn
| Name | Phone | Age |
| Peter | 1234 | 17 |
| Anna | 4321 | 25 |
```

In the above example, you used a template named ‘Custom’ and installed two table styles with the names ‘TableWithHeaderRowAndColumn’ and ‘TableWithFirstRowandLastRow’. (**Important:** The OpenDocument styles needed for producing the above template have been pre-defined for you. These styles are available under the section marked ‘Custom Table Template’ in `OrgOdtContentTemplate.xml` (see [Factory styles](#), page 169). If you need additional templates you have to define these styles yourselves.

To use this feature proceed as follows:

1. Create a table template<sup>34</sup>

A table template is nothing but a set of ‘table-cell’ and ‘paragraph’ styles for each of the following table cell categories:

- Body
- First column
- Last column
- First row
- Last row
- Even row
- Odd row
- Even column
- Odd Column

The names for the above styles must be chosen based on the name of the table template using a well-defined convention.

The naming convention is better illustrated with an example. For a table template with the name ‘Custom’, the needed style names are listed in the following table.

Table cell type	table-cell style	paragraph style
Body	‘CustomTableCell’	‘CustomTableParagraph’
First column	‘CustomFirstColumnTableCell’	‘CustomFirstColumnTableParagraph’
Last column	‘CustomLastColumnTableCell’	‘CustomLastColumnTableParagraph’

<sup>34</sup> See the `<table:table-template>` element of the OpenDocument-v1.2 specification

First row	<code>'CustomFirstRowTableCell'</code>	<code>'CustomFirstRowTableParagraph'</code>
Last row	<code>'CustomLastRowTableCell'</code>	<code>'CustomLastRowTableParagraph'</code>
Even row	<code>'CustomEvenRowTableCell'</code>	<code>'CustomEvenRowTableParagraph'</code>
Odd row	<code>'CustomOddRowTableCell'</code>	<code>'CustomOddRowTableParagraph'</code>
Even column	<code>'CustomEvenColumnTableCell'</code>	<code>'CustomEvenColumnTableParagraph'</code>
Odd column	<code>'CustomOddColumnTableCell'</code>	<code>'CustomOddColumnTableParagraph'</code>

To create a table template with the name `'Custom'`, define the above styles in the `<office:automatic-styles>...</office:automatic-styles>` element of the content template file (see [\[Factory styles\]](#), page 169).

## 2. Define a table style<sup>35</sup>

To define a table style, create an entry for the style in the variable `org-odt-table-styles` and specify the following:

- the name of the table template created in step (1)
- the set of cell styles in that template that are to be activated

For example, the entry below defines two different table styles `'TableWithHeaderRowAndColumn'` and `'TableWithFirstRowandLastRow'` based on the same template `'Custom'`. The styles achieve their intended effect by selectively activating the individual cell styles in that template.

```
(setq org-odt-table-styles
      (append org-odt-table-styles
              '(("TableWithHeaderRowAndColumn" "Custom"
                ((use-first-row-styles . t)
                 (use-first-column-styles . t))))
              ("TableWithFirstRowandLastRow" "Custom"
                ((use-first-row-styles . t)
                 (use-last-row-styles . t))))))
```

## 3. Associate a table with the table style

To do this, specify the table style created in step (2) as part of the `ATTR_ODT` line as shown below.

```
#+ATTR_ODT: :style "TableWithHeaderRowAndColumn"
| Name | Phone | Age |
| Peter | 1234 | 17 |
| Anna | 4321 | 25 |
```

## Validating OpenDocument XML

Occasionally, you will discover that the document created by the ODT exporter cannot be opened by your favorite application. One of the common reasons for this is that the `.odt` file is corrupt. In such cases, you may want to validate the document against the OpenDocument RELAX NG Compact Syntax (RNC) schema.

<sup>35</sup> See the attributes `table:template-name`, `table:use-first-row-styles`, `table:use-last-row-styles`, `table:use-first-column-styles`, `table:use-last-column-styles`, `table:use-banding-rows-styles`, and `table:use-banding-column-styles` of the `<table:table>` element in the OpenDocument-v1.2 specification

For de-compressing the `.odt` file<sup>36</sup>: See Info file `emacs`, node ‘File Archives’. For general help with validation (and schema-sensitive editing) of XML files: See Info file `nxml-mode`, node ‘Introduction’.

If you have ready access to OpenDocument `.rnc` files and the needed schema-locating rules in a single folder, you can customize the variable `org-odt-schema-dir` to point to that directory. The ODT exporter will take care of updating the `rng-schema-locating-files` for you.

## 12.13 Org export

`org` export back-end creates a normalized version of the Org document in current buffer. In particular, it evaluates Babel code (see [Section 14.5 \[Evaluating code blocks\]](#), page 198) and removes other back-ends specific contents.

### Org export commands

`C-c C-e O o` `org-org-export-to-org`  
Export as an Org document. For an Org file, `myfile.org`, the resulting file will be `myfile.org.org`. The file will be overwritten without warning.

`C-c C-e O O` `org-org-export-as-org`  
Export to a temporary buffer. Do not create a file.

`C-c C-e O v`  
Export to an Org file, then open it.

## 12.14 Texinfo export

‘`texinfo`’ export back-end generates Texinfo code and can compile it into an Info file.

### 12.14.1 Texinfo export commands

`C-c C-e i t` `org-texinfo-export-to-texinfo`  
Export as a Texinfo file. For an Org file, `myfile.org`, the resulting file will be `myfile.texi`. The file will be overwritten without warning.

`C-c C-e i i` `org-texinfo-export-to-info`  
Export to Texinfo and then process to an Info file<sup>37</sup>.

### 12.14.2 Texinfo specific export settings

The Texinfo exporter introduces a number of keywords, similar to the general options settings described in [Section 12.2 \[Export settings\]](#), page 136.

‘`SUBTITLE`’  
The document subtitle.

‘`SUBAUTHOR`’  
The document subauthor.

<sup>36</sup> `.odt` files are nothing but ‘`zip`’ archives

<sup>37</sup> By setting `org-texinfo-info-process`, it is possible to generate other formats, including DocBook.



<code>'TEXINFO_FILENAME'</code>	The Texinfo filename.
<code>'TEXINFO_CLASS'</code>	The class of the document ( <code>org-texinfo-default-class</code> ). This must be a member of <code>org-texinfo-classes</code> .
<code>'TEXINFO_HEADER'</code>	Arbitrary lines inserted at the end of the header.
<code>'TEXINFO_POST_HEADER'</code>	Arbitrary lines inserted after the end of the header.
<code>'TEXINFO_DIR_CATEGORY'</code>	The directory category of the document.
<code>'TEXINFO_DIR_TITLE'</code>	The directory title of the document.
<code>'TEXINFO_DIR_DESC'</code>	The directory description of the document.
<code>'TEXINFO_PRINTED_TITLE'</code>	The printed title of the document.

### 12.14.3 Texinfo file header

Upon creating the header of a Texinfo file, the back-end guesses a name for the Info file to be compiled. This may not be a sensible choice, e.g., if you want to produce the final document in a different directory. Specify an alternate path with `#+TEXINFO_FILENAME` keyword to override the default destination.

Along with the output file name, the header contains information about the language (see [Section 12.2 \[Export settings\], page 136](#)) and current encoding used<sup>38</sup>. Insert a `#+TEXINFO_HEADER` keyword for each additional command needed, e.g., `@code{@synindex}`.

If you happen to regularly install the same set of commands, it may be easier to define your own class in `org-texinfo-classes`. Set `#+TEXINFO_CLASS` keyword accordingly in your document to activate it.

### 12.14.4 Texinfo title and copyright page

The default template includes a title page for hard copy output. The title and author displayed on this page are extracted from, respectively, `#+TITLE` and `#+AUTHOR` keywords (see [Section 12.2 \[Export settings\], page 136](#)). It is also possible to print a different, more specific, title with `#+TEXINFO_PRINTED_TITLE` keyword, and add subtitles with `#+SUBTITLE` keyword. Both expect raw Texinfo code in their value.

Likewise, information brought by `#+AUTHOR` may not be enough. You can include other authors with several `#+SUBAUTHOR` keywords. Values are also expected to be written in Texinfo code.

```
#+AUTHOR: Jane Smith
#+SUBAUTHOR: John Doe
```

---

<sup>38</sup> See `org-texinfo-coding-system` for more information.

```
#+TEXINFO_PRINTED_TITLE: This Long Title@inlinefmt{tex,*} Is Broken in @TeX{}
```

Copying material is defined in a dedicated headline with a non-nil `:COPYING:` property. The contents are inserted within a `@copying` command at the beginning of the document whereas the heading itself does not appear in the structure of the document.

Copyright information is printed on the back of the title page.

```
* Copying
:PROPERTIES:
:COPYING: t
:END:
```

This is a short example of a complete Texinfo file, version 1.0.

Copyright \copy 2016 Free Software Foundation, Inc.

### 12.14.5 Texinfo ‘Top’ node

You may ultimately want to install your new Info file in your system. You can write an appropriate entry in the top level directory specifying its category and title with, respectively, `#+TEXINFO_DIR_CATEGORY` and `#+TEXINFO_DIR_TITLE`. Optionally, you can add a short description using `#+TEXINFO_DIR_DESC`. The following example would write an entry similar to Org’s in the ‘Top’ node.

```
#+TEXINFO_DIR_CATEGORY: Emacs
#+TEXINFO_DIR_TITLE: Org Mode: (org)
#+TEXINFO_DIR_DESC: Outline-based notes management and organizer
```

### 12.14.6 Headings and sectioning structure

‘texinfo’ uses a pre-defined scheme, or class, to convert headlines into Texinfo structuring commands. For example, a top level headline appears as `@chapter` if it should be numbered or as `@unnumbered` otherwise. If you need to use a different set of commands, e.g., to start with `@part` instead of `@chapter`, install a new class in `org-texinfo-classes`, then activate it with `#+TEXINFO_CLASS` keyword. Export process defaults to `org-texinfo-default-class` when there is no such keyword in the document.

If a headline’s level has no associated structuring command, or is below a certain threshold (see [Section 12.2 \[Export settings\], page 136](#)), that headline becomes a list in Texinfo output.

As an exception, a headline with a non-nil `:APPENDIX:` property becomes an appendix, independently on its level and the class used.

Each regular sectioning structure creates a menu entry, named after the heading. You can provide a different, e.g., shorter, title in `:ALT_TITLE:` property (see [Section 12.3 \[Table of contents\], page 139](#)). Optionally, you can specify a description for the item in `:DESCRIPTION:` property. E.g.,

```
* Controlling Screen Display
:PROPERTIES:
:ALT_TITLE: Display
:DESCRIPTION: Controlling Screen Display
:END:
```

### 12.14.7 Indices

Index entries are created using dedicated keywords. ‘texinfo’ back-end provides one for each predefined type: `#+CINDEX`, `#+FINDEX`, `#+KINDEX`, `#+PINDEX`, `#+TINDEX` and `#+VININDEX`. For custom indices, you can write raw Texinfo code (see [Section 12.14.8 \[Quoting Texinfo code\]](#), page 176).

`#+CINDEX: Defining indexing entries`

To generate an index, you need to set the `:INDEX:` property of a headline to an appropriate abbreviation (e.g., ‘cp’ or ‘vr’). The headline is then exported as an unnumbered chapter or section command and the index is inserted after its contents.

```
* Concept Index
:PROPERTIES:
:INDEX: cp
:END:
```

### 12.14.8 Quoting Texinfo code

It is possible to insert raw Texinfo code using any of the following constructs

```
Richard @@texinfo:@sc{@@Stallman@@texinfo:}@@ commence' GNU.
```

```
#+TEXINFO: @need800
This paragraph is preceded by...
```

```
#+BEGIN_EXPORT texinfo
@auindex Johnson, Mark
@auindex Lakoff, George
#+END_EXPORT
```

### 12.14.9 Plain lists in Texinfo export

In Texinfo output, description lists appear as two-column tables, using the default command `@table`. You can use `@ftable` or `@vtable`<sup>39</sup> instead with `:table-type` attribute.

In any case, these constructs require a highlighting command for entries in the list. You can provide one with `:indic` attribute. If you do not, it defaults to the value stored in `org-texinfo-def-table-markup`, which see.

```
#+ATTR_TEXINFO: :indic @asis
- foo :: This is the text for /foo/, with no highlighting.
```

### 12.14.10 Tables in Texinfo export

When exporting a table, column widths are deduced from the longest cell in each column. You can also define them explicitly as fractions of the line length, using `:columns` attribute.

```
#+ATTR_TEXINFO: :columns .5 .5
| a cell | another cell |
```

<sup>39</sup> For more information, See Info file `texinfo`, node ‘Two-column Tables’.

### 12.14.11 Images in Texinfo export

Images are links to files with a supported image extension and no description. Image scaling is set with `:width` and `:height` attributes. You can also use `:alt` to specify alternate text, as Texinfo code.

```
#+ATTR_TEXINFO: :width 1in :alt Alternate @i{text}
[[ridt.pdf]]
```

### 12.14.12 Special blocks

In Texinfo output, special blocks become commands of the same name. Value of `:options` attribute is added right after the beginning of the command. For example:

```
#+attr_texinfo: :options org-org-export-to-org ...
#+begin_defun
A somewhat obsessive function.
#+end_defun
```

becomes

```
@defun org-org-export-to-org ...
A somewhat obsessive function.
@end defun
```

### 12.14.13 A Texinfo example

Here is a thorough example. See Info file `texinfo`, node ‘GNU Sample Texts’ for an equivalent Texinfo code.

```
#+MACRO: version 2.0
#+MACRO: updated last updated 4 March 2014

#+OPTIONS: ':t toc:t author:t email:t
#+TITLE: GNU Sample {{{version}}}
#+AUTHOR: A.U. Thor
#+EMAIL: bug-sample@gnu.org
#+LANGUAGE: en

#+TEXINFO_FILENAME: sample.info
#+TEXINFO_HEADER: @syncodeindex pg cp

#+TEXINFO_DIR_CATEGORY: Texinfo documentation system
#+TEXINFO_DIR_TITLE: sample: (sample)
#+TEXINFO_DIR_DESC: Invoking sample

#+TEXINFO_PRINTED_TITLE: GNU Sample
#+SUBTITLE: for version {{{version}}}, {{{updated}}}

* Copying
:PROPERTIES:
:COPYING: t
:END:
```

This manual is for GNU Sample (version {{{version}}}),  
 {{{updated}}}), which is an example in the Texinfo documentation.

Copyright @@texinfo:copyright{}@@ 2013 Free Software Foundation,  
 Inc.

#+BEGIN\_QUOTE

Permission is granted to copy, distribute and/or modify this  
 document under the terms of the GNU Free Documentation License,  
 Version 1.3 or any later version published by the Free Software  
 Foundation; with no Invariant Sections, with no Front-Cover Texts,  
 and with no Back-Cover Texts. A copy of the license is included in  
 the section entitled "GNU Free Documentation License".

#+END\_QUOTE

\* Invoking sample

#+PINDEX: sample

#+CINDEX: invoking @command{sample}

This is a sample manual. There is no sample program to invoke, but  
 if there were, you could see its basic usage and command line  
 options here.

\* GNU Free Documentation License

:PROPERTIES:

:APPENDIX: t

:END:

#+TEXINFO: @include fdl.texi

\* Index

:PROPERTIES:

:INDEX: cp

:END:

## 12.15 iCalendar export

Some people use Org mode for keeping track of projects, but still prefer a standard calendar application for anniversaries and appointments. In this case it can be useful to show deadlines and other time-stamped items in Org files in the calendar application. Org mode can export calendar information in the standard iCalendar format. If you also want to have TODO entries included in the export, configure the variable `org-icalendar-include-todo`. Plain timestamps are exported as VEVENT, and TODO items as VTODO. It will also create events from deadlines that are in non-TODO items. Deadlines and scheduling

dates in TODO items will be used to set the start and due dates for the TODO entry<sup>40</sup>. As categories, it will use the tags locally defined in the heading, and the file/tree category<sup>41</sup>. See the variable `org-icalendar-alarm-time` for a way to assign alarms to entries with a time.

The iCalendar standard requires each entry to have a globally unique identifier (UID). Org creates these identifiers during export. If you set the variable `org-icalendar-store-UID`, the UID will be stored in the `:ID:` property of the entry and re-used next time you report this entry. Since a single entry can give rise to multiple iCalendar entries (as a timestamp, a deadline, a scheduled item, and as a TODO item), Org adds prefixes to the UID, depending on what triggered the inclusion of the entry. In this way the UID remains unique, but a synchronization program can still figure out from which entry all the different instances originate.

`C-c C-e c f` `org-icalendar-export-to-ics`  
Create iCalendar entries for the current buffer and store them in the same directory, using a file extension `.ics`.

`C-c C-e c a` `org-icalendar-export-agenda-files`  
Like `C-c C-e c f`, but do this for all files in `org-agenda-files`. For each of these files, a separate iCalendar file will be written.

`C-c C-e c c` `org-icalendar-combine-agenda-files`  
Create a single large iCalendar file from all files in `org-agenda-files` and write it to the file given by `org-icalendar-combined-agenda-file`.

The export will honor SUMMARY, DESCRIPTION and LOCATION<sup>42</sup> properties if the selected entries have them. If not, the summary will be derived from the headline, and the description from the body (limited to `org-icalendar-include-body` characters).

How this calendar is best read and updated, depends on the application you are using. The FAQ covers this issue.

## 12.16 Other built-in back-ends

On top of the aforementioned back-ends, Org comes with other built-in ones:

- `ox-man.el`: export to a man page.

To activate these export back-end, customize `org-export-backends` or load them directly with e.g., `(require 'ox-man)`. This will add new keys in the export dispatcher (see [Section 12.1 \[The export dispatcher\], page 135](#)).

See the comment section of these files for more information on how to use them.

## 12.17 Advanced configuration

<sup>40</sup> See the variables `org-icalendar-use-deadline` and `org-icalendar-use-scheduled`.

<sup>41</sup> To add inherited tags or the TODO state, configure the variable `org-icalendar-categories`.

<sup>42</sup> The LOCATION property can be inherited from higher in the hierarchy if you configure `org-use-property-inheritance` accordingly.

## Hooks

Two hooks are run during the first steps of the export process. The first one, `org-export-before-processing-hook` is called before expanding macros, Babel code and include keywords in the buffer. The second one, `org-export-before-parsing-hook`, as its name suggests, happens just before parsing the buffer. Their main use is for heavy duties, that is duties involving structural modifications of the document. For example, one may want to remove every headline in the buffer during export. The following code can achieve this:

```
(defun my-headline-removal (backend)
  "Remove all headlines in the current buffer.
  BACKEND is the export back-end being used, as a symbol."
  (org-map-entries
    (lambda () (delete-region (point) (progn (forward-line) (point))))))

(add-hook 'org-export-before-parsing-hook 'my-headline-removal)
```

Note that functions used in these hooks require a mandatory argument, a symbol representing the back-end used.

## Filters

Filters are lists of functions applied on a specific part of the output from a given back-end. More explicitly, each time a back-end transforms an Org object or element into another language, all functions within a given filter type are called in turn on the string produced. The string returned by the last function will be the one used in the final output.

There are filter sets for each type of element or object, for plain text, for the parse tree, for the export options and for the final output. They are all named after the same scheme: `org-export-filter-TYPE-functions`, where TYPE is the type targeted by the filter. Valid types are:

body	bold	babel-call
center-block	clock	code
diary-sexp	drawer	dynamic-block
entity	example-block	export-block
export-snippet	final-output	fixed-width
footnote-definition	footnote-reference	headline
horizontal-rule	inline-babel-call	inline-src-block
inlinetask	italic	item
keyword	latex-environment	latex-fragment
line-break	link	node-property
options	paragraph	parse-tree
plain-list	plain-text	planning
property-drawer	quote-block	radio-target
section	special-block	src-block
statistics-cookie	strike-through	subscript
superscript	table	table-cell
table-row	target	timestamp
underline	verbatim	verse-block

For example, the following snippet allows me to use non-breaking spaces in the Org buffer and get them translated into L<sup>A</sup>T<sub>E</sub>X without using the `\nbsp` macro (where `_` stands for the non-breaking space):

```
(defun my-latex-filter-nobreaks (text backend info)
  "Ensure \"_\" are properly handled in LaTeX export."
  (when (org-export-derived-backend-p backend 'latex)
    (replace-regexp-in-string "_" "~" text)))

(add-to-list 'org-export-filter-plain-text-functions
  'my-latex-filter-nobreaks)
```

Three arguments must be provided to a filter: the code being changed, the back-end used, and some information about the export process. You can safely ignore the third argument for most purposes. Note the use of `org-export-derived-backend-p`, which ensures that the filter will only be applied when using `latex` back-end or any other back-end derived from it (e.g., `beamer`).

## Defining filters for individual files

You can customize the export for just a specific file by binding export filter variables using `#+BIND`. Here is an example where we introduce two filters, one to remove brackets from time stamps, and one to entirely remove any strike-through text. The functions doing the filtering are defined in an `src` block that allows the filter function definitions to exist in the file itself and ensures that the functions will be there when needed.

```
#+BIND: org-export-filter-timestamp-functions (tmp-f-timestamp)
#+BIND: org-export-filter-strike-through-functions (tmp-f-strike-through)
#+begin_src emacs-lisp :exports results :results none
  (defun tmp-f-timestamp (s backend info)
    (replace-regexp-in-string "&[lg]t;\\|[] []" "" s))
  (defun tmp-f-strike-through (s backend info) "")
#+end_src
```

## Extending an existing back-end

This is obviously the most powerful customization, since the changes happen at the parser level. Indeed, some export back-ends are built as extensions of other ones (e.g., Markdown back-end an extension of HTML back-end).

Extending a back-end means that if an element type is not transcoded by the new back-end, it will be handled by the original one. Hence you can extend specific parts of a back-end without too much work.

As an example, imagine we want the `ascii` back-end to display the language used in a source block, when it is available, but only when some attribute is non-`nil`, like the following:

```
#+ATTR_ASCII: :language t
```

Because that back-end is lacking in that area, we are going to create a new back-end, `my-ascii` that will do the job.



```
(defun my-ascii-src-block (src-block contents info)
  "Transcode a SRC-BLOCK element from Org to ASCII.
  CONTENTS is nil. INFO is a plist used as a communication
  channel."
  (if (not (org-export-read-attribute :attr_ascii src-block :language))
      (org-export-with-backend 'ascii src-block contents info)
      (concat
        (format ",--[ %s ]--\n%s`-----"
          (org-element-property :language src-block)
          (replace-regexp-in-string
            "~" "| "
            (org-element-normalize-string
              (org-export-format-code-default src-block info))))))

  (org-export-define-derived-backend 'my-ascii 'ascii
    :translate-alist '((src-block . my-ascii-src-block)))
```

The `my-ascii-src-block` function looks at the attribute above the element. If it isn't true, it gives hand to the `ascii` back-end. Otherwise, it creates a box around the code, leaving room for the language. A new back-end is then created. It only changes its behavior when translating `src-block` type element. Now, all it takes to use the new back-end is calling the following from an Org buffer:

```
(org-export-to-buffer 'my-ascii "*Org MY-ASCII Export*")
```

It is obviously possible to write an interactive function for this, install it in the export dispatcher menu, and so on.

## 12.18 Export in foreign buffers

Most built-in back-ends come with a command to convert the selected region into a selected format and replace this region by the exported output. Here is a list of such conversion commands:

**org-html-convert-region-to-html**

Convert the selected region into HTML.

**org-latex-convert-region-to-latex**

Convert the selected region into L<sup>A</sup>T<sub>E</sub>X.

**org-texinfo-convert-region-to-texinfo**

Convert the selected region into Texinfo.

**org-md-convert-region-to-md**

Convert the selected region into Markdown.

This is particularly useful for converting tables and lists in foreign buffers. E.g., in an HTML buffer, you can turn on `orgstruct-mode`, then use Org commands for editing a list, and finally select and convert the list with `M-x org-html-convert-region-to-html RET`.

## 13 Publishing

Org includes a publishing management system that allows you to configure automatic HTML conversion of *projects* composed of interlinked org files. You can also configure Org to automatically upload your exported HTML pages and related attachments, such as images and source code files, to a web server.

You can also use Org to convert files into PDF, or even combine HTML and PDF conversion so that files are available in both formats on the server.

Publishing has been contributed to Org by David O'Toole.

### 13.1 Configuration

Publishing needs significant configuration to specify files, destination and many other properties of a project.

#### 13.1.1 The variable `org-publish-project-alist`

Publishing is configured almost entirely through setting the value of one variable, called `org-publish-project-alist`. Each element of the list configures one project, and may be in one of the two following forms:

```
("project-name" :property value :property value ...)
    i.e., a well-formed property list with alternating keys and values
or
("project-name" :components ("project-name" "project-name" ...))
```

In both cases, projects are configured by specifying property values. A project defines the set of files that will be published, as well as the publishing configuration to use when publishing those files. When a project takes the second form listed above, the individual members of the `:components` property are taken to be sub-projects, which group together files requiring different publishing options. When you publish such a “meta-project”, all the components will also be published, in the sequence given.

#### 13.1.2 Sources and destinations for files

Most properties are optional, but some should always be set. In particular, Org needs to know where to look for source files, and where to put published files.

<code>:base-directory</code>	Directory containing publishing source files
<code>:publishing-directory</code>	Directory where output files will be published. You can directly publish to a web server using a file name syntax appropriate for the Emacs <code>tramp</code> package. Or you can publish to a local directory and use external tools to upload your website (see <a href="#">Section 13.2 [Uploading files]</a> , page 191).
<code>:preparation-function</code>	Function or list of functions to be called before starting the publishing process, for example, to run <code>make</code> for updating files to be published. Each preparation function is called with a single argument, the project property list.

**:completion-function**      Function or list of functions called after finishing the publishing process, for example, to change permissions of the resulting files. Each completion function is called with a single argument, the project property list.

### 13.1.3 Selecting files

By default, all files with extension `.org` in the base directory are considered part of the project. This can be modified by setting the properties

**:base-extension**      Extension (without the dot!) of source files. This actually is a regular expression. Set this to the symbol `any` if you want to get all files in **:base-directory**, even without extension.

**:exclude**      Regular expression to match file names that should not be published, even though they have been selected on the basis of their extension.

**:include**      List of files to be included regardless of **:base-extension** and **:exclude**.

**:recursive**      `non-nil` means, check **base-directory** recursively for files to publish.

### 13.1.4 Publishing action

Publishing means that a file is copied to the destination directory and possibly transformed in the process. The default transformation is to export Org files as HTML files, and this is done by the function `org-html-publish-to-html`, which calls the HTML exporter (see [Section 12.9 \[HTML export\]](#), page 147). But you also can publish your content as PDF files using `org-latex-publish-to-pdf` or as `ascii`, `Texinfo`, etc., using the corresponding functions.

If you want to publish the Org file as an `.org` file but with the *archived*, *commented* and *tag-excluded* trees removed, use the function `org-org-publish-to-org`. This will produce `file.org` and put it in the publishing directory. If you want a htmlized version of this file, set the parameter **:htmlized-source** to `t`, it will produce `file.org.html` in the publishing directory<sup>1</sup>.

Other files like images only need to be copied to the publishing destination. For this you can use `org-publish-attachment`. For non-org files, you always need to specify the publishing function:

**:publishing-function**      Function executing the publication of a file. This may also be a list of functions, which will all be called in turn.

**:htmlized-source**      `non-nil` means, publish htmlized source.

The function must accept three arguments: a property list containing at least a **:publishing-directory** property, the name of the file to be published and the path to

---

<sup>1</sup> If the publishing directory is the same than the source directory, `file.org` will be exported as `file.org.org`, so probably don't want to do this.

the publishing directory of the output file. It should take the specified file, make the necessary transformation (if any) and place the result into the destination folder.

### 13.1.5 Options for the exporters

The property list can be used to set export options during the publishing process. In most cases, these properties correspond to user variables in Org. While some properties are available for all export back-ends, most of them are back-end specific. The following sections list properties along with the variable they belong to. See the documentation string of these options for details.

When a property is given a value in `org-publish-project-alist`, its setting overrides the value of the corresponding user variable (if any) during publishing. Options set within a file (see [Section 12.2 \[Export settings\], page 136](#)), however, override everything.

#### Generic properties

<code>:archived-trees</code>	<code>org-export-with-archived-trees</code>
<code>:exclude-tags</code>	<code>org-export-exclude-tags</code>
<code>:headline-levels</code>	<code>org-export-headline-levels</code>
<code>:language</code>	<code>org-export-default-language</code>
<code>:preserve-breaks</code>	<code>org-export-preserve-breaks</code>
<code>:section-numbers</code>	<code>org-export-with-section-numbers</code>
<code>:select-tags</code>	<code>org-export-select-tags</code>
<code>:with-author</code>	<code>org-export-with-author</code>
<code>:with-broken-links</code>	<code>org-export-with-broken-links</code>
<code>:with-clocks</code>	<code>org-export-with-clocks</code>
<code>:with-creator</code>	<code>org-export-with-creator</code>
<code>:with-date</code>	<code>org-export-with-date</code>
<code>:with-drawers</code>	<code>org-export-with-drawers</code>
<code>:with-email</code>	<code>org-export-with-email</code>
<code>:with-emphasize</code>	<code>org-export-with-emphasize</code>
<code>:with-fixed-width</code>	<code>org-export-with-fixed-width</code>
<code>:with-footnotes</code>	<code>org-export-with-footnotes</code>
<code>:with-latex</code>	<code>org-export-with-latex</code>
<code>:with-planning</code>	<code>org-export-with-planning</code>
<code>:with-priority</code>	<code>org-export-with-priority</code>
<code>:with-properties</code>	<code>org-export-with-properties</code>
<code>:with-special-strings</code>	<code>org-export-with-special-strings</code>
<code>:with-sub-superscript</code>	<code>org-export-with-sub-superscripts</code>
<code>:with-tables</code>	<code>org-export-with-tables</code>
<code>:with-tags</code>	<code>org-export-with-tags</code>
<code>:with-tasks</code>	<code>org-export-with-tasks</code>
<code>:with-timestamps</code>	<code>org-export-with-timestamps</code>
<code>:with-title</code>	<code>org-export-with-title</code>
<code>:with-toc</code>	<code>org-export-with-toc</code>
<code>:with-todo-keywords</code>	<code>org-export-with-todo-keywords</code>

## ASCII specific properties

:ascii-bullets	org-ascii-bullets
:ascii-caption-above	org-ascii-caption-above
:ascii-charset	org-ascii-charset
:ascii-global-margin	org-ascii-global-margin
:ascii-format-drawer-function	org-ascii-format-drawer-function
:ascii-format-inlinetask-function	org-ascii-format-inlinetask-function
:ascii-headline-spacing	org-ascii-headline-spacing
:ascii-indented-line-width	org-ascii-indented-line-width
:ascii-inlinetask-width	org-ascii-inlinetask-width
:ascii-inner-margin	org-ascii-inner-margin
:ascii-links-to-notes	org-ascii-links-to-notes
:ascii-list-margin	org-ascii-list-margin
:ascii-paragraph-spacing	org-ascii-paragraph-spacing
:ascii-quote-margin	org-ascii-quote-margin
:ascii-table-keep-all-vertical-lines	org-ascii-table-keep-all-vertical-lines
:ascii-table-use-ascii-art	org-ascii-table-use-ascii-art
:ascii-table-widen-columns	org-ascii-table-widen-columns
:ascii-text-width	org-ascii-text-width
:ascii-underline	org-ascii-underline
:ascii-verbatim-format	org-ascii-verbatim-format

## Beamer specific properties

:beamer-theme	org-beamer-theme
:beamer-column-view-format	org-beamer-column-view-format
:beamer-environments-extra	org-beamer-environments-extra
:beamer-frame-default-options	org-beamer-frame-default-options
:beamer-outline-frame-options	org-beamer-outline-frame-options
:beamer-outline-frame-title	org-beamer-outline-frame-title
:beamer-subtitle-format	org-beamer-subtitle-format

## HTML specific properties

:html-allow-name-attribute-in-anchors	org-html-allow-name-attribute-in-anchors
:html-checkbox-type	org-html-checkbox-type
:html-container	org-html-container-element
:html-divs	org-html-divs
:html-doctype	org-html-doctype
:html-extension	org-html-extension
:html-footnote-format	org-html-footnote-format
:html-footnote-separator	org-html-footnote-separator
:html-footnotes-section	org-html-footnotes-section
:html-format-drawer-function	org-html-format-drawer-function
:html-format-headline-function	org-html-format-headline-function
:html-format-inlinetask-function	org-html-format-inlinetask-function
:html-head-extra	org-html-head-extra
:html-head-include-default-style	org-html-head-include-default-style

:html-head-include-scripts	org-html-head-include-scripts
:html-head	org-html-head
:html-home/up-format	org-html-home/up-format
:html-html5-fancy	org-html-html5-fancy
:html-indent	org-html-indent
:html-infojs-options	org-html-infojs-options
:html-infojs-template	org-html-infojs-template
:html-inline-image-rules	org-html-inline-image-rules
:html-inline-images	org-html-inline-images
:html-link-home	org-html-link-home
:html-link-org-files-as-html	org-html-link-org-files-as-html
:html-link-up	org-html-link-up
:html-link-use-abs-url	org-html-link-use-abs-url
:html-mathjax-options	org-html-mathjax-options
:html-mathjax-template	org-html-mathjax-template
:html-metadata-timestamp-format	org-html-metadata-timestamp-format
:html-postamble-format	org-html-postamble-format
:html-postamble	org-html-postamble
:html-preamble-format	org-html-preamble-format
:html-preamble	org-html-preamble
:html-table-align-individual-fields	org-html-table-align-individual-fields
:html-table-attributes	org-html-table-default-attributes
:html-table-caption-above	org-html-table-caption-above
:html-table-data-tags	org-html-table-data-tags
:html-table-header-tags	org-html-table-header-tags
:html-table-row-tags	org-html-table-row-tags
:html-table-use-header-tags-for-first-column	org-html-table-use-header-tags-for-first-column
:html-tag-class-prefix	org-html-tag-class-prefix
:html-text-markup-alist	org-html-text-markup-alist
:html-todo-kwd-class-prefix	org-html-todo-kwd-class-prefix
:html-toplevel-hlevel	org-html-toplevel-hlevel
:html-use-infojs	org-html-use-infojs
:html-validation-link	org-html-validation-link
:html-viewport	org-html-viewport
:html-xml-declaration	org-html-xml-declaration

## **L<sup>A</sup>T<sub>E</sub>X** specific properties

:latex-active-timestamp-format	org-latex-active-timestamp-format
:latex-caption-above	org-latex-caption-above
:latex-classes	org-latex-classes
:latex-class	org-latex-default-class
:latex-compiler	org-latex-compiler
:latex-default-figure-position	org-latex-default-figure-position
:latex-default-table-environment	org-latex-default-table-environment
:latex-default-table-mode	org-latex-default-table-mode
:latex-diary-timestamp-format	org-latex-diary-timestamp-format

<code>:latex-footnote-defined-format</code>	<code>org-latex-footnote-defined-format</code>
<code>:latex-footnote-separator</code>	<code>org-latex-footnote-separator</code>
<code>:latex-format-drawer-function</code>	<code>org-latex-format-drawer-function</code>
<code>:latex-format-headline-function</code>	<code>org-latex-format-headline-function</code>
<code>:latex-format-inlinetask-function</code>	<code>org-latex-format-inlinetask-function</code>
<code>:latex-hyperref-template</code>	<code>org-latex-hyperref-template</code>
<code>:latex-image-default-height</code>	<code>org-latex-image-default-height</code>
<code>:latex-image-default-option</code>	<code>org-latex-image-default-option</code>
<code>:latex-image-default-width</code>	<code>org-latex-image-default-width</code>
<code>:latex-images-centered</code>	<code>org-latex-images-centered</code>
<code>:latex-inactive-timestamp-format</code>	<code>org-latex-inactive-timestamp-format</code>
<code>:latex-inline-image-rules</code>	<code>org-latex-inline-image-rules</code>
<code>:latex-link-with-unknown-path-format</code>	<code>org-latex-link-with-unknown-path-format</code>
<code>:latex-listings-langs</code>	<code>org-latex-listings-langs</code>
<code>:latex-listings-options</code>	<code>org-latex-listings-options</code>
<code>:latex-listings</code>	<code>org-latex-listings</code>
<code>:latex-minted-langs</code>	<code>org-latex-minted-langs</code>
<code>:latex-minted-options</code>	<code>org-latex-minted-options</code>
<code>:latex-prefer-user-labels</code>	<code>org-latex-prefer-user-labels</code>
<code>:latex-subtitle-format</code>	<code>org-latex-subtitle-format</code>
<code>:latex-subtitle-separate</code>	<code>org-latex-subtitle-separate</code>
<code>:latex-table-scientific-notation</code>	<code>org-latex-table-scientific-notation</code>
<code>:latex-tables-booktabs</code>	<code>org-latex-tables-booktabs</code>
<code>:latex-tables-centered</code>	<code>org-latex-tables-centered</code>
<code>:latex-text-markup-alist</code>	<code>org-latex-text-markup-alist</code>
<code>:latex-title-command</code>	<code>org-latex-title-command</code>
<code>:latex-toc-command</code>	<code>org-latex-toc-command</code>

## Markdown specific properties

<code>:md-footnote-format</code>	<code>org-md-footnote-format</code>
<code>:md-footnotes-section</code>	<code>org-md-footnotes-section</code>
<code>:md-headline-style</code>	<code>org-md-headline-style</code>

## ODT specific properties

<code>:odt-content-template-file</code>	<code>org-odt-content-template-file</code>
<code>:odt-display-outline-level</code>	<code>org-odt-display-outline-level</code>
<code>:odt-fontify-srcblocks</code>	<code>org-odt-fontify-srcblocks</code>
<code>:odt-format-drawer-function</code>	<code>org-odt-format-drawer-function</code>
<code>:odt-format-headline-function</code>	<code>org-odt-format-headline-function</code>
<code>:odt-format-inlinetask-function</code>	<code>org-odt-format-inlinetask-function</code>
<code>:odt-inline-formula-rules</code>	<code>org-odt-inline-formula-rules</code>
<code>:odt-inline-image-rules</code>	<code>org-odt-inline-image-rules</code>
<code>:odt-pixels-per-inch</code>	<code>org-odt-pixels-per-inch</code>
<code>:odt-styles-file</code>	<code>org-odt-styles-file</code>
<code>:odt-table-styles</code>	<code>org-odt-table-styles</code>
<code>:odt-use-date-fields</code>	<code>org-odt-use-date-fields</code>

## Texinfo specific properties

<code>:texinfo-active-timestamp-format</code>	<code>org-texinfo-active-timestamp-format</code>
<code>:texinfo-classes</code>	<code>org-texinfo-classes</code>
<code>:texinfo-class</code>	<code>org-texinfo-default-class</code>
<code>:texinfo-def-table-markup</code>	<code>org-texinfo-def-table-markup</code>
<code>:texinfo-diary-timestamp-format</code>	<code>org-texinfo-diary-timestamp-format</code>
<code>:texinfo-filename</code>	<code>org-texinfo-filename</code>
<code>:texinfo-format-drawer-function</code>	<code>org-texinfo-format-drawer-function</code>
<code>:texinfo-format-headline-function</code>	<code>org-texinfo-format-headline-function</code>
<code>:texinfo-format-inlinetask-function</code>	<code>org-texinfo-format-inlinetask-function</code>
<code>:texinfo-inactive-timestamp-format</code>	<code>org-texinfo-inactive-timestamp-format</code>
<code>:texinfo-link-with-unknown-path-format</code>	<code>org-texinfo-link-with-unknown-path-format</code>
<code>:texinfo-node-description-column</code>	<code>org-texinfo-node-description-column</code>
<code>:texinfo-table-scientific-notation</code>	<code>org-texinfo-table-scientific-notation</code>
<code>:texinfo-tables-verbatim</code>	<code>org-texinfo-tables-verbatim</code>
<code>:texinfo-text-markup-alist</code>	<code>org-texinfo-text-markup-alist</code>

### 13.1.6 Links between published files

To create a link from one Org file to another, you would use something like ‘`[[file:foo.org][The foo]]`’ or simply ‘`file:foo.org`’ (see [Section 4.3 \[External links\]](#), [page 39](#)). When published, this link becomes a link to `foo.html`. You can thus interlink the pages of your “org web” project and the links will work as expected when you publish them to HTML. If you also publish the Org source file and want to link to it, use an `http:` link instead of a `file:` link, because `file:` links are converted to link to the corresponding `html` file.

You may also link to related files, such as images. Provided you are careful with relative file names, and provided you have also configured Org to upload the related files, these links will work too. See [Section 13.3.2 \[Complex example\]](#), [page 192](#), for an example of this usage.

Eventually, links between published documents can contain some search options (see [Section 4.7 \[Search options\]](#), [page 45](#)), which will be resolved to the appropriate location in the linked file. For example, once published to HTML, the following links all point to a dedicated anchor in `foo.html`.

```
[[file:foo.org:*heading]]
[[file:foo.org:#custom-id]]
[[file:foo.org:target]]
```

### 13.1.7 Generating a sitemap

The following properties may be used to control publishing of a map of files for a given project.

<code>:auto-sitemap</code>	When non-nil, publish a sitemap during <code>org-publish-current-project</code> or <code>org-publish-all</code> .
<code>:sitemap-filename</code>	Filename for output of sitemap. Defaults to <code>sitemap.org</code> (which becomes <code>sitemap.html</code> ).



<code>:sitemap-title</code>	Title of sitemap page. Defaults to name of file.
<code>:sitemap-function</code>	Plug-in function to use for generation of the sitemap. Defaults to <code>org-publish-org-sitemap</code> , which generates a plain list of links to all files in the project.
<code>:sitemap-sort-folders</code>	Where folders should appear in the sitemap. Set this to <code>first</code> (default) or <code>last</code> to display folders first or last, respectively. Any other value will mix files and folders.
<code>:sitemap-sort-files</code>	How the files are sorted in the site map. Set this to <code>alphabetically</code> (default), <code>chronologically</code> or <code>anti-chronologically</code> . <code>chronologically</code> sorts the files with older date first while <code>anti-chronologically</code> sorts the files with newer date first. <code>alphabetically</code> sorts the files alphabetically. The date of a file is retrieved with <code>org-publish-find-date</code> .
<code>:sitemap-ignore-case</code>	Should sorting be case-sensitive? Default <code>nil</code> .
<code>:sitemap-file-entry-format</code>	With this option one can tell how a sitemap's entry is formatted in the sitemap. This is a format string with some escape sequences: <code>%t</code> stands for the title of the file, <code>%a</code> stands for the author of the file and <code>%d</code> stands for the date of the file. The date is retrieved with the <code>org-publish-find-date</code> function and formatted with <code>org-publish-sitemap-date-format</code> . Default <code>%t</code> .
<code>:sitemap-date-format</code>	Format string for the <code>format-time-string</code> function that tells how a sitemap entry's date is to be formatted. This property bypasses <code>org-publish-sitemap-date-format</code> which defaults to <code>%Y-%m-%d</code> .
<code>:sitemap-sans-extension</code>	When non- <code>nil</code> , remove filenames' extensions from the generated sitemap. Useful to have cool URIs (see <a href="http://www.w3.org/Provider/Style/URI">http://www.w3.org/Provider/Style/URI</a> ). Defaults to <code>nil</code> .

### 13.1.8 Generating an index

Org mode can generate an index across the files of a publishing project.

<code>:makeindex</code>	When non- <code>nil</code> , generate an index in the file <code>theindex.org</code> and publish it as <code>theindex.html</code> .
-------------------------	-------------------------------------------------------------------------------------------------------------------------------------

The file will be created when first publishing a project with the `:makeindex` set. The file only contains a statement `#+INCLUDE: "theindex.inc"`. You can then build around this include statement by adding a title, style information, etc.

Index entries are specified with `#+INDEX` keyword. An entry that contains an exclamation mark will create a sub item.

```
* Curriculum Vitae
#+INDEX: CV
#+INDEX: Application!CV
```

## 13.2 Uploading files

For those people already utilizing third party sync tools such as `rsync` or `unison`, it might be preferable not to use the built in *remote* publishing facilities of Org mode which rely heavily on Tramp. Tramp, while very useful and powerful, tends not to be so efficient for multiple file transfer and has been known to cause problems under heavy usage.

Specialized synchronization utilities offer several advantages. In addition to timestamp comparison, they also do content and permissions/attribute checks. For this reason you might prefer to publish your web to a local directory (possibly even *in place* with your Org files) and then use `unison` or `rsync` to do the synchronization with the remote host.

Since Unison (for example) can be configured as to which files to transfer to a certain remote destination, it can greatly simplify the project publishing definition. Simply keep all files in the correct location, process your Org files with `org-publish` and let the synchronization tool do the rest. You do not need, in this scenario, to include attachments such as `jpg`, `css` or `gif` files in the project definition since the 3rd party tool syncs them.

Publishing to a local directory is also much faster than to a remote one, so that you can afford more easily to republish entire projects. If you set `org-publish-use-timestamps-flag` to `nil`, you gain the main benefit of re-including any changed external files such as source example files you might include with `#+INCLUDE:.` The timestamp mechanism in Org is not smart enough to detect if included files have been modified.

## 13.3 Sample configuration

Below we provide two example configurations. The first one is a simple project publishing only a set of Org files. The second example is more complex, with a multi-component project.

### 13.3.1 Example: simple publishing configuration

This example publishes a set of Org files to the `public_html` directory on the local machine.

```
(setq org-publish-project-alist
  '(("org"
    :base-directory "~/org/"
    :publishing-directory "~/public_html"
    :section-numbers nil
    :with-toc nil
    :html-head "<link rel=\"stylesheet\"
               href=\"../other/mystyle.css\"
               type=\"text/css\"/>"))))
```

### 13.3.2 Example: complex publishing configuration

This more complicated example publishes an entire website, including Org files converted to HTML, image files, Emacs Lisp source code, and style sheets. The publishing directory is remote and private files are excluded.

To ensure that links are preserved, care should be taken to replicate your directory structure on the web server, and to use relative file paths. For example, if your Org files are kept in `~/org` and your publishable images in `~/images`, you would link to an image with

```
file:../images/myimage.png
```

On the web server, the relative path to the image should be the same. You can accomplish this by setting up an "images" folder in the right place on the web server, and publishing images to it.

```
(setq org-publish-project-alist
  '(("orgfiles"
    :base-directory "~/org/"
    :base-extension "org"
    :publishing-directory "/ssh:user@host:~/html/notebook/"
    :publishing-function org-html-publish-to-html
    :exclude "PrivatePage.org" ;; regexp
    :headline-levels 3
    :section-numbers nil
    :with-toc nil
    :html-head "<link rel=\"stylesheet\"
              href=\"../other/mystyle.css\" type=\"text/css\"/>"
    :html-preamble t)

    ("images"
     :base-directory "~/images/"
     :base-extension "jpg\\|gif\\|png"
     :publishing-directory "/ssh:user@host:~/html/images/"
     :publishing-function org-publish-attachment)

    ("other"
     :base-directory "~/other/"
     :base-extension "css\\|el"
     :publishing-directory "/ssh:user@host:~/html/other/"
     :publishing-function org-publish-attachment)

    ("website" :components ("orgfiles" "images" "other"))))
```

## 13.4 Triggering publication

Once properly configured, Org can publish with the following commands:

`C-c C-e P x` org-publish

Prompt for a specific project and publish all files that belong to it.

`C-c C-e P p` org-publish-current-project

Publish the project containing the current file.

*C-c C-e P f* **org-publish-current-file**  
Publish only the current file.

*C-c C-e P a* **org-publish-all**  
Publish every project.

Org uses timestamps to track when a file has changed. The above functions normally only publish changed files. You can override this and force publishing of all files by giving a prefix argument to any of the commands above, or by customizing the variable **org-publish-use-timestamps-flag**. This may be necessary in particular if files include other files via **#+SETUPFILE:** or **#+INCLUDE:.**

## 14 Working with source code

Source code can be included in Org mode documents using a ‘src’ block, e.g.:

```
#+BEGIN_SRC emacs-lisp
(defun org-xor (a b)
  "Exclusive or."
  (if a (not b) b))
#+END_SRC
```

Org mode provides a number of features for working with live source code, including editing of code blocks in their native major-mode, evaluation of code blocks, converting code blocks into source files (known as *tangling* in literate programming), and exporting code blocks and their results in several formats. This functionality was contributed by Eric Schulte and Dan Davison, and was originally named Org-babel.

The following sections describe Org mode’s code block handling facilities.

### 14.1 Structure of code blocks

Live code blocks can be specified with a ‘src’ block or inline.<sup>1</sup> The structure of a ‘src’ block is

```
#+NAME: <name>
#+BEGIN_SRC <language> <switches> <header arguments>
<body>
#+END_SRC
```

The `#+NAME:` line is optional, and can be used to name the code block. Live code blocks require that a language be specified on the `#+BEGIN_SRC` line. Switches and header arguments are optional.

Live code blocks can also be specified inline using

```
src_<language>{<body>}
```

or

```
src_<language>[<header arguments>]{<body>}
```

`<#+NAME: name>`

This line associates a name with the code block. This is similar to the `#+NAME: Name` lines that can be used to name tables in Org mode files. Referencing the name of a code block makes it possible to evaluate the block from other places in the file, from other files, or from Org mode table formulas (see [Section 3.5 \[The spreadsheet\]](#), page 24). Names are assumed to be unique and the behavior of Org mode when two or more blocks share the same name is undefined.

`<language>`

The language of the code in the block (see [Section 14.7 \[Languages\]](#), page 199).

`<switches>`

Optional switches control code block export (see the discussion of switches in [Section 11.5 \[Literal examples\]](#), page 129)

---

<sup>1</sup> Note that ‘src’ blocks may be inserted using Org mode’s [Section 15.2 \[Easy templates\]](#), page 224 system

**<header arguments>**

Optional header arguments control many aspects of evaluation, export and tangling of code blocks (see [Section 14.8 \[Header arguments\]](#), page 200). Header arguments can also be set on a per-buffer or per-subtree basis using properties.

**source code, header arguments**

**<body>** Source code in the specified language.

## 14.2 Editing source code

Use `C-c '` to edit the current code block. This brings up a language major-mode edit buffer containing the body of the code block. Manually saving this buffer with `C-x C-s` will write the contents back to the Org buffer. You can also set `org-edit-src-auto-save-idle-delay` to save the base buffer after some idle delay, or `org-edit-src-turn-on-auto-save` to auto-save this buffer into a separate file using `auto-save-mode`. Use `C-c '` again to exit.

The `org-src-mode` minor mode will be active in the edit buffer. The following variables can be used to configure the behavior of the edit buffer. See also the customization group `org-edit-structure` for further configuration options.

**org-src-lang-modes**

If an Emacs major-mode named `<lang>-mode` exists, where `<lang>` is the language named in the header line of the code block, then the edit buffer will be placed in that major-mode. This variable can be used to map arbitrary language names to existing major modes.

**org-src-window-setup**

Controls the way Emacs windows are rearranged when the edit buffer is created.

**org-src-preserve-indentation**

By default, the value is `nil`, which means that code blocks evaluated during export or tangled are indented according to context, possibly altering leading sequences of spaces and tab characters in the process. When non-`nil`, indentation is relative to left column, and therefore, not modified during export or tangling. This variable is especially useful for tangling languages such as Python, in which whitespace indentation in the output is critical.

**org-src-ask-before-returning-to-edit-buffer**

By default, Org will ask before returning to an open edit buffer. Set this variable to `nil` to switch without asking.

To turn on native code fontification in the *Org* buffer, set the variable `org-src-fontify-natively` to non-`nil`. You can also change the appearance of source blocks in general by customizing the `org-block` face or `org-src-block-faces` for specific languages. The following example shades the background of “ordinary” blocks while allowing Emacs Lisp and Python source blocks to have a separate colors.

```
(require 'color)
(set-face-attribute 'org-block nil :background
  (color-darken-name
    (face-attribute 'default :background) 3))
```

```
(setq org-src-block-faces '(("emacs-lisp" (:background "#EEE2FF"))
  ("python" (:background "#E5FFB8"))))
```

### 14.3 Exporting code blocks

It is possible to export the *code* of code blocks, the *results* of code block evaluation, *both* the code and the results of code block evaluation, or *none*. For most languages, the default exports code. However, for some languages (e.g., `ditaa`) the default exports the results of code block evaluation. For information on exporting code block bodies, see [Section 11.5 \[Literal examples\]](#), page 129. For information on exporting parts of Org documents, see [Chapter 12 \[Exporting\]](#), page 135.

The `:exports` header argument can be used to specify export behavior (note that these arguments are only relevant for code blocks, not inline code):

#### Header arguments:

##### `:exports code`

The default in most languages. The body of the code block is exported, as described in [Section 11.5 \[Literal examples\]](#), page 129.

##### `:exports results`

The code block will be evaluated each time to buffer is exported, and the results will be placed in the Org mode buffer for export, either updating previous results of the code block located anywhere in the buffer or, if no previous results exist, placing the results immediately after the code block. The body of the code block will not be exported.

##### `:exports both`

Both the code block and its results will be exported.

##### `:exports none`

Neither the code block nor its results will be exported.

It is possible to inhibit the evaluation of code blocks during export. Setting the `org-export-babel-evaluate` variable to `nil` will ensure that no code blocks are evaluated as part of the export process. This can be useful in situations where potentially untrusted Org mode files are exported in an automated fashion, for example when Org mode is used as the markup language for a wiki. It is also possible to set this variable to `inline-only`. In that case, only inline code blocks will be evaluated, in order to insert their results. Non-inline code blocks are assumed to have their results already inserted in the buffer by manual evaluation. This setting is useful to avoid expensive recalculations during export, not to provide security.

Code blocks in commented subtrees (see [Section 12.6 \[Comment lines\]](#), page 142) are never evaluated on export. However, code blocks in subtrees excluded from export (see [Section 12.2 \[Export settings\]](#), page 136) may be evaluated on export.

### 14.4 Extracting source code

Creating pure source code files by extracting code from source blocks is referred to as “tangling”—a term adopted from the literate programming community. During “tangling”

of code blocks their bodies are expanded using `org-babel-expand-src-block` which can expand both variable and “noweb” style references (see [Section 14.10 \[Noweb reference syntax\]](#), page 221).

## Header arguments

`:tangle no`

The default. The code block is not included in the tangled output.

`:tangle yes`

Include the code block in the tangled output. The output file name is the name of the org file with the extension `.org` replaced by the extension for the block language.

`:tangle filename`

Include the code block in the tangled output to file `'filename'`.

## Functions

`org-babel-tangle`

Tangle the current file. Bound to `C-c C-v t`.

With prefix argument only tangle the current code block.

`org-babel-tangle-file`

Choose a file to tangle. Bound to `C-c C-v f`.

## Hooks

`org-babel-post-tangle-hook`

This hook is run from within code files tangled by `org-babel-tangle`. Example applications could include post-processing, compilation or evaluation of tangled code files.

## Jumping between code and Org

When tangling code from an Org-mode buffer to a source code file, you'll frequently find yourself viewing the file of tangled source code (e.g., many debuggers point to lines of the source code file). It is useful to be able to navigate from the tangled source to the Org-mode buffer from which the code originated.

The `org-babel-tangle-jump-to-org` function provides this jumping from code to Org-mode functionality. Two header arguments are required for jumping to work, first the `padline` ([Section 14.8.2.12 \[padline\]](#), page 211) option must be set to true (the default setting), second the `comments` ([Section 14.8.2.11 \[comments\]](#), page 211) header argument must be set to `link`, which will insert comments into the source code buffer which point back to the original Org-mode file.



## 14.5 Evaluating code blocks

Code blocks can be evaluated<sup>2</sup> and the results of evaluation optionally placed in the Org mode buffer. The results of evaluation are placed following a line that begins by default with `#+RESULTS` and optionally a cache identifier and/or the name of the evaluated code block. The default value of `#+RESULTS` can be changed with the customizable variable `org-babel-results-keyword`.

By default, the evaluation facility is only enabled for Lisp code blocks specified as `emacs-lisp`. See [Section 14.7 \[Languages\]](#), page 199 to enable other supported languages. See [Section 14.1 \[Structure of code blocks\]](#), page 194 for information on the syntax used to define a code block.

There are a number of ways to evaluate code blocks. The simplest is to press `C-c C-c` or `C-c C-v e` with the point on a code block<sup>3</sup>. This will call the `org-babel-execute-src-block` function to evaluate the block and insert its results into the Org mode buffer.

It is also possible to evaluate named code blocks from anywhere<sup>4</sup> in an Org mode buffer or an Org mode table. These named code blocks can be located in the current Org mode buffer or in the “Library of Babel” (see [Section 14.6 \[Library of Babel\]](#), page 199). Named code blocks can be evaluated with a separate `#+CALL:` line or inline within a block of text. In both cases the result is wrapped according to the value of `org-babel-inline-result-wrap`, which by default is `"= %s ="` for markup that produces verbatim text.

The syntax of the `#+CALL:` line is

```
#+CALL: <name>(<arguments>)
#+CALL: <name>[<inside header arguments>](<arguments>) <end header arguments>
```

The syntax for inline evaluation of named code blocks is

```
... call_<name>(<arguments>) ...
... call_<name>[<inside header arguments>](<arguments>)[<end header arguments>] ...
```

**<name>** The name of the code block to be evaluated (see [Section 14.1 \[Structure of code blocks\]](#), page 194).

**<arguments>**

Arguments specified in this section will be passed to the code block. These arguments use standard function call syntax, rather than header argument syntax. For example, a `#+CALL:` line that passes the number four to a code block named `double`, which declares the header argument `:var n=2`, would be written as `#+CALL: double(n=4)`.

**<inside header arguments>**

Inside header arguments are passed through and applied to the named code block. These arguments use header argument syntax rather than standard

<sup>2</sup> Whenever code is evaluated there is a potential for that code to do harm. Org mode provides safeguards to ensure that code is only evaluated after explicit confirmation from the user. For information on these safeguards (and on how to disable them) see [Section 15.4 \[Code evaluation security\]](#), page 225.

<sup>3</sup> The option `org-babel-no-eval-on-ctrl-c-ctrl-c` can be used to remove code evaluation from the `C-c C-c` key binding.

<sup>4</sup> Actually, the constructs `call_<name>()` and `src_<lang>{ }` are not evaluated when they appear in a keyword line (i.e. lines starting with `#+KEYWORD:`, see [Section 15.6 \[In-buffer settings\]](#), page 226).

function call syntax. Inside header arguments affect how the code block is evaluated. For example, `[:results output]` will collect the results of everything printed to `STDOUT` during execution of the code block.

#### <end header arguments>

End header arguments are applied to the calling instance and do not affect evaluation of the named code block. They affect how the results are incorporated into the Org mode buffer and how the call line is exported. For example, `:results html` will insert the results of the call line evaluation in the Org buffer, wrapped in a `BEGIN_EXPORT html` block.

For more examples of passing header arguments to `#+CALL:` lines see [\[Header arguments in function calls\]](#), page 203.

## 14.6 Library of Babel

The “Library of Babel” consists of code blocks that can be called from any Org mode file. Code blocks defined in the “Library of Babel” can be called remotely as if they were in the current Org mode buffer (see [Section 14.5 \[Evaluating code blocks\]](#), page 198 for information on the syntax of remote code block evaluation).

The central repository of code blocks in the “Library of Babel” is housed in an Org mode file located in the ‘doc’ directory of Org mode.

Users can add code blocks they believe to be generally useful to their “Library of Babel.” The code blocks can be stored in any Org mode file and then loaded into the library with `org-babel-lob-ingest`.

Code blocks located in any Org mode file can be loaded into the “Library of Babel” with the `org-babel-lob-ingest` function, bound to `C-c C-v i`.

## 14.7 Languages

Code blocks in the following languages are supported.

Language	Identifier	Language	Identifier
Asymptote	asymptote	Awk	awk
C	C	C++	C++
Clojure	clojure	CSS	css
D	d	ditaa	ditaa
Graphviz	dot	Emacs Calc	calc
Emacs Lisp	emacs-lisp	Fortran	fortran
gnuplot	gnuplot	Haskell	haskell
Java	java	Javascript	js
LaTeX	latex	Ledger	ledger
Lisp	lisp	Lilypond	lilypond
Lua	lua	MATLAB	matlab
Mscgen	mscgen	Objective Caml	ocaml
Octave	octave	Org mode	org
Oz	oz	Perl	perl
Plantuml	plantuml	Processing.js	processing

Python	python	R	R
Ruby	ruby	Sass	sass
Scheme	scheme	GNU Screen	screen
Sed	sed	shell	sh
SQL	sql	SQLite	sqlite

Language-specific documentation is available for some languages. If available, it can be found at <http://orgmode.org/worg/org-contrib/babel/languages.html>.

The option `org-babel-load-languages` controls which languages are enabled for evaluation (by default only `emacs-lisp` is enabled). This variable can be set using the customization interface or by adding code like the following to your emacs configuration.

The following disables `emacs-lisp` evaluation and enables evaluation of R code blocks.

```
(org-babel-do-load-languages
 'org-babel-load-languages
 '((emacs-lisp . nil)
  (R . t)))
```

It is also possible to enable support for a language by loading the related elisp file with `require`.

The following adds support for evaluating `clojure` code blocks.

```
(require 'ob-clojure)
```

## 14.8 Header arguments

Code block functionality can be configured with header arguments. This section provides an overview of the use of header arguments, and then describes each header argument in detail.

### 14.8.1 Using header arguments

The values of header arguments can be set in several way. When the header arguments in each layer have been determined, they are combined in order from the first, least specific (having the lowest priority) up to the last, most specific (having the highest priority). A header argument with a higher priority replaces the same header argument specified at lower priority.

### System-wide header arguments

System-wide values of header arguments can be specified by adapting the `org-babel-default-header-args` variable:

```
:session    => "none"
:results    => "replace"
:exports    => "code"
:cache      => "no"
:noweb      => "no"
```

For example, the following example could be used to set the default value of `:noweb` header arguments to `yes`. This would have the effect of expanding `:noweb` references by default when evaluating source code blocks.

```
(setq org-babel-default-header-args
  (cons '(:noweb . "yes")
    (assq-delete-all :noweb org-babel-default-header-args)))
```

## Language-specific header arguments

Each language can define its own set of default header arguments in variable `org-babel-default-header-args:<lang>`, where `<lang>` is the name of the language. See the language-specific documentation available online at <http://orgmode.org/worg/org-contrib/babel>.

## Header arguments in Org mode properties

Buffer-wide header arguments may be specified as properties through the use of `#+PROPERTY:` lines placed anywhere in an Org mode file (see [Section 7.1 \[Property syntax\]](#), [page 64](#)).

For example the following would set `session` to `*R*` (only for R code blocks), and `results` to `silent` for every code block in the buffer, ensuring that all execution took place in the same session, and no results would be inserted into the buffer.

```
#+PROPERTY: header-args:R :session *R*
#+PROPERTY: header-args :results silent
```

Header arguments read from Org mode properties can also be set on a per-subtree basis using property drawers (see [Section 7.1 \[Property syntax\]](#), [page 64](#)). When properties are used to set default header arguments, they are always looked up with inheritance, regardless of the value of `org-use-property-inheritance`. Properties are evaluated as seen by the outermost call or source block.

In the following example the value of the `:cache` header argument will default to `yes` in all code blocks in the subtree rooted at the following heading:

```
* outline header
:PROPERTIES:
:header-args: :cache yes
:END:
```

Properties defined in this way override the properties set in `org-babel-default-header-args` and are applied for all activated languages. It is convenient to use the `org-set-property` function bound to `C-c C-x p` to set properties in Org mode documents.

## Language-specific header arguments in Org mode properties

Language-specific header arguments are also read from properties `header-args:<lang>` where `<lang>` is the name of the language targeted. As an example

```
* Heading
:PROPERTIES:
:header-args:clojure: :session *clojure-1*
:header-args:R: :session *R*
:END:
** Subheading
:PROPERTIES:
:header-args:clojure: :session *clojure-2*
```

```
:END:
```

would independently set a default session header argument for R and clojure for calls and source blocks under subtree “Heading” and change to a different clojure setting for evaluations under subtree “Subheading”, while the R session is inherited from “Heading” and therefore unchanged.

## Code block specific header arguments

The most common way to assign values to header arguments is at the code block level. This can be done by listing a sequence of header arguments and their values as part of the `#+BEGIN_SRC` line. Properties set in this way override both the values of `org-babel-default-header-args` and header arguments specified as properties. In the following example, the `:results` header argument is set to `silent`, meaning the results of execution will not be inserted in the buffer, and the `:exports` header argument is set to `code`, meaning only the body of the code block will be preserved on export to HTML or  $\text{\LaTeX}$ .

```
#+NAME: factorial
#+BEGIN_SRC haskell :results silent :exports code :var n=0
fac 0 = 1
fac n = n * fac (n-1)
#+END_SRC
```

Similarly, it is possible to set header arguments for inline code blocks

```
src_haskell[:exports both]{fac 5}
```

Code block header arguments can span multiple lines using `#+HEADER:` or `#+HEADERS:` lines preceding a code block or nested between the `#+NAME:` line and the `#+BEGIN_SRC` line of a named code block.

Multi-line header arguments on an un-named code block:

```
#+HEADERS: :var data1=1
#+BEGIN_SRC emacs-lisp :var data2=2
  (message "data1:%S, data2:%S" data1 data2)
#+END_SRC

#+RESULTS:
: data1:1, data2:2
```

Multi-line header arguments on a named code block:

```
#+NAME: named-block
#+HEADER: :var data=2
#+BEGIN_SRC emacs-lisp
  (message "data:%S" data)
#+END_SRC

#+RESULTS: named-block
: data:2
```

## Header arguments in function calls

At the most specific level, header arguments for “Library of Babel” or `#+CALL:` lines can be set as shown in the two examples below. For more information on the structure of `#+CALL:` lines see [Section 14.5 \[Evaluating code blocks\]](#), page 198.

The following will apply the `:exports results` header argument to the evaluation of the `#+CALL:` line.

```
#+CALL: factorial(n=5) :exports results
```

The following will apply the `:session special` header argument to the evaluation of the `factorial` code block.

```
#+CALL: factorial[:session special](n=5)
```

### 14.8.2 Specific header arguments

Header arguments consist of an initial colon followed by the name of the argument in lowercase letters. The following header arguments are defined:

Additional header arguments are defined on a language-specific basis, see [Section 14.7 \[Languages\]](#), page 199.

#### 14.8.2.1 :var

The `:var` header argument is used to pass arguments to code blocks. The specifics of how arguments are included in a code block vary by language; these are addressed in the language-specific documentation. However, the syntax used to specify arguments is the same across all languages. In every case, variables require a default value when they are declared.

The values passed to arguments can either be literal values, references, or Emacs Lisp code (see [Section 14.8.2.1 \[var\]](#), page 203). References include anything in the Org mode file that takes a `#+NAME:` or `#+RESULTS:` line: tables, lists, `#+BEGIN_EXAMPLE` blocks, other code blocks and the results of other code blocks.

Note: When a reference is made to another code block, the referenced block will be evaluated unless it has current cached results (see [Section 14.8.2.18 \[cache\]](#), page 214).

Argument values can be indexed in a manner similar to arrays (see [Section 14.8.2.1 \[var\]](#), page 203).

The following syntax is used to pass arguments to code blocks using the `:var` header argument.

```
:var name=assign
```

The argument, `assign`, can either be a literal value, such as a string `"string"` or a number `'9'`, or a reference to a table, a list, a literal example, another code block (with or without arguments), or the results of evaluating another code block.

Here are examples of passing values by reference:

*table*      an Org mode table named with either a `#+NAME:` line

```
#+NAME: example-table
| 1 |
| 2 |
| 3 |
```

```
| 4 |
```

```
#+NAME: table-length
#+BEGIN_SRC emacs-lisp :var table=example-table
(length table)
#+END_SRC
```

```
#+RESULTS: table-length
: 4
```

*list* a simple list named with a `#+NAME:` line (note that nesting is not carried through to the source code block)

```
#+NAME: example-list
- simple
- not
- nested
- list

#+BEGIN_SRC emacs-lisp :var x=example-list
(print x)
#+END_SRC

#+RESULTS:
| simple | list |
```

*code block without arguments*

a code block name (from the example above), as assigned by `#+NAME:`, optionally followed by parentheses

```
#+BEGIN_SRC emacs-lisp :var length=table-length()
(* 2 length)
#+END_SRC

#+RESULTS:
: 8
```

*code block with arguments*

a code block name, as assigned by `#+NAME:`, followed by parentheses and optional arguments passed within the parentheses following the code block name using standard function call syntax

```
#+NAME: double
#+BEGIN_SRC emacs-lisp :var input=8
(* 2 input)
#+END_SRC

#+RESULTS: double
: 16

#+NAME: squared
```

```

#+BEGIN_SRC emacs-lisp :var input=double(input=1)
(* input input)
#+END_SRC

#+RESULTS: squared
: 4

```

### *literal example*

a literal example block named with a `#+NAME:` line

```

#+NAME: literal-example
#+BEGIN_EXAMPLE
A literal example
on two lines
#+END_EXAMPLE

#+NAME: read-literal-example
#+BEGIN_SRC emacs-lisp :var x=literal-example
  (concatenate 'string x " for you.")
#+END_SRC

#+RESULTS: read-literal-example
: A literal example
: on two lines for you.

```

## Indexable variable values

It is possible to reference portions of variable values by “indexing” into the variables. Indexes are 0 based with negative values counting back from the end. If an index is separated by `,s` then each subsequent section will index into the next deepest nesting or dimension of the value. Note that this indexing occurs *before* other table related header arguments like `:hlines`, `:colnames` and `:rownames` are applied. The following example assigns the last cell of the first row the table `example-table` to the variable `data`:

```

#+NAME: example-table
| 1 | a |
| 2 | b |
| 3 | c |
| 4 | d |

#+BEGIN_SRC emacs-lisp :var data=example-table[0,-1]
data
#+END_SRC

#+RESULTS:
: a

```

Ranges of variable values can be referenced using two integers separated by a `:`, in which case the entire inclusive range is referenced. For example the following assigns the middle three rows of `example-table` to `data`.



```

#+NAME: example-table
| 1 | a |
| 2 | b |
| 3 | c |
| 4 | d |
| 5 | 3 |

#+BEGIN_SRC emacs-lisp :var data=example-table[1:3]
  data
#+END_SRC

#+RESULTS:
| 2 | b |
| 3 | c |
| 4 | d |

```

Additionally, an empty index, or the single character `*`, are both interpreted to mean the entire range and as such are equivalent to `0:-1`, as shown in the following example in which the entire first column is referenced.

```

#+NAME: example-table
| 1 | a |
| 2 | b |
| 3 | c |
| 4 | d |

#+BEGIN_SRC emacs-lisp :var data=example-table[,0]
  data
#+END_SRC

#+RESULTS:
| 1 | 2 | 3 | 4 |

```

It is possible to index into the results of code blocks as well as tables. Any number of dimensions can be indexed. Dimensions are separated from one another by commas, as shown in the following example.

```

#+NAME: 3D
#+BEGIN_SRC emacs-lisp
  '(((1 2 3) (4 5 6) (7 8 9))
    ((10 11 12) (13 14 15) (16 17 18))
    ((19 20 21) (22 23 24) (25 26 27)))
#+END_SRC

#+BEGIN_SRC emacs-lisp :var data=3D[1,,1]
  data
#+END_SRC

#+RESULTS:
| 11 | 14 | 17 |

```

## Emacs Lisp evaluation of variables

Emacs lisp code can be used to initialize variable values. When a variable value starts with `(`, `[`, `'` or ``` it will be evaluated as Emacs Lisp and the result of the evaluation will be assigned as the variable value. The following example demonstrates use of this evaluation to reliably pass the file-name of the Org mode buffer to a code block—note that evaluation of header arguments is guaranteed to take place in the original Org mode file, while there is no such guarantee for evaluation of the code block body.

```
#+BEGIN_SRC sh :var filename=(buffer-file-name) :exports both
  wc -w $filename
#+END_SRC
```

Note that values read from tables and lists will not be evaluated as Emacs Lisp, as shown in the following example.

```
#+NAME: table
| (a b c) |

#+HEADERS: :var data=table[0,0]
#+BEGIN_SRC perl
  $data
#+END_SRC

#+RESULTS:
: (a b c)
```

### 14.8.2.2 :results

There are four classes of `:results` header argument. Only one option per class may be supplied per code block.

- **collection** header arguments specify how the results should be collected from the code block
- **type** header arguments specify what type of result the code block will return—which has implications for how they will be processed before insertion into the Org mode buffer
- **format** header arguments specify what type of result the code block will return—which has implications for how they will be inserted into the Org mode buffer
- **handling** header arguments specify how the results of evaluating the code block should be handled.

## Collection

The following options are mutually exclusive, and specify how the results should be collected from the code block.

- **value** This is the default. The result is the value of the last statement in the code block. This header argument places the evaluation in functional mode. Note that in some languages, e.g., Python, use of this result type requires that a `return` statement be included in the body of the source code block. E.g., `:results value`.

- **output** The result is the collection of everything printed to STDOUT during the execution of the code block. This header argument places the evaluation in scripting mode. E.g., `:results output`.

## Type

The following options are mutually exclusive and specify what type of results the code block will return. By default, results are inserted as either a table or scalar depending on their value.

- **table, vector** The results should be interpreted as an Org mode table. If a single value is returned, it will be converted into a table with one row and one column. E.g., `:results value table`.
- **list** The results should be interpreted as an Org mode list. If a single scalar value is returned it will be converted into a list with only one element.
- **scalar, verbatim** The results should be interpreted literally—they will not be converted into a table. The results will be inserted into the Org mode buffer as quoted text. E.g., `:results value verbatim`.
- **file** The results will be interpreted as the path to a file, and will be inserted into the Org mode buffer as a file link. E.g., `:results value file`.

## Format

The following options are mutually exclusive and specify what type of results the code block will return. By default, results are inserted according to the type as specified above.

- **raw** The results are interpreted as raw Org mode code and are inserted directly into the buffer. If the results look like a table they will be aligned as such by Org mode. E.g., `:results value raw`.
- **org** The results are will be enclosed in a `BEGIN_SRC org` block. They are not comma-escaped by default but they will be if you hit `TAB` in the block and/or if you export the file. E.g., `:results value org`.
- **html** Results are assumed to be HTML and will be enclosed in a `BEGIN_EXPORT html` block. E.g., `:results value html`.
- **latex** Results assumed to be  $\text{\LaTeX}$  and are enclosed in a `BEGIN_EXPORT latex` block. E.g., `:results value latex`.
- **code** Result are assumed to be parsable code and are enclosed in a code block. E.g., `:results value code`.
- **pp** The result is converted to pretty-printed code and is enclosed in a code block. This option currently supports Emacs Lisp, Python, and Ruby. E.g., `:results value pp`.
- **drawer** The result is wrapped in a RESULTS drawer. This can be useful for inserting `raw` or `org` syntax results in such a way that their extent is known and they can be automatically removed or replaced.

## Handling

The following results options indicate what happens with the results once they are collected.

- **silent** The results will be echoed in the minibuffer but will not be inserted into the Org mode buffer. E.g., `:results output silent`.

- **replace** The default value. Any existing results will be removed, and the new results will be inserted into the Org mode buffer in their place. E.g., `:results output replace`.
- **append** If there are pre-existing results of the code block then the new results will be appended to the existing results. Otherwise the new results will be inserted as with **replace**.
- **prepend** If there are pre-existing results of the code block then the new results will be prepended to the existing results. Otherwise the new results will be inserted as with **replace**.

### 14.8.2.3 :file

The header argument `:file` is used to specify an external file in which to save code block results. After code block evaluation an Org mode style `[[file:]]` link (see [Section 4.1 \[Link format\]](#), page 38) to the file will be inserted into the Org mode buffer. Some languages including R, gnuplot, dot, and ditaa provide special handling of the `:file` header argument automatically wrapping the code block body in the boilerplate code required to save output to the specified file. This is often useful for saving graphical output of a code block to the specified file.

The argument to `:file` should be either a string specifying the path to a file, or a list of two strings in which case the first element of the list should be the path to a file and the second a description for the link.

### 14.8.2.4 :file-desc

The value of the `:file-desc` header argument is used to provide a description for file code block results which are inserted as Org mode links (see [Section 4.1 \[Link format\]](#), page 38). If the `:file-desc` header argument is given with no value the link path will be placed in both the “link” and the “description” portion of the Org mode link.

### 14.8.2.5 :file-ext

The value of the `:file-ext` header argument is used to provide an extension to write the file output to. It is combined with the `#+NAME:` of the source block and the value of the [Section 14.8.2.6 \[output-dir\]](#), page 209 header argument to generate a complete file name.

This header arg will be overridden by `:file`, and thus has no effect when the latter is specified.

### 14.8.2.6 :output-dir

The value of the `:output-dir` header argument is used to provide a directory to write the file output to. It may specify an absolute directory (beginning with `/`) or a relative directory (without `/`). It can be combined with the `#+NAME:` of the source block and the value of the [Section 14.8.2.5 \[file-ext\]](#), page 209 header argument to generate a complete file name, or used along with a [Section 14.8.2.3 \[file\]](#), page 209 header arg.

### 14.8.2.7 :dir and remote execution

While the `:file` header argument can be used to specify the path to the output file, `:dir` specifies the default directory during code block execution. If it is absent, then the

directory associated with the current buffer is used. In other words, supplying `:dir path` temporarily has the same effect as changing the current directory with *M-x cd path RET*, and then not supplying `:dir`. Under the surface, `:dir` simply sets the value of the Emacs variable `default-directory`.

When using `:dir`, you should supply a relative path for file output (e.g., `:file myfile.jpg` or `:file results/myfile.jpg`) in which case that path will be interpreted relative to the default directory.

In other words, if you want your plot to go into a folder called `Work` in your home directory, you could use

```
#+BEGIN_SRC R :file myplot.png :dir ~/Work
matplot(matrix(rnorm(100), 10), type="l")
#+END_SRC
```

## Remote execution

A directory on a remote machine can be specified using tramp file syntax, in which case the code will be evaluated on the remote machine. An example is

```
#+BEGIN_SRC R :file plot.png :dir /dand@yakuba.princeton.edu:
plot(1:10, main=system("hostname", intern=TRUE))
#+END_SRC
```

Text results will be returned to the local Org mode buffer as usual, and file output will be created on the remote machine with relative paths interpreted relative to the remote directory. An Org mode link to the remote file will be created.

So, in the above example a plot will be created on the remote machine, and a link of the following form will be inserted in the org buffer:

```
[[file:/scp:dand@yakuba.princeton.edu:/home/dand/plot.png][plot.png]]
```

Most of this functionality follows immediately from the fact that `:dir` sets the value of the Emacs variable `default-directory`, thanks to Tramp.

## Further points

- If `:dir` is used in conjunction with `:session`, although it will determine the starting directory for a new session as expected, no attempt is currently made to alter the directory associated with an existing session.
- `:dir` should typically not be used to create files during export with `:exports results` or `:exports both`. The reason is that, in order to retain portability of exported material between machines, during export links inserted into the buffer will *not* be expanded against `default-directory`. Therefore, if `default-directory` is altered using `:dir`, it is probable that the file will be created in a location to which the link does not point.

### 14.8.2.8 :exports

The `:exports` header argument specifies what should be included in HTML or  $\text{\LaTeX}$  exports of the Org mode file. Note that the `:exports` option is only relevant for code blocks, not inline code.

- `code` The default. The body of code is included into the exported file. E.g., `:exports code`.

- **results** The result of evaluating the code is included in the exported file. E.g., `:exports results`.
- **both** Both the code and results are included in the exported file. E.g., `:exports both`.
- **none** Nothing is included in the exported file. E.g., `:exports none`.

### 14.8.2.9 :tangle

The `:tangle` header argument specifies whether or not the code block should be included in tangled extraction of source code files.

- **tangle** The code block is exported to a source code file named after the full path (including the directory) and file name (w/o extension) of the Org mode file. E.g., `:tangle yes`.
- **no** The default. The code block is not exported to a source code file. E.g., `:tangle no`.
- **other** Any other string passed to the `:tangle` header argument is interpreted as a path (directory and file name relative to the directory of the Org mode file) to which the block will be exported. E.g., `:tangle path`.

### 14.8.2.10 :mkdirp

The `:mkdirp` header argument can be used to create parent directories of tangled files when missing. This can be set to **yes** to enable directory creation or to **no** to inhibit directory creation.

### 14.8.2.11 :comments

By default code blocks are tangled to source-code files without any insertion of comments beyond those which may already exist in the body of the code block. The `:comments` header argument can be set as follows to control the insertion of extra comments into the tangled code file.

- **no** The default. No extra comments are inserted during tangling.
- **link** The code block is wrapped in comments which contain pointers back to the original Org file from which the code was tangled.
- **yes** A synonym for “link” to maintain backwards compatibility.
- **org** Include text from the Org mode file as a comment. The text is picked from the leading context of the tangled code and is limited by the nearest headline or source block as the case may be.
- **both** Turns on both the “link” and “org” comment options.
- **noweb** Turns on the “link” comment option, and additionally wraps expanded noweb references in the code block body in link comments.

### 14.8.2.12 :padline

Control in insertion of padding lines around code block bodies in tangled code files. The default value is **yes** which results in insertion of newlines before and after each tangled code block. The following arguments are accepted.

- **yes** Insert newlines before and after each code block body in tangled code files.
- **no** Do not insert any newline padding in tangled output.

### 14.8.2.13 `:no-expand`

By default, code blocks are expanded with `org-babel-expand-src-block` during tangling. This has the effect of assigning values to variables specified with `:var` (see [Section 14.8.2.1 \[var\]](#), page 203), and of replacing “noweb” references (see [Section 14.10 \[Noweb reference syntax\]](#), page 221) with their targets. The `:no-expand` header argument can be used to turn off this behavior. Note: The `:no-expand` header argument has no impact on export, i.e. code blocks will irrespective of this header argument expanded for execution.

### 14.8.2.14 `:session`

The `:session` header argument starts a (possibly named) session for an interpreted language where the interpreter’s state is preserved. All code blocks sharing the same name are executed by the same interpreter process. By default, a session is not started.

- **none** The default. Each block is evaluated in its own interpreter process, which is terminated after the evaluation.
- **other** Any other string passed to the `:session` header argument will give the session a name. For example, `:session mysession`. If `:session` is given but no name string is specified, the session is named according to the language used in the block. All blocks with the same session name share the same session. Using different session names enables concurrent sessions (even for the same interpreted language, if the language supports multiple sessions).

### 14.8.2.15 `:noweb`

The `:noweb` header argument controls expansion of “noweb” syntax references (see [Section 14.10 \[Noweb reference syntax\]](#), page 221) when the code block is evaluated, tangled, or exported. The `:noweb` header argument can have one of the five values: `no`, `yes`, `tangle`, or `no-export strip-export`.

- **no** The default. “Noweb” syntax references in the body of the code block will not be expanded before the code block is evaluated, tangled or exported.
- **yes** “Noweb” syntax references in the body of the code block will be expanded before the code block is evaluated, tangled or exported.
- **tangle** “Noweb” syntax references in the body of the code block will be expanded before the code block is tangled. However, “noweb” syntax references will not be expanded when the code block is evaluated or exported.
- **no-export** “Noweb” syntax references in the body of the code block will be expanded before the block is evaluated or tangled. However, “noweb” syntax references will not be expanded when the code block is exported.
- **strip-export** “Noweb” syntax references in the body of the code block will be expanded before the block is evaluated or tangled. However, “noweb” syntax references will be removed when the code block is exported.
- **eval** “Noweb” syntax references in the body of the code block will only be expanded before the block is evaluated.

## Noweb prefix lines

Noweb insertions are now placed behind the line prefix of the `<<reference>>`. This behavior is illustrated in the following example. Because the `<<example>>` noweb reference

appears behind the SQL comment syntax, each line of the expanded noweb reference will be commented.

This code block:

```
-- <<example>>
```

expands to:

```
-- this is the
-- multi-line body of example
```

Note that noweb replacement text that does not contain any newlines will not be affected by this change, so it is still possible to use inline noweb references.

#### 14.8.2.16 :noweb-ref

When expanding “noweb” style references, the bodies of all code block with *either* a block name matching the reference name *or* a `:noweb-ref` header argument matching the reference name will be concatenated together to form the replacement text.

By setting this header argument at the subtree or file level, simple code block concatenation may be achieved. For example, when tangling the following Org mode file, the bodies of code blocks will be concatenated into the resulting pure code file<sup>5</sup>.

```
#+BEGIN_SRC sh :tangle yes :noweb yes :shebang #!/bin/sh
  <<fullest-disk>>
#+END_SRC
* the mount point of the fullest disk
  :PROPERTIES:
  :noweb-ref: fullest-disk
  :END:

** query all mounted disks
#+BEGIN_SRC sh
  df \
#+END_SRC

** strip the header row
#+BEGIN_SRC sh
  |sed '1d' \
#+END_SRC

** sort by the percent full
#+BEGIN_SRC sh
  |awk '{print $5 " " " $6}'|sort -n |tail -1 \
#+END_SRC

** extract the mount point
#+BEGIN_SRC sh
  |awk '{print $2}'
```

---

<sup>5</sup> (The example needs property inheritance to be turned on for the `noweb-ref` property, see [Section 7.4 \[Property inheritance\]](#), page 67).



```
#+END_SRC
```

The `:noweb-sep` (see [Section 14.8.2.17 \[noweb-sep\]](#), page 214) header argument holds the string used to separate accumulate noweb references like those above. By default a newline is used.

### 14.8.2.17 `:noweb-sep`

The `:noweb-sep` header argument holds the string used to separate accumulate noweb references (see [Section 14.8.2.16 \[noweb-ref\]](#), page 213). By default a newline is used.

### 14.8.2.18 `:cache`

The `:cache` header argument controls the use of in-buffer caching of the results of evaluating code blocks. It can be used to avoid re-evaluating unchanged code blocks. When the cache is active, a source block is not re-evaluated if a result for it is present in the buffer and neither the header arguments (including the value of `:var` references) nor the text of the block itself has changed since the result was computed. The feature helps avoid re-running long calculations. However, there are edge cases and you should not rely on the cache to behave reliably in all circumstances.

The caching feature works best when a babel block is a pure function of its arguments (see [Section 14.8.2.1 \[var\]](#), page 203). That is, the function always returns the same results when given the same arguments, and does not touch external resources (like the filesystem or the language’s RNG) in any way.<sup>6</sup>

Note that the `:cache` header argument will attempt to cache results when the `:session` header argument is used, even though the results of the code block execution stored in the session may lead to unexpected results.

Noweb references (see [Section 14.10 \[Noweb reference syntax\]](#), page 221) are currently not expanded when calculating whether the text of the code block has changed. Perhaps in principle they ought to be, but this could introduce unexpected complexity. See <http://thread.gmane.org/gmane.emacs.orgmode/79046>.

The `:cache` header argument can have one of two values: **yes** or **no**.

- **no** The default. No caching takes place, and the code block will be evaluated every time it is called.
- **yes** Every time the code block is run a SHA1 hash of the code and arguments passed to the block will be generated. This hash is packed into the `#+RESULTS:` line and will be checked on subsequent executions of the code block. If the code block has not changed since the last time it was evaluated, it will not be re-evaluated.

Code block caches notice if the value of a variable argument to the code block has changed. If this is the case, the cache is invalidated and the code block is re-run. In the following example, `caller` will not be re-run unless the results of `random` have changed since it was last run.

---

<sup>6</sup> The documentation of the knitr reproducible research package for the R language has some good discussion of issues that may arise when using the cache in such a context. See <http://yihui.name/knitr/demo/cache/>, especially the sections “Even more stuff for cache?” and “Reproducibility with RNG”. (Obviously, you will have to abstract away from the knitr implementation details which the documentation also discusses.)

```

#+NAME: random
#+BEGIN_SRC R :cache yes
runif(1)
#+END_SRC

#+RESULTS[a2a72cd647ad44515fab62e144796432793d68e1]: random
0.4659510825295

#+NAME: caller
#+BEGIN_SRC emacs-lisp :var x=random :cache yes
x
#+END_SRC

#+RESULTS[bec9c8724e397d5df3b696502df3ed7892fc4f5f]: caller
0.254227238707244

```

#### 14.8.2.19 :sep

The `:sep` header argument can be used to control the delimiter used when writing tabular results out to files external to Org mode. This is used either when opening tabular results of a code block by calling the `org-open-at-point` function bound to `C-c C-o` on the code block, or when writing code block results to an external file (see [Section 14.8.2.3 \[file\]](#), [page 209](#)) header argument.

By default, when `:sep` is not specified output tables are tab delimited.

#### 14.8.2.20 :hlines

Tables are frequently represented with one or more horizontal lines, or hlines. The `:hlines` argument to a code block accepts the values `yes` or `no`, with a default value of `no`.

- **no** Strips horizontal lines from the input table. In most languages this is the desired effect because an `hline` symbol is interpreted as an unbound variable and raises an error. Setting `:hlines no` or relying on the default value yields the following results.

```

#+NAME: many-cols
| a | b | c |
|---+---+---|
| d | e | f |
|---+---+---|
| g | h | i |

#+NAME: echo-table
#+BEGIN_SRC python :var tab=many-cols
return tab
#+END_SRC

#+RESULTS: echo-table
| a | b | c |
| d | e | f |
| g | h | i |

```

- **yes** Leaves hlines in the table. Setting `:hlines yes` has this effect.

```

#+NAME: many-cols
| a | b | c |
|---+---+---|
| d | e | f |
|---+---+---|
| g | h | i |

#+NAME: echo-table
#+BEGIN_SRC python :var tab=many-cols :hlines yes
    return tab
#+END_SRC

#+RESULTS: echo-table
| a | b | c |
|---+---+---|
| d | e | f |
|---+---+---|
| g | h | i |

```

#### 14.8.2.21 `:colnames`

The `:colnames` header argument accepts the values **yes**, **no**, or **nil** for unassigned. The default value is **nil**. Note that the behavior of the `:colnames` header argument may differ across languages.

- **nil** If an input table looks like it has column names (because its second row is an hline), then the column names will be removed from the table before processing, then reapplied to the results.

```

#+NAME: less-cols
| a |
|---|
| b |
| c |

#+NAME: echo-table-again
#+BEGIN_SRC python :var tab=less-cols
    return [[val + '*' for val in row] for row in tab]
#+END_SRC

#+RESULTS: echo-table-again
| a |
|---|
| b* |
| c* |

```

Please note that column names are not removed before the table is indexed using variable indexing See [Section 14.8.2.1 \[var\], page 203](#).

- **no** No column name pre-processing takes place

- **yes** Column names are removed and reapplied as with **nil** even if the table does not “look like” it has column names (i.e., the second row is not an hline)

#### 14.8.2.22 :rownames

The **:rownames** header argument can take on the values **yes** or **no**, with a default value of **no**. Note that Emacs Lisp code blocks ignore the **:rownames** header argument entirely given the ease with which tables with row names may be handled directly in Emacs Lisp.

- **no** No row name pre-processing will take place.
- **yes** The first column of the table is removed from the table before processing, and is then reapplied to the results.

```
#+NAME: with-rownames
| one | 1 | 2 | 3 | 4 | 5 |
| two | 6 | 7 | 8 | 9 | 10 |

#+NAME: echo-table-once-again
#+BEGIN_SRC python :var tab=with-rownames :rownames yes
    return [[val + 10 for val in row] for row in tab]
#+END_SRC

#+RESULTS: echo-table-once-again
| one | 11 | 12 | 13 | 14 | 15 |
| two | 16 | 17 | 18 | 19 | 20 |
```

Please note that row names are not removed before the table is indexed using variable indexing See [Section 14.8.2.1 \[var\]](#), page 203.

#### 14.8.2.23 :shebang

Setting the **:shebang** header argument to a string value (e.g., **:shebang "#!/bin/bash"**) causes the string to be inserted as the first line of any tangled file holding the code block, and the file permissions of the tangled file are set to make it executable.

#### 14.8.2.24 :tangle-mode

The **tangle-mode** header argument controls the permission set on tangled files. The value of this header argument will be passed to **set-file-modes**. For example, to set a tangled file as read only use **:tangle-mode (identity #o444)**, or to set a tangled file as executable use **:tangle-mode (identity #o755)**. Blocks with **shebang** ([Section 14.8.2.23 \[shebang\]](#), page 217) header arguments will automatically be made executable unless the **tangle-mode** header argument is also used. The behavior is undefined if multiple code blocks with different values for the **tangle-mode** header argument are tangled to the same file.

#### 14.8.2.25 :eval

The **:eval** header argument can be used to limit the evaluation of specific code blocks. The **:eval** header argument can be useful for protecting against the evaluation of dangerous code blocks or to ensure that evaluation will require a query regardless of the value of the **org-confirm-babel-evaluate** variable. The possible values of **:eval** and their effects are shown below.

**never or no**

The code block will not be evaluated under any circumstances.

**query**

Evaluation of the code block will require a query.

**never-export or no-export**

The code block will not be evaluated during export but may still be called interactively.

**query-export**

Evaluation of the code block during export will require a query.

If this header argument is not set then evaluation is determined by the value of the `org-confirm-babel-evaluate` variable see [Section 15.4 \[Code evaluation security\]](#), page 225.

### 14.8.2.26 :wrap

The `:wrap` header argument is used to mark the results of source block evaluation. The header argument can be passed a string that will be appended to `#+BEGIN_` and `#+END_`, which will then be used to wrap the results. If not string is specified then the results will be wrapped in a `#+BEGIN/END_RESULTS` block.

### 14.8.2.27 :post

The `:post` header argument is used to post-process the results of a code block execution. When a post argument is given, the results of the code block will temporarily be bound to the `*this*` variable. This variable may then be included in header argument forms such as those used in [Section 14.8.2.1 \[var\]](#), page 203 header argument specifications allowing passing of results to other code blocks, or direct execution via Emacs Lisp. Additional header arguments may be passed to the `:post`-function.

The following two examples illustrate the usage of the `:post` header argument. The first example shows how to attach a attribute-line via `:post`.

```
#+name: attr_wrap
#+begin_src sh :var data="" :var width="\textwidth" :results output
  echo "##ATTR_LATEX: :width $width"
  echo "$data"
#+end_src

#+header: :file /tmp/it.png
#+begin_src dot :post attr_wrap(width="5cm", data=*this*) :results drawer
  digraph{
    a -> b;
    b -> c;
    c -> a;
  }
#+end_src

#+RESULTS:
:RESULTS:
```

```
#+ATTR_LATEX :width 5cm
[[file:/tmp/it.png]]
:END:
```

The second examples shows how to use `:post` together with the `:colnames` header argument.

```
#+name: round-tbl
#+begin_src emacs-lisp :var tbl="" fmt="%.3f"
  (mapcar (lambda (row)
            (mapcar (lambda (cell)
                      (if (numberp cell)
                          (format fmt cell)
                          cell))
                    row))
          tbl)
#+end_src

#+begin_src R :colnames yes :post round-tbl[:colnames yes](*this*)
set.seed(42)
data.frame(foo=rnorm(1))
#+end_src

#+RESULTS:
|   foo |
|-----|
| 1.371 |
```

#### 14.8.2.28 `:prologue`

The value of the `prologue` header argument will be prepended to the code block body before execution. For example, `:prologue "reset"` may be used to reset a gnuplot session before execution of a particular code block, or the following configuration may be used to do this for all gnuplot code blocks. Also see [Section 14.8.2.29 \[epilogue\]](#), page 219.

```
(add-to-list 'org-babel-default-header-args:gnuplot
  '(:prologue . "reset"))
```

#### 14.8.2.29 `:epilogue`

The value of the `epilogue` header argument will be appended to the code block body before execution. Also see [Section 14.8.2.28 \[prologue\]](#), page 219.

### 14.9 Results of evaluation

The way in which results are handled depends on whether a session is invoked, as well as on whether `:results value` or `:results output` is used. The following table shows the table possibilities. For a full listing of the possible results header arguments see [Section 14.8.2.2 \[results\]](#), page 207.

	Non-session	Session
<code>:results value</code>	value of last expression	value of last expression

**:results output**                      contents of STDOUT                      concatenation of interpreter output

Note: With **:results value**, the result in both **:session** and non-session is returned to Org mode as a table (a one- or two-dimensional vector of strings or numbers) when appropriate.

## 14.9.1 Non-session

### 14.9.1.1 :results value

This is the default. Internally, the value is obtained by wrapping the code in a function definition in the external language, and evaluating that function. Therefore, code should be written as if it were the body of such a function. In particular, note that Python does not automatically return a value from a function unless a **return** statement is present, and so a ‘**return**’ statement will usually be required in Python.

This is the only one of the four evaluation contexts in which the code is automatically wrapped in a function definition.

### 14.9.1.2 :results output

The code is passed to the interpreter as an external process, and the contents of the standard output stream are returned as text. (In certain languages this also contains the error output stream; this is an area for future work.)

## 14.9.2 Session

### 14.9.2.1 :results value

The code is passed to an interpreter running as an interactive Emacs inferior process. Only languages which provide tools for interactive evaluation of code have session support, so some language (e.g., C and ditaa) do not support the **:session** header argument, and in other languages (e.g., Python and Haskell) which have limitations on the code which may be entered into interactive sessions, those limitations apply to the code in code blocks using the **:session** header argument as well.

Unless the **:results output** option is supplied (see below) the result returned is the result of the last evaluation performed by the interpreter. (This is obtained in a language-specific manner: the value of the variable `_` in Python and Ruby, and the value of `.Last.value` in R).

### 14.9.2.2 :results output

The code is passed to the interpreter running as an interactive Emacs inferior process. The result returned is the concatenation of the sequence of (text) output from the interactive interpreter. Notice that this is not necessarily the same as what would be sent to **STDOUT** if the same code were passed to a non-interactive interpreter running as an external process. For example, compare the following two blocks:

```
#+BEGIN_SRC python :results output
print "hello"
2
print "bye"
#+END_SRC
```

```
#+RESULTS:
: hello
: bye
```

In non-session mode, the “2” is not printed and does not appear.

```
#+BEGIN_SRC python :results output :session
print "hello"
2
print "bye"
#+END_SRC
```

```
#+RESULTS:
: hello
: 2
: bye
```

But in `:session` mode, the interactive interpreter receives input “2” and prints out its value, “2”. (Indeed, the other print statements are unnecessary here).

## 14.10 Noweb reference syntax

The “noweb” (see <http://www.cs.tufts.edu/~nr/noweb/>) Literate Programming system allows named blocks of code to be referenced by using the familiar Noweb syntax:

```
<<code-block-name>>
```

When a code block is tangled or evaluated, whether or not “noweb” references are expanded depends upon the value of the `:noweb` header argument. If `:noweb yes`, then a Noweb reference is expanded before evaluation. If `:noweb no`, the default, then the reference is not expanded before evaluation. See the [Section 14.8.2.16 \[noweb-ref\], page 213](#) header argument for a more flexible way to resolve noweb references.

It is possible to include the *results* of a code block rather than the body. This is done by appending parenthesis to the code block name which may optionally contain arguments to the code block as shown below.

```
<<code-block-name(optional arguments)>>
```

Note: the default value, `:noweb no`, was chosen to ensure that correct code is not broken in a language, such as Ruby, where `<<arg>>` is a syntactically valid construct. If `<<arg>>` is not syntactically valid in languages that you use, then please consider setting the default value.

Note: if noweb tangling is slow in large Org mode files consider setting the `org-babel-use-quick-and-dirty-noweb-expansion` variable to `t`. This will result in faster noweb reference resolution at the expense of not correctly resolving inherited values of the `:noweb-ref` header argument.

## 14.11 Key bindings and useful functions

Many common Org mode key sequences are re-bound depending on the context.

Within a code block, the following key bindings are active:



<i>C-c C-c</i>		org-babel-execute-src-block
<i>C-c C-o</i>		org-babel-open-src-block-result
<i>M-up</i>		org-babel-load-in-session
<i>M-down</i>		org-babel-switch-to-session

In an Org mode buffer, the following key bindings are active:

<i>C-c C-v p</i>	or	<i>C-c C-v C-p</i>	org-babel-previous-src-block
<i>C-c C-v n</i>	or	<i>C-c C-v C-n</i>	org-babel-next-src-block
<i>C-c C-v e</i>	or	<i>C-c C-v C-e</i>	org-babel-execute-maybe
<i>C-c C-v o</i>	or	<i>C-c C-v C-o</i>	org-babel-open-src-block-result
<i>C-c C-v v</i>	or	<i>C-c C-v C-v</i>	org-babel-expand-src-block
<i>C-c C-v u</i>	or	<i>C-c C-v C-u</i>	org-babel-goto-src-block-head
<i>C-c C-v g</i>	or	<i>C-c C-v C-g</i>	org-babel-goto-named-src-block
<i>C-c C-v r</i>	or	<i>C-c C-v C-r</i>	org-babel-goto-named-result
<i>C-c C-v b</i>	or	<i>C-c C-v C-b</i>	org-babel-execute-buffer
<i>C-c C-v s</i>	or	<i>C-c C-v C-s</i>	org-babel-execute-subtree
<i>C-c C-v d</i>	or	<i>C-c C-v C-d</i>	org-babel-demarcate-block
<i>C-c C-v t</i>	or	<i>C-c C-v C-t</i>	org-babel-tangle
<i>C-c C-v f</i>	or	<i>C-c C-v C-f</i>	org-babel-tangle-file
<i>C-c C-v c</i>	or	<i>C-c C-v C-c</i>	org-babel-check-src-block
<i>C-c C-v j</i>	or	<i>C-c C-v C-j</i>	org-babel-insert-header-arg
<i>C-c C-v l</i>	or	<i>C-c C-v C-l</i>	org-babel-load-in-session
<i>C-c C-v i</i>	or	<i>C-c C-v C-i</i>	org-babel-lob-ingest
<i>C-c C-v I</i>	or	<i>C-c C-v C-I</i>	org-babel-view-src-block-info
<i>C-c C-v z</i>	or	<i>C-c C-v C-z</i>	org-babel-switch-to-session-with-code
<i>C-c C-v a</i>	or	<i>C-c C-v C-a</i>	org-babel-sha1-hash
<i>C-c C-v h</i>	or	<i>C-c C-v C-h</i>	org-babel-describe-bindings
<i>C-c C-v x</i>	or	<i>C-c C-v C-x</i>	org-babel-do-key-sequence-in-edit- buffer

## 14.12 Batch execution

It is possible to call functions from the command line. This shell script calls `org-babel-tangle` on every one of its arguments.

Be sure to adjust the paths to fit your system.

```
#!/bin/sh
# -*- mode: shell-script -*-
#
# tangle files with org-mode
#
DIR=`pwd`
FILES=""

# wrap each argument in the code required to call tangle on it
for i in $@; do
```

```
FILES="$FILES \"$i\""  
done  
  
emacs -Q --batch \  
  --eval "(progn  
    (require 'org)(require 'ob)(require 'ob-tangle)  
    (mapc (lambda (file)  
      (find-file (expand-file-name file \"$DIR\"))  
      (org-babel-tangle)  
      (kill-buffer)) '($FILES)))" 2>&1 |grep -i tangled
```

## 15 Miscellaneous

### 15.1 Completion

Org supports in-buffer completion. This type of completion does not make use of the minibuffer. You simply type a few letters into the buffer and use the key to complete text right there.

*M-TAB* Complete word at point

- At the beginning of a headline, complete TODO keywords.
- After ‘\’, complete T<sub>E</sub>X symbols supported by the exporter.
- After ‘\*’, complete headlines in the current buffer so that they can be used in search links like ‘`[[*find this headline]]`’.
- After ‘.’ in a headline, complete tags. The list of tags is taken from the variable `org-tag-alist` (possibly set through the ‘`#+TAGS`’ in-buffer option, see [Section 6.2 \[Setting tags\]](#), page 59), or it is created dynamically from all tags used in the current buffer.
- After ‘:’ and not in a headline, complete property keys. The list of keys is constructed dynamically from all keys used in the current buffer.
- After ‘[’, complete link abbreviations (see [Section 4.6 \[Link abbreviations\]](#), page 44).
- After ‘#+’, complete the special keywords like ‘`TYP_TODO`’ or ‘`OPTIONS`’ which set file-specific options for Org mode. When the option keyword is already complete, pressing *M-TAB* again will insert example settings for this keyword.
- In the line after ‘`#+STARTUP:` ’, complete startup keywords, i.e., valid keys for this line.
- Elsewhere, complete dictionary words using Ispell.

### 15.2 Easy templates

Org mode supports insertion of empty structural elements (like `#+BEGIN_SRC` and `#+END_SRC` pairs) with just a few key strokes. This is achieved through a native template expansion mechanism. Note that Emacs has several other template mechanisms which could be used in a similar way, for example `yasnippet`.

To insert a structural element, type a ‘<’, followed by a template selector and `TAB`. Completion takes effect only when the above keystrokes are typed on a line by itself.

The following template selectors are currently supported.

<i>s</i>	<code>#+BEGIN_SRC ... #+END_SRC</code>
<i>e</i>	<code>#+BEGIN_EXAMPLE ... #+END_EXAMPLE</code>
<i>q</i>	<code>#+BEGIN_QUOTE ... #+END_QUOTE</code>
<i>v</i>	<code>#+BEGIN_VERSE ... #+END_VERSE</code>
<i>c</i>	<code>#+BEGIN_CENTER ... #+END_CENTER</code>
<i>l</i>	<code>#+BEGIN_EXPORT latex ... #+END_EXPORT</code>
<i>L</i>	<code>#+LATEX:</code>

```

h      +#+BEGIN_EXPORT html ... +#+END_EXPORT
H      +#+HTML:
a      +#+BEGIN_EXPORT ascii ... +#+END_EXPORT
A      +#+ASCII:
i      +#+INDEX: line
I      +#+INCLUDE: line

```

For example, on an empty line, typing "<e" and then pressing TAB, will expand into a complete EXAMPLE template.

You can install additional templates by customizing the variable `org-structure-template-alist`. See the docstring of the variable for additional details.

### 15.3 Speed keys

Single keys can be made to execute commands when the cursor is at the beginning of a headline, i.e., before the first star. Configure the variable `org-use-speed-commands` to activate this feature. There is a pre-defined list of commands, and you can add more such commands using the variable `org-speed-commands-user`. Speed keys not only speed up navigation and other commands, but they also provide an alternative way to execute commands bound to keys that are not or not easily available on a TTY, or on a small mobile device with a limited keyboard.

To see which commands are available, activate the feature and press ? with the cursor at the beginning of a headline.

### 15.4 Code evaluation and security issues

Org provides tools to work with code snippets, including evaluating them.

Running code on your machine always comes with a security risk. Badly written or malicious code can be executed on purpose or by accident. Org has default settings which will only evaluate such code if you give explicit permission to do so, and as a casual user of these features you should leave these precautions intact.

For people who regularly work with such code, the confirmation prompts can become annoying, and you might want to turn them off. This can be done, but you must be aware of the risks that are involved.

Code evaluation can happen under the following circumstances:

#### *Source code blocks*

Source code blocks can be evaluated during export, or when pressing `C-c C-c` in the block. The most important thing to realize here is that Org mode files which contain code snippets are, in a certain sense, like executable files. So you should accept them and load them into Emacs only from trusted sources—just like you would do with a program you install on your computer.

Make sure you know what you are doing before customizing the variables which take off the default security brakes.

`org-confirm-babel-evaluate` [User Option]

When `t` (the default), the user is asked before every code block evaluation.

When `nil`, the user is not asked. When set to a function, it is called with

two arguments (language and body of the code block) and should return `t` to ask and `nil` not to ask.

For example, here is how to execute "ditaa" code (which is considered safe) without asking:

```
(defun my-org-confirm-babel-evaluate (lang body)
  (not (string= lang "ditaa"))) ; don't ask for ditaa
(setq org-confirm-babel-evaluate 'my-org-confirm-babel-evaluate)
```

Following `shell` and `elisp` links

Org has two link types that can directly evaluate code (see [Section 4.3 \[External links\]](#), page 39). These links can be problematic because the code to be evaluated is not visible.

`org-confirm-shell-link-function` [User Option]  
Function to queries user about shell link execution.

`org-confirm-elisp-link-function` [User Option]  
Functions to query user for Emacs Lisp link execution.

Formulas in tables

Formulas in tables (see [Section 3.5 \[The spreadsheet\]](#), page 24) are code that is evaluated either by the *calc* interpreter, or by the *Emacs Lisp* interpreter.

## 15.5 Customization

There are more than 500 variables that can be used to customize Org. For the sake of compactness of the manual, I am not describing the variables here. A structured overview of customization variables is available with `M-x org-customize RET`. Or select **Browse Org Group** from the **Org->Customization** menu. Many settings can also be activated on a per-file basis, by putting special lines into the buffer (see [Section 15.6 \[In-buffer settings\]](#), page 226).

## 15.6 Summary of in-buffer settings

Org mode uses special lines in the buffer to define settings on a per-file basis. These lines start with a `#+` followed by a keyword, a colon, and then individual words defining a setting. Several setting words can be in the same line, but you can also have multiple lines for the keyword. While these settings are described throughout the manual, here is a summary. After changing any of these lines in the buffer, press `C-c C-c` with the cursor still in the line to activate the changes immediately. Otherwise they become effective only when the file is visited again in a new Emacs session.

**`#+ARCHIVE: %s_done:`**

This line sets the archive location for the agenda file. It applies for all subsequent lines until the next `#+ARCHIVE` line, or the end of the file. The first such line also applies to any entries before it. The corresponding variable is `org-archive-location`.

**`#+CATEGORY:`**

This line sets the category for the agenda file. The category applies to the whole document.

**#+COLUMNS:** *%25ITEM ...*

Set the default format for columns view. This format applies when columns view is invoked in locations where no **COLUMNS** property applies.

**#+CONSTANTS:** *name1=value1 ...*

Set file-local values for constants to be used in table formulas. This line sets the local variable **org-table-formula-constants-local**. The global version of this variable is **org-table-formula-constants**.

**#+FILETAGS:** *:tag1:tag2:tag3:*

Set tags that can be inherited by any entry in the file, including the top-level entries.

**#+LINK:** *linkword replace*

These lines (several are allowed) specify link abbreviations. See [Section 4.6 \[Link abbreviations\]](#), page 44. The corresponding variable is **org-link-abbrev-alist**.

**#+PRIORITIES:** *highest lowest default*

This line sets the limits and the default for the priorities. All three must be either letters A–Z or numbers 0–9. The highest priority must have a lower ASCII number than the lowest priority.

**#+PROPERTY:** *Property\_Name Value*

This line sets a default inheritance value for entries in the current buffer, most useful for specifying the allowed values of a property.

**#+SETUPFILE:** *file*

This line defines a file that holds more in-buffer setup. Normally this is entirely ignored. Only when the buffer is parsed for option-setting lines (i.e., when starting Org mode for a file, when pressing **C-c C-c** in a settings line, or when exporting), then the contents of this file are parsed as if they had been included in the buffer. In particular, the file can be any other Org mode file with internal setup. You can visit the file the cursor is in the line with **C-c '**.

**#+STARTUP:**

This line sets options to be used at startup of Org mode, when an Org file is being visited.

The first set of options deals with the initial visibility of the outline tree. The corresponding variable for global default settings is **org-startup-folded**, with a default value **t**, which means **overview**.

<b>overview</b>	top-level headlines only
<b>content</b>	all headlines
<b>showall</b>	no folding of any entries
<b>showeverything</b>	show even drawer contents

Dynamic virtual indentation is controlled by the variable **org-startup-indented**

<b>indent</b>	start with <b>org-indent-mode</b> turned on
<b>noindent</b>	start with <b>org-indent-mode</b> turned off

Then there are options for aligning tables upon visiting a file. This is useful in files containing narrowed table columns. The corresponding variable is `org-startup-align-all-tables`, with a default value `nil`.

<code>align</code>	align all tables
<code>noalign</code>	don't align tables on startup

When visiting a file, inline images can be automatically displayed. The corresponding variable is `org-startup-with-inline-images`, with a default value `nil` to avoid delays when visiting a file.

<code>inlineimages</code>	show inline images
<code>noinlineimages</code>	don't show inline images on startup

When visiting a file,  $\text{\LaTeX}$  fragments can be converted to images automatically. The variable `org-startup-with-latex-preview` which controls this behavior, is set to `nil` by default to avoid delays on startup.

<code>latexpreview</code>	preview $\text{\LaTeX}$ fragments
<code>nolatexpreview</code>	don't preview $\text{\LaTeX}$ fragments

Logging the closing and reopening of TODO items and clock intervals can be configured using these options (see variables `org-log-done`, `org-log-note-clock-out` and `org-log-repeat`)

<code>logdone</code>	record a timestamp when an item is marked DONE
<code>lognotedone</code>	record timestamp and a note when DONE
<code>nologdone</code>	don't record when items are marked DONE
<code>logrepeat</code>	record a time when reinstating a repeating item
<code>lognoterepeat</code>	record a note when reinstating a repeating item
<code>nologrepeat</code>	do not record when reinstating repeating item
<code>lognoteclock-out</code>	record a note when clocking out
<code>nolognoteclock-out</code>	don't record a note when clocking out
<code>logreschedule</code>	record a timestamp when scheduling time changes
<code>lognotereschedule</code>	record a note when scheduling time changes
<code>nologreschedule</code>	do not record when a scheduling date changes
<code>logredeadline</code>	record a timestamp when deadline changes
<code>lognoterededeadline</code>	record a note when deadline changes
<code>nologredeadline</code>	do not record when a deadline date changes
<code>logrefile</code>	record a timestamp when refiling
<code>lognoterefile</code>	record a note when refiling
<code>nologrefile</code>	do not record when refiling
<code>logdrawer</code>	store log into drawer
<code>nologdrawer</code>	store log outside of drawer
<code>logstatesreversed</code>	reverse the order of states notes
<code>nologstatesreversed</code>	do not reverse the order of states notes

Here are the options for hiding leading stars in outline headings, and for indenting outlines. The corresponding variables are `org-hide-leading-stars` and `org-odd-levels-only`, both with a default setting `nil` (meaning `showstars` and `oddeven`).

<code>hidestars</code>	make all but one of the stars starting a headline invisible.
<code>showstars</code>	show all stars starting a headline

<code>indent</code>	virtual indentation according to outline level
<code>noindent</code>	no virtual indentation according to outline level
<code>odd</code>	allow only odd outline levels (1,3,...)
<code>oddeven</code>	allow all outline levels

To turn on custom format overlays over timestamps (variables `org-put-time-stamp-overlays` and `org-time-stamp-overlay-formats`), use

`customtime` overlay custom time format

The following options influence the table spreadsheet (variable `constants-unit-system`).

<code>constcgs</code>	<code>constants.el</code> should use the c-g-s unit system
<code>constSI</code>	<code>constants.el</code> should use the SI unit system

To influence footnote settings, use the following keywords. The corresponding variables are `org-footnote-define-inline`, `org-footnote-auto-label`, and `org-footnote-auto-adjust`.

<code>fninline</code>	define footnotes inline
<code>fnnoinline</code>	define footnotes in separate section
<code>fnlocal</code>	define footnotes near first reference, but not inline
<code>fnprompt</code>	prompt for footnote labels
<code>fnauto</code>	create <code>[fn:1]</code> -like labels automatically (default)
<code>fnconfirm</code>	offer automatic label for editing or confirmation
<code>fnplain</code>	create <code>[1]</code> -like labels automatically
<code>fnadjust</code>	automatically renumber and sort footnotes
<code>nofnadjust</code>	do not renumber and sort automatically

To hide blocks on startup, use these keywords. The corresponding variable is `org-hide-block-startup`.

<code>hideblocks</code>	Hide all begin/end blocks on startup
<code>nohideblocks</code>	Do not hide blocks on startup

The display of entities as UTF-8 characters is governed by the variable `org-pretty-entities` and the keywords

<code>entitiespretty</code>	Show entities as UTF-8 characters where possible
<code>entitiesplain</code>	Leave entities plain

#### **`#+TAGS:` *TAG1(c1) TAG2(c2)***

These lines (several such lines are allowed) specify the valid tags in this file, and (potentially) the corresponding *fast tag selection* keys. The corresponding variable is `org-tag-alist`.

#### **`#+TBLFM:`** This line contains the formulas for the table directly above the line.

Table can have multiple lines containing '`#+TBLFM:`'. Note that only the first line of '`#+TBLFM:`' will be applied when you recalculate the table. For more details see [\[Using multiple `#+TBLFM` lines\]](#), page 33 in [Section 3.5.8 \[Editing and debugging formulas\]](#), page 31.



```
#+TITLE:, #+AUTHOR:, #+EMAIL:, #+LANGUAGE:, #+DATE:,
#+OPTIONS:, #+BIND:,
#+SELECT_TAGS:, #+EXCLUDE_TAGS:
```

These lines provide settings for exporting files. For more details see [Section 12.2 \[Export settings\]](#), page 136.

```
#+TODO: #+SEQ_TODO: #+TYP_TODO:
```

These lines set the TODO keywords and their interpretation in the current file. The corresponding variable is `org-todo-keywords`.

## 15.7 The very busy C-c C-c key

The key `C-c C-c` has many purposes in Org, which are all mentioned scattered throughout this manual. One specific function of this key is to add *tags* to a headline (see [Chapter 6 \[Tags\]](#), page 59). In many other circumstances it means something like “*Hey Org, look here and update according to what you see here*”. Here is a summary of what this means in different contexts.

- If there are highlights in the buffer from the creation of a sparse tree, or from clock display, remove these highlights.
- If the cursor is in one of the special `#+KEYWORD` lines, this triggers scanning the buffer for these lines and updating the information.
- If the cursor is inside a table, realign the table. This command works even if the automatic table editor has been turned off.
- If the cursor is on a `#+TBLFM` line, re-apply the formulas to the entire table.
- If the current buffer is a capture buffer, close the note and file it. With a prefix argument, file it, without further interaction, to the default location.
- If the cursor is on a `<<<target>>>`, update radio targets and corresponding links in this buffer.
- If the cursor is in a property line or at the start or end of a property drawer, offer property commands.
- If the cursor is at a footnote reference, go to the corresponding definition, and *vice versa*.
- If the cursor is on a statistics cookie, update it.
- If the cursor is in a plain list item with a checkbox, toggle the status of the checkbox.
- If the cursor is on a numbered item in a plain list, renumber the ordered list.
- If the cursor is on the `#+BEGIN` line of a dynamic block, the block is updated.
- If the cursor is at a timestamp, fix the day name in the timestamp.

## 15.8 A cleaner outline view

Some people find it noisy and distracting that the Org headlines start with a potentially large number of stars, and that text below the headlines is not indented. While this is no problem when writing a *book-like* document where the outline headings are really section headings, in a more *list-oriented* outline, indented structure is a lot cleaner:

* Top level headline		* Top level headline
** Second level		* Second level
*** 3rd level		* 3rd level
some text		some text
*** 3rd level		* 3rd level
more text		more text
* Another top level headline		* Another top level headline

This kind of view can be achieved dynamically at display time using `org-indent-mode`. In this minor mode, all lines are prefixed for display with the necessary amount of space<sup>1</sup>. Also headlines are prefixed with additional stars, so that the amount of indentation shifts by two<sup>2</sup> spaces per level. All headline stars but the last one are made invisible using the `org-hide` face<sup>3</sup>; see below under ‘2.’ for more information on how this works. You can turn on `org-indent-mode` for all files by customizing the variable `org-startup-indented`, or you can turn it on for individual files using

```
#+STARTUP: indent
```

If you want a similar effect in an earlier version of Emacs and/or Org, or if you want the indentation to be hard space characters so that the plain text file looks as similar as possible to the Emacs display, Org supports you in the following way:

1. *Indentation of text below headlines*

You may indent text below each headline to make the left boundary line up with the headline, like

```
*** 3rd level
    more text, now indented
```

Org supports this with paragraph filling, line wrapping, and structure editing<sup>4</sup>, preserving or adapting the indentation as appropriate.

2. *Hiding leading stars*

You can modify the display in such a way that all leading stars become invisible. To do this in a global way, configure the variable `org-hide-leading-stars` or change this on a per-file basis with

```
#+STARTUP: hidestars
#+STARTUP: showstars
```

With hidden stars, the tree becomes:

```
* Top level headline
* Second level
* 3rd level
...
```

The leading stars are not truly replaced by whitespace, they are only fontified with the face `org-hide` that uses the background color as font color. If you are not using either white or black background, you may have to customize this face to get the wanted effect.

<sup>1</sup> `org-indent-mode` also sets the `wrap-prefix` property, such that `visual-line-mode` (or purely setting `word-wrap`) wraps long lines (including headlines) correctly indented.

<sup>2</sup> See the variable `org-indent-indentation-per-level`.

<sup>3</sup> Turning on `org-indent-mode` sets `org-hide-leading-stars` to `t` and `org-adapt-indentation` to `nil`.

<sup>4</sup> See also the variable `org-adapt-indentation`.

Another possibility is to set this font such that the extra stars are *almost* invisible, for example using the color `grey90` on a white background.

- Things become cleaner still if you skip all the even levels and use only odd levels 1, 3, 5..., effectively adding two stars to go from one outline level to the next<sup>5</sup>. In this way we get the outline view shown at the beginning of this section. In order to make the structure editing and export commands handle this convention correctly, configure the variable `org-odd-levels-only`, or set this on a per-file basis with one of the following lines:

```
#+STARTUP: odd
#+STARTUP: oddeven
```

You can convert an Org file from single-star-per-level to the double-star-per-level convention with `M-x org-convert-to-odd-levels RET` in that file. The reverse operation is `M-x org-convert-to-oddeven-levels`.

## 15.9 Using Org on a tty

Because Org contains a large number of commands, by default many of Org's core commands are bound to keys that are generally not accessible on a tty, such as the cursor keys (`left`, `right`, `up`, `down`), `TAB` and `RET`, in particular when used together with modifiers like `Meta` and/or `Shift`. To access these commands on a tty when special keys are unavailable, the following alternative bindings can be used. The tty bindings below will likely be more cumbersome; you may find for some of the bindings below that a customized workaround suits you better. For example, changing a timestamp is really only fun with `S-cursor` keys, whereas on a tty you would rather use `C-c .` to re-insert the timestamp.

Default	Alternative 1	Speed key	Alternative 2
<code>S-TAB</code>	<code>C-u TAB</code>	<code>C</code>	
<code>M-left</code>	<code>C-c C-x l</code>	<code>l</code>	<code>Esc left</code>
<code>M-S-left</code>	<code>C-c C-x L</code>	<code>L</code>	
<code>M-right</code>	<code>C-c C-x r</code>	<code>r</code>	<code>Esc right</code>
<code>M-S-right</code>	<code>C-c C-x R</code>	<code>R</code>	
<code>M-up</code>	<code>C-c C-x u</code>		<code>Esc up</code>
<code>M-S-up</code>	<code>C-c C-x U</code>	<code>U</code>	
<code>M-down</code>	<code>C-c C-x d</code>		<code>Esc down</code>
<code>M-S-down</code>	<code>C-c C-x D</code>	<code>D</code>	
<code>S-RET</code>	<code>C-c C-x c</code>		
<code>M-RET</code>	<code>C-c C-x m</code>		<code>Esc RET</code>
<code>M-S-RET</code>	<code>C-c C-x M</code>		
<code>S-left</code>	<code>C-c left</code>		
<code>S-right</code>	<code>C-c right</code>		
<code>S-up</code>	<code>C-c up</code>		
<code>S-down</code>	<code>C-c down</code>		
<code>C-S-left</code>	<code>C-c C-x left</code>		
<code>C-S-right</code>	<code>C-c C-x right</code>		

<sup>5</sup> When you need to specify a level for a property search or refile targets, `'LEVEL=2'` will correspond to 3 stars, etc.

## 15.10 Interaction with other packages

Org lives in the world of GNU Emacs and interacts in various ways with other code out there.

### 15.10.1 Packages that Org cooperates with

`calc.el` by Dave Gillespie

Org uses the Calc package for implementing spreadsheet functionality in its tables (see [Section 3.5 \[The spreadsheet\]](#), page 24). Another possibility for interaction between the two packages is using Calc for embedded calculations. See [Section “Embedded Mode” in GNU Emacs Calc Manual](#).

`constants.el` by Carsten Dominik

In a table formula (see [Section 3.5 \[The spreadsheet\]](#), page 24), it is possible to use names for natural constants or units. Instead of defining your own constants in the variable `org-table-formula-constants`, install the `constants` package which defines a large number of constants and units, and lets you use unit prefixes like ‘M’ for ‘Mega’, etc. You will need version 2.0 of this package, available at <http://www.astro.uva.nl/~dominik/Tools>. Org checks for the function `constants-get`, which has to be autoloaded in your setup. See the installation instructions in the file `constants.el`.

`cdlatex.el` by Carsten Dominik

Org mode can make use of the CD $\LaTeX$  package to efficiently enter  $\LaTeX$  fragments into Org files. See [Section 11.8.3 \[CD \$\LaTeX\$  mode\]](#), page 134.

`imenu.el` by Ake Stenhoff and Lars Lindberg

Imenu allows menu access to an index of items in a file. Org mode supports Imenu—all you need to do to get the index is the following:

```
(add-hook 'org-mode-hook
  (lambda () (imenu-add-to-menubar "Imenu")))
```

By default the index is two levels deep—you can modify the depth using the option `org-imenu-depth`.

`speedbar.el` by Eric M. Ludlam

Speedbar is a package that creates a special frame displaying files and index items in files. Org mode supports Speedbar and allows you to drill into Org files directly from the Speedbar. It also allows you to restrict the scope of agenda commands to a file or a subtree by using the command `<` in the Speedbar frame.

`table.el` by Takaaki Ota

Complex ASCII tables with automatic line wrapping, column- and row-spanning, and alignment can be created using the Emacs table package by Takaaki Ota. Org mode will recognize these tables and export them properly. Because of interference with other Org mode functionality, you unfortunately cannot edit these tables directly in the buffer. Instead, you need to use the command `C-c '` to edit them, similar to source code snippets.

`C-c '` `org-edit-special`  
 Edit a `table.el` table. Works when the cursor is in a `table.el` table.

`C-c ~` `org-table-create-with-table.el`  
 Insert a `table.el` table. If there is already a table at point, this command converts it between the `table.el` format and the Org mode format. See the documentation string of the command `org-convert-table` for the restrictions under which this is possible.

### 15.10.2 Packages that lead to conflicts with Org mode

In Emacs, `shift-selection-mode` is on by default, meaning that cursor motions combined with the shift key should start or enlarge regions. This conflicts with the use of `S-cursor` commands in Org to change timestamps, TODO keywords, priorities, and item bullet types if the cursor is at such a location. By default, `S-cursor` commands outside special contexts don't do anything, but you can customize the variable `org-support-shift-select`. Org mode then tries to accommodate shift selection by (i) using it outside of the special contexts where special commands apply, and by (ii) extending an existing active region even if the cursor moves across a special context.

`CUA.el` by Kim. F. Storm

For the same reason, key bindings in Org also conflict with the `S-<cursor>` keys used by CUA mode. If you prefer to leave these keys to a different package while working in Org mode, configure the variable `org-replace-disputed-keys`. When set, Org will move the following key bindings in Org files, and in the agenda buffer (but not during date selection).

<code>S-UP</code>	$\Rightarrow$	<code>M-p</code>	<code>S-DOWN</code>	$\Rightarrow$	<code>M-n</code>
<code>S-LEFT</code>	$\Rightarrow$	<code>M--</code>	<code>S-RIGHT</code>	$\Rightarrow$	<code>M-+</code>
<code>C-S-LEFT</code>	$\Rightarrow$	<code>M-S--</code>	<code>C-S-RIGHT</code>	$\Rightarrow$	<code>M-S-+</code>

Yes, these are unfortunately more difficult to remember. If you want to have other replacement keys, look at the variable `org-disputed-keys`.

`ecomplete.el` by Lars Magne Ingebrigtsen [larsi@gnus.org](mailto:larsi@gnus.org)

Ecomplete provides “electric” address completion in address header lines in message buffers. Sadly Orgtbl mode cuts ecompletes power supply: No completion happens when Orgtbl mode is enabled in message buffers while entering text in address header lines. If one wants to use ecomplete one should *not* follow the advice to automatically turn on Orgtbl mode in message buffers (see [Section 3.4 \[Orgtbl mode\], page 24](#)), but instead—after filling in the message headers—turn on Orgtbl mode manually when needed in the messages body.

`filladapt.el` by Kyle Jones

Org mode tries to do the right thing when filling paragraphs, list items and other elements. Many users reported they had problems using both `filladapt.el` and Org mode, so a safe thing to do is to disable it like this:

```
(add-hook 'org-mode-hook 'turn-off-filladapt-mode)
```

**yasnippet.el**

The way Org mode binds the TAB key (binding to [tab] instead of "\t") overrules YASnippet's access to this key. The following code fixed this problem:

```
(add-hook 'org-mode-hook
  (lambda ()
    (org-set-local 'yas/trigger-key [tab])
    (define-key yas/keymap [tab] 'yas/next-field-or-maybe-expand)))
```

The latest version of yasnippet doesn't play well with Org mode. If the above code does not fix the conflict, start by defining the following function:

```
(defun yas/org-very-safe-expand ()
  (let ((yas/fallback-behavior 'return-nil)) (yas/expand)))
```

Then, tell Org mode what to do with the new function:

```
(add-hook 'org-mode-hook
  (lambda ()
    (make-variable-buffer-local 'yas/trigger-key)
    (setq yas/trigger-key [tab])
    (add-to-list 'org-tab-first-hook 'yas/org-very-safe-expand)
    (define-key yas/keymap [tab] 'yas/next-field)))
```

**windmove.el** by Hovav Shacham

This package also uses the *S-cursor* keys, so everything written in the paragraph above about CUA mode also applies here. If you want make the windmove function active in locations where Org mode does not have special functionality on *S-cursor*, add this to your configuration:

```
;; Make windmove work in org-mode:
(add-hook 'org-shiftup-final-hook 'windmove-up)
(add-hook 'org-shiftright-final-hook 'windmove-right)
(add-hook 'org-shiftleft-final-hook 'windmove-left)
(add-hook 'org-shiftdown-final-hook 'windmove-down)
```

**viper.el** by Michael Kifer

Viper uses C-c / and therefore makes this key not access the corresponding Org mode command `org-sparse-tree`. You need to find another key for this command, or override the key in `viper-vi-global-user-map` with

```
(define-key viper-vi-global-user-map "C-c /" 'org-sparse-tree)
```

**15.11 org-crypt.el**

Org-crypt will encrypt the text of an entry, but not the headline, or properties. Org-crypt uses the Emacs EasyPG library to encrypt and decrypt files.

Any text below a headline that has a `:crypt:` tag will be automatically be encrypted when the file is saved. If you want to use a different tag just customize the `org-crypt-tag-matcher` setting.

To use org-crypt it is suggested that you have the following in your `.emacs`:

```
(require 'org-crypt)
(org-crypt-use-before-save-magic)
```

```
(setq org-tags-exclude-from-inheritance (quote ("crypt")))  
  
(setq org-crypt-key nil)  
  ;; GPG key to use for encryption  
  ;; Either the Key ID or set to nil to use symmetric encryption.  
  
(setq auto-save-default nil)  
  ;; Auto-saving does not cooperate with org-crypt.el: so you need  
  ;; to turn it off if you plan to use org-crypt.el quite often.  
  ;; Otherwise, you'll get an (annoying) message each time you  
  ;; start Org.  
  
  ;; To turn it off only locally, you can insert this:  
  ;;  
  ;; # -*- buffer-auto-save-file-name: nil; -*-
```

Excluding the crypt tag from inheritance prevents already encrypted text being encrypted again.

## Appendix A Hacking

This appendix covers some areas where users can extend the functionality of Org.

### A.1 Hooks

Org has a large number of hook variables that can be used to add functionality. This appendix about hacking is going to illustrate the use of some of them. A complete list of all hooks with documentation is maintained by the Worg project and can be found at <http://orgmode.org/worg/org-configs/org-hooks.php>.

### A.2 Add-on packages

A large number of add-on packages have been written by various authors.

These packages are not part of Emacs, but they are distributed as contributed packages with the separate release available at <http://orgmode.org>. See the `contrib/README` file in the source code directory for a list of contributed files. You may also find some more information on the Worg page: <http://orgmode.org/worg/org-contrib/>.

### A.3 Adding hyperlink types

Org has a large number of hyperlink types built-in (see [Chapter 4 \[Hyperlinks\]](#), page 38). If you would like to add new link types, Org provides an interface for doing so. Let's look at an example file, `org-man.el`, that will add support for creating links like `'[[man:printf][The printf manpage]]'` to show Unix manual pages inside Emacs:

```
;;; org-man.el - Support for links to manpages in Org

(require 'org)

(org-add-link-type "man" 'org-man-open)
(add-hook 'org-store-link-functions 'org-man-store-link)

(defcustom org-man-command 'man
  "The Emacs command to be used to display a man page."
  :group 'org-link
  :type '(choice (const man) (const woman)))

(defun org-man-open (path)
  "Visit the manpage on PATH.
PATH should be a topic that can be thrown at the man command."
  (funcall org-man-command path))

(defun org-man-store-link ()
  "Store a link to a manpage."
  (when (memq major-mode '(Man-mode woman-mode))
    ;; This is a man page, we do make this link
    (let* ((page (org-man-get-page-name))
           (link (concat "man:" page)))
```



```

      (description (format "Manpage for %s" page)))
(org-store-link-props
 :type "man"
 :link link
 :description description))))

(defun org-man-get-page-name ()
  "Extract the page name from the buffer name."
  ;; This works for both `Man-mode' and `woman-mode'.
  (if (string-match " \\(\\S-+\\)\\*" (buffer-name))
      (match-string 1 (buffer-name))
      (error "Cannot create link to this man page")))

(provide 'org-man)

;;; org-man.el ends here

```

You would activate this new link type in `.emacs` with

```
(require 'org-man)
```

Let's go through the file and see what it does.

1. It does `(require 'org)` to make sure that `org.el` has been loaded.
2. The next line calls `org-add-link-type` to define a new link type with prefix `'man'`. The call also contains the name of a function that will be called to follow such a link.
3. The next line adds a function to `org-store-link-functions`, in order to allow the command `C-c l` to record a useful link in a buffer displaying a man page.

The rest of the file defines the necessary variables and functions. First there is a customization variable that determines which Emacs command should be used to display man pages. There are two options, `man` and `woman`. Then the function to follow a link is defined. It gets the link path as an argument—in this case the link path is just a topic for the manual command. The function calls the value of `org-man-command` to display the man page.

Finally the function `org-man-store-link` is defined. When you try to store a link with `C-c l`, this function will be called to try to make a link. The function must first decide if it is supposed to create the link for this buffer type; we do this by checking the value of the variable `major-mode`. If not, the function must exit and return the value `nil`. If yes, the link is created by getting the manual topic from the buffer name and prefixing it with the string `'man:'`. Then it must call the command `org-store-link-props` and set the `:type` and `:link` properties. Optionally you can also set the `:description` property to provide a default for the link description when the link is later inserted into an Org buffer with `C-c C-l`.

When it makes sense for your new link type, you may also define a function that implements special (e.g., completion) support for inserting such a link with `C-c C-l`. Such a function should not accept any arguments, and return the full link with prefix.

## A.4 Adding export back-ends

Org 8.0 comes with a completely rewritten export engine which makes it easy to write new export back-ends, either from scratch, or by deriving them from existing ones.

Your two entry points are respectively `org-export-define-backend` and `org-export-define-derived-backend`. To grok these functions, you should first have a look at `ox-latex.el` (for how to define a new back-end from scratch) and `ox-beamer.el` (for how to derive a new back-end from an existing one).

When creating a new back-end from scratch, the basic idea is to set the name of the back-end (as a symbol) and an alist of elements and export functions. On top of this, you will need to set additional keywords like `:menu-entry` (to display the back-end in the export dispatcher), and `:options-alist` (to let the user set export options that are specific to this back-end.)

Deriving a new back-end is similar, except that you need to set `:translate-alist` to an alist of export functions that should be used instead of the parent back-end functions.

For a complete reference documentation, see [the Org Export Reference on Worg](#).

## A.5 Context-sensitive commands

Org has several commands that act differently depending on context. The most important example is the `C-c C-c` (see [Section 15.7 \[The very busy C-c C-c key\]](#), page 230). Also the `M-cursor` and `M-S-cursor` keys have this property.

Add-ons can tap into this functionality by providing a function that detects special context for that add-on and executes functionality appropriate for the context. Here is an example from Dan Davison's `org-R.el` which allows you to evaluate commands based on the R programming language<sup>1</sup>. For this package, special contexts are lines that start with `#+R:` or `#+RR:`.

```
(defun org-R-apply-maybe ()
  "Detect if this is context for org-R and execute R commands."
  (if (save-excursion
        (beginning-of-line 1)
        (looking-at "#\\+RR?:"))
      (progn (call-interactively 'org-R-apply)
              t) ;; to signal that we took action
      nil)) ;; to signal that we did not

(add-hook 'org-ctrl-c-ctrl-c-hook 'org-R-apply-maybe)
```

The function first checks if the cursor is in such a line. If that is the case, `org-R-apply` is called and the function returns `t` to signal that action was taken, and `C-c C-c` will stop looking for other contexts. If the function finds it should do nothing locally, it returns `nil` so that other, similar functions can have a try.

## A.6 Tables and lists in arbitrary syntax

Since Orgtbl mode can be used as a minor mode in arbitrary buffers, a frequent feature request has been to make it work with native tables in specific languages, for example  $\text{\LaTeX}$ . However, this is extremely hard to do in a general way, would lead to a customization nightmare, and would take away much of the simplicity of the Orgtbl mode table editor.

<sup>1</sup> `org-R.el` has been replaced by the Org mode functionality described in [Chapter 14 \[Working with source code\]](#), page 194 and is now obsolete.

This appendix describes a different approach. We keep the Orgtbl mode table in its native format (the *source table*), and use a custom function to *translate* the table to the correct syntax, and to *install* it in the right location (the *target table*). This puts the burden of writing conversion functions on the user, but it allows for a very flexible system.

Bastien added the ability to do the same with lists, in Orgstruct mode. You can use Org’s facilities to edit and structure lists by turning `orgstruct-mode` on, then locally exporting such lists in another format (HTML, L<sup>A</sup>T<sub>E</sub>X or Texinfo.)

### A.6.1 Radio tables

To define the location of the target table, you first need to create two lines that are comments in the current mode, but contain magic words `BEGIN/END RECEIVE ORGTBL` for Orgtbl mode to find. Orgtbl mode will insert the translated table between these lines, replacing whatever was there before. For example in C mode where comments are between `/* ... */`:

```
/* BEGIN RECEIVE ORGTBL table_name */
/* END RECEIVE ORGTBL table_name */
```

Just above the source table, we put a special line that tells Orgtbl mode how to translate this table and where to install it. For example:

```
#+ORGTBL: SEND table_name translation_function arguments...
```

`table_name` is the reference name for the table that is also used in the receiver lines. `translation_function` is the Lisp function that does the translation. Furthermore, the line can contain a list of arguments (alternating key and value) at the end. The arguments will be passed as a property list to the translation function for interpretation. A few standard parameters are already recognized and acted upon before the translation function is called:

- `:skip N`     Skip the first N lines of the table. Hlines do count as separate lines for this parameter!
- `:skipcols (n1 n2 ...)`  
List of columns that should be skipped. If the table has a column with calculation marks, that column is automatically discarded as well. Please note that the translator function sees the table *after* the removal of these columns, the function never knows that there have been additional columns.

The one problem remaining is how to keep the source table in the buffer without disturbing the normal workings of the file, for example during compilation of a C file or processing of a L<sup>A</sup>T<sub>E</sub>X file. There are a number of different solutions:

- The table could be placed in a block comment if that is supported by the language. For example, in C mode you could wrap the table between `/*` and `*/` lines.
- Sometimes it is possible to put the table after some kind of *END* statement, for example `\bye` in T<sub>E</sub>X and `\end{document}` in L<sup>A</sup>T<sub>E</sub>X.
- You can just comment the table line-by-line whenever you want to process the file, and uncomment it whenever you need to edit the table. This only sounds tedious—the command `M-x orgtbl-toggle-comment RET` makes this comment-toggling very easy, in particular if you bind it to a key.

### A.6.2 A $\text{\LaTeX}$ example of radio tables

The best way to wrap the source table in  $\text{\LaTeX}$  is to use the `comment` environment provided by `comment.sty`. It has to be activated by placing `\usepackage{comment}` into the document header. Orgtbl mode can insert a radio table skeleton<sup>2</sup> with the command `M-x orgtbl-insert-radio-table RET`. You will be prompted for a table name, let's say we use 'salesfigures'. You will then get the following template:

```
% BEGIN RECEIVE ORGTBL salesfigures
% END RECEIVE ORGTBL salesfigures
\begin{comment}
#+ORGTBL: SEND salesfigures orgtbl-to-latex
| | |
\end{comment}
```

The `#+ORGTBL: SEND` line tells Orgtbl mode to use the function `orgtbl-to-latex` to convert the table into  $\text{\LaTeX}$  and to put it into the receiver location with name `salesfigures`. You may now fill in the table—feel free to use the spreadsheet features<sup>3</sup>:

```
% BEGIN RECEIVE ORGTBL salesfigures
% END RECEIVE ORGTBL salesfigures
\begin{comment}
#+ORGTBL: SEND salesfigures orgtbl-to-latex
| Month | Days | Nr sold | per day |
|-----+-----+-----+-----|
| Jan   | 23   | 55    | 2.4   |
| Feb   | 21   | 16    | 0.8   |
| March | 22   | 278   | 12.6  |
#+TBLFM: $4=$3/$2;%.1f
% $ (optional extra dollar to keep font-lock happy, see footnote)
\end{comment}
```

When you are done, press `C-c C-c` in the table to get the converted table inserted between the two marker lines.

Now let's assume you want to make the table header by hand, because you want to control how columns are aligned, etc. In this case we make sure that the table translator skips the first 2 lines of the source table, and tell the command to work as a *splice*, i.e., to not produce header and footer commands of the target table:

```
\begin{tabular}{lrrrr}
Month & \multicolumn{1}{c}{Days} & Nr.\ sold & per day\\
% BEGIN RECEIVE ORGTBL salesfigures
% END RECEIVE ORGTBL salesfigures
\end{tabular}
```

<sup>2</sup> By default this works only for  $\text{\LaTeX}$ , HTML, and Texinfo. Configure the variable `orgtbl-radio-table-templates` to install templates for other modes.

<sup>3</sup> If the `#+TBLFM` line contains an odd number of dollar characters, this may cause problems with font-lock in  $\text{\LaTeX}$  mode. As shown in the example you can fix this by adding an extra line inside the `comment` environment that is used to balance the dollar expressions. If you are using  $\text{\LaTeX}$  with the `font-latex` library, a much better solution is to add the `comment` environment to the variable `LaTeX-verbatim-environments`.

```
%
\begin{comment}
#+ORGTBL: SEND salesfigures orgtbl-to-latex :splice t :skip 2
| Month | Days | Nr sold | per day |
|-----+-----+-----+-----|
| Jan   | 23   | 55    | 2.4   |
| Feb   | 21   | 16    | 0.8   |
| March | 22   | 278   | 12.6  |
#+TBLFM: $4=$3/$2;%.1f
\end{comment}
```

The  $\text{\LaTeX}$  translator function `orgtbl-to-latex` is already part of `Orgtbl` mode. By default, it uses a `tabular` environment to typeset the table and marks horizontal lines with `\hline`. You can control the output through several parameters (see also see [Section A.6.3 \[Translator functions\]](#), [page 242](#)), including the following ones :

`:splice nil/t`

When non-`nil`, return only table body lines, don't wrap them into a `tabular` environment. Default is `nil`.

`:fmt fmt` A format to be used to wrap each field, it should contain `%s` for the original field value. For example, to wrap each field value in dollars, you could use `:fmt "$s$"`. This may also be a property list with column numbers and formats, for example `:fmt (2 "$s$" 4 "%s\\%")`. A function of one argument can be used in place of the strings; the function must return a formatted string.

`:efmt efmt`

Use this format to print numbers with exponentials. The format should have `%s` twice for inserting mantissa and exponent, for example `"%s\\times10^{%s}"`. This may also be a property list with column numbers and formats, for example `:efmt (2 "$s\\times10^{%s}" 4 "$s\\cdot10^{%s}")`. After `efmt` has been applied to a value, `fmt` will also be applied. Similar to `fmt`, functions of two arguments can be supplied instead of strings. By default, no special formatting is applied.

### A.6.3 Translator functions

`Orgtbl` mode has several translator functions built-in: `orgtbl-to-csv` (comma-separated values), `orgtbl-to-tsv` (TAB-separated values) `orgtbl-to-latex`, `orgtbl-to-html`, `orgtbl-to-texinfo`, `orgtbl-to-unicode` and `orgtbl-to-orgtbl`. These all use a generic translator, `orgtbl-to-generic`, which, in turn, delegates translations to various export back-ends.

In particular, properties passed into the function (i.e., the ones set by the '`ORGTBL SEND`' line) take precedence over translations defined in the function. So if you would like to use the  $\text{\LaTeX}$  translator, but wanted the line endings to be '`\\[2mm]`' instead of the default '`\\`', you could just overrule the default with

```
#+ORGTBL: SEND test orgtbl-to-latex :lend " \\[2mm]"
```

For a new language, you can use the generic function to write your own converter function. For example, if you have a language where a table is started with '`!BTBL!`', ended

with ‘!ETBL!’, and where table lines are started with ‘!BL!’, ended with ‘!EL!’, and where the field separator is a TAB, you could define your generic translator like this:

```
(defun orgtbl-to-language (table params)
  "Convert the orgtbl-mode TABLE to language."
  (orgtbl-to-generic
   table
   (org-combine-plists
    '(:tstart "!BTBL!" :tend "!ETBL!" :lstart "!BL!" :lend "!EL!" :sep "\t")
    params)))
```

Please check the documentation string of the function `orgtbl-to-generic` for a full list of parameters understood by that function, and remember that you can pass each of them into `orgtbl-to-latex`, `orgtbl-to-texinfo`, and any other function using the generic function.

Of course you can also write a completely new function doing complicated things the generic translator cannot do. A translator function takes two arguments. The first argument is the table, a list of lines, each line either the symbol `hline` or a list of fields. The second argument is the property list containing all parameters specified in the ‘`#+ORGTBL: SEND`’ line. The function must return a single string containing the formatted table. If you write a generally useful translator, please post it on [emacs-orgmode@gnu.org](mailto:emacs-orgmode@gnu.org) so that others can benefit from your work.

#### A.6.4 Radio lists

Sending and receiving radio lists works exactly the same way as sending and receiving radio tables (see [Section A.6.1 \[Radio tables\]](#), page 240). As for radio tables, you can insert radio list templates in HTML, L<sup>A</sup>T<sub>E</sub>X and Texinfo modes by calling `org-list-insert-radio-list`.

Here are the differences with radio tables:

- Orgstruct mode must be active.
- Use the `ORGLST` keyword instead of `ORGTBL`.
- `C-c C-c` will work when pressed on the first item of the list.

Built-in translators functions are : `org-list-to-latex`, `org-list-to-html` and `org-list-to-texinfo`. They all use the generic translator `org-list-to-generic`. Please check its documentation for a list of supported parameters, which can be used to control more accurately how the list should be rendered.

Here is a L<sup>A</sup>T<sub>E</sub>X example. Let’s say that you have this in your L<sup>A</sup>T<sub>E</sub>X file:

```
% BEGIN RECEIVE ORGLST to-buy
% END RECEIVE ORGLST to-buy
\begin{comment}
#+ORGLST: SEND to-buy org-list-to-latex
- a new house
- a new computer
+ a new keyboard
+ a new mouse
- a new life
\end{comment}
```

Pressing `C-c C-c` on `a new house` and will insert the converted L<sup>A</sup>T<sub>E</sub>X list between the two marker lines.

## A.7 Dynamic blocks

Org documents can contain *dynamic blocks*. These are specially marked regions that are updated by some user-written function. A good example for such a block is the clock table inserted by the command `C-c C-x C-r` (see [Section 8.4 \[Clocking work time\]](#), page 80).

Dynamic blocks are enclosed by a BEGIN-END structure that assigns a name to the block and can also specify parameters for the function producing the content of the block.

```
#+BEGIN: myblock :parameter1 value1 :parameter2 value2 ...

#+END:
```

Dynamic blocks are updated with the following commands

```
C-c C-x C-u                                     org-dblock-update
      Update dynamic block at point.
```

```
C-u C-c C-x C-u
      Update all dynamic blocks in the current file.
```

Updating a dynamic block means to remove all the text between BEGIN and END, parse the BEGIN line for parameters and then call the specific writer function for this block to insert the new content. If you want to use the original content in the writer function, you can use the extra parameter `:content`.

For a block with name `myblock`, the writer function is `org-dblock-write:myblock` with as only parameter a property list with the parameters given in the begin line. Here is a trivial example of a block that keeps track of when the block update function was last run:

```
#+BEGIN: block-update-time :format "on %m/%d/%Y at %H:%M"

#+END:
```

The corresponding block writer function could look like this:

```
(defun org-dblock-write:block-update-time (params)
  (let ((fmt (or (plist-get params :format) "%d. %m. %Y")))
    (insert "Last block update at: "
            (format-time-string fmt))))
```

If you want to make sure that all dynamic blocks are always up-to-date, you could add the function `org-update-all-dblocks` to a hook, for example `before-save-hook`. `org-update-all-dblocks` is written in a way such that it does nothing in buffers that are not in `org-mode`.

You can narrow the current buffer to the current dynamic block (like any other block) with `org-narrow-to-block`.

## A.8 Special agenda views

Org provides a special hook that can be used to narrow down the selection made by these agenda views: `agenda`, `agenda*`<sup>4</sup>, `todo`, `alltodo`, `tags`, `tags-todo`, `tags-tree`. You may specify a function that is used at each match to verify if the match should indeed be part of the agenda view, and if not, how much should be skipped. You can specify a global condition that will be applied to all agenda views, this condition would be stored in the variable `org-agenda-skip-function-global`. More commonly, such a definition is applied only to specific custom searches, using `org-agenda-skip-function`.

Let's say you want to produce a list of projects that contain a `WAITING` tag anywhere in the project tree. Let's further assume that you have marked all tree headings that define a project with the `TODO` keyword `PROJECT`. In this case you would run a `TODO` search for the keyword `PROJECT`, but skip the match unless there is a `WAITING` tag anywhere in the subtree belonging to the project line.

To achieve this, you must write a function that searches the subtree for the tag. If the tag is found, the function must return `nil` to indicate that this match should not be skipped. If there is no such tag, return the location of the end of the subtree, to indicate that search should continue from there.

```
(defun my-skip-unless-waiting ()
  "Skip trees that are not waiting"
  (let ((subtree-end (save-excursion (org-end-of-subtree t))))
    (if (re-search-forward ":waiting:" subtree-end t)
        nil ; tag found, do not skip
        subtree-end))) ; tag not found, continue after end of subtree
```

Now you may use this function in an agenda custom command, for example like this:

```
(org-add-agenda-custom-command
  '("b" todo "PROJECT"
    ((org-agenda-skip-function 'my-skip-unless-waiting)
     (org-agenda-overriding-header "Projects waiting for something: "))))
```

Note that this also binds `org-agenda-overriding-header` to get a meaningful header in the agenda view.

A general way to create custom searches is to base them on a search for entries with a certain level limit. If you want to study all entries with your custom search function, simply do a search for `'LEVEL>0'`<sup>5</sup>, and then use `org-agenda-skip-function` to select the entries you really want to have.

You may also put a Lisp form into `org-agenda-skip-function`. In particular, you may use the functions `org-agenda-skip-entry-if` and `org-agenda-skip-subtree-if` in this form, for example:

```
(org-agenda-skip-entry-if 'scheduled)
  Skip current entry if it has been scheduled.
```

<sup>4</sup> The `agenda*` view is the same as `agenda` except that it only considers *appointments*, i.e., scheduled and deadline items that have a time specification `[h]h:mm` in their time-stamps.

<sup>5</sup> Note that, when using `org-odd-levels-only`, a level number corresponds to order in the hierarchy, not to the number of stars.



```

(org-agenda-skip-entry-if 'notscheduled)
    Skip current entry if it has not been scheduled.
(org-agenda-skip-entry-if 'deadline)
    Skip current entry if it has a deadline.
(org-agenda-skip-entry-if 'scheduled 'deadline)
    Skip current entry if it has a deadline, or if it is scheduled.
(org-agenda-skip-entry-if 'todo '("TODO" "WAITING"))
    Skip current entry if the TODO keyword is TODO or WAITING.
(org-agenda-skip-entry-if 'todo 'done)
    Skip current entry if the TODO keyword marks a DONE state.
(org-agenda-skip-entry-if 'timestamp)
    Skip current entry if it has any timestamp, may also be deadline or scheduled.
(org-agenda-skip-entry-if 'regexp "regular expression")
    Skip current entry if the regular expression matches in the entry.
(org-agenda-skip-entry-if 'notregexp "regular expression")
    Skip current entry unless the regular expression matches.
(org-agenda-skip-subtree-if 'regexp "regular expression")
    Same as above, but check and skip the entire subtree.

```

Therefore we could also have written the search for WAITING projects like this, even without defining a special function:

```

(org-add-agenda-custom-command
  '("b" todo "PROJECT"
    ((org-agenda-skip-function '(org-agenda-skip-subtree-if
                               'regexp ":waiting:"))
     (org-agenda-overriding-header "Projects waiting for something: "))))

```

## A.9 Speeding up your agendas

When your Org files grow in both number and size, agenda commands may start to become slow. Below are some tips on how to speed up the agenda commands.

1. Reduce the number of Org agenda files: this will reduce the slowdown caused by accessing a hard drive.
2. Reduce the number of DONE and archived headlines: this way the agenda does not need to skip them.
3. Inhibit the dimming of blocked tasks:
 

```
(setq org-agenda-dim-blocked-tasks nil)
```
4. Inhibit agenda files startup options:
 

```
(setq org-agenda-inhibit-startup nil)
```
5. Disable tag inheritance in agenda:
 

```
(setq org-agenda-use-tag-inheritance nil)
```

You can set these options for specific agenda views only. See the docstrings of these variables for details on why they affect the agenda generation, and this [dedicated Worg page](#) for further explanations.

## A.10 Extracting agenda information

Org provides commands to access agenda information for the command line in Emacs batch mode. This extracted information can be sent directly to a printer, or it can be read by a program that does further processing of the data. The first of these commands is the function `org-batch-agenda`, that produces an agenda view and sends it as ASCII text to STDOUT. The command takes a single string as parameter. If the string has length 1, it is used as a key to one of the commands you have configured in `org-agenda-custom-commands`, basically any key you can use after `C-c a`. For example, to directly print the current TODO list, you could use

```
emacs -batch -l ~/.emacs -eval '(org-batch-agenda "t")' | lpr
```

If the parameter is a string with 2 or more characters, it is used as a tags/TODO match string. For example, to print your local shopping list (all items with the tag ‘shop’, but excluding the tag ‘NewYork’), you could use

```
emacs -batch -l ~/.emacs \
  -eval '(org-batch-agenda "+shop-NewYork")' | lpr
```

You may also modify parameters on the fly like this:

```
emacs -batch -l ~/.emacs \
  -eval '(org-batch-agenda "a" \
    org-agenda-span (quote month) \
    org-agenda-include-diary nil \
    org-agenda-files (quote ("~/org/project.org")))' \
  | lpr
```

which will produce a 30-day agenda, fully restricted to the Org file `~/org/projects.org`, not even including the diary.

If you want to process the agenda data in more sophisticated ways, you can use the command `org-batch-agenda-csv` to get a comma-separated list of values for each agenda item. Each line in the output will contain a number of fields separated by commas. The fields in a line are:

<b>category</b>	The category of the item																				
<b>head</b>	The headline, without TODO keyword, TAGS and PRIORITY																				
<b>type</b>	The type of the agenda entry, can be																				
	<table> <tr> <td><code>todo</code></td><td>selected in TODO match</td></tr> <tr> <td><code>tagsmatch</code></td><td>selected in tags match</td></tr> <tr> <td><code>diary</code></td><td>imported from diary</td></tr> <tr> <td><code>deadline</code></td><td>a deadline</td></tr> <tr> <td><code>scheduled</code></td><td>scheduled</td></tr> <tr> <td><code>timestamp</code></td><td>appointment, selected by timestamp</td></tr> <tr> <td><code>closed</code></td><td>entry was closed on date</td></tr> <tr> <td><code>upcoming-deadline</code></td><td>warning about nearing deadline</td></tr> <tr> <td><code>past-scheduled</code></td><td>forwarded scheduled item</td></tr> <tr> <td><code>block</code></td><td>entry has date block including date</td></tr> </table>	<code>todo</code>	selected in TODO match	<code>tagsmatch</code>	selected in tags match	<code>diary</code>	imported from diary	<code>deadline</code>	a deadline	<code>scheduled</code>	scheduled	<code>timestamp</code>	appointment, selected by timestamp	<code>closed</code>	entry was closed on date	<code>upcoming-deadline</code>	warning about nearing deadline	<code>past-scheduled</code>	forwarded scheduled item	<code>block</code>	entry has date block including date
<code>todo</code>	selected in TODO match																				
<code>tagsmatch</code>	selected in tags match																				
<code>diary</code>	imported from diary																				
<code>deadline</code>	a deadline																				
<code>scheduled</code>	scheduled																				
<code>timestamp</code>	appointment, selected by timestamp																				
<code>closed</code>	entry was closed on date																				
<code>upcoming-deadline</code>	warning about nearing deadline																				
<code>past-scheduled</code>	forwarded scheduled item																				
<code>block</code>	entry has date block including date																				
<b>todo</b>	The TODO keyword, if any																				
<b>tags</b>	All tags including inherited ones, separated by colons																				
<b>date</b>	The relevant date, like 2007-2-14																				
<b>time</b>	The time, like 15:00-16:50																				

<b>extra</b>	String with extra planning info
<b>priority-l</b>	The priority letter if any was given
<b>priority-n</b>	The computed numerical priority

Time and date will only be given if a timestamp (or deadline/scheduled) led to the selection of the item.

A CSV list like this is very easy to use in a post-processing script. For example, here is a Perl program that gets the TODO list from Emacs/Org and prints all the items, preceded by a checkbox:

```
#!/usr/bin/perl

# define the Emacs command to run
$cmd = "emacs -batch -l ~/.emacs -eval '(org-batch-agenda-csv \"t\")'";

# run it and capture the output
$agenda = qx{$cmd 2>/dev/null};

# loop over all lines
foreach $line (split(/\n/,$agenda)) {
    # get the individual values
    ($category,$head,$type,$todo,$tags,$date,$time,$extra,
     $priority_l,$priority_n) = split(/,/,$line);
    # process and print
    print "[ ] $head\n";
}
```

## A.11 Using the property API

Here is a description of the functions that can be used to work with properties.

**org-entry-properties** *&optional pom which* [Function]

Get all properties of the entry at point-or-marker POM.

This includes the TODO keyword, the tags, time strings for deadline, scheduled, and clocking, and any additional properties defined in the entry. The return value is an alist. Keys may occur multiple times if the property key was used several times.

POM may also be `nil`, in which case the current entry is used. If **WHICH** is `nil` or `all`, get all properties. If **WHICH** is `special` or `standard`, only get that subclass.

**org-entry-get** *pom property &optional inherit* [Function]

Get value of **PROPERTY** for entry at point-or-marker POM. By default, this only looks at properties defined locally in the entry. If **INHERIT** is non-`nil` and the entry does not have the property, then also check higher levels of the hierarchy. If **INHERIT** is the symbol `selective`, use inheritance if and only if the setting of `org-use-property-inheritance` selects **PROPERTY** for inheritance.

**org-entry-delete** *pom property* [Function]

Delete the property **PROPERTY** from entry at point-or-marker POM.

**org-entry-put** *pom property value* [Function]

Set **PROPERTY** to **VALUE** for entry at point-or-marker POM.

- org-buffer-property-keys** *&optional include-specials* [Function]  
Get all property keys in the current buffer.
- org-insert-property-drawer** [Function]  
Insert a property drawer for the current entry.
- org-entry-put-multivalued-property** *pom property &rest values* [Function]  
Set PROPERTY at point-or-marker POM to VALUES. VALUES should be a list of strings. They will be concatenated, with spaces as separators.
- org-entry-get-multivalued-property** *pom property* [Function]  
Treat the value of the property PROPERTY as a whitespace-separated list of values and return the values as a list of strings.
- org-entry-add-to-multivalued-property** *pom property value* [Function]  
Treat the value of the property PROPERTY as a whitespace-separated list of values and make sure that VALUE is in this list.
- org-entry-remove-from-multivalued-property** *pom property value* [Function]  
Treat the value of the property PROPERTY as a whitespace-separated list of values and make sure that VALUE is *not* in this list.
- org-entry-member-in-multivalued-property** *pom property value* [Function]  
Treat the value of the property PROPERTY as a whitespace-separated list of values and check if VALUE is in this list.
- org-property-allowed-value-functions** [User Option]  
Hook for functions supplying allowed values for a specific property. The functions must take a single argument, the name of the property, and return a flat list of allowed values. If ‘:ETC’ is one of the values, use the values as completion help, but allow also other values to be entered. The functions must return `nil` if they are not responsible for this property.

## A.12 Using the mapping API

Org has sophisticated mapping capabilities to find all entries satisfying certain criteria. Internally, this functionality is used to produce agenda views, but there is also an API that can be used to execute arbitrary functions for each or selected entries. The main entry point for this API is:

- org-map-entries** *func &optional match scope &rest skip* [Function]  
Call FUNC at each headline selected by MATCH in SCOPE.
- FUNC** is a function or a Lisp form. The function will be called without arguments, with the cursor positioned at the beginning of the headline. The return values of all calls to the function will be collected and returned as a list.
- The call to **FUNC** will be wrapped into a `save-excursion` form, so **FUNC** does not need to preserve point. After evaluation, the cursor will be moved to the end of the line (presumably of the headline of the processed entry) and search continues from there. Under some circumstances, this may not produce the wanted results. For example, if you have removed (e.g., archived) the current (sub)tree it could mean that the next

entry will be skipped entirely. In such cases, you can specify the position from where search should continue by making `FUNC` set the variable `org-map-continue-from` to the desired buffer position.

`MATCH` is a tags/property/todo match as it is used in the agenda match view. Only headlines that are matched by this query will be considered during the iteration. When `MATCH` is `nil` or `t`, all headlines will be visited by the iteration.

`SCOPE` determines the scope of this command. It can be any of:

<code>nil</code>	the current buffer, respecting the restriction if any
<code>tree</code>	the subtree started with the entry at point
<code>region</code>	The entries within the active region, if any
<code>file</code>	the current buffer, without restriction
<code>file-with-archives</code>	the current buffer, and any archives associated with it
<code>agenda</code>	all agenda files
<code>agenda-with-archives</code>	all agenda files with any archive files associated with them
<code>(file1 file2 ...)</code>	if this is a list, all files in the list will be scanned

The remaining args are treated as settings for the skipping facilities of the scanner. The following items can be given here:

<code>archive</code>	skip trees with the archive tag
<code>comment</code>	skip trees with the COMMENT keyword
<code>function</code> or Lisp form	will be used as value for <code>org-agenda-skip-function</code> , so whenever the function returns <code>t</code> , <code>FUNC</code> will not be called for that entry and search will continue from the point where the function leaves it

The function given to that mapping routine can really do anything you like. It can use the property API (see [Section A.11 \[Using the property API\], page 248](#)) to gather more information about the entry, or in order to change metadata in the entry. Here are a couple of functions that might be handy:

**org-todo &optional *arg*** [Function]  
Change the TODO state of the entry. See the docstring of the functions for the many possible values for the argument `ARG`.

**org-priority &optional *action*** [Function]  
Change the priority of the entry. See the docstring of this function for the possible values for `ACTION`.

**org-toggle-tag *tag* &optional *onoff*** [Function]  
Toggle the tag `TAG` in the current entry. Setting `ONOFF` to either `on` or `off` will not toggle tag, but ensure that it is either on or off.

**org-promote** [Function]  
Promote the current entry.

**org-demote**

[Function]

Demote the current entry.

Here is a simple example that will turn all entries in the current file with a tag **TOMORROW** into **TODO** entries with the keyword **UPCOMING**. Entries in comment trees and in archive trees will be ignored.

```
(org-map-entries
 '(org-todo "UPCOMING")
 "+TOMORROW" 'file 'archive 'comment)
```

The following example counts the number of entries with **TODO** keyword **WAITING**, in all agenda files.

```
(length (org-map-entries t "/+WAITING" 'agenda))
```

## Appendix B MobileOrg

*MobileOrg* is the name of the mobile companion app for Org mode, currently available for iOS and for Android. *MobileOrg* offers offline viewing and capture support for an Org mode system rooted on a “real” computer. It also allows you to record changes to existing entries. The **iOS implementation** for the *iPhone/iPod Touch/iPad* series of devices, was started by Richard Moreland and is now in the hands Sean Escriva. Android users should check out **MobileOrg Android** by Matt Jones. The two implementations are not identical but offer similar features.

This appendix describes the support Org has for creating agenda views in a format that can be displayed by *MobileOrg*, and for integrating notes captured and changes made by *MobileOrg* into the main system.

For changing tags and TODO states in MobileOrg, you should have set up the customization variables `org-todo-keywords` and `org-tag-alist` to cover all important tags and TODO keywords, even if individual files use only part of these. MobileOrg will also offer you states and tags set up with in-buffer settings, but it will understand the logistics of TODO state *sets* (see [Section 5.2.5 \[Per-file keywords\]](#), [page 49](#)) and *mutually exclusive* tags (see [Section 6.2 \[Setting tags\]](#), [page 59](#)) only for those set in these variables.

### B.1 Setting up the staging area

MobileOrg needs to interact with Emacs through a directory on a server. If you are using a public server, you should consider encrypting the files that are uploaded to the server. This can be done with Org mode 7.02 and with *MobileOrg 1.5* (iPhone version), and you need an `openssl` installation on your system. To turn on encryption, set a password in *MobileOrg* and, on the Emacs side, configure the variable `org-mobile-use-encryption`<sup>1</sup>.

The easiest way to create that directory is to use a free [Dropbox.com](#) account<sup>2</sup>. When MobileOrg first connects to your Dropbox, it will create a directory *MobileOrg* inside the Dropbox. After the directory has been created, tell Emacs about it:

```
(setq org-mobile-directory "~/Dropbox/MobileOrg")
```

Org mode has commands to put files for *MobileOrg* into that directory, and to read captured notes from there.

### B.2 Pushing to MobileOrg

This operation copies all files currently listed in `org-mobile-files` to the directory `org-mobile-directory`. By default this list contains all agenda files (as listed in `org-agenda-files`), but additional files can be included by customizing `org-mobile-files`. File names will be staged with paths relative to `org-directory`, so all files should be inside this directory<sup>3</sup>.

<sup>1</sup> If you can safely store the password in your Emacs setup, you might also want to configure `org-mobile-encryption-password`. Please read the docstring of that variable. Note that encryption will apply only to the contents of the `.org` files. The file names themselves will remain visible.

<sup>2</sup> If you cannot use Dropbox, or if your version of MobileOrg does not support it, you can use a webdav server. For more information, check out the documentation of MobileOrg and also this [FAQ entry](#).

<sup>3</sup> Symbolic links in `org-directory` need to have the same name as their targets.

The push operation also creates a special Org file `agendas.org` with all custom agenda view defined by the user<sup>4</sup>.

Finally, Org writes the file `index.org`, containing links to all other files. *MobileOrg* first reads this file from the server, and then downloads all agendas and Org files listed in it. To speed up the download, MobileOrg will only read files whose checksums<sup>5</sup> have changed.

### B.3 Pulling from MobileOrg

When *MobileOrg* synchronizes with the server, it not only pulls the Org files for viewing. It also appends captured entries and pointers to flagged and changed entries to the file `mobileorg.org` on the server. Org has a *pull* operation that integrates this information into an inbox file and operates on the pointers to flagged entries. Here is how it works:

1. Org moves all entries found in `mobileorg.org`<sup>6</sup> and appends them to the file pointed to by the variable `org-mobile-inbox-for-pull`. Each captured entry and each editing event will be a top-level entry in the inbox file.
2. After moving the entries, Org will attempt to implement the changes made in *MobileOrg*. Some changes are applied directly and without user interaction. Examples are all changes to tags, TODO state, headline and body text that can be cleanly applied. Entries that have been flagged for further action will receive a tag `:FLAGGED:`, so that they can be easily found again. When there is a problem finding an entry or applying the change, the pointer entry will remain in the inbox and will be marked with an error message. You need to later resolve these issues by hand.
3. Org will then generate an agenda view with all flagged entries. The user should then go through these entries and do whatever actions are necessary. If a note has been stored while flagging an entry in *MobileOrg*, that note will be displayed in the echo area when the cursor is on the corresponding agenda line.

?      Pressing ? in that special agenda will display the full flagging note in another window and also push it onto the kill ring. So you could use ? z C-y C-c C-c to store that flagging note as a normal note in the entry. Pressing ? twice in succession will offer to remove the `:FLAGGED:` tag along with the recorded flagging note (which is stored in a property). In this way you indicate that the intended processing for this flagged entry is finished.

If you are not able to process all flagged entries directly, you can always return to this agenda view<sup>7</sup> using `C-c a ?`.

---

<sup>4</sup> While creating the agendas, Org mode will force ID properties on all referenced entries, so that these entries can be uniquely identified if *MobileOrg* flags them for further action. If you do not want to get these properties in so many entries, you can set the variable `org-mobile-force-id-on-agenda-items` to `nil`. Org mode will then rely on outline paths, in the hope that these will be unique enough.

<sup>5</sup> Checksums are stored automatically in the file `checksums.dat`

<sup>6</sup> `mobileorg.org` will be empty after this operation.

<sup>7</sup> Note, however, that there is a subtle difference. The view created automatically by `M-x org-mobile-pull RET` is guaranteed to search all files that have been addressed by the last pull. This might include a file that is not currently in your list of agenda files. If you later use `C-c a ?` to regenerate the view, only the current agenda files will be searched.



## Appendix C History and acknowledgments

### C.1 From Carsten

Org was born in 2003, out of frustration over the user interface of the Emacs Outline mode. I was trying to organize my notes and projects, and using Emacs seemed to be the natural way to go. However, having to remember eleven different commands with two or three keys per command, only to hide and show parts of the outline tree, that seemed entirely unacceptable to me. Also, when using outlines to take notes, I constantly wanted to restructure the tree, organizing it parallel to my thoughts and plans. *Visibility cycling* and *structure editing* were originally implemented in the package `outline-magic.el`, but quickly moved to the more general `org.el`. As this environment became comfortable for project planning, the next step was adding *TODO entries*, basic *timestamps*, and *table support*. These areas highlighted the two main goals that Org still has today: to be a new, outline-based, plain text mode with innovative and intuitive editing features, and to incorporate project planning functionality directly into a notes file.

Since the first release, literally thousands of emails to me or to `emacs-orgmode@gnu.org` have provided a constant stream of bug reports, feedback, new ideas, and sometimes patches and add-on code. Many thanks to everyone who has helped to improve this package. I am trying to keep here a list of the people who had significant influence in shaping one or more aspects of Org. The list may not be complete, if I have forgotten someone, please accept my apologies and let me know.

Before I get to this list, a few special mentions are in order:

*Bastien Guerry*

Bastien has written a large number of extensions to Org (most of them integrated into the core by now), including the L<sup>A</sup>T<sub>E</sub>X exporter and the plain list parser. His support during the early days was central to the success of this project. Bastien also invented Worg, helped establishing the Web presence of Org, and sponsored hosting costs for the orgmode.org website. Bastien stepped in as maintainer of Org between 2011 and 2013, at a time when I desperately needed a break.

*Eric Schulte and Dan Davison*

Eric and Dan are jointly responsible for the Org-babel system, which turns Org into a multi-language environment for evaluating code and doing literate programming and reproducible research. This has become one of Org's killer features that define what Org is today.

*John Wiegley*

John has contributed a number of great ideas and patches directly to Org, including the attachment system (`org-attach.el`), integration with Apple Mail (`org-mac-message.el`), hierarchical dependencies of TODO items, habit tracking (`org-habits.el`), and encryption (`org-crypt.el`). Also, the capture system is really an extended copy of his great `remember.el`.

*Sebastian Rose*

Without Sebastian, the HTML/XHTML publishing of Org would be the pitiful work of an ignorant amateur. Sebastian has pushed this part of Org onto a

much higher level. He also wrote `org-info.js`, a Java script for displaying web pages derived from Org using an Info-like or a folding interface with single-key navigation.

See below for the full list of contributions! Again, please let me know what I am missing here!

## C.2 From Bastien

I (Bastien) have been maintaining Org between 2011 and 2013. This appendix would not be complete without adding a few more acknowledgements and thanks.

I am first grateful to Carsten for his trust while handing me over the maintainership of Org. His unremitting support is what really helped me getting more confident over time, with both the community and the code.

When I took over maintainership, I knew I would have to make Org more collaborative than ever, as I would have to rely on people that are more knowledgeable than I am on many parts of the code. Here is a list of the persons I could rely on, they should really be considered co-maintainers, either of the code or the community:

*Eric Schulte*

Eric is maintaining the Babel parts of Org. His reactivity here kept me away from worrying about possible bugs here and let me focus on other parts.

*Nicolas Goaziou*

Nicolas is maintaining the consistency of the deepest parts of Org. His work on `org-element.el` and `ox.el` has been outstanding, and it opened the doors for many new ideas and features. He rewrote many of the old exporters to use the new export engine, and helped with documenting this major change. More importantly (if that's possible), he has been more than reliable during all the work done for Org 8.0, and always very reactive on the mailing list.

*Achim Gratz*

Achim rewrote the building process of Org, turning some *ad hoc* tools into a flexible and conceptually clean process. He patiently coped with the many hiccups that such a change can create for users.

*Nick Dokos*

The Org mode mailing list would not be such a nice place without Nick, who patiently helped users so many times. It is impossible to overestimate such a great help, and the list would not be so active without him.

I received support from so many users that it is clearly impossible to be fair when shortlisting a few of them, but Org's history would not be complete if the ones above were not mentioned in this manual.

## C.3 List of contributions

- *Russel Adams* came up with the idea for drawers.
- *Suvayu Ali* has steadily helped on the mailing list, providing useful feedback on many features and several patches.

- *Luis Anaya* wrote `ox-man.el`.
- *Thomas Baumann* wrote `org-bbdb.el` and `org-mhe.el`.
- *Michael Brand* helped by reporting many bugs and testing many features. He also implemented the distinction between empty fields and 0-value fields in Org's spreadsheets.
- *Christophe Bataillon* created the great unicorn logo that we use on the Org mode website.
- *Alex Bochanek* provided a patch for rounding timestamps.
- *Jan Böcker* wrote `org-docview.el`.
- *Brad Bozarth* showed how to pull RSS feed data into Org mode files.
- *Tom Breton* wrote `org-choose.el`.
- *Charles Cave*'s suggestion sparked the implementation of templates for Remember, which are now templates for capture.
- *Pavel Chalmoviansky* influenced the agenda treatment of items with specified time.
- *Gregory Chernov* patched support for Lisp forms into table calculations and improved XEmacs compatibility, in particular by porting `nouline.el` to XEmacs.
- *Sacha Chua* suggested copying some linking code from Planner, and helped make Org popular through her blog.
- *Toby S. Cubitt* contributed to the code for clock formats.
- *Baoqiu Cui* contributed the first DocBook exporter. In Org 8.0, we go a different route: you can now export to Texinfo and export the `.texi` file to DocBook using `makeinfo`.
- *Eddward DeVilla* proposed and tested checkbox statistics. He also came up with the idea of properties, and that there should be an API for them.
- *Nick Dokos* tracked down several nasty bugs.
- *Kees Dullemond* used to edit projects lists directly in HTML and so inspired some of the early development, including HTML export. He also asked for a way to narrow wide table columns.
- *Jason Dunsmore* has been maintaining the Org-Mode server at Rackspace for several years now. He also sponsored the hosting costs until Rackspace started to host us for free.
- *Thomas S. Dye* contributed documentation on Worg and helped integrating the Org-Babel documentation into the manual.
- *Christian Egli* converted the documentation into Texinfo format, inspired the agenda, patched CSS formatting into the HTML exporter, and wrote `org-taskjuggler.el`, which has been rewritten by Nicolas Goaziou as `ox-taskjuggler.el` for Org 8.0.
- *David Emery* provided a patch for custom CSS support in exported HTML agendas.
- *Sean Escriva* took over MobileOrg development on the iPhone platform.
- *Nic Ferrier* contributed mailcap and XOXO support.
- *Miguel A. Figueroa-Villanueva* implemented hierarchical checkboxes.
- *John Foerch* figured out how to make incremental search show context around a match in a hidden outline tree.

- *Raimar Finken* wrote `org-git-line.el`.
- *Mikael Fornius* works as a mailing list moderator.
- *Austin Frank* works as a mailing list moderator.
- *Eric Fraga* drove the development of BEAMER export with ideas and testing.
- *Barry Gidden* did proofreading the manual in preparation for the book publication through Network Theory Ltd.
- *Niels Giesen* had the idea to automatically archive DONE trees.
- *Nicolas Goaziou* rewrote much of the plain list code. He also wrote `org-element.el` and `org-export.el`, which was a huge step forward in implementing a clean framework for Org exporters.
- *Kai Grossjohann* pointed out key-binding conflicts with other packages.
- *Brian Gough* of Network Theory Ltd publishes the Org mode manual as a book.
- *Bernt Hansen* has driven much of the support for auto-repeating tasks, task state change logging, and the clocktable. His clear explanations have been critical when we started to adopt the Git version control system.
- *Manuel Hermenegildo* has contributed various ideas, small fixes and patches.
- *Phil Jackson* wrote `org-irc.el`.
- *Scott Jaderholm* proposed footnotes, control over whitespace between folded entries, and column view for properties.
- *Matt Jones* wrote *MobileOrg Android*.
- *Tokuya Kameshima* wrote `org-wl.el` and `org-mew.el`.
- *Jonathan Leech-Pepin* wrote `ox-texinfo.el`.
- *Shidai Liu* ("Leo") asked for embedded L<sup>A</sup>T<sub>E</sub>X and tested it. He also provided frequent feedback and some patches.
- *Matt Lundin* has proposed last-row references for table formulas and named invisible anchors. He has also worked a lot on the FAQ.
- *David Maus* wrote `org-atom.el`, maintains the issues file for Org, and is a prolific contributor on the mailing list with competent replies, small fixes and patches.
- *Jason F. McBrayer* suggested agenda export to CSV format.
- *Max Mikhanosha* came up with the idea of refiling and sticky agendas.
- *Dmitri Minaev* sent a patch to set priority limits on a per-file basis.
- *Stefan Monnier* provided a patch to keep the Emacs-Lisp compiler happy.
- *Richard Moreland* wrote *MobileOrg* for the iPhone.
- *Rick Moynihan* proposed allowing multiple TODO sequences in a file and being able to quickly restrict the agenda to a subtree.
- *Todd Neal* provided patches for links to Info files and Elisp forms.
- *Greg Newman* refreshed the unicorn logo into its current form.
- *Tim O'Callaghan* suggested in-file links, search options for general file links, and TAGS.
- *Osamu Okano* wrote `orgcard2ref.pl`, a Perl program to create a text version of the reference card.
- *Takeshi Okano* translated the manual and David O'Toole's tutorial into Japanese.

- *Oliver Oppitz* suggested multi-state TODO items.
- *Scott Otterson* sparked the introduction of descriptive text for links, among other things.
- *Pete Phillips* helped during the development of the TAGS feature, and provided frequent feedback.
- *Francesco Pizzolante* provided patches that helped speeding up the agenda generation.
- *Martin Pohlack* provided the code snippet to bundle character insertion into bundles of 20 for undo.
- *Rackspace.com* is hosting our website for free. Thank you Rackspace!
- *T.V. Raman* reported bugs and suggested improvements.
- *Matthias Rempé* (Oelde) provided ideas, Windows support, and quality control.
- *Paul Rivier* provided the basic implementation of named footnotes. He also acted as mailing list moderator for some time.
- *Kevin Rogers* contributed code to access VM files on remote hosts.
- *Frank Ruell* solved the mystery of the `keymapp nil` bug, a conflict with `allout.el`.
- *Jason Riedy* generalized the send-receive mechanism for Orgtbl tables with extensive patches.
- *Philip Rooke* created the Org reference card, provided lots of feedback, developed and applied standards to the Org documentation.
- *Christian Schlauer* proposed angular brackets around links, among other things.
- *Christopher Schmidt* reworked `orgstruct-mode` so that users can enjoy folding in non-org buffers by using Org headlines in comments.
- *Paul Sexton* wrote `org-ctags.el`.
- Linking to VM/BBDB/Gnus was first inspired by *Tom Shannon's* `organizer-mode.el`.
- *Ilya Shlyakhter* proposed the Archive Sibling, line numbering in literal examples, and remote highlighting for referenced code lines.
- *Stathis Sideris* wrote the `ditaa.jar` ASCII to PNG converter that is now packaged into Org's `contrib` directory.
- *Daniel Sinder* came up with the idea of internal archiving by locking subtrees.
- *Dale Smith* proposed link abbreviations.
- *James TD Smith* has contributed a large number of patches for useful tweaks and features.
- *Adam Spiers* asked for global linking commands, inspired the link extension system, added support for mairix, and proposed the mapping API.
- *Ulf Stegemann* created the table to translate special symbols to HTML,  $\text{\LaTeX}$ , UTF-8, Latin-1 and ASCII.
- *Andy Stewart* contributed code to `org-w3m.el`, to copy HTML content with links transformation to Org syntax.
- *David O'Toole* wrote `org-publish.el` and drafted the manual chapter about publishing.
- *Jambunathan K* contributed the ODT exporter and rewrote the HTML exporter.

- *Sebastien Vauban* reported many issues with L<sup>A</sup>T<sub>E</sub>X and BEAMER export and enabled source code highlighting in Gnus.
- *Stefan Vollmar* organized a video-recorded talk at the Max-Planck-Institute for Neurology. He also inspired the creation of a concept index for HTML export.
- *Jürgen Vollmer* contributed code generating the table of contents in HTML output.
- *Samuel Wales* has provided important feedback and bug reports.
- *Chris Wallace* provided a patch implementing the ‘QUOTE’ keyword.
- *David Wainberg* suggested archiving, and improvements to the linking system.
- *Carsten Wimmer* suggested some changes and helped fix a bug in linking to Gnus.
- *Roland Winkler* requested additional key bindings to make Org work on a tty.
- *Piotr Zielinski* wrote `org-mouse.el`, proposed agenda blocks and contributed various ideas and code snippets.
- *Marco Wahl* wrote `org-eww.el`.

## Appendix D GNU Free Documentation License

Version 1.3, 3 November 2008

Copyright © 2000, 2001, 2002, 2007, 2008, 2013, 2014 Free Software Foundation, Inc.  
<http://fsf.org/>

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

### 0. PREAMBLE

The purpose of this License is to make a manual, textbook, or other functional and useful document *free* in the sense of freedom: to assure everyone the effective freedom to copy and redistribute it, with or without modifying it, either commercially or non-commercially. Secondly, this License preserves for the author and publisher a way to get credit for their work, while not being considered responsible for modifications made by others.

This License is a kind of “copyleft”, which means that derivative works of the document must themselves be free in the same sense. It complements the GNU General Public License, which is a copyleft license designed for free software.

We have designed this License in order to use it for manuals for free software, because free software needs free documentation: a free program should come with manuals providing the same freedoms that the software does. But this License is not limited to software manuals; it can be used for any textual work, regardless of subject matter or whether it is published as a printed book. We recommend this License principally for works whose purpose is instruction or reference.

### 1. APPLICABILITY AND DEFINITIONS

This License applies to any manual or other work, in any medium, that contains a notice placed by the copyright holder saying it can be distributed under the terms of this License. Such a notice grants a world-wide, royalty-free license, unlimited in duration, to use that work under the conditions stated herein. The “Document”, below, refers to any such manual or work. Any member of the public is a licensee, and is addressed as “you”. You accept the license if you copy, modify or distribute the work in a way requiring permission under copyright law.

A “Modified Version” of the Document means any work containing the Document or a portion of it, either copied verbatim, or with modifications and/or translated into another language.

A “Secondary Section” is a named appendix or a front-matter section of the Document that deals exclusively with the relationship of the publishers or authors of the Document to the Document’s overall subject (or to related matters) and contains nothing that could fall directly within that overall subject. (Thus, if the Document is in part a textbook of mathematics, a Secondary Section may not explain any mathematics.) The relationship could be a matter of historical connection with the subject or with related matters, or of legal, commercial, philosophical, ethical or political position regarding them.

The “Invariant Sections” are certain Secondary Sections whose titles are designated, as being those of Invariant Sections, in the notice that says that the Document is released

under this License. If a section does not fit the above definition of Secondary then it is not allowed to be designated as Invariant. The Document may contain zero Invariant Sections. If the Document does not identify any Invariant Sections then there are none.

The “Cover Texts” are certain short passages of text that are listed, as Front-Cover Texts or Back-Cover Texts, in the notice that says that the Document is released under this License. A Front-Cover Text may be at most 5 words, and a Back-Cover Text may be at most 25 words.

A “Transparent” copy of the Document means a machine-readable copy, represented in a format whose specification is available to the general public, that is suitable for revising the document straightforwardly with generic text editors or (for images composed of pixels) generic paint programs or (for drawings) some widely available drawing editor, and that is suitable for input to text formatters or for automatic translation to a variety of formats suitable for input to text formatters. A copy made in an otherwise Transparent file format whose markup, or absence of markup, has been arranged to thwart or discourage subsequent modification by readers is not Transparent. An image format is not Transparent if used for any substantial amount of text. A copy that is not “Transparent” is called “Opaque”.

Examples of suitable formats for Transparent copies include plain ASCII without markup, Texinfo input format, LaTeX input format, SGML or XML using a publicly available DTD, and standard-conforming simple HTML, PostScript or PDF designed for human modification. Examples of transparent image formats include PNG, XCF and JPG. Opaque formats include proprietary formats that can be read and edited only by proprietary word processors, SGML or XML for which the DTD and/or processing tools are not generally available, and the machine-generated HTML, PostScript or PDF produced by some word processors for output purposes only.

The “Title Page” means, for a printed book, the title page itself, plus such following pages as are needed to hold, legibly, the material this License requires to appear in the title page. For works in formats which do not have any title page as such, “Title Page” means the text near the most prominent appearance of the work’s title, preceding the beginning of the body of the text.

The “publisher” means any person or entity that distributes copies of the Document to the public.

A section “Entitled XYZ” means a named subunit of the Document whose title either is precisely XYZ or contains XYZ in parentheses following text that translates XYZ in another language. (Here XYZ stands for a specific section name mentioned below, such as “Acknowledgements”, “Dedications”, “Endorsements”, or “History”.) To “Preserve the Title” of such a section when you modify the Document means that it remains a section “Entitled XYZ” according to this definition.

The Document may include Warranty Disclaimers next to the notice which states that this License applies to the Document. These Warranty Disclaimers are considered to be included by reference in this License, but only as regards disclaiming warranties: any other implication that these Warranty Disclaimers may have is void and has no effect on the meaning of this License.

## 2. VERBATIM COPYING



You may copy and distribute the Document in any medium, either commercially or noncommercially, provided that this License, the copyright notices, and the license notice saying this License applies to the Document are reproduced in all copies, and that you add no other conditions whatsoever to those of this License. You may not use technical measures to obstruct or control the reading or further copying of the copies you make or distribute. However, you may accept compensation in exchange for copies. If you distribute a large enough number of copies you must also follow the conditions in section 3.

You may also lend copies, under the same conditions stated above, and you may publicly display copies.

### 3. COPYING IN QUANTITY

If you publish printed copies (or copies in media that commonly have printed covers) of the Document, numbering more than 100, and the Document's license notice requires Cover Texts, you must enclose the copies in covers that carry, clearly and legibly, all these Cover Texts: Front-Cover Texts on the front cover, and Back-Cover Texts on the back cover. Both covers must also clearly and legibly identify you as the publisher of these copies. The front cover must present the full title with all words of the title equally prominent and visible. You may add other material on the covers in addition. Copying with changes limited to the covers, as long as they preserve the title of the Document and satisfy these conditions, can be treated as verbatim copying in other respects.

If the required texts for either cover are too voluminous to fit legibly, you should put the first ones listed (as many as fit reasonably) on the actual cover, and continue the rest onto adjacent pages.

If you publish or distribute Opaque copies of the Document numbering more than 100, you must either include a machine-readable Transparent copy along with each Opaque copy, or state in or with each Opaque copy a computer-network location from which the general network-using public has access to download using public-standard network protocols a complete Transparent copy of the Document, free of added material. If you use the latter option, you must take reasonably prudent steps, when you begin distribution of Opaque copies in quantity, to ensure that this Transparent copy will remain thus accessible at the stated location until at least one year after the last time you distribute an Opaque copy (directly or through your agents or retailers) of that edition to the public.

It is requested, but not required, that you contact the authors of the Document well before redistributing any large number of copies, to give them a chance to provide you with an updated version of the Document.

### 4. MODIFICATIONS

You may copy and distribute a Modified Version of the Document under the conditions of sections 2 and 3 above, provided that you release the Modified Version under precisely this License, with the Modified Version filling the role of the Document, thus licensing distribution and modification of the Modified Version to whoever possesses a copy of it. In addition, you must do these things in the Modified Version:

- A. Use in the Title Page (and on the covers, if any) a title distinct from that of the Document, and from those of previous versions (which should, if there were any,

- be listed in the History section of the Document). You may use the same title as a previous version if the original publisher of that version gives permission.
- B. List on the Title Page, as authors, one or more persons or entities responsible for authorship of the modifications in the Modified Version, together with at least five of the principal authors of the Document (all of its principal authors, if it has fewer than five), unless they release you from this requirement.
  - C. State on the Title page the name of the publisher of the Modified Version, as the publisher.
  - D. Preserve all the copyright notices of the Document.
  - E. Add an appropriate copyright notice for your modifications adjacent to the other copyright notices.
  - F. Include, immediately after the copyright notices, a license notice giving the public permission to use the Modified Version under the terms of this License, in the form shown in the Addendum below.
  - G. Preserve in that license notice the full lists of Invariant Sections and required Cover Texts given in the Document's license notice.
  - H. Include an unaltered copy of this License.
  - I. Preserve the section Entitled "History", Preserve its Title, and add to it an item stating at least the title, year, new authors, and publisher of the Modified Version as given on the Title Page. If there is no section Entitled "History" in the Document, create one stating the title, year, authors, and publisher of the Document as given on its Title Page, then add an item describing the Modified Version as stated in the previous sentence.
  - J. Preserve the network location, if any, given in the Document for public access to a Transparent copy of the Document, and likewise the network locations given in the Document for previous versions it was based on. These may be placed in the "History" section. You may omit a network location for a work that was published at least four years before the Document itself, or if the original publisher of the version it refers to gives permission.
  - K. For any section Entitled "Acknowledgements" or "Dedications", Preserve the Title of the section, and preserve in the section all the substance and tone of each of the contributor acknowledgements and/or dedications given therein.
  - L. Preserve all the Invariant Sections of the Document, unaltered in their text and in their titles. Section numbers or the equivalent are not considered part of the section titles.
  - M. Delete any section Entitled "Endorsements". Such a section may not be included in the Modified Version.
  - N. Do not retitle any existing section to be Entitled "Endorsements" or to conflict in title with any Invariant Section.
  - O. Preserve any Warranty Disclaimers.

If the Modified Version includes new front-matter sections or appendices that qualify as Secondary Sections and contain no material copied from the Document, you may at your option designate some or all of these sections as invariant. To do this, add their

titles to the list of Invariant Sections in the Modified Version's license notice. These titles must be distinct from any other section titles.

You may add a section Entitled "Endorsements", provided it contains nothing but endorsements of your Modified Version by various parties—for example, statements of peer review or that the text has been approved by an organization as the authoritative definition of a standard.

You may add a passage of up to five words as a Front-Cover Text, and a passage of up to 25 words as a Back-Cover Text, to the end of the list of Cover Texts in the Modified Version. Only one passage of Front-Cover Text and one of Back-Cover Text may be added by (or through arrangements made by) any one entity. If the Document already includes a cover text for the same cover, previously added by you or by arrangement made by the same entity you are acting on behalf of, you may not add another; but you may replace the old one, on explicit permission from the previous publisher that added the old one.

The author(s) and publisher(s) of the Document do not by this License give permission to use their names for publicity for or to assert or imply endorsement of any Modified Version.

## 5. COMBINING DOCUMENTS

You may combine the Document with other documents released under this License, under the terms defined in section 4 above for modified versions, provided that you include in the combination all of the Invariant Sections of all of the original documents, unmodified, and list them all as Invariant Sections of your combined work in its license notice, and that you preserve all their Warranty Disclaimers.

The combined work need only contain one copy of this License, and multiple identical Invariant Sections may be replaced with a single copy. If there are multiple Invariant Sections with the same name but different contents, make the title of each such section unique by adding at the end of it, in parentheses, the name of the original author or publisher of that section if known, or else a unique number. Make the same adjustment to the section titles in the list of Invariant Sections in the license notice of the combined work.

In the combination, you must combine any sections Entitled "History" in the various original documents, forming one section Entitled "History"; likewise combine any sections Entitled "Acknowledgements", and any sections Entitled "Dedications". You must delete all sections Entitled "Endorsements."

## 6. COLLECTIONS OF DOCUMENTS

You may make a collection consisting of the Document and other documents released under this License, and replace the individual copies of this License in the various documents with a single copy that is included in the collection, provided that you follow the rules of this License for verbatim copying of each of the documents in all other respects.

You may extract a single document from such a collection, and distribute it individually under this License, provided you insert a copy of this License into the extracted document, and follow this License in all other respects regarding verbatim copying of that document.

## 7. AGGREGATION WITH INDEPENDENT WORKS

A compilation of the Document or its derivatives with other separate and independent documents or works, in or on a volume of a storage or distribution medium, is called an “aggregate” if the copyright resulting from the compilation is not used to limit the legal rights of the compilation’s users beyond what the individual works permit. When the Document is included in an aggregate, this License does not apply to the other works in the aggregate which are not themselves derivative works of the Document.

If the Cover Text requirement of section 3 is applicable to these copies of the Document, then if the Document is less than one half of the entire aggregate, the Document’s Cover Texts may be placed on covers that bracket the Document within the aggregate, or the electronic equivalent of covers if the Document is in electronic form. Otherwise they must appear on printed covers that bracket the whole aggregate.

## 8. TRANSLATION

Translation is considered a kind of modification, so you may distribute translations of the Document under the terms of section 4. Replacing Invariant Sections with translations requires special permission from their copyright holders, but you may include translations of some or all Invariant Sections in addition to the original versions of these Invariant Sections. You may include a translation of this License, and all the license notices in the Document, and any Warranty Disclaimers, provided that you also include the original English version of this License and the original versions of those notices and disclaimers. In case of a disagreement between the translation and the original version of this License or a notice or disclaimer, the original version will prevail.

If a section in the Document is Entitled “Acknowledgements”, “Dedications”, or “History”, the requirement (section 4) to Preserve its Title (section 1) will typically require changing the actual title.

## 9. TERMINATION

You may not copy, modify, sublicense, or distribute the Document except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, or distribute it is void, and will automatically terminate your rights under this License.

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, receipt of a copy of some or all of the same material does not give you any rights to use it.

## 10. FUTURE REVISIONS OF THIS LICENSE

The Free Software Foundation may publish new, revised versions of the GNU Free Documentation License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns. See <http://www.gnu.org/copyleft/>.

Each version of the License is given a distinguishing version number. If the Document specifies that a particular numbered version of this License “or any later version” applies to it, you have the option of following the terms and conditions either of that specified version or of any later version that has been published (not as a draft) by the Free Software Foundation. If the Document does not specify a version number of this License, you may choose any version ever published (not as a draft) by the Free Software Foundation. If the Document specifies that a proxy can decide which future versions of this License can be used, that proxy’s public statement of acceptance of a version permanently authorizes you to choose that version for the Document.

## 11. RELICENSING

“Massive Multiauthor Collaboration Site” (or “MMC Site”) means any World Wide Web server that publishes copyrightable works and also provides prominent facilities for anybody to edit those works. A public wiki that anybody can edit is an example of such a server. A “Massive Multiauthor Collaboration” (or “MMC”) contained in the site means any set of copyrightable works thus published on the MMC site.

“CC-BY-SA” means the Creative Commons Attribution-Share Alike 3.0 license published by Creative Commons Corporation, a not-for-profit corporation with a principal place of business in San Francisco, California, as well as future copyleft versions of that license published by that same organization.

“Incorporate” means to publish or republish a Document, in whole or in part, as part of another Document.

An MMC is “eligible for relicensing” if it is licensed under this License, and if all works that were first published under this License somewhere other than this MMC, and subsequently incorporated in whole or in part into the MMC, (1) had no cover texts or invariant sections, and (2) were thus incorporated prior to November 1, 2008.

The operator of an MMC Site may republish an MMC contained in the site under CC-BY-SA on the same site at any time before August 1, 2009, provided the MMC is eligible for relicensing.

## ADDENDUM: How to use this License for your documents

To use this License in a document you have written, include a copy of the License in the document and put the following copyright and license notices just after the title page:

```
Copyright (C)  year  your name.
Permission is granted to copy, distribute and/or modify this document
under the terms of the GNU Free Documentation License, Version 1.3
or any later version published by the Free Software Foundation;
with no Invariant Sections, no Front-Cover Texts, and no Back-Cover
Texts.  A copy of the license is included in the section entitled ``GNU
Free Documentation License''.
```

If you have Invariant Sections, Front-Cover Texts and Back-Cover Texts, replace the “with...Texts.” line with this:

```
with the Invariant Sections being list their titles, with
the Front-Cover Texts being list, and with the Back-Cover Texts
being list.
```

If you have Invariant Sections without Cover Texts, or some other combination of the three, merge those two alternatives to suit the situation.

If your document contains nontrivial examples of program code, we recommend releasing these examples in parallel under your choice of free software license, such as the GNU General Public License, to permit their use in free software.

# Concept index

## #

#+ARCHIVE .....	98
#+ASCII .....	143
#+ATTR_ASCII .....	143
#+ATTR_BEAMER .....	146
#+ATTR_HTML .....	150, 151
#+ATTR_LATEX, in example blocks .....	160
#+ATTR_LATEX, in horizontal rules .....	161
#+ATTR_LATEX, in images .....	158
#+ATTR_LATEX, in plain lists .....	159
#+ATTR_LATEX, in source blocks .....	159
#+ATTR_LATEX, in special blocks .....	160
#+ATTR_LATEX, in tables .....	156
#+ATTR_ODT .....	164, 165, 166, 170
#+ATTR_TEXINFO, in images .....	177
#+ATTR_TEXINFO, in plain lists .....	176
#+ATTR_TEXINFO, in special blocks .....	177
#+ATTR_TEXINFO, in tables .....	176
#+AUTHOR .....	136
#+BEAMER .....	145
#+BEAMER_FONT_THEME .....	144
#+BEAMER_HEADER .....	144
#+BEAMER_INNER_THEME .....	144
#+BEAMER_OUTER_THEME .....	144
#+BEAMER_THEME .....	144
#+BEGIN, clocktable .....	83
#+BEGIN, columnview .....	71
#+BEGIN:dynamic block .....	244
#+BEGIN_CENTER .....	128
#+BEGIN_COMMENT .....	142
#+BEGIN_EXAMPLE .....	129
#+BEGIN_EXPORT ascii .....	143
#+BEGIN_EXPORT beamer .....	145
#+BEGIN_EXPORT html .....	149, 150
#+BEGIN_EXPORT latex .....	156
#+BEGIN_EXPORT texinfo .....	176
#+BEGIN_JUSTIFYLEFT .....	143
#+BEGIN_JUSTIFYRIGHT .....	143
#+BEGIN_QUOTE .....	128
#+BEGIN_SRC .....	130, 194
#+BEGIN_VERSE .....	128
#+BIND .....	139
#+CALL .....	198
#+CAPTION .....	129, 150, 151
#+CATEGORY .....	109
#+CINDEX .....	176
#+COLUMNS .....	68
#+CONSTANTS .....	26
#+CREATOR .....	136
#+DATE .....	136
#+DESCRIPTION (Beamer) .....	144
#+DESCRIPTION (HTML) .....	147
#+DESCRIPTION (L <sup>A</sup> T <sub>E</sub> X) .....	155
#+DESCRIPTION (ODT) .....	162
#+EMAIL .....	136
#+EXCLUDE_TAGS .....	137
#+FILETAGS .....	59
#+FINDEX .....	176
#+HEADER: .....	202
#+HEADERS: .....	202
#+HTML .....	149
#+HTML_CONTAINER .....	147
#+HTML_DOCTYPE .....	147
#+HTML_HEAD .....	148, 153
#+HTML_HEAD_EXTRA .....	148, 153
#+HTML_INCLUDE_STYLE .....	153
#+HTML_LINK_HOME .....	147
#+HTML_LINK_UP .....	147
#+HTML_MATHJAX .....	147
#+INCLUDE .....	140
#+INDEX .....	190
#+INFOJS_OPT .....	153
#+KEYWORDS (Beamer) .....	144
#+KEYWORDS (HTML) .....	148
#+KEYWORDS (L <sup>A</sup> T <sub>E</sub> X) .....	155
#+KEYWORDS (ODT) .....	162
#+KINDEX .....	176
#+LANGUAGE .....	137
#+LATEX .....	156
#+LATEX_CLASS .....	155, 156
#+LATEX_CLASS_OPTIONS .....	155, 156
#+LATEX_COMPILER .....	155
#+LATEX_HEADER .....	155, 156
#+LATEX_HEADER (HTML) .....	148
#+LATEX_HEADER_EXTRA .....	155, 156
#+LINK .....	44
#+MACRO .....	141
#+NAME .....	38, 129, 194
#+NAME, for table .....	26
#+ODT_STYLES_FILE .....	163
#+OPTIONS .....	136
#+ORGLST .....	243
#+ORGTBL .....	240
#+ORGTBL, SEND .....	241
#+PINDEX .....	176
#+PLOT .....	36
#+PRIORITIES .....	55
#+PROPERTY .....	65
#+RESULTS .....	198
#+SELECT_TAGS .....	137
#+SEQ_TODO .....	49
#+SETUPFILE .....	136, 227
#+STARTUP .....	227
#+SUBAUTHOR .....	173, 174
#+SUBTILE (HTML) .....	148
#+SUBTILE (ASCII) .....	142
#+SUBTILE (Beamer) .....	144
#+SUBTILE (L <sup>A</sup> T <sub>E</sub> X) .....	155

#+SUBTITLE (Texinfo)..... 173  
 #+TAGS..... 60  
 #+TBLFM..... 29, 33, 229  
 #+TBLFM line, multiple..... 33  
 #+TBLFM, switching..... 33  
 #+TEXINFO..... 176  
 #+TEXINFO\_CLASS..... 174, 175  
 #+TEXINFO\_DIR\_CATEGORY..... 174, 175  
 #+TEXINFO\_DIR\_DESC..... 174, 175  
 #+TEXINFO\_DIR\_TITLE..... 174, 175  
 #+TEXINFO\_FILENAME..... 174  
 #+TEXINFO\_HEADER..... 174  
 #+TEXINFO\_POST\_HEADER..... 174  
 #+TEXINFO\_PRINTED\_TITLE..... 174  
 #+TINDEX..... 176  
 #+TITLE..... 137  
 #+TOC..... 139  
 #+TODO..... 49  
 #+TYP\_TODO..... 49  
 #+VINDEK..... 176

:

:cache, src header argument..... 200, 214  
 :colnames, src header argument..... 216  
 :comments, src header argument..... 211  
 :dir, src header argument..... 209  
 :epilogue, src header argument..... 219  
 :eval, src header argument..... 217  
 :exports, src header argument..... 196, 200, 210  
 :file, src header argument..... 209  
 :file-ext, src header argument..... 209  
 :hlines, src header argument..... 215  
 :mkdirp, src header argument..... 211  
 :no-expand, src header argument..... 212  
 :noweb, src header argument..... 200, 212  
 :noweb-ref, src header argument..... 213  
 :noweb-sep, src header argument..... 214  
 :output-dir, src header argument..... 209  
 :padline, src header argument..... 211  
 :post, src header argument..... 218  
 :prologue, src header argument..... 219  
 :results, src header argument..... 200, 207, 220  
 :rownames, src header argument..... 217  
 :sep, src header argument..... 215  
 :session, src header argument..... 200, 212  
 :shebang, src header argument..... 217  
 :tangle, src header argument..... 197, 211  
 :tangle-mode, src header argument..... 217  
 :var, src header argument..... 203  
 :wrap, src header argument..... 218

## A

abbreviation, links..... 44  
 abstract, in L<sup>A</sup>T<sub>E</sub>X export..... 160  
 acknowledgments..... 254  
 action, for publishing..... 184

activation..... 3  
 active region..... 11, 21, 162  
 add-on packages..... 237  
 add-ons, context-sensitive commands..... 239  
 agenda..... 102  
 agenda dispatcher..... 101  
 agenda files..... 100  
 agenda files, removing buffers..... 121  
 agenda views..... 100  
 agenda views, custom..... 121  
 agenda views, exporting..... 121, 124, 125  
 agenda views, main example..... 122  
 agenda views, optimization..... 246  
 agenda views, user-defined..... 245  
 agenda\*, as an agenda views..... 122  
 agenda, as an agenda views..... 122  
 agenda, column view..... 126  
 agenda, pipe..... 247  
 agenda, sticky..... 102  
 agenda, with block views..... 123  
 align, STARTUP keyword..... 228  
 alignment in tables..... 22  
 anniversaries, from BBDB..... 104  
 API, for mapping..... 249  
 API, for properties..... 72, 248  
 appointment..... 73, 104  
 appointment reminders..... 104  
 appt.el..... 104  
 archive locations..... 98  
 Archives mode..... 115  
 archiving..... 97  
 ASCII export..... 142  
 Atom feeds..... 96  
 attachments..... 95  
 author..... 3  
 author, macro..... 141  
 autoload..... 3

## B

babel, languages..... 199  
 babel, library of..... 199  
 backtrace of an error..... 4  
 BBDB links..... 39  
 BBDB, anniversaries..... 104  
 Beamer export..... 143  
 block agenda..... 123  
 blocking, of checkboxes..... 57  
 blocks, folding..... 16  
 bold text, markup rules..... 128  
 Boolean logic, for tag/property searches..... 106  
 bug reports..... 3

## C

C-c C-c, overview..... 230  
 calc package..... 24  
 calc.el..... 233



- calculations, in tables . . . . . 21, 24
- calendar commands, from agenda . . . . . 120
- calendar integration . . . . . 103
- calendar, for selecting date . . . . . 76
- capture . . . . . 89
- capturing, from agenda . . . . . 119
- category . . . . . 109
- category filtering, in agenda . . . . . 111
- category, require for tags/property match . . . . . 106
- `cdlatex.el` . . . . . 233
- `CDIATEX` . . . . . 134
- center blocks . . . . . 128
- center image (`LaTeX` export) . . . . . 159
- checkbox blocking . . . . . 57
- checkbox statistics . . . . . 57
- checkboxes . . . . . 56
- checkboxes and TODO dependencies . . . . . 51
- children, subtree visibility state . . . . . 6
- clean outline view . . . . . 230
- clocking time . . . . . 80
- clocktable, dynamic block . . . . . 83
- code block, batch execution . . . . . 222
- code block, editing . . . . . 195
- code block, evaluating . . . . . 198
- code block, exporting . . . . . 196
- code block, extracting source code . . . . . 196
- code block, header arguments . . . . . 200
- code block, key bindings . . . . . 221
- code block, languages . . . . . 199
- code block, library . . . . . 199
- code block, noweb reference . . . . . 221
- code block, results of evaluation . . . . . 219
- code block, structure . . . . . 194
- code line references, markup rules . . . . . 129
- code text, markup rules . . . . . 128
- column formula . . . . . 30
- column view, for properties . . . . . 68
- column view, in agenda . . . . . 126
- column, of field coordinates . . . . . 26
- commands, in agenda buffer . . . . . 113
- comment lines . . . . . 142
- completion, of dictionary words . . . . . 224
- completion, of file names . . . . . 42
- completion, of link abbreviations . . . . . 224
- completion, of links . . . . . 42
- completion, of option keywords . . . . . 49, 224
- completion, of property keys . . . . . 224
- completion, of tags . . . . . 59, 224
- completion, of `TEX` symbols . . . . . 224
- completion, of TODO keywords . . . . . 47, 224
- constants, in calculations . . . . . 26
- `constants.el` . . . . . 233
- `constcgs`, STARTUP keyword . . . . . 229
- `constSI`, STARTUP keyword . . . . . 229
- `content`, STARTUP keyword . . . . . 8, 227
- contents, global visibility state . . . . . 7
- context-sensitive commands, hooks . . . . . 239
- continuous clocking . . . . . 86

- convert . . . . . 168
- converter . . . . . 168
- coordinates, of field . . . . . 26
- copying notes . . . . . 97
- copying, of subtrees . . . . . 9
- countdown timer . . . . . 87
- creating timestamps . . . . . 74
- CSS, for HTML export . . . . . 152
- `CUA.el` . . . . . 234
- custom agenda views . . . . . 121
- custom date/time format . . . . . 77
- custom search strings . . . . . 45
- customization . . . . . 226
- `customtime`, STARTUP keyword . . . . . 229
- cutting, of subtrees . . . . . 9
- cycling, in plain lists . . . . . 13
- cycling, of agenda files . . . . . 100
- cycling, of TODO states . . . . . 46
- cycling, visibility . . . . . 6

## D

- daily agenda . . . . . 102
- dash, special symbol . . . . . 132
- date format, custom . . . . . 77
- date range . . . . . 74
- date stamp . . . . . 73
- date stamps . . . . . 73
- date tree . . . . . 89
- date, macro . . . . . 141
- date, reading in minibuffer . . . . . 75
- dates . . . . . 73
- Davison, Dan . . . . . 194
- DEADLINE keyword . . . . . 77
- deadlines . . . . . 73
- debugging, of table formulas . . . . . 33
- demotion, of subtrees . . . . . 9
- dependencies, of TODO states . . . . . 50
- diary entries, creating from agenda . . . . . 120
- diary integration . . . . . 103
- dictionary word completion . . . . . 224
- directories, for publishing . . . . . 183
- dispatching agenda commands . . . . . 101
- display changing, in agenda . . . . . 114
- doc, docx, rtf . . . . . 168
- document structure . . . . . 6
- document title . . . . . 137
- Dominik, Carsten . . . . . 233
- DONE, final TODO keyword . . . . . 49
- dragging, agenda lines . . . . . 119
- drawer, for properties . . . . . 64
- drawer, for state change recording . . . . . 52
- drawers . . . . . 15
- Duration, computing . . . . . 29
- `dvipng` . . . . . 151, 167
- `dvisvgm` . . . . . 151, 167
- dynamic blocks . . . . . 244
- dynamic indentation . . . . . 230

**E**

<b>ecomplete.el</b> .....	234
editing tables .....	19
editing, of table formulas .....	31
edits, catching invisible .....	8
effort estimates .....	86
effort filtering, in agenda .....	111
Elisp links .....	39
ellipsis, special symbol .....	132
ELPA .....	3
emacsserver .....	96
email, macro .....	141
embedding images in ODT .....	165
<b>entitiesplain</b> , STARTUP keyword .....	229
<b>entitiespretty</b> , STARTUP keyword ....	132, 229
escaping characters .....	131
evaluate time range .....	75
<b>even</b> , STARTUP keyword .....	228
example blocks, in L <sup>A</sup> T <sub>E</sub> X export .....	160
export back-end .....	135
export back-ends, built-in .....	179
Export, dispatcher .....	135
export, OpenDocument .....	162
Export, settings .....	136
Export, writing back-ends .....	238
exporting .....	135
exporting agenda views .....	121, 125
exporting, not .....	142
extended TODO keywords .....	47
external archiving .....	98
external links .....	39
external links, in HTML export .....	150

**F**

faces, for TODO keywords .....	50
FAQ .....	1
feedback .....	3
field coordinates .....	26
field formula .....	29
field references .....	24
file links .....	39
file links, searching .....	45
file name completion .....	42
files for agenda .....	100
files, adding to agenda list .....	100
files, selecting for publishing .....	184
<b>filladapt.el</b> .....	234
filtering, by tag, category, top headline and effort, in agenda .....	111
Filters, exporting .....	180
<b>fnadjust</b> , STARTUP keyword .....	229
<b>fnauto</b> , STARTUP keyword .....	229
<b>fnconfirm</b> , STARTUP keyword .....	229
<b>fninline</b> , STARTUP keyword .....	229
<b>fnlocal</b> , STARTUP keyword .....	229
<b>fnplain</b> , STARTUP keyword .....	229
<b>fnprompt</b> , STARTUP keyword .....	229

folded, subtree visibility state .....	6
folding, sparse trees .....	11
following links .....	42
footnotes .....	16
format specifier .....	27
format, of links .....	38
formatting source code, markup rules .....	129
formula debugging .....	33
formula editing .....	31
formula syntax, Calc .....	27
formula, for individual table field .....	29
formula, for range of fields .....	29
formula, for table column .....	30
formula, in tables .....	21

**G**

Gillespie, Dave .....	233
global cycling .....	7
global key bindings .....	3
global TODO list .....	104
global visibility states .....	7
Gnus links .....	39
graph, in tables .....	36
group tags .....	62
group tags, as regular expressions .....	106
grouping columns in tables .....	23

**H**

habits .....	53
hacking .....	237
header, for L <sup>A</sup> T <sub>E</sub> X files .....	156
headline navigation .....	8
headline tagging .....	59
headline, promotion and demotion .....	9
headlines .....	6
hide text .....	6
<b>hideblocks</b> , STARTUP keyword .....	16, 229
<b>hidestars</b> , STARTUP keyword .....	228
hiding leading stars .....	230
history .....	254
hooks .....	237
horizontal rules, in ASCII export .....	143
horizontal rules, in L <sup>A</sup> T <sub>E</sub> X export .....	161
horizontal rules, markup rules .....	129
HTML entities .....	131
HTML export .....	147
HTML export, CSS .....	152
HTML, and Orgtbl mode .....	242
HTML5, export new elements .....	148
hyperlinks .....	38
hyperlinks, adding new types .....	237

**I**

iCalendar export .....	178
identify, ImageMagick .....	165

idle, resolve, dangling ..... 85  
 image, centering (L<sup>A</sup>T<sub>E</sub>X export) ..... 159  
 imagemagick ..... 151, 167  
 images, embedding in ODT ..... 165  
 images, inline in HTML ..... 151  
 images, inline in L<sup>A</sup>T<sub>E</sub>X ..... 158  
 images, inlining ..... 43  
`imenu.el` ..... 233  
 in-buffer settings ..... 226  
 inactive timestamp ..... 74  
 include files, during export ..... 140  
`indent`, STARTUP keyword ..... 227  
 indentation, in source blocks ..... 130, 195  
 index, in a publishing project ..... 190  
 Info links ..... 39  
 inheritance, of properties ..... 67  
 inheritance, of tags ..... 59  
 inlined images, markup rules ..... 129  
`inlineimages`, STARTUP keyword ..... 43, 228  
 inlining images ..... 43  
 inlining images in HTML ..... 151  
 inlining images in L<sup>A</sup>T<sub>E</sub>X ..... 158  
 input file, macro ..... 141  
 inserting links ..... 42  
 insertion, of templates ..... 224  
 installation ..... 2  
 internal links ..... 38  
 internal links, in HTML export ..... 150  
 introduction ..... 1  
 iPhone ..... 252  
 IRC links ..... 39  
 italic text, markup rules ..... 128

## J

jumping, to headlines ..... 8

## K

key bindings, global ..... 3  
 keyword options ..... 49

## L

L<sup>A</sup>T<sub>E</sub>X class ..... 156  
 L<sup>A</sup>T<sub>E</sub>X entities ..... 131  
 L<sup>A</sup>T<sub>E</sub>X export ..... 154  
 L<sup>A</sup>T<sub>E</sub>X fragments ..... 132  
 L<sup>A</sup>T<sub>E</sub>X fragments, preview ..... 133  
 L<sup>A</sup>T<sub>E</sub>X header ..... 156  
 L<sup>A</sup>T<sub>E</sub>X interpretation ..... 132  
 L<sup>A</sup>T<sub>E</sub>X sectioning structure ..... 156  
 L<sup>A</sup>T<sub>E</sub>X, and Orgtbl mode ..... 241  
`latexpreview`, STARTUP keyword ..... 228  
 Latin-1 export ..... 142  
 level, require for tags/property match ..... 106  
 LibreOffice ..... 162, 163  
 limits, in agenda ..... 112

link abbreviations ..... 44  
 link abbreviations, completion of ..... 224  
 link completion ..... 42  
 link format ..... 38  
 links, external ..... 39  
 links, finding next/previous ..... 43  
 links, handling ..... 41  
 links, in HTML export ..... 150  
 links, in ODT export ..... 164  
 links, internal ..... 38  
 links, publishing ..... 189  
 links, radio targets ..... 39  
 links, returning to ..... 43  
 linter ..... 18  
 Lisp forms, as table formulas ..... 29  
 list of listings ..... 139  
 list of tables ..... 139  
 lists, in other modes ..... 239  
 lists, ordered ..... 12  
 lists, plain ..... 12  
 literal examples, markup rules ..... 129  
`logdone`, STARTUP keyword ..... 228  
`logdrawer`, STARTUP keyword ..... 228  
 logging, of progress ..... 52  
`lognoteclock-out`, STARTUP keyword ..... 228  
`lognotedone`, STARTUP keyword ..... 228  
`lognoteredeadline`, STARTUP keyword ..... 228  
`lognoterefile`, STARTUP keyword ..... 228  
`lognoterepeat`, STARTUP keyword ..... 228  
`lognotereschedule`, STARTUP keyword ..... 228  
`logredeadline`, STARTUP keyword ..... 228  
`logrefile`, STARTUP keyword ..... 228  
`logrepeat`, STARTUP keyword ..... 228  
`logreschedule`, STARTUP keyword ..... 228  
`logstatesreversed`, STARTUP keyword ..... 228  
 lookup functions in tables ..... 31  
 Ludlam, Eric M. .... 233

## M

macro replacement, during export ..... 141  
 maintainer ..... 3  
 mapping entries, API ..... 249  
 mark ring ..... 43  
 Markdown export ..... 161  
 marking characters, tables ..... 35  
 match view ..... 105  
 matching, of properties ..... 105  
 matching, of tags ..... 105  
 matching, tags ..... 59  
 math symbols ..... 131  
 MathJax ..... 151  
 MathML ..... 166  
 MH-E links ..... 39  
 minor mode for structure editing ..... 17  
 minor mode for tables ..... 24  
 MobileOrg ..... 252  
 mode, for `calc` ..... 27

modification time, macro ..... 141  
 motion commands in agenda ..... 113  
 motion, between headlines ..... 8

## N

name, of column or field ..... 26  
 named references ..... 26  
 names as TODO keywords ..... 48  
 narrow columns in tables ..... 22  
**noalign**, STARTUP keyword ..... 228  
**nofnadjust**, STARTUP keyword ..... 229  
**nofninline**, STARTUP keyword ..... 229  
**nohideblocks**, STARTUP keyword ..... 16, 229  
**noindent**, STARTUP keyword ..... 227  
**noinlineimages**, STARTUP keyword ..... 43, 228  
**nolatexpreview**, STARTUP keyword ..... 228  
**nologdone**, STARTUP keyword ..... 228  
**nologdrawer**, STARTUP keyword ..... 228  
**nolognoteclock-out**, STARTUP keyword ..... 228  
**nologredeadline**, STARTUP keyword ..... 228  
**nologrefile**, STARTUP keyword ..... 228  
**nologrepeat**, STARTUP keyword ..... 228  
**nologreschedule**, STARTUP keyword ..... 228  
**nologstatesreversed**, STARTUP keyword ... 228

## O

occur, command ..... 11  
 occur-tree ..... 122  
**odd**, STARTUP keyword ..... 228  
 odd-levels-only outlines ..... 230  
 ODT ..... 162  
 ODT\_STYLES\_FILE ..... 162  
 OpenDocument ..... 162  
 option keyword completion ..... 224  
 options, for custom agenda views ..... 123  
 options, for customization ..... 226  
 options, for publishing ..... 185  
 ordered lists ..... 12  
 Org entities ..... 131  
 Org export ..... 173  
 Org mode, turning on ..... 3  
 Org syntax ..... 18  
 org-agenda, command ..... 102  
 org-capture-last-stored ..... 90  
**org-crypt.el** ..... 235  
**org-decrypt-entry** ..... 235  
 org-hide-block-startup ..... 229  
 org-insert-drawer ..... 15, 65  
 org-list-insert-radio-list ..... 243  
 org-pretty-entities ..... 229  
 org-publish-project-alist ..... 183  
 Orgstruct mode ..... 17  
 Orgtbl mode ..... 24, 239  
 Ota, Takaaki ..... 233  
 Outline mode ..... 6  
 outline tree ..... 6

outlines ..... 6  
 overview, global visibility state ..... 7  
**overview**, STARTUP keyword ..... 8, 227

## P

packages, interaction with other ..... 233  
 paragraphs, markup rules ..... 128  
 pasting, of subtrees ..... 9  
 PDF export ..... 154  
 per-file keywords ..... 49  
 plain lists ..... 12  
 plain lists, in L<sup>A</sup>T<sub>E</sub>X export ..... 159  
 plain text external links ..... 40  
 plot tables using Gnuplot ..... 36  
 presentation, of agenda items ..... 109  
 print edition ..... 1  
 printing sparse trees ..... 12  
 priorities ..... 55  
 priorities, of agenda items ..... 110  
 progress logging ..... 52  
 projects, for publishing ..... 183  
 promotion, of subtrees ..... 9  
 proof, in L<sup>A</sup>T<sub>E</sub>X export ..... 160  
 properties ..... 64  
 properties, API ..... 72, 248  
 properties, column view ..... 68  
 properties, inheritance ..... 67  
 properties, searching ..... 66  
 properties, special ..... 66  
 property EXPORT\_FILE\_NAME ..... 162  
 property syntax ..... 64  
 property, + ..... 65  
 property, \_ALL ..... 65  
 property, ALT\_TITLE ..... 139  
 property, APPENDIX ..... 175  
 property, ARCHIVE ..... 67, 98  
 property, ATTACH\_DIR ..... 96  
 property, ATTACH\_DIR\_INHERIT ..... 96  
 property, BEAMER\_ACT ..... 145  
 property, BEAMER\_COL ..... 145  
 property, BEAMER\_ENV ..... 144  
 property, BEAMER\_OPT ..... 145  
 property, BEAMER\_REF ..... 145  
 property, CATEGORY ..... 67, 109  
 property, COLUMNS ..... 67, 227  
 property, COOKIE\_DATA ..... 56, 57  
 property, COPYING ..... 175  
 property, CUSTOM\_ID ..... 38, 41  
 property, DESCRIPTION ..... 175, 179  
 property, Effort ..... 86  
 property, EXPORT\_FILE\_NAME ..... 139  
 property, EXPORT\_LATEX\_CLASS ..... 156  
 property, EXPORT\_LATEX\_CLASS\_OPTIONS ..... 156  
 property, ID ..... 41, 71, 179  
 property, INDEX ..... 176  
 property, LOCATION ..... 179

property, LOG\_INTRO\_DRAWER..... 52, 81  
 property, LOGGING..... 53, 67  
 property, macro..... 141  
 property, ORDERED..... 50, 57, 58  
 property, special, ALLTAGS..... 66  
 property, special, BLOCKED..... 66  
 property, special, CLOCKSUM..... 66, 127  
 property, special, CLOCKSUM\_T..... 66, 127  
 property, special, CLOSED..... 66  
 property, special, DEADLINE..... 66  
 property, special, FILE..... 66  
 property, special, ITEM..... 66  
 property, special, PRIORITY..... 66  
 property, special, SCHEDULED..... 66  
 property, special, TAGS..... 66  
 property, special, TIMESTAMP..... 66  
 property, special, TIMESTAMP\_IA..... 66  
 property, special, TODO..... 66  
 property, SUMMARY..... 179  
 property, UNNUMBERED..... 138  
 property, VISIBILITY..... 8  
 property: CLOCK\_MODELINE\_TOTAL..... 81  
 property: LAST\_REPEAT..... 81  
 protocols, for external access..... 96  
 publishing..... 183

## Q

query editing, in agenda..... 111  
 quote blocks..... 128

## R

radio lists..... 243  
 radio tables..... 240  
 radio targets..... 39  
 range formula..... 29  
 range references..... 25  
 ranges, time..... 73  
 recomputing table fields..... 34  
 references..... 24  
 references, named..... 26  
 references, remote..... 26  
 references, to a different table..... 26  
 references, to fields..... 24  
 references, to ranges..... 25  
 refiling notes..... 97  
 region, active..... 11, 21, 162  
 regular expressions, with tags search..... 106  
 relative timer..... 87  
 reminders..... 104  
 remote editing, bulk, from agenda..... 119  
 remote editing, from agenda..... 117  
 remote editing, undo..... 117  
 remote references..... 26  
 repeated tasks..... 79  
 report, of clocked time..... 83  
 resolve idle time..... 85

revealing context..... 7  
 RMAIL links..... 39  
 Rose, Sebastian..... 153  
 row, of field coordinates..... 26  
 RSS feeds..... 96  
 rsync..... 191

## S

SCHEDULED keyword..... 77  
 scheduling..... 73  
 Schulte, Eric..... 194  
 Scripts, for agenda processing..... 247  
 search option in file links..... 45  
 search strings, custom..... 45  
 search view..... 108  
 searching for tags..... 63  
 searching, for text..... 108  
 searching, of properties..... 66  
 sectioning structure, for L<sup>A</sup>T<sub>E</sub>X export..... 156  
 set startup visibility, command..... 7  
 setting tags..... 59  
 SHELL links..... 39  
 shift-selection-mode..... 14  
**shift-selection-mode**..... 234  
 show all, command..... 7  
 show all, global visibility state..... 7  
 show branches, command..... 7  
 show children, command..... 7  
 show hidden text..... 6  
**showall**, STARTUP keyword..... 8, 227  
**showeverything**, STARTUP keyword..... 8, 227  
**showstars**, STARTUP keyword..... 228  
 shy hyphen, special symbol..... 132  
 sitemap, of published pages..... 189  
 sorting, of agenda items..... 110  
 sorting, of plain list..... 15  
 sorting, of subtrees..... 9  
 source blocks, in L<sup>A</sup>T<sub>E</sub>X export..... 159  
 source code, batch execution..... 222  
 source code, block header arguments..... 200  
 source code, block structure..... 194  
 source code, editing..... 195  
 source code, evaluating..... 198  
 source code, exporting..... 196  
 source code, extracting..... 196  
 source code, inline..... 194  
 source code, language..... 194  
 source code, languages..... 199  
 source code, library..... 199  
 source code, noweb reference..... 221  
 source code, results of evaluation..... 219  
 source code, switches..... 194  
 source code, working with..... 194  
 sparse tree, for deadlines..... 79  
 sparse tree, for TODO..... 46  
 sparse tree, tag based..... 59  
 sparse trees..... 11

special blocks, in ASCII export .....	143
special blocks, in L <sup>A</sup> T <sub>E</sub> X export .....	160
special keywords .....	226
special symbols .....	131
special symbols, in-buffer display .....	131
speed keys .....	225
<b>speedbar.el</b> .....	233
spreadsheet capabilities .....	24
square brackets, around links .....	40
statistics, for checkboxes .....	57
statistics, for TODO items .....	56
storing links .....	41
Storm, Kim. F. ....	234
strike-through text, markup rules .....	128
structure editing .....	9
structure of document .....	6
styles, custom .....	163, 168
sublevels, inclusion into tags match .....	59
sublevels, inclusion into TODO list .....	105
subscript .....	132
SUBTITLE (ODT) .....	162
subtree cycling .....	6
subtree visibility states .....	6
subtree, cut and paste .....	9
subtree, subtree visibility state .....	6
subtrees, cut and paste .....	9
summary .....	1
superscript .....	132
syntax checker .....	18
syntax, noweb .....	221
syntax, of formulas .....	27

## T

table editor, built-in .....	19
table editor, <b>table.el</b> .....	233
table lookup functions .....	31
table of contents .....	139
<b>table.el</b> .....	233
tables .....	19
tables, in HTML .....	150
tables, in L <sup>A</sup> T <sub>E</sub> X export .....	156
tables, in ODT export .....	164, 170
tables, in other modes .....	239
tables, markup rules .....	129
tag completion .....	224
tag filtering, in agenda .....	111
tag hierarchy .....	62
tag inheritance .....	59
tag searches .....	63
tags .....	59
tags view .....	105
tags, as an agenda view .....	122
tags, groups .....	62
tags, setting .....	59
tags-todo .....	122
tags-tree .....	122
tangling .....	196

targets, for links .....	38
targets, radio .....	39
tasks, breaking down .....	56
tasks, repeated .....	79
template insertion .....	224
template, custom .....	163, 168
templates, for Capture .....	90
T <sub>E</sub> X interpretation .....	132
T <sub>E</sub> X symbol completion .....	224
Texinfo export .....	173
text areas, in HTML .....	152
text search .....	108
thanks .....	254
time clocking .....	80
time format, custom .....	77
time grid .....	110
Time, computing .....	29
time, macro .....	141
time, reading in minibuffer .....	75
time-of-day specification .....	109
time-sorted view .....	108
timeline, single file .....	108
timerange .....	74
times .....	73
timestamp .....	73
timestamp, inactive .....	74
timestamp, with repeater interval .....	73
timestamps .....	73
timestamps, creating .....	74
title, macro .....	141
TODO dependencies .....	50
TODO dependencies, NOBLOCKING .....	50
TODO items .....	46
TODO keyword matching .....	105
TODO keyword matching, with tags search ...	106
TODO keyword sets .....	48
TODO keywords completion .....	224
TODO list, global .....	104
TODO types .....	48
TODO workflow .....	47
todo, as an agenda view .....	122
todo-tree .....	122
top headline filtering, in agenda .....	111
transient mark mode .....	11, 21
transient-mark-mode .....	162
translator function .....	242
trees, sparse .....	11
trees, visibility .....	6
tty key bindings .....	232
types as TODO keywords .....	48

## U

underlined text, markup rules .....	128
undoing remote-editing events .....	117
unison .....	191
<b>unocnv</b> .....	163
updating, table .....	34

URL links ..... 39  
USENET links ..... 39  
UTF-8 export ..... 142

## V

variables, for customization ..... 226  
vectors, in table calculations ..... 27  
verbatim blocks, in L<sup>A</sup>T<sub>E</sub>X export ..... 160  
verbatim text, markup rules ..... 128  
verse blocks ..... 128  
**viper.el** ..... 235  
visibility cycling ..... 6  
visibility cycling, drawers ..... 15  
visibility, initialize ..... 8  
visible text, printing ..... 12

VM links ..... 40

## W

WANDERLUST links ..... 40  
weekly agenda ..... 102  
**windmove.el** ..... 235  
workflow states as TODO keywords ..... 47

## Y

**yasnippet.el** ..... 235

## Z

zip ..... 162

# Key index

<b>\$</b>		<b>&gt;</b>	
\$..... 117		>..... 71, 76, 101, 118	
<b>%</b>		<b>?</b>	
%..... 119		?..... 253	
<b>,</b>		<b>[</b>	
'..... 134		[..... 111, 115	
<b>*</b>		<b>]</b>	
*..... 119		]..... 111	
<b>+</b>		<b>^</b>	
+..... 118		^..... 112, 116, 134	
<b>,</b>		<b>-</b>	
,..... 118		-..... 112, 134	
<b>-</b>		<b>`</b>	
-..... 118		`..... 134	
<b>.</b>		<b> </b>	
..... 115		..... 112, 117	
<b>/</b>		{..... 111	
/..... 111, 116		}..... 111	
<b>:</b>		<b>~</b>	
:..... 117		~..... 113	
<b>;</b>		<b>A</b>	
;..... 87		a..... 71, 117	
<b>&lt;</b>		A..... 114	
<..... 71, 76, 101, 112, 116		<b>B</b>	
<TAB>..... 20		b..... 115	
<b>=</b>		B..... 119	
=..... 112, 116		<b>C</b>	
		c..... 120	
		C..... 121	
		C-#..... 34	
		C-'..... 100	



C-	100	C-c C-a D	96
C- <sub>1</sub>	117	C-c C-a f	95
C-0 C-c C-w	97	C-c C-a F	95
C-c !	74	C-c C-a i	96
C-c #	58	C-c C-a l	95
C-c \$	98	C-c C-a m	95
C-c %	43	C-c C-a n	95
C-c &	43	C-c C-a o	95
C-c ' 17, 32, 131, 140, 195, 234		C-c C-a O	95
C-c *	11, 15, 34	C-c C-a s	96
C-c +	21	C-c C-a z	95
C-c ,	55	C-c C-b	8, 146
C-c -	14, 20	C-c C-c... 14, 17, 19, 32, 33, 57, 60, 65, 71, 72, 74, 82, 83, 89, 133, 198, 222, 230, 233	
C-c .	74	C-c C-c c	66
C-c /	11, 235	C-c C-c d	66
C-c / /	11	C-c C-c D	66
C-c / a	79	C-c C-c s	65
C-c / b	79	C-c C-d	78, 118
C-c / d	79	C-c C-e	135
C-c / m	63, 66	C-c C-e c a	179
C-c / p	67	C-c C-e c c	179
C-c / r	11	C-c C-e c f	179
C-c / t	46	C-c C-e C-v	12
C-c ;	142	C-c C-e h h	147
C-c <	74	C-c C-e h H	147
C-c =	31	C-c C-e i i	173
C-c >	74	C-c C-e i t	173
C-c ?	32	C-c C-e l b	143
C-c @	10	C-c C-e l B	143
C-c [	100	C-c C-e l l	154
C-c ]	100	C-c C-e l L	154
C-c ^ 11, 15, 20		C-c C-e l p	154
C-c `	21	C-c C-e l P	143
C-c \	63, 66	C-c C-e m m	161
C-c	19, 22	C-c C-e m M	161
C-c {	32, 134	C-c C-e o o	162
C-c }	32, 33	C-c C-e O o	173
C-c ~	234	C-c C-e O O	173
C-c a	5	C-c C-e P a	193
C-c a !	108	C-c C-e P f	192
C-c a #	108	C-c C-e P p	192
C-c a ?	253	C-c C-e P x	192
C-c a a	102	C-c C-e t a/l/u	142
C-c a C	122	C-c C-e t A/L/U	142
C-c a e	126	C-c C-f	8
C-c a L	108	C-c C-j	8
C-c a m	63, 66, 105	C-c C-k	7, 90
C-c a M	63, 66, 105	C-c C-l	42
C-c a s	108	C-c C-n	8
C-c a t	47, 105	C-c C-o	17, 42, 74, 114, 222
C-c a T	105	C-c C-p	8
C-c c	5, 89	C-c C-q	32, 59
C-c c C	90	C-c C-r	7, 32
C-c C-*	15	C-c C-s	78, 118
C-c C-a	95, 118	C-c C-t	46, 82
C-c C-a a	95	C-c C-u	8
C-c C-a c	95	C-c C-v a	222
C-c C-a d	95		

C-c C-v b .....	222	C-c C-x C-b .....	57
C-c C-v c .....	222	C-c C-x C-c .....	70, 116, 127
C-c C-v C-a .....	222	C-c C-x C-d .....	82
C-c C-v C-b .....	222	C-c C-x C-e .....	82, 87
C-c C-v C-c .....	222	C-c C-x C-i .....	81
C-c C-v C-d .....	222	C-c C-x C-j .....	82
C-c C-v C-e .....	222	C-c C-x C-l .....	133
C-c C-v C-f .....	222	C-c C-x C-n .....	43
C-c C-v C-g .....	222	C-c C-x C-o .....	81
C-c C-v C-h .....	222	C-c C-x C-p .....	43
C-c C-v C-i .....	222	C-c C-x C-q .....	82
C-c C-v C-l .....	222	C-c C-x C-r .....	83
C-c C-v C-l .....	222	C-c C-x C-s .....	98, 117
C-c C-v C-n .....	222	C-c C-x C-t .....	77
C-c C-v C-o .....	222	C-c C-x C-u .....	72, 83, 244
C-c C-v C-p .....	222	C-c C-x C-v .....	43
C-c C-v C-r .....	222	C-c C-x C-w .....	10, 21
C-c C-v C-s .....	222	C-c C-x C-x .....	82
C-c C-v C-t .....	222	C-c C-x C-y .....	10, 21
C-c C-v C-u .....	222	C-c C-x d .....	15
C-c C-v C-v .....	222	C-c C-x e .....	87
C-c C-v C-x .....	222	C-c C-x f .....	16
C-c C-v C-z .....	222	C-c C-x g .....	96
C-c C-v d .....	222	C-c C-x G .....	96
C-c C-v e .....	222	C-c C-x i .....	72
C-c C-v f .....	222	C-c C-x M-w .....	10, 21
C-c C-v g .....	222	C-c C-x o .....	50, 58
C-c C-v h .....	222	C-c C-x p .....	65, 201
C-c C-v i .....	199, 222	C-c C-x q .....	63
C-c C-v I .....	222	C-c C-x v .....	7
C-c C-v j .....	222	C-c C-y .....	75, 82
C-c C-v l .....	222	C-c C-z .....	15, 118
C-c C-v n .....	222	C-c l .....	41, 131
C-c C-v o .....	222	C-c M-w .....	97
C-c C-v p .....	222	C-c RET .....	20
C-c C-v r .....	222	C-c SPC .....	19
C-c C-v s .....	222	C-c TAB .....	7
C-c C-v t .....	197, 222	C-k .....	117
C-c C-v u .....	222	C-RET .....	9
C-c C-v v .....	222	C-S-left .....	48, 117
C-c C-v x .....	222	C-S-RET .....	9
C-c C-v z .....	222	C-S-right .....	48, 117
C-c C-w .....	10, 89, 97, 117	C-S-up/down .....	82
C-c C-x , .....	88	C-TAB .....	99
C-c C-x - .....	88	C-u C-c ! .....	74
C-c C-x .....	88	C-u C-c * .....	34
C-c C-x ; .....	88	C-u C-c .....	74
C-c C-x < .....	101	C-u C-c = .....	30, 31
C-c C-x > .....	101, 116	C-u C-c c .....	90
C-c C-x _ .....	88	C-u C-c C-c .....	34
C-c C-x \ .....	132	C-u C-c C-l .....	42
C-c C-x 0 .....	87	C-u C-c C-t .....	46
C-c C-x a .....	99, 117	C-u C-c C-w .....	97
C-c C-x A .....	99, 117	C-u C-c C-x a .....	99
C-c C-x b .....	7, 114	C-u C-c C-x C-s .....	98
C-c C-x c .....	10	C-u C-c C-x C-u .....	72, 83, 244
C-c C-x C-a .....	97, 117	C-u C-u C-c * .....	34
		C-u C-u C-c = .....	31

C-u C-u C-c c .....	90
C-u C-u C-c C-c .....	34
C-u C-u C-c C-t .....	48
C-u C-u C-c C-w .....	97
C-u C-u C-c C-x C-s .....	98
C-u C-u C-u C-c C-t .....	50
C-u C-u C-u TAB .....	7
C-u C-u TAB .....	7, 8
C-v .....	76
C-x C-s .....	32, 116
C-x C-w .....	121, 125
C-x n b .....	11
C-x n s .....	11
C-x n w .....	11
C-y .....	10

## D

d .....	114
D .....	115

## E

e .....	71
E .....	116

## F

f .....	114
F .....	114

## G

g .....	70, 116
G .....	116

## H

H .....	121
---------	-----

## I

i .....	120
I .....	118

## J

j .....	115
J .....	115, 119

## K

k .....	119
---------	-----

## L

l .....	115
L .....	114

## M

m .....	119
M .....	121
M-* .....	119
M-<down> .....	119
M-<up> .....	119
M-a .....	20
M-down .....	14, 20, 32
M-down .....	222
M-e .....	20
M-g M-n .....	12
M-g M-p .....	12
M-g n .....	12
M-g p .....	12
M-h .....	10
M-left .....	9, 14, 20
M-m .....	119
M-RET .....	9, 14, 21, 88
M-right .....	9, 14, 20
M-S-down .....	10, 20, 32, 76
M-S-left .....	9, 14, 20, 76
M-S-RET .....	9, 14, 58
M-S-right .....	10, 14, 20, 76
M-S-up .....	10, 20, 32, 76
M-TAB .....	32, 49, 59, 65, 224
M-up .....	14, 20, 32
M-up .....	222
M-v .....	76
M-x org-iswitchb .....	101
mouse-1 .....	17, 43, 76
mouse-2 .....	17, 43, 114
mouse-3 .....	43, 114

## N

n .....	71, 113
N .....	113

## O

o .....	114
O .....	118

## P

p .....	71, 113
P .....	113, 118

## Q

q .....	70, 121
---------	---------

## R

r .....	70, 105, 116
R .....	115
RET .....	20, 43, 61, 76, 114

**S**

s	116
S	121
S-down	14, 32, 55, 74, 76, 118
S-left	15, 32, 46, 48, 65, 70, 74, 76, 83, 118
S-M-left	71
S-M-RET	47
S-M-right	71
S-M-up/down	82
S-RET	21
S-right	15, 32, 46, 48, 65, 70, 74, 76, 83, 118
S-TAB	7, 20
S-up	32, 55, 74, 76, 118
SPC	61, 114

**T**

t	117
T	117
TAB	7, 9, 13, 32, 61, 114, 134

**U**

u	119
U	119

**V**

v	71
v [	115
v a	115
v A	115
v c	115
v d	114
v E	116
v l	115
v L	115
v m	114
v R	115
v SPC	114
v t	114
v w	114
v y	114

**W**

w	114
---	-----

**X**

x	121
X	119

**Z**

z	118
---	-----

## Command and function index

### L

lisp-complete-symbol ..... 32

### N

next-error ..... 12

### O

org-agenda ..... 3, 5  
 org-agenda-add-note ..... 118  
 org-agenda-archive ..... 117  
 org-agenda-archive-default-with-confirmation ..... 117  
 org-agenda-archive-to-archive-sibling ... 117  
 org-agenda-archives-mode ..... 115  
 org-agenda-archives-mode 'files ..... 115  
 org-agenda-bulk-action ..... 119  
 org-agenda-bulk-mark ..... 119  
 org-agenda-bulk-mark-all ..... 119  
 org-agenda-bulk-mark-regexp ..... 119  
 org-agenda-bulk-remove-all-marks ..... 119  
 org-agenda-bulk-toggle ..... 119  
 org-agenda-bulk-toggle-all ..... 119  
 org-agenda-bulk-unmark ..... 119  
 org-agenda-capture ..... 119  
 org-agenda-clock-cancel ..... 119  
 org-agenda-clock-goto ..... 115, 119  
 org-agenda-clock-in ..... 118  
 org-agenda-clock-out ..... 118  
 org-agenda-clockreport-mode ..... 115  
 org-agenda-columns ..... 116, 127  
 org-agenda-convert-date ..... 121  
 org-agenda-date-prompt ..... 118  
 org-agenda-day-view ..... 114  
 org-agenda-deadline ..... 118  
 org-agenda-diary-entry ..... 120  
 org-agenda-do-date-earlier ..... 118  
 org-agenda-do-date-later ..... 118  
 org-agenda-drag-line-backward ..... 119  
 org-agenda-drag-line-forward ..... 119  
 org-agenda-earlier ..... 115  
 org-agenda-entry-text-mode ..... 116  
 org-agenda-exit ..... 121  
 org-agenda-file-to-front ..... 100  
 org-agenda-filter-by-category ..... 112, 116  
 org-agenda-filter-by-effort ..... 112  
 org-agenda-filter-by-regexp ..... 112, 116  
 org-agenda-filter-by-tag ..... 111, 116  
 org-agenda-filter-by-top-headline ... 112, 116  
 org-agenda-filter-remove-all ..... 112, 117  
 org-agenda-follow-mode ..... 114  
 org-agenda-fortnight-view ..... 114  
 org-agenda-goto ..... 114

org-agenda-goto-calendar ..... 120  
 org-agenda-goto-date ..... 115  
 org-agenda-goto-today ..... 115  
 org-agenda-holidays ..... 121  
 org-agenda-kill ..... 117  
 org-agenda-later ..... 114  
 org-agenda-limit-interactively ..... 113  
 org-agenda-list ..... 102  
 org-agenda-list-stuck-projects ..... 108  
 org-agenda-log-mode ..... 115  
 org-agenda-manipulate-query-add ..... 115  
 org-agenda-month-view ..... 114  
 org-agenda-next-item ..... 113  
 org-agenda-next-line ..... 113  
 org-agenda-open-link ..... 114  
 org-agenda-phases-of-moon ..... 121  
 org-agenda-previous-item ..... 113  
 org-agenda-previous-line ..... 113  
 org-agenda-priority-down ..... 118  
 org-agenda-priority-up ..... 118  
 org-agenda-quit ..... 121  
 org-agenda-recenter ..... 114  
 org-agenda-redo ..... 116  
 org-agenda-refile ..... 117  
 org-agenda-remove-restriction-lock .. 101, 116  
 org-agenda-reset-view ..... 114  
 org-agenda-schedule ..... 118  
 org-agenda-set-restriction-lock ..... 101  
 org-agenda-set-tags ..... 117  
 org-agenda-show-and-scroll-up ..... 114  
 org-agenda-show-priority ..... 118  
 org-agenda-show-tags ..... 117  
 org-agenda-sunrise-sunset ..... 121  
 org-agenda-switch-to ..... 114  
 org-agenda-todo ..... 117  
 org-agenda-todo-nextset ..... 117  
 org-agenda-todo-previousset ..... 117  
 org-agenda-toggle-archive-tag ..... 117  
 org-agenda-toggle-diary ..... 115  
 org-agenda-toggle-time-grid ..... 116  
 org-agenda-tree-to-indirect-buffer ..... 114  
 org-agenda-undo ..... 117  
 org-agenda-week-view ..... 114  
 org-agenda-write ..... 121, 125  
 org-agenda-year-view ..... 114  
 org-archive-subtree ..... 98  
 org-archive-subtree-default ..... 97  
 org-archive-to-archive-sibling ..... 99  
 org-ascii-export-as-ascii ..... 142  
 org-ascii-export-to-ascii ..... 142  
 org-attach ..... 95, 118  
 org-attach-attach ..... 95  
 org-attach-delete-all ..... 96  
 org-attach-delete-one ..... 95  
 org-attach-new ..... 95

org-attach-open	95	org-demote-subtree	10
org-attach-open-in-emacs	95	org-do-demote	9
org-attach-reveal	95	org-do-promote	9
org-attach-reveal-in-emacs	95	org-edit-special	234
org-attach-set-directory	96	org-entities-help	131
org-attach-set-inherit	96	org-entry-add-to-multivalued-property	249
org-attach-sync	95	org-entry-delete	248
org-backward-same-level	8	org-entry-get	248
org-beamer-export-as-latex	143	org-entry-get-multivalued-property	249
org-beamer-export-to-latex	143	org-entry-member-in-multivalued-property	249
org-beamer-export-to-pdf	143	org-entry-properties	248
org-beamer-select-environment	146	org-entry-put	248
org-buffer-property-keys	249	org-entry-put-multivalued-property	249
org-calendar-goto-agenda	120	org-entry-remove-from-multivalued-property	249
org-capture	3, 5, 89	org-evaluate-time-range	75, 82
org-capture-finalize	89	org-export-dispatch	135
org-capture-kill	90	org-feed-goto-inbox	96
org-capture-refile	89	org-feed-update-all	96
org-check-after-date	79	org-force-cycle-archived	99
org-check-before-date	79	org-forward-same-level	8
org-check-deadlines	79	org-global-cycle	7
org-clock-cancel	82	org-goto	8
org-clock-display	82	org-goto-calendar	74
org-clock-goto	82	org-html-export-as-html	147
org-clock-in	81	org-html-export-to-html	147
org-clock-in-last	82	org-icalendar-combine-agenda-files	179
org-clock-modify-effort-estimate	82, 87	org-icalendar-export-agenda-files	179
org-clock-out	81	org-icalendar-export-to-ics	179
org-clock-report	83	org-insert-columns-dblock	72
org-clock-timestamps-up/down	82	org-insert-heading	9, 14, 88
org-clocktable-try-shift	83	org-insert-heading-respect-content	9
org-clone-subtree-with-time-shift	10	org-insert-link	42
org-columns	70	org-insert-property-drawer	248, 249
org-columns-delete	71	org-insert-todo-heading	9, 47, 58
org-columns-edit-allowed	71	org-insert-todo-heading-respect-content	9
org-columns-edit-value	71	org-iswitchb	3
org-columns-narrow	71	org-latex-export-as-latex	154
org-columns-new	71	org-latex-export-to-latex	154
org-columns-next-allowed-value	71	org-latex-export-to-pdf	154
org-columns-previous-allowed-value	71	org-lookup-all	31
org-columns-quit	70	org-lookup-first	31
org-columns-redo	70	org-lookup-last	31
org-columns-set-tags-or-toggle	71	org-map-entries	249
org-columns-show-value	71	org-mark-element	10
org-columns-widen	71	org-mark-ring-goto	43
org-compute-property-at-point	66	org-mark-ring-push	43
org-copy	97	org-mark-subtree	10
org-copy-subtree	10	org-match-sparse-tree	63, 66
org-copy-visible	7	org-md-export-as-markdown	161
org-cut-subtree	10	org-md-export-to-markdown	161
org-cycle	7, 9, 13	org-move-subtree-down	10
org-cycle-agenda-files	100	org-move-subtree-up	10
org-date-from-calendar	74	org-narrow-to-block	11
org-dblock-update	72, 83, 244	org-narrow-to-subtree	11
org-deadline	78	org-next-link	43
org-delete-property	66	org-next-visible-heading	8
org-delete-property-globally	66		
org-demote	251		

org-occur.....	11	org-table-fedit-ref-down.....	32
org-odt-export-to-odt.....	162	org-table-fedit-ref-left.....	32
org-open-at-point.....	42, 74	org-table-fedit-ref-right.....	32
org-org-export-as-org.....	173	org-table-fedit-ref-up.....	32
org-org-export-to-org.....	173	org-table-fedit-scroll-down.....	32
org-paste-subtree.....	10	org-table-fedit-scroll-up.....	32
org-previous-link.....	43	org-table-fedit-toggle-ref-type.....	32
org-previous-visible-heading.....	8	org-table-field-info.....	32
org-priority.....	55, 250	org-table-hline-and-move.....	20
org-priority-down.....	55	org-table-insert-column.....	20
org-priority-up.....	55	org-table-insert-hline.....	20
org-promote.....	250	org-table-insert-row.....	20
org-promote-subtree.....	9	org-table-iterate.....	34
org-property-action.....	65	org-table-iterate-buffer-tables.....	34
org-property-next-allowed-value.....	65	org-table-kill-row.....	20
org-property-previous-allowed-value.....	65	org-table-move-column-left.....	20
org-publish.....	192	org-table-move-column-right.....	20
org-publish-all.....	193	org-table-move-row-down.....	20
org-publish-current-file.....	192	org-table-move-row-up.....	20
org-publish-current-project.....	192	org-table-next-field.....	20
org-refile.....	10, 97	org-table-next-row.....	20
org-refile-cache-clear.....	97	org-table-paste-rectangle.....	21
org-refile-goto-last-stored.....	97	org-table-previous-field.....	20
org-remove-file.....	100	org-table-recalculate.....	34
org-reveal.....	7	org-table-recalculate-buffer-tables.....	34
org-save-all-org-buffers.....	116	org-table-rotate-recalc-marks.....	34
org-schedule.....	78	org-table-sort-lines.....	20
org-search-view.....	108	org-table-sum.....	21
org-set-effort.....	87	org-table-toggle-coordinate-overlays..	32, 33
org-set-property.....	65	org-table-toggle-formula-debugger.....	32
org-set-startup-visibility.....	7, 8	org-table-wrap-region.....	21
org-set-tags-command.....	59, 60	org-tags-view.....	63, 66, 105
org-show-todo-tree.....	46	org-texinfo-export-to-info.....	173
org-sort.....	11	org-texinfo-export-to-texinfo.....	173
org-sparse-tree.....	11	org-time-stamp.....	74
org-speedbar-set-agenda-restriction.....	101	org-time-stamp-inactive.....	74
org-store-agenda-views.....	126	org-timeline.....	108
org-store-link.....	3, 41	org-timer.....	88
org-table-align.....	19	org-timer-item.....	88
org-table-beginning-of-field.....	20	org-timer-pause-or-continue.....	88
org-table-blank-field.....	19	org-timer-set-timer.....	88
org-table-copy-down.....	21	org-timer-start.....	87
org-table-copy-region.....	21	org-timer-stop.....	88
org-table-create-or-convert-from-region.....	19, 22	org-timestamp-down-day.....	74
org-table-create-with-table.el.....	234	org-timestamp-down-down.....	74
org-table-cut-region.....	21	org-timestamp-up.....	74
org-table-delete-column.....	20	org-timestamp-up-day.....	74
org-table-edit-field.....	21	org-timestamp-up/down.....	82
org-table-edit-formulas.....	32	org-todo.....	46, 82, 250
org-table-end-of-field.....	20	org-todo-list.....	47, 105
org-table-eval-formula.....	30, 31	org-toggle-archive-tag.....	99
org-table-export.....	22	org-toggle-checkbox.....	57
org-table-fedit-abort.....	32	org-toggle-heading.....	11
org-table-fedit-finish.....	32	org-toggle-inline-images.....	43
org-table-fedit-line-down.....	32	org-toggle-ordered-property.....	50, 58
org-table-fedit-line-up.....	32	org-toggle-tag.....	250
org-table-fedit-lisp-indent.....	32	org-toggle-time-stamp-overlays.....	77
		org-tree-to-indirect-buffer.....	7

org-update-all-dblocks..... 72  
org-update-statistics-cookies..... 58  
org-yank..... 10  
outline-show-all..... 7  
outline-show-branches..... 7  
outline-show-children..... 7  
outline-up-heading..... 8

**P**

pcomplete..... 65  
previous-error..... 12

**W**

widen..... 11



## Variable index

This is not a complete index of variables and faces, only the ones that are mentioned in the manual. For a more complete list, use *M-x org-customize RET* and then click yourself through the tree.

### C

cdlatex-simplify-sub-super-scripts ..... 134  
 constants-unit-system ..... 26, 229

### H

htmlize-output-type ..... 125

### L

L<sup>A</sup>T<sub>E</sub>X-verbatim-environments ..... 241

### O

org-adapt-indentation ..... 231  
 org-agenda-add-entry-text-maxlines ..... 125  
 org-agenda-bulk-custom-functions ..... 119  
 org-agenda-category-filter-preset ... 112, 116  
 org-agenda-clock-consistency-checks ..... 115  
 org-agenda-columns-add-appointments-to-  
   effort-sum ..... 87  
 org-agenda-confirm-kill ..... 117  
 org-agenda-custom-commands .. 12, 122, 123, 124,  
   247  
 org-agenda-custom-commands-contexts ..... 124  
 org-agenda-diary-file ..... 120  
 org-agenda-dim-blocked-tasks ..... 51, 246  
 org-agenda-effort-filter-preset ..... 112  
 org-agenda-entry-text-maxlines ..... 116  
 org-agenda-exporter-settings ..... 121, 125  
 org-agenda-files ..... 100, 110, 179  
 org-agenda-inhibit-startup ..... 8, 246  
 org-agenda-log-mode-items ..... 115  
 org-agenda-max-effort ..... 112  
 org-agenda-max-entries ..... 112  
 org-agenda-max-tags ..... 112  
 org-agenda-max-todos ..... 112  
 org-agenda-ndays ..... 102  
 org-agenda-overriding-header ..... 245  
 org-agenda-prefix-format ..... 109  
 org-agenda-regexp-filter-preset ..... 112, 117  
 org-agenda-restore-windows-after-quit ... 100  
 org-agenda-show-inherited-tags ..... 117, 246  
 org-agenda-skip-archived-trees ..... 99  
 org-agenda-skip-deadline-prewarning-if-  
   scheduled ..... 77  
 org-agenda-skip-function ..... 245, 250  
 org-agenda-skip-function-global ..... 245  
 org-agenda-skip-scheduled-delay-if-deadline  
   ..... 78

org-agenda-skip-scheduled-if-deadline-is-  
   shown ..... 80  
 org-agenda-skip-scheduled-if-done ..... 77  
 org-agenda-sorting-strategy ..... 111  
 org-agenda-span ..... 102, 114  
 org-agenda-start-day ..... 102  
 org-agenda-start-on-weekday ..... 102  
 org-agenda-start-with-clockreport-mode .. 115  
 org-agenda-start-with-entry-text-mode ... 116  
 org-agenda-start-with-follow-mode ..... 114  
 org-agenda-sticky ..... 102  
 org-agenda-tag-filter-preset ..... 111, 116  
 org-agenda-tags-column ..... 109  
 org-agenda-tags-todo-honor-ignore-options  
   ..... 106  
 org-agenda-text-search-extra-files .. 102, 108  
 org-agenda-time-grid ..... 110, 116  
 org-agenda-todo-ignore-deadlines ..... 105  
 org-agenda-todo-ignore-scheduled ..... 105  
 org-agenda-todo-ignore-timestamp ..... 105  
 org-agenda-todo-ignore-with-date ..... 105  
 org-agenda-todo-list-sublevels ..... 56, 105  
 org-agenda-use-tag-inheritance ..... 59, 246  
 org-agenda-use-time-grid ..... 110, 116  
 org-agenda-window-setup ..... 100  
 org-archive-default-command ..... 97, 117  
 org-archive-location ..... 98, 226  
 org-archive-save-context-info ..... 98  
 org-ascii-links-to-notes ..... 142  
 org-ascii-text-width ..... 142  
 org-attach-directory ..... 95  
 org-attach-method ..... 95  
 org-babel-default-header-args ..... 200, 201  
 org-beamer-environments-default ..... 145  
 org-beamer-environments-extra ..... 145  
 org-beamer-frame-level ..... 144  
 org-beamer-subtitle-format ..... 144  
 org-beamer-theme ..... 144  
 org-calc-default-modes ..... 27  
 org-capture-bookmark ..... 90  
 org-capture-templates-contexts ..... 94  
 org-capture-use-agenda-date ..... 119  
 org-catch-invisible-edits ..... 8  
 org-checkbox-hierarchical-statistics ..... 57  
 org-clock-continuously ..... 81, 82, 86  
 org-clock-idle-time ..... 85  
 org-clock-into-drawer ..... 81  
 org-clock-modeline-total ..... 81  
 org-clock-report-include-clocking-task .. 115  
 org-clock-x11idle-program-name ..... 85

org-clocktable-defaults.....	83	org-export-with-entities.....	138
org-closed-keep-when-no-todo.....	52	org-export-with-fixed-width.....	137
org-coderef-label-format.....	131	org-export-with-footnotes.....	138
org-columns-default-format....	70, 87, 116, 127	org-export-with-inlinetasks.....	138
org-columns-skip-archived-trees.....	99	org-export-with-latex.....	133, 138
org-columns-summary-types.....	69	org-export-with-planning.....	138
org-confirm-babel-evaluate.....	225	org-export-with-priority.....	138
org-confirm-elisp-link-function.....	226	org-export-with-properties.....	16, 138
org-confirm-shell-link-function.....	226	org-export-with-section-numbers.....	138
org-create-file-search-functions.....	45	org-export-with-smart-quotes.....	137
org-ctrl-c-ctrl-c-hook.....	239	org-export-with-special-strings.....	137
org-ctrl-k-protect-subtree.....	6	org-export-with-statistics-cookies.....	138
org-cycle-emulate-tab.....	7	org-export-with-sub-superscripts.....	137
org-cycle-global-at-bob.....	7	org-export-with-tables.....	139
org-cycle-include-plain-lists.....	13	org-export-with-tags.....	138
org-cycle-open-archived-trees.....	98	org-export-with-tasks.....	138
org-cycle-separator-lines.....	6	org-export-with-timestamps.....	137
org-deadline-warning-days.....	77, 79	org-export-with-title.....	138
org-default-notes-file.....	89, 91	org-export-with-toc.....	138, 139
org-default-priority.....	55, 227	org-export-with-todo-keywords.....	138
org-display-custom-times.....	77	org-fast-tag-selection-include-todo.....	49
org-display-internal-link-with-indirect- buffer.....	43	org-fast-tag-selection-single-key.....	61
org-disputed-keys.....	234	org-file-apps.....	42, 95
org-done (face).....	50	org-fontify-emphasized-text.....	128
org-edit-footnote-reference.....	17	org-footnote-auto-adjust.....	16, 229
org-edit-src-auto-save-idle-delay.....	195	org-footnote-auto-label.....	16, 229
org-edit-src-turn-on-auto-save.....	195	org-footnote-define-inline.....	16, 229
org-emphasis-alist.....	128	org-footnote-section.....	6, 16
org-emphasis-regexp-components.....	128	org-format-latex-header.....	132, 133
org-enable-table-editor.....	19	org-format-latex-options.....	133
org-enforce-todo-dependencies.....	50, 51	org-from-is-user-regexp.....	94
org-entities-user.....	131	org-global-properties.....	65, 87
org-execute-file-search-functions.....	45	org-goto-auto-isearch.....	8
org-export-allow-bind-keywords.....	139	org-goto-interface.....	9
org-export-async-init-file.....	136	org-group-tags.....	63
org-export-backends.....	135, 179	org-hide (face).....	231
org-export-before-parsing-hook.....	180	org-hide-block-startup.....	16
org-export-before-processing-hook.....	180	org-hide-leading-stars.....	228, 231
org-export-creator-string.....	136, 149	org-hierarchical-todo-statistics.....	56
org-export-date-timestamp-format.....	136	org-highest-priority.....	55, 227
org-export-default-language.....	137	org-html-container-element.....	147
org-export-dispatch-use-expert-ui.....	135	org-html-doctype.....	147, 148
org-export-exclude-tags.....	137	org-html-doctype-alist.....	148
org-export-headline-levels.....	138	org-html-head.....	148, 153
org-export-in-background.....	136	org-html-head-extra.....	148, 153
org-export-initial-scope.....	136	org-html-head-include-default-style.....	153
org-export-preserve-breaks.....	137	org-html-html5-elements.....	149
org-export-select-tags.....	137	org-html-html5-fancy.....	148
org-export-time-stamp-file.....	138, 149	org-html-infojs-options.....	154
org-export-with-archived-trees.....	99, 137	org-html-inline-images.....	151
org-export-with-author.....	137	org-html-link-home.....	147
org-export-with-broken-links.....	137	org-html-link-org-files-as-html.....	150
org-export-with-clocks.....	137	org-html-link-up.....	147
org-export-with-creator.....	138	org-html-mathjax-options.....	147
org-export-with-date.....	138	org-html-postamble.....	149
org-export-with-drawers.....	16, 138	org-html-postamble-format.....	149
org-export-with-email.....	138	org-html-preamble.....	149
		org-html-preamble-format.....	149

- org-html-style-default..... 153
- org-html-table-align-individual-fields.. 150
- org-html-table-caption-above..... 150
- org-html-table-data-tags..... 150
- org-html-table-default-attributes..... 150
- org-html-table-header-tags..... 150
- org-html-table-row-tags..... 150
- org-html-table-use-header-tags-for-first-  
column..... 151
- org-html-tag-class-prefix..... 152
- org-html-todo-kwd-class-prefix..... 152
- org-html-use-infojs..... 154
- org-html-validation-link..... 149
- org-icalendar-alarm-time..... 178
- org-icalendar-categories..... 178
- org-icalendar-combined-agenda-file..... 179
- org-icalendar-include-body..... 179
- org-icalendar-include-todo..... 178
- org-icalendar-store-UID..... 179
- org-icalendar-use-deadline..... 178
- org-icalendar-use-scheduled..... 178
- org-id-link-to-org-use-id..... 41
- org-imenu-depth..... 233
- org-insert-mode-line-in-empty-file..... 3
- org-irc-link-to-logs..... 41
- org-keep-stored-link-after-insertion..... 42
- org-latex-bibtex-compiler..... 154
- org-latex-classes..... 155, 156
- org-latex-compiler..... 154, 155
- org-latex-default-class..... 155, 156
- org-latex-default-packages-alist.... 154, 156
- org-latex-default-table-environment..... 157
- org-latex-default-table-mode..... 157
- org-latex-images-centered..... 159
- org-latex-listings..... 129
- org-latex-listings-options..... 160
- org-latex-minted-options..... 160
- org-latex-packages-alist..... 156
- org-latex-subtitle-format..... 155
- org-latex-subtitle-separate..... 155
- org-latex-tables-booktabs..... 157
- org-latex-tables-centered..... 157
- org-latex-to-mathml-convert-command..... 166
- org-latex-to-mathml-jar-file..... 166
- org-link-abbrev-alist..... 44, 227
- org-link-frame-setup..... 42
- org-link-parameters..... 42
- org-list-allow-alphabetical..... 12
- org-list-automatic-rules..... 13, 14, 56
- org-list-demote-modify-bullet..... 13
- org-list-empty-line-terminates-plain-lists  
..... 13
- org-list-indent-offset..... 13
- org-list-use-circular-motion..... 14
- org-log-done..... 53, 115, 228
- org-log-into-drawer..... 52, 118
- org-log-note-clock-out..... 81, 228
- org-log-refile..... 97
- org-log-repeat..... 79, 228
- org-log-states-order-reversed..... 52
- org-lowest-priority..... 55, 227
- org-M-RET-may-split-line..... 9, 14
- org-md-headline-style..... 161
- org-odd-levels-only..... 106, 228, 232, 245
- org-odt-category-map-alist..... 167
- org-odt-convert..... 163
- org-odt-convert-capabilities..... 168
- org-odt-convert-process..... 168
- org-odt-convert-processes..... 168
- org-odt-create-custom-styles-for-srcblocks  
..... 168
- org-odt-fontify-srcblocks..... 168
- org-odt-pixels-per-inch..... 165
- org-odt-preferred-output-format..... 162, 163
- org-odt-schema-dir..... 173
- org-odt-styles-file..... 162, 163
- org-odt-table-styles..... 170, 172
- org-outline-path-complete-in-steps..... 97
- org-overriding-columns-format..... 127
- org-plain-list-ordered-item-terminator... 12,  
14
- org-popup-calendar-for-date-prompt..... 76
- org-preview-latex-default-process..... 133
- org-priority-faces..... 55
- org-priority-start-cycle-with-default.... 55
- org-property-allowed-value-functions..... 249
- org-publish-project-alist..... 183, 185
- org-publish-use-timestamps-flag..... 193
- org-put-time-stamp-overlays..... 229
- org-read-date-display-live..... 76
- org-read-date-force-compatible-dates..... 76
- org-read-date-prefer-future..... 75
- org-refile-allow-creating-parent-nodes... 97
- org-refile-keep..... 97
- org-refile-targets..... 97
- org-refile-use-cache..... 97
- org-refile-use-outline-path..... 97
- org-remove-highlights-with-change..... 12, 82
- org-replace-disputed-keys..... 234
- org-return-follows-link..... 43
- org-reverse-note-order..... 97
- org-scheduled-delay-days..... 78
- org-show-context-detail..... 11
- org-sort-agenda-noeffort-is-high..... 112
- org-sparse-tree-open-archived-trees..... 98
- org-special-ctrl-a/e..... 6
- org-special-ctrl-k..... 6
- org-speed-commands-user..... 225
- org-startup-align-all-tables..... 23, 227
- org-startup-folded..... 8, 227, 246
- org-startup-indented..... 227
- org-startup-with-inline-images..... 43, 228
- org-startup-with-latex-preview..... 134, 228
- org-store-link-functions..... 238
- org-stuck-projects..... 108
- org-support-shift-select..... 14, 15, 234

org-table-auto-blank-field .....	19	org-track-ordered-property-with-tag ...	50, 58
org-table-copy-increment .....	21	org-treat-insert-todo-heading-as-state-	
org-table-duration-custom-format .....	29	change .....	9
org-table-export-default-format .....	22	org-treat-S-cursor-todo-selection-as-state-	
org-table-formula .....	227	change .....	46
org-table-formula-constants .....	26, 227, 233	org-use-fast-todo-selection .....	46
org-table-use-standard-references .....	24, 31	org-use-property-inheritance .....	67, 179, 201, 248
org-tag-alist .....	60, 229	org-use-speed-commands .....	225
org-tag-faces .....	59	org-use-sub-superscripts .....	132
org-tag-persistent-alist .....	60	org-use-tag-inheritance .....	59
org-tags-column .....	59	org-yank-adjusted-subtrees .....	10
org-tags-exclude-from-inheritance .....	59	org-yank-folded-subtrees .....	10
org-tags-match-list-sublevels ..	59, 63, 67, 106	orgstruct-heading-prefix-regexp .....	18
org-texinfo-classes .....	174, 175		
org-texinfo-coding-system .....	174		
org-texinfo-def-table-markup .....	176		
org-texinfo-default-class .....	174, 175		
org-texinfo-info-process .....	173		
org-time-stamp-custom-formats .....	77		
org-time-stamp-overlay-formats .....	229		
org-time-stamp-rounding-minutes .....	74		
org-todo (face) .....	50		
org-todo-keyword-faces .....	50		
org-todo-keywords .....	46, 47, 105, 230		
org-todo-repeat-to-state .....	79		
org-todo-state-tags-triggers .....	47		

## P

parse-time-months .....	76
parse-time-weekdays .....	76
ps-landscape-mode .....	125
ps-number-of-columns .....	125

## U

user-full-name .....	136
user-mail-address .....	136