

Computer and Robot Vision Homework 8

Noise Removal

資工碩一 張家源 R07922102

使用語言：Python

Gaussian Noise

根據下列公式，更新每個Pixel。

$$I(nim, i, j) = I(im, i, j) + amplitude * N(0,1)$$

$N(0,1)$: Gaussian random variable with zero mean and st. dev. 1

amplitude determines signal-to-noise ratio, try 10, 30

```
def GaussianNoise(img, amp):
    res = np.zeros(img.shape)
    for i in range(img.shape[0]):
        for j in range(img.shape[1]):
            res[i,j] = img[i, j] + amp * np.random.normal(0, 1, 1)
    cv2.imwrite("GaussianNoise{}.jpg".format(str(amp)), res)
    return res
```

Salt-And-Pepper Noise

根據下列公式，更新每個Pixel。

$$I(nim, i, j) = 0 \text{ if } \text{uniform}(0,1) < 0.05$$

$$I(nim, i, j) = 255 \text{ if } \text{uniform}(0,1) > 1 - 0.05$$

$$I(nim, i, j) = I(im, i, j) \text{ otherwise}$$

uniform(0,1): random variable uniformly distributed over [0,1]

try both 0.05 and 0.1

```
def SaltAndPepper(img, threshold):
    res = np.zeros(img.shape)
    for i in range(img.shape[0]):
        for j in range(img.shape[1]):
            if np.random.rand(1) < threshold:
                res[i,j] = 0
            elif np.random.rand(1) > 1-threshold:
                res[i,j] = 255
            else:
                res[i, j] = img[i,j]
    cv2.imwrite("SaltAndPepper{}.jpg".format(str(threshold)), res)
    return res
```

Box Filter

以mask範圍內的平均值更新Pixel。

```
def BoxFilter(img,f_size, noise):
    res = np.zeros(img.shape)
    #===kernel===
    move = []
    steps = [i for i in range(f_size//2, -f_size//2, -1)] #steps. eg:0,1,-1,2...
    for i in steps: #get all movements from steps
        for j in steps:
            move.append((i,j))
    kernel = np.full( (f_size,f_size), 1)
    kernel = kernel/kernel.size #divide by size of kernel
    k_c = f_size//2 #kernel center index
    #===convolution===
    for i in range(img.shape[0]):
        for j in range(img.shape[1]):
            s = 0
            for m in move:
                r = i+m[1] #index after movement
                c = j+m[0]
                if r < 0 or r >= img.shape[0] or c < 0 or c >= img.shape[1]:
                    continue
                s += img[r,c] * kernel[k_c+m[1], k_c+m[0]]
            res[i, j] = s
    cv2.imwrite("BoxFilter{}_{}.jpg".format(str(f_size),str(noise)), res)
```

Median Filter

以mask範圍內的中位數來更新Pixel。

```
def MedianFilter(img,f_size, noise):
    res = np.zeros(img.shape)
    #===kernel===
    move = []
    steps = [i for i in range(f_size//2, -f_size//2, -1)]
    for i in steps: #get all movements from steps
        for j in steps:
            move.append((i,j))
    kernel = np.full( (f_size,f_size), 1)
    k_c = f_size//2 #kernel center index
    #===convolution===
    for i in range(img.shape[0]):
        for j in range(img.shape[1]):
            s = []
            for m in move:
                r = i+m[1] #index after movement
                c = j+m[0]
                if r < 0 or r >= img.shape[0] or c < 0 or c >= img.shape[1]:
                    continue
                s.append(img[r,c] * kernel[k_c+m[1], k_c+m[0]])
            s = np.array(s)
            res[i, j] = np.median(s)
    cv2.imwrite("MedianFilter{}_{}.jpg".format(str(f_size),str(noise)), res)
```

Opening and Closing

根據HW5的Dilation & Erosion實作Opening and Closing。

```
def opening(img, kernel):  
    result = erosion(img, kernel)  
    result = dilation(result, kernel)  
    return result  
  
def closing(img, kernel):  
    result = dilation(img, kernel)  
    result = erosion(result, kernel)  
    return result
```

Result

Noise

Gaussian Noise with amplitude 10



Gaussian Noise with amplitude 30



Salt-And-Pepper with threshold 0.05



Salt-And-Pepper with threshold 0.1



Gaussian Noise with amplitude 10

3x3 Box filter



5x5 Box filter



3x3 Median filter



5x5 Median filter



Opening then Closing



Closing then Opening



Gaussian Noise with amplitude 30

3x3 Box filter



5x5 Box filter



3x3 Median filter



5x5 Median filter



Opening then Closing



Closing then Opening



Salt-And-Pepper with threshold 0.05

3x3 Box filter




5x5 Box filter



3x3 Median filter



5x5 Median filter



Opening then Closing



Closing then Opening



Salt-And-Pepper with threshold 0.1

3x3 Box filter




5x5 Box filter



3x3 Median filter



5x5 Median filter



Opening then Closing



Closing then Opening



SNR

根據定義算出SNR。

$$VS = \frac{\sum_{\forall n} (I(i, j) - \mu)^2}{\|n\|}$$
$$\mu = \frac{\sum_{\forall n} I(i, j)}{\|n\|}$$
$$VN = \frac{\sum (I_N(i, j) - I(i, j) - \mu_N)^2}{\|n\|}$$
$$\mu_N = \frac{\sum_{\forall n} (I_N(i, j) - I(i, j))}{\|n\|}$$
$$SNR = 20 \log_{10} \frac{\sqrt{VS}}{\sqrt{VN}}$$

```
def SNR(img_s , img_n):  
    var_s = np.var(img_s)  
    img_ns = img_n - img_s  
    var_n = np.var(img_ns)  
    return 20*np.log10(np.sqrt(var_s)/np.sqrt(var_n))
```

SNR	Gaussian Noise with amplitude 10	Gaussian Noise with amplitude 30	Salt-and-pepper with threshold 0.05	Salt-and-pepper with threshold 0.1
Box filter 3x3	12.15	4.37	0.99	-2.24
Box filter 5x5	10.36	3.52	0.14	-3.35
Median filter 3x3	12.83	4.40	1.11	-1.76
Median filter 5x5	11.60	3.76	0.95	-1.92
Opening then closing	20.97	15.85	2.68	4.28
Closing then opening	18.26	14.85	1.96	3.49