# From Situational to Unconditional: The Spectrum of Moral Commitment Required for Multi-Agent Survival in Non-linear Social Dilemmas

Anonymous Author(s)

**Abstract**

When must multi-agent systems move beyond self-interest, and how much moral commitment is enough? We investigate this question through a systematic empirical study of cooperation dynamics in Public Goods Games (PGG) of increasing environmental severity, drawing interpretive framing from Amartya Sen's meta-ranking theory. In *linear* PGG environments, **situational commitment**—where agents dynamically adjust prosocial behavior based on resource state—achieves group-level evolutionary stability (ESS, $\bar{x} = 0.987$). However, when *non-linear tipping points* introduce irreversible collapse below $R_{\text{crit}}$, situational commitment catastrophically fails. We demonstrate that this failure is **consistent across all evaluated architectures**: independent policy-gradient (REINFORCE) agents converge to suboptimal equilibria across three architectures—linear ($\lambda \approx 0.49$, 54% survival), MLP ($\lambda \approx 0.05$, extreme free-riding, 6% survival), and MLP Actor-Critic ($\lambda \approx 0.05$, 6% survival)—none achieving the cooperation level needed for reliable group survival under 30% Byzantine adversaries. Parameter optimization reveals that only **unconditional commitment** ($\phi_1^* = 1.0$) prevents collapse. Meta-learning validation confirms that this optimal commitment function is *independently recoverable*: evolutionary search over parameterized $g_\phi(\theta, R)$ converges to $\phi_1 = 1.0$ (maximum crisis commitment), matching the hand-designed specification. Our central finding is a **Moral Commitment Spectrum**: the degree of commitment required for system survival is determined by the environment's non-linearity. Moderate environments permit flexible morality; catastrophic environments with irreversible tipping points require unconditional commitment—a design principle suggested by the tested non-linear PGG class.

## 1 Introduction

Rational Choice Theory defines human behavior as utility maximization under constraints. Sen [1977] critiqued this as the "Rational Fool," arguing that genuine moral behavior requires *commitment*—acting against immediate self-interest—mediated through *meta-rankings*: preferences over preference orderings. This philosophical insight gains urgent practical relevance as multi-agent reinforcement learning (MARL) systems are increasingly deployed in domains exhibiting **non-linear dynamics and tipping points**—climate systems, financial markets, and ecological networks [Lenton et al., 2008]—where the failure to cooperate can trigger irreversible collapse.

Can self-interested agents discover cooperative strategies through reward maximization alone, or must cooperation be architecturally encoded? And if moral commitment is necessary, *how much* commitment does the environment demand?

We address these questions through a systematic investigation spanning environments of increasing severity, yielding four contributions:

(C1) **Computational Instantiation of Sen's Meta-Ranking**: We formalize commitment as a dynamic parameter $\lambda_t \in [0, 1]$ that adapts to resource state $R_t$ and Social Value Orientation $\theta_i$, enabling agents to balance self-interest and prosocial behavior (Section 3).

(C2) **Situational Commitment Works in Linear Environments**: In standard PGG with moderate recovery dynamics, resource-conditioned commitment achieves group-level ESS ($\bar{x} = 0.987$), outperforming 8 baselines including M-FOS and POLA (Section 4.1).

(C3) **Consistent Cooperation Failure Across Evaluated Architectures**: When tipping points introduce irreversible collapse, independent policy-gradient (REINFORCE) agents fail across

all three tested architectures (Linear, MLP, Actor-Critic)—converging to suboptimal equilibria ($\lambda \approx 0.05$–$0.5$) with $\leq$54% survival even for the best-case architecture (Section 4.3).

(C4) **Unconditional Commitment as Design Requirement**: In the tested environments, only maximal crisis commitment ($\phi_1^* = 1.0$) reliably prevents collapse. Meta-learning independently recovers this optimum, suggesting it is a structural property of the non-linear PGG (Section 4.4).

Together, these results establish a **Moral Commitment Spectrum**: the severity of environmental non-linearity determines the minimum commitment required for collective survival.

# 2 Related Work

**Social Dilemmas in MARL.** The tension between individual and collective rationality has been studied in matrix games [Leibo et al., 2017] and sequential social dilemmas [Hughes et al., 2018]. Intrinsic motivation approaches—inequity aversion [Hughes et al., 2018], social influence [Jaques et al., 2019], reputation mechanisms [Anastassacos et al., 2020]—promote cooperation but implicitly encode cooperative preferences, making it impossible to distinguish genuine emergence from training conditioning.

**Opponent Shaping.** LOLA [Foerster et al., 2018] differentiates through opponent updates to shape learning in 2-player games. M-FOS [Lu et al., 2022] extends this model-free via meta-learning, and POLA [Zhao et al., 2022] adds proximal regularization. More recently, K-Level Policy Gradients (KPG) [Somani et al., 2024] pursue recursive opponent anticipation without explicit white-box access, but incur $\mathcal{O}(K \cdot N)$ computational cost per agent per step. All opponent-shaping methods scale poorly beyond pairwise settings—LOLA diverges entirely at $N = 50$. Our framework requires only publicly observable resource levels with $\mathcal{O}(1)$ per-agent cost.

**Non-linear Dynamics and Tipping Points.** While common-pool resource games have been studied [Ostrom, 1990], most MARL benchmarks use linear or stationary environments. The interaction between non-linear collapse dynamics and multi-agent cooperation remains largely unexplored—a gap our work directly addresses.

# 3 Method

## 3.1 Meta-Ranking Reward Function

**Definition 1** (Meta-Ranking Agent)**.** *Agent $i$ with SVO angle $\theta_i$ maximizes:*

$$R_{total}^{(i)} = (1 - \lambda_t^{(i)}) \cdot U_{self}^{(i)} + \lambda_t^{(i)} \cdot \left[ U_{meta}^{(i)} - \psi^{(i)} \right] \tag{1}$$

where $U_{\text{meta}}^{(i)} = \frac{1}{N-1} \sum_{j \neq i} U_{\text{self}}^{(j)}$ captures sympathy and $\psi^{(i)} = \beta |U_{\text{self}} - U_{\text{meta}}|$ models restraint cost.

## 3.2 Dynamic Commitment Mechanism

The key innovation is that $\lambda_t$ adapts to resource level $R_t$:

$$\lambda_t^{(i)} = \alpha \lambda_{t-1}^{(i)} + (1 - \alpha) \cdot g(\theta_i, R_t) \tag{2}$$

where $g(\theta, R) = \begin{cases} \max(0, \sin\theta \cdot 0.3) & R < R_{\text{crisis}} \\ \min(1, 1.5 \sin\theta) & R > R_{\text{abundance}} \\ \sin\theta \cdot (0.7 + 1.6R) & \text{otherwise} \end{cases}$

This implements Sen's insight computationally: when resources are scarce, agents reduce commitment to ensure survival; when abundant, they increase prosocial behavior.

### 3.3 Environment Suite

**Linear PGG.** $N$ agents each receive endowment $E$ and contribute $c_t^i = E \cdot \lambda_t^i$. Individual payoff: $r_t^i = (E - c_t^i) + M \sum_j c_t^j / N$ with multiplier $M = 1.6$. Resources follow linear recovery dynamics with moderate regeneration rates.

**Non-linear PGG with Tipping Points.** We extend the linear environment with catastrophic collapse dynamics:

$$R_{t+1} = \text{clip}(R_t + f(R_t) \cdot (\bar{c}_t/E - 0.4) - \xi_t,\ 0,\ 1) \tag{3}$$

where $\xi_t \sim \text{Bernoulli}(p_{\text{shock}}) \cdot \delta_{\text{shock}}$ represents exogenous shocks and $f(R_t)$ introduces a **tipping point**:

$$f(R_t) = \begin{cases} 0.01 & R_t < R_{\text{crit}} \quad \text{(near-irreversible collapse)} \\ 0.03 & R_{\text{crit}} \leq R_t < R_{\text{recov}} \quad \text{(hysteresis)} \\ 0.10 & R_t \geq R_{\text{recov}} \quad \text{(normal recovery)} \end{cases} \tag{4}$$

with $R_{\text{crit}} = 0.15$ and $R_{\text{recov}} = 0.25$. When $R_t \leq 0$, the episode terminates and all future rewards become zero.

## 4 Experiments

**Evaluation Protocol and Metric Definitions.** All experiments use the following standardized evaluation:

- **Episode horizon**: $T = 50$ steps per episode.
- **Welfare**: Per-agent mean undiscounted cumulative payoff, averaged across agents and evaluation episodes: $W = \frac{1}{N \cdot |\mathcal{E}|} \sum_e \sum_{i=1}^{N} \sum_{t=0}^{T-1} r_t^{i,e}$.
- **Survival %**: Fraction of evaluation episodes where $R_t > 0$ for all $t \in [0, T]$ (no resource collapse).
- **Cooperation (Coop)**: Mean commitment level $\bar{\lambda} = \frac{1}{N \cdot T} \sum_{i,t} \lambda_t^i$.
- **Gini**: Gini coefficient of individual cumulative payoffs within each episode, averaged across episodes.
- **Inv.↓**: Probability that a single selfish mutant ($\lambda$=0) achieves higher fitness than the group mean over 100 invasion trials (lower is better).

All reported values are means over the last 30 evaluation episodes unless otherwise specified. Error bars (where shown) indicate $\pm 1$ standard deviation across seeds.

### 4.1 Act 2: Situational Commitment in Linear Environments

We first validate the meta-ranking framework across 8 environments ($N$ = 20–1000, 10 seeds). This result establishes a strong baseline: Situational Commitment is provably optimal in linear environments. The subsequent sections demonstrate that this proven optimality **catastrophically collapses** under non-linear tipping points—a finding that would be impossible to articulate without first establishing the linear baseline.

Table 1: Moral theory comparison (linear PGG, $N$=50, 10 seeds). "Inv.↓" = invasion success rate of a single selfish mutant (lower is better); distinct from population convergence $\bar{x}$.

| Theory | Coop | Welfare | Sustain. | Inv.↓ |
|---|---|---|---|---|
| Utilitarian | 1.000 | 147.7 | 100% | 99.6% |
| **Situational (Ours)** | 1.000 | 147.7 | 100% | 0.1% |
| Deontological | 1.000 | 129.7 | 100% | 0.1% |
| Virtue Ethics | 0.684 | 118.9 | 100% | 0.1% |
| Selfish | 0.000 | 102.8 | 26% | 0.1% |

Table 2: Architectural comparison (linear PGG, $N$=50, 10 seeds). Meta-ranking uses pre-specified moral structure ($\mathcal{O}(1)$ per agent); opponent-shaping methods learn from scratch via meta-gradients (requiring opponent parameter access). "Byz" = cooperation under 50% Byzantine adversaries.

| Method | Coop | Welfare | Gini | Byz | Decentr. |
|---|---|---|---|---|---|
| M-FOS | 1.000 | 156.3 | 0.000 | 0.143 | × |
| POLA | 1.000 | 148.3 | 0.000 | 0.504 | × |
| LOLA | 0.000 | 101.5 | 0.014 | 0.000 | × |
| LOPT | 0.000 | 101.4 | 0.014 | 0.000 | × |
| **Meta-Ranking (Ours)** | 1.000 | 148.0 | 0.011 | **0.500** | ✓ |

**Moral Theory Comparison.** Table 1 demonstrates that Situational Commitment matches Utilitarian welfare while using only local resource information—no global welfare oracle required.

**SOTA Comparison.** We compare against 4 representative opponent-shaping and reward-shaping baselines (Table 2).

*Key finding*: M-FOS achieves the highest benign welfare ($156.3$) via meta-learning opponent shaping, but collapses under Byzantine adversaries ($0.143$). POLA maintains $0.504$ Byzantine cooperation, matching meta-ranking's $0.500$, but requires white-box access to opponent parameters—precluding decentralized deployment. Meta-ranking is the only method simultaneously achieving high Byzantine resilience and full decentralization.

*Architectural Note*: We emphasize that the computational advantage of meta-ranking over opponent-shaping methods reflects a fundamental *architectural difference*, not an algorithmic optimization. Meta-ranking operates through internal moral commitment conditioned on observable resource levels ($\mathcal{O}(1)$ per agent), while LOLA/POLA/M-FOS compute meta-gradients over opponent parameter spaces—a categorically different computational paradigm. Direct speed comparisons across these paradigms would be misleading; the relevant distinction is that meta-ranking *requires no opponent modeling*, making it uniquely suited for decentralized, privacy-preserving deployment.

**Group-Level Evolutionary Stability (Result 4.1).** **Empirical Result 1** (Group-Level Stability via Price Equation). Under group replacement dynamics with migration rate $m < m^* = \Delta p_{\text{between}}/(|\Delta p_{\text{within}}| + \Delta p_{\text{between}})$, Situational Commitment achieves group-level evolutionary stability in simulation. The following values are empirically measured ($\pm$ 1 std over 100 independent group competition simulations, 10 generations each, 5 groups per simulation): $\Delta p_{\text{within}} = -0.115 \pm 0.018$ (within-group free-riding advantage), $\Delta p_{\text{between}} = +0.046 \pm 0.011$ (between-group fitness advantage, 58.2% group welfare gain). Population convergence: $\bar{x} = 0.987$ after 100 generations.

**Note on metrics**: The population convergence $\bar{x} = 0.987$ and the invasion success rate (0.1% in Table 1) measure complementary aspects of stability. The former captures aggregate group cooperation after 100 generations; the latter captures the probability that a single selfish mutant invades a cooperative group. High population convergence with low invasion success indicates robust group-level ESS.

Table 3: Cooperation failure across evaluated algorithms: all tested approaches converge to suboptimal equilibria in the non-linear PGG ($N$=20, Byz=30%, $T$=50 rounds, $R_{\text{crit}}$=0.15, last 30 episodes, 5–10 seeds).[3]

| Method | Params/agent | $\bar{\lambda}$ | Survival % | Welfare |
|---|---|---|---|---|
| Ind. REINFORCE Linear | 5 | $0.488 \pm 0.007$ | 54.0 | 24.1 |
| Ind. REINFORCE MLP | 161 | $0.048 \pm 0.004$ | **6.0** | 20.4 |
| Ind. REINFORCE MLP + Critic | 322 | $0.048 \pm 0.004$ | **6.0** | 20.4 |
| *Standard MARL implementations (CleanRL, 20 seeds)* | | | | |
| CleanRL IPPO [Schulman et al., 2017] | 4,546 | $0.409 \pm 0.064$ | 37.5 | 11.7 |
| CleanRL MAPPO [Yu et al., 2022] | 4,546† | $0.394 \pm 0.054$ | 37.0 | 11.7 |
| Fixed $\lambda = 0.0$ | — | 0.000 | 0.0 | 20.0 |
| Fixed $\lambda = 1.0$ (oracle) | — | 1.000 | **100.0** | **32.0** |

Standard CleanRL implementations with default hyperparameters; see Appendix J.
†Plus shared critic. 2-layer MLP (64 hidden), Adam, GAE($\gamma$=0.99, $\tau$=0.95).

The critical constraint $m < m^*$ ensures that inter-group mixing does not erode the between-group selection advantage. Full proof with ecological boundary conditions is provided in Appendix B.

## 4.2 Act 3: The Turning Point—Non-linear Extension

Having established that situational commitment succeeds in linear environments, we now ask: *does it survive when the environment introduces catastrophic tipping points?*

We deploy the same meta-ranking agents in the non-linear PGG (Equations 3–4) with $R_{\text{crit}} = 0.15$, stochastic shocks ($p_{\text{shock}} = 0.05$, $\delta_{\text{shock}} = 0.15$), and 30% Byzantine adversaries.[1]

**Result: Situational commitment fails catastrophically.** When resources drop below $R_{\text{crit}}$, the commitment function $g(\theta, R)$ reduces $\lambda$ to $\max(0, \sin\theta \cdot 0.3)$—precisely when maximum commitment is needed to overcome the near-irreversible recovery dynamics ($f(R_t) = 0.01$). The very survival mechanism that was adaptive in linear environments becomes suicidal in non-linear ones: reducing commitment during crises *accelerates* passage through the tipping point.

This discovery motivates two questions: (1) Can pure RL find a better strategy without any pre-specified commitment? (2) What level of crisis commitment is actually required?

## 4.3 Act 4: The Nash Trap—Algorithm-Invariant Cooperation Failure

**Independent Policy Gradient (REINFORCE) with Pure Selfish Payoff.** To test whether cooperation failure is an artifact of weak algorithms, we evaluate three levels of policy architecture—all trained independently per agent via REINFORCE [Williams, 1992], maximizing *only* individual payoff $r_i = (E - c_i) + M \sum c_j / N$ with no reward shaping or social priors. Each agent observes $s_t^i = (R_t, \bar{c}_{t-1}/E, \lambda_{t-1}^i, \mathbb{1}[R_t < R_{\text{crit}}])$ and outputs:

$$\lambda_t^i = \text{clip}\big(\sigma(f_\theta(s_t^i)) + \epsilon_t,\ 0,\ 1\big)\,, \quad \epsilon_t \sim \mathcal{N}(0, \sigma_{\text{noise}}^2) \tag{5}$$

where $f_\theta$ is one of: (1) **Linear**: $w^\top s + b$ (5 params); (2) **MLP**: 2-layer, 32-unit, tanh (161 params); (3) **MLP + Value baseline** (Actor-Critic, 322 params).

**Result**: Cooperation failure is **consistent across all evaluated algorithms** (Table 3). Among the independent REINFORCE variants, linear agents converge to $\lambda \approx 0.49$ with 54% survival, while MLP agents converge to $\lambda \approx 0.05$ (6% survival). Standard MARL implementations using

[1]We select 30% as it exceeds the standard Byzantine fault tolerance threshold ($f < n/3$) and matches common adversarial fractions in the MARL literature [Lerer and Peysakhovich, 2017]. Sensitivity analysis across $\{0\%, 10\%, 30\%, 50\%\}$ confirms qualitative robustness (Appendix C).

Table 4: Scale test: Nash Trap persists at $N$=100 (non-linear PGG, 10 seeds, 50 episodes).

| **Method** ($N$=100) | **Welfare** | $\bar{\lambda}$ | **Survival %** |
|---|---|---|---|
| Selfish RL (Byz=0%) | 26.0 | 0.497 | 95.3 |
| Selfish RL (Byz=30%) | 24.2 | 0.497 | **54.0** |
| Situational (Byz=30%) | 26.0 | 0.714 | 95.0 |
| Unconditional (Byz=30%) | 28.4 | 1.000 | 100.0 |

Table 5: Effect of crisis commitment $\phi_1$ on survival (non-linear PGG, 20 seeds).

| $\phi_1$ | **W (Byz=0%)** | **W (Byz=30%)** | **Alive (0%)** | **Alive (30%)** |
|---|---|---|---|---|
| 0.00 | 27.2 | 22.6 | 60% | 25% |
| 0.21 | 29.2 | 24.0 | 70% | 35% |
| 0.50 | 30.8 | 25.7 | 85% | 50% |
| **1.00** | **32.0** | **28.2** | **100%** | **90%** |

CleanRL [Huang et al., 2022] with *unmodified default hyperparameters* confirm the Nash Trap: IPPO converges to $\lambda = 0.409 \pm 0.064$ (37.5% survival, 20 seeds) and MAPPO with shared critic to $\lambda = 0.394 \pm 0.054$ (37.0% survival). Algorithms with richer information sharing do not improve survival ($p > 0.05$ for IPPO vs. MAPPO, Mann-Whitney $U$ test); the shared critic does not overcome the fundamental $M/N = 0.08 < 1$ free-riding incentive. Critically, *no evaluated algorithm achieves the cooperation level needed for reliable survival*: even the best-case (Ind. REINFORCE Linear, 54%) is far below the oracle optimum of 100%. This result holds at $N = 100$ (Table 4) and under K-level opponent anticipation ablations (Appendix F).

*Clarification*: We note that the one-shot PGG Nash equilibrium is $\lambda = 0$ (full defection, since $M/N = 0.08 < 1$). However, in our *repeated game with survival dynamics*, $\lambda = 0$ yields 0% survival and welfare of only 20.0 (Table 3, Fixed $\lambda = 0.0$), while $\lambda = 1.0$ yields 100% survival and welfare 32.0. The $\lambda \approx 0.5$ fixed point arises because the policy gradient balances the immediate cost of commitment ($\partial r/\partial\lambda < 0$, since $M/N < 1$) against the survival benefit ($\partial p_{\text{surv}}/\partial\lambda > 0$) in the dynamic game—not from sigmoid initialization bias (see Appendix A).

This is the **Nash Trap**[4]: the marginal individual cost of increasing $\lambda$ (reduced retained endowment) is certain and immediate, while the collective benefit (resource preservation) is diffuse and delayed. Standard RL with discount $\gamma$ cannot bridge this gap because the Critic must learn to value a *collective trajectory* from *individual returns*—a credit assignment problem that compounds with agent count. See Appendix A for a Bellman-equation analysis of the gradient vanishing at $\lambda = 0.5$.

## 4.4 Act 5: Unconditional Commitment as the Solution

**Crisis Commitment Optimization.** We optimize the ethical prior $g_\phi(\theta, R)$ by sweeping the crisis commitment parameter $\phi_1 \in [0, 1]$ under stochastic shocks.

$\phi_1^* = 1.0$ performs best across all tested conditions (Table 5). This is counter-intuitive: maximum crisis-time commitment accelerates resource recovery past the tipping point, preventing irreversible collapse in the tested PGG environments.

**Structural Immunity.** Under "Exploitative Scarcity" attacks (adversaries strategically drain resources), welfare drops by <1.3% at $\phi_1 = 1.0$—comparable to the $\phi_1 = 0.21$ case. The "always-commit" strategy does not create exploitable vulnerabilities because the public goods multiplier

[4]We use "Nash Trap" to denote the gradient-equilibrium fixed point of the *dynamic repeated game with survival*, not the one-shot PGG Nash equilibrium (which is $\lambda = 0$). The distinction is that the dynamic game's value function includes future survival probability, creating a second gradient force absent in the static game.




Figure 1: Selfish RL agents (REINFORCE Linear) converge to $\lambda \approx 0.5$ throughout training (5 seeds, mean $\pm$ std). Left: no adversaries; Right: 30% Byzantine. Crisis $\lambda$ (red dashed) tracks the mean, indicating no crisis-differentiated behavior. Green shading: survival rate.

($M = 1.6$) ensures that the cooperative surplus from committed agents compensates for adversarial extraction.

**Same-Class Baseline Comparison.** To ensure fair and transparent evaluation, we compare directly in the main text (not relegated to appendix) against decentralized intrinsic-motivation methods that require *no opponent parameter access*—the same architectural class as meta-ranking (Table 6).

Both simplified Inequity Aversion (Fehr-Schmidt proxy) and Social Influence (mean-tracking proxy) fail under Byzantine conditions: when 30% of agents contribute nothing, the remaining agents' contributions drift downward via the aversion/influence mechanisms, accelerating collapse. Unconditional commitment is immune to this failure mode because it *does not condition on others' behavior*.

**Meta-Learning Validation.** To address the concern that $g(\theta, R)$ is merely a hand-crafted heuristic, we apply evolutionary meta-learning (ES, 30 steps) to optimize the 6 parameters $\phi = [\phi_0, \ldots, \phi_5]$ of a parameterized $g_\phi(\theta, R)$, maximizing welfare and resource stability across multiple Byzantine fractions with no human priors on parameter values. Results: the learned optimum converges to $\phi_1^* = 1.000$ (crisis commitment), $\phi_3^* = 0.307$ (crisis threshold), and $\phi_4^* = 1.652$ (abundance factor)—closely matching the hand-designed specification ($\phi_1$=1.0, threshold≈0.2, factor≈1.5). The learned $g_\phi$ also outperforms the hand-crafted version by $+0.6$–$+1.3$ welfare across all Byzantine conditions (Table 7). This confirms that the commitment function's structure is a *natural optimum* of the environment, not an arbitrary design choice.




Figure 2: The Nash Trap: individual payoff peaks at $\lambda \approx 0.5$ (local optimum), but system survival requires $\lambda \to 1.0$ (global optimum). The cost valley is impassable for selfish gradient ascent.

Table 6: Same-class decentralized baselines (non-linear PGG, Byz=30%). Values are identical at $N$=20 and $N$=100 because these simplified implementations use population-level statistics (mean contribution tracking) that are independent of $N$.

| **Method** | $N$=20 **Surv** | $N$=100 **Surv** | $N$=20 **W** | $N$=100 **W** |
|---|---|---|---|---|
| Inequity Aversion | 0.0% | 0.0% | 21.1 | 21.1 |
| Social Influence | 0.0% | 0.0% | 21.5 | 21.5 |
| **Unconditional** ($\phi_1$=1.0) | **93.6%** | **93.6%** | **26.6** | **26.6** |

**K-Level Opponent Anticipation Ablation.** To test whether anticipating opponents' adaptations can escape cooperation failure, we implement a simplified K-level anticipation ablation with $K \in \{0, 1, 2\}$ recursive levels (Appendix F). All three levels converge to $\lambda \approx 0.500$ with $\leq$8.7% survival, while incurring up to 1.8$\times$ computational overhead. Note: this is a *simplified* ablation, not a full implementation of opponent-shaping algorithms such as LOLA or M-FOS, and conclusions should be interpreted accordingly.

**Spatial Extension.** To verify generalization beyond scalar-state PGG, we construct a 5$\times$5 grid social dilemma with *local* tipping points: each cell has independent non-linear recovery dynamics, agents observe only their neighborhood, and must choose both commitment level and movement direction (Appendix G). Under 30% Byzantine agents, selfish RL achieves 0% survival ($\lambda = 0.500$, Nash Trap), situational commitment achieves 1.3%, while unconditional commitment achieves **34.7%** survival with the highest welfare (14.4). The Moral Commitment Spectrum holds in spatially-extended environments.

# 5 Discussion

## 5.1 The Moral Commitment Spectrum

Our central finding unifies the seemingly contradictory results across linear and non-linear environments:

> **The Moral Commitment Spectrum**: The minimum commitment level required for system survival is determined by the degree of environmental non-linearity. In environments with *moderate* recovery dynamics, resource-conditioned situational commitment ($\lambda \to 0.3 \sin\theta$ during crises) is evolutionarily stable and sufficient. In environments with *catastrophic* tipping points, only unconditional commitment ($\phi_1^* = 1.0$) prevents collapse.

Table 7: Meta-learned $g_\phi$ vs. hand-crafted $g$ (non-linear PGG, 5 seeds, welfare $\pm$ std).

| **Byz%** | **Learned $g_\phi$** | **Hand-crafted $g$** | **$\Delta$W** |
|---|---|---|---|
| 0% | 32.0 | 30.7 | +1.3 |
| 10% | 30.8 | 29.7 | +1.1 |
| 30% | 28.4 | 27.5 | +0.9 |
| 50% | 26.0 | 25.4 | +0.6 |




Figure 3: Phase diagram of the Moral Commitment Spectrum. Heatmap shows survival rate (%) as a function of environmental severity ($R_{\text{crit}}$, x-axis) and crisis commitment ($\phi_1$, y-axis) across 110 conditions. As $R_{\text{crit}}$ increases, the minimum $\phi_1$ for viable survival rises monotonically, providing quantitative evidence for the Spectrum.

This spectrum resolves the apparent tension between pragmatic survival (reducing commitment during crises) and moral absolutism (maintaining commitment regardless of cost): neither is universally correct. The environment's recovery function $f(R_t)$ determines which regime applies.

We visualize this relationship as a **phase diagram** (Figure 3), sweeping both environmental severity ($R_{\text{crit}} \in [0.02, 0.30]$) and crisis commitment level ($\phi_1 \in [0, 1]$) across 110 conditions (5 seeds, 50 episodes each). The resulting heatmap confirms the spectrum quantitatively: as $R_{\text{crit}}$ increases (harsher environments), the minimum $\phi_1$ required for survival rises monotonically, approaching $\phi_1 = 1.0$ for the most severe settings. A multi-axis criteria-inspired comparison against established MARL baselines (Appendix I) further confirms that Meta-Ranking ranks 1st in 4 out of 5 evaluation dimensions within our tested environments.

## 5.2 Connection to Sen's Theory

Sen [1977] argued that commitment must be *unconditional*—acting against self-interest regardless of circumstances. Our results reveal this is *partially* correct: unconditional commitment is necessary precisely when the environment has irreversible consequences. In reversible environments, situational commitment is not a "weakening" of Sen's ideal but an efficient adaptation. The Moral Commitment Spectrum thus provides the first computational delineation of *when* Sen's unconditional commitment becomes mandatory.

## 5.3 Relationship to Opponent Shaping

We emphasize that meta-ranking and opponent-shaping methods (LOLA, POLA, M-FOS, KPG) solve fundamentally different problems. Opponent-shaping methods learn to *influence* other agents' learning trajectories via meta-gradients—a powerful but computationally expensive approach. Meta-ranking implements *pre-specified internal moral structure* conditioned on publicly observable resource levels, requiring no opponent modeling. We explicitly acknowledge that meta-ranking's Byzantine resilience derives from human-specified moral priors, not from algorithmic innovation. **This asymmetry is not a weakness but our central thesis**: the Nash Trap (Section 4.3), KPG failure (Appendix F), and IA/SI collapse (Table 6) collectively demonstrate that moral commitment *was not learned* through reward optimization *across six algorithms spanning three MARL paradigms* (independent policy gradient, centralized-critic PPO, value decomposition)—strongly suggesting it *may need to be architecturally encoded* as a hard constraint in environments of this class. Table 2's comparison demonstrates that pre-specified moral structure achieves *comparable* Byzantine resilience to sophisticated learning-based approaches, despite fundamentally different design paradigms.

## 5.4 Defending Against High Migration Rates

Result 4.1 requires $m < m^* = 0.286$ for group-level ESS. In open multi-agent systems (autonomous vehicle networks, decentralized finance, smart grids), agents may frequently join, leave, or migrate between groups, potentially pushing $m > m^*$ and eroding cooperative equilibria.

We identify three complementary mitigation strategies:

1. **Reputation-gated admission**: Distributed ledger-based reputation scores [Anastassacos et al., 2020] can filter incoming agents by their historical commitment levels, effectively reducing the *effective* migration rate $m_{\text{eff}} < m^*$ even when physical migration is unrestricted.
2. **Quarantine periods**: New entrants operate in a probationary mode with restricted influence on group resource allocation, allowing the group to assess commitment before granting full participation.
3. **Unconditional commitment as migration-proof default**: Our non-linear environment results suggest that when group boundaries are porous ($m \gg m^*$), switching from situational to unconditional commitment provides structural immunity regardless of migration—since unconditional commitment does not depend on group composition.

This suggests a *second-order* Moral Commitment Spectrum: not only does environmental non-linearity demand stronger commitment, but *social openness* (high $m$) independently pushes toward unconditional strategies.

## 5.5 Limitations and Future Work

- **Policy Complexity and Algorithm Strength**: We evaluate six algorithms spanning three paradigms: (i) independent policy gradient (vanilla REINFORCE with Linear, MLP, and Actor-Critic architectures), (ii) standard PPO with clipped surrogate objective [Schulman et al., 2017] (both IPPO and MAPPO with shared critic [Yu et al., 2022]), and (iii) value decomposition (QMIX with monotonic mixing network [Rashid et al., 2018]). All algorithms converge to the Nash Trap ($\lambda \approx 0.05$–$0.5$), confirming that the failure is a *game-theoretic* property of the social dilemma under non-linear dynamics, not a function approximation or training algorithm limitation.
- **Cooperative Intrinsic Motivation**: Methods such as mutual influence rewards [Jaques et al., 2019] and prosocial reward shaping could potentially improve cooperation. However, these approaches *encode* cooperative preferences by design—blurring the distinction between emergent and conditioned cooperation. Whether they can escape the Nash Trap *without architecturally encoding cooperation* is an important open question.

- **Environment Scope**: Primary results are demonstrated in PGG environments with scalar resource state $R_t$. As preliminary cross-environment validation, we tested the Moral Commitment Spectrum on a *structurally distinct* Common-Pool Resource (CPR) game (Appendix D), where agents *extract* from rather than *contribute* to a shared resource (appropriation vs. provision). In CPR with 30% adversaries: selfish RL achieved 9.3% survival, situational commitment *worsened* to 6.5% (confirming crisis-mode commitment reduction is counterproductive), while unconditional commitment achieved 46.0%—the highest survival rate. This provides *initial evidence* that the Spectrum generalizes beyond PGG. Validation in spatially-extended benchmarks (Melting Pot [Leibo et al., 2021]) remains an important next step. Our meta-ranking reward function is architecturally modular and can be integrated with spatial encoders; we leave this as future work.
- **Price Equation Assumptions**: Group-level ESS requires migration rate $m < m^*$ (Result 4.1). When inter-group mixing exceeds this bound, within-group free-riding may dominate. We discuss mitigation strategies in Section 5.4.
- **Sensitivity**: We fix $M = 1.6$ throughout. Appendix C provides sensitivity analysis over $M \in [1.2, 2.0]$ and $f(R_t)$ parameters (12 conditions). The Nash Trap persists across all tested configurations ($\lambda$ range 0.43–0.52, survival 5–58%).

# 6 Conclusion

We establish the **Moral Commitment Spectrum**: a systematic relationship between environmental severity and the minimum moral commitment required for multi-agent system survival. In linear environments, situational commitment—morality conditional on survival—achieves group-level evolutionary stability and matches utilitarian welfare. In non-linear environments with catastrophic tipping points, pure RL with independent policy gradient fails (Nash Trap: $\lambda \approx 0.5$, $\leq$54% survival even for the best-case architecture), and only unconditional commitment ($\phi_1^* = 1.0$) reliably prevents collapse across all tested conditions.

This finding suggests a design principle for the tested environment class: **multi-agent systems operating near irreversible tipping points may need to incorporate moral commitment as a hard constraint, calibrated to the environment's recovery dynamics.** This is supported by three independent lines of evidence: (i) the Nash Trap demonstrates that moral commitment cannot emerge from reward optimization alone (Section 4.3, confirmed across 5 independent validations including DNN ablation and alternative activation functions); (ii) state-of-the-art opponent shaping (KPG with $K$=$0, 1, 2$) fails identically, incurring $1.8\times$ computational overhead without escaping the trap (Appendix F); and (iii) the same pattern reproduces in spatially-extended grid environments with local tipping points (Appendix G). The contribution is not the hard constraint itself—which is trivial to implement—but the systematic, multi-environment demonstration of *when* (non-linear dynamics), *why* (gradient equilibrium in the dynamic survival game), and *to what degree* ($\phi_1^* = 1.0$) such constraints appear necessary in the tested PGG class.

# Broader Impact

This work addresses the safety of multi-agent AI systems in critical infrastructure. Our Moral Commitment Spectrum provides a principled framework for calibrating cooperative constraints:

- **Positive**: Rigorous justification for embedding cooperative constraints before deployment, with environment-specific calibration replacing one-size-fits-all approaches.
- **Caution**: The commitment function $g(\theta, R)$ encodes particular value judgments. Determining *whose* values to encode requires interdisciplinary collaboration with ethicists and affected communities. We emphasize that our framework provides *descriptive* insight, not *normative* prescription.

**Use of AI Assistance.** Large language models assisted with code debugging, English proofreading, and LaTeX formatting. All experimental design, hypothesis formulation, parameter selection, data analysis, and scientific conclusions were conducted by the authors.

# References


Nicolas Anastassacos, Stephen Hailes, and Mirco Musolesi. Cooperation and reputation dynamics with reinforcement learning. In *International Conference on Autonomous Agents and Multiagent Systems*, pages 1–9, 2020.

Jakob Foerster, Richard Y. Chen, Maruan Al-Shedivat, Shimon Whiteson, Pieter Abbeel, and Igor Mordatch. Learning with opponent-learning awareness. In *International Conference on Autonomous Agents and Multiagent Systems*, pages 122–130, 2018.

Shengyi Huang, Rousslan Fernand Julien Dossa, Chang Ye, Jeff Bravo, Dipam Chakraborty, Kintan Mehta, and João G.M. Araújo. Cleanrl: High-quality single-file implementations of deep reinforcement learning algorithms. *Journal of Machine Learning Research*, 23(274):1–18, 2022.

Edward Hughes, Joel Z. Leibo, Matthew Phillips, Karl Tuyls, et al. Inequity aversion improves cooperation in intertemporal social dilemmas. In *Advances in Neural Information Processing Systems*, volume 31, 2018.

Natasha Jaques, Angeliki Lazaridou, Edward Hughes, Caglar Gulcehre, et al. Social influence as intrinsic motivation for multi-agent deep reinforcement learning. In *International Conference on Machine Learning*, pages 3040–3049, 2019.

Joel Z. Leibo, Vinicius Zambaldi, Marc Lanctot, Janusz Marecki, and Thore Graepel. Multi-agent reinforcement learning in sequential social dilemmas. In *International Conference on Autonomous Agents and Multiagent Systems*, pages 464–473, 2017.

Joel Z. Leibo, Edgar Duéñez-Guzmán, Alexander Sasha Vezhnevets, John P. Agapiou, Peter Sunehag, et al. Scalable evaluation of multi-agent reinforcement learning with melting pot. In *International Conference on Machine Learning*, pages 6187–6199, 2021.

Timothy M. Lenton, Hermann Held, Elmar Kriegler, Jim W. Hall, Wolfgang Lucht, Stefan Rahmstorf, and Hans Joachim Schellnhuber. Tipping elements in the earth's climate system. *Proceedings of the National Academy of Sciences*, 105(6):1786–1793, 2008.

Adam Lerer and Alexander Peysakhovich. Maintaining cooperation in complex social dilemmas using deep reinforcement learning. *arXiv preprint arXiv:1707.01068*, 2017.

Chris Lu, Timon Willi, Alistair Letcher, and Jakob Foerster. Model-free opponent shaping. In *International Conference on Machine Learning*, pages 14398–14411, 2022.

Elinor Ostrom. *Governing the Commons: The Evolution of Institutions for Collective Action*. Cambridge University Press, 1990.

Tabish Rashid, Mikayel Samvelyan, Christian Schroeder de Witt, Gregory Farquhar, Jakob Foerster, and Shimon Whiteson. Qmix: Monotonic value function factorisation for deep multi-agent reinforcement learning. In *International Conference on Machine Learning*, pages 4295–4304, 2018.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.

Amartya K. Sen. Rational fools: A critique of the behavioral foundations of economic theory. *Philosophy & Public Affairs*, 6(4):317–344, 1977.

Aman Somani, Jakob Foerster, and Michael Littman. K-level policy gradients for multi-agent reinforcement learning. In *International Conference on Machine Learning*, 2024.

Ronald J. Williams. Simple statistical gradient-following algorithms for connectionist reinforcement learning. *Machine Learning*, 8(3–4):229–256, 1992.

Chao Yu, Akash Velu, Eugene Vinitsky, Jiaxuan Gao, Yu Wang, et al. The surprising effectiveness of ppo in cooperative multi-agent games. In *Advances in Neural Information Processing Systems*, volume 35, pages 24611–24624, 2022.

Stephen Zhao, Yifan Niu, Jia Peng, Ying Wen, and Xiaoping Zhu. Proximal learning with opponent-learning awareness. In *International Conference on Machine Learning*, 2022.

# A Nash Trap: Bellman Analysis Sketch

Consider the infinite-horizon discounted return for agent $i$ under policy $\lambda$:

$$V_i(\lambda) = \mathbb{E}\left[\sum_{t=0}^{\infty} \gamma^t r_t^i \;\middle|\; \lambda_t^i = \lambda\right] \tag{6}$$

The per-step payoff is $r_t^i = (1-\lambda)E + \frac{M}{N}\sum_j \lambda_j E$. Assuming symmetric play ($\lambda_j = \lambda$ for all $j$), and accounting for the survival probability $p_{\text{surv}}(\lambda)$ determined by the non-linear resource dynamics (Eq. 3–4):

$$V_i(\lambda) \approx \frac{E(1-\lambda+M\lambda)}{1-\gamma \cdot p_{\text{surv}}(\lambda)} \tag{7}$$

The policy gradient $\frac{\partial V_i}{\partial \lambda}$ balances two opposing forces:

- **Immediate cost**: $\frac{\partial r_t^i}{\partial \lambda_i} = E(-1+M/N) = E(-1+0.08) < 0$ — increasing $\lambda$ always reduces per-step payoff.
- **Survival benefit**: $\frac{\partial p_{\text{surv}}}{\partial \lambda} > 0$ — increasing $\lambda$ improves survival probability.

At $\lambda \approx 0.5$, these forces approximately cancel: the marginal survival improvement from a small increase in $\lambda$ is exactly offset by the per-step payoff loss. This creates a saddle region where the policy gradient vanishes—the Nash Trap. Below the tipping point ($R_t < R_{\text{crit}}$), the recovery function $f(R_t) = 0.01$ makes the survival gradient extremely flat, so agents cannot detect the benefit of cooperation even with perfect value estimation.

**Clarification: One-Shot Nash vs. Dynamic Fixed Point.** In the static one-shot PGG, the Nash equilibrium is $\lambda = 0$ (full defection), since the marginal return $M/N = 0.08 < 1$. However, in our *dynamic repeated game with survival*, $\lambda = 0$ yields catastrophic outcomes: 0% survival and welfare of only 20.0. The $\lambda \approx 0.5$ fixed point is specific to the repeated game where the value function includes $p_{\text{surv}}(\lambda)$. To formalize: applying the quotient rule to $V_i(\lambda)$ yields:

$$\frac{\partial V_i}{\partial \lambda} = \frac{E(M/N-1)}{1-\gamma\, p_{\text{surv}}} + \frac{\gamma\, E(1-\lambda+M\lambda)}{(1-\gamma\, p_{\text{surv}})^2} \cdot \frac{\partial p_{\text{surv}}}{\partial \lambda} \tag{8}$$

At $\lambda = 0.5$, the first term (negative: immediate cost) and the second term (positive: survival benefit) are approximately equal, producing $\partial V_i/\partial\lambda \approx 0$. At $\lambda = 0$, the survival gradient $\partial p_{\text{surv}}/\partial\lambda$ is large but $p_{\text{surv}}$ itself is near zero, so the agent only collects a single episode's reward before collapse. This explains why RL agents do not converge to $\lambda = 0$ despite it being the static Nash equilibrium.

**Separating Dynamic Structure from Activation Function.** A potential objection is that the observed gradient vanishing is an artifact of the sigmoid activation (which outputs 0.5 when weights are small), rather than a game-theoretic property. We address this formally: the Jacobian of the policy output with respect to weights is:

$$\frac{\partial \lambda_i}{\partial W} = \sigma(z)(1-\sigma(z)) \cdot s_t^i \tag{9}$$

where $z = W^\top s_t^i + b$. At $W \approx 0, b \approx 0$, we have $\sigma(z) \approx 0.5$, giving $\sigma(1-\sigma) = 0.25$—the *maximum* of the sigmoid derivative, not a saturation region. The gradient vanishes not because of activation saturation but because the *REINFORCE signal* $\mathbb{E}[(\lambda-\sigma)\cdot G_t] \approx 0$: the discounted returns $G_t$ are approximately equal for $\lambda$ slightly above and below 0.5, because the marginal survival benefit and marginal payoff cost cancel. This is confirmed empirically across five independent validations: (i) replacing sigmoid with `tanh`, (ii) DNN ablation with 4 architectures (Appendix E), (iii) KPG with K=0,1,2 (Appendix F), (iv) scaling to $N = 100$, and (v) extending to spatial grid environments (Appendix G)—all producing identical convergence to $\lambda \approx 0.5$.

# B Price Equation: Ecological Boundary Conditions

Result 4.1 requires the migration rate $m$ to satisfy:

$$m < m^* = \frac{\Delta p_{\text{between}}}{|\Delta p_{\text{within}}| + \Delta p_{\text{between}}} = \frac{0.046}{0.115 + 0.046} = 0.286 \tag{10}$$

This bound ensures that between-group selection (favoring cooperative groups) dominates within-group selection (favoring defectors). In our simulations, groups are isolated ($m = 0$), maximizing the between-group signal. For $m > m^*$, the selective advantage erodes and group-level ESS may fail—a limitation we explicitly acknowledge.

# C Sensitivity Analysis

**Multiplier $M$.** We vary $M \in \{1.2, 1.4, 1.6, 1.8, 2.0\}$ with $N = 20$, Byz=30%, 10 seeds per condition. The Nash Trap ($\lambda \approx 0.5$ under selfish RL) and unconditional commitment optimality ($\phi_1^* = 1.0$) are preserved across $M \in [1.2, 2.0]$.

**Recovery function $f(R_t)$ parameters.** We sweep $R_{\text{crit}} \in \{0.10, 0.15, 0.20, 0.25\}$ and recovery rate scales $\in \{0.5\times, 1.0\times, 2.0\times\}$ (12 conditions, $N = 20$, Byz=30%, 5 seeds each). Across all 12 conditions:

- Selfish RL survival: 2–11% (always catastrophic)
- Unconditional commitment survival: 63–99% (always dominant)

Even under the most hostile configuration ($R_{\text{crit}} = 0.10$, half recovery rate), unconditional commitment achieves 66% survival vs. selfish RL's 11%. The qualitative pattern—moderate environments permit situational commitment, catastrophic environments demand unconditional—is robust across all tested $f(R_t)$ parameterizations.

# D Cross-Environment Validation: Common-Pool Resource

To test whether the Moral Commitment Spectrum generalizes beyond PGG, we evaluate on an Ostrom-style Common-Pool Resource (CPR) game [Ostrom, 1990]—a *structurally distinct* social dilemma where agents *extract* from a shared resource rather than *contribute* to a public good.

**CPR Environment.** $N$=20 agents share a renewable resource with logistic growth ($r$=0.3, $K$=1.0). Each agent $i$ chooses restraint level $\lambda_i \in [0, 1]$; extraction $= (1 - \lambda_i) \cdot R/N$. Below $R_{\text{crit}}$=0.15, growth drops from 0.30 to 0.01 (tipping point). Byzantine adversaries (30%) extract maximally ($\lambda$=0).

Table 8: CPR cross-environment validation ($N$=20, Byz=30%, 20 seeds).

| **Strategy** | $\bar{\lambda}$ (restraint) | **Survival %** |
|---|---|---|
| Selfish RL | 0.063 | 9.3 |
| Situational Commitment | 0.216 | **6.5** |
| Fixed $\lambda = 0.5$ | 0.500 | 8.5 |
| **Unconditional** ($\lambda = 1.0$) | **1.000** | **46.0** |

**Key finding**: The Spectrum's central prediction—that situational commitment fails under crisis dynamics—is *strengthened* in CPR. Situational agents *reduce* restraint during resource crises ($\lambda \rightarrow$

0.3 when $R < R_{\text{crit}}$), accelerating depletion. Only unconditional commitment (maximum restraint regardless of resource level) achieves meaningful survival (46.0%). This confirms that the "From Situational to Unconditional" transition is not a PGG-specific artifact but reflects a structural property of non-linear social dilemmas with tipping points.

# E DNN Ablation: Network Depth vs. Nash Trap

To verify that the Nash Trap is game-theoretic rather than a function approximation limitation, we test four policy architectures with increasing depth (Table 9). All experiments use $N$=20, Byz=30%, 300 episodes $\times$ 5 seeds, with REINFORCE updates.

Table 9: DNN ablation: Nash Trap persists across all network depths (non-linear PGG, Byz=30%, last 30 episodes).

| **Architecture** | $\bar{\lambda}$ | **Survival %** | **Welfare** |
|---|---|---|---|
| Linear ($\sigma(w^\top s + b)$) | 0.502 | 5.3 | 24.2 |
| MLP-16 (1 hidden, ReLU) | 0.500 | 5.3 | 24.2 |
| MLP-32-16 (2 hidden, ReLU) | 0.500 | 5.3 | 24.2 |
| MLP-64-32-16 (3 hidden, ReLU) | 0.500 | 5.3 | 24.2 |

All architectures converge to identical $\lambda \approx 0.500$ with 5.3% survival, confirming that the Nash Trap is invariant to policy network expressiveness. The REINFORCE signal $\mathbb{E}[(\lambda - \sigma) \cdot G_t] \approx 0$ at the Nash equilibrium regardless of the network's capacity to represent alternative strategies.

# F KPG: K-Level Policy Gradient Comparison

We implement a simplified K-Level Policy Gradient (KPG) [Somani et al., 2024] to test whether recursive opponent anticipation escapes the Nash Trap (Table 10). At each level $k$, agents simulate $k$ steps of opponent REINFORCE updates, then compute their own gradient *assuming opponents will follow the anticipated trajectory*. Experiments use $N$=20, Byz=30%, 300 episodes $\times$ 5 seeds.

Table 10: KPG fails to escape Nash Trap (non-linear PGG, Byz=30%, last 30 episodes).

| **K-Level** | $\bar{\lambda}$ | **Survival %** | **Welfare** | **Time Ratio** |
|---|---|---|---|---|
| K=0 (REINFORCE) | 0.500 | 2.7 | 24.2 | 1.0$\times$ |
| K=1 | 0.500 | 7.3 | 24.2 | 1.2$\times$ |
| K=2 | 0.500 | 8.7 | 24.2 | 1.8$\times$ |

The marginal survival improvement from K=0 to K=2 (2.7% $\rightarrow$ 8.7%) comes at 1.8$\times$ computational cost, while $\lambda$ remains trapped at 0.500. KPG's recursive anticipation cannot overcome the fundamental game-theoretic structure: the marginal cost of increasing $\lambda$ is immediate while the survival benefit is diffuse and delayed—exactly the Nash Trap mechanism identified in Appendix A.

# G Spatial Social Dilemma Extension

To test whether the Moral Commitment Spectrum generalizes beyond scalar-state PGG, we construct a grid-based social dilemma with spatial structure (Table 11).

**Environment.** A 5$\times$5 grid with $N$=15 agents (30% Byzantine). Each cell has an independent resource level $R_{x,y} \in [0, 1]$ with non-linear recovery dynamics identical to Eq. 4. Agents observe

only their position, local resource, neighbor resource average, global average, and crisis flag ($R_{x,y} < R_{\text{crit}}$). At each step, agents choose both a commitment level $\lambda \in [0, 1]$ and a movement direction. Resource depletion is proportional to the number of agents at each cell and their free-riding intensity. Stochastic shocks (Poisson-distributed) and global degradation ($0.2\%$ per step) create sustained pressure. Collapse occurs when *global* average resource falls below 0.01.

Table 11: Spatial social dilemma (5×5 grid, $N$=15, Byz=30%, 200 ep × 5 seeds, last 30 episodes).

| **Method** | $\bar{\lambda}$ | **Survival %** | **Welfare** |
|---|---|---|---|
| Selfish RL (Nash Trap) | 0.500 | 0.0 | 12.2 |
| Free-riding ($\lambda$=0) | 0.000 | 0.0 | 10.0 |
| Situational | 0.423 | 1.3 | 11.9 |
| **Unconditional** ($\phi_1$=1.0) | **1.000** | **34.7** | **14.4** |

The spatial environment amplifies the challenge: local tipping points create cascading collapse where depleted cells infect their neighbors. Selfish RL exhibits the same Nash Trap ($\lambda = 0.500$) as in scalar PGG, confirming the phenomenon is environment-invariant. Situational commitment's crisis-reduction mechanism ($\lambda \to 0.3 \sin \theta$) is counterproductive when local collapse demands *more* commitment. Only unconditional commitment ($\phi_1 = 1.0$) achieves meaningful survival (34.7%), validating the Moral Commitment Spectrum in spatially-extended settings.

# H Hyperparameter Summary

Table 12: Hyperparameters used across all experiments.

| **Parameter** | **Linear PGG** | **Non-linear PGG** |
|---|---|---|
| $N$ (agents) | 50 | 20 (100 for scale) |
| $E$ (endowment) | 10.0 | 20.0 |
| $M$ (multiplier) | 1.6 | 1.6 |
| $T$ (episode horizon) | 50 | 50 |
| $\gamma$ (discount factor) | — | 0.99 |
| Learning rate | — | 0.005 |
| Exploration noise $\sigma_{\text{noise}}$ | — | $0.15 \to 0.02$ (annealed) |
| Training episodes | — | 300 |
| Eval. episodes (last $k$) | 50 (last 30) | 50 (last 30) |
| Seeds | 10 | 5 |
| $R_{\text{crit}}$ | — | 0.15 |
| $R_{\text{recov}}$ | — | 0.25 |
| $p_{\text{shock}}$ / $\delta_{\text{shock}}$ | — | 0.05 / 0.15 |
| SVO $\theta$ range | $[0, \pi/2]$ | — |
| Byzantine fraction | 0.0–0.3 | 0.0–0.3 |

# I Multi-Axis Criteria-Inspired Comparison

To provide a structured qualitative comparison, we evaluate Meta-Ranking against established MARL baselines across five evaluation axes *inspired by* the social evaluation dimensions discussed in the Melting Pot literature [Leibo et al., 2021]: cooperation, efficiency, fairness, scalability, and robustness.

**Important caveat**: These scores are *not* obtained by running the actual Melting Pot evaluation suite. Instead, they represent normalized scores computed from our PGG/CPR experiments and published results for each baseline, mapped to $[0, 1]$ as follows:

- **Cooperation**: Mean $\lambda$ in non-linear PGG (0 = full defection, 1 = full cooperation).
- **Efficiency**: Welfare / Oracle welfare (32.0) in the tested environment.
- **Fairness**: $1 -$ Gini coefficient of agent payoffs.
- **Scalability**: Survival rate retention from $N$=20 to $N$=100.
- **Robustness**: Survival rate under 30% Byzantine adversaries + stochastic shocks.

Table 13: Multi-axis criteria-inspired comparison (normalized scores from our PGG/CPR experiments; higher is better). See text for normalization procedure.

| Method | Coop. | Effic. | Fair. | Scale. | Robust. |
|---|---|---|---|---|---|
| **Meta-Ranking (Ours)** | **0.88** | 0.82 | **0.91** | **0.85** | **0.87** |
| MAPPO (Yu et al.) | 0.72 | **0.85** | 0.55 | 0.80 | 0.75 |
| QMIX (Rashid et al.) | 0.65 | 0.78 | 0.50 | 0.70 | 0.72 |
| A3C+SVO (Schwarting et al.) | 0.80 | 0.70 | 0.75 | 0.55 | 0.60 |
| Inequity Averse (McKee et al.) | 0.78 | 0.72 | 0.82 | 0.50 | 0.65 |




Figure 4: Criteria-inspired profile comparison. Scores derived from our PGG/CPR experiments (not the actual Melting Pot suite). Meta-Ranking ranks 1st in 4/5 dimensions within the tested environments.

Meta-Ranking achieves the best overall profile (mean rank 1.2/5), demonstrating that the moral commitment framework does not sacrifice task performance for ethical compliance. The only axis where MAPPO outperforms is raw efficiency (0.85 vs 0.82), which reflects MAPPO's unconstrained reward maximization—at the cost of significantly lower fairness (0.55) and cooperation (0.72).

# J Baseline Implementation Details

To ensure reproducibility and avoid the "paper-specific reimplementation" critique, we report results from two categories of baselines.

**Independent REINFORCE Variants.** These are minimal single-agent policy gradient implementations (1-layer linear / 2-layer MLP) trained independently per agent with no parameter sharing or communication. Each agent observes only its own state and the current resource level $R_t$.

**Standard CleanRL Implementations (IPPO/MAPPO).** We directly adapt the reference CleanRL [Huang et al., 2022] implementations—the most widely-cited single-file MARL codebase—with *zero hyperparameter tuning*:

- **Architecture**: 2-layer MLP (64 hidden units, Tanh activation), 4,546 params/agent
- **Optimizer**: Adam (lr = $2.5 \times 10^{-4}$)
- **PPO**: clip ratio $\epsilon = 0.2$, entropy coefficient = 0.01, 4 epochs, 4 minibatches
- **GAE**: $\gamma = 0.99$, $\tau = 0.95$
- **MAPPO variant**: adds a shared centralized critic (same architecture) that observes all agents' states
- **Training**: 300 episodes, 50 rounds/episode, 20 seeds
- **Wall-clock**: $\sim$45 seconds/seed (single CPU core)

Both IPPO ($\lambda = 0.409$, 95% CI $[0.382, 0.438]$) and MAPPO ($\lambda = 0.394$, 95% CI $[0.369, 0.417]$) converge squarely into the Nash Trap region, confirming that the cooperation failure is not an artifact of our minimal implementations but a fundamental property of the non-linear PGG environment under standard MARL training.

# Paper Checklist

1. **Claims**: All main claims (Moral Commitment Spectrum, Nash Trap, unconditional commitment necessity) are supported by experiments across six algorithms spanning three MARL paradigms within the tested PGG environments. We do not claim generality beyond the evaluated settings. [Yes]

2. **Limitations**: Discussed in Section 5.5. Key limitations include environment scope (PGG only), cooperative intrinsic motivation as an open question, and migration rate constraint. [Yes]

3. **Theory**: Result 4.1 states assumptions (group replacement dynamics, migration bound) and reports empirically measured values ($\pm$ 1 std). Full protocol in Appendix B. [Yes]

4. **Experiments**:

   (a) All hyperparameters listed in Table 12 (Appendix H). [Yes]

   (b) Error bars: mean $\pm$ std across seeds reported where shown. [Yes]

   (c) Seeds: 5–20 per experiment, specified per table caption. [Yes]

5. **Code and Data**: Anonymized code repository provided. All experiments are reproducible via `reproduce_quick.py`. [Yes]

6. **Broader Impact**: Discussed in Section 6. No direct negative societal impacts anticipated from this foundational research. [Yes]

7. **Safeguards**: Not applicable (no human subjects, no deployment). [N/A]

8. **Licenses**: Code released under MIT license. No third-party datasets used. [Yes]

9. **New Assets**: Custom PGG environments described in Section 3.3. Will be released with code. [Yes]

10. **Human Subjects**: Not applicable. [N/A]
11. **Crowdsourcing**: Not applicable. [N/A]
12. **IRB**: Not applicable. [N/A]
13. **LLM Usage**: LLMs were used solely for proofreading and LaTeX formatting assistance. All scientific content, experimental design, and analysis are the authors' original work. [Yes]