# WhyLab: A Causal Safety Monitoring Framework for Stable Self-Improving Agents

**Anonymous Author(s)**
Affiliation
Address
email

## Abstract

Self-improving AI agents that refine strategies through feedback loops risk *cognitive policy oscillation*—a failure mode where hallucinated or spuriously correlated feedback causes strategy degradation below the pre-improvement baseline. Existing causal inference tools (DoWhy, EconML) provide rigorous offline estimation but do not address online safety monitoring in noisy agent environments.

We present WhyLab, a causal safety monitoring framework comprising: **(C1)** an information-theoretic drift index for detecting distributional shifts; **(C2)** a sensitivity filter combining E-values and partial $R^2$ bounds to reject fragile successes; and **(C3)** a Lyapunov-bounded adaptive damping controller.

On SWE-bench Lite (300 real-world coding problems), the C2 sensitivity filter maintains **zero regressions** across 10,500 episodes with only 1.4 percentage-point pass-rate cost. C1 and C3 are validated in controlled synthetic experiments: C1 detects distributional drift 11.7% earlier than uniform monitoring; C3 prevents energy divergence ($10^{11}\times$ reduction vs. uncontrolled updates). On static agent benchmarks (HumanEval, SWE-bench), C1 and C3 operate transparently—as expected, since these benchmarks lack the non-stationarity and continuous parameter updates they target.

## 1 Introduction

Autonomous AI agents that refine their strategies through feedback loops Shinn et al. [2023], Yao et al. [2023] represent a powerful paradigm for continuous improvement. However, when hallucinated or spuriously correlated feedback accumulates, the agent's policy oscillates between contradictory strategies—a phenomenon we term *cognitive policy oscillation*—silently degrading performance below the pre-improvement baseline.

Preventing oscillation requires solving three intertwined challenges: (1) *drift detection*—distinguishing genuine distributional shifts from normal variance (§3.1); (2) *effect filtering*—identifying improvements that are causally robust rather than spuriously confounded (§3.2); and (3) *step-size control*—bounding update magnitude to prevent oscillation without causing learning deadlock under heavy-tailed noise (§3.3). Existing tools Sharma and Kiciman [2022], Battocchi et al. [2019] address parts of this problem in isolation but do not provide an online safety framework for continuously operating agents.

We present **WhyLab**, a causal safety monitoring framework with three contributions: **C1** Information-theoretic drift detection (§3.1)—an entropy-weighted index providing early warning for environmental shifts; **C2** Sensitivity-aware effect filtering (§3.2)—E-values and partial $R^2$

Submitted to 39th Conference on Neural Information Processing Systems (NeurIPS 2025). Do not distribute.




Figure 1: WhyLab causal safety monitoring framework. Instead of uncritically accepting potentially hallucinated updates ($\hat{g}_t$) that cause cognitive oscillation, proposed updates are routed through a safety monitoring layer. **C1** detects environmental drift, **C2** filters out fragile successes lacking unmeasured-confounder robustness, and **C3** adapts the step size to bound the Lyapunov energy of the policy. Unsafe updates are rejected, preserving the status quo.

bounds that gate fragile successes; and **C3** Lyapunov-bounded adaptive damping (§3.3)—a controller with provable energy non-increase guarantees.

On SWE-bench Lite Jimenez et al. [2024] (300 real-world coding problems), the C2 sensitivity filter maintains zero regressions across 10,500 episodes. A non-stationary online learning experiment (E6) shows all three components contributing independently: C3 reduces energy by 49%, C2 reduces oscillation by 76%, and C1 cuts drift detection delay by 16%.

## 2 Problem Formulation

Consider an autonomous agent with strategy parameter $\theta_t \in \mathbb{R}^d$ at discrete time $t$. The agent observes a reward signal $R_t$ and updates its strategy via:

$$\theta_{t+1} = \theta_t - \zeta_t \hat{g}_t \tag{1}$$

where $\hat{g}_t = g_t + \omega_t$ is a noisy gradient estimate, $g_t = \nabla_\theta L(\theta_t)$ is the true causal gradient, and $\omega_t$ represents noise from LLM judgment uncertainty, hallucinated feedback, and environmental drift.

**Failure mode.** When $\omega_t$ is large relative to $g_t$ (e.g., due to hallucination), the update (1) may move $\theta_t$ *away* from the optimum $\theta^*$. If this occurs repeatedly, the policy oscillates: $\theta_t$ alternates between contradictory strategies, and the Lyapunov energy $V(\theta_t) = \frac{1}{2}\|\theta_t - \theta^*\|^2$ increases monotonically.

**Desiderata.** A causal audit system should provide: (D1) early detection of distributional drift that inflates $\|\omega_t\|$; (D2) filtering of causally fragile signals before they enter the gradient estimate; and (D3) a provably stable update rule that guarantees $\mathbb{E}[\Delta V] \leq 0$ under realistic noise conditions.

## 3 Method

### 3.1 C1: Information-Theoretic Drift Index

**Definition 1** (Drift Index)**.** *Given $K$ audit signal streams $S_1, \ldots, S_K$ (e.g., verdict consistency, ATE stability, confidence calibration) with Shannon entropies $H(S_i)$, define uncapped weights $\tilde{w}_i \propto 1/(H(S_i) + \epsilon)$. The final weights are obtained by projecting onto the capped simplex:*

$$w = \Pi_{\{w \geq 0,\ \sum_i w_i = 1,\ w_i \leq w_{\max}\}}(\tilde{w}) \tag{2}$$

*with $w_{\max} = 0.6$ and $\epsilon = 0.1$. The drift index is:*

$$DI = \sum_{i=1}^{K} w_i \cdot d_i \tag{3}$$

*where $d_i = JSD(P_i^{(t)} \| P_i^{ref})$ is the Jensen–Shannon divergence of stream $i$ from its reference (pre-shift) distribution. We fix $k$=10 histogram bins per stream for reproducibility. A drift alarm is raised when $DI > \tau$, where $\tau$ is calibrated on pre-shift data at a fixed false-positive rate (FPR $= 0.05$).*

**Intuition.** Low-entropy (highly concentrated) streams carry more information per observation and receive higher weights. The capped simplex projection (2) ensures that no single stream receives weight exceeding $w_{\max}$, even after normalization.

**Proposition 1** (Detection advantage under inactive projection)**.** *Assume the projection* (2) *is inactive (i.e., all uncapped weights satisfy $\tilde{w}_i \leq w_{\max}$). Under a single-stream shift of magnitude $\delta$ in stream $S_j$ with $H(S_j) < H(S_i)$ for all $i \neq j$, the entropy-weighted DI satisfies $DI_{entropy} > DI_{uniform}$ whenever $H(S_j) + \epsilon < \overline{H + \epsilon}_{HM}$, the harmonic mean of $\{H(S_i) + \epsilon\}_{i=1}^{K}$.*

### 3.2 C2: Sensitivity-Aware Effect Filtering

Not all positive treatment effects are causally robust. We combine two complementary sensitivity measures to filter fragile evidence before it influences strategy updates.

**Definition 2** (Approximate E-value for continuous outcomes VanderWeele and Ding [2017])**.** *For a continuous outcome, we compute an approximate E-value using the standard mean-difference conversion VanderWeele and Ding [2017]: the standardized effect $d = ATE/\sigma_{pooled}$ (in the agent context, ATE is the observed episode effect $\Delta R_t$) is converted to an approximate risk-ratio scale via $RR \approx \exp(0.91 \cdot d)$, yielding:*

$$E = RR + \sqrt{RR \cdot (RR - 1)} \tag{4}$$

*An unobserved confounder must associate with both treatment and outcome at $RR \geq E$ to nullify the observed effect.*

**Robustness Value.** We complement the E-value with the robustness value $RV_q$ of Cinelli & Hazlett Cinelli and Hazlett [2020], which quantifies the minimum strength (in partial $R^2$ terms) an unobserved confounder must have to reduce the effect below threshold $q$. The formal definition is given in Appendix J.

**Filtering rule.** A decision is classified as *robust* only if $E > E_{\min}$ (default 2.0) *and* $RV_q > RV_{\min}$ (default 0.1). Decisions failing *either* threshold are excluded from the gradient estimate $\hat{g}_t$ in Eq. (1), reducing the effective noise in $\omega_t$.

### 3.3 C3: Lyapunov-Bounded Adaptive Damping

We derive a sufficient condition for stable strategy updates.

**Assumptions.**

(A1) *Local gradient alignment:* $\langle \theta_t - \theta^*, g_t \rangle > 0$ (the true gradient points toward the optimum).

(A2) *Zero-mean residual noise:* $\mathbb{E}[\omega_t] = 0$ after C2 filtering (see Appendix A for discussion of residual bias).

(A3) *Finite second moment:* $\mathbb{E}[\|\omega_t\|^2] < \infty$.

**Theorem 1** (Sufficient condition for stable updates)**.** *Under assumptions (A1)–(A3), let $\theta_t$ follow the update* (1) *with Lyapunov energy $V(\theta_t) = \frac{1}{2}\|\theta_t - \theta^*\|^2$. Then $\mathbb{E}[\Delta V] \leq 0$ if:*

$$\zeta_t \leq \zeta_{\max} = \frac{2\langle \theta_t - \theta^*, g_t \rangle}{\mathbb{E}[\|\hat{g}_t\|^2]} \tag{5}$$

*Proof sketch.* Expanding $V(\theta_{t+1}) - V(\theta_t) = -\zeta_t \langle \theta_t - \theta^*, \hat{g}_t \rangle + \frac{\zeta_t^2}{2}\|\hat{g}_t\|^2$ and taking expectations under (A2) yields a quadratic in $\zeta_t$ that is non-positive when $\zeta_t \leq \zeta_{\max}$. Full proof in Appendix A.

**Connection to C1 and C2.** The denominator $\mathbb{E}[\|\hat{g}_t\|^2] = \|g_t\|^2 + \mathbb{E}[\|\omega_t\|^2]$ increases when drift is high (large $DI$ from C1) or evidence is fragile (large sensitivity uncertainty from C2). Thus, $\zeta_{\max}$ automatically tightens under adverse conditions, forming a unified feedback control loop.

**Practical controller.** Since the inner product $\langle \theta_t - \theta^*, g_t \rangle$ and $\mathbb{E}[\|\hat{g}_t\|^2]$ in (5) are not directly observable, we use an EMA-smoothed proxy:

$$\hat{\zeta}_t^{\text{raw}} = \frac{2\|\hat{g}_t\|}{\hat{m}_{2,t} + \delta}, \quad \hat{m}_{2,t} = \beta\, \hat{m}_{2,t-1} + (1-\beta)\|\hat{g}_t\|^2 \tag{6}$$

$$\bar{\zeta}_t = \beta\, \bar{\zeta}_{t-1} + (1-\beta)\, \hat{\zeta}_t^{\text{raw}}, \quad \zeta_t = \text{clip}(\bar{\zeta}_t,\ \epsilon_{\text{floor}},\ \mathcal{C}) \tag{7}$$

where $\hat{m}_{2,t}$ is the EMA second-moment estimate of $\|\hat{g}_t\|^2$, $\beta$=0.9, and $\delta$=$10^{-10}$. The numerator $2\|\hat{g}_t\|$ replaces the unobservable inner product; the EMA smoothing provides implicit regularization that prevents the per-step bound from being brittle under stochastic fluctuations (validated in §5.3).

**Floor-ceiling constraint.** When noise $\omega_t$ is heavy-tailed (e.g., Student-$t$ with low degrees of freedom), assumption (A3) may be violated and $\zeta_{\max} \to 0$, causing learning deadlock. As a practical safeguard, Eq. (7) enforces:

$$\zeta_t \in [\epsilon_{\text{floor}}, \mathcal{C}] \quad \text{where } \epsilon_{\text{floor}} = 0.01,\ \mathcal{C} = 0.8 \tag{8}$$

This maintains nonzero step sizes even under high noise variance, at the cost of losing the theoretical guarantee of Theorem 1. We analyze this trade-off in Appendix E.

**Observable energy proxy.** Since $\theta^*$ is unknown in practice, we monitor an observable proxy: $\hat{V}_t = \frac{1}{2}(R_{\max} - R_t)^2$ where $R_{\max}$ is a rolling EMA upper bound ($\alpha = 0.1$). Theorem 1 validates the control rule analytically in parameter space; experiments (§5.3) test whether the observable proxy $\hat{V}_t$ tracks the predicted stabilization behavior consistently with the theory.

**Proposition 2** (Proxy Fidelity)**.** *Let $V_t = \frac{1}{2}\|\theta_t - \theta^*\|^2$ be the true Lyapunov energy and $\hat{V}_t = \frac{1}{2}(R_{\max} - R_t)^2$ the observable proxy. If (i) the reward signal $R_t$ is monotone in $\|\theta_t - \theta^*\|$ (i.e., closer parameters yield higher reward), and (ii) the hallucination rate $h > 0$ introduces additive perturbations to $R_t$ with variance $\sigma_h^2 \propto h$, then:*

$$\rho_S(\hat{V}_t, V_t) \geq \rho_0 + c \cdot h \tag{9}$$

*where $\rho_S$ denotes Spearman rank correlation, $\rho_0$ is the base correlation under zero hallucination, and $c > 0$ is a constant depending on the signal-to-noise ratio of the controller.*

**Intuition.** Under higher hallucination rates, the agent's updates exhibit larger variance, making the energy landscape more "rugged" for the proxy to track. Paradoxically, this increased variance *improves* rank correlation because the proxy's deviations from $V_t$ become dominated by the larger signal fluctuations rather than measurement noise. Empirical validation (§5.3, 200 seeds $\times$ 8 conditions) confirms $\hat{\rho}_0 = 0.49 \pm 0.04$ and $\hat{c} \approx 0.46$, yielding $\rho_S \geq 0.72$ at $h$=0.5—precisely where the audit layer is most needed.

# 4 System Overview

The three contributions are deployed as a lightweight audit layer that wraps the agent's decision loop: the agent's output stream passes through drift detection (C1), sensitivity filtering (C2), and Lyapunov-bounded damping (C3) before updating the strategy parameter $\theta_t$. During initial deployment, all components operate in *shadow mode*—logging audit decisions without modifying the live strategy—to validate calibration before production activation. A transactional outbox ensures zero data loss under API quota throttling, and a cost-aware circuit breaker caps evaluation spend. Implementation details are in the supplementary material.

# 5 Experiments

We evaluate each contribution through experiments designed to directly validate the theoretical claims. Each contribution is validated by a dedicated experiment: C1 by within-horizon detection rates at matched FPR (E1, §5.1), C2 by fragile-rate reduction and fragile-success rejection (E2, §5.2), and C3 by Lyapunov-violation frequency and proxy–state alignment (E3a, §5.3; heavy-tail analysis in Appendix E).

Table 1: Within-horizon detection rate (%) at matched FPR $= 5\%$, across 40 seeds (bootstrap 95% CI in brackets). Higher is better. ADWIN uses a speed-optimized variant (single-split budget-bounded scan) rather than the full adaptive-window algorithm of Bifet and Gavaldà [2007].

| **Severity** | **C1 (ours)** | **B4: Uniform** | **B5: ADWIN** |
|---|---|---|---|
| Mild | 2.5 [0, 8] | 0.0 | 0.0 |
| Moderate | **20.0** [8, 33] | 12.5 [3, 23] | 2.5 [0, 8] |
| Severe | **40.0** [25, 55] | 32.5 [18, 48] | 30.0 [15, 45] |




Figure 2: Kaplan–Meier cumulative detection curves for severe shifts (40 seeds). C1 (solid blue) detects shifts earlier and more frequently than uniform (dashed orange) and ADWIN (dotted green). Lower $S(t)$ indicates faster, more reliable detection.

### 5.1 E1: Drift Detection Performance

We evaluate C1 (entropy-weighted drift index) against uniform aggregation (B4) and ADWIN (B5) as online distributional shift detectors in a multistream setting. Each run observes $K$=3 heterogeneous streams (low/mid/high entropy) for 1000 steps, with a shift injected at $t$=300. All detectors are calibrated to a matched false-positive rate of 5%, and detection is declared within a 700-step post-change budget.

At matched FPR, C1 achieved higher within-horizon detection rates than both baselines across all evaluated severities (Table 1). Bootstrap 95% CIs (seed resampling, $n$=10,000) confirm that the moderate C1–ADWIN gap is statistically reliable (McNemar mid-$p = 0.008$), while the severe C1–uniform gap is directionally consistent but CIs overlap (mid-$p = 0.125$; McNemar details in supplementary). Mild shifts remained largely below the detection horizon for all methods.

The Kaplan–Meier curves (Figure 2) confirm that C1 detects severe shifts both earlier and more frequently than uniform and ADWIN baselines. Due to conservative thresholding (FPR $= 5\%$), a large fraction of runs remained censored under mild shifts; censoring analysis is provided in Appendix D.2.

### 5.2 E2: Sensitivity Filtering

We test whether the dual-threshold filter (C2) reliably separates genuine from fragile causal estimates. We generate a synthetic observational study with a known hidden confounder $U$ that inflates the naïve treatment effect. For each of 40 seeds, we estimate ATE via OLS, compute E-values using Def. 2, and compute the robustness value $RV_q$ following Appendix J. We compare four strategies—no filter, E-value only, $RV_q$ only, and C2 (E+$RV_q$)—sweeping thresholds over $E \in [1.0, 5.0]$ and $RV_q \in [0.01, 0.5]$.

The two axes capture complementary information: E-values measure effect *magnitude* (standardized by outcome variability $\sigma_{\text{pooled}}$), while $RV_q$ measures statistical *precision* (normalized by regression SE). Table 2 reports optimal operating points under two recall regimes, applying the same selection rule (minimize fragile rate) to all filters. Under the high-recall regime (recall $\geq 0.9$), the $RV_q$ axis dominates: $RV_q$-only and C2 both reduce fragile rate from 33.5% (E-only) to 28.7%, demonstrating

Table 2: Filtering performance under two operating regimes from the threshold sweep (40 seeds, mean over synthetic observational studies). For each regime, the operating point minimizing fragile rate is selected per filter. E-values: $d = |ATE|/\sigma_{\text{pooled}}$; $RV_q$: $f_q = |\hat{\beta}|/\text{SE}$.

| Regime | Filter | Frag. rate ↓ | Recall ↑ | Frag. rej. ↑ | Retention |
|---|---|---|---|---|---|
| Recall≥0.9 | No filter | 0.403 | 1.000 | 0.000 | 1.000 |
| | E-only ($E$≥1.5) | 0.335 | 0.963 | 0.312 | 0.813 |
| | $RV_q$-only ($RV_q$≥0.50) | 0.287 | 0.939 | 0.475 | 0.718 |
| | **C2** ($E$≥1.0, $RV_q$≥0.50) | **0.287** | 0.939 | **0.475** | 0.718 |
| Recall≥0.5 | No filter | 0.403 | 1.000 | 0.000 | 1.000 |
| | E-only ($E$≥2.5) | 0.134 | 0.677 | 0.873 | 0.387 |
| | $RV_q$-only ($RV_q$≥0.50) | 0.287 | 0.939 | 0.475 | 0.718 |
| | **C2** ($E$≥2.5, $RV_q$≥0.15) | **0.134** | 0.677 | **0.873** | 0.387 |




Figure 3: E2 threshold sweep: (a) fragile rate vs. recall Pareto frontier and (b) fragile rejection vs. retention. Each marker represents one (E, $RV_q$) threshold pair.

that $RV_q$ captures fragile estimates that E-value alone misses. Under the high-precision regime (recall $\geq$ 0.5), the E-value axis dominates: E-only and C2 both achieve 13.4% fragile rate and 87.3% fragile rejection. Across both regimes, C2 matches or exceeds the better of the two single-axis filters, confirming that the dual-threshold design never degrades performance while providing a *robustness envelope* that guards against the failure mode of either axis alone.

**Refutation tests.** To confirm that the robust/fragile separation is not an artifact of threshold sweeping, we conduct three standard refutation tests following the DoWhy workflow Sharma and Kiciman [2022]: (i) adding a random common cause $Z \sim \mathcal{N}(0,1)$ to the estimator, (ii) replacing treatment with a placebo $T_{\text{rand}} \sim \text{Bernoulli}(0.5)$, and (iii) re-estimating on five 80% data subsets. Reliable scenarios pass all three refuters at high rates (data subset 98.6%, random CC 97.4%), while fragile scenarios fail disproportionately (placebo pass rate 28.9–36.2%). The full per-scenario breakdown is in Appendix G, Table 10. These results confirm that C2's causal signals withstand standard refutation perturbations, addressing the identification concern raised for observational causal claims VanderWeele and Ding [2017], Cinelli and Hazlett [2020].

### 5.3 E3a: Stability Validation

We validate the Lyapunov stability framework (C3) in a stationary quadratic environment with fixed optimum $\theta^* = 0$ and $A = \text{diag}(1, 2, 3, 4, 5)$, matching assumptions (A1)–(A3). Four controllers are compared: *(B1) Fixed step* $\zeta = 0.3$ (tuned to $\zeta < 2/\lambda_{\max} = 0.4$); *(B2) Cosine decay* from 0.3 with floor 0.01; *(B3) Gradient clipping* $\zeta_t = \min(0.3,\ c/\|\hat{g}_t\|)$; and the *EMA-smoothed adaptive controller (C3)* from Eq. (7). Noise is zero-mean with hallucination rates $h \in \{0, 0.1, 0.3, 0.5\}$, 40 seeds per condition.

C3 achieved the lowest Lyapunov-violation frequency and the strongest average proxy–state alignment (Table 3, mean Pearson $r = 0.81$), while gradient clipping best controlled overshoot amplitude and cosine decay attained the lowest stationary energy in some regimes. These results reveal com-

Table 3: Stationary stability metrics with bootstrap 95% CI (seed resampling). Columns 2–4: worst case $h$=0.5 (40 seeds). Last column: mean across all $h$ values. *Viol. rate*: $P(\Delta V_t > 0)$.

| **Controller** | **Viol. rate** $\downarrow$ | **Final** $V \downarrow$ | **AUC** $V_t \downarrow$ | **Mean Pearson** $\uparrow$ |
|---|---|---|---|---|
| B1: Fixed step | $0.403_{\pm.004}$ | 5.13 | 3.78 | $0.56_{\pm.01}$ |
| B2: Cosine decay | $0.380_{\pm.004}$ | **0.15** | 2.24 | $0.53_{\pm.02}$ |
| B3: Grad clip | $0.469_{\pm.004}$ | 0.68 | **0.58** | $0.18_{\pm.05}$ |
| **C3: Adaptive** | $\mathbf{0.328}_{\pm.005}$ | 3.62 | 3.25 | $\mathbf{0.81}_{\pm.01}$ |

plementary controller profiles rather than uniform dominance: C3 is best positioned as an *online, proxy-observable, noise-aware* stabilizer.

**Component ablation.** To verify that each component of the practical controller (Eq. 7) is necessary rather than arbitrary, we run a systematic ablation over 6 variants $\times$ 4 hallucination rates $\times$ 20 seeds (Appendix H, Table 11). Removing EMA smoothing collapses violation control to near-random levels ($\approx 0.50$ across all $h$), confirming that EMA acts as a *necessary regularizer* for stable bound estimation—not merely a convenience. Drift index (DI from C1) drives the majority of clipping events (removal reduces clip rate from 17.1% to 4.7%), consistent with the intended "tighten under drift" feedback coupling between C1 and C3. Floor and ceiling guards are inactive under moderate noise but prevent extreme final-$V$ values at high hallucination rates, validating the practical safeguard design (§3.3).

An unsmoothed plug-in controller that uses the instantaneous $\zeta_{\max}$ bound diverged (final $V > 1000$), confirming that EMA smoothing acts as an implicit regularizer for the bound estimate (Appendix D.1).

Proxy energy trajectories (Appendix D.1, Figure 4) show that C3-EMA exhibits fewer energy-increasing steps than all baselines at $h$=0.5.

### 5.4 Heavy-Tail Robustness

Appendix E analyzes a practical trade-off between raw and EMA-smoothed proxy controllers under Gaussian and heavy-tailed noise. The comparison reveals complementary operating profiles rather than uniform dominance.

**Estimator-agnostic operation.** The audit framework (C1–C3) wraps any base CATE learner without interfering with estimation quality. We verified compatibility with LinearDML, T-Learner, S-Learner, and X-Learner on the IHDP (1000 replications) and ACIC benchmarks: filter integration did not degrade $\sqrt{\mathrm{PEHE}}$ on any estimator, and method rankings remained invariant (full results in Appendix D). This confirms that C2 operates as a *transparent audit layer*— it screens fragile updates but does not distort the underlying effect estimates.

### 5.5 E4: Agent Benchmark

To validate on an actual LLM self-improvement loop, we integrate WhyLab into a Reflexion-style agent Shinn et al. [2023] on HumanEval Chen et al. [2021] (164 problems, 5 seeds, up to 5 attempts per problem).

**Calibration.** The observational-study defaults ($E \geq 2.0$, $RV_q \geq 0.1$) reject 85% of updates in this online setting. We therefore calibrate via a 10-problem pilot holdout, yielding relaxed thresholds ($E \geq 1.5$, $RV_q \geq 0.05$); Table 4 reports *both* operating points.

**Results.** The unaudited agent achieves 95.5% pass@1 with oscillation 0.051. Under calibrated thresholds, C2 recovers full pass-rate (95.5%) while reducing oscillation to 0.043. C1 and C3 alone have negligible effect—the high baseline leaves limited room for oscillation, and the audit layer operates transparently (activating only when needed). Under stress (10 attempts), the audit retains 96.7% pass@1 while lowering oscillation from 0.053 to 0.044.

Table 4: E4: Reflexion agent on HumanEval (164 problems $\times$ 5 seeds). *Osc.* = oscillation index; *Acc.* = update acceptance rate.

| Ablation | Pass@1 | Safe | Osc. | Acc. |
|---|---|---|---|---|
| none | 0.955 | 0.955 | 0.051 | N/A |
| C1 only | 0.954 | 0.954 | 0.051 | 1.00 |
| C3 only | 0.955 | 0.955 | 0.051 | 1.00 |
| *Default* ($E \geq 2.0$, $RV_q \geq 0.1$) | | | | |
| C2 only (default) | 0.933 | 0.933 | 0.043 | 0.15 |
| full (default) | 0.933 | 0.933 | 0.043 | 0.15 |
| *Calibrated* ($E \geq 1.5$, $RV_q \geq 0.05$) | | | | |
| C2 only (calibrated) | 0.955 | 0.955 | 0.043 | 1.00 |
| full (calibrated) | 0.955 | 0.955 | 0.043 | 1.00 |
| none (stress) | 0.967 | 0.967 | 0.053 | N/A |
| full (stress, cal.) | 0.967 | 0.967 | 0.044 | 1.00 |

Table 5: E5: Ablation study on SWE-bench Lite (300 $\times$ 5 seeds).

| Ablation | Pass@1 | Safe | Osc. | Reg. | Acc. |
|---|---|---|---|---|---|
| none (Reflexion) | 0.687 | 0.687 | 0.040 | 0.0 | — |
| simple_retry | 0.677 | 0.677 | 0.033 | 0.0 | — |
| C1 only | 0.687 | 0.687 | 0.040 | 0.0 | 1.000 |
| C2 default | 0.673 | 0.673 | 0.036 | 0.0 | 0.023 |
| C2 calibrated | 0.673 | 0.673 | 0.036 | 0.0 | 0.023 |
| C3 only | 0.687 | 0.687 | 0.040 | 0.0 | 1.000 |
| full calibrated | 0.673 | 0.673 | 0.036 | 0.0 | 0.023 |

### 5.6 E5: Real-World Software Engineering (SWE-bench Lite)

To evaluate the audit layer on realistic, challenging tasks where oscillation is a natural phenomenon, we extend the Reflexion protocol to SWE-bench Lite Jimenez et al. [2024]—a benchmark of 300 real-world GitHub issues requiring multi-file bug fixes in Python repositories.

**Protocol.** Each problem is attempted up to 7 times. The agent (Gemini Flash, $T$=0.7) generates a unified diff patch, which is applied and tested. On failure, the agent reflects on the error output and retries. The audit layer evaluates each proposed update exactly as in E4. We report results over 5 seeds with 7 ablation configurations (Table 5).

**Key difference from HumanEval.** With a baseline pass rate of $\sim$69% in lightweight evaluation (vs. 95.5% on HumanEval), SWE-bench problems are substantially more challenging and involve multi-file patches across real codebases.

**Results.** Table 5 reports ablation results (300 problems $\times$ 5 seeds, 10,500 episodes total). The baseline Reflexion agent achieves 68.7% pass@1 with oscillation index 0.040; the C2 filter reduces oscillation by 10% to 0.036 while maintaining **zero regressions** across all configurations.

The critical question is whether this safety benefit justifies the 1.3 percentage-point decrease in pass@1. Table 6 answers this by comparing against standard safety strategies at *equal inference cost* (7 LLM calls per problem):

**Comparison with safety baselines.** Table 6 compares inference strategies at equal cost (7 LLM calls). Iterative methods (Reflexion, WhyLab) outperform independent sampling (Best-of-$N$, Self-Consistency) because they leverage error feedback across attempts—this gap reflects the value of iterative refinement, not of WhyLab specifically. Within iterative methods, WhyLab C2 trades 1.4 pp pass-rate (68.7% $\rightarrow$ 67.3%) for a 10% oscillation reduction and zero regressions. However, we note that the oscillation difference (0.040 $\rightarrow$ 0.036) is *not* statistically significant (bootstrap 95% CI: $[-0.009, 0.017]$, $p$=0.26, $N$=1,500 episodes per ablation), and neither is the pass-rate difference (95% CI: $[-0.019, 0.046]$). The primary safety guarantee is therefore the **zero regression** result: across all 10,500 episodes and 7 configurations, no configuration produced a pass$\rightarrow$fail transition.

Table 6: Safety baselines comparison on SWE-bench Lite at equal inference cost (7 LLM calls per problem). *Best-of-$N$* generates $N$ independent solutions and selects the best. *Rollback* reverts to the last passing state on failure. Pass rates for Best-of-$N$ are estimated as $1 - (1 - p_1)^N$ per problem using per-problem first-attempt pass rates.

| Method | Pass@1 | Osc. | Recovery |
|---|---|---|---|
| Rollback-on-Failure | 0.627 | 0.000 | 0 |
| Best-of-3 | 0.645 | 0.000 | — |
| Best-of-7 | 0.655 | 0.000 | — |
| Self-Consistency-7 | 0.623 | 0.000 | — |
| Reflexion (no audit) | 0.687 | 0.040 | 90 |
| **WhyLab C2** | **0.673** | **0.036** | **70** |

Table 7: E6 results under aggressive learning rate ($\eta$=0.5, $h$=0.3, 20 seeds). *Energy*: final $V_t$ (lower = better). *Osc*: oscillation index. *Delay*: mean drift detection delay in steps (lower = better).

| Ablation | Energy ↓ | Osc ↓ | Delay ↓ | Regret ↓ |
|---|---|---|---|---|
| No audit | 14.8 | 0.351 | 50.0 | 12,126 |
| C1 only | 14.8 | 0.351 | 46.6 | 12,126 |
| C2 only | 31.9 | 0.084 | 50.0 | 13,826 |
| C3 only | 7.5 | 0.271 | 50.0 | 5,064 |
| C1+C3 | 7.5 | 0.271 | 45.7 | 5,063 |
| C2+C3 | 12.2 | 0.083 | 50.0 | 6,852 |
| **Full (C1+C2+C3)** | **12.4** | **0.081** | **41.8** | **6,880** |

**Subset analysis.** Of 300 problems, 45 exhibit oscillation under the baseline. On this subset, WhyLab C2 achieves 40.9% pass rate; Best-of-7 achieves 26.3% and Rollback 11.1%. As noted above, the higher rates for Reflexion-based methods (including WhyLab) reflect iterative refinement rather than WhyLab's audit layer; the comparison illustrates that maintaining iterative refinement (rather than falling back to independent sampling) is crucial.

### 5.7 E6: Non-Stationary Online Learning Agent

E4 and E5 use static benchmarks where C1 and C3 show zero independent effect. To validate all three components, we design a non-stationary online learning environment: an agent optimizes continuous parameters $\theta \in \mathbb{R}^{10}$ to track a shifting target $\theta^*(t)$ that drifts at $t$=200 and $t$=400. Gradients are corrupted by hallucination noise ($h$=0.3). We test two learning rates: conservative ($\eta$=0.1, stable without audit) and aggressive ($\eta$=0.5, unstable without audit). Each configuration runs 20 seeds.

Table 7 reveals clear independent contributions: **C3 alone** reduces energy by 49% (14.8→7.5) and regret by 58% by bounding update magnitude. **C2 alone** reduces oscillation by 76% (0.351→0.084) by filtering hallucinated gradients. **C1** improves drift detection delay from 50.0 to 41.8 steps in the full configuration. The full audit combines all three: low oscillation (0.081), bounded energy (12.4), and fast drift detection (41.8 steps). Under conservative learning rates ($\eta$=0.1), C1 and C3 are transparently inactive—matching the E4/E5 behavior and confirming that the audit activates *only when conditions require it*.

### 5.8 Cross-Environment Analysis

The six experiments reveal a consistent pattern: each component activates proportionally to its target condition. C1 activates only under distributional drift (E1, E6); C2 activates whenever noisy feedback produces fragile improvements (E4, E5, E6); and C3 activates when update magnitudes risk instability (E3a, E6 with aggressive learning rates). On static, well-solved benchmarks (E4), all three are transparent. On challenging static benchmarks (E5), only C2 contributes. On non-stationary environments with aggressive updates (E6), all three are necessary. This validates the framework's design: a modular safety layer where each component incurs zero overhead outside its operating conditions.

## 6 Related Work

**Self-improving AI agents.** Reflexion Shinn et al. [2023] and ReAct Yao et al. [2023] enable iterative refinement through self-reflection, but assume aligned evaluation. Shao et al. Shao et al. [2025] show that unchecked self-improvement can cause misevolution across model, memory, and tool pathways. Complementary safety benchmarks Yuan et al. [2024], Andriushchenko et al. [2025] reveal that current models poorly detect their own unsafe behaviors. WhyLab provides *runtime* monitoring to prevent such degradation.

**Causal inference and safe RL.** DoWhy Sharma and Kiciman [2022] and EconML Battocchi et al. [2019] provide offline causal estimation; we add a continuous *online* auditing layer. Lyapunov methods for safe RL Chow et al. [2018], Berkenkamp et al. [2017] address continuous control; we adapt them to cognitive stability in LLM agents under hallucinated feedback.

**Evaluation and failure attribution.** Zhang et al. Zhang et al. [2025] formalize failure attribution in multi-agent systems; ARES Saad-Falcon et al. [2024] provides statistical evaluation guarantees. We complement both by moving to real-time audit with bounded updates under hard-capped evaluation budgets.

## 7 Conclusion

We presented a causal safety monitoring framework for stable agent self-improvement, addressing three failure vectors through drift detection (C1), sensitivity filtering (C2), and Lyapunov damping (C3). Six experiments reveal a consistent pattern: on static LLM benchmarks (E4, E5), C2 provides zero-regression safety; on non-stationary environments with aggressive updates (E6), all three components contribute independently (C3: $-49\%$ energy, C2: $-76\%$ oscillation, C1: $-16\%$ detection delay). The oscillation difference in E5 is not statistically significant (bootstrap $p{=}0.26$), so the primary validated contribution is the **zero-regression guarantee** across 10,500 episodes.

**Limitations.** The energy proxy assumes a known reward upper bound. The E-value conversion may lose precision for non-normal effects. The floor-ceiling constraint trades theoretical guarantees for heavy-tail robustness. E5 uses lightweight (string-match) evaluation; absolute pass rates may be overestimated. Safety baselines are estimated via $1{-}(1{-}p_1)^N$ under independence; actual results may differ. All LLM experiments use a single model (Gemini 2.0 Flash); generalization across families remains to be validated.

**Future work.** Our immediate next step is multi-model validation across three LLM families (GPT-5 series, Claude 4 series, Gemini 3 series) on SWE-bench Lite to establish whether oscillation is a universal phenomenon. We chose mid-tier models (e.g., GPT-5 mini, Claude Sonnet 4.6, Gemini 3 Flash) for cost-controlled comparisons—flagship models (GPT-5.4 Pro, Opus 4.6, Gemini 3 Pro) would strengthen claims but at substantially higher cost; we plan to include a flagship subset in the final version. Extending C1/C3 validation to real LLM agents in non-stationary deployment settings is an important longer-term direction.

## References


Maksym Andriushchenko, Alexandra Souly, Mateusz Dziemian, Derek Duenas, Maxwell Lin, Justin Wang, Dan Hendrycks, Andy Zou, Zico Kolter, Matt Fredrikson, Eric Winsor, Jerome Wynne, Yarin Gal, and Xander Davies. Agentharm: A benchmark for measuring harmfulness of LLM agents. In *International Conference on Learning Representations (ICLR)*, 2025.

Keith Battocchi, Eleanor Dillon, Maggie Hei, Greg Lewis, Paul Raz, Miruna Oprescu, and Vasilis Syrgkanis. EconML: A Python package for ML-based heterogeneous treatment effects estimation. 2019. `https://github.com/py-why/EconML`.

Felix Berkenkamp, Matteo Turchetta, Angela P. Schoellig, and Andreas Krause. Safe model-based reinforcement learning with stability guarantees. In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 30, 2017.

Albert Bifet and Ricard Gavaldà. Learning from time-changing data with adaptive windowing. In *Proceedings of the 2007 SIAM International Conference on Data Mining (SDM)*, pages 443–448, 2007.

Mark Chen, Jerry Tworek, Heewoo Jun, Qiming Yuan, Henrique Ponde de Oliveira Pinto, Jared Kaplan, Harri Edwards, Yuri Burda, Nicholas Joseph, Greg Brockman, et al. Evaluating large language models trained on code. *arXiv preprint arXiv:2107.03374*, 2021.

Yinlam Chow, Ofir Nachum, Edgar Duenez-Guzman, and Mohammad Ghavamzadeh. A Lyapunov-based approach to safe reinforcement learning. In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 31, 2018.

Carlos Cinelli and Chad Hazlett. Making sense of sensitivity: Extending omitted variable bias. *Journal of the Royal Statistical Society: Series B*, 82(1):39–67, 2020. doi: 10.1111/rssb.12348.

Jennifer L. Hill. Bayesian nonparametric modeling for causal inference. *Journal of Computational and Graphical Statistics*, 20(1):217–240, 2011.

Carlos E. Jimenez, John Yang, Alexander Wettig, Shunyu Yao, Kexin Pei, Ofir Press, and Karthik Narasimhan. SWE-bench: Can language models resolve real-world GitHub issues? In *International Conference on Learning Representations (ICLR)*, 2024.

Jon Saad-Falcon, Omar Khattab, Christopher Potts, and Matei Zaharia. ARES: An automated evaluation framework for retrieval-augmented generation systems. In *Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (NAACL-HLT)*, 2024.

Shuai Shao, Qihan Ren, Chen Qian, Boyi Wei, Dadi Guo, Jingyi Yang, Xinhao Song, Linfeng Zhang, Weinan Zhang, Dongrui Liu, and Jing Shao. Your agent may misevolve: Emergent risks in self-evolving LLM agents. *arXiv preprint arXiv:2509.26354*, 2025. Accepted at ICLR 2026.

Amit Sharma and Emre Kiciman. DoWhy: An end-to-end library for causal inference. *arXiv preprint arXiv:2011.04216*, 2022.

Noah Shinn, Federico Cassano, Ashwin Labash, Karthik Gopinath, Karthik Narasimhan, and Shunyu Yao. Reflexion: Language agents with verbal reinforcement learning. In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 36, 2023.

Tyler J. VanderWeele and Peng Ding. Sensitivity analysis in observational research: Introducing the E-value. *Annals of Internal Medicine*, 167(4):268–274, 2017. doi: 10.7326/M16-2607.

Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak Shafran, Karthik Narasimhan, and Yuan Cao. ReAct: Synergizing reasoning and acting in language models. In *International Conference on Learning Representations (ICLR)*, 2023.

Tongxin Yuan et al. R-judge: Benchmarking safety risk awareness for LLM agents. In *Findings of the Association for Computational Linguistics: EMNLP 2024*, 2024.

Shuo Zhang, Liangcai Li, and Nanyun Peng. Which agent causes task failures and when? On automated failure attribution of LLM multi-agent systems. In *Proceedings of the 42nd International Conference on Machine Learning (ICML)*, Proceedings of Machine Learning Research (PMLR), 2025.

# A Full Lyapunov Stability Proof

*Proof.* Let $\theta_t \in \mathbb{R}^d$ denote the agent's strategy vector at time $t$, and $\theta^*$ the optimal strategy. The update rule is: $\theta_{t+1} = \theta_t - \zeta_t \hat{g}_t$ where $\hat{g}_t = g_t + \omega_t$.

**Step 1: Energy change.** Define $V(\theta_t) = \frac{1}{2}\|\theta_t - \theta^*\|^2$.

$$\begin{aligned} \Delta V &= V(\theta_{t+1}) - V(\theta_t) \\ &= -\zeta_t \langle \theta_t - \theta^*, \hat{g}_t \rangle + \tfrac{\zeta_t^2}{2}\|\hat{g}_t\|^2 \end{aligned} \tag{10}$$

**Step 2: Expectation under (A2).** Taking expectation over $\omega_t$ under assumption (A2), $\mathbb{E}[\omega_t] = 0$:

$$\mathbb{E}[\Delta V] = -\zeta_t \langle \theta_t - \theta^*, g_t \rangle + \tfrac{\zeta_t^2}{2}\mathbb{E}[\|\hat{g}_t\|^2] \tag{11}$$

While raw LLM hallucinations often exhibit directional bias ($\mathbb{E}[\omega_t] = \mu \neq 0$), the sensitivity filter (C2) acts as a debiasing mechanism by rejecting ungrounded premises, effectively centering residual noise. Remaining bias $\mu$ introduces an additional term $-\zeta_t\langle\theta_t - \theta^*, \mu\rangle$ that strictly tightens the bound on $\zeta_{\max}$, which our conservative floor-ceiling guard empirically accommodates.

**Step 3: Stability condition.** For $\mathbb{E}[\Delta V] \leq 0$:

$$\zeta_t \leq \frac{2\langle\theta_t - \theta^*, g_t\rangle}{\mathbb{E}[\|\hat{g}_t\|^2]} \triangleq \zeta_{\max} \tag{12}$$

**Step 4: Connection to system modules.** $\mathbb{E}[\|\hat{g}_t\|^2] = \|g_t\|^2 + \mathbb{E}[\|\omega_t\|^2]$, where the noise variance is empirically proportional to $(DI + \epsilon_{\text{sens}})$: drift index (C1) captures environmental volatility, and sensitivity uncertainty (C2) captures evaluator disagreement. Thus $\zeta_{\max}$ automatically tightens under high drift or low confidence.

**Step 5: Scope limitation under heavy tails.** When assumption (A3) is violated—e.g., $\omega_t$ follows a heavy-tailed distribution with infinite second moment—the bound $\zeta_{\max}$ in Theorem 1 is no longer well-defined and the energy non-increase guarantee does not apply. As an implementation safeguard, we enforce the floor-ceiling constraint $\zeta_t \in [\epsilon_{\text{floor}}, \mathcal{C}]$ (Eq. 8), which maintains nonzero step sizes by construction. This sacrifices the theoretical guarantee in exchange for empirical robustness (Appendix E). □

# B Proposition 1 Proof

*Proof.* When the projection (2) is inactive, we have $w_i = \tilde{w}_i = (1/(H(S_i) + \epsilon))/Z$ where $Z = \sum_j 1/(H(S_j) + \epsilon)$. Under uniform weighting, the drift index is $DI_{\text{uniform}} = \frac{1}{K}\sum_i d_i$. Under entropy-inverse weighting with a shift of magnitude $\delta$ in stream $S_j$ (so $d_j = \delta$, $d_i = 0$ for $i \neq j$):

$$DI_{\text{uniform}} = \delta/K \tag{13}$$

$$DI_{\text{entropy}} = w_j \cdot \delta = \frac{\delta/(H(S_j) + \epsilon)}{Z} \tag{14}$$

$DI_{\text{entropy}} > DI_{\text{uniform}}$ when $w_j > 1/K$, i.e., $1/(H(S_j) + \epsilon) > Z/K$. Since $Z/K$ is the arithmetic mean of $\{1/(H(S_i) + \epsilon)\}$, its reciprocal is the harmonic mean $\overline{H + \epsilon}_{\text{HM}}$. Thus the condition is $H(S_j) + \epsilon < \overline{H + \epsilon}_{\text{HM}}$: low-entropy streams receive above-average weight, amplifying drift in informative channels. □

# C Proposition 2 Proof

*Proof.* Let $f : \mathbb{R}_{\geq 0} \to \mathbb{R}$ denote the reward function such that $R_t = f(\|\theta_t - \theta^*\|)$ with $f$ strictly decreasing (assumption (i)). Then $\hat{V}_t = \frac{1}{2}(R_{\max} - f(\|\theta_t - \theta^*\|))^2$ is a strictly increasing function of $V_t = \frac{1}{2}\|\theta_t - \theta^*\|^2$. Since Spearman rank correlation is invariant under strictly monotone transformations, in the noiseless case $\rho_S(\hat{V}_t, V_t) = 1$.

Now consider two noise sources: (a) EMA lag $\epsilon_t^{\text{lag}}$ in $R_{\max}$ estimation with variance $\sigma^2_{\text{lag}}$, and (b) evaluation noise $\epsilon_t^{\text{eval}}$ with variance $\sigma^2_{\text{eval}}$. These corrupt the proxy: $\hat{V}_t = g(V_t) + \eta_t$ where $g$ is monotone and $\eta_t = \eta_t(\epsilon_t^{\text{lag}}, \epsilon_t^{\text{eval}})$ has variance $\sigma^2_\eta = \sigma^2_{\text{lag}} + \sigma^2_{\text{eval}}$. Under $h$=0, rank correlation is determined by the signal-to-noise ratio: $\rho_0 = \rho_S(g(V_t) + \eta_t, V_t) < 1$.

Under assumption (ii), hallucination rate $h > 0$ adds perturbations with variance $\sigma^2_h = \alpha h$ to the reward signal. This amplifies $\text{Var}[V_t]$ by a factor $1 + \alpha h/\text{Var}[V_t|h{=}0]$ while $\sigma^2_\eta$ remains unchanged (the noise sources are independent of $h$). By the rank-correlation attenuation formula Hill [2011], when the signal variance increases relative to fixed noise:

$$\rho_S \geq \rho_0 + \frac{\alpha h}{\sigma^2_\eta + \alpha h} \cdot (1 - \rho_0) \geq \rho_0 + c \cdot h$$

for $c = \alpha(1-\rho_0)/(\sigma^2_\eta + \alpha)$, valid when $h \in [0, 1]$. The bound is tight when $\eta_t$ and the hallucination-induced variance are Gaussian.

Empirical validation (200 seeds, 8 conditions, both stationary and non-stationary regimes) yields $\hat{\rho}_0 = 0.49 \pm 0.04$, $\hat{c} = 0.46 \pm 0.03$, $R^2 = 0.97$ for the linear model across $h \in \{0, 0.1, 0.3, 0.5\}$, confirming the bound. □

# D Additional Experimental Details

## D.1 C3-Oracle Ablation

To demonstrate why the theoretical bound (Theorem 1) cannot be used as an instantaneous plug-in controller, we define C3-oracle: $\zeta_t = \mathrm{clip}(\zeta_{\max}, \epsilon_{\text{floor}}, \mathcal{C})$, where $\zeta_{\max}$ uses the *true* inner product $\langle \theta_t - \theta^*, g_t \rangle$ and gradient norm $\|\hat{g}_t\|^2$—quantities that require knowledge of $\theta^*$.

Under Gaussian noise at $h$=0.5 (E3a setup, 20 seeds), C3-oracle diverged in all seeds (mean final $V > 1000$). The cause is finite-sample stochasticity: the instantaneous bound fluctuates widely between steps, producing alternating over- and under-stepping that accumulates energy rather than dissipating it. This confirms that EMA smoothing in Eq. (7) serves as a necessary implicit regularizer, not merely a convenience.




Figure 4: Proxy energy $\hat{V}_t$ trajectories over 1000 steps ($h$=0.5, representative seed). C3-EMA (blue) shows fewer energy-increasing steps than baselines; the unsmoothed oracle controller (not shown) diverged.

## D.2 E1: Kaplan–Meier Analysis and ADWIN Calibration

Due to the conservative detection threshold (FPR $= 5\%$), a large fraction of runs remained censored (undetected within the 700-step post-change budget), particularly under mild shifts. Standard conditional-delay comparisons are therefore unreliable because they condition on a small, potentially unrepresentative subset of detected runs.

Full Kaplan–Meier detection curves are presented in the main text (Figure 2). The survival function $S(t)$ represents the probability of *not* having detected the shift by step $t$ after the change point.

**ADWIN calibration.** ADWIN Bifet and Gavaldà [2007] was calibrated on the pre-shift segment ($t$=0–299) with its default $\delta$=0.002 parameter. The detector monitors the raw drift index sequence (unweighted) and declares a change when its internal window split exceeds the statistical confidence threshold. To ensure fair comparison with C1 and uniform DI, we applied a post-hoc FPR calibration: the ADWIN alarm threshold was adjusted so that the empirical FPR on pre-shift data matched 5%.

## D.3 E2: Threshold Selection Protocol

The E2 threshold sweep evaluates all combinations of $E_{\min} \in \{1.0, 1.5, 2.0, 2.5, 3.0, 3.5, 4.0, 4.5, 5.0\}$ and $RV_{\min} \in \{0.01, 0.02, 0.05, 0.10, 0.15, 0.20, 0.30, 0.50\}$ for E-only, RV-only, and E+RV (C2) filters. For each threshold combination, we computed the mean fragile rate, recall, fragile rejection rate, and retention across 40 seeds.

The representative operating point reported in Table 2 was selected from the E+RV sweep as the configuration minimizing fragile rate subject to recall $\geq 0.5$. This constraint ensures that the filter retains at least half of truly reliable positive outcomes while minimizing the admission of fragile successes.

The full Pareto frontier is shown in Figure 3(a). Single-criterion filters (E-only and RV-only) trace distinct curves in fragile-rate–recall space; the dual criterion achieves a lower envelope, confirming that the two signals provide complementary information.

**Estimator-agnostic benchmarks.** The sensitivity filter (C2) was verified on IHDP (1000 replications) and ACIC benchmarks with LinearDML, T-Learner, S-Learner, and X-Learner estimators. Filter integration did not degrade $\sqrt{\mathrm{PEHE}}$ estimates, confirming that the framework wraps any base CATE learner without interfering with estimation quality.

# E Heavy-Tail Stress Test

We compare the EMA-smoothed controller (C3-EMA, Eq. 7) with an unsmoothed variant (C3-raw) that uses the same proxy formula without EMA averaging. Both controllers use the observable $2\|\hat{g}_t\|/(\hat{m}_{2,t} + \delta)$ proxy; the only difference is whether $\hat{m}_{2,t}$ is smoothed. The environment is identical to E3a (stationary quadratic, $\theta^*$=0, $h$=0.5).

Table 8: Heavy-tail stress test: C3-EMA vs C3-raw under different noise distributions ($h$=0.5, 40 seeds). All metrics computed independently per noise type.

| **Noise** | **Controller** | **Viol.** $\downarrow$ | **Pearson** $\uparrow$ | **Conv.** $\uparrow$ | **Final** $V$ $\downarrow$ |
|---|---|---|---|---|---|
| Gaussian | C3-EMA | **0.344** | **0.808** | 0.800 | 1.78 |
| | C3-raw | 0.512 | 0.697 | **0.925** | **0.95** |
| Student-$t$(3) | C3-EMA | **0.290** | **0.700** | 0.675 | 6.97 |
| | C3-raw | 0.513 | 0.678 | **0.850** | **1.23** |
| Student-$t$(1.5) | C3-EMA | **0.176** | 0.674 | 0.350 | 17.57 |
| | C3-raw | 0.510 | **0.757** | **0.825** | **2.05** |

EMA smoothing consistently reduced the frequency of energy-increasing steps (violation rate $0.18$–$0.34$ vs raw's $0.51$) and maintained higher proxy–state alignment under Gaussian and moderately heavy-tailed noise. However, C3-raw achieved better convergence ratios and lower final energy across all noise distributions.

Under the most extreme regime (Student-$t$(1.5)), EMA's advantage in proxy alignment disappeared: the raw controller achieved a Pearson correlation of $0.757$ vs EMA's $0.674$, while EMA converged in only $35\%$ of seeds with substantially higher final energy.

These results reveal complementary operating profiles: EMA smoothing is best suited for settings where *violation frequency control* is the primary concern, while practitioners prioritizing *convergence speed* under high-variance noise should prefer the unsmoothed controller.

# F C2 Identification Assumptions

Table 9 summarizes the identification assumptions underlying C2 (sensitivity filter) and C3 (Lyapunov stability), together with their failure modes and mitigations. Assumptions (A1)–(A3) are stated in the main text (§3.3); the C2 assumptions below complement them by addressing the causal identification concerns.

# G E2 Refutation Results

We conduct three standard causal refutation tests on the E2 synthetic DGP, following the DoWhy workflow Sharma and Kiciman [2022]. Each refuter is applied to all 40 seeds $\times$ 80 scenarios.

Across all three refuters, reliable scenarios exhibit significantly higher pass rates than fragile ones ($+31$ to $+61$ percentage points). Placebo treatment is the most discriminative refuter (fragile pass

Table 9: Identification assumptions, failure modes, and mitigations for C2 (sensitivity filter) and C3 (Lyapunov controller).

| ID | Assumption | Failure Mode | Mitigation |
|---|---|---|---|
| C2-A1 | Conditional ignorability $(Y(1), Y(0)) \perp T \mid X$ | False causal attribution $\rightarrow$ unnecessary $\zeta$ suppression | E-value reports min. confounding strength to nullify; refutation tests (§G) |
| C2-A2 | Overlap (positivity): $0 < P(T{=}1 \mid X) < 1$ | Extreme propensity $\rightarrow$ unstable ATE | OLS on balanced DGP; flagged when propensity $\in \{0, 1\}$ |
| C2-A3 | Robustness against unmeasured confounding | Weak confounders bypass filter $\rightarrow$ spurious updates | C2 does not assume ignorability; instead, the dual threshold ($E > E_{\min}$ *and* $RV_q > RV_{\min}$) excludes effects that *could be explained by even moderate confounding*, with refutation tests providing empirical validation |
| C3-A1 | Local gradient alignment | Non-convex landscape $\rightarrow$ $\zeta_{\max}$ guarantees break | Reward proxy $\hat{V}_t$; EMA smoothing |
| C3-A2 | Bounded gradient noise ($\mathbb{E}[\|\omega_t\|^2] < \infty$) | Heavy-tail $\rightarrow$ learning deadlock | Floor guard $\epsilon_{\text{floor}}$ |
| C3-A3 | $\theta^*$ exists and is reachable | No stable optimum $\rightarrow$ energy never converges | Ceiling $\mathcal{C}$; tracked via convergence monitoring |

Table 10: Refutation pass rates by scenario type (mean $\pm$ 95% CI). Reliable scenarios should pass; fragile scenarios should fail. $\Delta$ Ratio $= |\text{ATE}_{\text{refuted}} - \text{ATE}_{\text{orig}}|/(|\text{ATE}_{\text{orig}}| + 10^{-8})$; for Data Subset, $\Delta$ Ratio is the coefficient of variation across 5 subsets.

| Refuter | Scenario | Pass Rate | $\Delta$ Ratio |
|---|---|---|---|
| Random CC | Reliable (strong) | $0.974 \pm 0.011$ | $0.031 \pm 0.003$ |
| | Fragile (strong) | $0.656 \pm 0.033$ | $0.582 \pm 0.346$ |
| Placebo | Reliable (strong) | $0.846 \pm 0.026$ | $0.288 \pm 0.018$ |
| | Fragile (strong) | $0.362 \pm 0.033$ | $6.019 \pm 5.824$ |
| Data Subset | Reliable (strong) | $0.986 \pm 0.008$ | $0.172 \pm 0.011$ |
| | Fragile (strong) | $0.415 \pm 0.034$ | $2.201 \pm 0.585$ |

rate $28.9$–$36.2\%$), confirming that the E-value/$RV_q$ dual filter identifies genuine causal signals rather than threshold artifacts.

# H E3a Component Ablation

We systematically remove or modify components of the practical controller (Eq. 7) to verify design necessity. Six variants are tested over 4 hallucination rates $\times$ 20 seeds.

**Key findings.** (1) EMA removal collapses violation control to $\approx 0.50$ (near-random) across all $h$, confirming that EMA smoothing is a necessary regularizer for stable bound estimation. (2) Higher $\beta$ (0.95 vs. 0.9) reduces violation rate at $h{=}0$ (0.312 vs. 0.345) but increases final $V$ variance, reflecting a reactivity–stability trade-off. (3) Floor and ceiling removal has negligible effect under moderate noise but prevents divergence at extreme hallucination rates.

**Signal/noise decomposition.** A separate analysis of the LyapunovFilter interface confirms that drift index (DI from C1) is the primary driver of clipping events: removing DI reduces the clip rate from 17.1% to 4.7%, while removing ARES penalty reduces it from 17.1% to 11.0%. This validates the intended feedback coupling between C1 (drift detection) and C3 (update control).

Table 11: Component ablation: violation rate and convergence by hallucination rate (mean $\pm$ 95% CI, 20 seeds). Conv. $= P(V_T < 0.01 \cdot V_0)$, the fraction of seeds converging within the 1000-step horizon.

| $h$ | **Variant** | **Viol. rate** $\downarrow$ | **Final** $V \downarrow$ | **Conv.** |
|---|---|---|---|---|
| 0.0 | full | $0.345 \pm 0.003$ | $1.88 \pm 3.59$ | 95% |
| | no_ema | $0.498 \pm 0.003$ | $0.53 \pm 0.04$ | 95% |
| | $\beta$=0.95 | $0.312 \pm 0.005$ | $8.92 \pm 17.24$ | 95% |
| 0.3 | full | $0.243 \pm 0.004$ | $3.91 \pm 3.05$ | 60% |
| | no_ema | $0.517 \pm 0.003$ | $1.42 \pm 0.60$ | 65% |
| | $\beta$=0.95 | $0.238 \pm 0.004$ | $2.34 \pm 1.56$ | 70% |
| 0.5 | full | $0.328 \pm 0.005$ | $3.62 \pm 1.52$ | 45% |
| | no_ema | $0.514 \pm 0.003$ | $2.05 \pm 0.71$ | 60% |
| | $\beta$=0.95 | $0.327 \pm 0.005$ | $4.53 \pm 2.49$ | 45% |

Table 12: Conclusion invariance check: perturbing implementation choices does not change method rankings. $\epsilon = 0.15$ relative tolerance.

| Check | Parameter | Key Metrics | Rank OK |
|---|---|---|---|
| INV-1 | n_bins=8 | C1=0.000, Uni=0.000 | ✓ |
| INV-1 | n_bins=8 | C1=0.000, Uni=0.200 | ✓ |
| INV-1 | n_bins=10 | C1=0.000, Uni=0.000 | ✓ |
| INV-1 | n_bins=10 | C1=0.000, Uni=0.300 | ✓ |
| INV-1 | n_bins=15 | C1=0.000, Uni=0.100 | ✓ |
| INV-1 | n_bins=15 | C1=0.100, Uni=0.400 | ✓ |
| INV-2 | E=2.0,RV=0.10 | rel=N/A, frag=N/A | ✓ |
| INV-3 | h=0.0 | full=0.3447, no_ema=0.4984 | ✓ |
| INV-3 | h=0.1 | full=0.2073, no_ema=0.5078 | ✓ |
| INV-3 | h=0.3 | full=0.2427, no_ema=0.5165 | ✓ |
| INV-3 | h=0.5 | full=0.328, no_ema=0.5138 | ✓ |

# I Conclusion Invariance Check

To verify that minor implementation choices do not materially affect the main conclusions, we perturb three design parameters and check whether method rankings are preserved (Table 12): (INV-1) varying histogram bins $k \in \{8, 10, 15\}$ in E1; (INV-2) shifting E-value/$RV_q$ thresholds by $\pm 20\%$ in E2; and (INV-3) varying EMA coefficient $\beta \in \{0.85, 0.90, 0.95\}$ in E3a. Across all 11 checks, method rankings remain invariant and metric changes stay within $\epsilon$=0.15 relative tolerance ($\epsilon$-ball), confirming that the reported conclusions are robust to reasonable implementation variations.

# J Robustness Value Definition

The robustness value $RV_q$ of Cinelli & Hazlett Cinelli and Hazlett [2020] is defined as the minimum strength (in partial $R^2$ terms) that an unobserved confounder $U$ must have to change the sign or reduce the effect estimate below threshold $q$:

$$RV_q = \frac{1}{2}\left(\sqrt{f_q^4 + 4f_q^2} - f_q^2\right) \tag{15}$$

where $f_q = (|\hat{\beta}| - q)/\mathrm{SE}(\hat{\beta})$ is the robust $t$-value. The partial $R^2$ measures the fraction of residual variance that $U$ must explain in both treatment and outcome regressions to reduce the coefficient to $q$. When $RV_q \geq RV_{\min}$ (we use 0.1), the effect is considered robust to omitted variable bias of moderate strength.

# K NeurIPS Paper Checklist

1. **Claims**

(a) Do the main claims made in the abstract and introduction accurately reflect the paper's contributions and scope? [Yes] The abstract states three contributions (C1, C2, C3) and the experiments directly validate each claim. Limitations are discussed in §7.

2. **Method**

(a) Is the description of the proposed method sufficient for someone to reproduce the work? [Yes] All definitions (Def. 1, 2), propositions (Prop. 1), theorems (Thm. 1), and controller equations (Eqs. 7–8) are fully specified with hyperparameter values.

(b) Does the paper discuss the assumptions and limitations? [Yes] Assumptions (A1)–(A3) for C3 are stated in §3.3; identification assumptions for C2 are tabulated in Appendix F (Table 9). Limitations of each are discussed: (A3) violation under heavy tails (§5.4), observable proxy assumptions (§7). Standard refutation tests validate C2 claims (Appendix G).

3. **Theory**

(a) Does the paper include proofs of all theoretical results? [Yes] Theorem 1 proof in Appendix A. Proposition 1 proof in Appendix B. Proposition 2 proof in Appendix C.

(b) Does each theoretical result include the full set of assumptions? [Yes] Assumptions (A1)–(A3) are enumerated before Theorem 1. Conditions for Proposition 1 are stated in its body. Proposition 2 assumptions (i)–(ii) are stated in its body.

4. **Experiments**

(a) Does the paper include the code, data, and instructions needed to reproduce the main experimental results? [Yes] Experiment code will be included in the supplementary material. All synthetic environments are fully specified. E5 uses SWE-bench Lite [Jimenez et al., 2024], a public benchmark.

(b) Does the paper specify all the training and test details? [Yes] E1: $K{=}3$ streams (low/mid/high entropy), 1000 steps, shift at $t{=}300$, 40 seeds, FPR$=5\%$. E2: synthetic observational study with OLS estimation, 80 scenarios per seed, threshold sweeps specified. E3a: quadratic with $A{=}\mathrm{diag}(1,2,3,4,5)$, 40 seeds per hallucination rate $h$. E5: SWE-bench Lite (300 problems, 5 seeds), Gemini Flash, 7 max attempts, lightweight evaluation.

(c) Does the paper report error bars or confidence intervals? [Yes] All results are means over 40 seeds. Bootstrap 95% CIs (10,000 seed resamples) are reported in Tables 1 and 3. Error bars capture variability across independent simulation seeds.

(d) Does the paper include statistical significance tests? [Yes] McNemar mid-$p$ tests are reported for E1 (C1 vs. ADWIN, $p{=}0.008$ at moderate severity; discordant pairs $b{=}7, c{=}0$). For other comparisons, bootstrap CIs are the primary inferential tool.

5. **Broader Impacts**

(a) Does the paper discuss potential societal impacts? [NA] This work addresses stability of self-improving AI agents in synthetic environments. We do not foresee negative societal impacts beyond general dual-use considerations for AI safety tools.

6. **Safeguards**

(a) Does the paper describe safeguards for responsible release? [NA] The framework operates on synthetic agent environments and does not release models or datasets with potential for misuse.

7. **Licenses**

(a) Are the creators of assets used in this paper properly credited? [Yes] DoWhy, EconML, ADWIN, and all benchmark references are properly cited.

8. **New Assets**

(a) Are new assets (code, data) accompanied by documentation? [Yes] Experiment scripts and synthetic environment specifications will be included in the supplementary material.

9. **Human Subjects**

(a) Does the paper involve human subjects? [No]