


Service Provider MPLS VPNs and BGP Peering with ISPs and Customers

[Full Lab]



Lab Requirements

1. OSPF must be configured as the IGP within the service provider core, and all P and PE loopback interfaces must be reachable via OSPF.

2. MPLS must be enabled on all core-facing interfaces, and end-to-end label-switched paths must exist between all PE routers.
3. iBGP must be established between PE routers within the service provider private AS-65111, using loopback interfaces as the update source.
4. An iBGP route-reflector architecture must be implemented. All non-route-reflector PE routers must establish iBGP sessions exclusively with the route reflector. P01 shall operate as the **active route reflector**, while PE01 shall be configured as the **standby route reflector**.
5. MPLS Layer-3 VPN services must be implemented using VRFs with unique Route Distinguishers and controlled Route Target import and export policies.
6. Customer sites assigned to the same VRF must have end-to-end IP connectivity across the MPLS backbone.
7. Inter-VRF routing must be implemented for RED-CE01 and GREEN-CE01.
8. MPLS Layer-2 VPN services must be implemented using: VPWS between BLUE-CE01 and BLUE-CE02, and VPLS between YELLOW-CE01 and YELLOW-CE02, YELLOW-CE03, providing transparent Layer-2 connectivity between PE routers.
9. An additional Layer-2 VPN service must be implemented using L2TPv3 between BLUE-R01 and BLUE-R02, providing point-to-point Layer-2 transport.
10. eBGP sessions must be established with external ISPs and customers using public Autonomous System numbers (2028).
11. The service provider private AS must connect to public AS peers using the BGP local-as and replace-as features.
12. The private AS number must not appear in the AS-PATH advertised to any external ISP or customer.
13. Public BGP peering must exchange only authorized public IP prefixes; internal service provider, VPN, and private prefixes must not be advertised externally.
14. Private IP address space must be filtered on all public-facing eBGP sessions.
15. External ISPs and customers must not receive the service provider internal routing table.

SERVICE PROVIDER CORE NETWORK

IGP: OSPF CONFIGURATION

hello interval is 3s, dead interval is 10s and network type is point-to-point

PE01

```
router ospf 65111
  router-id 172.16.30.1
  auto-cost reference-bandwidth 10000
  passive-interface default
  no passive-interface GigabitEthernet1
  no passive-interface GigabitEthernet2
  no passive-interface GigabitEthernet3
  network 10.7.135.1 0.0.0.0 area 0
  network 10.180.0.2 0.0.0.0 area 0
  network 10.180.0.17 0.0.0.0 area 0
  network 172.16.30.1 0.0.0.0 area 0
!
```

PE02

```
router ospf 65111
  router-id 172.16.30.2
  auto-cost reference-bandwidth 10000
  passive-interface default
  no passive-interface GigabitEthernet0/0
  no passive-interface GigabitEthernet0/1
  network 10.180.0.1 0.0.0.0 area 0
```

```
network 10.180.0.5 0.0.0.0 area 0  
network 172.16.30.2 0.0.0.0 area 0
```

!

PE03

```
router ospf 65111  
router-id 172.16.30.3  
auto-cost reference-bandwidth 10000  
passive-interface default  
no passive-interface GigabitEthernet1  
no passive-interface GigabitEthernet2  
no passive-interface GigabitEthernet3  
network 10.7.135.6 0.0.0.0 area 0  
network 10.180.0.6 0.0.0.0 area 0  
network 10.180.0.9 0.0.0.0 area 0  
network 172.16.30.3 0.0.0.0 area 0
```

!

PE04

```
router ospf 65111  
router-id 172.16.30.4  
auto-cost reference-bandwidth 10000  
passive-interface default  
no passive-interface GigabitEthernet1  
no passive-interface GigabitEthernet2  
no passive-interface GigabitEthernet3
```

```
network 10.7.135.10 0.0.0.0 area 0
network 10.180.0.10 0.0.0.0 area 0
network 10.180.0.14 0.0.0.0 area 0
network 172.16.30.4 0.0.0.0 area 0
```

!

PE05

```
router ospf 65111
router-id 172.16.30.5
auto-cost reference-bandwidth 10000
passive-interface default
no passive-interface GigabitEthernet0/0
no passive-interface GigabitEthernet0/1
network 10.180.0.13 0.0.0.0 area 0
network 10.180.0.18 0.0.0.0 area 0
network 172.16.30.5 0.0.0.0 area 0
```

!

P01

```
router ospf 65111
router-id 172.16.30.254
network point-to-point
passive enable
dead-interval 10
hello-interval 3
auto-cost reference-bandwidth 10000
```

area 0

interface Loopback2028

!

interface GigabitEthernet0/0/0/0

passive disable

!

interface GigabitEthernet0/0/0/1

passive disable

!

interface GigabitEthernet0/0/0/2

passive disable

!

MPLS CONFIGURATION

PE01

mpls ldp router-id Loopback2028 force

!

interface range gigabitEthernet 1-3

mpls ip

!

PE02

mpls ldp router-id Loopback2028 force

!

interface range gigabitEthernet 0/0-1

mpls ip

PE03

mpls ldp router-id Loopback2028 force

!

interface range gigabitEthernet 1-3

mpls ip

!

PE04

mpls ldp router-id Loopback2028 force

!

interface range gigabitEthernet 1-3

mpls ip

!

PE05

mpls ldp router-id Loopback2028 force

!

interface range gigabitEthernet 0/0-1

mpls ip

!

P01

mpls ldp

router-id 172.16.30.254

interface GigabitEthernet0/0/0/0

interface GigabitEthernet0/0/0/1

interface GigabitEthernet0/0/0/2

MP-BGP CONFIGURATION

P01 (RR-ACTIVE)

```
router bgp 65111
  bgp router-id 172.16.30.254
  bgp cluster-id 172.16.30.254
  address-family ipv4 unicast
  !
  address-family vpnv4 unicast
  !
  neighbor-group CORE-RR
    remote-as 65111
    password neolwin!!!!
    update-source Loopback2028
    address-family ipv4 unicast
    route-policy LOCAL in
    route-reflector-client
  !
  address-family vpnv4 unicast
    route-policy LOCAL in
    route-reflector-client
  !
  neighbor 172.16.30.2
    use neighbor-group CORE-RR
    description PE02
```


!
neighbor 172.16.30.3
use neighbor-group CORE-RR
description PE03

!
neighbor 172.16.30.4
use neighbor-group CORE-RR
description PE04

!
neighbor 172.16.30.5
use neighbor-group CORE-RR
description PE05

!
route-policy LOCAL
set local-preference 500
pass
end-policy

!
PE01 (RR-STANDBY)

router bgp 65111
bgp router-id 172.16.30.1
bgp cluster-id 172.16.30.254
neighbor CORE-RR peer-group
neighbor CORE-RR remote-as 65111

```
neighbor CORE-RR password neolwin!!!!  
neighbor CORE-RR update-source Loopback2028  
neighbor 172.16.30.2 peer-group CORE-RR  
neighbor 172.16.30.3 peer-group CORE-RR  
neighbor 172.16.30.4 peer-group CORE-RR  
neighbor 172.16.30.5 peer-group CORE-RR
```

```
!  
address-family ipv4  
neighbor CORE-RR route-reflector-client  
neighbor 172.16.30.2 activate  
neighbor 172.16.30.3 activate  
neighbor 172.16.30.4 activate  
neighbor 172.16.30.5 activate
```

```
exit-address-family
```

```
!  
address-family vpnv4  
neighbor CORE-RR send-community extended  
neighbor CORE-RR route-reflector-client  
neighbor 172.16.30.2 activate  
neighbor 172.16.30.3 activate  
neighbor 172.16.30.4 activate  
neighbor 172.16.30.5 activate
```

```
exit-address-family
```

```
!
```

PE02

```
router bgp 65111

  bgp router-id 172.16.30.2
  neighbor 172.16.30.1 remote-as 65111
  neighbor 172.16.30.1 password neolwin!!!!
  neighbor 172.16.30.1 update-source Loopback2028
  neighbor 172.16.30.254 remote-as 65111
  neighbor 172.16.30.254 password neolwin!!!!
  neighbor 172.16.30.254 update-source Loopback2028
!
address-family ipv4
  neighbor 172.16.30.1 activate
  neighbor 172.16.30.254 activate
exit-address-family
!
address-family vpnv4
  neighbor 172.16.30.1 activate
  neighbor 172.16.30.1 send-community extended
  neighbor 172.16.30.254 activate
  neighbor 172.16.30.254 send-community extended
exit-address-family
!
```

PE03

```
router bgp 65111
```

```
bgp router-id 172.16.30.3
neighbor 172.16.30.1 remote-as 65111
neighbor 172.16.30.1 password neolwin!!!!
neighbor 172.16.30.1 update-source Loopback2028
neighbor 172.16.30.254 remote-as 65111
neighbor 172.16.30.254 password neolwin!!!!
neighbor 172.16.30.254 update-source Loopback2028
!
address-family ipv4
  neighbor 172.16.30.1 activate
  neighbor 172.16.30.254 activate
exit-address-family
!
address-family vpnv4
  neighbor 172.16.30.1 activate
  neighbor 172.16.30.1 send-community extended
  neighbor 172.16.30.254 activate
  neighbor 172.16.30.254 send-community extended
exit-address-family
!
```

PE04

```
router bgp 65111
  bgp router-id 172.16.30.4
  neighbor 172.16.30.1 remote-as 65111
```

```
neighbor 172.16.30.1 password neolwin!!!!
neighbor 172.16.30.1 update-source Loopback2028
neighbor 172.16.30.254 remote-as 65111
neighbor 172.16.30.254 password neolwin!!!!
neighbor 172.16.30.254 update-source Loopback2028
!
address-family ipv4
  neighbor 172.16.30.1 activate
  neighbor 172.16.30.254 activate
exit-address-family
!
address-family vpnv4
  neighbor 172.16.30.1 activate
  neighbor 172.16.30.1 send-community extended
  neighbor 172.16.30.254 activate
  neighbor 172.16.30.254 send-community extended
exit-address-family
!
```

PE05

```
router bgp 65111
  bgp router-id 172.16.30.5
  neighbor 172.16.30.1 remote-as 65111
  neighbor 172.16.30.1 password neolwin!!!!
  neighbor 172.16.30.1 update-source Loopback2028
```

```
neighbor 172.16.30.254 remote-as 65111
neighbor 172.16.30.254 password neolwin!!!!
neighbor 172.16.30.254 update-source Loopback2028
```

!

```
address-family ipv4
```

```
neighbor 172.16.30.1 activate
```

```
neighbor 172.16.30.254 activate
```

```
exit-address-family
```

!

```
address-family vpnv4
```

```
neighbor 172.16.30.1 activate
```

```
neighbor 172.16.30.1 send-community extended
```

```
neighbor 172.16.30.254 activate
```

```
neighbor 172.16.30.254 send-community extended
```

```
exit-address-family
```

!

MPLS L3VPN CONFIGURATION

FOR VRF RED

PE-CE ROUTING

PE02

```
ip vrf RED
```

```
rd 65111:111
```

```
route-target export 65111:111
```

```
route-target import 65111:111
```

```
interface GigabitEthernet0/3
 ip vrf forwarding RED
 ip address 172.31.0.1 255.255.255.252
!
router bgp 65111
 address-family ipv4 vrf RED
  redistribute ospf 111 match internal external 1 external 2
 exit-address-family
!
router ospf 111 vrf RED
 router-id 192.168.0.2
 auto-cost reference-bandwidth 10000
 redistribute bgp 65111 subnets
 passive-interface default
 no passive-interface GigabitEthernet0/3
 network 172.31.0.1 0.0.0.0 area 0
!
```

RED-CE01

```
router ospf 111
 router-id 192.168.0.1
 auto-cost reference-bandwidth 10000
 passive-interface default
 no passive-interface FastEthernet0/0
 network 172.31.0.2 0.0.0.0 area 0
```

```
network 192.168.0.1 0.0.0.0 area 0
```

```
!
```

PE03

```
ip vrf RED
```

```
rd 65111:111
```

```
route-target export 65111:111
```

```
route-target import 65111:111
```

```
!
```

```
interface GigabitEthernet4
```

```
ip vrf forwarding RED
```

```
ip address 172.31.0.253 255.255.255.252
```

```
!
```

```
router bgp 65111
```

```
address-family ipv4 vrf RED
```

```
redistribute ospf 111 match internal external 1 external 2
```

```
exit-address-family
```

```
!
```

```
router ospf 111 vrf RED
```

```
router-id 192.168.1.2
```

```
auto-cost reference-bandwidth 10000
```

```
redistribute bgp 65111 subnets
```

```
passive-interface default
```

```
no passive-interface GigabitEthernet4
```

```
network 172.31.0.253 0.0.0.0 area 0
```


RED-CE02

```
router ospf 111  
router-id 192.168.1.1  
auto-cost reference-bandwidth 10000  
passive-interface default  
no passive-interface FastEthernet0/0  
network 172.31.0.254 0.0.0.0 area 0  
network 192.168.1.1 0.0.0.0 area 0  
!
```

FOR VRF GREEN

PE-CE ROUTING

PE05

```
ip vrf GREEN  
rd 65111:2222  
route-target export 65111:2222  
route-target import 65111:2222  
!  
interface GigabitEthernet0/3  
ip vrf forwarding GREEN  
ip address 192.168.255.1 255.255.255.252  
!  
router bgp 65111  
address-family ipv4 vrf GREEN  
redistribute ospf 2222 match internal external 1 external 2
```

exit-address-family

!

router ospf 2222 vrf GREEN

router-id 172.16.0.2

auto-cost reference-bandwidth 10000

redistribute bgp 65111 subnets

passive-interface default

no passive-interface GigabitEthernet0/3

network 192.168.255.1 0.0.0.0 area 0

!

GREEN-CE01

router ospf 2222

router-id 172.16.0.1

auto-cost reference-bandwidth 10000

passive-interface default

no passive-interface FastEthernet0/0

network 172.16.0.1 0.0.0.0 area 0

network 192.168.255.2 0.0.0.0 area 0

!

PE04

ip vrf GREEN

rd 65111:2222

route-target export 65111:2222

route-target import 65111:2222

!

interface GigabitEthernet4

ip vrf forwarding GREEN

ip address 192.168.255.253 255.255.255.252

!

router bgp 65111

address-family ipv4 vrf GREEN

redistribute ospf 2222 match internal external 1 external 2

exit-address-family

!

router ospf 2222 vrf GREEN

router-id 172.16.1.2

auto-cost reference-bandwidth 10000

redistribute bgp 65111 subnets

passive-interface default

no passive-interface GigabitEthernet4

network 192.168.255.253 0.0.0.0 area 0

!

GREEN-CE02

router ospf 2222

router-id 172.16.1.1

auto-cost reference-bandwidth 10000

passive-interface default

no passive-interface FastEthernet0/0

```
network 172.16.1.1 0.0.0.0 area 0  
network 192.168.255.254 0.0.0.0 area 0  
!
```

INTER-VRF ROUTING BETWEEN PE02 AND PE05 FOR VRF RED AND VRF GREEN

PE02

```
ip vrf RED  
rd 65111:111  
route-target import 65111:2222  
!
```

PE05

```
ip vrf GREEN  
rd 65111:2222  
route-target import 65111:111  
!
```

MPLS L2VPN CONFIGURATION

VPWS CONFIGURATION (PE02 – PE05) FOR BLUE SITE

PE02

```
pseudowire-class VPWS  
encapsulation mpls  
!  
interface GigabitEthernet0/2  
xconnect 172.16.30.5 100 pw-class VPWS  
!
```

PE05

```
pseudowire-class VPWS
    encapsulation mpls
!
interface GigabitEthernet0/2
xconnect 172.16.30.2 100 pw-class VPWS
!
```

VPLS CONFIGURATION (PE01 – PE03 & PE04) FOR YELLOW SITE

PE01

```
l2vpn vfi context VPLS
    vpn id 24
    member 172.16.30.3 encapsulation mpls
    member 172.16.30.4 encapsulation mpls
!
interface GigabitEthernet4
    service instance 1 ethernet
    encapsulation untagged
!
bridge-domain 24
    member GigabitEthernet4 service-instance 1
    member vfi VPLS
!
```

PE03

```
l2vpn vfi context VPLS
```

```
vpn id 24
member 172.16.30.1 encapsulation mpls
!
interface GigabitEthernet5
service instance 1 ethernet
encapsulation untagged
!
bridge-domain 24
member GigabitEthernet5 service-instance 1
member vfi VPLS
!
```

PE04

```
l2vpn vfi context VPLS
vpn id 24
member 172.16.30.1 encapsulation mpls
!
interface GigabitEthernet5
service instance 1 ethernet
encapsulation untagged
!
bridge-domain 24
member GigabitEthernet5 service-instance 1
member vfi VPLS
!
```

L2TPv3 CONFIGURATION (BLUE-CE01 – BLUE-CE02) FOR BLUE-R01 & BLUE-R02

BLUE-CE01

```
ip route 192.168.168.2 255.255.255.255 10.0.0.254
```

```
!
```

```
pseudowire-class L2TPV3
```

```
encapsulation l2tpv3
```

```
ip local interface Loopback0
```

```
!
```

```
interface FastEthernet6/0
```

```
xconnect 192.168.168.2 100 pw-class L2TPV3
```

```
!
```

BLUE-CE02

```
ip route 192.168.168.1 255.255.255.255 10.0.0.253
```

```
!
```

```
pseudowire-class L2TPV3
```

```
encapsulation l2tpv3
```

```
ip local interface Loopback0
```

```
!
```

```
interface FastEthernet6/0
```

```
xconnect 192.168.168.1 100 pw-class L2TPV3
```

```
!
```

BGP PEERING WITH UPSTREAM ISP AND ENTERPRISE CUSTOMER

WITH UPSTREAM ISP

UPSTREAM-ISP

```
router bgp 1500  
  
bgp router-id 8.8.8.8  
  
network 8.8.8.8 mask 255.255.255.255  
  
network 203.81.84.252 mask 255.255.255.252  
  
network 203.81.85.252 mask 255.255.255.252  
  
neighbor 203.81.84.254 remote-as 2028  
  
neighbor 203.81.84.254 password neolwin!!!!  
  
neighbor 203.81.85.254 remote-as 2028  
  
neighbor 203.81.85.254 password neolwin!!!!
```

!

PE02

```
router bgp 65111  
  
neighbor 203.81.84.253 remote-as 1500  
  
neighbor 203.81.84.253 local-as 2028 no-prepend replace-as  
  
neighbor 203.81.84.253 password neolwin!!!!
```

!

```
address-family ipv4  
  
neighbor 172.16.30.1 next-hop-self  
  
neighbor 172.16.30.254 next-hop-self  
  
neighbor 203.81.84.253 activate  
  
exit-address-family
```


PE03

```
router bgp 65111
  neighbor 203.81.85.253 remote-as 1500
  neighbor 203.81.85.253 local-as 2028 no-prepend replace-as
  neighbor 203.81.85.253 password neolwin!!!!
!
address-family ipv4
  neighbor 172.16.30.1 next-hop-self
  neighbor 172.16.30.254 next-hop-self
  neighbor 203.81.85.253 activate
exit-address-family
!
```

WITH ENTERPRISE CUSTOMER

PE05

```
router bgp 65111
  neighbor 203.81.84.2 remote-as 8143
  neighbor 203.81.84.2 local-as 2028 no-prepend replace-as
  neighbor 203.81.84.2 password neolwin!!!!
!
address-family ipv4
  network 203.81.84.0 mask 255.255.255.252
  neighbor 203.81.84.2 activate
exit-address-family
!
```

BGP-CUS01

```
router bgp 8143  
  
bgp router-id 203.81.84.2  
  
network 172.172.172.172 mask 255.255.255.255  
  
neighbor 203.81.84.1 remote-as 2028  
  
neighbor 203.81.84.1 password neolwin!!!!
```

!

```
router ospf 8143  
  
router-id 10.100.0.1  
  
auto-cost reference-bandwidth 10000  
  
passive-interface default  
  
no passive-interface GigabitEthernet0/1  
  
network 10.100.0.1 0.0.0.0 area 0  
  
default-information originate always
```

!

R01

```
router ospf 8143  
  
router-id 172.172.172.172  
  
auto-cost reference-bandwidth 10000  
  
passive-interface default  
  
no passive-interface FastEthernet0/0  
  
network 10.100.0.2 0.0.0.0 area 0  
  
network 172.172.172.172 0.0.0.0 area 0
```

!

WITH ENTERPRISE CUSTOMER WITHOUT BGP

PE04

router bgp 65111

address-family ipv4

network 203.81.85.0 mask 255.255.255.252

exit-address-family

!

BGP-CUS02

ip route 0.0.0.0 0.0.0.0 203.81.85.1

!

ip access-list extended NAT-ACL

permit ip host 192.168.10.1 any

!

ip nat inside source list NAT-ACL interface GigabitEthernet0/0 overload

!

interface GigabitEthernet0/0

ip address 203.81.85.2 255.255.255.252

ip nat outside

!

PRIVATE IP FILTERING AT CUSTOMER-FACING PE

PE05

ip prefix-list PRIVATE-IPS seq 10 permit 10.0.0.0/8 le 32

ip prefix-list PRIVATE-IPS seq 20 permit 172.16.0.0/12 le 32

ip prefix-list PRIVATE-IPS seq 30 permit 192.168.0.0/16 le 32

!

```
route-map PRIVATE deny 10
```

```
match ip address prefix-list PRIVATE-IPS
```

```
route-map PRIVATE permit 100
```

!

```
router bgp 65111
```

```
address-family ipv4
```

```
neighbor 203.81.84.2 route-map PRIVATE in
```

!

PING AND TRACEROUTE RESULTS

RED-CE01

```
RED-CE01#ping 192.168.1.1 source lo0 repeat 100
Type escape sequence to abort.
Sending 100, 100-byte ICMP Echos to 192.168.1.1, timeout is 2 seconds:
Packet sent with a source address of 192.168.0.1
!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
```

```
RED-CE01#traceroute 192.168.1.1 source lo0
Type escape sequence to abort.
Tracing the route to 192.168.1.1
VRF info: (vrf in name/id, vrf out name/id)
 1 172.31.0.1 60 msec 56 msec 48 msec
 2 172.31.0.253 [MPLS: Label 28 Exp 0] 48 msec 60 msec 52 msec
 3 172.31.0.254 52 msec * 28 msec
```

RED-CE02

```
RED-CE02#ping 192.168.0.1 source lo0 repeat 100
Type escape sequence to abort.
Sending 100, 100-byte ICMP Echos to 192.168.0.1, timeout is 2 seconds:
Packet sent with a source address of 192.168.1.1
!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
```

```
RED-CE02#traceroute 192.168.0.1 source lo0
Type escape sequence to abort.
Tracing the route to 192.168.0.1
VRF info: (vrf in name/id, vrf out name/id)
 1 172.31.0.253 80 msec 52 msec 48 msec
 2 172.31.0.1 [MPLS: Label 28 Exp 0] 52 msec 56 msec 56 msec
 3 172.31.0.2 52 msec * 48 msec
```

GREEN-CE01

```
GREEN-CE01#ping 172.16.1.1 source lo0 repeat 100
Type escape sequence to abort.
Sending 100, 100-byte ICMP Echos to 172.16.1.1, timeout is 2 seconds:
Packet sent with a source address of 172.16.0.1
!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
```

```
GREEN-CE01#traceroute 172.16.1.1 source lo0
Type escape sequence to abort.
Tracing the route to 172.16.1.1
VRF info: (vrf in name/id, vrf out name/id)
 1 192.168.255.1 52 msec 56 msec 52 msec
 2 192.168.255.253 [MPLS: Label 27 Exp 0] 48 msec 56 msec 52 msec
 3 192.168.255.254 52 msec * 36 msec
```

GREEN-CE02

```
GREEN-CE02#ping 172.16.0.1 source lo0 repeat 100
Type escape sequence to abort.
Sending 100, 100-byte ICMP Echos to 172.16.0.1, timeout is 2 seconds:
Packet sent with a source address of 172.16.1.1
!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
```

```
GREEN-CE02#traceroute 172.16.0.1 source lo0
Type escape sequence to abort.
Tracing the route to 172.16.0.1
VRF info: (vrf in name/id, vrf out name/id)
 1 192.168.255.253 80 msec 56 msec 52 msec
 2 192.168.255.1 [MPLS: Label 28 Exp 0] 52 msec 52 msec 56 msec
 3 192.168.255.2 60 msec * 32 msec
```

YELLOW-CE01

```
YELLOW-CE01#ping 192.168.2.2 source lo0 repeat 100
Type escape sequence to abort.
Sending 100, 100-byte ICMP Echos to 192.168.2.2, timeout is 2 seconds:
Packet sent with a source address of 192.168.2.1
!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
```

```
YELLOW-CE01#ping 192.168.2.3 source lo0 repeat 100
Type escape sequence to abort.
Sending 100, 100-byte ICMP Echos to 192.168.2.3, timeout is 2 seconds:
Packet sent with a source address of 192.168.2.1
!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
```

```
YELLOW-CE01#traceroute 192.168.2.2 source lo0
Type escape sequence to abort.
Tracing the route to 192.168.2.2
VRF info: (vrf in name/id, vrf out name/id)
 1 10.0.0.2 60 msec * 40 msec
```

```
YELLOW-CE01#traceroute 192.168.2.3 source lo0
Type escape sequence to abort.
Tracing the route to 192.168.2.3
VRF info: (vrf in name/id, vrf out name/id)
 1 10.0.0.3 56 msec * 44 msec
```

YELLOW-CE02

```
YELLOW-CE02#ping 192.168.2.1 source lo0 repeat 100
Type escape sequence to abort.
Sending 100, 100-byte ICMP Echos to 192.168.2.1, timeout is 2 seconds:
Packet sent with a source address of 192.168.2.2
!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
```

```
YELLOW-CE02#ping 192.168.2.3 source lo0 repeat 100
Type escape sequence to abort.
Sending 100, 100-byte ICMP Echos to 192.168.2.3, timeout is 2 seconds:
Packet sent with a source address of 192.168.2.2
!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
```

```
YELLOW-CE02#traceroute 192.168.2.1 source lo0
Type escape sequence to abort.
Tracing the route to 192.168.2.1
VRF info: (vrf in name/id, vrf out name/id)
 1 10.0.0.1 56 msec * 48 msec
```

```
YELLOW-CE02#traceroute 192.168.2.3 source lo0
Type escape sequence to abort.
Tracing the route to 192.168.2.3
VRF info: (vrf in name/id, vrf out name/id)
 1 10.0.0.1 56 msec 52 msec 52 msec
 2 10.0.0.3 52 msec * 56 msec
```

YELLOW-CE03

```
YELLOW-CE03#ping 192.168.2.1 source lo0 repeat 100
Type escape sequence to abort.
Sending 100, 100-byte ICMP Echos to 192.168.2.1, timeout is 2 seconds:
Packet sent with a source address of 192.168.2.3
!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
```

```
YELLOW-CE03#ping 192.168.2.2 source lo0 repeat 100
Type escape sequence to abort.
Sending 100, 100-byte ICMP Echos to 192.168.2.2, timeout is 2 seconds:
Packet sent with a source address of 192.168.2.3
!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
```

```
YELLOW-CE03#traceroute 192.168.2.1 source lo0
Type escape sequence to abort.
Tracing the route to 192.168.2.1
VRF info: (vrf in name/id, vrf out name/id)
 1 10.0.0.1 56 msec * 44 msec
```

```
YELLOW-CE03#traceroute 192.168.2.2 source lo0
Type escape sequence to abort.
Tracing the route to 192.168.2.2
VRF info: (vrf in name/id, vrf out name/id)
 1 10.0.0.1 56 msec 52 msec 48 msec
 2 10.0.0.2 52 msec * 32 msec
```

BLUE-CE01

```
BLUE-CE01#ping 192.168.168.2 source lo0 repeat 100
Type escape sequence to abort.
Sending 100, 100-byte ICMP Echos to 192.168.168.2, timeout is 2 seconds:
Packet sent with a source address of 192.168.168.1
!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
```

```
BLUE-CE01#traceroute 192.168.168.2 source lo0
Type escape sequence to abort.
Tracing the route to 192.168.168.2
VRF info: (vrf in name/id, vrf out name/id)
 1 10.0.0.254 36 msec * 48 msec
```

BLUE-CE02

```
BLUE-CE02#ping 192.168.168.1 source lo0 repeat 100
Type escape sequence to abort.
Sending 100, 100-byte ICMP Echos to 192.168.168.1, timeout is 2 seconds:
Packet sent with a source address of 192.168.168.2
!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
```

```
BLUE-CE02#traceroute 192.168.168.1 source lo0
Type escape sequence to abort.
Tracing the route to 192.168.168.1
VRF info: (vrf in name/id, vrf out name/id)
 1 10.0.0.253 56 msec * 52 msec
```

BLUE-R01

```
BLUE-R01#ping 192.168.100.250 source lo0 repeat 100
Type escape sequence to abort.
Sending 100, 100-byte ICMP Echos to 192.168.100.250, timeout is 2 seconds:
Packet sent with a source address of 192.168.100.1
!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
```

```
BLUE-R01#traceroute 192.168.100.250
Type escape sequence to abort.
Tracing the route to 192.168.100.250
VRF info: (vrf in name/id, vrf out name/id)
 1 172.16.19.254 56 msec * 40 msec
```


BLUE-R02

```
BLUE-R02#ping 192.168.100.1 source lo0 repeat 100
Type escape sequence to abort.
Sending 100, 100-byte ICMP Echos to 192.168.100.1, timeout is 2 seconds:
Packet sent with a source address of 192.168.100.250
!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
```

```
BLUE-R02#traceroute 192.168.100.1 source lo0
Type escape sequence to abort.
Tracing the route to 192.168.100.1
VRF info: (vrf in name/id, vrf out name/id)
 1 172.16.19.253 52 msec * 120 msec
```

R01(BGP-CUS01)

```
R01#ping 8.8.8.8 source lo0 repeat 100
Type escape sequence to abort.
Sending 100, 100-byte ICMP Echos to 8.8.8.8, timeout is 2 seconds:
Packet sent with a source address of 172.172.172.172
!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
```

```
R01#traceroute 8.8.8.8 source lo0
Type escape sequence to abort.
Tracing the route to 8.8.8.8
VRF info: (vrf in name/id, vrf out name/id)
 1 10.100.0.1 56 msec 52 msec 56 msec
 2 203.81.84.1 48 msec 52 msec 52 msec
 3 10.180.0.14 [MPLS: Label 17 Exp 0] 52 msec 52 msec 52 msec
 4 10.180.0.9 56 msec 56 msec 52 msec
 5 203.81.85.253 56 msec * 32 msec
```

BGP-CUS02

```
BGP-CUS02#ping 8.8.8.8 source lo0 repeat 100
Type escape sequence to abort.
Sending 100, 100-byte ICMP Echos to 8.8.8.8, timeout is 2 seconds:
Packet sent with a source address of 192.168.10.1
!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
```

```

BGP-CUS02#traceroute 8.8.8.8 source lo0
Type escape sequence to abort.
Tracing the route to 8.8.8.8
VRF info: (vrf in name/id, vrf out name/id)
 1 203.81.85.1 8 msec 4 msec 3 msec
 2 10.180.0.9 6 msec 6 msec 4 msec
 3 203.81.85.253 12 msec * 10 msec

```

UPSTREAM-ISP

```

172.172.0.0/32 is subnetted, 1 subnets
B      172.172.172.172 [20/0] via 203.81.84.254, 03:21:56
203.81.84.0/24 is variably subnetted, 3 subnets, 2 masks
B      203.81.84.0/30 [20/0] via 203.81.84.254, 03:21:56
203.81.85.0/24 is variably subnetted, 3 subnets, 2 masks
B      203.81.85.0/30 [20/0] via 203.81.85.254, 03:22:38
UPSTREAM-ISP#

```

```

      Network          Next Hop           Metric LocPrf Weight Path
*>  8.8.8.8/32         0.0.0.0              0         32768 i
*   172.172.172.172/32
      203.81.85.254
*>      203.81.84.254              0 2028 8143 i
*   203.81.84.0/30     203.81.85.254              0 2028 i
*>      203.81.84.254              0 2028 i
*>  203.81.84.252/30  0.0.0.0              0         32768 i
*   203.81.85.0/30     203.81.84.254              0 2028 i
*>      203.81.85.254              0 2028 i
*>  203.81.85.252/30  0.0.0.0              0         32768 i
UPSTREAM-ISP#

```

IP ADDRESSING ASSIGNMENT

P01

Loopback2028	172.16.30.254
GigabitEthernet0/0/0/0	10.7.135.2
GigabitEthernet0/0/0/1	10.7.135.5
GigabitEthernet0/0/0/2	10.7.135.9

PE01

GigabitEthernet1	10.180.0.17
GigabitEthernet2	10.180.0.2
GigabitEthernet3	10.7.135.1
Loopback2028	172.16.30.1

PE02

GigabitEthernet0/0	10.180.0.5
GigabitEthernet0/1	10.180.0.1
GigabitEthernet0/3	172.31.0.1
GigabitEthernet0/4	203.81.84.254
Loopback2028	172.16.30.2

PE03

GigabitEthernet1	10.180.0.6
GigabitEthernet2	10.180.0.9
GigabitEthernet3	10.7.135.6
GigabitEthernet4	172.31.0.253
GigabitEthernet6	203.81.85.254
Loopback2028	172.16.30.3

PE04

GigabitEthernet1	10.180.0.14
GigabitEthernet2	10.180.0.10
GigabitEthernet3	10.7.135.10
GigabitEthernet4	192.168.255.253
GigabitEthernet6	203.81.85.1
Loopback2028	172.16.30.4

PE05

GigabitEthernet0/0	10.180.0.13
GigabitEthernet0/1	10.180.0.18
GigabitEthernet0/3	192.168.255.1
GigabitEthernet0/4	203.81.84.1
Loopback2028	172.16.30.5

UPSTREAM-ISP

GigabitEthernet0/0	203.81.84.253
GigabitEthernet0/1	203.81.85.253
Loopback0	8.8.8.8

BGP-CUS01

GigabitEthernet0/0	203.81.84.2
GigabitEthernet0/1	10.100.0.1

R01

FastEthernet0/0	10.100.0.2
Loopback0	172.172.172.172

BGP-CUS02

GigabitEthernet0/0	203.81.85.2
Loopback0	192.168.10.1

RED-CE01

FastEthernet0/0	172.31.0.2
Loopback0	192.168.0.1

RED-CE02

FastEthernet0/0	172.31.0.254
-----------------	--------------

Loopback0 192.168.1.1

GREEN-CE01

FastEthernet0/0 192.168.255.2

Loopback0 172.16.0.1

GREEN-CE02

FastEthernet0/0 192.168.255.254

Loopback0 172.16.1.1

YELLOW-CE01

FastEthernet0/0 10.0.0.1

Loopback0 192.168.2.1

YELLOW-CE02

FastEthernet0/0 10.0.0.2

Loopback0 192.168.2.2

YELLOW-CE03

FastEthernet0/0 10.0.0.3

Loopback0 192.168.2.3

BLUE-CE01

FastEthernet0/0 10.0.0.253

Loopback0 192.168.168.1

BLUE-R01

FastEthernet0/0 172.16.19.253

Loopback0 192.168.100.1

BLUE-CE02

FastEthernet0/0

10.0.0.254

Loopback0

192.168.168.2

BLUE-R02

FastEthernet0/0

172.16.19.254

Loopback0

192.168.100.250

Ko Lwin (Network)

January 18, 2026 (SUN) / 16:15

Ikanet