


Seamless (or) Unified MPLS Basic LAB



Lab Requirements

1. Make single MPLS Domain From 3 different MPLS domains with different IGPs.
2. Make reachability for VRF S1 and VRF OAM.

Configuring IGP

PE01

```
router ospf 65001
router-id 172.29.29.3
auto-cost reference-bandwidth 10000
passive-interface default
no passive-interface GigabitEthernet0/0
network 10.180.0.2 0.0.0.0 area 0
network 172.29.29.3 0.0.0.0 area 0
```

!

P01

```
router ospf 65001
router-id 172.29.29.1
auto-cost reference-bandwidth 10000
```

```
passive-interface default
no passive-interface GigabitEthernet0/0
network 10.180.0.1 0.0.0.0 area 0
network 172.29.29.1 0.0.0.0 area 0
!
router isis NEOTEL
net 49.0001.8143.5456.1501.00
is-type level-2-only
advertise passive-only
metric-style wide
passive-interface Loopback0
!
```

P02

```
router ospf 65002
router-id 172.29.29.2
auto-cost reference-bandwidth 10000
passive-interface default
no passive-interface GigabitEthernet0/0
network 10.180.0.253 0.0.0.0 area 0
network 172.29.29.2 0.0.0.0 area 0
!
router isis NEOTEL
net 49.0001.8143.5456.1502.00
is-type level-2-only
advertise passive-only
metric-style wide
passive-interface Loopback0
!
```

PE02

```
router ospf 65002
  router-id 172.29.29.4
  auto-cost reference-bandwidth 10000
  passive-interface default
  no passive-interface GigabitEthernet0/0
  network 10.180.0.254 0.0.0.0 area 0
  network 172.29.29.4 0.0.0.0 area 0
```

!

Configure MPLS in Respective Interfaces

!

Configure BGP

PE01

```
router bgp 65000
  bgp router-id 172.29.29.3
  neighbor 172.29.29.1 remote-as 65000
  neighbor 172.29.29.1 password !@#$%
  neighbor 172.29.29.1 update-source Loopback0
```

!

```
  address-family ipv4
```

```
    neighbor 172.29.29.1 activate
```

```
    neighbor 172.29.29.1 send-label
```

```
  exit-address-family
```

!

```
  address-family vpng4
```

```
    neighbor 172.29.29.1 activate
```

```
    neighbor 172.29.29.1 send-community extended
```

```
  exit-address-family
```

!

```
address-family ipv4 vrf OAM
```

```
 redistribute static
```

```
 exit-address-family
```

```
!
```

```
address-family ipv4 vrf S1
```

```
 redistribute static
```

```
 exit-address-family
```

```
!
```

P01

```
router bgp 65000
```

```
bgp router-id 172.29.29.1
```

```
neighbor 172.29.29.2 remote-as 65000
```

```
neighbor 172.29.29.2 password !@#$
```

```
neighbor 172.29.29.2 update-source Loopback0
```

```
neighbor 172.29.29.3 remote-as 65000
```

```
neighbor 172.29.29.3 password !@#$
```

```
neighbor 172.29.29.3 update-source Loopback0
```

```
!
```

```
address-family ipv4
```

```
neighbor 172.29.29.2 activate
```

```
neighbor 172.29.29.2 route-reflector-client
```

```
neighbor 172.29.29.2 next-hop-self all
```

```
neighbor 172.29.29.2 send-label
```

```
neighbor 172.29.29.3 activate
```

```
neighbor 172.29.29.3 route-reflector-client
```

```
neighbor 172.29.29.3 next-hop-self all
```

```
neighbor 172.29.29.3 send-label
```

```
exit-address-family
```

```
!
```

```
address-family vpnv4
```

```
neighbor 172.29.29.2 activate
neighbor 172.29.29.2 send-community extended
neighbor 172.29.29.2 route-reflector-client
neighbor 172.29.29.2 next-hop-self all
neighbor 172.29.29.3 activate
neighbor 172.29.29.3 send-community extended
neighbor 172.29.29.3 route-reflector-client
neighbor 172.29.29.3 next-hop-self all
exit-address-family
```

!

P02

```
router bgp 65000
bgp router-id 172.29.29.2
neighbor 172.29.29.1 remote-as 65000
neighbor 172.29.29.1 password !@#$
neighbor 172.29.29.1 update-source Loopback0
neighbor 172.29.29.4 remote-as 65000
neighbor 172.29.29.4 password !@#$
neighbor 172.29.29.4 update-source Loopback0
```

!

address-family ipv4

```
neighbor 172.29.29.1 activate
neighbor 172.29.29.1 route-reflector-client
neighbor 172.29.29.1 next-hop-self all
neighbor 172.29.29.1 send-label
neighbor 172.29.29.4 activate
neighbor 172.29.29.4 route-reflector-client
neighbor 172.29.29.4 next-hop-self all
neighbor 172.29.29.4 send-label
exit-address-family
```

!

```
address-family vpnv4
neighbor 172.29.29.1 activate
neighbor 172.29.29.1 send-community extended
neighbor 172.29.29.1 route-reflector-client
neighbor 172.29.29.1 next-hop-self all
neighbor 172.29.29.4 activate
neighbor 172.29.29.4 send-community extended
neighbor 172.29.29.4 route-reflector-client
neighbor 172.29.29.4 next-hop-self all
exit-address-family
```

!

PE02

```
router bgp 65000
bgp router-id 172.29.29.4
neighbor 172.29.29.2 remote-as 65000
neighbor 172.29.29.2 password !@#$%
neighbor 172.29.29.2 update-source Loopback0
!
```

```
address-family ipv4
neighbor 172.29.29.2 activate
neighbor 172.29.29.2 send-label
exit-address-family
```

!

```
address-family vpnv4
neighbor 172.29.29.2 activate
neighbor 172.29.29.2 send-community extended
exit-address-family
```

!

```
address-family ipv4 vrf OAM
```

```

redistribute static
exit-address-family
!
address-family ipv4 vrf S1
redistribute static
exit-address-family
!

```

Verification For VRF S1 and VRF OAM

PE01

Network	Next Hop	Metric	LocPrf	Weight	Path
Route Distinguisher: 65000:1 (default for vrf S1)					
*> 172.17.0.0/24	10.7.235.2	0		32768	?
*>i 172.18.0.0/24	172.29.29.1	0	100	0	?
Route Distinguisher: 65000:2 (default for vrf OAM)					
*>i 172.29.0.0/24	172.29.29.1	0	100	0	?
*> 172.30.0.0/24	10.7.135.2	0		32768	?

PE02

Network	Next Hop	Metric	LocPrf	Weight	Path
Route Distinguisher: 65000:1 (default for vrf S1)					
*>i 172.17.0.0/24	172.29.29.2	0	100	0	?
*> 172.18.0.0/24	10.7.135.2	0		32768	?
Route Distinguisher: 65000:2 (default for vrf OAM)					
*> 172.29.0.0/24	10.7.235.2	0		32768	?
*>i 172.30.0.0/24	172.29.29.2	0	100	0	?

Unified MPLS or Seamless MPLS

Seamless MPLS provides a highly flexible and scalable architecture to integrate multiple networks into a single MPLS domain.

