

## IPSEC VTI with IKEv2

S01\_CSR01

interface Tunnel2028

ip address 172.16.0.253 255.255.255.252

tunnel source 222.255.255.254

tunnel mode ipsec ipv4

tunnel destination 11.2.24.254

tunnel protection ipsec profile IPSEC\_VTI\_PRO

!

crypto ikev2 proposal VTI\_PROPO

encryption aes-cbc-256

integrity sha512

group 14

!

crypto ikev2 policy VTI\_POL

proposal VTI\_PROPO

!

crypto ikev2 keyring VTI\_KEYRING

peer SITE-02

address 11.2.24.254

pre-shared-key local zte!@#

pre-shared-key remote zte123

!

!

```
crypto ikev2 profile VTI_PRO_01  
match identity remote address 11.2.24.254  
authentication remote pre-share  
authentication local pre-share  
keyring local VTI_KEYRING
```

!

```
crypto ipsec transform-set VTI_SET esp-aes esp-sha-hmac  
mode transport
```

!

```
crypto ipsec profile IPSEC_VTI_PRO  
set transform-set VTI_SET  
set ikev2-profile VTI_PRO_01
```

!

S02\_CSR01

```
interface Tunnel2028  
ip address 172.16.0.254 255.255.255.252  
tunnel source 11.2.24.254  
tunnel mode ipsec ipv4  
tunnel destination 222.255.255.254  
tunnel protection ipsec profile IPSEC_VTI_PRO  
!  
crypto ikev2 proposal VTI_PROPO
```

encryption aes-cbc-256

integrity sha512

group 14

!

crypto ikev2 policy VTI\_POL

proposal VTI\_PROPO

!

crypto ikev2 keyring VTI\_KEYRING

peer SITE-01

address 222.255.255.254

pre-shared-key local zte123

pre-shared-key remote zte!@#

!

!

crypto ikev2 profile VTI\_PRO\_01

match identity remote address 222.255.255.254

authentication remote pre-share

authentication local pre-share

keyring local VTI\_KEYRING

!

crypto ipsec transform-set VTI\_SET esp-aes esp-sha-hmac

mode transport


!

```
crypto ipsec profile IPSEC_VTI_PRO
```

```
set transform-set VTI_SET
```

```
set ikev2-profile VTI_PRO_01
```

```
!
```



K