


## Redistribution

### Route-tag, Unequal Cost Loadbalancing And Leak-map



### Lab Requirements

1. Make a *multi-point two-way redistribution* between OSPF-1500 and EIGRP-528 (LKANET) at S1-R02 and S2-R02 using *route-tag* for loop prevention.
2. Make *unequal cost loadbalancing* between S2-R03 and S2-R01 for Serial link and Ethernet link.
3. Config EIGRP *leak-map* for the networks behind S2-R01 to advertise S2-R03 that Serial link for 172.16.0.1, 172.16.1.1 and Ethernet link for 172.16.2.1, 172.16.3.1.

### OSPF Configurations

*hello interval is 2s, dead interval is 11s and network type is point-to-point.*

#### S1-R01

```
router ospf 1500
```

```
router-id 222.255.255.1
```

```
auto-cost reference-bandwidth 1000
```

passive-interface default

no passive-interface **FastEthernet0/0**

no passive-interface **FastEthernet1/0**

network 10.106.0.1 0.0.0.0 area 0

network 192.168.0.1 0.0.0.0 area 0

network 192.168.1.1 0.0.0.0 area 0

network 192.168.2.1 0.0.0.0 area 0

network 192.168.3.1 0.0.0.0 area 0

network 192.192.0.1 0.0.0.0 area 0

network 222.255.255.1 0.0.0.0 area 0

!

### **S1-R02**

router **ospf 1500**

router-id 222.255.255.2

auto-cost reference-bandwidth **1000**

passive-interface default

no passive-interface **GigabitEthernet1**

network 10.106.0.2 0.0.0.0 area 0

network 222.255.255.2 0.0.0.0 area 0

!

### **S2-R02**

router **ospf 1500**

router-id 222.255.255.3

```
auto-cost reference-bandwidth 1000

passive-interface default

no passive-interface GigabitEthernet1

network 192.192.0.2 0.0.0.0 area 0

network 222.255.255.3 0.0.0.0 area 0

!
```

### EIGRP Configurations

*hello timer is 2s and hold timer is 11s.*

#### S1-R02

```
router eigrp LKANET

!

address-family ipv4 unicast autonomous-system 528

!

af-interface default

passive-interface

exit-af-interface

!

af-interface GigabitEthernet2

hello-interval 2

hold-time 11

no passive-interface

exit-af-interface
```

```
!  
network 172.16.192.169 0.0.0.0  
eigrp router-id 222.255.255.2
```

```
!
```

### S2-R02

```
router eigrp LKANET
```

```
!
```

```
address-family ipv4 unicast autonomous-system 528
```

```
!
```

```
af-interface default
```

```
passive-interface
```

```
exit-af-interface
```

```
!
```

```
af-interface GigabitEthernet2
```

```
hello-interval 2
```

```
hold-time 11
```

```
no passive-interface
```

```
exit-af-interface
```

```
!
```

```
network 192.168.172.17 0.0.0.0
```

```
eigrp router-id 222.255.255.3
```

```
!
```

### S2-R03

router **eigrp LKANET**

!

address-family **ipv4 unicast autonomous-system 528**

!

af-interface **default**

passive-interface

exit-af-interface

!

af-interface **Ethernet0/3**

hello-interval **2**

hold-time **11**

no passive-interface

exit-af-interface

!

af-interface **Serial1/1**

hello-interval **2**

hold-time **11**

no passive-interface

exit-af-interface

!

af-interface **Ethernet0/0**

hello-interval **2**

hold-time 11

no passive-interface

exit-af-interface

!

af-interface Ethernet0/1

hello-interval 2

hold-time 11

no passive-interface

exit-af-interface

!

network 10.180.2.29 0.0.0.0

network 10.255.255.253 0.0.0.0

network 172.16.192.170 0.0.0.0

network 192.168.172.18 0.0.0.0

eigrp router-id 222.255.255.253

!

### S2-R01

router eigrp LKANET

!

address-family ipv4 unicast autonomous-system 528

!

af-interface default

passive-interface

```
exit-af-interface
!
af-interface Serial1/1
hello-interval 2
hold-time 11
no passive-interface
exit-af-interface
!
af-interface Ethernet0/1
hello-interval 2
hold-time 11
no passive-interface
exit-af-interface
!
network 10.180.2.30 0.0.0.0
network 10.255.255.254 0.0.0.0
network 172.16.0.1 0.0.0.0
network 172.16.1.1 0.0.0.0
network 172.16.2.1 0.0.0.0
network 172.16.3.1 0.0.0.0
eigrp router-id 222.255.255.254
!
```

## Redistribution With Route-tag

### S1-R02

```
route-map O_TO_E permit 10
```

```
set tag 111
```

```
!
```

```
route-map O_TO_E deny 20
```

```
match tag 999
```

```
!
```

```
route-map E_TO_O permit 10
```

```
set tag 999
```

```
!
```

```
route-map E_TO_O deny 20
```

```
match tag 111
```

```
!
```

```
router ospf 1500
```

```
redistribute eigrp 528 metric 110 subnets route-map E_TO_O
```

```
!
```

```
router eigrp LKANET
```

```
!
```

```
address-family ipv4 unicast autonomous-system 528
```

```
!
```

```
topology base
```



```
redistribute ospf 1500 match internal external 1 external 2 metric 1000000 1 255 1  
1500 route-map O_TO_E
```

```
!
```

## S2-R02

```
route-map O_TO_E permit 10
```

```
set tag 111
```

```
!
```

```
route-map O_TO_E deny 20
```

```
match tag 999
```

```
!
```

```
route-map E_TO_O permit 10
```

```
set tag 999
```

```
!
```

```
route-map E_TO_O deny 20
```

```
match tag 111
```

```
!
```

```
router ospf 1500
```

```
redistribute eigrp 528 metric 110 subnets route-map E_TO_O
```

```
!
```

```
router eigrp LKANET
```

```
!
```

```
address-family ipv4 unicast autonomous-system 528
```

```
!
```

topology base

```
redistribute ospf 1500 match internal external 1 external 2 metric 100000 1 255 1  
1500 route-map O_TO_E
```

!

## Unequal Cost Loadbalancing

### S2-R03

router eigrp LKANET

!

address-family ipv4 unicast autonomous-system 528

!

topology base

*variance 14*

!

### S2-R01

router eigrp LKANET

!

address-family ipv4 unicast autonomous-system 528

!

topology base

*variance 10*

!

## Leak-map Configuration

### S2-R01

access-list 10 permit 172.16.1.1

access-list 10 permit 172.16.0.1

access-list 20 permit 172.16.3.1

access-list 20 permit 172.16.2.1

!

route-map SERIAL permit 10

match ip address 10

!

route-map ETHERNET permit 10

match ip address 20

!

router eigrp LKANET

!

address-family ipv4 unicast autonomous-system 528

!

af-interface Serial1/1

*summary-address 172.16.0.0 255.255.252.0 leak-map SERIAL*

!

af-interface Ethernet0/1

*summary-address 172.16.0.0 255.255.252.0 leak-map ETHERNET*

!

## Unequal Cost Loadbalancing Calculation

We need to know FD Value (Feasible Distance) of Successor and Feasible Successor of a specific route.

For example,

Successor = 150456

Feasible Successor = 1456123

So, We need to multiply FD of Successor with a number and the result must be more than FD of Feasible Successor.

$$150456 \times 10 = 1504560 > 1456123$$

Thus, Variance is 10.