



C++ server

0.1

Launch a C++ server on your computer

Contents

0.1	Introduction	1
0.2	Installation	1
0.3	Class Index	1
0.3.1	Class List	1
0.4	File Index	1
0.4.1	File List	1
0.5	Class Documentation	2
0.5.1	Data Struct Reference	2
0.5.1.1	Detailed Description	2
0.5.2	Question Class Reference	2
0.5.3	QuestionBank Class Reference	2
0.5.4	Server Class Reference	3
0.5.4.1	Detailed Description	3
0.6	File Documentation	3
0.6.1	server.h File Reference	3
0.6.1.1	Macro Definition Documentation	4
0.6.1.2	Typedef Documentation	4
0.6.2	ssl.h File Reference	5
	Index	7

0.1 Introduction

This program launches the server on the specified port on the header file (localhost:5000).

This server accepts commands such as:

question#n

(for n in (0, max)) it returns a JSON string containing the question(string, type, options)

0.2 Installation

cd into this folder

type:

make clean

make

To run the server type:

****./server****

0.3 Class Index

0.3.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

Data		
	All transmitted info == 1 data	2
Question	2
QuestionBank	2
Server		
	Server object	3

0.4 File Index

0.4.1 File List

Here is a list of all documented files with brief descriptions:

globals.h	??
QuestionBank.h	??
server.h	3
ssl.h	5

0.5 Class Documentation

0.5.1 Data Struct Reference

all transmitted info == 1 data

```
#include <server.h>
```

Public Attributes

- long [size](#)
the number of pieces of content
- char [type](#) [8]
The type of transmission requested.
- [Byte](#) * [content](#)
Actual content.

0.5.1.1 Detailed Description

all transmitted info == 1 data

The documentation for this struct was generated from the following file:

- [server.h](#)

0.5.2 Question Class Reference

Public Member Functions

- **Question** (char, std::string, std::vector< std::string >)
- char **getType** ()
- std::string **getQString** ()
- std::vector< std::string > **getOptions** ()

The documentation for this class was generated from the following files:

- QuestionBank.h
- QuestionBank.cpp

0.5.3 QuestionBank Class Reference

Public Member Functions

- **QuestionBank** (std::string)
- std::string **getFileName** ()
- [Question](#) **getQuestion** (int)
- int **getSize** ()
- int **setFile** (std::string)

The documentation for this class was generated from the following files:

- QuestionBank.h
- QuestionBank.cpp

0.5.4 Server Class Reference

[Server](#) object.

```
#include <server.h>
```

Public Member Functions

- **Server** (int)
- void [initOpenSSL](#) ()
Initializes [Server](#) with openssl context :0.
- int [run](#) ()
Runs the [Server](#) ♡.
- int [getPort](#) ()
Gets port that the server is running on.
- void [setCtx](#) (SSL_CTX *)
Sets the SSL_CCONTEXT.
- SSL_CTX * [getCtx](#) ()
Gets the SSL_CTX.
- void [setMainLoop](#) (std::function< void(SSL_CTX *ctx, int server_fd, int client_fd)>)
Sets the main loop of the server.

0.5.4.1 Detailed Description

[Server](#) object.

This object looks after running the [Server](#), it has been made modular so it's easy to implement once the core is designed

The documentation for this class was generated from the following files:

- [server.h](#)
- serverImp.cpp

0.6 File Documentation

0.6.1 server.h File Reference

```
#include "globals.h"
#include "ssl.h"
#include <iostream>
#include <string.h>
#include <cmath>
#include <regex>
#include <signal.h>
#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>
#include <sys/types.h>
#include <sys/socket.h>
#include <netinet/in.h>
#include <arpa/inet.h>
#include "QuestionBank.h"
```

Classes

- struct [Data](#)
all transmitted info == 1 data
- class [Server](#)
[Server](#) object.

Macros

- #define [PORT](#) 5000
The default port the [Server](#) runs on if no port specified.
- #define [BUFFER_STD](#) 4
The size of 1 piece of content.

Typedefs

- typedef char [Byte](#)
Defines a Byte through a char.
- typedef struct [Data](#) [Data](#)
all transmitted info == 1 data

Functions

- void [defaultDataLoop](#) (SSL_CTX *ctx, int server_fd, int client_fd)
This loop runs when no loop is specified.
- void [defaultSSLDataLoop](#) (SSL_CTX *ctx, int server_fd, int client_fd)
This loop runs when SSL is enabled.
- void [error](#) (const char *msg)
Error Handling.
- void [action](#) (int sock)
- void [actionSSL](#) (SSL *ssl)

0.6.1.1 Macro Definition Documentation

0.6.1.1.1 BUFFER_STD

```
#define BUFFER_STD 4
```

The size of 1 piece of content.

The content needs to be split into pieces of size BUFFER_STD for the server to work properly

0.6.1.2 Typedef Documentation

0.6.1.2.1 Byte

```
typedef char Byte
```

Defines a Byte through a char.

1 byte == 1 char

0.6.2 ssl.h File Reference

```
#include <openssl/ssl.h>  
#include <openssl/err.h>
```

Functions

- void `init_openssl` ()
Initializes openSSL.
- void `cleanup_openssl` ()
Cleans up openSSL.
- `SSL_CTX *` `create_context` ()
Creates context.
- void `configure_context` (`SSL_CTX *`ctx)
Configures context.

Index

BUFFER_STD
server.h, [4](#)

Byte
server.h, [4](#)

Data, [2](#)

Question, [2](#)

QuestionBank, [2](#)

Server, [3](#)

server.h, [3](#)
BUFFER_STD, [4](#)
Byte, [4](#)

ssl.h, [5](#)