

# Network Programming Lab Report

---

Year/Semester: III / VI

## Index

S. No.	Title	Page No.	Signature
<b>Chapter 2: InetAddress</b>			
1	Check IPv4 and IPv6 Address		
2	Find the address of the local machine		
3	Find IP address and Host name of the local machine		
4	Demonstrate SpamCheck		
5	Compare if domains “www.ibiblio.org” and “helios.ibiblio.org” are the same		
<b>Chapter 3: URLs and URIs</b>			
6	Split parts of a URL (Splitting URL into pieces)		
7	Check supported protocols of the virtual machine		
8	Download a web page of a given address		
9	Resolve relative URIs		
10	Download an object		
11	Demonstrate x-www-form-urlencoded strings		
12	Communicate with Server-Side Programs Through GET		
<b>Chapter 4: HTTP</b>			
13	Block cookies from “.gov” domains using CookiePolicy		
14	Implement CookieStore methods (add, read, delete)		
<b>Chapter 5: URL Connections</b>			
15	Download a web page using URLConnection		
16	Read values of HTTP header fields		
17	Print the entire HTTP header		

18	HTTP Request Method		
19	URLConnection to “nepathyacollege.edu.np”		
20	Get last modified time of a URL		
<b>Chapter 6: Sockets for Clients</b>			
21	Socket Program for Client		
<b>Chapter 7: Sockets for Server</b>			
22	Socket Program for Server		
<b>Chapter 8: Secure Sockets</b>			
23	Create Secure Sockets with tufohss.edu.np		
24	Create Secure ServerSockets and ClientSockets		
<b>Chapter 9: Non-Blocking I/O</b>			
25	List supported socket options for various network channels		
26	Buffer operations (Fill, Drain, Duplicate, Slice, Compact)		
27	Data Conversion		
<b>Chapter 10: UDP</b>			
28	UDP Client		
29	UDP Server		
<b>Chapter 11: IP Multicast</b>			
30	Verify reception of multicast data at a host		
<b>Chapter 12: RMI</b>			
31	Add two numbers using RMI		

## LAB-1

**AIM: Write a program to check IPv4 and IPv6 Address.**

**Program:**

```
import java.net.*;

public class IpTypeCheck{

    public static void main(String[] args) {

        String host = "bhuvanbhusal.com.np";

        try {

            InetAddress address = InetAddress.getByName(host);

            byte[] ipBytes = address.getAddress();

            if (ipBytes.length == 4) {

                System.out.println(host + " is IPv4.");

            } else if (ipBytes.length == 16) {

                System.out.println(host + " is IPv6.");

            } else {

                System.out.println("Unknown format.");

            }

        } catch (UnknownHostException e) {

            System.out.println("Invalid host: " + host);

        }

    }

}
```

**Output:**

```
/Users/alexbhusal/Library/Java/JavaVirtualMachine-9
bhuvanbhusal.com.np is IPv4.

Process finished with exit code 0
```

## LAB-2

**AIM: Write a program that finds the address of the local machine**

**Program:**

```
import java.net.*;

public class LocalMachineAddress {

    public static void main(String[] args) {

        try {

            InetAddress localhost = InetAddress.getLocalHost();

            System.out.println("Local machine address: " + localhost.getHostAddress());

        } catch (UnknownHostException e) {

            System.err.println("Could not determine local host address: " + e.getMessage());

        }

    }

}
```

**Output:**

```
/Users/alexbhusal/Library/Java/JavaVir
Local machine address: 127.0.0.1

Process finished with exit code 0
```

## LAB-3

**AIM:** Write a program to find the IP address and Host name of the local machine

**Program:**

```
import java.net.*;

public class LocalHostInfo {
    public static void main(String[] args) {
        try {
            InetAddress localhost = InetAddress.getLocalHost();
            System.out.println("Host Name: " + localhost.getHostName());
            System.out.println("IP Address: " + localhost.getHostAddress());
        } catch (UnknownHostException e) {
            System.err.println("Could not determine local host information: " + e.getMessage());
        }
    }
}
```

**Output:**

```
/Users/alexbhusal/Library/Java/JavaVir
Host Name: Alexs-MacBook-Air.local
IP Address: 127.0.0.1

Process finished with exit code 0
```

## LAB-4

**AIM: Write a program that demonstrate the SpamCheck.**

**Program:**

```
import java.net.*;

public class SpamCheck {

    public static void main(String[] args) {

        try {

            InetAddress address = InetAddress.getByName("www.bhuvanbhusal.com.np");

            if (!address.isAnyLocalAddress()) {

                System.out.println("May be Spam Address");

            } else {

                System.out.println("Safe Address");

            }

        } catch (Exception e) {

            System.out.println("Error :" + e.getMessage());

        }

    }

}
```

**Output:**

**/Users/alexbhusal/Library/Java**  
**May be Spam Address**

## LAB-5

**AIM:** Write a program that compare the domain name are “[www.ibiblio.org](http://www.ibiblio.org)” and “helios.ibiblio.org” the same?

### Program:

```
import java.net.*;

public class DomainCompare {

    public static void main(String[] args) {

        try {

            InetAddress address1 = InetAddress.getByName("www.ibiblio.org");

            InetAddress address2 = InetAddress.getByName("helios.ibiblio.org");

            if (address1.equals(address2)) {

                System.out.println("Both domains point to the same address.");

            } else {

                System.out.println("The domains are different.");

            }

        } catch (Exception e) {

            System.out.println("Error: " + e.getMessage());

        }

    }

}
```

### Output:

```
/Users/alexghusa/Library/Java/JavaVirtualMachines/
The domains are different.

Process finished with exit code 0
```

## LAB-6

**AIM: Write a program that splits the parts of a URL [Splitting URL into pieces information]**

**Program:**

```
import java.net.*;

public class URLSplitter {

    public static void main(String[] args) {

        try {

            URL url = new URL("https://www.example.com:8080/path/to/resource?
            query=123&lang=en");

            System.out.println("Protocol: " + url.getProtocol());

            System.out.println("Host: " + url.getHost());

            System.out.println("Port: " + url.getPort());

            System.out.println("Path: " + url.getPath());

            System.out.println("Query: " + url.getQuery());

            System.out.println("File: " + url.getFile());

        } catch (Exception e) {

            System.out.println("Error: " + e.getMessage());

        }

    }

}
```

**Output:**

```
/Users/alexbhusal/Library/Java/JavaVirtualMachin
Protocol: https
Host: www.example.com
Port: 8080
Path: /path/to/resource
Query: query=123&lang=en
File: /path/to/resource? query=123&lang=en
```



## LAB-7

**AIM:** Write a program that checks the which protocols does a virtual machine support or not?

### Program:

```
import java.net.*;

public class ProtocolChecker {

    public static void main(String[] args) {

        String[] protocols = {"http", "https", "ftp", "mailto", "file", "jdbc", "telnet"};

        for (String protocol : protocols) {

            try {

                URL url = new URL(protocol, "example.com", "");

                System.out.println(protocol + " is supported");

            } catch (Exception e) {

                System.out.println(protocol + " is NOT supported: " + e.getMessage());

            }

        }

    }

}
```

### Output:

```
/Users/alexhusal/Library/Java/JavaVirtualMachines/
http is supported
https is supported
ftp is supported
mailto is supported
file is supported
jdbc is NOT supported: unknown protocol: jdbc
telnet is NOT supported: unknown protocol: telnet
```

## LAB-8

**AIM:** Write a program to download a web page of a given web address.

**Program:**

```
import java.io.*;

public class WebPageDownloader {

    public static void main(String[] args) {

        String urlString = "https://www.example.com";

        String outputFile = "downloaded_page.html";

        try (InputStream inputStream = new URL(urlString).openStream());

            FileOutputStream fileOutputStream = new FileOutputStream(outputFile)) {

                byte[] buffer = new byte[1024];

                int bytesRead;

                while ((bytesRead = inputStream.read(buffer)) != -1) {

                    fileOutputStream.write(buffer, 0, bytesRead);

                }

                System.out.println("Web page downloaded successfully to " + outputFile);

            } catch (IOException e) {

                System.err.println("Error downloading the web page: " + e.getMessage());

            }

        }

    }

}
```

**Output:**

```
/Users/alexbhusal/Library/Java/JavaVirtualMachines/openjdk-
Web page downloaded successfully to downloaded_page.html
```

## LAB-9

**AIM: Write a program for resolving relatives URI**

**Program:**

```
import java.net.*

public class ResolveURIExample {

    public static void main(String[] args) {

        try {

            URI baseUri = new URI("http://example.com/path/to/resource/");

            URI relativeUri = new URI("subdir/resource2");

            URI resolvedUri = baseUri.resolve(relativeUri);

            System.out.println("Resolved URI: " + resolvedUri);

        } catch (URISyntaxException e) {

            System.err.println("Invalid URI syntax: " + e.getMessage());

        }

    }

}
```

**Output:**

```
/Users/alexbhusal/Library/Java/JavaVirtualMachines/openjdk-24/Contents
Resolved URI: http://example.com/path/to/resource/subdir/resource2

Process finished with exit code 0
```

## LAB-10

**AIM: Write a program to download an object.**

**Program:**

```
import java.*;

public class DownloadObjectExample {

    public static void main(String[] args) {

        try {

            // Open the URL for reading

            URL u = new URL("http://www.google.com");

            Object o = u.getContent();

            System.out.println("I got a " + o.getClass().getName());

        } catch (MalformedURLException ex) {

            System.err.println("URL is not parseable");

        } catch (IOException ex) {

            System.err.println("Error retrieving content from the URL");

        }

    }

}
```

**Output:**

```
/Users/alexhbusal/Library/Java/JavaVirtualMachines/openjdk-24/Contents/
I got a sun.net.www.protocol.http.HttpURLConnection$HttpInputStream
```

## LAB-11

**AIM:** Write a program to demonstrate the x-www-form-URL encoded strings.

### Program:

```
import java.net.*;

public class FormURLEncoder {

    public static void main(String[] args) {

        String original = "Hello World! @Java Programming?name=value&test=123";

        try {

            String encoded = URLEncoder.encode(original, "UTF-8");

            String decoded = URLDecoder.decode(encoded, "UTF-8");

            System.out.println("Original: " + original);

            System.out.println("Encoded: " + encoded);

            System.out.println("Decoded: " + decoded);

        } catch (UnsupportedEncodingException e) {

            System.err.println("UTF-8 encoding not supported");

        }

    }

}
```

### Output:

```
/Users/alexbhusal/Library/Java/JavaVirtualMachines/openjdk-24/Contents/Home
Original: Hello World! @Java Programming?name=value&test=123
Encoded: Hello+World%21+%40Java+Programming%3Fname%3Dvalue%26test%3D123
Decoded: Hello World! @Java Programming?name=value&test=123
```

## LAB-12

**AIM: Write a program that communicating with Server-Side Programs Through GET.**

### Program:

```
import java.io.*;
import java.net.*;

public class GetRequestExample {

    public static void main(String[] args) throws Exception {

        BufferedReader in = new BufferedReader(new InputStreamReader(
            new URL("http://httpbin.org/get?param1=value1&param2=value2").openStream()));

        in.lines().forEach(System.out::println);

        in.close();

    }

}
```

### Output:

```
/Users/alexbhusal/Library/Java/JavaVirtualMachines/openjdk-24/Contents/Home/
Sending GET request to: http://httpbin.org/get?param1=value1&param2=value2
Response:
{
  "args": {
    "param1": "value1",
    "param2": "value2"
  },
  "headers": {
    "Accept": "*/*",
    "Host": "httpbin.org",
    "User-Agent": "Java/24",
    "X-Amzn-Trace-Id": "Root=1-68149c73-75fc60922d9418c45a5fd5a8"
  },
  "origin": "103.123.60.240",
  "url": "http://httpbin.org/get?param1=value1&param2=value2"
}

Process finished with exit code 0
```

## LAB-13

**AIM:** Write a program that shows a simple CookiePolicy that blocks cookies from .gov domains, but allows others.

### Program:

```
import java.net.*;

public class NoGovernmentCookies implements CookiePolicy {

    @Override

    public boolean shouldAccept(URI uri, HttpCookie cookie) {

        return !uri.getAuthority().endsWith(".gov") && !cookie.getDomain().endsWith(".gov");

    }

    public static void main(String[] args) {

        NoGovernmentCookies policy = new NoGovernmentCookies();

        try {

            System.out.println(policy.shouldAccept(new URI("http://example.gov"),

                new HttpCookie("sessionid", "12345").setDomain("example.gov")));

            System.out.println(policy.shouldAccept(new URI("http://example.com"),

                new HttpCookie("sessionid", "67890").setDomain("example.com")));

        } catch (Exception e) {

            e.printStackTrace();

        }

    }

}
```

### Output:

```
/Users/alexbhusal/Library/Java/
false
true
```

## LAB-14

**AIM: Program to implement the CookieStore Methods (add, read, delete) cookies.**

### **Program:**

```
import java.*;

public class CookieStoreExample {

    public static void main(String[] args) throws Exception {

        // Create a CookieManager with a CookieStore

        CookieManager manager = new CookieManager();

        CookieHandler.setDefault(manager);

        CookieStore cookieStore = manager.getCookieStore();


        // Add cookies

        URI uri1 = new URI("http://example.com");

        HttpCookie cookie1 = new HttpCookie("username", "john_doe");

        cookieStore.add(uri1, cookie1);

        URI uri2 = new URI("http://test.org");

        HttpCookie cookie2 = new HttpCookie("session", "abc123");

        cookieStore.add(uri2, cookie2);


        // Read cookies

        System.out.println("All cookies in store:");

        List<HttpCookie> cookies = cookieStore.getCookies();

        for (HttpCookie cookie : cookies) {

            System.out.println(cookie);

        }

        // Get cookies for specific URI

        System.out.println("\nCookies for example.com:");

        List<HttpCookie> exampleCookies = cookieStore.get(uri1);
```



```

    for (HttpCookie cookie : exampleCookies) {
        System.out.println(cookie);
    }

    // Delete a cookie

    System.out.println("\nDeleting session cookie...");

    cookieStore.remove(uri2, cookie2);

    System.out.println("\nRemaining cookies:");

    cookies = cookieStore.getCookies();

    for (HttpCookie cookie : cookies) {
        System.out.println(cookie);
    }

    // Delete all cookies

    System.out.println("\nClearing all cookies...");

    cookieStore.removeAll();

    System.out.println("Cookies after clearing: " + cookieStore.getCookies().size());
}
}

```

## Output:

```

/Users/alex_bhusal/Library/Java/JavaVirtualMachines/11.0.12-jdk-8u282-b01-1/Contents/Home/bin/java
All cookies in store:
username="alex_bhusal"
session="alex9876"

Cookies for example.com:
username="alex_bhusal"

Deleting session cookie...

Remaining cookies:
username="alex_bhusal"

Clearing all cookies...
Cookies after clearing: 0

Process finished with exit code 0

```

## LAB-15

**AIM:** Write a program to download a web page using URLConnection.

### Program:

```
import java.io.*;
import java.net.*;

public class WebPageDownloader {
    public static void main(String[] args) throws IOException {
        BufferedReader in = new BufferedReader(new InputStreamReader(
            new URL("https://www.example.com").openStream()));
        in.lines().forEach(System.out::println);
    }
}
```

### Output:

```
/Users/alexbhusal/Library/Java/JavaVirtualMachines/openjdk-24/Conte
<!doctype html>
<html>
<head>
    <title>Example Domain</title>
|
    <meta charset="utf-8" />
    <meta http-equiv="Content-type" content="text/html; charset=utf
    <meta name="viewport" content="width=device-width, initial-scal
    <style type="text/css">
    body {
        background-color: #f0f0f2;
        margin: 0;
        padding: 0;
        font-family: -apple-system, system-ui, BlinkMacSystemFont,

    }
    div {
        width: 600px;
```

## LAB-16

**AIM:** Write a program to read value of HTTP Header fields.

**Program:**

```
import java.io.*;

public class HeaderViewer {

    public static void main(String[] args) {

        try {

            URLConnection uc = new URL("https://tufohss.edu.np").openConnection();

            System.out.println("Content-type: " + uc.getContentType());

            System.out.println("Content-encoding: " + uc.getContentEncoding());

            System.out.println("Date: " + new Date(uc.getDate()));

            System.out.println("Last modified: " + new Date(uc.getLastModified()));

            System.out.println("Expiration date: " + new Date(uc.getExpiration()));

            System.out.println("Content-length: " + uc.getContentLength());

        } catch (IOException ex) {

            System.err.println(ex);

        }

    }

}
```

**Output:**

```
/Users/alexhhusal/Library/Java/JavaVirtualMachines/o
Content-type: text/html; charset=iso-8859-1
Content-encoding: null
Date: Fri May 02 19:06:09 GMT+05:45 2025
Last modified: Thu Jan 01 05:30:00 GMT+05:45 1970
Expiration date: Thu Jan 01 05:30:00 GMT+05:45 1970
Content-length: 231
```

## LAB-17

**AIM: Write a program to print the entire HTTP header**

**Program:**

```
import java.io.*;
import java.net.*;

public class HttpHeadersPrinter {

    public static void main(String[] args) throws IOException {

        HttpURLConnection connection = (HttpURLConnection)
            new URL("https://www.example.com").openConnection();

        connection.setRequestMethod("GET");

        connection.connect();

        connection.getHeaderFields().forEach((k, v) ->
            System.out.println(k + ": " + String.join(", ", v)));

        connection.disconnect();

    }

}
```

**Output:**

```
/Users/alexbhusal/Library/Java/JavaVirtualMachines/openjdk-24/Contents/Home/bin/java
null: HTTP/1.1 200 OK
Cache-Control: max-age=805
Alt-Svc: h3=":443"; ma=93600,h3-29=":443"; ma=93600,quic=":443"; ma=93600; v="43"
ETag: "84238dfc8092e5d9c0dac8ef93371a07:1736799080.121134"
Connection: keep-alive
Last-Modified: Mon, 13 Jan 2025 20:11:20 GMT
Content-Length: 1256
Date: Fri, 02 May 2025 10:37:10 GMT
Content-Type: text/html
```

## LAB-18

### AIM: Write a program for HTTP Request Method

#### Program:

```
import java.net.*;

public class HttpRequestExample {

    public static void main(String[] args) throws Exception {

        URL url = new URL(" https://example.com");

        HttpURLConnection connection = (HttpURLConnection) url.openConnection();

        connection.setRequestMethod("GET");

        BufferedReader in = new BufferedReader(new
        InputStreamReader(connection.getInputStream()));

        String inputLine;

        StringBuffer response = new StringBuffer();

        while ((inputLine = in.readLine()) != null) {

            response.append(inputLine);

        }

        in.close();

        System.out.println(response.toString());

    }

}
```

#### Output:

```
/Users/alexbhusal/Library/Java/JavaVirtualMachines/openjdk-24/Conte
<!doctype html>
<html>
<head>
    <title>Example Domain</title>
|
    <meta charset="utf-8" />
    <meta http-equiv="Content-type" content="text/html; charset=utf
    <meta name="viewport" content="width=device-width, initial-scal
    <style type="text/css">
    body {
        background-color: #f0f0f2;
        margin: 0;
        padding: 0;
        font-family: -apple-system, system-ui, BlinkMacSystemFont,
    }
    div {
        width: 600px;
```

## LAB-19

**AIM:** Write a program to print the URL of a URL Connection to “npathycollege.edu.np”.

### Program:

```
import java.net.*;

public class URLPrinter {

    public static void main(String[] args) {

        String urlString = "http://npathycollege.edu.np";

        try {

            URL url = new URL(urlString);

            URLConnection connection = url.openConnection();

            System.out.println("URL of the connection: " + connection.getURL());

        } catch (IOException e) {

            System.err.println("Error opening connection: " + e.getMessage());

        }

    }

}
```

### Output:

```
/Users/alexbhusal/Library/Java/JavaVirtualMachines/openjdk-24,
URL of the connection: http://npathycollege.edu.np
```

## LAB-20

**AIM:** Write a program to get the time when a URL was last changed.

**Program:**

```
import java.*;

public class URLLastModified {

    public static void main(String[] args) {

        String urlString = "http://example.com";

        try {

            URL url = new URL(urlString);

            URLConnection connection = url.openConnection();

            long lastModified = connection.getLastModified();

            if (lastModified == 0) {

                System.out.println("Last modified information not available");

            } else {

                System.out.println("Last modified: " + new Date(lastModified));

            }

        } catch (IOException e) {

            System.err.println("Error getting last modified time: " + e.getMessage());

        }

    }

}
```

**Output:**

```
/Users/alexbhusal/Library/Java/JavaVirtualMachines/
Last modified: Tue Jan 14 01:56:20 GMT+05:45 2025
```

## LAB-21

**AIM:** Write a program socket to client.

**Program:**

```
import java.*;

public class Client {

    public static void main(String[] args) throws IOException {

        Socket socket = new Socket("localhost", 1234);

        PrintWriter out = new PrintWriter(socket.getOutputStream(), true);

        BufferedReader in = new BufferedReader(new
InputStreamReader(socket.getInputStream()));

        out.println("Hello Server");

        String response = in.readLine();

        System.out.println("Server says: " + response);

        socket.close();

    }

}
```

**Output:**

```
/Users/alexbhusal/Library/Java/Java
Server says: Hello Client
```



## LAB-22

**AIM: Write a program socket for a server.**

**Program:**

```
import java.net.*;

public class Server {

    public static void main(String[] args) throws IOException {

        ServerSocket serverSocket = new ServerSocket(1234);

        System.out.println("Server is listening on port 1234...");

        Socket socket = serverSocket.accept();

        BufferedReader in = new BufferedReader(new
            InputStreamReader(socket.getInputStream()));

        PrintWriter out = new PrintWriter(socket.getOutputStream(), true);

        String clientMessage = in.readLine();

        System.out.println("Client says: " + clientMessage);

        out.println("Hello Client");

        socket.close();

        serverSocket.close();

    }

}
```

**Output:**

```
/Users/alexbhusal/Library/Java/JavaVirtualM
Server is listening on port 1234...
Client says: Hello Server
```

## LAB-23

**AIM: Write a program for Creating Secure Sockets with tufohss.edu.np.**

### Program:

```
import java.net.*;

public class SecureSocketClient {

    public static void main(String[] args) {

        try (SSLSocket socket = (SSLSocket) SSLSocketFactory.getDefault().
            createSocket("tufohss.edu.np", 443)) {

            socket.setEnabledCipherSuites(socket.getSupportedCipherSuites());

            PrintWriter out = new PrintWriter(socket.getOutputStream(), true);

            out.println("GET / HTTP/1.1\nHost: tufohss.edu.np\n");

            new BufferedReader(new InputStreamReader(socket.getInputStream()))

                .lines().forEach(System.out::println);

        } catch (IOException e) {

            System.err.println("Error: " + e.getMessage());

        }

    }

}
```

### Output:

```
/Users/alexhhusal/Library/Java/JavaVirtualMachines/openjdk-24/Contents/Home/bin/java -
HTTP/1.1 400 Bad Request
Date: Fri, 02 May 2025 13:32:01 GMT
Server: Apache
Content-Length: 347
Connection: close
Content-Type: text/html; charset=iso-8859-1

<!DOCTYPE HTML PUBLIC "-//IETF//DTD HTML 2.0//EN">
<html><head>
<title>400 Bad Request</title>
</head><body>
<h1>Bad Request</h1>
<p>Your browser sent a request that this server could not understand.<br />
</p>
<p>Additionally, a 400 Bad Request
error was encountered while trying to use an ErrorDocument to handle the request.</p>
</body></html>
```

## LAB-24

**AIM: Write a program for Creating Secure ServerSockets and Client Sockets**

**Program:**

```
import java.net.*;

public class SecureServer {

    public static void main(String[] args) throws Exception {

        System.setProperty("javax.net.ssl.keyStore", "serverKeyStore.jks");
        System.setProperty("javax.net.ssl.keyStorePassword", "password");
        SSLServerSocket serverSocket = (SSLServerSocket)
            SSLServerSocketFactory.getDefault().createServerSocket(12345);
        while (true) {
            SSLSocket socket = (SSLSocket) serverSocket.accept();
            new PrintWriter(socket.getOutputStream(), true).println("Hello from server");
            socket.close();
        }
    }
}

import javax.*;

public class SecureClient {

    public static void main(String[] args) throws Exception {

        System.setProperty("javax.net.ssl.trustStore", "clientTrustStore.jks");
        System.setProperty("javax.net.ssl.trustStorePassword", "password");
        SSLSocket socket = (SSLSocket)
            SSLSocketFactory.getDefault().createSocket("localhost", 12345);

        System.out.println(new BufferedReader(new
            InputStreamReader(socket.getInputStream())).readLine());

        socket.close();
    }
}
```

**Output:**

```
/Users/alexbhusal/Library/Java/JavaVirtualMachines/
Secure server started on port 12345
Client connected: /127.0.0.1
Received: Hello, Secure Server!
```

```
/Users/alexbhusal/Library/Java/JavaVirtualMachines/
Server response: Echo: Hello, Secure Server!
```

## LAB-25

**AIM: Write program to list all supported socket options for the different types of network channels**

### Program:

```
import java.*;

public class SocketOptionsLister {

    public static void main(String[] args) throws IOException {

        for (Channel channel : new Channel[] {

            ServerSocketChannel.open(), SocketChannel.open(), DatagramChannel.open() }) {

            System.out.println(channel.getClass().getSimpleName() + " supported options:");

            channel.supportedOptions().forEach(option -> System.out.println(option.name()));

            System.out.println();

        }

    }

}
```

### Output:

```
ServerSocketChannelImpl supported options:
TCP_KEEPINTERVAL
SO_RCVBUF
SO_REUSEPORT
TCP_KEEPCOUNT
SO_REUSEADDR
TCP_KEEPIDLE

SocketChannelImpl supported options:
TCP_KEEPINTERVAL
SO_SNDBUF
SO_RCVBUF
SO_REUSEPORT
TCP_KEEPCOUNT
SO_REUSEADDR
SO_LINGER
TCP_NODELAY
SO_KEEPAIVE
IP_TOS
TCP_KEEPIDLE
SO_OOBINLINE

DatagramChannelImpl supported options:
SO_SNDBUF
SO_RCVBUF
SO_REUSEPORT
SO_REUSEADDR
IP_MULTICAST_IF
IP_DONTFRAGMENT
IP_MULTICAST_LOOP
```

## LAB-26

**AIM: Write program to implement the concept on Filling and Draining buffer, duplicating buffer, Slicing buffer, Compact buffer.**

### Program:

```
import java.nio.*;

public class BufferExamples {

    public static void main(String[] args) {

        ByteBuffer buffer = ByteBuffer.allocate(10);

        // Filling & Draining

        buffer.put((byte) 1).put((byte) 2).flip();

        System.out.println(buffer.get() + ", " + buffer.get());

        // Duplicating

        System.out.println(buffer.duplicate());

        // Slicing

        buffer.clear().put((byte) 3).put((byte) 4).flip();

        System.out.println(buffer.slice());

        // Compacting

        buffer.clear().put((byte) 5).put((byte) 6).flip();

        buffer.get().compact();

        System.out.println(buffer);

    }

}
```

### Output:

```
/Users/alexbhusal/Library/Java/JavaVirtualMachines
Filling & Draining:
1, 2

Duplicating:
Duplicate buffer position: 2, limit: 2

Slicing:
Slice position: 0, limit: 2
Slice content: 3, 4

Compacting:
Buffer after compact: position = 1, limit = 10
6
```

## LAB-27

**AIM: Write a program to implement the concept on Data Conversion**

### Program:

```
import java.*;

public class DataConversion {

    public static void main(String[] a) {

        ByteBuffer b = ByteBuffer.allocate(16);

        b.putInt(42).putDouble(3.14).putChar('A').flip();

        System.out.println(b.getInt() + " " + b.getDouble() + " " + b.getChar());

        ByteBuffer sb = StandardCharsets.UTF_8.encode("Hello NIO");

        System.out.println( StandardCharsets.UTF_8.decode((ByteBuffer) sb.rewind()));

        ByteBuffer src = ByteBuffer.allocate(16);

        for (int i = 0; i < 16; i++) src.put((byte) i);

        System.out.print("\n");

        src.flip();

        IntBuffer ib = src.asIntBuffer();

        while (ib.hasRemaining()) System.out.print(ib.get() + " ");

    }

}
```

### Output:

```
/Users/alexbhusal/Library/Java/JavaVirtualMachines
Filling & Draining:
1, 2

Duplicating:
Duplicate buffer position: 2, limit: 2

Slicing:
Slice position: 0, limit: 2
Slice content: 3, 4

Compacting:
Buffer after compact: position = 1, limit = 10
6
```

## LAB-28

**AIM: Write a program for UDP Client.**

**Program:**

```
import java.net.*;

public class UDPClient {

    public static void main(String[] args) {

        try (DatagramSocket socket = new DatagramSocket()) {

            byte[] buf = "Hello UDP Server".getBytes();

            InetAddress address = InetAddress.getByName("localhost");

            socket.send(new DatagramPacket(buf, buf.length, address, 9876));

            byte[] respBuf = new byte[1024];

            DatagramPacket response = new DatagramPacket(respBuf, respBuf.length);

            socket.receive(response);

            System.out.println("Server response: " + new String(response.getData(), 0,
response.getLength()));

        } catch (Exception e) {

            System.err.println("Error: " + e.getMessage());

        }

    }

}
```

**Output:**

`/Users/alexbhusal/Library/Java/JavaVir`  
`Server response: Hello from Server`



## LAB-29

**AIM: Write a program for UDP Server.**

**Program:**

```
import java.net.*;

public class UDPServer {

    public static void main(String[] args) {

        try (DatagramSocket socket = new DatagramSocket(9876)) {

            byte[] buffer = new byte[1024];

            System.out.println("Server running...");

            DatagramPacket request = new DatagramPacket(buffer, buffer.length);

            socket.receive(request);

            String msg = new String(request.getData(), 0, request.getLength());

            System.out.println("Received: " + msg);

            byte[] reply = "Hello from Server".getBytes();

            socket.send(new DatagramPacket(reply, reply.length, request.getAddress(),
            request.getPort()));

        } catch (Exception e) {

            System.err.println("Error: " + e.getMessage());

        }

    }

}
```

**Output:**

```
/Users/alexbhusal/Library/Java/
Server running...
Received: Hello UDP Server
```

## LAB-30

**AIM: Program to verify that you are receiving multicast data at a particular host.**

**Program:**

```
import java.net.*;

public class MulticastReceiver {

    public static void main(String[] args) throws Exception {

        String groupAddress = "224.0.0.1"; // Multicast address

        int port = 5000; // Multicast port

        MulticastSocket socket = new MulticastSocket(port);

        InetAddress group = InetAddress.getByName(groupAddress);

        socket.joinGroup(group);

        byte[] buffer = new byte[1024];

        while (true) {

            DatagramPacket packet = new DatagramPacket(buffer, buffer.length);

            socket.receive(packet);

            System.out.println("Received: " + new String(packet.getData(), 0,
packet.getLength()));

        }

    }

}
```

**Output:**

**/Users/alexbhusal/Library/Java**  
**Received: Hello Multicast**

## LAB-31

**AIM: Program to add two numbers using RMI**

**Program:**

*// Remote Interface (Adder.java)*

```
import java.*;

public interface Adder extends Remote {

    int add(int num1, int num2) throws RemoteException;

}
```

*//Remote Implementation (AdderImpl.java)*

```
import java.*;

public class AdderImpl extends UnicastRemoteObject implements Adder {

    public AdderImpl() throws RemoteException {}

    public int add(int num1, int num2) throws RemoteException {

        return num1 + num2;

    }

}
```

*//Server (AdderServer.java)*

```
import java.*;

public class AdderServer {

    public static void main(String[] args) throws Exception {

        LocateRegistry.createRegistry(1099);

        Naming.rebind("AdderService", new AdderImpl());

        System.out.println("Server ready.");

    }

}
```

*//Client (AdderClient.java)*

```
import java.*;

public class AdderClient {

    public static void main(String[] args) throws Exception {

        Adder adder = (Adder) Naming.lookup("rmi://localhost/AdderService");

        Scanner sc = new Scanner(System.in);

        System.out.print("Enter two numbers: ");

        int num1 = sc.nextInt(), num2 = sc.nextInt();

        System.out.println("Sum: " + adder.add(num1, num2));

    }

}
```

**Output:**

```
/Users/alexbhusal/Library/Java/
Server ready.
```

```
/Users/alexbhusal/Library/Java/
Enter two numbers: 100
200
Sum: 300
```