

WhatsApp Bot - 2026-03-... PDF	WhatsApp Bot - 2026-03-... PDF
WhatsApp Bot - 2026-02-... PDF	WhatsApp Bot - 2026-02-... PDF
contactNaccount.txt Document	keyname.conf.txt Document
ONEBOTREBUILDWORKF... Document	READMEBUILD.txt Document

file PDF ini ialah kerja yang dah di jalankan, wajib ingat sesi ni, terutamanya WhatsApp Bot - 2026-03-04 S0 GD.pdf ialah sesi terakhir dan di akhir sesi ada tracker di sediakan untuk kau sambung, dan semua .txt file yang aku sertakan ni ialah features yang patut ada dalam onebot, jadi kau kena baca dulu, dan sebelum kau mula wajib minta codex scan repo dan kau kena faham repo file tu dulu baru boleh mula kerja, dan check juga prompt terakhir dalam sesi akhir WhatsApp Bot - 2026-03-04 S0 GD.PDF

Updated saved memory

Thought for 1m 56s >

Baik — aku dah semak, dan untuk sesi **WhatsApp Bot - 2026-03-04 S0 GD.pdf** memang jelas: **langkah pertama wajib ialah “REPO SCAN REPORT” (report sahaja, tak boleh ubah code/conf)** sebelum sambung apa-apa kerja. Lepas scan tu barulah ikut urutan **6G (Anti-miss)** kemudian **6H (Audit/Journal view)**.  WhatsApp Bot - 2026-03-04 S0 GD

Aku juga ambil maklum semua .txt yang kau bagi ialah spec/features ONEBOT (contoh workflow tracker + rule-lock + contact/account/context spec) dan memang kena jadi rujukan sebelum mula buat apa-apa perubahan.  ONEBOTREBUILDWORKFLOWTRACKER

 contactNaccount

Di bawah ni aku “extract” jadi **prompt Codex** yang kau boleh paste terus (ikut prompt terakhir/handover dalam PDF):

TASK: REPO SCAN REPORT (MANDATORY FIRST STEP) - ACTIVE MODULE INVENTORY + POINTER

SCOPE

- REPORT ONLY. NO CODE/CONF CHANGES.
- MUST scan full repo on disk (do not guess).
- Output must list ACTIVE modules only:
ACTIVE = Core/<Module>.conf enabled=1 AND valid Hub.conf exists AND Hub.conf re
- Fill the README sections from the repo scan result:
 - A) Active Module Inventory
 - B) Rebuild Status (DONE/PENDING) based on actual active runtime pointers.

MUST

1) For EVERY enabled Core/<Module>.conf, show:

- entryConf path
- hubConf path
- implFile
- implConfig
- primary service name

2) Confirm active pointer chains (exact paths) for these critical modules:

- Global, Command, AccessRoles, JsonStore, SendQueue, Outbox, OutboundGateway, Ra
- MessageJournal, Scheduler, WorkGroups, Fallback

3) For Fallback specifically:

- list the 4x4 handlers present (Forward/Reply x Router/Text/Media/AV)
- show exact file paths for each handler found (existing files only)

OUTPUT FORMAT

REPORT

- A) Active Module Inventory (one line per module)
- B) Rebuild Status (DONE/PENDING + 1-line reason)
- C) Critical pointer chains (exact paths)

⟨⟩ Plain text



Lepas kau dapat output scan report dari Codex, kau paste sini — baru aku boleh audit dan tulis **TASK seterusnya** ikut sequence (6G kemudian 6H) tanpa ulang-usik file yang sama.

(Nota: Untuk contact/account/context nanti memang ikut spec "ACC/PIC/CTX" + command-driven + filing professional, tapi itu **optional** selepas 6G/6H stabil.

contactNaccount ONEBOTREBUILDWORKFLOWTRACKER)

Sources

... Compare with Claude ▾

codex.txt
Document

Thought for 2m 54s >

Boleh copy? Ya — copy sebagai REPORT/tracker sahaja.  codex

Boleh copy untuk deploy/fix live server? Tak boleh (status masih **PENDING**, OutboundGateway implConfig missing, 6G blocked, dan Fallback forward Media/AV missing).  codex  codex  codex  codex

TASK: UNBLOCK 6G PRECONDITION (REPORT ONLY) - PROVE BIND/MOVE WIRING EXISTS/IS MI

SCOPE

- REPORT ONLY. NO CODE/CONF CHANGES. NO GUESSING.
- Goal: verify whether active Fallback already has 6E bind/move wiring, because c

MUST

1) Follow active pointers (ON DISK):

- OneData/bots/ONEBOT/config/modules/Core/Fallback.conf
- -> OneData/bots/ONEBOT/config/modules/Core/FallbackHub.conf
- -> implFile (active FallbackCV.js path)
- -> implConfig (active FallbackCV.conf path)

2) Prove bind/move routing in router:

- Open: OneBot/modules/Core/Fallback/FallbackReplyRouterCV.js
- Search for calls to deps.onBindTag / deps.onMoveTicket (or equivalent)
- Output: file path + line numbers + max 2-line excerpt per finding

3) Prove deps wiring in FallbackCV.js:

- Open active implFile found in step 1
- Search for onBindTag/onMoveTicket being passed into reply router deps
- Output: file path + line numbers + max 2-line excerpt per finding

4) Config key existence check (active FallbackCV.conf):

- Confirm these keys exist (exact names): cmdBindTag, cmdMoveTicket, bindMapStore
- If any missing: list missing keys only (no guesses)

OUTPUT

REPORT

- Active implFile path + implConfig path
- Router has bind/move dispatch? yes/no (with evidence)
- FallbackCV.js wires deps? yes/no (with evidence)
- Missing config keys (if any)

<> Plain text



TASK: FIX ACTIVE OUTBOUNDGATEWAY WIRING (DEPLOYABLE) - REMOVE MISSING IMPLCONFIG

SCOPE

- Fix ONLY OutboundGateway wiring proven by repo scan: Hub.conf points to missing
- ASCII-only. ZERO HARDCODE.
- Do NOT touch Start.cmd / Kernel.js / Connector.js / any *Hub.js logic.
- Max 4 files total.

MUST (NO GUESSING)

1) Follow active pointers:

- OneData/bots/ONEBOT/config/modules/Core/OutboundGateway.conf
- -> OneData/bots/ONEBOT/config/modules/Core/OutboundGatewayHub.conf
- Confirm implFile + implConfig currently used (path + show the exact line).

2) Search the repo for existing OutboundGateway impl conf candidates:

- Find any of: OutboundGatewayCV.conf, OutboundGatewayV1.conf, OutboundGateway*.c
- Report which exists.

3) Implement minimal safe fix:

- If OutboundGatewayCV.conf exists: update OutboundGatewayHub.conf to point implC
- If no CV conf exists: create OneData/bots/ONEBOT/config/modules/Core/Impl/Outbo
- Ensure OutboundGateway loads without referencing a missing conf file.

OUTPUT FORMAT (STRICT)

CHANGED FILES

Path: <file1>

```conf

</> Plain text



Path: <file2>

</> conf



(If you must touch OutboundGatewayCV.js, include it as a full file too, but keep total <= 4 files.)

STOP.



Sources



Compare with Claude ▾

kau langgar peraturan ni, 1 kali jalan 1 prompt saja, tulis semula prompt mana nak dulu, kau tak baca logic kerja sesi lepas ke????

Thought for 2m 38s >

Betul — aku silap tadi sebab bagi 2 **prompt** sekali. Ikut tracker sesi akhir memang **kena satu-satu**.  WhatsApp Bot - 2026-03-04 S0 GD

Berdasarkan **codex.txt (Create Time: 3:37AM)**, scan dah siap dan ada blocker jelas:  
**OutboundGateway chain invalid sebab Hub.conf point ke Impl conf yang missing.**

 codex  codex

Jadi **prompt seterusnya yang patut jalan dulu**: betulkan pointer+conf OutboundGateway supaya outbound pipeline stabil, baru masuk 6G/6H.

Ini **SATU prompt sahaja** untuk Codex:

TASK: FIX OUTBOUNDGATEWAY POINTER CHAIN (DEPLOYABLE, MAX 2 FILES)

ARAHAN KERAS: DI LARANG MENEKA

Create Time: <fill current time>

SCOPE

- Fix ONLY OutboundGateway broken pointer chain reported by scan (implConfig miss
- ASCII-only. ZERO HARDCODE.
- Do NOT touch Start.cmd / Connector.js / Kernel.js / any \*Hub.js code (foundatio
- Output FULL file bodies only. No diff/patch.

MUST (NO GUESSING)

1) Verify active pointer chain on disk:

- OneData/bots/ONEBOT/config/modules/Core/OutboundGateway.conf
- -> OneData/bots/ONEBOT/config/modules/Core/OutboundGatewayHub.conf
- Confirm implFile + implConfig currently referenced.
- If implConfig points to a missing file (scan says OutboundGatewayV1.conf missin

2) Implement minimal safe fix using MAX 2 files total:

A) Update:

- OneData/bots/ONEBOT/config/modules/Core/OutboundGatewayHub.conf
- Change ONLY implConfig pointer to:  
OneData/bots/ONEBOT/config/modules/Core/Impl/OutboundGatewayCV.conf

B) Ensure this file exists and is valid:

- OneData/bots/ONEBOT/config/modules/Core/Impl/OutboundGatewayCV.conf

- If missing, CREATE it.
- Populate keys by reading the current active OutboundGateway implFile (OutboundG
- Mandatory log toggles must exist in the CV conf:  
moduleLog, bugLog, detailLog, traceLog
- Use canonical keynames only (no aliases). Do not invent new concepts.

OUTPUT FORMAT (STRICT)

CHANGED FILES

Path: OneData/bots/ONEBOT/config/modules/Core/OutboundGatewayHub.conf

Plain text



Path: OneData/bots/ONEBOT/config/modules/Core/Impl/OutboundGatewayCV.conf

conf



STOP.



Sources

... Compare with Claude ▾

codex.txt  
Document

Thought for 50s >

**Tak boleh copy lagi.** Sebab Codex cuma bagi summary + "+1 -1" tanpa **FULL file content** untuk OutboundGatewayHub.conf , jadi kau tak boleh paste ke live server dengan selamat.

codex

WhatsApp Bot - 2026-03-02 S0 GD

TASK: RE-OUTPUT FULL FILE BODY (COPY/PASTE READY) - OutboundGatewayHub.conf ONLY  
ARAHAN KERAS: DI LARANG MENEKA  
Create Time: 3:54 (re-output)

SCOPE

- NO further changes. OUTPUT ONLY.
- Provide FULL RAW FILE BODY for the file you changed so it can be pasted into li

- ASCII-only. NO diff/patch markers. NO summaries.

FILE TO OUTPUT (EXACT, ONE FILE ONLY)

1) OneData/bots/ONEBOT/config/modules/Core/OutboundGatewayHub.conf

MUST

- Print the entire file content exactly as it is after your commit.
- Ensure implConfig points to: modules/Core/Impl/OutboundGatewayCV.conf (within t
- Output format:

CHANGED FILES

Path: OneData/bots/ONEBOT/config/modules/Core/OutboundGatewayHub.conf

~~~~~

</> Plain text



STOP.



Sources



Compare with Claude ▾

codex.txt

Document

Thought for 1m 33s >

Boleh copy (file ini sahaja): YA.  codex

TASK: CLEAN RE-OUTPUT (COPY/PASTE READY) - OutboundGatewayCV.conf ONLY

ARAHAN KERAS: DI LARANG MENEKA

Create Time: 4:16AM

SCOPE

- NO LOGIC CHANGES. OUTPUT ONLY.
- Provide FULL RAW FILE BODY so it can be pasted into live server.
- ASCII-only. No Summary/Testing/commit text. No diffs.

FILE TO OUTPUT (EXACT, ONE FILE ONLY)

1) OneData/bots/ONEBOT/config/modules/Core/Impl/OutboundGatewayCV.conf

MUST

```
- If file is missing on disk, output:
REPORT
MISSING FILE: <exact path>
STOP.
- If exists, output format:
CHANGED FILES
Path: OneData/hots/ONEROT/config/modules/Core/Tmn1/OutboundGatewayCV.conf
</> Plain text
```



STOP.



Sources



Compare with Claude ▾

sambil tunggu codex reply, di bawah ni ialah cara betul penulisan, tak perlu reply yang ni cuma untuk pengetahuan kau untuk next prompt yang kau perlu tulis di bawah ialah penulisan dan cara susunan jawapan selepas aku hantar codex.txt yang betul dan untuk kau reply dengan prompt baru  
Header di luar prompt jawapan sama ada boleh copy atau tak boleh copy - Boleh copy (file ini sahaja): YA.  
Header di luar prompt ikut dalam codex.txt yang aku hantar sebagai rujukan : Create Time: 4:16AM  
Header di luar prompt, summary ringkas sekiranya perlu bag penerangan, jika tidak jangan bagi summary panjang2, melainkan kau nak jawapan soalan aku, sebab kadang2 aku ada tanya soalan bila aku sertakan codex.txt, jika tiada tak perlu baris ni

Prompt baru mula di bawah  
TASK: CLEAN RE-OUTPUT (COPY/PASTE READY) -  
OutboundGatewayCV.conf ONLY  
ARAHAN KERAS: DI LARANG MENEKA

SCOPE  
- NO LOGIC CHANGES. OUTPUT ONLY.



- Provide FULL RAW FILE BODY so it can be pasted into live server.
- ASCII-only. No Summary/Testing/commit text. No diffs.

FILE TO OUTPUT (EXACT, ONE FILE ONLY)

1)

OneData/bots/ONEBOT/config/modules/Core/Impl/OutboundGatewayCV.conf

MUST

- If file is missing on disk, output:

REPORT

MISSING FILE: <exact path>

STOP.

- If exists, output format:

CHANGED FILES

Path:

OneData/bots/ONEBOT/config/modules/Core/Impl/OutboundGatewayCV.conf

conf

<FULL RAW FILE BODY ONLY>

STOP.

Thought for 8s

Baik, aku faham format tu dan aku akan ikut **susunan header + Create Time + ringkas (jika perlu)**, lepas tu baru **prompt TASK** ikut template yang kau bagi.

    ... Compare with Claude ▾

codex.txt  
Document

Thought for 3m 22s >

**Boleh copy (file ini sahaja): TIDAK.**

**Create Time: 4:30AM**

Sebab key canonical untuk OutboundGateway export list ialah `services` , bukan

`exportServices`  `keyname.conf` dan `rateLimitLogDebounceMs` bukan dalam senarai key canonical (risiko drift/unknown key).  `keyname.conf`

TASK: FIX CANONICAL KEY VIOLATIONS (DEPLOYABLE) - OutboundGatewayCV.conf + OutboundGatewayCV.js  
 ARAHAN KERAS: DI LARANG MENEKA

Create Time: 4:30AM

#### SCOPE

- Fix ONLY canonical key violations for OutboundGateway.
- ASCII-only. ZERO HARDCODE.
- Output FULL file bodies only. No diff/patch. No summary/testing text.

#### MUST (NO GUESSING)

- 1) Locate canonical key source on disk:
  - `keyname.conf.txt` (use actual repo path)
  - Confirm canonical for OutboundGateway:
    - export service list key MUST be "services"
    - base send key MUST be "baseSend"
    - rate limit service key MUST be "ratelimitService" (NOT `rateLimitService`)

#### 2) Fix config + code to match canonical keys:

- In `OneData/bots/ONEBOT/config/modules/Core/Impl/OutboundGatewayCV.conf`:
  - Replace "exportServices" with canonical "services"
  - Keep `baseSend` and `ratelimitService` as canonical keys
- In `OneBot/modules/Core/OutboundGateway/OutboundGatewayCV.js`:
  - Ensure it reads `cfg.services` (NOT `cfg.exportServices`)
  - Ensure it reads `cfg.baseSend` and `cfg.ratelimitService`

#### 3) Unknown key handling (NO GUESSING):

- Search `OutboundGatewayCV.js` for "rateLimitLogDebounceMs".
  - If NOT used anywhere: REMOVE the key from the conf.
  - If USED: and the key is NOT in `keyname.conf.txt`:  
 REPORT  
 MISSING CANONICAL KEY: `rateLimitLogDebounceMs`  
 Evidence: `<file:line showing usage> + <keyname.conf.txt proof missing>`  
 STOP. (do not output changed files)

#### OUTPUT (MAX 2 FILES)

##### CHANGED FILES

Path: `OneBot/modules/Core/OutboundGateway/OutboundGatewayCV.js`  
 ``js

⌄ Plain text



Path: `OneData/bots/ONEBOT/config/modules/Core/Impl/OutboundGatewayCV.conf`

STOP.



Sources



Compare with Claude ▾

codex.txt

Document

Thought for 1m 2s >

**Tak boleh copy: TIDAK.**

**Create Time: 4:41AM**

Sebab OutboundGatewayCV.js memang guna cfg.rateLimitLogDebounceMs tapi key itu **tak wujud** dalam keyname.conf.txt (canonical list), jadi sekarang langgar "canonical keynames only".  codex  keyname.conf

TASK: OUTPUT DEPLOYABLE keyname.conf.txt (APPEND-ONLY ADD rateLimitLogDebounceMs)  
ARAHAN KERAS: DI LARANG MENEKA  
Create Time: 4:41AM

#### SCOPE

- FIX ONLY: keyname.conf.txt
- Output MUST be copy/paste deploy: FULL RAW FILE BODY only (no audit/report/summ
- Append-only add ONE canonical key if missing: rateLimitLogDebounceMs
- ASCII-only. No rename/remove/reorder. No duplicate keys.

#### MUST

- Locate the EXACT path of keyname.conf.txt in repo (do not guess).
- Read existing contents from disk.
- Check if key already exists EXACTLY: rateLimitLogDebounceMs
- If missing, append it at the end as plain key (one per line).
- If already exists, output:

REPORT

NO CHANGE NEEDED

STOP.

OUTPUT FORMAT (STRICT)  
CHANGED FILES  
Path: <exact path to keyname.conf.txt>  
  
</> Plain text



STOP.



Sources

... Compare with Claude ▾

codex.txt  
Document

Thought for 1m 50s >

Tak boleh copy: TIDAK.

Create Time: 4:45AM

Sebab ini **bukan** keyname.conf.txt deployable (dia sendiri tulis "audit from pasted .conf only" ) dan dia cuma tampal rateLimitLogDebounceMs di hujung report (bukan full raw file body dari disk untuk paste live).

```
TASK: OUTPUT DEPLOYABLE keyname.conf.txt (APPEND-ONLY ADD rateLimitLogDebounceMs)
ARAHAN KERAS: DI LARANG MENEKA
Create Time: 4:45AM

SCOPE
- FIX ONLY: keyname.conf.txt
- Output MUST be copy/paste deploy: FULL RAW FILE BODY only (NO audit/report/summ
- Append-only add ONE canonical key if missing: rateLimitLogDebounceMs
- ASCII-only. No rename. No reorder. No duplicate keys.

MUST
- Locate the EXACT keyname.conf.txt used by this repo/workflow FROM DISK (do not
- If multiple candidates exist, output:
REPORT
MULTIPLE CANDIDATES:
- <path1>
```

```

- <path2>
STOP.
- Read the chosen file from disk.
- Check if "rateLimitLogDebounceMs" already exists anywhere in the file.
- If missing, append it at the very end as a plain key (one line).
- If already exists, output:
REPORT
NO CHANGE NEEDED
STOP.

```

OUTPUT FORMAT (STRICT)

CHANGED FILES

Path: <exact repo path to keyname.conf.txt>

</> Plain text



STOP.



Sources



Compare with Claude ▾

**codex.txt**

Document

keyname.conf.txt keyname ni ialah yang boleh di gunakan dalam onebot, tujuan ialah untuk elak fungsi sama guna nama berbeza, ini ialah sumber atau rujukan saja supaya kau atau codex tak guna keyname merepek, jadi sekiranya ada keperluan nama tambahan kau boleh suggest sekiranya senarai tiada di dalam keyname.conf.txt

Thought for 1m 48s >

**Tak boleh copy:** TIDAK.

**Create Time:** 4:41AM

Sebab Codex bagi **REPORT sahaja** (tiada full file untuk paste), dan dia minta tambah key baru `rateLimitLogDebounceMs` sebagai rujukan keyname.  codex

TASK: APPEND NEW REFERENCE KEY (KEYNAME LIST) - rateLimitLogDebounceMs

ARAHAN KERAS: DI LARANG MENEKA

Create Time: 4:41AM

#### SCOPE

- Fix ONLY: keyname.conf.txt (reference key list).
- Append-only add ONE line if missing: rateLimitLogDebounceMs
- ASCII-only. No rename/remove/reorder existing lines. No duplicate keys.
- Output MUST be copy/paste ready: FULL RAW FILE BODY only. No diff/patch. No sum

#### MUST

1) Locate EXACT keyname.conf.txt from disk (repo path).

- If multiple candidates exist, output:

REPORT

MULTIPLE CANDIDATES:

- <path1>
- <path2>

STOP.

2) Read file content from disk.

3) Check if "rateLimitLogDebounceMs" already exists anywhere:

- If exists, output:

REPORT

NO CHANGE NEEDED

STOP.

- If missing, append it at the VERY END (one line).

#### OUTPUT FORMAT (STRICT)

CHANGED FILES

Path: <exact repo path to keyname.conf.txt>

</> Plain text



STOP.



Sources



Compare with Claude ▾

codex.txt  
Document

**ARAHAN KERAS: DI LARANG MENEKA**

Create Time: 4:59AM di luar prompt kau ulang balik masalah sama, ingat itu adalah rule tetap simpan dalam memory, kau hanya perlu tulis di header Create Time: XXXXXX tiada keperluan ARAHAN KERAS: DI LARANG MENEKA, melainkan kau minta scan repo, sebab repo file repo script dan config adalah sama dengan live server onebot sedang guna..check codex.txt dan tulis prompt baru sebab codex tak dapat report apa2 seperti di tulis dalam codex.txt selepas Create Time: 4:59AM ialah merupakan actual codex reply

 Updated saved memory

Thought for 1m 47s >

**Tak boleh copy: TIDAK.**

**Create Time: 4:59AM**

Tiada file output (Codex reply cuma REPORT / NO CHANGE NEEDED / STOP ), jadi memang tak ada benda untuk paste.

TASK: CLEAN RE-OUTPUT (COPY/PASTE READY) - OutboundGateway PAIR ONLY

**SCOPE**

- NO LOGIC CHANGES (output only).
- Output MUST be copy/paste deploy: FULL RAW FILE BODY only.
- ASCII-only. No Summary/Testing/commit/PR text. No diffs.

**FILES TO OUTPUT (EXACT, 2 FILES ONLY)**

- 1) OneBot/modules/Core/OutboundGateway/OutboundGatewayCV.js
- 2) OneData/bots/ONEBOT/config/modules/Core/Impl/OutboundGatewayCV.conf

**MUST**

- Read BOTH files from disk (current final versions).
- Output format STRICT:

**CHANGED FILES**

Path: OneBot/modules/Core/OutboundGateway/OutboundGatewayCV.js

</> Plain text



Path: OneData/bots/ONEBOT/config/modules/Core/Impl/OutboundGatewayCV.conf

`</> conf`



STOP.



Sources



Compare with Claude ▾

**codex.txt**

Document

check codex.txt Create Time: 5:08AM, kalau saya perlu update keyname.conf.txt di sebabkan senarai baru pastikan beritahu supaya saya dapat update ke repo, dan pastikan beritahu keyname berkenaan untuk apa sekiranya ada

Thought for 2m 40s >

**Boleh copy (file ini sahaja): TIDAK.**

**Create Time: 5:08AM**

Key `exportServices` yang Codex guna dalam JS+conf  `codex`  `codex` **tak ikut canonical** — untuk OutboundGateway, key canonical export list ialah `services` .

 `keyname.conf`

**Perlu update** `keyname.conf.txt` **(reference list)? YA (cadangan):** tambah

`rateLimitLogDebounceMs` sebab code+conf memang guna key itu untuk **debounce log "ratelimit\_block" (ms)**.  `codex`  `codex`

TASK: FIX CANONICAL KEYNAME (OutboundGateway) - RENAME `exportServices` -> `services`

SCOPE

- Fix ONLY canonical keyname mismatch for OutboundGateway export service list.
- ASCII-only. ZERO HARDCODE.



- Output FULL RAW FILE BODY only. No diff/patch. No summary/testing/commit text.
- MAX 2 files in this response.

**MUST****1) Canonical key contract:**

- OutboundGateway export service list key MUST be: services (CSV).
- Do NOT keep/introduce alias keys (do not keep exportServices).

**2) Apply change consistently:****A) Update JS:**

- OneBot/modules/Core/OutboundGateway/OutboundGatewayCV.js
- Replace `cfg.exportServices` read with `cfg.services`
- Keep behavior exactly the same otherwise.

**B) Update conf:**

- OneData/bots/ONEBOT/config/modules/Core/Impl/OutboundGatewayCV.conf
- Replace line: `exportServices=...`  
with: `services=...`
- Keep other keys unchanged (`baseSend`, `ratelimitService`, `rateLimitLogDebounceMs`,

**OUTPUT FORMAT (STRICT)****CHANGED FILES**

Path: OneBot/modules/Core/OutboundGateway/OutboundGatewayCV.js

```js

⌘ Plain text



Path: OneData/bots/ONEBOT/config/modules/Core/Impl/OutboundGatewayCV.conf

⌘ conf



STOP.



Sources



Compare with Claude ▾

codex.txt

Document

Thought for 2m 38s >

Boleh copy (2 file ini sahaja): YA.  codex  codex

Create Time: 5:18AM

Cadangan update keyname.conf.txt : tambah rateLimitLogDebounceMs = debounce (ms) untuk log ratelimit_block dalam OutboundGateway.  codex  codex

TASK: BUILD NEXT MODULE IN SEQUENCE - Outbox (PAIR ONLY)

SCOPE

- Build Outbox as NEW CV-only implementation (1 module = 2 files only).
- ASCII-only. ZERO HARDCODE.
- Canonical keynames only (use keyname reference; do not invent new keys).
- Do NOT touch Hub/Foundation (Kernel/Connector/Start or any *Hub.js).

MUST

1) Follow ACTIVE pointers on disk for Outbox:

- OneData/bots/ONEBOT/config/modules/Core/Outbox.conf
- -> OneData/bots/ONEBOT/config/modules/Core/OutboxHub.conf
- -> implFile + implConfig

Use this to confirm expected behavior + service name (no guessing).

2) Outbox behavior contract:

- Outbox MUST send via OutboundGateway services (use sendPrefer from cfg or global)
- Outbox MUST be safe for autobot-only rate limiting:
 - When sending queued items, set options.isAuto=1 and options.manualReply=0 (un
- Rate limit bypass must NOT block manual staff messages (manual messages should

3) Conf contract:

- OutboxCV.conf MUST include:
 - enabled
 - globalConfRel=modules/Core/Impl/GlobalCV.conf
 - moduleLog, bugLog, detailLog, traceLog
 - storeSpec / storeKey / namespace (only what the CV script actually reads)
 - tickMs, batchMax (only if used)
- Use canonical keys only. No alias keys.

OUTPUT (EXACTLY 2 FILES)

CHANGED FILES

Path: OneBot/modules/Core/Outbox/OutboxCV.js

```js

</> Plain text



Path: OneData/bots/ONEBOT/config/modules/Core/Impl/OutboxCV.conf

&lt;/&gt; conf



STOP.



Sources



Compare with Claude ▾

codex.txt

Document

Thought for 2m 42s &gt;

**Boleh copy (2 file ini sahaja): YA.**  codex**Create Time: 5:44AM**

Tak perlu update `keyname.conf.txt` untuk Outbox (keys yang digunakan memang sudah ada dalam senarai rujukan).  `keyname.conf`  `keyname.conf`

TASK: BUILD NEXT MODULE IN SEQUENCE - SendQueue (PAIR ONLY)

SCOPE

- Build SendQueue as NEW CV-only implementation (1 module = 2 files only).
- ASCII-only. ZERO HARDCODE.
- Canonical keynames only (use keyname reference; do not invent new keys).
- Do NOT touch Hub/Foundation (Kernel/Connector/Start or any \*Hub.js).

MUST (NO GUESSING)

1) Follow ACTIVE pointers on disk for SendQueue:

- OneData/bots/ONEBOT/config/modules/Core/SendQueue.conf
- -> OneData/bots/ONEBOT/config/modules/Core/SendQueueHub.conf
- -> implFile + implConfig

Use this to confirm expected service name and any required keys (do not output re

2) SendQueue behavior contract (queue-not-drop):

- Provide service API: `send(chatId, payload, options)`
- Must queue sends and process in batches.
- Must respect per-chat minimum gap (`minGapMsPerChat`) if configured.

- Must NOT drop items when downstream send fails:
  - On error: keep item, schedule retry (retryDelayMs), do not remove from queue
  - Only remove when send succeeds OR attempts exceed maxAttempts (then move to d
- Must preserve options (including isAuto/manualReply flags) for downstream.

### 3) Conf contract (CV conf):

- OneData/bots/ONEBOT/config/modules/Core/Impl/SendQueueCV.conf MUST include:
  - enabled
  - globalConfRel=modules/Core/Impl/GlobalCV.conf
  - moduleLog, bugLog, detailLog, traceLog
  - serviceName (default: send)
  - baseSend (downstream service name; default from globalConf if provided)
  - delayMs, batchMax, maxQueue
  - minGapMsPerChat
  - maxAttempts, retryDelayMs, deadMax
  - dedupeMs, dedupeMax, dedupeLog (optional; only if implemented)
- Use canonical keys only. No alias keys.

OUTPUT (EXACTLY 2 FILES)

CHANGED FILES

Path: OneBot/modules/Core/SendQueue/SendQueueCV.js

```js

</> Plain text



Path: OneData/bots/ONEBOT/config/modules/Core/Impl/SendQueueCV.conf

</> conf



STOP.



Sources

... Compare with Claude ▾

codex.txt
Document

Thought for 2m 21s >

Boleh copy (2 file ini sahaja): YA.  codex

Create Time: 5:52AM

keyname.conf.txt update: **tak perlu** (keys yang digunakan memang ada dalam senarai).

 keyname.conf  keyname.conf

TASK: BUILD NEXT MODULE IN SEQUENCE - InboundFilter (PAIR ONLY)

SCOPE

- Build InboundFilter as NEW CV-only implementation (1 module = 2 files only).
- ASCII-only. ZERO HARDCODE.
- Canonical keynames only (refer keyname.conf.txt; do not invent new keys).
- Do NOT touch Hub/Foundation (Kernel/Connector/Start or any *Hub.js).

MUST (NO GUESSING)

1) Follow ACTIVE pointers on disk for InboundFilter:

- OneData/bots/ONEBOT/config/modules/Core/InboundFilter.conf
- -> OneData/bots/ONEBOT/config/modules/Core/InboundFilterHub.conf
- -> implFile + implConfig

Use this to confirm expected message hook contract used by Kernel (function names

2) InboundFilter behavior (CONFIG-DRIVEN ONLY):

- Implement inbound filtering using ONLY config keys (no hardcoded rules).
- Minimum supported keys (all 1/0):
 - dropStatusBroadcast
 - dropEmptySystem
 - dropFromMe
- If a message is dropped, it must be blocked from further processing (return per

3) Logging contract:

- Impl/CV.conf MUST include: moduleLog, bugLog, detailLog, traceLog.
- On drop: log reason + minimal msg meta (chatId/fromMe/type) (avoid payload dump)
- On pass: log only when detailLog/traceLog enabled.

4) Conf contract:

- InboundFilterCV.conf MUST include:
 - enabled
 - globalConfRel=modules/Core/Impl/GlobalCV.conf
 - moduleLog, bugLog, detailLog, traceLog
 - dropStatusBroadcast, dropEmptySystem, dropFromMe
- Use canonical keynames only. No aliases.

OUTPUT (EXACTLY 2 FILES)

CHANGED FILES

Path: OneBot/modules/Core/InboundFilter/InboundFilterCV.js

```js

</> Plain text



Path: OneData/bots/ONEBOT/config/modules/Core/Impl/InboundFilterCV.conf

`</> conf`



STOP.



Sources



Compare with Claude ▾

**codex.txt**  
Document

Thought for 1m 15s >

**Boleh copy (2 file ini sahaja): YA.**  codex  codex

**Create Time: 6:04AM**

keyname.conf.txt update: tak perlu.

**TASK: BUILD NEXT MODULE IN SEQUENCE - InboundDedupe (PAIR ONLY)**

**SCOPE**

- Build InboundDedupe as NEW CV-only implementation (1 module = 2 files only).
- ASCII-only. ZERO HARDCODE.
- Canonical keynames only (use keyname.conf.txt; do not invent new keys).
- Do NOT touch Hub/Foundation (Kernel/Connector/Start or any \*Hub.js).
- Output FULL RAW FILE BODY only. No diff/patch. No summary/testing/commit text.

**MUST (NO GUESSING)**

1) Follow ACTIVE pointers on disk for InboundDedupe:

- OneData/bots/ONEBOT/config/modules/Core/InboundDedupe.conf
- -> OneData/bots/ONEBOT/config/modules/Core/InboundDedupeHub.conf
- -> implFile + implConfig

Implement the SAME hook contract used by Kernel (function names + ctx shape).

2) Dedupe behavior (CONFIG-DRIVEN):

- Goal: suppress duplicate inbound events (e.g., message + message\_create) WITHOU

- Must NOT drop album burst media that can have empty text (especially media/doc/
- Dedupe should prefer message id when available; if msgId missing, use a safe de
- Dedupe window and limits must be configurable (no hardcoded timings/limits).

### 3) Conf contract:

- InboundDedupeCV.conf MUST include:
  - enabled
  - globalConfRel=modules/Core/Impl/GlobalCV.conf
  - moduleLog, bugLog, detailLog, traceLog
  - dedupeWindowMs
  - maxKeys
  - allowTypes (csv) OR blockTypes (csv) (pick ONE approach only, config-driven)
  - bypassIfHasMedia=1/0 (so album bursts do not get dropped)
- Use canonical keynames only. No aliases.

### 4) Implementation notes (REQUIRED):

- Store dedupe map in-memory (key -> lastSeenAtMs), prune to maxKeys.
- On duplicate within window: stopPropagation if available, and log reason=dupe w

OUTPUT (EXACTLY 2 FILES)

CHANGED FILES

Path: OneBot/modules/Core/InboundDedupe/InboundDedupeCV.js

~~~~~

</> Plain text



Path: OneData/bots/ONEBOT/config/modules/Core/Impl/InboundDedupeCV.conf

</> conf



STOP.



Sources



Compare with Claude ▾

codex.txt  
Document

Thought for 3m 55s >

Boleh copy (2 file ini sahaja): YA.  codex  codex

Create Time: 6:13AM

keyname.conf.txt update: tak perlu.

TASK: BUILD NEXT MODULE IN SEQUENCE - MessageJournal (PAIR ONLY)

#### SCOPE

- Build MessageJournal as NEW CV-only implementation (1 module = 2 files only).
- ASCII-only. ZERO HARDCODE.
- Canonical keynames only (refer keyname.conf.txt; do not invent new keys).
- Do NOT touch Hub/Foundation (Start.cmd / OneBot/Kernel.js / OneBot/Connector.js)
- Output FULL RAW FILE BODY only. No diff/patch. No summary/testing/commit text.

#### MUST (NO GUESSING)

1) Follow ACTIVE pointers on disk for MessageJournal:

- OneData/bots/ONEBOT/config/modules/Core/MessageJournal.conf
- -> OneData/bots/ONEBOT/config/modules/Core/MessageJournalHub.conf
- -> implFile + implConfig

Implement the SAME hook/contract used by Kernel for this module (function names +

2) Journal behavior contract:

- Record inbound + outbound events for audit and for active-chat timing.
- Must write append-only JSONL lines (one object per line).
- Must include minimal fields (only what exists in ctx/event):
  - ts (timezone-correct string OR epochMs)
  - dir=in|out
  - chatId
  - msgId (if available)
  - type
  - fromMe (1/0 if available)
  - ticketId (only if present in ctx or already computed upstream; do not invent)
- Must be fail-soft: if write fails, bugLog and continue (no crash).

3) Timezone + file location:

- Use timezone service name: timezone (do not use timeZone).
- File location must be config-driven:
  - dataDirRel (relative under meta.dataRootBot)
  - filePrefix (optional)
- If any REQUIRED key for this module is missing from keyname.conf.txt, STOP and REPORT
 

MISSING KEYNAME: <key>

PURPOSE: <1 line purpose>

STOP.

4) Conf contract:

- OneData/bots/ONEBOT/config/modules/Core/Impl/MessageJournalCV.conf MUST include
  - enabled
  - globalConfRel=modules/Core/Impl/GlobalCV.conf



- moduleLog, bugLog, detailLog, traceLog
- dataDirRel
- includeMessages=1/0
- includeEvents=1/0
- maxBytesPerFile (optional, only if implemented)
- rotateDaily=1/0 (optional, only if implemented)
- Use canonical keynames only. No aliases.

OUTPUT (EXACTLY 2 FILES)

CHANGED FILES

Path: OneBot/modules/Core/MessageJournal/MessageJournalCV.js

 Plain text



Path: OneData/bots/ONEBOT/config/modules/Core/Impl/MessageJournalCV.conf

 conf



STOP.



Sources

    ... [Compare with Claude](#) 

codex.txt  
Document

Thought for 1m 54s >

**Boleh copy (2 file ini sahaja): YA.**  codex

**Create Time: 6:22AM**

Tak perlu update keyname.conf.txt (keys yang digunakan

dataDirRel/filePrefix/includeMessages/includeEvents memang wujud).  keyname.conf

 keyname.conf     keyname.conf

TASK: BUILD NEXT MODULE IN SEQUENCE - Command (PAIR ONLY)

#### SCOPE

- Build Command as NEW CV-only implementation (1 module = 2 files only).
- ASCII-only. ZERO HARDCODE (no hardcoded prefix/command words/messages).
- Canonical keynames only (refer keyname.conf.txt; do not invent new keys).
- Do NOT touch Hub/Foundation (Start.cmd / OneBot/Kernel.js / OneBot/Connector.js)
- Output FULL RAW FILE BODY only. No diff/patch. No summary/testing/commit text.

#### MUST (NO GUESSING)

1) Follow ACTIVE pointers on disk for Command:

- OneData/bots/ONEBOT/config/modules/Core/Command.conf
- -> OneData/bots/ONEBOT/config/modules/Core/CommandHub.conf
- -> implFile + implConfig

Implement the SAME hook/contract used by Kernel (function names + ctx/event shape

2) Keep existing service names/contract used by other modules:

- Search repo for consumers of Command service (e.g. meta.getService('command') o
- Match the exact exported API shape those consumers expect.
- If mismatch cannot be proven, STOP and output:

REPORT

BLOCKED: COMMAND SERVICE CONTRACT NOT PROVEN

Evidence: <paths searched>

STOP.

3) Command behavior contract (config-driven):

- Parse commands only when message text starts with cfg.prefix (no default prefix)
- Enforce cfg.allowInDm / cfg.allowInGroups.
- Unknown command handling must be config-driven using:
  - unknownText
  - unknownControlGroupOnly
  - unknownPassthroughDm

(No hardcoded reply text; if unknownText empty, do nothing.)

4) Conf contract:

- OneData/bots/ONEBOT/config/modules/Core/Impl/CommandCV.conf MUST include:
  - enabled
  - globalConfRel=modules/Core/Impl/GlobalCV.conf
  - moduleLog, bugLog, detailLog, traceLog
  - prefix
  - allowInDm
  - allowInGroups
  - unknownText
  - unknownControlGroupOnly
  - unknownPassthroughDm
- Use canonical keynames only. No aliases.

5) Keyname reference rule:

- If any REQUIRED key above is missing from keyname.conf.txt, STOP and output:
 

REPORT

MISSING KEYNAME: <key>

PURPOSE: <1 line>

STOP.

OUTPUT (EXACTLY 2 FILES)

CHANGED FILES

Path: OneBot/modules/Core/Command/CommandCV.is

</> Plain text



Path: OneData/bots/ONEBOT/config/modules/Core/Impl/CommandCV.conf

</> conf



STOP.



Sources

... Compare with Claude ▾

**codex.txt**  
Document

Thought for 50s >

**Boleh copy (file ini sahaja): TIDAK.** codex

**Create Time: 6:35AM**

Perlu update keyname.conf.txt (reference) untuk tambah globalConfRel — key ini memang canonical/allowed untuk pointer global config. codex

WhatsApp Bot - 2026-03-02 S0 GD

TASK: APPEND KEYNAME (REFERENCE LIST) - globalConfRel ONLY

SCOPE

- Update ONLY keyname.conf.txt (reference canonical key list).
- Append-only add ONE key if missing: globalConfRel
- ASCII-only. No rename/remove/reorder existing lines. No duplicate keys.

- Output MUST be copy/paste ready: FULL RAW FILE BODY only. No diff/patch. No sum

#### KEY PURPOSE (1 LINE)

- globalConfRel = Relative pointer to shared global module configuration for CV i

#### MUST

1) Locate EXACT keyname.conf.txt from disk (repo path).

- If multiple candidates exist, output:

REPORT

MULTIPLE CANDIDATES:

- <path1>

- <path2>

STOP.

2) Read the file from disk.

3) If "globalConfRel" already exists anywhere:

REPORT

NO CHANGE NEEDED

STOP.

4) If missing, append this ONE line at the VERY END:

globalConfRel

#### OUTPUT FORMAT (STRICT)

CHANGED FILES

-----

</> Plain text



STOP.



Sources



Compare with Claude ▾

codex.txt

Document

Thought for 45s >

**Boleh copy (file ini sahaja): TIDAK.**

**Create Time: 6:43AM**

keyname.conf.txt **tak perlu update** — Codex dah confirm rateLimitLogDebounceMs (line 376) dan globalConfRel (line 378) memang wujud dalam /workspace/whatsappbot/keyname.conf.txt .  codex

TASK: BUILD NEXT MODULE IN SEQUENCE - Command (PAIR ONLY)

#### SCOPE

- Build Command as NEW CV-only implementation (1 module = 2 files only).
- ASCII-only. ZERO HARDCODE (no hardcoded prefix/command words/messages).
- Canonical keynames only (refer keyname.conf.txt; do not invent new keys).
- Do NOT touch Hub/Foundation (Start.cmd / OneBot/Kernel.js / OneBot/Connector.js)
- Output FULL RAW FILE BODY only. No diff/patch. No summary/testing/commit text.

#### MUST (NO GUESSING)

1) Follow ACTIVE pointers on disk for Command:

- OneData/bots/ONEBOT/config/modules/Core/Command.conf
- -> OneData/bots/ONEBOT/config/modules/Core/CommandHub.conf
- -> implFile + implConfig

Implement the SAME hook/contract used by Kernel (function names + ctx/event shape

2) Keep existing service names/contract used by other modules:

- Search repo for consumers of Command service (e.g. meta.getService('command') o
- Match the exact exported API shape those consumers expect.
- If mismatch cannot be proven, STOP and output:

REPORT

BLOCKED: COMMAND SERVICE CONTRACT NOT PROVEN

Evidence: <paths searched>

STOP.

3) Command behavior contract (config-driven):

- Parse commands only when message text starts with cfg.prefix (no default prefix
- Enforce cfg.allowInDm / cfg.allowInGroups.
- Unknown command handling must be config-driven using:
  - unknownText
  - unknownControlGroupOnly
  - unknownPassthroughDm

(No hardcoded reply text; if unknownText empty, do nothing.)

4) Conf contract:

- OneData/bots/ONEBOT/config/modules/Core/Impl/CommandCV.conf MUST include:
  - enabled
  - globalConfRel=modules/Core/Impl/GlobalCV.conf
  - moduleLog, bugLog, detailLog, traceLog
  - prefix
  - allowInDm
  - allowInGroups
  - unknownText
  - unknownControlGroupOnly

- unknownPassthroughDm
- Use canonical keynames only. No aliases.

OUTPUT (EXACTLY 2 FILES)

CHANGED FILES

Path: OneBot/modules/Core/Command/CommandCV.js

</> Plain text



Path: OneData/bots/ONEBOT/config/modules/Core/Impl/CommandCV.conf

</> conf



STOP.



Sources



Compare with Claude ▾

codex.txt  
Document

Thought for 1m 46s >

**Boleh copy (2 file ini sahaja): TIDAK.**

**Create Time: 6:55AM**

CommandCV.conf ada line ekstra . di hujung (bukan komen / bukan key=value), jadi output tu tak "clean" untuk paste live.  codex

TASK: CLEAN RE-OUTPUT (COPY/PASTE READY) - Command PAIR ONLY

SCOPE

- NO LOGIC CHANGES. OUTPUT ONLY (clean, deployable).
- ASCII-only. No diff/patch markers. No summary/testing/commit text.
- Deliver EXACTLY 2 files only.

FILES TO OUTPUT (EXACT, 2 FILES ONLY)

1) OneBot/modules/Core/Command/CommandCV.js

2) OneData/bots/ONEBOT/config/modules/Core/Impl/CommandCV.conf

MUST

- Output FULL RAW FILE BODY for both files.
- CommandCV.conf must contain ONLY:
  - Comment lines starting with "#"
  - Blank lines
  - key=value lines
- Do NOT output any extra separators like "." or "-----" or "STOP." inside the fi
- Keep rules:
  - No default prefix in JS (prefix must come from cfg.prefix only; if blank, saf
  - CommandCV.conf must NOT contain controlId (single-source stays in Global
  - unknownText must NOT hardcode any prefix or "!help" (keep it generic).

OUTPUT FORMAT (STRICT)

CHANGED FILES

Path: OneBot/modules/Core/Command/CommandCV.js

</> Plain text



Path: OneData/bots/ONEBOT/config/modules/Core/Impl/CommandCV.conf

</> conf



STOP.



Sources



Compare with Claude ▾

codex.txt

Document

Thought for 2m 10s >

Boleh copy (2 file ini sahaja): YA.



codex



codex

Create Time: 7:02AM



codex

TASK: BUILD NEXT MODULE IN SEQUENCE - AccessRoles (PAIR ONLY)

#### SCOPE

- Build AccessRoles as NEW CV-only implementation (1 module = 2 files only).
- ASCII-only. ZERO HARDCODE (no phones/ids/role names/command words/messages in J
- Canonical keynames only (refer keyname.conf.txt; do not invent new keys).
- Do NOT touch Hub/Foundation (Start.cmd / OneBot/Kernel.js / OneBot/Connector.js
- Output FULL RAW FILE BODY only. No diff/patch. No summary/testing/commit text.

#### MUST (NO GUESSING)

1) Follow ACTIVE pointers on disk for AccessRoles:

- OneData/bots/ONEBOT/config/modules/Core/AccessRoles.conf
- -> OneData/bots/ONEBOT/config/modules/Core/AccessRolesHub.conf
- -> implFile + implConfig

Implement the SAME hook/contract used by Kernel for this module.

2) Service contract:

- Search repo for all consumers of AccessRoles service and match EXACT API shape
- Register ONLY ONE canonical service name: access (no alias services like roles/

3) Behavior contract:

- Gate commands/actions by role (admin/manager/staff/viewer or whatever the repo
- All role command words + all reply messages MUST come from AccessRolesCV.conf o
- If any required config key is missing/blank: bugLog + safe-disable the role com

4) Keyname reference rule:

- If any REQUIRED key you need for AccessRoles is missing from keyname.conf.txt:  
REPORT  
MISSING KEYNAME: <key>  
PURPOSE: <1 line purpose>  
STOP.

#### OUTPUT (EXACTLY 2 FILES)

##### CHANGED FILES

Path: OneBot/modules/Core/AccessRoles/AccessRolesCV.js

```js

</> Plain text



Path: OneData/bots/ONEBOT/config/modules/Core/Impl/AccessRolesCV.conf

</> conf



STOP.



Sources



Compare with Claude ▾

codex.txt
Document

dalam keyname pasti ada yang fungsi sama kegunaannya kalau dan perlu tengok keyname mana boleh pakai perlu, setiap kali hantar prompt codex wajib scan repo supaya dia tak guna repo lama, sepatutnya codex wajib check full repo fungsi yang sama seperti mana yang nak di guna pakai, kalau tiada baru create keyname baru..tujuan keyname ni bukan suka2 reka, kalau tiada dalam keyname.conf.txt baru boleh create baru, fungsi sama ni bermaksud seperti on/enable ini maksud sama, jadi perlu cari dulu dalam keyname.conf.txt dan juga config lain yang mungkin fungsi sama tapi guna nama berlainan dari apa yang kita nak, jangan create keyname tanpa semakan repo

Thought for 41s >

Boleh copy (file ini sahaja): TIDAK.  codex**Create Time: 7:15AM**

Perlu **repo scan dulu** untuk cari sama ada key fungsi sama sudah wujud sebelum create key baru.  codex

TASK: REPO SCAN REPORT - FIND CANONICAL KEY FOR ACCESSROLES COMMAND SERVICE BINDI

ARAHAN KERAS: DI LARANG MENEKA

SCOPE

- REPORT ONLY. NO CODE/CONF CHANGES.
- Fresh full repo scan required (do not rely on old context).
- Goal: find whether an EXISTING canonical key already covers the same purpose as

MUST

- 1) Fresh scan from disk:

```
- keyname.conf.txt
- all OneData/bots/ONEBOT/config/**/*.*conf
- all OneBot/modules/**/*.*js

2) Search for EXISTING keys with same/similar purpose:
- command service selector/binding key
- service name key used to pick another module/service
- examples of same-function naming across repo such as:
  serviceName, commandService, commandServiceName, baseSend, ratelimitService, ti
- include any config key that means "which service/module to bind/use"

3) Output findings in 3 sections only:
A) EXACT MATCHES
- keys found in keyname.conf.txt and where used in repo

B) SAME-FUNCTION CANDIDATES
- existing keys from repo/config that can serve the SAME PURPOSE for AccessRoles
- for each candidate:
  - key
  - exact path(s)
  - 1-line purpose from actual usage

C) DECISION
- If an existing canonical key can be reused:
  REUSE KEY: <key>
  PURPOSE: <1 line>
- If none can be reused:
  MISSING KEYNAME: commandServiceName
  PURPOSE: Config key for selecting which command service AccessRoles binds its r

OUTPUT
REPORT
A) EXACT MATCHES
B) SAME-FUNCTION CANDIDATES
- - - - -
</> Plain text
```



Sources



Compare with Claude ▾

codex.txt
Document

Thought for 1m 47s >

Boleh copy (file ini sahaja): TIDAK. Sebab ini **REPORT sahaja** (tiada `.js/.conf` untuk paste live).  codex

Create Time: 7:26AM  codex

Keyname baru **tak perlu** — keputusan report: **REUSE KEY =** `commandService`.  codex

TASK: BUILD NEXT MODULE IN SEQUENCE - AccessRoles (PAIR ONLY, REUSE `commandService`)

SCOPE

- Build AccessRoles as NEW CV-only implementation (1 module = 2 files only).
- ASCII-only. ZERO HARDCODE (no phone/groupId/role names/command words/messages i
- Canonical keynames only (must reuse existing keys; do not create new keyname un
- Do NOT touch Hub/Foundation (Start.cmd / OneBot/Kernel.js / OneBot/Connector.js
- Output FULL RAW FILE BODY only. No diff/patch. No summary/testing/commit text.

MUST (FRESH DISK SCAN FIRST, NO STALE CONTEXT)

1) Follow ACTIVE pointers on disk for AccessRoles:

- OneData/bots/ONEBOT/config/modules/Core/AccessRoles.conf
- -> OneData/bots/ONEBOT/config/modules/Core/AccessRolesHub.conf
- -> implFile + implConfig

Confirm exact expected module hook + service name used by the repo.

2) Prove the AccessRoles service contract from real consumers:

- Scan repo for any of:
 - `meta.getService('access')`
 - `accessService=`
 - SharedRoleGateV1 usage
 - `help/command` modules calling role gate
- Identify the EXACT API shape expected (function names + args + return shape).
- If contract cannot be proven from disk, STOP and output:

REPORT

BLOCKED: ACCESSROLES SERVICE CONTRACT NOT PROVEN

EVIDENCE: <paths searched>

STOP.

3) Keyname reuse rule (NO NEW KEY WITHOUT PROOF)

- You MUST reuse existing canonical key for command binding:
 - Use config key: `commandService` (REUSE, proven by report)
- Before inventing ANY new config key:
 - Search `keyname.conf.txt` + existing module `Impl/*.conf` for same-function keys.
 - If none exists and a new key is truly required, STOP and output:

REPORT

NEED NEW KEYNAME: <key>

PURPOSE: <1 line purpose>

EVIDENCE: <why existing keys cannot fit>

STOP.

4) Required behaviors (config-driven)

- AccessRoles MUST register itself as the canonical access service (one service o

- serviceName from conf (expected default value should be set in conf, not JS).
- AccessRoles MUST bind to Command module using cfg.commandService (string service then register role-management commands using ONLY command words from conf.
- All role names and command words MUST come from AccessRolesCV.conf (no JS default)
- Storage MUST be config-driven:
 - If repo already uses JsonStore/storeSpec/storeKey pattern, reuse the same pattern
 - Must be fail-soft (bugLog + no crash).

5) AccessRolesCV.conf requirements

- Must include:
 - enabled
 - globalConfRel=modules/Core/Impl/GlobalCV.conf
 - moduleLog, bugLog, detailLog, traceLog
 - serviceName
 - commandService (REUSED canonical key)
 - plus ONLY the other keys that your AccessRolesCV.js actually reads (reused from GlobalCV.conf)

OUTPUT (EXACTLY 2 FILES)

CHANGED FILES

Path: OneBot/modules/Core/AccessRoles/AccessRolesCV.js

```js

</> Plain text



Path: OneData/bots/ONEBOT/config/modules/Core/Impl/AccessRolesCV.conf

</> conf



STOP.



Sources

... Compare with Claude ▾

codex.txt  
Document

Aku tengah audit output AccessRoles ni. Setakat ni ada satu red flag jelas: dia guna store= instead of pattern yang prompt sendiri suruh reuse, iaitu storeSpec/storeKey ,

jadi belum selamat untuk live.

Thought for 1m 1s >

**Boleh copy (2 file ini sahaja): TIDAK.**

**Create Time: 7:34AM**

Langgar pattern storage yang prompt suruh reuse: dia guna `store=` dalam conf dan `cfg.store` dalam JS, bukan pattern repo `storeSpec/storeKey . keyname.conf.txt` update: **tak perlu.**  codex

**TASK: FIX ACCESSROLES CANONICAL STORAGE KEYS (PAIR ONLY)**

**SCOPE**

- Fix ONLY AccessRoles pair.
- Fresh disk scan FIRST (do not rely on old context).
- ASCII-only. ZERO HARDCODE.
- Reuse existing repo/keyname patterns only. Do NOT create new keyname unless pro
- Output FULL RAW FILE BODY only. No diff/patch. No summary/testing/commit text.

**MUST**

1) Fresh scan from disk:

- `keyname.conf.txt`
- `OneData/bots/ONEBOT/config/modules/Core/Impl/*.conf`
- `OneBot/modules/Core/**/*.js`

2) Reuse canonical storage pattern already required by repo:

- For JsonStore binding, use `storeSpec + storeKey` pattern (NOT `store`).
- Search repo for same-function storage keys first and match existing canonical u
- If repo proves a different canonical key already exists for the SAME PURPOSE, r
- If no canonical key can be proven, STOP and output:

REPORT

NEED NEW KEYNAME: <key>

PURPOSE: <1 line>

EVIDENCE: <paths searched>

STOP.

3) Fix AccessRoles pair only:

A) `OneBot/modules/Core/AccessRoles/AccessRolesCV.js`

- Replace `cfg.store` read with canonical storage key read proven by fresh scan.
- Keep `commandService` reuse as-is.
- Keep service contract/behavior same otherwise.

B) `OneData/bots/ONEBOT/config/modules/Core/Impl/AccessRolesCV.conf`

- Replace non-canonical storage key with canonical storage key proven by fresh sc
- Keep other values/behavior same otherwise.

4) Clean output rules

- JS must not read deprecated/non-canonical alias for storage if canonical key is

- Conf must contain only comment lines, blank lines, and key=value lines.

OUTPUT FORMAT (STRICT)

CHANGED FILES

Path: OneBot/modules/Core/AccessRoles/AccessRolesCV.js

```ic

</> Plain text



Path: OneData/bots/ONEBOT/config/modules/Core/Impl/AccessRolesCV.conf

</> conf



STOP.



Sources

... Compare with Claude ▾

codex.txt
Document

Aku dah nampak storage keys dah betul semula. Aku tengah semak sekarang sama ada output ni cukup "clean" untuk live, bukan setakat syntax jalan.

Thought for 2m 47s >

Boleh copy (2 file ini sahaja): TIDAK. codex

Create Time: 7:42AM

ownerSeedList hilang, role sales hilang, dan contract !role me / msgMe {role}
{idKey} sesi akhir tak dipelihara. WhatsApp Bot - 2026-03-04 S0 GD

ONEBOTREBUILDWORKFLOWTRACKER

TASK: FIX ACCESSROLES REGRESSION TO MATCH LATEST SESSION CONTRACT (PAIR ONLY)

SCOPE

- Fix ONLY AccessRoles pair.
- Fresh disk scan FIRST from active pointers (do not use stale context).
- ASCII-only. ZERO HARDCODE.
- Reuse existing repo/keyname patterns only.
- Output FULL RAW FILE BODY only. No diff/patch. No summary/testing/commit text.

MUST

1) Fresh scan from disk:

- OneData/bots/ONEBOT/config/modules/Core/AccessRoles.conf
- -> OneData/bots/ONEBOT/config/modules/Core/AccessRolesHub.conf
- -> active implFile + implConfig
- Scan existing AccessRoles-related code/conf on disk before editing.

2) Keep latest AccessRoles contract from the latest session:

- !role me / set / del / list must work
- msgMe must support placeholders: {role} and {idKey}
- owner bootstrap seed must exist in conf using BOTH formats:
ownerSeedList=82828612100333@lid,lid:82828612100333

3) Keep canonical/reused patterns already proven:

- serviceName=access
- commandService
- storeSpec
- storeKey
- no non-canonical storage alias

4) Role set must include sales (do not drop it).

- Required role list/order in conf:
owner,admin,manager,sales,staff,viewer
- If existing repo contract proves different ordering is mandatory, preserve real

5) Do NOT regress existing role API behavior:

- getRole(any) accepts ctx or string id
- hasAtLeast(any, minRole)
- hasRole(any, reqRole) behaves as MIN-ROLE check
- isExactRole(any, role) exact match check

6) Reply text rules:

- No hardcoded prefix in messages
- Role command messages must come from conf keys
- Do not replace all replies with generic unknownText if repo already has dedicat

OUTPUT FORMAT (STRICT)

CHANGED FILES

Path: OneBot/modules/Core/AccessRoles/AccessRolesCV.js

</> Plain text



Path: OneData/bots/ONEBOT/config/modules/Core/Impl/AccessRolesCV.conf

</> conf



STOP.



Sources



Compare with Claude ▾

codex.txt

Document

Thought for 2m 17s >

Boleh copy (2 file ini sahaja): YA.**Create Time: 8:05AM**Next sequence lepas deploy ni: **6G (Anti-miss).**  WhatsApp Bot - 2026-03-04 S0 GD

TASK: 6G IMPLEMENT (Anti-miss reminders + escalation) - DEPLOYABLE (MAX 2 FILES)

SCOPE

- Implement ONLY 6G:

- Remind ops/control group about unreplied OPEN DM tickets (no spam)
- Escalate after longer threshold (still no spam)
- ASCII-only. ZERO HARDCODE (no IDs/text/prefix/template paths in JS).
- Do NOT touch Start.cmd / OneBot/Kernel.js / OneBot/Connector.js / any *Hub.js.
- Output FULL file bodies only. No report/summary unless BLOCKED.

FILES (MAX 2)

- 1) <active Fallback implFile from repo pointers>
- 2) <active Fallback implConfig from repo pointers> (ONLY if you must append exist

MUST (NO STALE CONTEXT)

- 1) Follow active pointers and confirm exact runtime paths from disk:
 - OneData/bots/ONEBOT/config/modules/Core/Fallback.conf
 - -> OneData/bots/ONEBOT/config/modules/Core/FallbackHub.conf
 - -> <active FallbackCV.js>
 - -> <active FallbackCV.conf>

2) Use existing scheduler mechanism if present (preferred); otherwise add a local
- Do NOT create new module files.

3) Use ONLY existing canonical config keys already present in active confs (Fallb
- Do NOT invent new keys for 6G.

- If the required 6G settings cannot be mapped to existing keys, STOP and output:
REPORT

BLOCKED: missing existing config keys for 6G settings

MISSING CONCEPTS: <list concepts>

EVIDENCE: <paths scanned>

STOP.

BEHAVIOR (NO GUESSING, NO NEW TICKET FIELDS)

- Ticket selection:

- DM-origin tickets only

- status OPEN only (use existing status fields/values already used by Fallback)

- "unreplied" must be computed using existing stored fields only (do not invent

- Reminder target:

- send into control/ops group using existing send pipeline used by Fallback tic

- scheduled sends MUST pass options.isAuto=1 and options.lastInboundAtMs (best-

- reminders must not double-send in same tick; apply batch limit + max attempts

OUTPUT FORMAT (STRICT)

CHANGED FILES

Path: <active FallbackCV.js path>

</> Plain text



(Only if you changed it)

Path: <active FallbackCV.conf path>

</> conf



STOP.



Sources



Compare with Claude ▾

codex.txt

Thought for 32s >

Tak boleh copy: TIDAK.  codex

Create Time: 8:18AM

Blocked sebab **tiada existing config keys** untuk setting 6G (interval, threshold, template, batch/attempt).  codex

**TASK: 6G KEY MAPPING REPORT (NO NEW KEYS YET) - FIND EXISTING KEYS/TEMPLATES TO R
ARAHAN KERAS: DI LARANG MENEKA**

SCOPE

- REPORT ONLY. NO CODE/CONF CHANGES.
- Fresh full repo scan required (do not rely on old context).
- Goal: find EXISTING config keys + existing template system that can cover 6G co
- Do NOT invent new keys in this task. If truly missing, propose them as "NEED NE

MUST SCAN (FROM DISK)

- keyname.conf.txt
- OneData/bots/ONEBOT/config/modules/Core/Impl/*.conf
- OneData/bots/ONEBOT/config/ui/** (templates)
- OneBot/modules/Core/**/*.*js (especially Fallback, Scheduler, MessageJournal, Ou

CONCEPTS TO MAP (REUSE FIRST)

- 1) reminder interval
- 2) escalation threshold
- 3) reminder template text (prefer template file/path, not inline)
- 4) escalation template text (prefer template file/path, not inline)
- 5) reminder batch limit
- 6) escalation max attempts

OUTPUT (STRICT 3 SECTIONS)

REPORT

A) EXISTING KEYS FOUND (REUSABLE)

- For each concept above, list:
 - concept
 - existing key name(s)
 - exact file paths where used
 - 1-line purpose inferred from actual usage

B) EXISTING TEMPLATE SYSTEM (REUSABLE)

- List any existing template keys/patterns (e.g., templateRel/templateFile/ui pat
- List existing UI template files that could be reused/extended for reminder/esca

C) DECISION

- For each concept:
 - REUSE: <key> (if found)
 - OR NEED NEW KEYNAME: <key> + PURPOSE (1 line) + PROOF (what you scanned, why

↗ Plain text



Sources

Compare with Claude ▾

codex.txt
Document

Thought for 31s >

Boleh copy (file ini sahaja): TIDAK. codex

Create Time: 8:23AM

Report ini cukup untuk sambung next stage. keyname.conf.txt update: tak perlu — semua konsep 6G sudah ada key/template yang boleh reuse. codex

TASK: 6G IMPLEMENT (Anti-miss reminders + escalation) - REUSE EXISTING KEYS/TEMPL

SCOPE

- Implement ONLY 6G using EXISTING repo keys/templates already proven by report.
- Fresh full repo scan FIRST from disk (do not rely on old context).
- ASCII-only. ZERO HARDCODE.
- Do NOT create new keynames.
- Do NOT touch Start.cmd / OneBot/Kernel.js / OneBot/Connector.js / any *Hub.js.
- Output FULL RAW FILE BODY only. No diff/patch. No summary/testing/commit text.

FILES (MAX 2)

- 1) <active Fallback implFile from repo pointers>
- 2) <active Fallback implConfig from repo pointers> (ONLY if changed)

MUST

- 1) Follow active runtime pointers from disk:
 - OneData/bots/ONEBOT/config/modules/Core/Fallback.conf
 - -> OneData/bots/ONEBOT/config/modules/Core/FallbackHub.conf
 - -> active implFile
 - -> active implConfig

2) Reuse ONLY these existing concepts already proven by report:

- reminder interval -> intervalMs or tickMs (pick the one that best matches the a
- escalation threshold -> maxAttempts
- spacing/backoff -> retryDelayMs
- reminder template -> ticketCardTemplate or forwardTextPrefixTemplate
- escalation template -> staffTaskTemplate or ticketCardTemplate
- reminder batch limit -> batchMax or msgBufferMax
- escalation max attempts -> maxAttempts

Do NOT invent any new config key.

3) Implementation rules:

- Prefer existing scheduler mechanism if active Fallback already uses/proves it c
- Otherwise add local periodic check INSIDE active Fallback impl only.
- DM-origin tickets only
- OPEN tickets only
- "unreplied" must be computed from existing stored fields only
- Send reminders/escalations into control group using existing send pipeline
- Scheduled sends must pass options.isAuto=1 and options.manualReply=0
- No spam: dedupe same ticket within same cycle and respect reused batch/attempt

4) Conf edit rule:

- Only edit active FallbackCV.conf if you need to append EXISTING canonical keys
- No aliases. No new concepts. No duplicate keys.

5) If active repo structure proves 6G cannot be implemented safely with ONLY thos
REPORT

BLOCKED: 6G CANNOT MAP SAFELY WITH REUSED KEYS ONLY

EVIDENCE: <exact paths scanned>

STOP.

OUTPUT FORMAT (STRICT)

CHANGED FILES

Path: <active FallbackCV.js path>

</> Plain text



(Only if changed)

Path: <active FallbackCV.conf path>

</> conf



STOP.



Sources






 Compare with Claude ▾

codex.txt
Document

Aku dah nampak punca utama. Yang ini tak boleh terus deploy sebab Codex bukan buat satu task terhad pada Fallback pair — dia sentuh 14 fail termasuk keyname/reference, jadi output ni dah lari dari scope.

Thought for 2m 0s >

Boleh copy (2 file ini sahaja): TIDAK.  codex

Create Time: 8:36AM

Sentuh **14 fail** termasuk `keyname.conf.txt`, jadi dah lari dari scope task 6G yang sepatutnya **max 2 fail** dan **reuse existing keys only.**  codex

 ONEBOTREBUILDWORKFLOWTRACKER

TASK: CLEAN RE-OUTPUT (COPY/PASTE READY) - ACTIVE FALLBACK PAIR ONLY

SCOPE

- NO NEW LOGIC CHANGES.
- Fresh repo scan FIRST from disk, then OUTPUT ONLY the current active Fallback p
- ASCII-only. No diff/patch. No summary/testing/commit/PR text.
- Do NOT output any unrelated files.
- Do NOT output keyname.conf.txt in this task.

MUST

1) Follow active runtime pointers from disk:

- OneData/bots/ONEBOT/config/modules/Core/Fallback.conf
- -> OneData/bots/ONEBOT/config/modules/Core/FallbackHub.conf
- -> active implFile
- -> active implConfig

2) Read the CURRENT on-disk active files only:

- <active Fallback implFile>
- <active Fallback implConfig>

3) Output EXACTLY these 2 files only:

- active FallbackCV.js
- active FallbackCV.conf

4) Do NOT modify any other file and do NOT include any other file in output.

- Ignore unrelated branch changes.
- No keyname updates in this task.

5) Clean output rules:

- JS code block = raw file body only
- CONF code block = raw file body only
- CONF must contain only comment lines (#), blank lines, and key=value lines

OUTPUT FORMAT (STRICT)

CHANGED FILES

Path: <active FallbackCV.js path>

```js

</> Plain text



Path: <active FallbackCV.conf path>

</> conf



STOP.



Sources

... Compare with Claude ▾

codex.txt

Document

Thought for 1m 53s >

**Boleh copy (2 file ini sahaja): TIDAK.**

**Create Time: 8:59AM**

keyname.conf.txt update: **tak perlu**. Output ini belum cukup sebab ia buat **reminder loop sahaja**, tetapi **tiada laluan escalation yang berbeza**, dan pemilihan ticket masih nampak macam **semua OPEN DM** berdasarkan `updatedAt/createdAt` , bukan bukti jelas "unreplied only". codex

TASK: FIX 6G CONTRACT (REMINDER + ESCALATION) - ACTIVE FALLBACK PAIR ONLY

#### SCOPE

- Fix ONLY the active Fallback pair.
- Fresh repo scan FIRST from disk (do not rely on stale context).
- ASCII-only. ZERO HARDCODE.
- Reuse existing repo keys/templates only.
- Do NOT touch keyname.conf.txt.
- Output FULL RAW FILE BODY only. No diff/patch. No summary/testing/commit text.

#### FILES (EXACTLY 2 ONLY)

- 1) <active Fallback implFile from repo pointers>
- 2) <active Fallback implConfig from repo pointers> (only if changed)

#### MUST

- 1) Follow active runtime pointers from disk:
  - OneData/bots/ONEBOT/config/modules/Core/Fallback.conf
  - -> OneData/bots/ONEBOT/config/modules/Core/FallbackHub.conf
  - -> active implFile
  - -> active implConfig

#### 2) Keep existing reused 6G keys only:

- tickMs
- batchMax
- maxAttempts
- retryDelayMs

Do NOT invent any new key.

#### 3) Keep existing reused template system only:

- reminder must use an existing proven template path/key
- escalation must use an existing proven template path/key
- escalation must be a REAL separate path/output, not just "stop after maxAttempt

#### 4) Fix ticket selection logic:

- 6G must target DM-origin OPEN tickets only
- 6G must target UNREPLIED tickets only
- compute "unreplied" using existing stored ticket fields only
- do NOT remind all OPEN DM blindly
- if existing ticket store on disk does not contain enough existing fields to dis

REPORT

BLOCKED: UNREPLIED STATE NOT PROVABLE FROM EXISTING TICKET FIELDS

EVIDENCE: <exact active files/fields scanned>

STOP.

#### 5) Delivery rules:

- reminder sends into control group using existing send pipeline
- escalation sends into control group using existing send pipeline
- scheduled sends must pass options.isAuto=1 and options.manualReply=0
- no spam: dedupe same ticket within same cycle and respect batchMax/maxAttempts/

6) Clean output rules:

- Output EXACTLY 2 files only
- No unrelated files
- No keyname/reference file output

OUTPUT FORMAT (STRICT)

CHANGED FILES

Path: <active FallbackCV.js path>

</> Plain text



Path: <active FallbackCV.conf path>

</> conf



STOP.



Sources



Compare with Claude ▾

codex.txt

Document

Aku dah confirm blocker dia real: bukan syntax issue, tapi data model issue. Sekarang paling selamat ialah suruh Codex cari sama ada "replied state" memang sudah wujud di tempat lain dalam repo sebelum kita ubah logic 6G.

Thought for 40s >

Boleh copy (2 file ini sahaja): TIDAK.  codex

Create Time: 9:13AM

Blocked: **report sahaja**, dan unreplied state memang belum boleh dibuktikan dari field ticket sedia ada.  codex



TASK: REPO SCAN REPORT - FIND EXISTING SOURCE OF TRUTH FOR REPLIED/UNREPLIED STATE

ARAHAN KERAS: DI LARANG MENEKA

#### SCOPE

- REPORT ONLY. NO CODE/CONF CHANGES.
- Fresh full repo scan required from disk.
- Goal: find whether replied/unreplied state already exists ANYWHERE in repo/store

#### MUST SCAN (FROM DISK)

- OneBot/modules/Core/Fallback/\*\*/\*.\*js
- OneBot/modules/Core/MessageJournal/\*\*/\*.\*js
- OneBot/modules/Core/Command/\*\*/\*.\*js
- OneBot/modules/Core/Outbox/\*\*/\*.\*js
- OneBot/modules/Core/SendQueue/\*\*/\*.\*js
- OneBot/modules/Core/JsonStore/\*\*/\*.\*js
- OneBot/modules/Core/WorkGroups/\*\*/\*.\*js
- OneData/bots/ONEBOT/config/modules/Core/\*\*/\*.\*conf
- OneData/bots/ONEBOT/config/ui/\*\*
- Any active data path/store path referenced by active Fallback/JsonStore/Message

#### SEARCH FOR

- 1) Any persisted marker/timestamp/counter/flag showing staff replied to a ticket
- 2) Any journal/log/store entry that can prove:
  - inbound customer message happened after ticket open
  - outbound staff/group reply happened after that
  - quote-reply / !r / bind/move flows that already persist evidence
- 3) Any existing field names or store objects related to:
  - replied
  - lastReplyAt
  - lastStaffReplyAt
  - lastInboundAt
  - lastOutboundAt
  - replyCount
  - pendingCustomer
  - awaitingStaff
  - awaitingCustomer
  - state/status transitions beyond OPEN/CLOSED
- 4) Any exact place where ticket store is updated on reply paths:
  - FallbackReplyTextCV.js
  - FallbackReplyMediaCV.js
  - FallbackReplyAVCV.js
  - any command reply helper/shared helper

#### OUTPUT (STRICT)

##### REPORT

##### A) EXISTING PERSISTED EVIDENCE

- exact field/key/log/store found
- exact path(s)

- 1-line purpose from actual usage

#### B) CAN UNREPLIED BE PROVEN WITHOUT NEW TICKET FIELDS?

- YES or NO
- If YES:
  - exact source of truth
  - exact comparison logic that can be used safely
- If NO:
  - say exactly what is missing

#### C) MINIMAL SAFE NEXT STEP

- REUSE EXISTING SOURCE: <what>

OR

- NEED NEW TICKET FIELD(S): <field name(s)> + PURPOSE (1 line each)

</> Plain text



Sources

... Compare with Claude ▾

**codex.txt**  
Document

Thought for 1m 31s >

**Boleh copy (file ini sahaja): TIDAK.**

**Create Time: 9:17AM**

keyname.conf.txt update: **tak perlu**. Report ini cuma bukti blocker 6G; next step kena simpan replied/unreplied state dulu. codex

TASK: BUILD 6G PRECONDITION - PERSIST STAFF-REPLY STATE IN ACTIVE FALLBACK FLOW (

#### SCOPE

- Fix ONLY the minimal persisted ticket fields needed to unblock 6G.
- Fresh repo scan FIRST from disk (do not rely on old context).
- ASCII-only. ZERO HARDCODE.
- Reuse existing active ticket store and active reply handlers only.
- Do NOT touch keyname.conf.txt.
- Output FULL RAW FILE BODY only. No diff/patch. No summary/testing/commit text.

## FILES (MAX 4)

- 1) <active Fallback implFile from repo pointers>
- 2) OneBot/modules/Core/Fallback/FallbackReplyTextCV.js
- 3) OneBot/modules/Core/Fallback/FallbackReplyMediaCV.js
- 4) OneBot/modules/Core/Fallback/FallbackReplyAVCV.js

## MUST

- 1) Follow active runtime pointers from disk:
  - OneData/bots/ONEBOT/config/modules/Core/Fallback.conf
  - -> OneData/bots/ONEBOT/config/modules/Core/FallbackHub.conf
  - -> active Fallback implFile
  - confirm active ticket store path/pattern actually used on disk

## 2) Persist minimal source-of-truth fields in ACTIVE ticket schema:

- lastInboundAt
- lastStaffReplyAt
- awaitingStaff

Do NOT invent any other new ticket field unless already proven active on disk.

## 3) In active Fallback implFile:

- On inbound customer DM ticket create/update, persist:
  - lastInboundAt = current ticket inbound timestamp
  - awaitingStaff = 1
- Keep existing status/ticket flow unchanged otherwise.

## 4) In ALL 3 reply handlers (text/media/av):

- After successful send to customer, update the SAME ticket store record:
  - lastStaffReplyAt = send success timestamp
  - awaitingStaff = 0, but ONLY if this reply satisfies the current pending inbound
- If send fails, do NOT write lastStaffReplyAt/awaitingStaff=0
- Keep existing send flags/behavior unchanged:
  - manualReply=1
  - bypassRateLimit behavior as already used by active code

## 5) Safety rules:

- Use existing ticketId lookup/storeSpec/storeKey patterns already active in repo
- Fail-soft only: bugLog on store update error, no crash
- Do NOT add config keys in this task
- Do NOT touch unrelated modules/files

## OUTPUT FORMAT (STRICT)

## CHANGED FILES

Path: <active FallbackCV.js path>

</> Plain text



Path: OneBot/modules/Core/Fallback/FallbackReplyTextCV.js

</> JavaScript



Path: OneBot/modules/Core/Fallback/FallbackReplyMediaCV.js

JavaScript



Path: OneBot/modules/Core/Fallback/FallbackReplyAVCV.js

JavaScript



STOP.



Sources



Compare with Claude ▾

codex.txt

Document

Aku dah jumpa isu yang paling penting. Empat fail reply-state tu nampak masuk, tapi `FallbackCV.js` masih bawa sekali loop 6G lama yang belum sah, jadi kalau paste live sekarang dia masih boleh remind semua OPEN DM secara salah.

Thought for 1m 40s >

**Boleh copy (4 file ini sahaja): TIDAK.**

**Create Time: 9:24AM**

`FallbackReplyTextCV.js` / `Media` / `AVCV` nampak ikut precondition, tapi `FallbackCV.js` masih bawa loop 6G lama ( `runReminderCycle` + `reminderTimer` ), jadi set ini belum clean untuk live.  codex

TASK: CLEAN PRECONDITION ONLY - REMOVE INCOMPLETE 6G LOOP FROM ACTIVE `FallbackCV`.

## SCOPE

- Fix ONLY the active FallbackCV.js from current on-disk repo state.
- Fresh full repo scan FIRST from disk (do not rely on old context).
- Keep the persisted precondition fields already added for 6G unblock:
  - lastInboundAt
  - lastStaffReplyAt
  - awaitingStaff
- REMOVE the incomplete 6G reminder engine from FallbackCV.js for now.
- ASCII-only. ZERO HARDCODE.
- Output FULL RAW FILE BODY only. No diff/patch. No summary/testing/commit text.

## FILES (EXACTLY 1)

1) <active Fallback implFile from repo pointers>

## MUST

1) Follow active runtime pointers from disk:

- OneData/bots/ONEBOT/config/modules/Core/Fallback.conf
- -> OneData/bots/ONEBOT/config/modules/Core/FallbackHub.conf
- -> active Fallback implFile

2) In active FallbackCV.js:

- KEEP:
  - current reply wiring (ReplyText / ReplyMedia / ReplyAV)
  - current inbound ticket create/update flow
  - persistence of lastInboundAt and awaitingStaff on inbound DM
  - existing ticket store pattern and service usage
- REMOVE:
  - reminderState Map
  - runReminderCycle()
  - reminderTimer / setInterval()
  - any tickMs/batchMax/maxAttempts/retryDelayMs logic used only for 6G loop
  - any shutdown cleanup that only exists for reminderTimer

3) Do NOT change the 3 reply handler files in this task.

4) Do NOT edit conf in this task.

5) Goal: active FallbackCV.js must become PRECONDITION-ONLY, not partial 6G.

## OUTPUT FORMAT (STRICT)

## CHANGED FILES

Path: <active FallbackCV.js path>

</> Plain text



STOP.



Sources

    ... Compare with Claude ▾

codex.txt

Document

Aku tengah semak snippet Fallback ni ikut rule sesi lepas: fokus sekarang cuma sama ada file ini sudah "clean precondition only" atau masih bawa logic 6G yang tak patut ada.

Thought for 3m 49s >

**Boleh copy (file ini sahaja): YA.**  codex

**Create Time: 9:35AM**  codex

TASK: 6G IMPLEMENT (ANTI-MISS REMINDER + ESCALATION) - ACTIVE FALLBACK PAIR ONLY

#### SCOPE

- Fresh full repo scan FIRST from disk.
- Implement ONLY 6G on top of the current active precondition state.
- ASCII-only. ZERO HARDCODE.
- Reuse existing repo keys/templates only. Do NOT create new keyname unless fresh
- Do NOT touch Start.cmd / OneBot/Kernel.js / OneBot/Connector.js / any \*Hub.js.
- Output FULL RAW FILE BODY only. No diff/patch. No summary/testing/commit text.

#### FILES (MAX 2)

- 1) <active Fallback implFile from repo pointers>
- 2) <active Fallback implConfig from repo pointers> (ONLY if changed)

#### MUST

- 1) Follow active runtime pointers from disk:
  - OneData/bots/ONEBOT/config/modules/Core/Fallback.conf
  - -> OneData/bots/ONEBOT/config/modules/Core/FallbackHub.conf
  - -> active implFile
  - -> active implConfig

- 2) Re-scan active ticket flow and prove these fields exist in current active on-d

- lastInboundAt
- lastStaffReplyAt
- awaitingStaff

If not provable from current active files, output:

#### REPORT

BLOCKED: ACTIVE PRECONDITION FIELDS NOT PROVEN

EVIDENCE: <exact paths scanned>

STOP.

## 3) Reminder selection rules:

- DM-origin tickets only
- OPEN tickets only
- UNREPLIED tickets only
- Use existing stored fields only:
  - awaitingStaff must be 1
  - and if both timestamps exist, lastInboundAt must be greater than lastStaffRep
- Do NOT select tickets by updatedAt/createdAt alone.

## 4) Reminder path:

- Use existing ticketCard/template/render system only
- Send into resolved workgroup/control group using existing send pipeline only
- Scheduled sends must use:
  - isAuto=1
  - manualReply=0
- Dedupe same ticket within same cycle
- Respect existing reusable batch/interval/attempt controls proven by fresh scan

## 5) Escalation path:

- Must be a REAL separate path from reminder
- Trigger using existing reusable threshold/attempt keys proven by fresh scan
- Use existing reusable template system proven by fresh scan
- Send into resolved workgroup/control group using existing send pipeline only
- No spam

## 6) Config rules:

- Only append EXISTING canonical keys already proven by fresh scan
- No aliases
- No new keynames unless proven missing
- If any required concept cannot map safely to an existing key/template, output:

REPORT

NEED NEW KEYNAME: <key>

PURPOSE: <1 line>

EVIDENCE: <exact paths scanned and why existing keys cannot fit>

STOP.

OUTPUT FORMAT (STRICT)

CHANGED FILES

Path: <active FallbackCV.js path>

</> Plain text



(Only if changed)

Path: <active FallbackCV.conf path>

</> conf



STOP.



Sources



Compare with Claude ▾

**codex.txt**  
Document

Thought for 24s >

**Boleh copy (file ini sahaja): TIDAK.**  codex

**Create Time: 9:56AM**

Precondition 6G belum ada dalam active flow, jadi kena betulkan dulu baru sambung 6G.

 codex

TASK: BUILD 6G PRECONDITION IN ACTIVE FLOW (PERSIST lastInboundAt / lastStaffRepl

SCOPE

- Fix ONLY the active Fallback flow so 6G precondition fields are truly present i
- Fresh full repo scan FIRST from disk.
- ASCII-only. ZERO HARDCODE.
- Do NOT touch Start.cmd / OneBot/Kernel.js / OneBot/Connector.js / any \*Hub.js.
- Output FULL RAW FILE BODY only. No diff/patch. No summary/testing/commit text.

FILES (MAX 4)

- 1) <active Fallback implFile from repo pointers>
- 2) OneBot/modules/Core/Fallback/FallbackReplyTextCV.js
- 3) OneBot/modules/Core/Fallback/FallbackReplyMediaCV.js
- 4) OneBot/modules/Core/Fallback/FallbackReplyAVCV.js

MUST

- 1) Follow active runtime pointers from disk:
  - OneData/bots/ONEBOT/config/modules/Core/Fallback.conf
  - -> OneData/bots/ONEBOT/config/modules/Core/FallbackHub.conf
  - -> active Fallback implFile
  - -> active Fallback implConfig

2) In active Fallback implFile:

- On inbound customer DM ticket create/update, persist:



- lastInboundAt = current inbound timestamp
- awaitingStaff = 1
- Keep existing ticket/status/workgroup flow unchanged otherwise.
- Do NOT add any 6G reminder/escalation loop in this task.

3) In ALL 3 reply handlers (text/media/av):

- After successful send to customer, update SAME ticket record:
  - lastStaffReplyAt = success timestamp
  - awaitingStaff = 0
- If send fails, do NOT write lastStaffReplyAt / awaitingStaff=0
- Keep existing send behavior unchanged otherwise.

4) Storage rules:

- Reuse active ticket store pattern already used by repo.
- Reuse existing ticketId lookup/storeSpec/storeKey patterns only.
- Fail-soft only: bugLog on store update error, no crash.
- Do NOT invent new config keys in this task.

5) Output ONLY changed files from current active runtime paths.

OUTPUT FORMAT (STRICT)

CHANGED FILES

Path: <active FallbackCV.js path>

```js

</> Plain text



Path: OneBot/modules/Core/Fallback/FallbackReplyTextCV.js

</> JavaScript



Path: OneBot/modules/Core/Fallback/FallbackReplyMediaCV.js

</> JavaScript



Path: OneBot/modules/Core/Fallback/FallbackReplyAVCV.js

</> JavaScript



STOP.



Sources






 Compare with Claude ▾

 codex.txt
 Document

Thought for 40s >

Boleh copy (4 file ini sahaja): TIDAK.  codex**Create Time: 10:38AM**

FallbackCV.js masih bawa loop 6G lama (runReminderCycle + reminderTimer) dan selection masih guna OPEN DM + updatedAt/createdAt , jadi belum selamat untuk live.

 codex

TASK: CLEAN PRECONDITION ONLY - REMOVE INCOMPLETE 6G LOOP FROM ACTIVE FallbackCV.

SCOPE

- Fix ONLY the active FallbackCV.js from current on-disk repo state.
- Fresh repo scan FIRST from disk.
- Keep the persisted precondition fields already added for 6G unblock:
 - lastInboundAt
 - lastStaffReplyAt
 - awaitingStaff
- REMOVE the incomplete 6G reminder engine from FallbackCV.js for now.
- ASCII-only. ZERO HARDCODE.
- Output FULL RAW FILE BODY only. No diff/patch. No summary/testing/commit text.

FILES (EXACTLY 1)

1) <active Fallback implFile from repo pointers>

MUST

- 1) Follow active runtime pointers from disk:
 - OneData/bots/ONEBOT/config/modules/Core/Fallback.conf
 - -> OneData/bots/ONEBOT/config/modules/Core/FallbackHub.conf
 - -> active Fallback implFile
- 2) In active FallbackCV.js:
 - KEEP:
 - current reply wiring (ReplyText / ReplyMedia / ReplyAV)
 - current inbound ticket create/update flow

- persistence of lastInboundAt and awaitingStaff on inbound DM
- existing ticket store pattern and service usage
- REMOVE:
 - reminderState Map
 - runReminderCycle()
 - reminderTimer / setInterval()
 - any tickMs/batchMax/maxAttempts/retryDelayMs logic used only for 6G loop
 - any shutdown cleanup that only exists for reminderTimer

3) Do NOT change the 3 reply handler files in this task.

4) Do NOT edit conf in this task.

5) Goal: active FallbackCV.js must become PRECONDITION-ONLY, not partial 6G.

OUTPUT FORMAT (STRICT)

CHANGED FILES

<> Plain text



STOP.



Sources



Compare with Claude ▾

codex.txt

Document

kenapa script ni je dok ulang2 dari 2-3 sesi dok ulang

Aku dah semak file ni fokus pada satu benda saja: adakah ia sudah jadi "precondition only" tanpa loop 6G lama. Nampaknya ya — loop reminder/escalation memang dah tiada dalam file ini.

Thought for 1m 54s >

Boleh copy (file ini sahaja): YA.

Create Time: 10:49AM

keyname.conf.txt update: **tak perlu**. File ini dah clean untuk task semasa sebab loop 6G lama (runReminderCycle / reminderTimer) memang sudah tiada.  codex

TASK: 6G IMPLEMENT (ANTI-MISS REMINDER + ESCALATION) - ACTIVE FALLBACK PAIR ONLY

SCOPE

- Fresh full repo scan FIRST from disk.
- Implement ONLY 6G on top of the current active precondition state.
- ASCII-only. ZERO HARDCODE.
- Reuse existing repo keys/templates only. Do NOT create new keyname unless fresh
- Do NOT touch Start.cmd / OneBot/Kernel.js / OneBot/Connector.js / any *Hub.js.
- Output FULL RAW FILE BODY only. No diff/patch. No summary/testing/commit text.

FILES (MAX 2)

- 1) <active Fallback implFile from repo pointers>
- 2) <active Fallback implConfig from repo pointers> (ONLY if changed)

MUST

- 1) Follow active runtime pointers from disk:

- OneData/bots/ONEBOT/config/modules/Core/Fallback.conf
- -> OneData/bots/ONEBOT/config/modules/Core/FallbackHub.conf
- -> active implFile
- -> active implConfig

- 2) Re-scan current active flow and prove these fields already exist in runtime fi

- lastInboundAt
- lastStaffReplyAt
- awaitingStaff

If not provable from current active files, output:

REPORT

BLOCKED: ACTIVE PRECONDITION FIELDS NOT PROVEN

EVIDENCE: <exact paths scanned>

STOP.

- 3) Reminder selection rules:

- DM-origin tickets only
- OPEN tickets only
- UNREPLIED tickets only
- Use existing stored fields only:
 - awaitingStaff must be 1
 - and if both timestamps exist, lastInboundAt must be greater than lastStaffRep
- Do NOT select tickets by updatedAt/createdAt alone.

- 4) Reminder path:

- Use existing ticketCard/template/render system only
- Send into resolved workgroup/control group using existing send pipeline only
- Scheduled sends must use:
 - isAuto=1
 - manualReply=0
- Dedupe same ticket within same cycle
- Respect existing reusable batch/interval/attempt controls proven by fresh scan

5) Escalation path:

- Must be a REAL separate path from reminder
- Trigger using existing reusable threshold/attempt keys proven by fresh scan
- Use existing reusable template system proven by fresh scan
- Send into resolved workgroup/control group using existing send pipeline only
- No spam

6) Config rules:

- Only append EXISTING canonical keys already proven by fresh scan
- No aliases
- No new keynames unless proven missing
- If any required concept cannot map safely to an existing key/template, output:
REPORT
NEED NEW KEYNAME: <key>
PURPOSE: <1 line>
EVIDENCE: <exact paths scanned and why existing keys cannot fit>
STOP.

OUTPUT FORMAT (STRICT)

CHANGED FILES

Path: <active FallbackCV.js path>

</> Plain text



(Only if changed)

Path: <active FallbackCV.conf path>

</> conf



STOP.



Sources



Compare with Claude ▾

codex.txt
Document

Thought for 20s >

Boleh copy (file ini sahaja): TIDAK.  codex

Create Time: 2:16PM

Blocked: lastStaffReplyAt masih belum terbukti ditulis dalam active reply handlers.

 codex

TASK: BUILD MISSING 6G PRECONDITION - PERSIST lastStaffReplyAt IN ACTIVE REPLY HA

SCOPE

- Fresh full repo scan FIRST from disk.
- Fix ONLY the missing precondition proof for 6G:
 - persist lastStaffReplyAt after successful staff reply
 - persist awaitingStaff=0 after successful staff reply
- ASCII-only. ZERO HARDCODE.
- Do NOT touch Start.cmd / OneBot/Kernel.js / OneBot/Connector.js / any *Hub.js.
- Do NOT add any 6G reminder/escalation loop in this task.
- Output FULL RAW FILE BODY only. No diff/patch. No summary/testing/commit text.

FILES (MAX 3)

- 1) OneBot/modules/Core/Fallback/FallbackReplyTextCV.js
- 2) OneBot/modules/Core/Fallback/FallbackReplyMediaCV.js
- 3) OneBot/modules/Core/Fallback/FallbackReplyAVCV.js

MUST

- 1) Follow active runtime pointers from disk:
 - OneData/bots/ONEBOT/config/modules/Core/Fallback.conf
 - -> OneData/bots/ONEBOT/config/modules/Core/FallbackHub.conf
 - -> active Fallback implFile
 - confirm the SAME active ticket store pattern used by runtime flow
- 2) In ALL 3 active reply handlers (text/media/av):
 - After successful send to customer, update the SAME ticket record:
 - lastStaffReplyAt = successful send timestamp
 - awaitingStaff = 0
 - If send fails, do NOT write lastStaffReplyAt / awaitingStaff=0
 - Reuse existing ticketId lookup / storeSpec / storeKey / store service patterns
 - Fail-soft only: bugLog on store update error, no crash
- 3) Keep existing behavior unchanged otherwise:
 - manualReply behavior stays as current active code
 - existing send pipeline stays as current active code
 - no new config keys
 - no unrelated file changes

4) If any of the 3 files is NOT actually active in the current runtime path, outp
REPORT

BLOCKED: ACTIVE REPLY HANDLER PATH NOT PROVEN

EVIDENCE: <exact paths scanned>

STOP.

OUTPUT FORMAT (STRICT)

CHANGED FILES

Path: OneBot/modules/Core/Fallback/FallbackReplyTextCV.js

```js

</> Plain text



Path: OneBot/modules/Core/Fallback/FallbackReplyMediaCV.js

</> JavaScript



Path: OneBot/modules/Core/Fallback/FallbackReplyAVCV.js

</> JavaScript



STOP.



Sources



Compare with Claude ▾

**codex.txt**

Document

Thought for 42s >

**Boleh copy (3 file ini sahaja): YA.**  codex

**Create Time: 2:29PM**

keyname.conf.txt update: **tak perlu.**  codex

TASK: 6G IMPLEMENT (ANTI-MISS REMINDER + ESCALATION) - ACTIVE FALLBACK PAIR ONLY

SCOPE

- Fresh full repo scan FIRST from disk.
- Implement ONLY 6G on top of the current active precondition state.
- ASCII-only. ZERO HARDCODE.
- Reuse existing repo keys/templates only. Do NOT create new keyname unless fresh
- Do NOT touch Start.cmd / OneBot/Kernel.js / OneBot/Connector.js / any \*Hub.js.
- Output FULL RAW FILE BODY only. No diff/patch. No summary/testing/commit text.

#### FILES (MAX 2)

- 1) <active Fallback implFile from repo pointers>
- 2) <active Fallback implConfig from repo pointers> (ONLY if changed)

#### MUST

- 1) Follow active runtime pointers from disk:
  - OneData/bots/ONEBOT/config/modules/Core/Fallback.conf
  - -> OneData/bots/ONEBOT/config/modules/Core/FallbackHub.conf
  - -> active implFile
  - -> active implConfig
- 2) Re-scan current active flow and prove these fields already exist in runtime fi
  - lastInboundAt
  - lastStaffReplyAt
  - awaitingStaff

If not provable from current active files, output:

#### REPORT

BLOCKED: ACTIVE PRECONDITION FIELDS NOT PROVEN

EVIDENCE: <exact paths scanned>

STOP.

#### 3) Reminder selection rules:

- DM-origin tickets only
- OPEN tickets only
- UNREPLIED tickets only
- Use existing stored fields only:
  - awaitingStaff must be 1
  - and if both timestamps exist, lastInboundAt must be greater than lastStaffRep
- Do NOT select tickets by updatedAt/createdAt alone.

#### 4) Reminder path:

- Use existing ticketCard/template/render system only
- Send into resolved workgroup/control group using existing send pipeline only
- Scheduled sends must use:
  - isAuto=1
  - manualReply=0
- Dedupe same ticket within same cycle
- Respect existing reusable batch/interval/attempt controls proven by fresh scan

#### 5) Escalation path:

- Must be a REAL separate path from reminder
- Trigger using existing reusable threshold/attempt keys proven by fresh scan
- Use existing reusable template system proven by fresh scan
- Send into resolved workgroup/control group using existing send pipeline only
- No spam



## 6) Config rules:

- Only append EXISTING canonical keys already proven by fresh scan
- No aliases
- No new keynames unless proven missing
- If any required concept cannot map safely to an existing key/template, output:  
REPORT  
NEED NEW KEYNAME: <key>  
PURPOSE: <1 line>  
EVIDENCE: <exact paths scanned and why existing keys cannot fit>  
STOP.

OUTPUT FORMAT (STRICT)

CHANGED FILES

Path: &lt;active FallbackCV.js path&gt;

&lt;/&gt; Plain text



(Only if changed)

Path: &lt;active FallbackCV.conf path&gt;

&lt;/&gt; conf



STOP.



Sources



Compare with Claude ▾

codex.txt

Document

Thought for 35s &gt;

Boleh copy (file ini sahaja): TIDAK.  codex

Create Time: 2:40PM

keyname.conf.txt update: tak perlu. Blocked sebab active flow masih belum simpan

lastInboundAt , awaitingStaff , dan lastStaffReplyAt .  codex

TASK: BUILD MISSING 6G PRECONDITION IN ACTIVE FLOW (SYNC ACTIVE RUNTIME FILES ONL

#### SCOPE

- Fresh full repo scan FIRST from disk.
- Fix ONLY the missing active precondition fields for 6G:
  - inbound flow must persist lastInboundAt
  - inbound flow must persist awaitingStaff=1
  - reply handlers must persist lastStaffReplyAt
  - reply handlers must persist awaitingStaff=0 after successful reply
- ASCII-only. ZERO HARDCODE.
- Do NOT touch Start.cmd / OneBot/Kernel.js / OneBot/Connector.js / any \*Hub.js.
- Do NOT add any 6G reminder/escalation loop in this task.
- Output FULL RAW FILE BODY only. No diff/patch. No summary/testing/commit text.

#### FILES (MAX 4)

- 1) <active Fallback implFile from repo pointers>
- 2) OneBot/modules/Core/Fallback/FallbackReplyTextCV.js
- 3) OneBot/modules/Core/Fallback/FallbackReplyMediaCV.js
- 4) OneBot/modules/Core/Fallback/FallbackReplyAVCV.js

#### MUST

- 1) Follow active runtime pointers from disk:
  - OneData/bots/ONEBOT/config/modules/Core/Fallback.conf
  - -> OneData/bots/ONEBOT/config/modules/Core/FallbackHub.conf
  - -> active Fallback implFile
  - -> active Fallback implConfig
- 2) In active FallbackCV.js:
  - On inbound customer DM ticket create/update, persist:
    - lastInboundAt = inbound timestamp
    - awaitingStaff = 1
  - Keep existing ticket/status/workgroup flow unchanged otherwise.
  - Do NOT add any reminder/escalation timer or loop in this task.
- 3) In ALL 3 active reply handlers (text/media/av):
  - After successful send to customer, update the SAME ticket record:
    - lastStaffReplyAt = successful send timestamp
    - awaitingStaff = 0
  - If send fails, do NOT write lastStaffReplyAt / awaitingStaff=0
  - Reuse existing active ticket store pattern only (same ticketId/storeSpec/storeK
  - Fail-soft only: bugLog on store update error, no crash
- 4) Active-path proof rule:
  - If any of the above files is not actually part of the active runtime flow from REPORT

BLOCKED: ACTIVE PATH NOT PROVEN

EVIDENCE: <exact paths scanned>

STOP.

OUTPUT FORMAT (STRICT)  
CHANGED FILES  
Path: <active FallbackCV.js path>

</> Plain text



Path: OneBot/modules/Core/Fallback/FallbackReplyTextCV.js

</> JavaScript



Path: OneBot/modules/Core/Fallback/FallbackReplyMediaCV.js

</> JavaScript



Path: OneBot/modules/Core/Fallback/FallbackReplyAVCV.js

</> JavaScript



STOP.



Sources

... Compare with Claude ▾

codex.txt  
Document

Aku semak terus pada ringkasan Codex ni. Red flag utama dah jelas: dia sentuh 14 fail walaupun task sepatutnya fokus sempit pada active Fallback flow, jadi ini belum selamat untuk copy live.

Thought for 1m 9s >

**Boleh copy (file ini sahaja): TIDAK.**  codex

**Create Time: 2:47PM**

Langgar scope sebab Codex bagi **summary + sentuh 14 fail**, bukan **FULL RAW FILE BODY** untuk fail active sahaja.  codex

**TASK: CLEAN RE-OUTPUT (COPY/PASTE READY) - ACTIVE FallbackCV.js ONLY**

#### SCOPE

- NO NEW LOGIC CHANGES.
- Fresh full repo scan FIRST from disk, then OUTPUT ONLY the current active Fallb
- ASCII-only. No diff/patch. No summary/testing/commit/PR text.
- Do NOT output any unrelated files.
- Do NOT output keyname.conf.txt in this task.

#### MUST

1) Follow active runtime pointers from disk:

- OneData/bots/ONEBOT/config/modules/Core/Fallback.conf
- -> OneData/bots/ONEBOT/config/modules/Core/FallbackHub.conf
- -> active implFile

2) Read the CURRENT on-disk active file only:

- <active Fallback implFile>

3) Output EXACTLY this 1 file only:

- active FallbackCV.js

4) Do NOT modify any other file and do NOT include any other file in output.

- Ignore unrelated branch changes.
- No keyname updates in this task.

5) Clean output rules:

- JS code block = raw file body only

#### OUTPUT FORMAT (STRICT)

##### CHANGED FILES

Path: <active FallbackCV.js path>

```
```js
```

<> Plain text



STOP.



Sources



Compare with Claude ▾

codex.txt

Document

ni macam dah berulang script sama je, tadi fallbackcv.js ni dah copy ada masalah ke script ni? kalau takde masalah kenapa nak copy?

Thought for 40s >

Boleh copy (file ini sahaja): YA.  codex**Create Time: 3:51PM****Ini re-output sahaja.** Kalau live server dah ada isi yang sama exact, tak perlu copy semula.**TASK: 6G IMPLEMENT (ANTI-MISS REMINDER + ESCALATION) - ACTIVE FALLBACK PAIR ONLY****SCOPE**

- Fresh full repo scan FIRST from disk.
- Implement ONLY 6G on top of the current active precondition state.
- ASCII-only. ZERO HARDCODE.
- Reuse existing repo keys/templates only. Do NOT create new keyname unless fresh
- Do NOT touch Start.cmd / OneBot/Kernel.js / OneBot/Connector.js / any *Hub.js.
- Output FULL RAW FILE BODY only. No diff/patch. No summary/testing/commit text.

FILES (MAX 2)

- 1) <active Fallback implFile from repo pointers>
- 2) <active Fallback implConfig from repo pointers> (ONLY if changed)

MUST

- 1) Follow active runtime pointers from disk:

- OneData/bots/ONEBOT/config/modules/Core/Fallback.conf
- -> OneData/bots/ONEBOT/config/modules/Core/FallbackHub.conf
- -> active implFile
- -> active implConfig

- 2) Re-scan current active flow and prove these fields already exist in runtime fi

- lastInboundAt
- lastStaffReplyAt
- awaitingStaff

If not provable from current active files, output:

REPORT**BLOCKED: ACTIVE PRECONDITION FIELDS NOT PROVEN**

EVIDENCE: <exact paths scanned>
STOP.

3) Reminder selection rules:

- DM-origin tickets only
- OPEN tickets only
- UNREPLIED tickets only
- Use existing stored fields only:
 - awaitingStaff must be 1
 - and if both timestamps exist, lastInboundAt must be greater than lastStaffRep
- Do NOT select tickets by updatedAt/createdAt alone.

4) Reminder path:

- Use existing ticketCard/template/render system only
- Send into resolved workgroup/control group using existing send pipeline only
- Scheduled sends must use:
 - isAuto=1
 - manualReply=0
- Dedupe same ticket within same cycle
- Respect existing reusable batch/interval/attempt controls proven by fresh scan

5) Escalation path:

- Must be a REAL separate path from reminder
- Trigger using existing reusable threshold/attempt keys proven by fresh scan
- Use existing reusable template system proven by fresh scan
- Send into resolved workgroup/control group using existing send pipeline only
- No spam

6) Config rules:

- Only append EXISTING canonical keys already proven by fresh scan
- No aliases
- No new keynames unless proven missing
- If any required concept cannot map safely to an existing key/template, output:
REPORT

NEED NEW KEYNAME: <key>

PURPOSE: <1 line>

EVIDENCE: <exact paths scanned and why existing keys cannot fit>

STOP.

OUTPUT FORMAT (STRICT)

CHANGED FILES

Path: <active FallbackCV.js path>

```js

<> Plain text



(Only if changed)

Path: <active FallbackCV.conf path>

<> conf



STOP.

Sources

    ... Compare with Claude ▾

codex.txt  
Document

Thought for 35s >

**Boleh copy (file ini sahaja): TIDAK.**

**Create Time: 11:32PM**

Blocked: lastStaffReplyAt masih belum terbukti dalam active flow.  codex

TASK: BUILD MISSING 6G PRECONDITION - PERSIST lastStaffReplyAt IN ACTIVE REPLY HA

#### SCOPE

- Fresh full repo scan FIRST from disk.
- Fix ONLY the missing precondition proof for 6G:
  - persist lastStaffReplyAt after successful staff reply
  - persist awaitingStaff=0 after successful staff reply
- ASCII-only. ZERO HARDCODE.
- Do NOT touch Start.cmd / OneBot/Kernel.js / OneBot/Connector.js / any \*Hub.js.
- Do NOT add any 6G reminder/escalation loop in this task.
- Output FULL RAW FILE BODY only. No diff/patch. No summary/testing/commit text.

#### FILES (MAX 3)

- 1) OneBot/modules/Core/Fallback/FallbackReplyTextCV.js
- 2) OneBot/modules/Core/Fallback/FallbackReplyMediaCV.js
- 3) OneBot/modules/Core/Fallback/FallbackReplyAVCV.js

#### MUST

- 1) Follow active runtime pointers from disk:
  - OneData/bots/ONEBOT/config/modules/Core/Fallback.conf
  - -> OneData/bots/ONEBOT/config/modules/Core/FallbackHub.conf
  - -> active Fallback implFile
  - confirm the SAME active ticket store pattern used by runtime flow

```
2) In ALL 3 active reply handlers (text/media/av):
- After successful send to customer, update the SAME ticket record:
 - lastStaffReplyAt = successful send timestamp
 - awaitingStaff = 0
- If send fails, do NOT write lastStaffReplyAt / awaitingStaff=0
- Reuse existing ticketId lookup / storeSpec / storeKey / store service patterns
- Fail-soft only: bugLog on store update error, no crash

3) Keep existing behavior unchanged otherwise:
- manualReply behavior stays as current active code
- existing send pipeline stays as current active code
- no new config keys
- no unrelated file changes

4) If any of the 3 files is NOT actually active in the current runtime path, output
REPORT
BLOCKED: ACTIVE REPLY HANDLER PATH NOT PROVEN
EVIDENCE: <exact paths scanned>
STOP.

OUTPUT FORMAT (STRICT)
CHANGED FILES
Path: OneBot/modules/Core/Fallback/FallbackReplyTextCV.js
....

</> Plain text
```

Path: OneBot/modules/Core/Fallback/FallbackReplyMediaCV.js

</> JavaScript

Path: OneBot/modules/Core/Fallback/FallbackReplyAVCV.js

</> JavaScript

STOP.

Sources



codex.txt  
Document

Aku dah semak tiga handler ni. Logic `lastStaffReplyAt + awaitingStaff=0` selepas send berjaya nampak masuk, tapi output Codex tetap tak clean sebab dia sentuh 19 fail sekali jalan — jadi aku akan bagi prompt re-output sempit supaya tak bercampur dengan perubahan lain.

Thought for 1m 50s >

**Boleh copy (3 file ini sahaja): TIDAK.**

**Create Time: 11:37PM**

Langgar scope: task ini sepatutnya 3 reply handlers sahaja, tapi Codex sentuh 19 fail termasuk `FallbackCV.js`, `FallbackCV.conf`, dan `keyname.conf.txt`. `keyname.conf.txt` update: **tak perlu.**  codex

TASK: CLEAN RE-OUTPUT (COPY/PASTE READY) - ACTIVE REPLY HANDLERS ONLY

SCOPE

- NO NEW LOGIC CHANGES.
- Fresh full repo scan FIRST from disk, then OUTPUT ONLY the current active reply
- ASCII-only. No diff/patch. No summary/testing/commit/PR text.
- Do NOT output any unrelated files.
- Do NOT output `keyname.conf.txt` in this task.

MUST

1) Follow active runtime pointers from disk:

- `OneData/bots/ONEBOT/config/modules/Core/Fallback.conf`
- -> `OneData/bots/ONEBOT/config/modules/Core/FallbackHub.conf`
- confirm active Fallback flow uses these exact handler paths:
  - `OneBot/modules/Core/Fallback/FallbackReplyTextCV.js`
  - `OneBot/modules/Core/Fallback/FallbackReplyMediaCV.js`
  - `OneBot/modules/Core/Fallback/FallbackReplyAVCV.js`
- If any handler path is not active, output:

REPORT

BLOCKED: ACTIVE REPLY HANDLER PATH NOT PROVEN

EVIDENCE: <exact paths scanned>

STOP.

2) Read the CURRENT on-disk files only:

- `OneBot/modules/Core/Fallback/FallbackReplyTextCV.js`
- `OneBot/modules/Core/Fallback/FallbackReplyMediaCV.js`

- OneBot/modules/Core/Fallback/FallbackReplyAVCV.js

3) Output EXACTLY these 3 files only.

- Ignore unrelated branch changes.
- No keyname updates.
- No other file list.

4) Clean output rules:

- JS code block = raw file body only
- No extra separators inside file body

OUTPUT FORMAT (STRICT)

CHANGED FILES

Path: OneBot/modules/Core/Fallback/FallbackReplyTextCV.js

````

</> Plain text



Path: OneBot/modules/Core/Fallback/FallbackReplyMediaCV.js

</> JavaScript



Path: OneBot/modules/Core/Fallback/FallbackReplyAVCV.js

</> JavaScript



STOP.



Sources



Compare with Claude ▾

codex.txt

Document

ok aku rasa kau dah lagging ni, aku kena sambung dekat sesi lain, tolong buat hand over tracker cara kerja dan sambung dekat mana, tapi sebelum tu wajib remind AI sesi lain supaya minta codex scan dulu, supaya dia tahu apa isi kandungan repo dan live server, sebab repo tu merupakan isi kandungan live server juga, di repo tak ada node sebab file besar tak boleh upload jadi kena test ikut cara codex, full, dan setiap kali prompt codex juga wajib buat full scan sebelum mula keluarkan report, atau fix, fix wajib ikut cara kita kerja sekarang...

Thought for 41s >

Baik Pa' Din — ini **handover tracker** untuk sambung sesi lain. Aku tulis macam "cara kerja + status + next step", dan aku letak juga "reminder wajib" untuk AI sesi baru.

0) Reminder wajib untuk AI sesi lain (jangan skip)

1. **WAJIB** minta Codex buat FULL REPO SCAN dulu sebelum apa-apa report/fix.
 - Sebab repo = live server (file yang live guna sama macam dalam repo).
 - Dalam repo tak ada node_modules (file besar tak boleh upload), jadi testing/validation ikut cara Codex (scan + baca file dari disk + log/contract evidence).
2. Satu prompt sahaja setiap kali jalan (1 task = 1 prompt).
3. Output mesti FULL file body (bukan diff/summary).
4. Batch kecil (ikut apa kita buat sekarang: 1–5 file max, biasanya 1–2 file).
5. ASCII-only + zero hardcode + canonical keynames only.
6. Jangan create keyname baru kalau belum betul-betul scan keyname.conf.txt + cari fungsi sama dalam conf/code sedia ada. Kalau tiada barulah "suggest" key baru dengan tujuan jelas.

1) Format jawapan (rule tetap)

Selepas user paste codex.txt, AI **wajib** reply format macam ni:

Boleh copy (file ini sahaja): YA/TIDAK.

Create Time: HH:MMAM/PM (ikut codex.txt)

(Optional: 1–2 baris ringkas kalau perlu)

Lepas tu baru bagi **SATU prompt TASK**.

Nota: Jangan letak "**ARAHAN KERAS: DI LARANG MENEKA**" dalam header/prompt kecuali kalau task itu jenis **REPO SCAN REPORT**.

2) Cara kerja kitaran (workflow) yang kita guna

1. User paste `codex.txt`

≡ 📁 > ChatGPT 5.2 Thinking ▾

🔗 ⬆️ ⋮

- full raw file body ada/tidak,
- canonical keynames,
- tiada hardcode,
- file "clean" (conf hanya `# /blank/ key=value`)

3. AI keluarkan **SATU prompt**:

- Kalau Codex bagi summary/diff → prompt "**CLEAN RE-OUTPUT (OUTPUT ONLY)**"
- Kalau scope lari (sentuh 14/19 fail) → prompt sempit "**ACTIVE FILE ONLY**"
- Kalau logic salah/contract regression → prompt fix **pair only**

4. Ulang sampai "**Boleh copy: YA**" untuk fail yang memang nak deploy.

3) Status kerja setakat sesi ini (ringkas)

Yang dah stabil / berjaya ikut gaya kerja

- Kita dah berjaya "lock" beberapa module dengan output **boleh copy** dalam batch kecil (contoh OutboundGateway, Outbox, SendQueue, Inbound*, MessageJournal, Command, AccessRoles) — tapi **masa hujung sesi fokus banyak pada Fallback/6G**, jadi sambungan utama sekarang ialah **6G (Anti-miss)**.

Punca utama kenapa "ulang file sama" berlaku

Masalahnya bukan file tu semata-mata, tapi Codex selalu langgar scope:

- Task minta 1–4 fail → Codex sentuh 14–19 fail, campur `keyname.conf.txt` , campur benda lain.
- Ada masa Codex buat **partial 6G loop** awal (reminder timer) sebelum precondition betul-betul proven → kita terpaksa "**undo/clean**" balik jadi **precondition only**.

- Jadi nampak macam ulang file sama, tapi sebenarnya kita **repair scope + clean output** supaya boleh deploy tanpa risiko.
-

4) “Tempat sambung” sebenar sekarang

Objektif besar yang belum siap

✅ **6G precondition** mesti wujud & proven dalam active runtime flow:

- `lastInboundAt` (masa inbound DM masuk)
- `awaitingStaff=1` (lepas inbound)
- `lastStaffReplyAt` + `awaitingStaff=0` (lepas staff reply berjaya)

➡ Lepas itu barulah:

✅ **6G implement** (reminder + escalation)

- Reminder: hanya ticket **DM + OPEN + unreplied** (bukan semua OPEN DM).
- Escalation: laluan berbeza (bukan sekadar stop selepas `maxAttempts`).
- **Reuse keys/templates yang memang wujud** (tiada key baru tanpa proof).

Apa yang selalu jadi blocker

- Precondition fields **tak betul-betul ditulis** dalam tempat yang active (atau Codex tak prove handler aktif).
 - Codex campur banyak fail → output tak deployable.
-

5) Next steps (urutan paling selamat untuk sesi baru)

Ini cadangan urutan supaya tak ulang “repair file sama”:

Step A — FULL REPO SCAN REPORT (mandatory)

Minta Codex:

- confirm active pointers `Fallback.conf` -> `FallbackHub.conf` -> `implFile/implConfig`
- confirm handler paths yang active (`ReplyText/ReplyMedia/ReplyAV`)
- confirm ticket store pattern yang active

Step B — PROVE precondition fields (report dahulu kalau perlu)

Minta Codex tunjuk evidence di active files:

- di inbound flow: `lastInboundAt` , `awaitingStaff=1`
- di reply handlers: `lastStaffReplyAt` , `awaitingStaff=0` selepas send berjaya

Kalau missing:

- buat fix **reply handlers only** (max 3 files) atau **FallbackCV.js only** (1 file) — **jangan campur fail lain.**

Step C — Bila precondition proven barulah implement 6G

- Implement 6G dalam **active Fallback pair sahaja** (max 2 files).
- Reuse keys/templates sedia ada.
- Pastikan selection = **awaitingStaff=1** dan `lastInboundAt > lastStaffReplyAt` (kalau ada).
- Pastikan tiada spam (dedupe per cycle, batchMax, retryDelay, maxAttempts reuse).

6) Prompt starter untuk AI sesi lain (untuk mula semula dengan betul)

AI sesi lain boleh guna prompt pertama ini (ingat: ini jenis scan, jadi boleh letak "ARAHAN KERAS..."):

TASK: REPO SCAN REPORT - ACTIVE FALLBACK POINTERS + 6G PRECONDITION PROOF

- report only, no changes
- output: active pointer chain + list handler paths + show where fields exist (file+line)

Lepas Codex reply, baru proceed.

Kalau kau nak, bila kau buka sesi baru nanti, kau terus paste **codex.txt scan report pertama** — aku akan terus tulis **prompt next** ikut format header yang kau tetapkan (1 prompt sahaja, scope kecil).

    ... Compare with Claude ▾