

T2_programs_vha

December 1, 2024

1 1. Python program to convert integer to roman

```
[40]: num=int(input("enter number:"))
symbols = [
    (1000, 'M'),
    (900, 'CM'),
    (500, 'D'),
    (400, 'CD'),
    (100, 'C'),
    (90, 'XC'),
    (50, 'L'),
    (40, 'XL'),
    (10, 'X'),
    (9, 'IX'),
    (5, 'V'),
    (4, 'IV'),
    (1, 'I')
]

roman = ''
for value, symbol in symbols:
    while num >= value:
        roman += symbol
        num -= value

print(roman)
```

enter number:525
DXXV

2 2. Write Python Program to Convert Roman to Integer

```
[9]: roman_num = input("enter roman ")

roman_dict = {'I': 1, 'V': 5, 'X': 10, 'L': 50, 'C': 100, 'D': 500, 'M': 1000}
result = 0
prev = 0
```

```

for curr in roman_num[::-1]:
    curr_val = roman_dict[curr]

    if curr_val < prev:
        result -= curr_val
    else:
        result += curr_val

    prev = curr_val

print(result)

```

enter roman CDXV
415

3 3. CANDY

There are n children standing in a line. Each child is assigned a rating value given in the integer array ratings.

You are giving candies to these children subjected to the following requirements:

Each child must have at least one candy.

Children with a higher rating get more candies than their neighbors.

Return the minimum number of candies you need to have to distribute the candies to the children.

Example 1:

Input: ratings = [1,0,2]

Output: 5

Explanation: You can allocate to the first, second and third child with 2, 1, 2 candies respectively.

Example 2:

Input: ratings = [1,2,2]

Output: 4

Explanation: You can allocate to the first, second and third child with 1, 2, 1 candies respectively. The third child gets 1 candy because it satisfies the above two conditions.

```

[11]: ratings=eval(input("ENTER LIST "))
n=len(ratings)
dp=[1]*n
for i in range(1,n):
    if ratings[i]>ratings[i-1]:
        dp[i]=dp[i-1]+1

```

```

for i in range(n-2,-1,-1):
    if ratings[i]>ratings[i+1]:
        dp[i]=max(dp[i],dp[i+1]+1)
print("candy distribution",dp)
print("total candy", sum(dp))

```

ENTER LIST [5,2,4,7,1,3,5,8,3,6]
candy distribution [2, 1, 2, 3, 1, 2, 3, 4, 1, 2]
total candy 21

4 What Is The Container With Most Water Problem?

Container With the Most Water is a coding problem that involves finding the largest possible area that can be formed by two vertical lines on a graph, bound by the height of the shorter line. This problem can be solved using a two-pointer approach, which involves traversing the array from both sides and keeping track of the maximum area found so far.

You are given an integer array height of length n. There are n vertical lines drawn such that the two endpoints of the ith line are (i, 0) and (i, height[i]).

Find two lines that together with the x-axis form a container, such that the container contains the most water.

Return the maximum amount of water a container can store.

Notice that you may not slant the container.

Input: height = [1,8,6,2,5,4,8,3,7]

Output: 49

Explanation: vertical lines are represented by array [1,8,6,2,5,4,8,3,7].

```

[12]: height=eval(input("enter of list "))
left = 0
right = len(height) - 1
Area = 0
while left < right:
    currentArea = min(height[left], height[right]) * (right - left)
    Area = max(Area, currentArea)
    if height[left] < height[right]:
        left += 1
    else:
        right -= 1

print(Area)

```

enter of list [1,8,6,2,5,4,8,3,7]
49

5 Trapping Rain Water

Given n non-negative integers representing an elevation map where the width of each bar is 1, compute how much water it can trap after raining.

height = [0,1,0,2,1,0,1,3,2,1,2,1]

Output: 6

Explanation: The above elevation map (black section) is represented by array [0,1,0,2,1,0,1,3,2,1,2,1]. In this case, 6 units of rain water (blue section) are being trapped.

```
[13]: height=[0,1,0,2,1,0,1,3,2,1,2,1]
      n = len(height)

      if n < 1:
          ans=0

      ans = 0
      left_max = [0] * n
      right_max = [0] * n

      left_max[0] = height[0]
      for i in range(1, n):
          left_max[i] = max(left_max[i-1], height[i])

      right_max[-1] = height[-1]
      for i in range(n-2, -1, -1):
          right_max[i] = max(right_max[i+1], height[i])

      for i in range(n):
          ans += min(left_max[i], right_max[i]) - height[i]
      print(ans)
```

6

6 Write a Python program to find the minimum window in a given string which will contain all the characters of another given string.

- Given two strings s and t of lengths m and n respectively, return the minimum window substring of s such that every character in t (including duplicates) is included in the window. If there is no such substring, return the empty string “”.

```
[16]: def minWindow(s,t):
      if t == "":
          return ""

      countT, window = {}, {}
```

```

    for c in t:
        countT[c] = 1 + countT.get(c, 0)

    have, need = 0, len(countT)

    res, resLen = [-1, -1], float("infinity")
    l = 0

    for r in range(len(s)):
        c = s[r]
        window[c] = 1 + window.get(c, 0)

        if c in countT and window[c] == countT[c]:
            have += 1

        while have == need:

            if (r - l + 1) < resLen:
                res = [l, r]
                resLen = (r - l + 1)

            window[s[l]] -= 1
            if window[s[l]] == 0 and s[l] in countT:
                have -= 1
            l += 1

    return "" if resLen == float("infinity") else s[res[0]:res[1]+1]

s="AA"
t="AAA"
print(minWindow(s,t))
s="AVCFBVBNGADFCBNA"
t="ABC"
print(minWindow(s,t))
s="AA"
t="A"
print(minWindow(s,t))

```

CBNA

A

7 Python Program To Find Longest Common Prefix Using Sorting

Problem Statement: Given a set of strings, find the longest common prefix. Example:

Input: ["apple", "ape", "april"]

Output: "ap"

```
[17]: def longestCommonPrefix( a):
    size=len(a)
    if size==0:
        return -1
    a.sort()
    end = min(len(a[0]), len(a[size - 1]))
    i = 0
    while (i < end and a[0][i] == a[size - 1][i]):
        i += 1
    pre = a[0][0: i]
    if pre:
        return pre
    else:
        return -1

print("The longest Common Prefix is :",longestCommonPrefix(["lessonplan",
↪"lesson","lees", "length"]))
```

The longest Common Prefix is : le

8 that element makes the list balanced. The list will be balanced if sum of even index elements is equal to the sum of odd elements. Also print the updated lists after removal of special elements.

Example 1:

Input:

L=[5, 5, 2, 5, 8]

Output:

Original List: [5, 5, 2, 5, 8]

Index to be removed is: 0

List after removing index 0 : [5, 2, 5, 8]

Original List: [5, 5, 2, 5, 8]

Index to be removed is: 1

List after removing index 1 : [5, 2, 5, 8]

Total number of special elements: 2

Explanation:

If we delete L[0] or L[1], list will be balanced.

[5, 2, 5, 8]

$$(5+5) = (2+8)$$

So $L[0]$ and $L[1]$ are special elements, So Count is 2.

After removal of the special elements, list will be: $[5, 2, 5, 8]$

Example 2:

Input:

$L=[2,1,6,4]$

Output:

Original List: $[2, 1, 6, 4]$

Index to be removed is: 1

List after removing index 1 : $[2, 6, 4]$

Total Number of Special elements: 1

Explanation:

If we delete $L[1]$ from list : $[2,6,4]$

$$(2+4) = (6)$$

Here only 1 special element. So Count is 1.

After removal of special element, list will be : $[2,6,4]$

```
[18]: l=eval(input("enter list"))
print("Original List:",l)
count=0
for i in range(0,len(l)):
    c=l.copy()
    c.pop(i)
    sum1=sum(c[0::2])
    sum2=sum(c[1::2])
    if sum1==sum2:
        print("index to be removed is: ",i)
        count+=1
        print("List after removing index ",i,"is ",l[0:i]+l[i+1:])
print("Total Number of Special elements:",count)
```

enter list $[1,2,6,4]$

Original List: $[1, 2, 6, 4]$

index to be removed is: 0

List after removing index 0 is $[2, 6, 4]$

Total Number of Special elements: 1

9 Python program to convert a given number into words

```
[50]: def convert_to_words(num):
    if num == 0:
        return "zero"
    ones = ["", "one", "two", "three", "four", "five", "six", "seven", "eight",
    ↪ "nine"]
    tens = ["", "", "twenty", "thirty", "forty", "fifty", "sixty", "seventy",
    ↪ "eighty", "ninety"]
    teens = ["ten", "eleven", "twelve", "thirteen", "fourteen", "fifteen",
    ↪ "sixteen", "seventeen", "eighteen", "nineteen"]
    words = ""
    if num >= 1000:
        words += ones[num // 1000] + " thousand "
    num %= 1000
    if num >= 100:
        words += ones[num // 100] + " hundred "
    num %= 100
    if num >= 10 and num <= 19:
        words += teens[num - 10] + " "
    elif num >= 20:
        words += tens[num // 10] + " "
    num %= 10
    if num >= 1 and num <= 9:
        words += ones[num] + " "
    return words.strip()
num = int(input("Enter a number"))
words = convert_to_words(num)
print(words)
```

Enter a number4558

four thousand five hundred fifty eight

10 Write Python Program to create a dictionary with the key as the first character and value as a list of words starting with that character.

Example:

Input: Don't wait for your feelings to change to take the action. Take the action and your feelings will change

Output:

{ 'D': ['Don't'], 'w': ['wait', 'will'], 'f': ['for', 'feelings', 'feelings'], 'y': ['your', 'your'], 't': ['to', 'to', 'take', 'the', 'the'], 'c': ['change', 'change'], 'a': ['action.', 'action', 'and'], 'T': ['Take'] }


```
[19]: s=input("enter a string: ")
      l=s.split()
      d={}
      for i in l:
          d[i[0]]=d.get(i[0],[])
          d[i[0]].append(i)
      print(d)
```

enter a string: Don't wait for your feelings to change to take the action. Take the action and your feelings will change

```
{'D': ['Don't'], 'w': ['wait', 'will'], 'f': ['for', 'feelings', 'feelings'],
'y': ['your', 'your'], 't': ['to', 'to', 'take', 'the', 'the'], 'c': ['change',
'change'], 'a': ['action.', 'action', 'and'], 'T': ['Take']}
```

11 **d={"student0":'Student@0',"student1":'Student@11',"student2":'Student@01278',"student3":'Student@052',"student4":'Student@01278',"student5":'Student@01278',"student6":'Student@042',"student7":'Student@07800',"student8":'Student@04789',"student9":'Student@04789'}**

Write a python program to update the password of any user given the above dictionary(d) which stores the username as the key of the dictionary and the username's password as the value of the dictionary. print the updated dictionary and print the username and password according to ascending order of password length of the updated dictionary. For the password updating of that username follow some instructions. Give the three chances to user enter the correct username and password. If the user does not enter the correct username and password then display "enter correct password and username". if the user does not enter the correct username and password in a given three chances then display "enter correct password and username" and "try after 24h" If the user enters the correct username and password in a given three chances. Give the three chances to user enter a new password to update the password of that username. If the user enters a new password not follow the below format, then display "follow the password format". if the user does not enter the password in a given format in a given three chances, then display "follow the password format" and "try after 24h" The check, of whether the new password format is correct or wrong makes the user define a function. That user define a function to return True or False for password valid or not. That user define function return value used in this program for new password validation. o New password must have the below format:

at least 1 number between 0 and 9

at least 1 upper letter (between a and z)

at least 1 lower letter (between A and Z)

at least 1 special character out of @\$__

minimum length of the password is 8 and the maximum length is 15

Do not use space and other special characters. Only uses @\$__

If the new password follows the format of the password in a given three chances. then print the updated dictionary and print the username and password according to ascending order of password

length of an updated dictionary. If the dictionary is not updated then take the old dictionary

```
[20]: def password_check(password):
    l, u, p, d = 0, 0, 0, 0
    if (len(password) >= 8 and len(password) <= 15):
        for i in password:
            # counting lowercase alphabets
            if (i.islower()):
                l+=1
            # counting uppercase alphabets
            if (i.isupper()):
                u+=1
            # counting digits
            if (i.isdigit()):
                d+=1
            # counting the mentioned special characters
            if(i=='@'or i=='$' or i=='_'):
                p+=1
        if (l>=1 and u>=1 and p>=1 and d>=1 and l+p+u+d==len(password)):
            return True
        else:
            return False
    else:
        return False

d={"student0":'Student00',"student1":'Student011',"student2":
↪ 'Student0121',"student3":'Student0052',"student4":'Student001278',
    "student5":'Student00125',    "student6":'Student0042',"student7":
↪ 'Student007800',"student8":'Student0012',
    "student9":'Student004789'}
first_password_username_count=0
s=" "
while first_password_username_count<3:
    if s=="stop":
        break
    username=input("enter correct username:")
    password=input("enter correct password:")
    if ((username not in d.keys()) or (d[username]!=password)):
        print("enter correct username and password")
        first_password_username_count+=1
        continue
    else:
        #update password
        update_count=0
        while(update_count<3):
            update_password=input("enter update password: ")
            if password_check(update_password):
                d[username]=update_password
```

```

        s="stop"
        break
    else:
        update_count+=1
        print(""" # The Password must have:
1. at least 1 number between 0 and 9
2. at least 1 upper letter (between a and z)
3. at least 1 lower letter (between A and Z)
4. at least 1 special character out of @$_:
5. minimum length of password is 8 and maximum length is 15""")
        continue
    else:
        print("try after 24h")
        s="stop"
        break
else:
    print("try after 24h")

print(d)
#Find and print longest and shortest password with its username
sorted_list=sorted(d.items(),key=lambda x:len(x[1]))
print("longest password",sorted_list[-1][0],"--",sorted_list[-1][1])
print("shortest password",sorted_list[0][0],"--",sorted_list[0][1])

```

```

enter correct username:student0
enter correct password:Student@0
enter update password: Student@88888
{'student0': 'Student@88888', 'student1': 'Student@11', 'student2':
'Student@121', 'student3': 'Student@052', 'student4': 'Student@01278',
'student5': 'Student@0125', 'student6': 'Student@042', 'student7':
'Student@07800', 'student8': 'Student@012', 'student9': 'Student@04789'}
longest password student9 -- Student@04789
shortest password student1 -- Student@11

```

- 12 One of the ways to encrypt a string is by rearranging its characters by certain rules, they are broken up by threes, fours or something larger. For instance, in the case of threes, the string ‘secret message’ would be broken into three groups. The first group is sr sg, the characters at indices 0, 3, 6, 9 and 12. The second group is eemse, the characters at indices 1, 4, 7, 10, and 13. The last group is ctea, the characters at indices 2, 5, 8, and 11. The encrypted message is sr sgeemsectea.

If the string ‘secret message’ would be broken into four groups. The first group is seeg, the characters at indices 0, 4, 8 and 12. The second group is etse, the characters at indices 1, 5, 9 and 13. The

third group is c s, the characters at indices 2, 6 and 10. The fourth group is rma, the characters at indices 3, 7 and 11. The encrypted message is seegetsec srma.

- (A). Write a program that asks the user for a string, and an integer determining whether to break things up by threes, fours, or whatever user inputs. Encrypt the string using above method. For example,

Input message: This is python, a programming language

Input Key: 4

Output Encrypted Message: T poaomngnghiyn gm geist,prilus h ranaa

Input message: This is python, a programming language

Input Key: 7

Output Message: T ,ggahp r giyaalest ma hpmniorigsnonu

- (B). If you get a message which is encoded by the method above then, Write a decryption program for the general case. Taking input of any encrypted string from user with key number used while breaking message apart during encryption. For example,

Input Encrypted message: Hloe gl o sogrilw g epntstfii o yotay hee nnh aoirtiimreegehrun nhnse ne

Input Key used during encryption: 5

Output Decrypted Message: Hi hello how are you going to learn python in this semester of engineering

Input Encrypted message: Ig ntot oopid ys lt dehaaaao yrn

Input Key used during encryption: 8

Output Decrypted Message: It is a good day to learn python

Input Encrypted message: istemoaa!t e ym ntt p eiohitlgs

Input Key used during encryption: 4

Output Decrypted Message: it is not the time to play games!

encode program

```
[23]: s=input()
s1=""
key=int(input())
for i in range(key):
    s1+=s[i::key]
print(s1)
```

secret message

7

smeecsrseatg e

decode program

```
[24]: encode=input()
      decode=[""]*len(encode)
      key=int(input())
      count=0
      for i in range(0,key):
          for j in range(i,len(encode),key):
              decode[j]=encode[count]
              count+=1
      print("".join(decode))
```

```
smeecsrseatg e
7
secret message
```

13 Given a list **L** of size **N**. You need to count the number of special elements in the given list. An element is special if removal of that element makes the list balanced. The list will be balanced if sum of even index elements is equal to the sum of odd elements. Also print the updated lists after removal of special elements.

Example 1:

Input:

L=[5, 5, 2, 5, 8]

Output:

Original List: [5, 5, 2, 5, 8]

Index to be removed is: 0

List after removing index 0 : [5, 2, 5, 8]

Original List: [5, 5, 2, 5, 8]

Index to be removed is: 1

List after removing index 1 : [5, 2, 5, 8]

Total number of special elements: 2

Explanation:

If we delete **L**[0] or **L**[1], list will be balanced.

[5, 2, 5, 8]

(5+5) = (2+8)

So **L**[0] and **L**[1] are special elements, So Count is 2.

After removal of the special elements, list will be: [5, 2, 5, 8]

Example 2:

Input:

L=[2,1,6,4]

Output:

Original List: [2, 1, 6, 4]

Index to be removed is: 1

List after removing index 1 : [2, 6, 4]

Total Number of Special elements: 1

Explanation:

If we delete L[1] from list : [2,6,4]

$(2+4) = (6)$

Here only 1 special element. So Count is 1.

After removal of special element, list will be : [2,6,4]

```
[25]: l=eval(input("enter list"))
print("Original List:",l)
count=0
for i in range(0,len(l)):
    c=l[:i]+l[i+1:]

    sum1=sum(c[0::2])
    sum2=sum(c[1::2])
    if sum1==sum2:
        print("index to be removed is: ",i)
        count+=1
        print("List after removing index ",i,"is ",l[0:i]+l[i+1:])
print("Total Number of Special elements:",count)
```

enter list[5,5,2,5,8]

Original List: [5, 5, 2, 5, 8]

index to be removed is: 0

List after removing index 0 is [5, 2, 5, 8]

index to be removed is: 1

List after removing index 1 is [5, 2, 5, 8]

Total Number of Special elements: 2

14 Valid Parentheses

Given a string s containing just the characters '(', ')', '{', '}', '[' and ']', determine if the input string is valid.

An input string is valid if:

Open brackets must be closed by the same type of brackets.

Open brackets must be closed in the correct order.

Every close bracket has a corresponding open bracket of the same type.

Example 1:

Input: s = “()”

Output: true

Example 2:

Input: s = “()”

Output: true

Example 3:

Input: s = “[()]”

Output: false

```
[35]: def isValid(s):
    stack = [] # Stack to store opening brackets
    closeToOpen = {')': '(', '}': '{', ']': '['} # Map of closing to opening
    ↪brackets

    for c in s:
        if c in closeToOpen: # If c is a closing bracket
            # Check if the stack is not empty and top of stack matches the
            ↪opening bracket
            if stack and stack[-1] == closeToOpen[c]:
                stack.pop() # Pop the matching opening bracket from stack
            else:
                ↪found
                return False # Return False if no matching opening bracket is
            ↪stack
        else:
            stack.append(c) # If c is an opening bracket, push it onto the

    ↪True; otherwise, False
    return not stack # If stack is empty, all brackets are balanced, return
    ↪True; otherwise, False

# Test case
print(isValid("[{}]()")) # Expected output: False
```

False

```
[26]: s="))()"
max_length = 0
stack = [-1] # Initialize with a start index
```

```

for i in range(len(s)):
    if s[i] == '(':
        stack.append(i)
    else:
        stack.pop()

    if not stack:
        stack.append(i) # If popped -1, add a new start index
    else:
        # Update the length of the valid substring
        max_length = max(max_length, i - stack[-1])
print(max_length)

```

2

- 15 **Problem Definition:** Given a 2D list `l`, calculate the frequency of each unique number in the list. Sort the numbers based on their frequency in descending order and print the sorted frequency. Additionally, print the two most frequent numbers with their frequencies.

```

[39]: # 2D list containing integer values
l = [[1, 2, 3, 1, 2], [4, 3, 2, 1, 2], [5, 1, 4, 3, 2], [1, 1, 1, 2, 3], [3, 2, 1, 3, 4]]

# Dictionary to store the frequency of each number
d = {}

# Loop through each list in the 2D list `l`
for i in l:
    # Loop through each element in the inner list
    for j in i:
        # Update the frequency of the number `j` in the dictionary
        d[j] = d.get(j, 0) + 1

# Convert the dictionary `d` into a list of tuples (number, frequency)
l = list(d.items())

# Sort the list of tuples in descending order based on the frequency
l.sort(key=lambda x: x[1], reverse=True)

# Print the entire dictionary of frequencies sorted by frequency
print(dict(l))

```



```
# Print the two most frequent numbers and their frequencies
print("Max two frequencies:")
for i in range(2): # Loop to print the top 2 frequent numbers
    print(l[i][0], ">", l[i][1])
```

{1: 8, 2: 7, 3: 6, 4: 3, 5: 1}

Max two frequencies:

1 > 8

2 > 7

16 Rearrange positive and negative numbers

```
[10]: array_nums = [-1, 2, -3, 5, 7, 8, 9, -10]
print("Original arrays:")
print(array_nums)
result = sorted(array_nums, key = lambda i: 0 if i == 0 else -1 / i)
print("\nRearrange positive and negative numbers of the said array:")
print(result)
```

Original arrays:

[-1, 2, -3, 5, 7, 8, 9, -10]

Rearrange positive and negative numbers of the said array:

[2, 5, 7, 8, 9, -10, -3, -1]

T2_Practice Programs_VHA

December 1, 2024

0.1 Python Program for Leaders in an array

Write a program to print all the LEADERS in the array. An element is leader if it is greater than all the elements to its right side. And the rightmost element is always a leader. For example in the array {16, 17, 4, 3, 5, 2}, leaders are 17, 5 and 2. Let the input array be arr[] and length of the array be size.

```
[10]: # Python Function to print leaders in array

def printLeaders(arr,size):

    for i in range(0, size):
        for j in range(i+1, size):
            if arr[i]<=arr[j]:
                break
        if j == size-1: # If loop didn't break
            print (arr[i])
arr=[16, 17, 4, 3, 5, 2]
printLeaders(arr, len(arr))
```

```
17
5
2
```

0.2 Python Dictionary to find mirror characters in a string

Given a string and a number N, we need to mirror the characters from the N-th position up to the length of the string in alphabetical order. In mirror operation, we change 'a' to 'z', 'b' to 'y', and so on.

```
[2]: def mirrorChars(input,k):
    # create dictionary
    original = 'abcdefghijklmnopqrstuvwxyz'
    reverse = 'zyxwvutsrqponmlkjihgfedcba'
    dictChars = {}
    for i in range(len(original)):
        dictChars[original[i]]=reverse[i]

    # separate out string after length k to change
```

```

# characters in mirror
prefix = input[0:k-1]
suffix = input[k-1:]
mirror = ''
# change into mirror
for i in range(0,len(suffix)):
    mirror = mirror + dictChars[suffix[i]]
# concat prefix and mirrored part
print (prefix+mirror)

input = 'ljietengx'
k = 3
mirrorChars(input,k)

```

ljrvgvmtc

0.3 Program for Equilibrium index of an array

Equilibrium index of an array is an index such that the sum of elements at lower indexes is equal to the sum of elements at higher indexes. For example, in an array A:

for example: Input: A[] = [-7, 1, 5, 2, -4, 3, 0]

Output: 3

3 is an equilibrium index, because:

$$A[0] + A[1] + A[2] = A[4] + A[5] + A[6]$$

Input: A[] = [1, 2, 3]

Output: -1

```

[11]: # Python program to find the equilibrium
# index of an array

# function to find the equilibrium index
def equilibrium(arr):

    # finding the sum of whole array
    total_sum = sum(arr)
    leftsum = 0
    for i, num in enumerate(arr):

        # total_sum is now right sum
        # for index i
        total_sum -= num

        if leftsum == total_sum:
            return i
        leftsum += num

```

```

    # If no equilibrium index found,
    # then return -1
    return -1

```

```

# Driver code
arr = [-7, 1, 5, 2, -4, 3, 0]
print ('First equilibrium index is ',
        equilibrium(arr))

```

First equilibrium index is 3

0.4 Python Program To Find Longest Common Prefix Using Sorting

Problem Statement: Given a set of strings, find the longest common prefix. Example:

Input: ["apple", "ape", "april"]

Output: "ap"

```

[12]: def longestCommonPrefix( a):
        size=len(a)
        if size==0:
            return -1
        a.sort()
        end = min(len(a[0]), len(a[size - 1]))
        i = 0
        while (i < end and a[0][i] == a[size - 1][i]):
            i += 1
        pre = a[0][0: i]
        if pre:
            return pre
        else:
            return -1

print("The longest Common Prefix is :",longestCommonPrefix(["lessonplan",
↪"lesson","lees", "length"]))

```

The longest Common Prefix is : le

0.5 Python Program for Tower of Hanoi

Tower of Hanoi is a mathematical puzzle where we have three rods and n disks. The objective of the puzzle is to move the entire stack to another rod, obeying the following simple rules: 1) Only one disk can be moved at a time. 2) Each move consists of taking the upper disk from one of the stacks and placing it on top of another stack i.e. a disk can only be moved if it is the uppermost disk on a stack. 3) No disk may be placed on top of a smaller disk. Note: Transferring the top n-1 disks from source rod to Auxiliary rod can again be thought of as a fresh problem and can be solved in the same manner.

```
[4]: # Recursive Python function to solve the tower of hanoi

def TowerOfHanoi(n , source, destination, auxiliary):
    if n==1:
        print ("Move disk 1 from source",source,"to destination",destination)
        return
    TowerOfHanoi(n-1, source, auxiliary, destination)
    print ("Move disk",n,"from source",source,"to destination",destination)
    TowerOfHanoi(n-1, auxiliary, destination, source)

# Driver code
n = 4
TowerOfHanoi(n,'A','B','C')
# A, C, B are the name of rods
```

```
Move disk 1 from source A to destination C
Move disk 2 from source A to destination B
Move disk 1 from source C to destination B
Move disk 3 from source A to destination C
Move disk 1 from source B to destination A
Move disk 2 from source B to destination C
Move disk 1 from source A to destination C
Move disk 4 from source A to destination B
Move disk 1 from source C to destination B
Move disk 2 from source C to destination A
Move disk 1 from source B to destination A
Move disk 3 from source C to destination B
Move disk 1 from source A to destination C
Move disk 2 from source A to destination B
Move disk 1 from source C to destination B
```

1 balanced parentheses in an expression

```
[8]: # balanced parentheses in an expression
def check(my_string):
    brackets = ['()', '{}', '[]']
    while any(x in my_string for x in brackets):
        for br in brackets:
            my_string = my_string.replace(br, '')
    return not my_string

# Driver code
string = "{[]{}()}"
print(string, "-", "Balanced"
      if check(string) else "Unbalanced")
```

```
{[]{}()} - Unbalanced
```

1.1 Program to generate all possible valid IP addresses from given string

Given a string containing only digits, restore it by returning all possible valid IP address combinations. A valid IP address must be in the form of A.B.C.D, where A, B, C, and D are numbers from 0-255. The numbers cannot be 0 prefixed unless they are 0.

Examples :

Input: 25525511135

Output: ["255.255.11.135", "255.255.111.35"]

Explanation:

These are the only valid possible IP addresses.

Input: "25505011535"

Output: []

Explanation:

We cannot generate a valid IP address with this string.

```
[9]: def solve(s, i, j, level, temp, res):

    if (i == (j + 1) and level == 5):
        res.append(temp[1:])

    # Digits of a number ranging 0-255 can lie only between
    # 0-3
    k = i
    while(k < i + 3 and k <= j):

        ad = s[i: k + 1]

        # Return if string starting with '0' or it is
        # greater than 255.
        if ((s[i] == '0' and len(ad) > 1) or int(ad) > 255):
            return

        # Recursively call for another level.
        solve(s, k + 1, j, level + 1, temp + '.' + ad, res)

        k += 1

    # driver code
    s = "25525511135"
    n = len(s)
    ans = []
    solve(s, 0, n - 1, 1, "", ans)
    for s in ans:
        print(s)
```

255.255.11.135
255.255.111.35

2 Sort a list of tuples using Lambda

```
[1]: subject_marks = [('English', 88), ('Science', 90), ('Maths', 97), ('Social_
    ↳sciences', 82)]
print("Original list of tuples:")
print(subject_marks)
subject_marks.sort(key = lambda x: x[1])
print("\nSorting the List of Tuples:")
print(subject_marks)
```

Original list of tuples:

```
[('English', 88), ('Science', 90), ('Maths', 97), ('Social sciences', 82)]
```

Sorting the List of Tuples:

```
[('Social sciences', 82), ('English', 88), ('Science', 90), ('Maths', 97)]
```

3 Convert a given list of strings into list of lists using map function

```
[2]: def strings_to_listOflists(str):
    result = map(list, str)
    return list(result)

colors = ["Red", "Green", "Black", "Orange"]
print('Original list of strings:')
print(colors)
print("\nConvert the said list of strings into list of lists:")
print(strings_to_listOflists(colors))
```

Original list of strings:

```
['Red', 'Green', 'Black', 'Orange']
```

Convert the said list of strings into list of lists:

```
[['R', 'e', 'd'], ['G', 'r', 'e', 'e', 'n'], ['B', 'l', 'a', 'c', 'k'], ['O',
'r', 'a', 'n', 'g', 'e']]
```

4 Find the numbers of a given string and store them in a list, display the numbers which are bigger than the length of the list in sorted form

```
[3]: str1 = "sdf 23 safs8 5 sdfsd8 sdfs 56 21sfs 20 5"
print("Original string: ",str1)
str_num=[i for i in str1.split(' ')]
lenght=len(str_num)
```

```

numbers=sorted([int(x) for x in str_num if x.isdigit()])
print('Numbers in sorted form:')
for i in ((filter(lambda x:x>lenght,numbers))):
    print(i,end=' ')

```

Original string: sdf 23 safs8 5 sdfsd8 sdfs 56 21sfs 20 5
 Numbers in sorted form:
 20 23 56

5 Calculate the sum of the positive and negative numbers of a given list of numbers using lambda function

```

[5]: nums = [2, 4, -6, -9, 11, -12, 14, -5, 17]
print("Original list:",nums)

total_negative_nums = list(filter(lambda nums:nums<0,nums))
total_positive_nums = list(filter(lambda nums:nums>0,nums))

print("Sum of the positive numbers: ",sum(total_negative_nums))
print("Sum of the negative numbers: ",sum(total_positive_nums))

```

Original list: [2, 4, -6, -9, 11, -12, 14, -5, 17]
 Sum of the positive numbers: -32
 Sum of the negative numbers: 48

6 Find the nested lists elements, which are present in another list using lambda

```

[6]: def intersection_nested_lists(l1, l2):
    result = [list(filter(lambda x: x in l1, sublist)) for sublist in l2]
    return result

nums1 = [1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14]
nums2 = [[12, 18, 23, 25, 45], [7, 11, 19, 24, 28], [1, 5, 8, 18, 15, 16]]
print("\nOriginal lists:")
print(nums1)
print(nums2)
print("\nIntersection of said nested lists:")
print(intersection_nested_lists(nums1, nums2))

```

Original lists:
 [1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14]
 [[12, 18, 23, 25, 45], [7, 11, 19, 24, 28], [1, 5, 8, 18, 15, 16]]

Intersection of said nested lists:
 [[12], [7, 11], [1, 5, 8]]


```
[8]: # python code to demonstrate working of reduce()
      # using operator functions

      # importing functools for reduce()
      import functools

      # importing operator for operator functions
      import operator

      # initializing list
      lis = [1, 3, 5, 6, 2]

      # using reduce to compute sum of list
      # using operator functions
      print("The sum of the list elements is : ", end="")
      print(functools.reduce(operator.add, lis))

      # using reduce to compute product
      # using operator functions
      print("The product of list elements is : ", end="")
      print(functools.reduce(operator.mul, lis))

      # using reduce to concatenate string
      print("The concatenated product is : ", end="")
      print(functools.reduce(operator.add, ["geeks", "for", "geeks"]))
```

```
The sum of the list elements is : 17
The product of list elements is : 180
The concatenated product is : geeksforgeeks
```

T2_CLASS _PROGRAM_VHA (1)

December 1, 2024

- 1 Get a string from a given string where all occurrences of its first char have been changed to '\$', except the first char itself

Sample String : 'restart' Expected Result : 'resta\$t'

```
[1]: def change_char(str1):  
    char = str1[0]  
    str1 = str1.replace(char, '$')  
    str1 = char + str1[1:]  
  
    return str1  
  
print(change_char('restart'))
```

resta\$t

- 2 Count the occurrences of each word in a given sentence

```
[2]: def word_count(str):  
    counts = dict()  
    words = str.split()  
  
    for word in words:  
        if word in counts:  
            counts[word] += 1  
        else:  
            counts[word] = 1  
  
    return counts  
  
print( word_count('the quick brown fox jumps over the lazy dog.'))
```

```
{'the': 2, 'quick': 1, 'brown': 1, 'fox': 1, 'jumps': 1, 'over': 1, 'lazy': 1,  
'dog.': 1}
```

3 Write a Python program to create a Caesar encryption.

Note: In cryptography, a Caesar cipher, also known as Caesar's cipher, the shift cipher, Caesar's code or Caesar shift, is one of the simplest and most widely known encryption techniques. It is a type of substitution cipher in which each letter in the plaintext is replaced by a letter some fixed number of positions down the alphabet. For example, with a left shift of 3, D would be replaced by A, E would become B, and so on. The method is named after Julius Caesar, who used it in his private correspondence.

key would be in negative if you want to left shift. key would be positive if you want to right shift.

4 1st Method

```
[59]: s=input()
key=int(input())
s1=""
for i in s:
    if i>='A' and i<='Z':
        if ord(i)+key>ord('Z'):
            i=chr(ord(i)+key-26)
        else:
            i=chr(ord(i)+key)
        s1+= i
    elif i>='a' and i<='z':
        if ord(i)+key>ord('z'):
            i=chr(ord(i)+key-26)
        else:
            i=chr(ord(i)+key)
        s1+= i
    else:
        s1+= i
print(s1)
```

thisispython

2

vjkukuravjqp

5 2nd Method

```
[58]: def caesar_encrypt(realText, step):
    outText = []
    cryptText = []

    uppercase = ['A', 'B', 'C', 'D', 'E', 'F', 'G', 'H', 'I', 'J', 'K', 'L', 'M', 'N', 'O', 'P', 'Q', 'R', 'S', 'T', 'U', 'V', 'W', 'X', 'Y', 'Z']
    lowercase = ['a', 'b', 'c', 'd', 'e', 'f', 'g', 'h', 'i', 'j', 'k', 'l', 'm', 'n', 'o', 'p', 'q', 'r', 's', 't', 'u', 'v', 'w', 'x', 'y', 'z']
```

```

for eachLetter in realText:
    if eachLetter in uppercase:
        index = uppercase.index(eachLetter)
        crypting = (index + step) % 26
        cryptText.append(crypting)
        newLetter = uppercase[crypting]
        outText.append(newLetter)
    elif eachLetter in lowercase:
        index = lowercase.index(eachLetter)
        crypting = (index + step) % 26
        cryptText.append(crypting)
        newLetter = lowercase[crypting]
        outText.append(newLetter)
return ''.join(outText)
code = caesar_encrypt('thisispython', 2)
print()
print(code)
print()

```

vjkukuravjqp

6 3rd Method

```

[61]: def encrypt(key, message):
    message = message.upper()
    alpha = "ABCDEFGHIJKLMNOPQRSTUVWXYZ"
    result = ""

    for letter in message:
        if letter in alpha: #if the letter is actually a letter
            #find the corresponding ciphertext letter in the alphabet
            letter_index = (alpha.find(letter) + key) % len(alpha)

            result = result + alpha[letter_index]
        else:
            result = result + letter

    return result

def decrypt(key, message):
    message = message.upper()
    alpha = "ABCDEFGHIJKLMNOPQRSTUVWXYZ"
    result = ""

```

```

for letter in message:
    if letter in alpha: #if the letter is actually a letter
        #find the corresponding ciphertext letter in the alphabet
        letter_index = (alpha.find(letter) - key) % len(alpha)

        result = result + alpha[letter_index]
    else:
        result = result + letter

return result
message="ywa"
print(encrypt(4, message))
print(decrypt(4, 'cae'))

```

CAE

YWA

7 Demo of Join Function

```

[4]: #demo of join function
#if joins all arguments given inside of list of strings to a blank string.
a="hello"
b="LJU"
print(''.join([a,b]))

```

helloLJU

```

[5]: #demo of join function
#if joins all arguments given inside of list of strings with space in between.
a="hello"
b="LJU"
c='welcome'
print(' '.join([a,b,c]))

```

hello LJU welcome

8 Write a Python program to reverse words in a string

```

[9]: def reverse_string_words(text):
    for line in text.split('\n'):
        return(' '.join(line.split()[::-1]))
print(reverse_string_words("The quick brown fox jumps over the lazy dog. "))
print(reverse_string_words("Python Exercises. "))

```

dog. lazy the over jumps fox brown quick The
Exercises. Python

9 Write a Python program to find the second most repeated word in a given string.

```
[15]: def word_count(str):
    counts = dict()
    words = str.split()

    for word in words:
        if word in counts:
            counts[word] += 1
        else:
            counts[word] = 1

    counts_x = sorted(counts.items(), key=lambda kv: kv[1])
    print(counts_x)
    return counts_x[-2]

print(word_count("Both of these issues are fixed by postponing the evaluation_
↳of annotations. Instead of compiling code which executes expressions in_
↳annotations at their definition time, the compiler stores the annotation in_
↳a string form equivalent to the AST of the expression in question. If_
↳needed, annotations can be resolved at runtime using typing.get_type_hints().
↳ In the common case where this is not required, the annotations are cheaper_
↳to store (since short strings are interned by the interpreter) and make_
↳startup time faster."))
```

```
[('Both', 1), ('these', 1), ('issues', 1), ('fixed', 1), ('postponing', 1),
('evaluation', 1), ('annotations.', 1), ('Instead', 1), ('compiling', 1),
('code', 1), ('which', 1), ('executes', 1), ('expressions', 1), ('their', 1),
('definition', 1), ('time,', 1), ('compiler', 1), ('stores', 1), ('annotation',
1), ('a', 1), ('string', 1), ('form', 1), ('equivalent', 1), ('AST', 1),
('expression', 1), ('question.', 1), ('If', 1), ('needed,', 1), ('can', 1),
('be', 1), ('resolved', 1), ('runtime', 1), ('using', 1),
('typing.get_type_hints().', 1), ('In', 1), ('common', 1), ('case', 1),
('where', 1), ('this', 1), ('is', 1), ('not', 1), ('required,', 1), ('cheaper',
1), ('store', 1), ('(since', 1), ('short', 1), ('strings', 1), ('interned', 1),
('interpreter)', 1), ('and', 1), ('make', 1), ('startup', 1), ('time', 1),
('faster.', 1), ('by', 2), ('at', 2), ('to', 2), ('are', 3), ('in', 3),
('annotations', 3), ('of', 4), ('the', 8)]
('of', 4)
```

10 Write a Python program to create a string from two given strings concatenating uncommon characters of the said strings

```
[16]: def uncommon_chars_concat(s1, s2):

    set1 = set(s1)
    set2 = set(s2)

    common_chars = list(set1 & set2)
    result = [ch for ch in s1 if ch not in common_chars] + [ch for ch in s2 if
↪ch not in common_chars]
    return(''.join(result))

s1 = 'abcdpqr'
s2 = 'xyzabcd'
print("Original Substrings:\n",s1+"\n",s2)
print("\nAfter concatenating uncommon characters:")
print(uncommon_chars_concat(s1, s2))
```

Original Substrings:

abcdpqr
xyzabcd

After concatenating uncommon characters:

pqrxyz

11 Write a Python program to find the minimum window in a given string which will contain all the characters of another given string. (You can use your own method to find the solution as well)

Input : str1 = " PRWSOERIUSFK "

str2 = " OSU "

Output: Minimum window is "OERIUS"

```
[25]: def minWindow(s,t) :

    counter_t = {}
    counter_s = {}

    for c in t:
        counter_t[c] = counter_t.get(c, 0) + 1

    i = 0
```

```

j = 0

left = -1
right = -1

valid = 0

for i in range(len(s)):

    while j < len(s) and valid < len(counter_t):
        counter_s[s[j]] = counter_s.get(s[j], 0) + 1

        if s[j] in counter_t and counter_s[s[j]] == counter_t[s[j]]:
            valid += 1

        j += 1

    if valid == len(counter_t):
        if left == -1 or j - i < right - left:
            left = i
            right = j

        counter_s[s[i]] -= 1
        if s[i] in counter_t and counter_s[s[i]] == counter_t[s[i]] - 1:
            valid -= 1

    if left == -1:
        return "not found"

    return s[left : right]

s="1a2b3cbva"
t="abc"
print(minWindow(s,t))
s = "PRWSvOERIUSFK"
t = "OSU"
print(minWindow(s,t))
s="abcfghioi9i99i9i9ijnbhhjkmijnbhfi  hklij %^^hilkiujj_
↳hjmjkfrtygh00000000ijnhjhihhgfgghjmnbvghoiuhghgfij hjkjij"
t="hijkwxy"
print(minWindow(s,t))

```

cbva

OERIUS

not found


```
[1]: def password_check(password):
    l, u, p, d = 0, 0, 0, 0
    if (len(password) >= 8 and len(password) <= 15):
        for i in password:
            # counting lowercase alphabets
            if (i.islower()):
                l+=1
            # counting uppercase alphabets
            if (i.isupper()):
                u+=1
            # counting digits
            if (i.isdigit()):
                d+=1
            # counting the mentioned special characters
            if(i=='@'or i=='$' or i=='_'):
                p+=1
        if (l>=1 and u>=1 and p>=1 and d>=1 and l+p+u+d==len(password)):
            return True
        else:
            return False
    else:
        return False

d={"student0":'Student@0', "student1":'Student@11', "student2":
↪ 'Student@121', "student3":'Student@052', "student4":'Student@01278',
    "student5":'Student@0125',    "student6":'Student@042', "student7":
↪ 'Student@07800', "student8":'Student@012',
    "student9":'Student@04789'}
first_password_username_count=0
s=" "
while first_password_username_count<3:
    if s=="stop":
        break
    username=input("enter correct username:")
    password=input("enter correct password:")
    if ((username not in d.keys()) or (d[username]!=password)):
        print("enter correct username and password")
        first_password_username_count+=1
        continue
    else:
        #update password
        update_count=0
        while(update_count<3):
            update_password=input("enter update password: ")
            if password_check(update_password):
                d[username]=update_password
                s="stop"
                break
```

```

        else:
            update_count+=1
            print(""" # The Password must have:
1. at least 1 number between 0 and 9
2. at least 1 upper letter (between a and z)
3. at least 1 lower letter (between A and Z)
4. at least 1 special character out of @$_:
5. minimum length of password is 8 and maximum length is 15""")
            continue
    else:
        print("try after 24h")
        s="stop"
        break
else:
    print("try after 24h")

print(d)
#Find and print longest and shortest password with its username
sorted_list=sorted(d.items(),key=lambda x:len(x[1]))
print("longest password",sorted_list[-1][0],"--",sorted_list[-1][1])
print("shortest password",sorted_list[0][0],"--",sorted_list[0][1])

```

```

enter correct username:student0
enter correct password:Student@0
enter update password: Student@88888
{'student0': 'Student@88888', 'student1': 'Student@11', 'student2':
'Student@121', 'student3': 'Student@052', 'student4': 'Student@01278',
'student5': 'Student@0125', 'student6': 'Student@042', 'student7':
'Student@07800', 'student8': 'Student@012', 'student9': 'Student@04789'}
longest password student9 -- Student@04789
shortest password student1 -- Student@11

```

12 Write a Python program to remove unwanted characters from a given string.

Sample Output:

Original String : Pyth*^on Exercis^es

After removing unwanted characters:

Python Exercises

Original String : A%^!B#*CD

After removing unwanted characters:

ABCD

[]:

```
[32]: def remove_chars(str1, unwanted_chars):
        for i in unwanted_chars:
            str1 = str1.replace(i, '')
        return str1

str1 = "Pyth*^on Exercis^es"
str2 = "A%~!B#*CD"

unwanted_chars = ["#", "*", "!", "^", "%"]
print ("Original String : " + str1)
print("After removing unwanted characters:")
print(remove_chars(str1, unwanted_chars))
print ("\nOriginal String : " + str2)
print("After removing unwanted characters:")
print(remove_chars(str2, unwanted_chars))
```

Original String : Pyth*^on Exercis^es
After removing unwanted characters:
Python Exercises

Original String : A%~!B#*CD
After removing unwanted characters:
ABCD

13 Write a Python program to remove punctuations from a given string.

Sample Output:

Original text:

String! With. Punctuation?

After removing Punctuations from the said string:

String With Punctuation

```
[33]: def remove_punctuations(text):
        punc_list = '!"()~[]{};: "\, <> . / ? @ # $ % ^ & * _ ~ '
        result = ""
        for char in text:
            if char not in punc_list:
                result = result + char
```

```

    return result
text = "@~&$String! With.-- Punctuation?"
print("Original text:")
print(text)
result = remove_punctuations(text)
print("\nAfter removing Punctuations from the said string:")
print(result)

```

Original text:

@~&\$String! With.-- Punctuation?

After removing Punctuations from the said string:

String With Punctuation

14 Write a Python program to remove repeated consecutive characters and replace with the single letters and print new updated string.

Sample Data:

("Red Green White") -> "Red Gren White"

("aabbbcdeffff") -> "abcdef"

("Yellowwooddoor") -> "Yelowodor"

```

[34]: def test(text):
    result = []
    for x in text:
        if not result or result[-1] != x:
            result.append(x)
    return ''.join(result)

text = "Red Green White"
print("Original string:", text)
print("Remove repeated consecutive characters and replace with the single
↳ letters:")
print(test(text))
text = "aabbbcdeffff"
print("\nOriginal string:", text)
print("Remove repeated consecutive characters and replace with the single
↳ letters:")
print(test(text))
text = "Yellowwooddoor"
print("\nOriginal string:", text)
print("Remove repeated consecutive characters and replace with the single
↳ letters:")
print(test(text))

```

Original string: Red Green White
Remove repeated consecutive characters and replace with the single letters:
Red Gren White

Original string: aabbbbcdeffff
Remove repeated consecutive characters and replace with the single letters:
abcdef

Original string: Yellowwooddoor
Remove repeated consecutive characters and replace with the single letters:
Yelowodor

```
[35]: def test(text):  
        return ''.join(text[i] for i in range(len(text)) if i==0 or text[i-1]!  
        ↪=text[i])  
text = "Red Green White"  
print("Original string:", text)  
print("Remove repeated consecutive characters and replace with the single_  
    ↪letters:")  
print(test(text))  
text = "aabbbbcdeffff"  
print("\nOriginal string:", text)  
print("Remove repeated consecutive characters and replace with the single_  
    ↪letters:")  
print(test(text))  
text = "Yellowwooddoor"  
print("\nOriginal string:", text)  
print("Remove repeated consecutive characters and replace with the single_  
    ↪letters:")  
print(test(text))
```

Original string: Red Green White
Remove repeated consecutive characters and replace with the single letters:
Red Gren White

Original string: aabbbbcdeffff
Remove repeated consecutive characters and replace with the single letters:
abcdef

Original string: Yellowwooddoor
Remove repeated consecutive characters and replace with the single letters:
Yelowodor

- 15 Write a Python program to that takes two strings. Count the number of times each string contains the same three letters at the same index. Go to the editor

Sample Data:

("Red RedGreen") -> 1

("Red White Red White") -> 7

("Red White White Red") -> 0

```
[36]: def test(text1, text2):
        ctr = 0
        for i in range(len(text1) - 2):
            if text1[i:i+3] == text2[i:i+3]:
                ctr += 1

        return ctr

text1 = "Red"
text2 = "RedGreen"
print("Original strings:", text1, text2)
print("Check said two strings contain three letters at the same index:")
print(test(text1, text2))
text1 = "Red White"
text2 = "Red White"
print("Original strings:", text1, text2)
print("Check said two strings contain three letters at the same index:")
print(test(text1, text2))
text1 = "Red White"
text2 = "White Red"
print("Original strings:", text1, text2)
print("Check said two strings contain three letters at the same index:")
print(test(text1, text2))
```

Original strings: Red RedGreen

Check said two strings contain three letters at the same index:

1

Original strings: Red White Red White

Check said two strings contain three letters at the same index:

7

Original strings: Red White White Red

Check said two strings contain three letters at the same index:

0

16 Write a Python script to sort (ascending and descending) a dictionary by value.

```
[37]: def sort_dict_by_value(d, reverse = False):
        return dict(sorted(d.items(), key = lambda x: x[1], reverse = reverse))
    print("Original dictionary elements:")
    colors = {'Red': 1, 'Green': 3, 'Black': 5, 'White': 2, 'Pink': 4}
    print(colors)
    print("\nSort (ascending) the said dictionary elements by value:")
    print(sort_dict_by_value(colors))
    print("\nSort (descending) the said dictionary elements by value:")
    print(sort_dict_by_value(colors, True))
```

Original dictionary elements:

```
{'Red': 1, 'Green': 3, 'Black': 5, 'White': 2, 'Pink': 4}
```

Sort (ascending) the said dictionary elements by value:

```
{'Red': 1, 'White': 2, 'Green': 3, 'Pink': 4, 'Black': 5}
```

Sort (descending) the said dictionary elements by value:

```
{'Black': 5, 'Pink': 4, 'Green': 3, 'White': 2, 'Red': 1}
```

17 I have a string of words. I would like to sort the list by the length of each word so that the longest word is at the top

```
[1]: s="nbhg mjknh kiuytgft nbh nbhgtygnm mnjku lkmnhg nbh nb ghyuytredf bghyyt_
    ↪kmnjkmnjkmn bghbghb vfgbvc hgv bvg"
    d={}
    for i in s.split():
        d[i]=len(i)
    #print(d)
    l1=d.values()
    l2=d.keys()
    #print(l1)
    #print(l2)
    ans=[i[1] for i in sorted(list(zip(l1,l2)),reverse=True)]
    print(ans)
```

```
['kmnjkmnjkmn', 'ghyuytredf', 'nbhgtygnm', 'kiuytgft', 'bghbghb', 'vfgbvc',
'lkmnhg', 'bghyyt', 'mnjku', 'mjknh', 'nbhg', 'nbh', 'hgv', 'bvg', 'nb']
```

18 This is a Python Program to create a dictionary with key as first character and value as words starting with that character.

```
[ ]: s="acd bcd avf ght dfg bgh kju avf ghv bvf ujh kju bgh avf nhj bgh bvf cdf avg_  
      ↳sde kju gty frt der cdf xsd zse"  
d={}  
for i in s.split():  
    if i[0] not in d.keys():  
        d[i[0]]=[]  
        d[i[0]].append(i)  
    else:  
        d[i[0]].append(i)  
print(d)
```

19 This is a Python Program to create a dictionary with key as character and value as character count repeated in string.first five more repeated character

```
[39]: s="acd bcd avf ght dfg bgh kju avf ghv bvf ujh kju bgh avf nhj bgh bvf cdf avg_  
      ↳sde kju gty frt der cdf xsd zse"  
d={}  
for i in s.split():  
    d[i[0]]=d.get(i[0],0)+1  
print(d)  
y=sorted(d.items(),key=lambda x:x[1],reverse=True)  
for i in range(5):  
    print(y[i])
```

```
{'a': 5, 'b': 6, 'g': 3, 'd': 2, 'k': 3, 'u': 1, 'n': 1, 'c': 2, 's': 1, 'f': 1,  
'x': 1, 'z': 1}  
( 'b', 6)  
( 'a', 5)  
( 'g', 3)  
( 'k', 3)  
( 'd', 2)
```

20 Sort Dictionary key and values List.

Example 1:

Input:

```
{'c': [3], 'b': [12, 10], 'a': [19, 4]}
```

Output:

```
{'a': [4, 19], 'b': [10, 12], 'c': [3]}
```


Example 2:

Input:

{'c': [10, 34, 3]}

Output:

{'c': [3, 10, 34]}

```
[40]: d = {'c': [3], 'b': [12, 10], 'a': [19, 4]}

res = {}

for i in sorted(d):
    res[i] = sorted(d[i])

print(res)
```

{'a': [4, 19], 'b': [10, 12], 'c': [3]}

21 Convert a list of Tuples into Dictionary.

Example 1:

Input:

[("akash", 10), ("gaurav", 12), ("anand", 14), ("suraj", 20), ("akhil", 25), ("ashish", 30)]

Output:

{'akash': [10], 'gaurav': [12], 'anand': [14], 'suraj': [20], 'akhil': [25], 'ashish': [30]}

Example 2:

Input:

[('A', 1), ('B', 2), ('C', 3)]

Output:

{'A': [1], 'B': [2], 'C': [3]}

```
[41]: L1 = [("akash", 10), ("gaurav", 12), ("anand", 14), ("suraj", 20), ("akhil", 25), ("ashish", 30)]

L = [('A', 1), ('B', 2), ('C', 3)]

d = {}

for i,j in L:
    d[i] = [j]

print(d)
```

{'A': [1], 'B': [2], 'C': [3]}

22 Key with maximum unique values

Given a dictionary with values list, extract key whose value has most unique values.

Example 1:

Input:

test_dict = {"CampusX": [5, 7, 9, 4, 0], "is": [6, 7, 4, 3, 3], "Best": [9, 9, 6, 5, 5]}

Output:

CampusX

Example 2:

Input:

test_dict = {"CampusX": [5, 7, 7, 7, 7], "is": [6, 7, 7, 7], "Best": [9, 9, 6, 5, 5]}

Output:

Best

```
[42]: test_dict = {"CampusX": [5, 7, 7, 7, 7], "is": [6, 7, 7, 7], "Best": [9, 9, 6, 5, 5]}
      ↪
max_val = 0
max_key = ''
for i in test_dict:
    if max_val < len(set(test_dict[i])):
        max_val = len(set(test_dict[i]))
        max_key = i
print(max_key)
```

Best

23 find uncommon words from two Strings. Statement: Given two sentences as strings A and B. The task is to return a list of all uncommon words. A word is uncommon if it appears exactly once in any one of the sentences, and does not appear in the other sentence. Note: A sentence is a string of space-separated words. Each word consists only of lowercase letters.

Example 1:

Input:

A = "apple banana mango" B = "banana fruits mango"

```
[3]: # Code here
A = "apple banana mango"
B = "banana fruits mango"

L = []

for i in A.split():
    if i not in B and i not in L:
        L.append(i)

for j in B.split():
    if j not in A and j not in L:
        L.append(j)

print(L)
```

```
['apple', 'fruits']
```

24 Check whether the string is Symmetrical. Statement: Given a string. the task is to check if the string is symmetrical or not. A string is said to be symmetrical if both the halves of the string are the same.

Example 1:

Input

khokho Output

The entered string is symmetrical

```
[5]: s = input('enter the string')

if len(s)%2 == 0:
    s1 = s[0:len(s)//2]
    s2 = s[len(s)//2:]
else:
    s1 = s[0:len(s)//2]
    s2 = s[len(s)//2 + 1:]
if s1 == s2:
    print('symmetrical')
else:
    print('not symmetrical')
```

enter the stringKHOKHO

symmetrical

25 Take a alphanumeric string input and print the sum and average of the digits that appear in the string, ignoring all other characters. Input:

hel123O4every093

Output:

Sum: 22 Avg: 3.14

```
[6]: s = 'hel123O4every093'
```

```
sum = 0
count = 0

for i in s:
    if i.isdigit():
        sum = sum + int(i)
        count += 1

print(sum)
print(sum/count)
print(count)
```

22

3.142857142857143

7

26 Create Short Form from initial character

Given a string create short form of the string from Initial character. Short form should be capitalised.

Example:

Input:

Data science mentorship program

Output:

```
[7]: inp = 'Data science Mentorship Program'
```

```
res = ''

for i in inp.split():
    res = res + i[0].upper()

print(res)
```

DSMP

26.0.1 Given a list L of size N. You need to count the number of special elements in the given list.

26.0.2 An element is special if removal of that element makes the list balanced. The list will be balanced if sum of even index elements is equal to the sum of odd index elements.

Example Input

Input 1:

A = [2, 1, 6, 4] Input 2:

A = [5, 5, 2, 5, 8] Example Output

Output 1:

1

Output 2:

2

Explanation 1:

After deleting 1 from list : [2,6,4] $(2+4) = (6)$

Hence 1 is the only special element, so count is 1 Explanation 2:

If we delete A[0] or A[1] , list will be balanced $(5+5) = (2+8)$

So A[0] and A[1] are special elements, so count is 2.

```
[1]: l=eval(input("enter list"))
count=0
for i in range(0,len(l)):
    c=l.copy()
    c.pop(i)
    sum1=sum(c[0::2])
    sum2=sum(c[1::2])
    if sum1==sum2:
        print(i)
        count+=1
print("total count",count)
```

enter list[1,2,3,2]

1

total count 1

26.0.3 A simple way of encrypting a message is to rearrange its characters. One way to rearrange the characters is to pick out the characters at even indices, put them first in the encrypted string, and follow them by the odd characters. For example, the string message would be encrypted as msaeesg because the even characters are m, s, a, e (at indices 0, 2, 4, and 6) and the odd characters are e, s, g (at indices 1, 3, and 5).

26.0.4 (1). Write a program that asks the user for a string and uses this method to encrypt the string.

26.0.5 (2). Write a program that decrypts a string that was encrypted with this method.

```
[6]: def encrypt():#to put all our code in function
    strings=input('what is your message: ')
    even=strings[::2]#extract the even part
    odd=strings[1::2]#extract the odd part
    print(even+odd)#print the result
encrypt()

def decrypt():
    string=input('what is your message: ')
    length=len(string)#to get the length of the input
    half_length=(length+1)//2 #half of the input
    even=string[:half_length]#even part
    odd=string[half_length:]#odd part
    #here we start inserting each of the part to form original
    msg=''
    for i in range (half_length):
        join=even[i:i+1]+odd[i:i+1]
        msg=msg+join
    print(msg)
decrypt()
```

```
what is your message: This is python programming
Ti spto rgamnhsi yhnpormig
what is your message: Ti spto rgamnhsi yhnpormig
This is python programming
```

27 A more general version of the above technique is the rail fence cipher, where instead of breaking things into evens and odds, they are broken up by threes, fours or something larger. For instance, in the case of threes, the string secret message would be broken into three groups. The first group is sr sg, the characters at indices 0, 3, 6, 9 and 12. The second group is eemse, the characters at indices 1, 4, 7, 10, and 13. The last group is ctea, the characters at indices 2, 5, 8, and 11. The encrypted message is sr sgeemsectea.

27.0.1 Write a program that asks the user for a string, and an integer determining whether to break things up by threes, fours, or whatever user inputs. Encrypt the string using above method.

27.0.2 Write a decryption program for the same general case. Taking input of any encrypted string from user with number used to break things apart during encryption.

27.0.3 Encryption

```
[7]: s=input()
s1=""
key=int(input())
for i in range(key):
    s1+=s[i::key]
print(s1)
```

This is python, a programming language

5

Tit omlahshagiagi o rnnespnagg y,rm u

27.0.4 1st Solution for Decryption

```
[8]: string=input('what is your message: ')
key=int(input())
length=len(string)#to get the length of the input
part=length//key #half of the input
extra=length%key #extra characters after dividing string in equal parts
part1=string[: (part+1)*extra]
part2=string[(part+1)*extra:]
msg=''
for i in range(part+1):
    if i<part:
        msg+=part1[i::part+1]+part2[i::part]
    else:
        msg+=part1[i::part+1]
```

```
print(msg)
```

what is your message: Tit omlahshagiagi o rnnespnpagg y,rm u
5
This is python, a programming language

27.0.5 2nd Solution for Decryption

```
[9]: string=input('what is your message: ')
key=int(input())
length=len(string)#to get the length of the input
part=length//key #half of the input
extra=length%key #extra characters after dividing string in equal parts
part1=string[: (part+1)*extra]
part2=string[(part+1)*extra:]
msg=''
for i in range(part+1):
    if i<part:
        msg+=part1[i::part+1]+part2[i::part]
    else:
        msg+=part1[i::part+1]
print(msg)
```

what is your message: Tit omlahshagiagi o rnnespnpagg y,rm u
5
This is python, a programming language

28 Write a Python program which will return the sum of the numbers in the array, returning 0 for an empty array. Except the number 13 is very unlucky, so it does not count and number that come immediately after 13 also do not count.

Example : $[1, 2, 3, 4] = 10$ $[1, 2, 3, 4, 13] = 10$ $[13, 1, 2, 3, 13] = 5$

```
[5]: def sum_list(l):
    if len(l)==0:
        return 0
    else:
        sum=0
        for i in range(len(l)):
            if l[i]==13 or l[i-1]==13 and i!=0:
                continue
            else:
                sum+=l[i]
        return sum
l=eval(input("enter list"))
print(sum_list(l))
```


enter list[1,13,1,2,13,3,3,13]
6

29 Write Python Program to Add Two Matrices

```
matrix_1 = [[1, 2, 3],  
            [4, 5, 6],  
            [7, 8, 9]]  
matrix_2 = [[1, 2, 3],  
            [4, 5, 6],  
            [7, 8, 9]]
```

```
[7]: matrix_1 = [[1, 2, 3],[4, 5, 6], [7, 8, 9]]  
matrix_2 = [[1, 2, 3],[4, 5, 6], [7, 8, 9]]  
matrix_result = [[0, 0, 0],[0, 0, 0],[0, 0, 0]]  
for rows in range(len(matrix_1)):  
    for columns in range(len(matrix_2[0])):  
        matrix_result[rows][columns] = matrix_1[rows][columns] +  
        ↪matrix_2[rows][columns]  
print("Addition of two matrices is")  
print(matrix_result)  
for items in matrix_result:  
    print(items)
```

```
Addition of two matrices is  
[[2, 4, 6], [8, 10, 12], [14, 16, 18]]  
[2, 4, 6]  
[8, 10, 12]  
[14, 16, 18]
```

30 Program to multiply two matrices using nested for loops

```
[8]: #Program to multiply two matrices using nested for loops  
# 3x3 matrix  
A = [[1,2,3],  
     [4,5,6],  
     [7,8,9]]  
  
B = [[1,2,3,4],  
     [5,6,7,8],  
     [2,4,6,8]]  
  
result = [[0,0,0,0],
```

```

        [0,0,0,0],
        [0,0,0,0]]

for i in range(len(A)):

    for j in range(len(B[0])):

        for k in range(len(B)):
            result[i][j] += A[i][k] * B[k][j]
print(result)
print('Multiplied Matrix:')
for r in result:
    print(r)

```

```

[[17, 26, 35, 44], [41, 62, 83, 104], [65, 98, 131, 164]]
Multiplied Matrix:
[17, 26, 35, 44]
[41, 62, 83, 104]
[65, 98, 131, 164]

```

```

[9]: #make the dictionary as key is charcter and value is the count of character in_
      ↪ string.after print
      #first five max repeated character
s="avbgkbhjd yfbckbvdfgbybncv h bvhcvbmnbvcxasdfghjklpoiuytrewq hjujnbvawdp scmsbndysnvnbnvbnfddnbjv"
d={}
for i in s:
    d[i]=d.get(i,0)+1
#print(d)
k=sorted(d.items(),key=lambda x:x[1],reverse=True )
#print(k)
print("first five max repeated character")
for i in range(0,5):
    print(k[i])

```

```

first five max repeated character
('b', 14)
('v', 10)
('n', 8)
('d', 7)
('h', 5)

```

31 Q. Repeatedly ask the user to enter a team name and how many games the team has won and how many they lost. Store this information in a dictionary where the keys are the team names and the values are a list of the form [wins, losses].

- (i) using the dictionary created above, allow the user to enter a team name and print out the team's winning percentage.
- (ii) using dictionary create a list whose entries are the number of wins for each team.
- (iii) using the dictionary, create a list of all those teams that have winning records.

```
[10]: dic = {}
lstwin = []
lstrec = []
while True :
    name = input ("Enter the name of team (enter q for quit)= ")
    if name == "Q" or name == "q" :
        print()
        break
    else :
        win = int (input("Enter the no.of win match = "))
        loss = int(input("Enter the no.of loss match = "))
        print()
        dic [ name ] = [ win , loss ]
        lstwin += [ win ]
        if win > 0 :
            lstrec += [ name ]

nam = input ("Enter the name of team For Winning = ")
print ("Winning percentage = ",dic [ nam ][0] *100 / (dic [nam ][0] + dic[nam_
↵][1] ))
print()
print("Winning list of all team = ",lstwin)
print("Team who has winning records are ",lstrec)
```

```
Enter the name of team (enter q for quit)= nhm
Enter the no.of win match = 8
Enter the no.of loss match = 2
```

```
Enter the name of team (enter q for quit)= nhj
Enter the no.of win match = 7
Enter the no.of loss match = 5
```

```
Enter the name of team (enter q for quit)= q
```

```
Enter the name of team For Winning = nhm
Winning percentage = 80.0
```

Winning list of all team = [8, 7]
Team who has winning records are ['nhm', 'nhj']

32 Write a Python function that accepts a string and calculate the number of upper case letters and lower case letters.

```
[11]: #Write a Python function that accepts a string and calculate the number of  
      ↪upper case letters and lower case letters.
```

```
def up_low(string):  
    uppers = 0  
    lowers = 0  
    for char in string:  
        if char.islower():  
            lowers += 1  
        elif char.isupper():  
            uppers +=1  
  
    return(uppers, lowers)  
  
print(up_low('Hello Mr. Rogers, how are you this fine Tuesday?'))
```

(4, 33)

33 Use a list comprehension to produce a list that consists of all palindromic numbers between 100 and 1000.

```
[12]: L=[i for i in range(100,1001) if str(i)==str(i)[::-1]]  
      print(L)
```

[101, 111, 121, 131, 141, 151, 161, 171, 181, 191, 202, 212, 222, 232, 242, 252,
262, 272, 282, 292, 303, 313, 323, 333, 343, 353, 363, 373, 383, 393, 404, 414,
424, 434, 444, 454, 464, 474, 484, 494, 505, 515, 525, 535, 545, 555, 565, 575,
585, 595, 606, 616, 626, 636, 646, 656, 666, 676, 686, 696, 707, 717, 727, 737,
747, 757, 767, 777, 787, 797, 808, 818, 828, 838, 848, 858, 868, 878, 888, 898,
909, 919, 929, 939, 949, 959, 969, 979, 989, 999]

- 34 Write a program that converts Roman numerals into ordinary numbers. Here are the conversions: M=1000, D=500, C=100, L=50, X=10, V=5 I=1. Don't forget about things like IV being 4 and XL being 40.
- 35 Write a program that converts ordinary numbers into Roman numerals

```
[1]: def romanToInt(s):  
    """  
    :type s: str  
    :rtype: int  
    """  
    roman = {'I':1, 'V':5, 'X':10, 'L':50, 'C':100, 'D':500, 'M':1000, 'IV':4, 'IX':  
↪9, 'XL':40, 'XC':90, 'CD':400, 'CM':900}  
    i = 0  
    num = 0  
    while i < len(s):  
        if i+1<len(s) and s[i:i+2] in roman:  
            num+=roman[s[i:i+2]]  
            i+=2  
        else:  
            num+=roman[s[i]]  
            i+=1  
    return num  
s=input("Enter number in Roman: ")  
print(romanToInt(s))
```

Enter number in Roman: LVIII
58

```
[14]: def int_to_Roman(num):  
    val = [  
        1000, 900, 500, 400,  
        100, 90, 50, 40,  
        10, 9, 5, 4,  
        1  
    ]  
    syb = [  
        "M", "CM", "D", "CD",  
        "C", "XC", "L", "XL",  
        "X", "IX", "V", "IV",  
        "I"  
    ]  
    roman_num = ''  
    i = 0
```

```

        while num > 0:
            for j in range(num // val[i]):
                roman_num += syb[i]
                num -= val[i]
            i += 1
        return roman_num
num=int(input("Input an integer: "))
print(int_to_Roman(num))

```

Input an integer: 58
LVIII

36 Create a 5×5 list of numbers. Then write a program that creates a dictionary whose keys are the numbers and whose values are the how many times the number occurs. Then print the three most common numbers.

```

[15]: L=[[5, 3, 3, 5, 5],
        [3, 2, 4, 3, 3],
        [3, 3, 3, 3, 4],
        [3, 4, 5, 3, 3],
        [5, 4, 1, 2, 3]]
d={}
for i in range(len(L)):
    for j in L[i]:
        d[j]=d.get(j,0)+1
print(d)
L1=[]
for i,j in d.items():
    L1.append([j,i])
L1.sort()
L1.reverse()
L2=[]
for i in range(3):
    print(L1[i][1], 'comes', L1[i][0], 'times in a 5x5 list')
    L2.append(L1[i][1])
print('Three most common numbers in 5x5 list are', L2)

```

```

{5: 5, 3: 13, 2: 2, 4: 4, 1: 1}
3 comes 13 times in a 5x5 list
5 comes 5 times in a 5x5 list
4 comes 4 times in a 5x5 list
Three most common numbers in 5x5 list are [3, 5, 4]

```

- 37 Given an integer value, return a string with the equivalent English text of each digit. For example, an input of 89 results in “eighty-nine” being returned. Restrict values to be between 0 and 1,000.

```
[2]: """Given an int32 number, print it in English."""
def int_to_en(num):
    d = { 0 : 'zero', 1 : 'one', 2 : 'two', 3 : 'three', 4 : 'four', 5 : 'five',
          6 : 'six', 7 : 'seven', 8 : 'eight', 9 : 'nine', 10 : 'ten',
          11 : 'eleven', 12 : 'twelve', 13 : 'thirteen', 14 : 'fourteen',
          15 : 'fifteen', 16 : 'sixteen', 17 : 'seventeen', 18 : 'eighteen',
          19 : 'nineteen', 20 : 'twenty',
          30 : 'thirty', 40 : 'forty', 50 : 'fifty', 60 : 'sixty',
          70 : 'seventy', 80 : 'eighty', 90 : 'ninety' }
    k = 1000

    assert(0 <= num)

    if (num < 20):
        return d[num]

    if (num < 100):
        if num % 10 == 0: return d[num]
        else: return d[num // 10 * 10] + '-' + d[num % 10]

    if (num < k):
        if num % 100 == 0: return d[num // 100] + ' hundred'
        else: return d[num // 100] + ' hundred and ' + int_to_en(num % 100)

    print(int_to_en(200))
```

two hundred

- 38 Given an integer value, return a string with the equivalent English text of each digit. For example, an input of 89 results in “eighty-nine” being returned. Restrict values to be between 0 and 10^{15} .

```
[16]: def int_to_en(num):
    d = { 0 : 'zero', 1 : 'one', 2 : 'two', 3 : 'three', 4 : 'four', 5 : 'five',
          6 : 'six', 7 : 'seven', 8 : 'eight', 9 : 'nine', 10 : 'ten',
          11 : 'eleven', 12 : 'twelve', 13 : 'thirteen', 14 : 'fourteen',
          15 : 'fifteen', 16 : 'sixteen', 17 : 'seventeen', 18 : 'eighteen',
          19 : 'nineteen', 20 : 'twenty',
          30 : 'thirty', 40 : 'forty', 50 : 'fifty', 60 : 'sixty',
```

```

        70 : 'seventy', 80 : 'eighty', 90 : 'ninety' }
k = 1000
m = k * 1000
b = m * 1000
t = b * 1000

if (num < 20):
    return d[num]

if (num < 100):
    if num % 10 == 0:
        return d[num]
    else:
        return d[num // 10 * 10] + '-' + d[num % 10]

if (num < k):
    if num % 100 == 0:
        return d[num // 100] + ' hundred'
    else:
        return d[num // 100] + ' hundred and ' + int_to_en(num % 100)

if (num < m):
    if num % k == 0:
        return int_to_en(num // k) + ' thousand'
    else:
        return int_to_en(num // k) + ' thousand, ' + int_to_en(num % k)

if (num < b):
    if (num % m) == 0:
        return int_to_en(num // m) + ' million'
    else:
        return int_to_en(num // m) + ' million, ' + int_to_en(num % m)

if (num < t):
    if (num % b) == 0:
        return int_to_en(num // b) + ' billion'
    else:
        return int_to_en(num // b) + ' billion, ' + int_to_en(num % b)

if (num >= t):
    if (num % t == 0):
        return int_to_en(num // t) + ' trillion'
    else:
        return int_to_en(num // t) + ' trillion, ' + int_to_en(num % t)
num=int(input("Enter any positive integer: "))
print(int_to_en(num))

```

Enter any positive integer: 3669478521369427

three thousand, six hundred and sixty-nine trillion, four hundred and seventy-eight billion, five hundred and twenty-one million, three hundred and sixty-nine thousand, four hundred and twenty-seven

38.1 Write a Python program to count the number of strings where the string length is 2 or more and the first and last character are same from a given list of strings.

Example: Input: ['abc', 'xyz', 'aba', '1221']

Output: 2

```
[10]: def match_words(words):
    ctr = 0

    for word in words:
        if len(word) > 1 and word[0] == word[-1]:
            ctr += 1
    return ctr

print(match_words(['abc', 'xyz', 'aba', '1221']))
```

2

38.2 Find the indices of all occurrences of target in the uneven matrix

38.3 An irregular/uneven matrix, or ragged matrix, is a matrix that has a different number of elements in each row. Ragged matrices are not used in linear algebra, since standard matrix transformations cannot be performed on them, but they are useful as arrays in computing.

38.4 Write a Python program to find the indices of all occurrences of target in the uneven matrix.

Input: [[1, 3, 2, 32, 19], [19, 2, 48, 19], [], [9, 35, 4], [3, 19], 19]

Output: [[0, 4], [1, 0], [1, 3], [4, 1]]

Input: [[1, 2, 3, 2], [], [7, 9, 2, 1, 4], 2]

Output: [[0, 1], [0, 3], [2, 2]]

```
[14]: def test(M, T):
    L=[]
    for i,row in enumerate(M):
        for j,k in enumerate(row):
            if k==T:
                L.append([i,j])
    return L

M = [[1, 3, 2, 32, 19], [19, 2, 48, 19], [], [9, 35, 4], [3, 19]]
T = 19
```

```

print("Matrix:")
print(M)
print("Target value:")
print(T)
print("Indices of all occurrences of the target value in the said uneven matrix:
↪")
print(test(M,T))

```

Matrix:

```
[[1, 3, 2, 32, 19], [19, 2, 48, 19], [], [9, 35, 4], [3, 19]]
```

Target value:

```
19
```

Indices of all occurrences of the target value in the said uneven matrix:

```
[[0, 4], [1, 0], [1, 3], [4, 1]]
```

38.5 Write a Python program to find the numbers that are greater than 10 and have odd first and last digits.

Input: [1, 3, 79, 10, 4, 1, 39, 62]

Output: [79, 39]

Input: [11, 31, 77, 93, 48, 1, 57]

Output: [11, 31, 77, 93, 57]

```

[19]: def test(nums):
        L=[]
        for i in nums:
            if i>10:
                if int(str(i)[len(str(i))-1])%2==1 and int(str(i)[0]) % 2==1:
                    L.append(i)
        return L

nums = [1, 3, 79, 10, 4, 1, 39]
print("Original list of numbers:")
print(nums)
print("Numbers of the said array that are greater than 10 and have odd first_
↪and last digits:")
print(test(nums))

```

Original list of numbers:

```
[1, 3, 79, 10, 4, 1, 39]
```

Numbers of the said array that are greater than 10 and have odd first and last digits:

```
[79, 39]
```

38.6 Write a Python program to shift the decimal digits n places to the left, wrapping the extra digits around. If $\text{shift} >$ the number of digits of n , reverse the string.

```
[21]: def test(n, shift):
        s = str(n)
        if shift > len(s):
            return s[::-1]
        return s[shift:] + s[:shift]

print("Shift the decimal digits n places to the left. If shift > the number of_
↳digits of n, reverse the string.:")

n = 12345
shift = 1
print("\nn =",n," and shift =",shift)
print("Result = ",test(n, shift))
n = 12345
shift = 2
print("\nn =",n," and shift =",shift)
print("Result = ",test(n, shift))
n = 12345
shift = 3
print("\nn =",n," and shift =",shift)
print("Result = ",test(n, shift))
n = 12345
shift = 5
print("\nn =",n," and shift =",shift)
print("Result = ",test(n, shift))
n = 12345
shift = 7
print("\nn =",n," and shift =",shift)
print("Result = ",test(n, shift))
```

Shift the decimal digits n places to the left. If $\text{shift} >$ the number of digits of n , reverse the string.:

$n = 12345$ and $\text{shift} = 1$
Result = 23451

$n = 12345$ and $\text{shift} = 2$
Result = 34512

$n = 12345$ and $\text{shift} = 3$
Result = 45123

$n = 12345$ and $\text{shift} = 5$
Result = 12345

n = 12345 and shift = 7
Result = 54321

38.7 write a Python program to create a list containing that number in between each pair of adjacent numbers.

Input: [12, -7, 3, -89, 14, 88, -78, -1, 2, 7]

Separator: 6

Output: [12, 6, -7, 6, 3, 6, -89, 6, 14, 6, 88, 6, -78, 6, -1, 6, 2, 6, 7]

Input: [1, 2, 3, 4, 5, 6]

Separator: 9

Output: [1, 9, 2, 9, 3, 9, 4, 9, 5, 9, 6]

```
[25]: def test(nums, sep):
        L=[]
        for i in range(len(nums)):
            if i==len(nums)-1:
                L.append(nums[i])
            else:
                L.append(nums[i])
                L.append(sep)
        return L
nums = [12, -7, 3, -89, 14, 88, -78, -1, 2, 7]
separator = 6
print("List of numbers:",nums)
print("Separator:",separator)
print("Inject the separator in between each pair of adjacent numbers of the_
↪said list:")
print(test(nums,separator))
```

List of numbers: [12, -7, 3, -89, 14, 88, -78, -1, 2, 7]

Separator: 6

Inject the separator in between each pair of adjacent numbers of the said list:

[12, 6, -7, 6, 3, 6, -89, 6, 14, 6, 88, 6, -78, 6, -1, 6, 2, 6, 7]

38.8 Write a Python program to start with a list of integers, keep every other element in place and otherwise sort the list.

Input: [2, 5, 6, 3, 1, 4, 34]

Output: [1, 5, 2, 3, 6, 4, 34]

Input: [8, 0, 7, 2, 9, 4, 1, 2, 8, 3]

Output: [1, 0, 7, 2, 8, 4, 8, 2, 9, 3]

```
[33]: nums=[8, 0, 7, 2, 9, 4, 1, 2, 8, 3]
      L1=nums[::2]
      L2=nums[1::2]
      L1.sort()
      L=[]
      for i in range(len(L1)):
          if len(L1)==len(L2):
              L.append(L1[i])
              L.append(L2[i])
          else:
              L.append(L1[i])
      print(L)
```

[1, 0, 7, 2, 8, 4, 8, 2, 9, 3]

38.9 Write a Python program to get the single digits in numbers sorted backwards and converted to English words.

Input: [1, 3, 4, 5, 11]

Output: ['five', 'four', 'three', 'one']

Input: [27, 3, 8, 5, 1, 31]

Output: ['eight', 'five', 'three', 'one']

```
[40]: def test(nums):
      digits = {None: 'zero', 1: 'one', 2: 'two', 3: 'three', 4: 'four', 5: 'five', 6: 'six', 7: 'seven', 8: 'eight', 9: 'nine'}
      nums.sort()
      L=[digits[i] for i in nums if i>=0 and i<10]
      L.reverse()
      print(L)
      nums= [27, 3, 8, 5, 1, 31]
      test(nums)
```

['eight', 'five', 'three', 'one']

38.10 Write a Python program to find the following strange sort of list of numbers: the first element is the smallest, the second is the largest of the remaining, the third is the smallest of the remaining, the fourth is the smallest of the remaining, etc.

Input: [1, 3, 4, 5, 11]

Output: [1, 11, 3, 5, 4]

Input: [27, 3, 8, 5, 1, 31]

Output: [1, 31, 3, 27, 5, 8]

Input: [1, 2, 7, 3, 4, 5, 6]

Output: [1, 7, 2, 6, 3, 5, 4]

```
[44]: nums = eval(input("Enter list: "))
temp=nums.copy()
L=[]
i=0
while i<len(temp):
    if i%2==0:
        L.append(min(nums))
        nums.remove(min(nums))
        i+=1
    else:
        L.append(max(nums))
        nums.remove(max(nums))
        i+=1
print(L)
```

Enter list: [27, 3, 8, 5, 1, 31]

[1, 31, 3, 27, 5, 8]

38.11 Write a Python program to find four positive even integers whose sum is a given integer.

Input: n = 100

Output: [94, 2, 2, 2]

Input: n = 1000

Output: [994, 2, 2, 2]

Input: n = 10000

Output: [9994, 2, 2, 2]

Input: n = 1234567890

Output: [1234567884, 2, 2, 2]

```
[49]: def test(n):
    for a in range(n, 0, -1):
        if a % 2 != 0:
            continue
        for b in range(n - a, 0, -1):
            if b % 2 != 0:
                continue
            for c in range(n - b - a, 0, -1):
                if c % 2 != 0:
                    continue
                for d in range(n - b - c - a, 0, -1):
                    if d % 2 != 0:
                        continue
```

```

        if a + b + c + d == n:
            return [a, b, c, d]

n = int(input("Enter a number"))
print("Four positive even integers whose sum is",n)
print(test(n))

```

Enter a number1234567890

Four positive even integers whose sum is 1234567890

[1234567884, 2, 2, 2]

38.12 Write a python program to implement linear search.

Linear search is a method of finding elements within a list. It is also called a sequential search. It is the simplest searching algorithm because it searches the desired element in a sequential manner. It compares each and every element with the value that we are searching for. If both are matched, the element is found, and the algorithm returns the key's index position.

```

[50]: def linearsearch(arr, x):
        for i in range(len(arr)):
            if arr[i] == x:
                return i
        return -1
arr = ['t','u','t','o','r','i','a','l']
x = 'a'
print("element found at index "+str(linearsearch(arr,x)))

```

element found at index 6

38.13 Find three numbers from an array such that the sum of three numbers equal to zero

```

[51]: # return a list of lists of length 3
def three_Sum(num):
    if len(num)<3:
        return []
    num.sort()
    result=[]
    for i in range(len(num)-2):
        left=i+1
        right=len(num)-1
        if i!=0 and num[i]==num[i-1]:
            continue
        while left<right:
            if num[left]+num[right]==-num[i]:
                result.append([num[i],num[left],num[right]])
                left=left+1
                right=right-1

```

```

        while num[left]==num[left-1] and left<right:left=left+1
        while num[right]==num[right+1] and left<right: right=right-1
    elif num[left]+num[right]<-num[i]:
        left=left+1
    else:
        right=right-1
    return result

nums1=[-1,0,1,2,-1,-4]
nums2 = [-25,-10,-7,-3,2,4,8,10]
print(three_Sum(nums1))
print(three_Sum(nums2))

```

```

[[-1, -1, 2], [-1, 0, 1]]
[[-10, 2, 8], [-7, -3, 10]]

```

38.14 Write a python program to check a sequence of numbers is a geometric progression or not.

```

[53]: def is_geometric(li):
        if len(li) <= 1:
            return True
        # Calculate ratio
        ratio = li[1]/(li[0])
        # Check the ratio of the remaining
        for i in range(1, len(li)):
            if li[i]/(li[i-1]) != ratio:
                return False
        return True

print(is_geometric([2, 6, 18, 54]))

print(is_geometric([10, 5, 2.5, 1.25]))

print(is_geometric([5, 8, 9, 11]))

```

```

True
True
False

```

```

[4]: def mirrorChars(input,k):
        # create dictionary
        original = 'abcdefghijklmnopqrstuvwxyz'
        reverse = 'zyxwvutsrqponmlkjihgfedcba'
        dictChars = {}
        for i in range(len(original)):
            dictChars[original[i]]=reverse[i]

```



```

# separate out string after length k to change
# characters in mirror
prefix = input[0:k-1]
suffix = input[k-1:]
mirror = ''
# change into mirror
for i in range(0,len(suffix)):
    mirror = mirror + dictChars[suffix[i]]
# concat prefix and mirrored part
print (prefix+mirror)

input = 'ljietengx'
k = 3
mirrorChars(input,k)

```

ljrvgvmtc

```

[5]: test_dict = {'Gfg' : {'a' : 7, 'b' : 9, 'c' : 12},
'is' : {'a' : 15, 'b' : 19, 'c' : 20},
'best' : {'a' : 5, 'b' : 10, 'c' : 2}}
# printing original dictionary
print("The original dictionary is : " + str(test_dict))
# initializing key
temp = "c"
# using keys() and values() to extract values
res = [sub[temp] for sub in test_dict.values() if temp in sub.keys()]
# printing result
print("The extracted values : " + str(res))

```

The original dictionary is : {'Gfg': {'a': 7, 'b': 9, 'c': 12}, 'is': {'a': 15, 'b': 19, 'c': 20}, 'best': {'a': 5, 'b': 10, 'c': 2}}

The extracted values : [12, 20, 2]

```

[7]: def Convert(tup, di):
    for a, b in tup:
        di.setdefault(a, []).append(b)
    return di
tups = [("akash", 10), ("gaurav", 12), ("anand", 14),
("suraj", 20), ("akhil", 25), ("ashish", 30)]
dictionary = {}
print (Convert(tups, dictionary))

```

{'akash': [10], 'gaurav': [12], 'anand': [14], 'suraj': [20], 'akhil': [25], 'ashish': [30]}

[]: