Git Cheat Sheet

GIT BASICS

`git init <directory>`	Create empty Git repo in specified directory. Run with no arguments to initialize the current directory as a git repository.
`git clone <repo>`	Clone repo located at `<repo>` onto local machine. Original repo can be located on the local filesystem or on a remote machine via `HTTP` or `SSH`.
`git config user.name <name>`	Define author name to be used for all commits in current repo. Devs commonly use `--global` flag to set config options for current user.
`git add <directory>`	Stage all changes in `<directory>` for the next commit. Replace `<directory>` with a `<file>` to change a specific file.
`git commit -m "<message>"`	Commit the staged snapshot, but instead of launching a text editor, use `<message>` as the commit message.
`git status`	List which files are staged, unstaged, and untracked.
`git log`	Display the entire commit history using the default format. For customization see additional options.
`git diff`	Show unstaged changes between your index and working directory.

UNDOING CHANGES

`git revert <commit>`	Create new commit that undoes all of the changes made in `<commit>`, then apply it to the current branch.
`git reset <file>`	Remove `<file>` from the staging area, but leave the working directory unchanged. This unstages a file without overwriting any changes.
`git clean -n`	Shows which files would be removed from working directory. Use the `-f` flag in place of the `-n` flag to execute the clean.

REWRITING GIT HISTORY

`git commit --amend`	Replace the last commit with the staged changes and last commit combined. Use with nothing staged to edit the last commit's message.
`git rebase <base>`	Rebase the current branch onto `<base>`. `<base>` can be a commit ID, branch name, a tag, or a relative reference to `HEAD`.
`git reflog`	Show a log of changes to the local repository's `HEAD`. Add `--relative-date` flag to show date info or `--all` to show all refs.

GIT BRANCHES

`git branch`	List all of the branches in your repo. Add a `<branch>` argument to create a new branch with the name `<branch>`.
`git checkout -b <branch>`	Create and check out a new branch named `<branch>`. Drop the `-b` flag to checkout an existing branch.
`git merge <branch>`	Merge `<branch>` into the current branch.

REMOTE REPOSITORIES

`git remote add <name> <url>`	Create a new connection to a remote repo. After adding a remote, you can use `<name>` as a shortcut for `<url>` in other commands.
`git fetch <remote> <branch>`	Fetches a specific `<branch>`, from the repo. Leave off `<branch>` to fetch all remote refs.
`git pull <remote>`	Fetch the specified remote's copy of current branch and immediately merge it into the local copy.
`git push <remote> <branch>`	Push the branch to `<remote>`, along with necessary commits and objects. Creates named branch in the remote repo if it doesn't exist.

Additional Options +

GIT CONFIG

`git config --global user.name <name>`	Define the author name to be used for all commits by the current user.
`git config --global user.email <email>`	Define the author email to be used for all commits by the current user.
`git config --global alias. <alias-name> <git-command>`	Create shortcut for a Git command. E.g. `alias.glog "log --graph --oneline"` will set `"git glog"` equivalent to `"git log --graph --oneline.`
`git config --system core.editor <editor>`	Set text editor used by commands for all users on the machine. `<editor>` arg should be the command that launches the desired editor (e.g., vi).
`git config --global --edit`	Open the global configuration file in a text editor for manual editing.

GIT LOG

`git log -<limit>`	Limit number of commits by `<limit>`. E.g. `"git log -5"` will limit to 5 commits.
`git log --oneline`	Condense each commit to a single line.
`git log -p`	Display the full diff of each commit.
`git log --stat`	Include which files were altered and the relative number of lines that were added or deleted from each of them.
`git log --author= "<pattern>"`	Search for commits by a particular author.
`git log --grep="<pattern>"`	Search for commits with a commit message that matches `<pattern>`.
`git log <since>..<until>`	Show commits that occur between `<since>` and `<until>`. Args can be a commit ID, branch name, `HEAD`, or any other kind of revision reference.
`git log -- <file>`	Only display commits that have the specified file.
`git log --graph --decorate`	`--graph` flag draws a text based graph of commits on left side of commit msgs. `--decorate` adds names of branches or tags of commits shown.

GIT DIFF

`git diff HEAD`	Show difference between working directory and last commit.
`git diff --cached`	Show difference between staged changes and last commit

GIT RESET

`git reset`	Reset staging area to match most recent commit, but leave the working directory unchanged.
`git reset --hard`	Reset staging area and working directory to match most recent commit and **overwrites all changes** in the working directory.
`git reset <commit>`	Move the current branch tip backward to `<commit>`, reset the staging area to match, but leave the working directory alone.
`git reset --hard <commit>`	Same as previous, but resets both the staging area & working directory to match. **Deletes** uncommitted changes, and **all commits after** `<commit>`.

GIT REBASE

`git rebase -i <base>`	Interactively rebase current branch onto `<base>`. Launches editor to enter commands for how each commit will be transferred to the new base.

GIT PULL

`git pull --rebase <remote>`	Fetch the remote's copy of current branch and rebases it into the local copy. Uses git rebase instead of merge to integrate the branches.

GIT PUSH

`git push <remote> --force`	Forces the `git push` even if it results in a non-fast-forward merge. Do not use the `--force` flag unless you're absolutely sure you know what you're doing.
`git push <remote> --all`	Push all of your local branches to the specified remote.
`git push <remote> --tags`	Tags aren't automatically pushed when you push a branch or use the `--all` flag. The `--tags` flag sends all of your local tags to the remote repo.