

# Arbeidskrav 1

34

## Quarto

Quarto enables you to weave together content and executable code into a finished document. To learn more about Quarto see <https://quarto.org>.

## Running Code

When you click the **Render** button a document will be generated that includes both content and the output of embedded code. You can embed code like this:

```
rm(list=ls())  
library(tidyverse)
```

```
-- Attaching packages ----- tidyverse 1.3.2 --  
v ggplot2 3.4.0      v purrr   1.0.1  
v tibble  3.1.8      v dplyr   1.1.0  
v tidyr   1.3.0      v stringr 1.5.0  
v readr   2.1.3      v forcats 1.0.0  
-- Conflicts ----- tidyverse_conflicts() --  
x dplyr::filter() masks stats::filter()  
x dplyr::lag()    masks stats::lag()
```

```
library(readxl)  
library(zoo)
```

Attaching package: 'zoo'

The following objects are masked from 'package:base':

```
as.Date, as.Date.numeric
```

```
# I use import dataset from excel and copy the code preview.
```

```
low_trop <- read_excel("C:/Users/47911/Desktop/SAMFUNNS ØKONOMI/SOK 1005 - Datavitenskap/L  
  col_names = FALSE, col_types = c("skip", "numeric", "numeric",  
    "numeric", "skip", "skip",  
    "skip", "skip", "skip",  
    "skip", "skip", "skip",  
    "skip", "skip", "skip",  
    "skip", "skip", "skip",  
    "skip", "skip", "skip",  
    "skip", "skip", "skip"),  
  skip = 2, n_max = 529)
```

New names:

```
* `` -> `...1`  
* `` -> `...2`  
* `` -> `...3`
```

```
# I use import dataset from excel and copy the code preview.
```

```
mid_trop <- read_excel("C:/Users/47911/Desktop/SAMFUNNS ØKONOMI/SOK 1005 - Datavitenskap/M  
  col_names = FALSE, col_types = c("skip", "numeric", "numeric",  
    "numeric", "skip", "skip",  
    "skip", "skip", "skip",  
    "skip", "skip", "skip",  
    "skip", "skip", "skip",  
    "skip", "skip", "skip",  
    "skip", "skip", "skip",  
    "skip", "skip", "skip"),  
  skip = 2, n_max = 529)
```

New names:

```
* `` -> `...1`
```

```
* `` -> `...2`
* `` -> `...3`
```

```
# I use import dataset from excel and copy the code preview.
```

```
tropop <- read_excel("C:/Users/47911/Desktop/SAMFUNNS ØKONOMI/SOK 1005 - Datavitenskap/Tro
  col_names = FALSE, col_types = c("skip", "numeric", "numeric",
    "numeric", "skip", "skip",
    "skip", "skip", "skip",
    "skip", "skip", "skip",
    "skip", "skip", "skip",
    "skip", "skip", "skip",
    "skip", "skip", "skip",
    "skip", "skip", "skip"),
  skip = 2, n_max = 529)
```

New names:

```
* `` -> `...1`
* `` -> `...2`
* `` -> `...3`
```

```
# I use import dataset from excel and copy the code preview.
```

```
low_strat <- read_excel("C:/Users/47911/Desktop/SAMFUNNS ØKONOMI/SOK 1005 - Datavitenskap/
  col_names = FALSE, col_types = c("skip", "numeric", "numeric",
    "numeric", "skip", "skip",
    "skip", "skip", "skip",
    "skip", "skip", "skip",
    "skip", "skip", "skip",
    "skip", "skip", "skip",
    "skip", "skip", "skip",
    "skip", "skip", "skip"),
  skip = 2, n_max = 529)
```

New names:

```
* `` -> `...1`
```

```
* `` -> `...2`  
* `` -> `...3`
```

```
# I rename every column to make the dataframes readable.
```

```
low_trop <- rename(low_trop, year = "...1", month = "...2", globe = "...3")  
mid_trop <- rename(mid_trop, year = "...1", month = "...2", globe = "...3")  
tropop <- rename(tropop, year = "...1", month = "...2", globe = "...3")  
low_strat <- rename(low_strat, year = "...1", month = "...2", globe = "...3")
```

```
# Code found at: https://stackoverflow.com/questions/39420136/combine-separate-year-and-month-into-a-date-column  
# I use the 'year' and 'month' columns to make a 'date' column.
```

```
low_trop$date <- as.yearmon(paste(low_trop$year, low_trop$month), "%Y %m")  
mid_trop$date <- as.yearmon(paste(mid_trop$year, mid_trop$month), "%Y %m")  
tropop$date <- as.yearmon(paste(tropop$year, tropop$month), "%Y %m")  
low_strat$date <- as.yearmon(paste(low_strat$year, low_strat$month), "%Y %m")
```

```
# Code found at: https://www.statology.org/rolling-average-in-r/  
# I use 'rollmean' to create the mean of each dataframe and specify the start of the calculation
```

```
low_trop$mean <- rollmean(low_trop$globe, 13, fill=NA, align='right')  
mid_trop$mean <- rollmean(mid_trop$globe, 13, fill=NA, align='right')  
tropop$mean <- rollmean(tropop$globe, 13, fill=NA, align='right')  
low_strat$mean <- rollmean(low_strat$globe, 13, fill=NA, align='right')
```

```
# I create the average of the four dataframes.
```

```
average <- low_trop$mean+mid_trop$mean+tropop$mean+low_strat$mean/4
```

```
# I use the 'year' and 'month' columns to make a 'date' value to add to the dataframe for
```

```
avg_date <- as.yearmon(paste(low_trop$year, low_trop$month), "%Y %m")
```

```
# I create a dataframe
```

```
avg <- data.frame(avg_date, average)
```

```
# I plot all the mean's and the average from the dataframes into a plot, and give each line
ggplot() +
  geom_line(data=low_trop, aes(x = date, y = mean, color = "Lower Troposphere"), size = 0.71) +
  geom_line(data=mid_trop, aes(x = date, y = mean, color = "Mid-Troposphere"), size = 0.71) +
  geom_line(data=tropop, aes(x = date, y = mean, color = "Tropopause"), size = 0.71) +
  geom_line(data=low_strat, aes(x = date, y = mean, color = "Lower Stratosphere"), size = 0.71) +
  geom_line(data=avg, aes(x = avg_date, y = average, color = "Average"), size = 0.71) +
  labs (title = "Mean and average of temperature in the atmosphere", y = "Temperature", x = "Date") +
  theme_bw()
```

Warning: Using `size` aesthetic for lines was deprecated in ggplot2 3.4.0.  
 i Please use `linewidth` instead.

Warning: Removed 12 rows containing missing values (`geom\_line()`).  
 Removed 12 rows containing missing values (`geom\_line()`).  
 Removed 12 rows containing missing values (`geom\_line()`).  
 Removed 12 rows containing missing values (`geom\_line()`).  
 Removed 12 rows containing missing values (`geom\_line()`).

