

Kahoot





Linux Plus for AWS and DevOps

Session - 7






Table of Contents



- Loops
- Functions





While loops

```
while [[ <some test> ]]
do
     <commands>
done
```

```
#!/bin/bash

number=1

while [[ $number -le 10 ]]

do
  echo $number
  ((number++))

done
echo "Now, number is $number"
```

```
$./while-loops.sh
5
8
10
Now, number is 11
```



Until loops

```
until [[ <some test> ]]
do
     <commands>
done
```

```
#!/bin/bash
number=1

until [[ $number -ge 10 ]]
do
  echo $number
  ((number++))
done
echo "Now, number is $number"
```

```
$./until.sh
1
2
3
4
5
6
7
8
9
Now, number is 10
```



For loops

```
for item in [list]
do
   commands
done
```

```
#!/bin/sh
echo "Numbers:"

for number in 0 1 2 3 4 5 6 7 8 9
do
   echo $number
done
```

```
$./for-loop.sh
Numbers:
0
2
5
6
8
9
```



Continue and Break Statement



Infinite loop

```
#!/bin/bash

number=1

until [[ $number -lt 1 ]]

do
  echo $number
  ((number++))

done
echo "Now, number is $number"
```



Continue and Break Statement



Break Statement

```
number=1
until [[ $number -lt 1 ]]
do
 echo $number
 if [[ $number -eq 10 ]]
   break
done
```

```
./infinite-loop.sh
1
2
3
4
5
6
7
8
```



Continue and Break Statement



Continue Statement

```
number=1
until [[ $number -lt 1 ]]
do
  tens=$(($number % 10))
 if [[ $tens -eq 0 ]]
 echo $number
 if [[ $number -gt 14 ]]
   break
```

```
$./continue.sh
3
5
6
8
9
12
13
14
15
```



Exercise 1



- 1. Calculate sum of the numbers between 1 to 100.
- 2. Print result.



Exercise 2



- 1. Ask user to input multiple names in a single line
- 2. Print "Hello" message for each name in separate lines.



Functions



```
function function_name () {
  commands
}
```

```
#!/bin/bash

Welcome () {
   echo "Welcome to Linux Lessons"
}
Welcome
```





Passing Arguments to Functions

```
#!/bin/bash

Welcome () {
    echo "Welcome to Linux Lessons
$1 $2 $3"
}
Welcome Joe Matt Timothy
```

Output:

\$./functions.sh
Welcome to Linux Lessons Joe Matt Timothy







```
function one () {
 echo "This is from the first
 echo "This is from the second
function one
```

Output:

\$./nested.function.sh
This is from the first function
This is from the second function





Variables Scope

```
#!/bin/bash
var1='global 1'
var2='global 2'
var scope () {
 local var1='function 1'
var2='function 2'
 echo -e "Inside function:\nvar1: $var1\nvar2: $var2"
echo -e "Before calling function:\nvar1: $var1\nvar2: $var2"
var scope
echo -e "After calling function:\nvar1: $var1\nvar2: $var2"
```

Local variable

local variable_name=value

Output:

Before calling function:

var1: global 1

var2: global 2

Inside function:

var1: function 1

var2: function 2

After calling function:

var1: global 1

var2: function 2



Functions

Local variable

local variable_name=value

```
#!/bin/bash
num1=5
function add_one(){
        local num2=1
        echo "Total $(( $num1 + $num2 ))"
add_one
echo "Number1: $num1"
echo "Number2: $num2"
```

```
[[ec2-user@ip-172-31-91-206 ~]$ ./cmd.sh
Total 6
Number1: 5
Number2:
[ec2-user@ip-172-31-91-206 ~]$
```



Exercise 3



1. Create a function named **print_age** that accepts one argument

Ask user to input his/her year of birth and store it to local birth_year variable

Calculate **age** using current year value from the first argument

Print age with a message

2. Call **print_age** function with **2025**





THANKS!

Any questions?

