

1928584 - "Start of HostService failed" error - SAPHOSTAGENT start failed

Version	4	Type	SAP Knowledge Base Article
Language	English	Master Language	English
Release Status	Released to Customer	Category	Problem
Component	BC-CCM-HAG (Host Agent)	Released On	29.10.2018

Please find the original document at <https://launchpad.support.sap.com/#/notes/1928584>

Symptom

The SAPHOSTAGENT does not start, the saphostexec service fails to start with the following error messages in the file dev_saphostexec:

```
[Thr 01] *** ERROR => Connection of channel 0 failed
[Thr 01] *** ERROR => Connection of channel 1 failed
...
[Thr 01] *** ERROR => Connection of channel 10 failed
[Thr 01] *** ERROR => Setup of too many communication channels failed. Giving up.
[Thr 01] *** ERROR => Channel Accept failed
[Thr 01] *** ERROR => Start of HostService failed
```

Environment

Unix/Linux OS

Cause

- There is still an old "orphaned" host agent sapstartsrv process running.
- /tmp directory is not writable or filesystem has no free space left.
- The permission of /tmp/.sapstartsrv99_sapstartsrv.log file is incorrect.
- The permissions and ownership of the host agent work directory (DIR_HOME /usr/sap/hostctrl/work) is wrong. host agent work directory is "/usr/sap/hostctrl/work" which defined in host agent profile (/usr/sap/hostctrl/exe/host_profile), DIR_HOME = /usr/sap/hostctrl/work is a mandatory setting, other settings/values are not supported which would also cause this issue.

Resolution

1. Please check the old "orphaned" Host Agent sapstartsrv process and kill them via

```
ps -ef | grep hostctrl
kill -9 <processnumber>
```

And then start saphostagent again via

```
/usr/sap/hostctrl/exe/saphostexec -restart
```

2. Make sure that /tmp directory is writable for the sapadm user and filesystem has free space left.
3. Make sure that permission of /tmp/.sapstartsrv99_sapstartsrv.log file is correct.

-rw-rw-rw- sapadm sapsys .sapstartsrv99_sapstartsrv.log

/tmp/.sapstartsrv99_sapstartsrv.log file is the lock file of /usr/sap/hostctrl/exe/sapstartsrv process, you can also delete wrong permission file (/tmp/.sapstartsrv99_sapstartsrv.log) directly and start saphostagent again.
it will be generated again after saphostagent starting correctly.

4. The ownership and permissions of /usr/sap/hostctrl/work must be kept as created by the host agent installation/upgrade.

The best approach to fix it is by re-installing/upgrading the host agent according to [SAP Note 1031096](#).

Please also refer to [SAP Host Agent Troubleshooting Guide](#) for more information.

Keywords

Host Agent sapstartsrv process saphostexec

This document refers to

SAP Note/KBA	Title
1031096	Installing Package SAPHOSTAGENT
	SAP Host Agent Troubleshooting Guide

Terms of use | Copyright | Trademark | Legal Disclosure | Privacy