

Debug Servers

bashbug.sh [Bash script]
 /bash/bashbug.sh
 Thread[1]
 main: ./bashbug.sh : line 43

Variables Breakpoints Expressions

Name	Value
OPTERR	1
OPTIND	1
OS	Windows_NT
ACTIVE	.

s.sh script.sh bashbug.sh

```
#
# configuration section:
# these variables are filled in by the make target in Make
#
MACHINE="i686"
OS="cygwin"
CC="gcc-4"
CFLAGS=" -DPROGRAM='bash.exe' -DCONF_HOSTTYPE='i686' -DCONF_RELEASE='3.2'
PATCHLEVEL='49'
RELSTATUS='release'
MACHTYPE='i686-pc-cygwin'

PATH=/bin:/usr/bin:/usr/local/bin:$PATH
```

Outline

- if [-x /usr/bin/editor]; then()
- if (uname) >/dev/null 2>&1; then()
- if [-f /usr/lib/sendmail]; then()
- INITIAL_SUBJECT='[50 character or so descrip
- fix for the problem, don't include this section.
- trap " 2# ignore interrupts while in editor()
- while [\$edstat -ne 0]; do()
- if [\$edstat -ne 0]; then()
- case "\$ans" in()
- case "\$CURR_SUB" in()
- case "\$ans" in()
- if cmp -s "\$STEMPFILE1" "\$STEMPFILE2")()
- case "\$ans" in()