DNS Configuration Guide for IT Support

Sender Authentication Setup for **mail.acmecorp.com**

Client / Organization:	Acme Corp	**Target Domain:**	`mail.acmecorp.com`
Initiating Service:	Transactional Notification System	**Date of Request:**	October 28, 2026
Technical Contact:	support@example.com	**Email Provider:**	Scaleway TEM (EU Infrastructure)

1. Purpose & Overview

This document provides the exact DNS records required by **Acme Corp**'s IT Support / Domain Administrator to authorize transactional email delivery from the domain **mail.acmecorp.com**.

To ensure emails (e.g. notifications, invoices, user alerts) arrive reliably in user inboxes without being marked as spam or rejected by major providers (Google, Microsoft 365, Yahoo), domain authentication must be published via **DKIM** (cryptographic signature) and **SPF** (sender authorization), aligned with a **DMARC** policy.

2. Required DNS Records (Summary Table)

Record Type	Host / Name	Value / Destination	TTL
TXT (DKIM)	`scaleway._domainkey.mail.acmecorp.com`	`v=DKIM1; k=rsa; p=MIIBIjANBgkqhkiG9w0BAQEFAAOCAQ8AMIIBCgKCAQEA...[Unique Key Provided via API]...QIDAQAB`	300
TXT (SPF)	`mail.acmecorp.com`	`v=spf1 include:_spf.tem.scaleway.com ~all`	300
TXT (DMARC)	`_dmarc.mail.acmecorp.com`	`v=DMARC1; p=none; rua=mailto:support@example.com;`	300
MX (Return-Path)	`mail.acmecorp.com`	`Priority: 10` `10 mx0.templ.scaleway.com`	300

3. Specific Implementation Notes for IT Staff

Dedicated Subdomain Best Practice
Because **mail.acmecorp.com** is a dedicated sending subdomain, it has its own isolated SPF record. Publish the SPF record directly on this subdomain. This guarantees zero interference with your main corporate email (e.g. Office 365 / Google Workspace).

• **Cloudflare Users:** Ensure the DNS records have Proxy status disabled (**DNS Only / Grey Cloud**). Email records cannot be proxied through Cloudflare CDN.

• **Host Field Formatting:** Depending on your DNS provider (e.g. GoDaddy, Namecheap), the host field may automatically append your domain name. Enter scaleway._domainkey if your manager auto-appends the root domain.

• **TTL Setting:** We recommend setting TTL to **300 seconds (5 minutes)** initially to speed up propagation and verification.

4. How to Verify DNS Propagation

Once published, the IT team can verify propagation using standard command-line tools:

Linux / macOS (dig):

```
dig TXT scaleway._domainkey.mail.acmecorp.com +short
dig TXT mail.acmecorp.com +short
```

Windows PowerShell:

```
Resolve-DnsName -Type TXT scaleway._domainkey.mail.acmecorp.com
Resolve-DnsName -Type TXT mail.acmecorp.com
```