

EXAMEN RA2

1. (6P)

```
pruebaRA2.py X
EXAMEN > pruebaRA2.py > ...
1  from netmiko import ConnectHandler
2
3  lista_ip_routers = [f'192.168.56.{n}' for n in range(106,108)]
4  listaDispositivos = []
5
6  for router in lista_ip_routers:
7      device = {
8          "device_type": "cisco_ios",
9          "host": router,
10         "username": "cisco",
11         "password": "cisco123!",
12     }
13     listaDispositivos.append(device)
14
15     conn = ConnectHandler(**listaDispositivos[0])
16
17     print("Conectado a: ", listaDispositivos[0])
18     print('\nCerrado conexion...')
19     conn.disconnect()
20
21
22     conn = ConnectHandler(**listaDispositivos[1])
23     print("Conectado a: ", listaDispositivos[1])
24     print('\nCerrado conexion...')
25     conn.disconnect()
```

a.

```
PS G:\Mi unidad\Curso 2º GS 25 26\Documents\MARTÍN\ASIR2A\IPCR\RA2> & "C:/Program Files/Python311/python.exe" "g:/Mi un
ASIR2A/IPCR/RA2/EXAMEN/pruebaRA2.py"
● Conectado a... {'device_type': 'cisco_ios', 'host': '192.168.56.106', 'username': 'cisco', 'password': 'cisco123!'}

Cerrando conexión...
Conectado a... {'device_type': 'cisco_ios', 'host': '192.168.56.107', 'username': 'cisco', 'password': 'cisco123!'}

Cerrando conexión...
○ PS G:\Mi unidad\Curso 2º GS 25 26\Documents\MARTÍN\ASIR2A\IPCR\RA2>
```

```
pruebaRA2.py X
EXAMEN > pruebaRA2.py > ...
1  from netmiko import ConnectHandler
2
3  lista_ip_routers = [f'192.168.56.{n}' for n in range(106,108)]
4  listaDispositivos = []
5
6  for router in lista_ip_routers:
7      device = {
8          "device_type": "cisco_ios",
9          "host": router,
10         "username": "cisco",
11         "password": "cisco123!",
12     }
13     listaDispositivos.append(device)
14
15     conn = ConnectHandler(**listaDispositivos[0])
16     nombresRouter = [f'CSR1000v{i}' for i in range(106,108)]
17
18     for nombre in nombresRouter:
19         conn.config_mode()
20
21     conn = ConnectHandler(**listaDispositivos[0])
22     print("Conectado a: ", listaDispositivos[0])
23     print(conn.send_command("show running-config | include hostname"))
24
25     conn.exit_config_mode()
26     print('\nCerrado conexion...')
27     conn.disconnect()
28
29
30     conn = ConnectHandler(**listaDispositivos[1])
31     print("Conectado a: ", listaDispositivos[1])
32     print(conn.send_command("show running-config | include hostname"))
33
34     conn.exit_config_mode()
35     print('\nCerrado conexion...')
36     conn.disconnect()
```

b.

```
PS G:\Mi unidad\Curso 2º GS 25 26\Documents\MARTÍN\ASIR2A\IPCR\RA2> & "C:/Program Files/Python311/python.exe" "g:/Mi un
EXAMEN/pruebaRA2.py"
Conectado a: {'device_type': 'cisco_ios', 'host': '192.168.56.106', 'username': 'cisco', 'password': 'cisco123!'}
hostname CSR1000v106

Cerrado conexion...
Conectado a: {'device_type': 'cisco_ios', 'host': '192.168.56.107', 'username': 'cisco', 'password': 'cisco123!'}
hostname CSR1000v107

Cerrado conexion...
PS G:\Mi unidad\Curso 2º GS 25 26\Documents\MARTÍN\ASIR2A\IPCR\RA2>
```

pruebaRA2.py X

EXAMEN > pruebaRA2.py > ...

```
1  from netmiko import ConnectHandler
2
3  lista_ip_routers = [f'192.168.56.{n}' for n in range(106,108)]
4  listaDispositivos = []
5
6  for router in lista_ip_routers:
7      device = {
8          "device_type": "cisco_ios",
9          "host": router,
10         "username": "cisco",
11         "password": "cisco123!",
12     }
13     listaDispositivos.append(device)
14
15  conn = ConnectHandler(**listaDispositivos[0])
16  nombresRouter = [f'CSR1000v{i}' for i in range(106,108)]
17
18  for nombre in nombresRouter:
19      conn.config_mode()
20
21  conn = ConnectHandler(**listaDispositivos[0])
22  print("Conectado a: ", listaDispositivos[0])
23  print(conn.send_command("show running-config | include hostname"))
24  print(conn.send_command("show ip interface brief"))
25  conn.exit_config_mode()
26  print('\nCerrado conexion...')
27  conn.disconnect()
28
29
30  conn = ConnectHandler(**listaDispositivos[1])
31  print("Conectado a: ", listaDispositivos[1])
32  print(conn.send_command("show running-config | include hostname"))
33  print(conn.send_command("show ip interface brief"))
34  conn.exit_config_mode()
35  print('\nCerrado conexion...')
36  conn.disconnect()
```

C.

```
PS G:\Mi unidad\Curso 2º GS 25 26\Documents\MARTÍN\ASIR2A\IPCR\RA2> & "C:/Program Files/Python311/python.exe" "g:/Mi unidad/EXAMEN/pruebaRA2.py"
● Conectado a: {'device_type': 'cisco_ios', 'host': '192.168.56.106', 'username': 'cisco', 'password': 'cisco123!'}
hostname CSR1000v106
Interface      IP-Address      OK? Method Status          Protocol
GigabitEthernet1  192.168.56.106  YES manual up              up

Cerrado conexion...
Conectado a: {'device_type': 'cisco_ios', 'host': '192.168.56.107', 'username': 'cisco', 'password': 'cisco123!'}
hostname CSR1000v107
Interface      IP-Address      OK? Method Status          Protocol
GigabitEthernet1  192.168.56.107  YES manual up              up

Cerrado conexion...
○ PS G:\Mi unidad\Curso 2º GS 25 26\Documents\MARTÍN\ASIR2A\IPCR\RA2>
```

```

pruebaRA2.py X
EXAMEN > pruebaRA2.py > ...
1  from netmiko import ConnectHandler
2
3  lista_ip_routers = [f'192.168.56.{n}' for n in range(106,108)]
4  listaDispositivos = []
5
6  for router in lista_ip_routers:
7      device = {
8          "device_type": "cisco_ios",
9          "host": router,
10         "username": "cisco",
11         "password": "cisco123!",
12     }
13     listaDispositivos.append(device)
14
15 conn = ConnectHandler(**listaDispositivos[0])
16 nombresRouter = [f'CSR1000v{i}' for i in range(106,108)]
17 hosts = [1,2]
18
19 for nombre, host in zip(nombresRouter, hosts):
20     conn.config_mode()
21     for subred in range(0,1):
22         crear_loopback = [f'interface Loopback {subred}',
23                             f'ip address 10.0.{subred}.{host} 255.255.255.0',
24                             f'description Interfaz Loopback{subred} {nombre}']
25
26
27     print(conn.send_config_set(crear_loopback))
28
29
30 conn = ConnectHandler(**listaDispositivos[0])
31 print("Conectado a: ", listaDispositivos[0])
32 print(conn.send_command("show running-config | include hostname"))
33 print(conn.send_command("show ip interface brief"))
34 conn.exit_config_mode()
35 print('\nCerrado conexion...')
36 conn.disconnect()
37
38
39 conn = ConnectHandler(**listaDispositivos[1])
40 print("Conectado a: ", listaDispositivos[1])
41 print(conn.send_command("show running-config | include hostname"))
42 print(conn.send_command("show ip interface brief"))
43 conn.exit_config_mode()
44 print('\nCerrado conexion...')
45 conn.disconnect()
46

```

d.

```

PS G:\VI unidad\Curso 2º GS 25 26\Documents\WARTIN\ASIR2A\IPCR\RA2> & "C:/Program Files/Python311/python.exe" "g:/VI unidad/Curso 2º GS 25 26/Documents/WARTIN/ASIR2A/IPCR/RA2/EXAMEN/pruebaRA2.py"
Interface Loopback 0
CSR1000v106(config-if)#ip address 10.0.0.1 255.255.255.0
CSR1000v106(config-if)#description Interfaz Loopback0 CSR1000v106
CSR1000v106(config-if)#end
CSR1000v106#
Interface Loopback 0
CSR1000v106(config-if)#ip address 10.0.0.2 255.255.255.0
CSR1000v106(config-if)#description Interfaz Loopback0 CSR1000v107
CSR1000v106(config-if)#end
CSR1000v106#
Conectado a: {'device_type': 'cisco_ios', 'host': '192.168.56.106', 'username': 'cisco', 'password': 'cisco123!'}
hostname CSR1000v106
Interface      IP-Address      OK? Method Status      Protocol
GigabitEthernet1 192.168.56.106 YES manual up          up
Loopback0       10.0.0.2        YES manual up          up

Cerrado conexion...
Conectado a: {'device_type': 'cisco_ios', 'host': '192.168.56.107', 'username': 'cisco', 'password': 'cisco123!'}
hostname CSR1000v107
Interface      IP-Address      OK? Method Status      Protocol
GigabitEthernet1 192.168.56.107 YES manual up          up

Cerrado conexion...
PS G:\VI unidad\Curso 2º GS 25 26\Documents\WARTIN\ASIR2A\IPCR\RA2>

```