HSE Safety Circular No. SC-2026-011

Unit: Aromatic Complex (MSEZ) | Classification: Confidential - Internal Use | Issue Date: 2026-05-02

Subject: Benzene Exposure Control - Storage Tank Farm TK-701 to TK-704

1. Background

This circular reiterates mandatory exposure control measures for personnel working in or near the Benzene storage and loading area (TK-701 to TK-704) within the Aromatic Complex. Benzene is classified as a Category 1 carcinogen. All requirements below are mandatory and supersede general area PPE guidance for this specific zone.

2. Exposure Limits

3. Mandatory Controls

Personal benzene dosimeter badges worn at all times within the tank farm boundary, logged out/in at the HSE gate register.

Supplied-air respiratory protection required for any tank-top gauging, sampling, or connection/disconnection of loading arms.

No hot work within 30 metres of TK-701 to TK-704 without an active Hot Work Permit co-signed by the Aromatic Complex Shift Supervisor and HSE.

Continuous fixed benzene detection required to be in-service before any loading operation commences; loading is prohibited if any detector in the zone is under maintenance without an approved compensatory monitoring plan.

4. Reference Documents

SOP-221 (Benzene Loading Arm Operation), SOP-225 (Confined Space Entry - Aromatic Complex), HSE Manual Section 7.4 (Carcinogen Management)

This is a synthetic, illustrative document generated for RAG/retrieval testing purposes. It does not represent an actual MRPL internal document.