



# Provision NVMe storage

## ONTAP 9

NetApp  
July 15, 2021

This PDF was generated from [https://docs.netapp.com/us-en/ontap/task\\_nvme\\_provision\\_suse\\_linux.html](https://docs.netapp.com/us-en/ontap/task_nvme_provision_suse_linux.html) on July 15, 2021. Always check docs.netapp.com for the latest.

# Table of Contents

- Provision NVMe storage. . . . . 1
  - NVMe overview . . . . . 1
  - Provision NVMe storage for SUSE Linux. . . . . 1

# Provision NVMe storage

The topics in this section show you how to configure and manage NVMe with ONTAP System Manager in ONTAP 9.7 and later releases.

If you are using the ONTAP CLI to configure and manage NVMe, see this content:

- [SAN Administration Guide](#)
- [SAN Configuration Guide](#)

If you are using legacy OnCommand System Manager for ONTAP 9.7 and earlier releases to configure and manage NVMe, see the content for your ONTAP release:

- [Cluster management using System Manager 9.6 and 9.7](#)
- [Cluster management using System Manager 9.5](#)
- [Cluster management using System Manager 9.3 and 9.4](#)
- [Cluster management using System Manager 9.2 and earlier](#)

## NVMe overview

You can use the non-volatile memory express (NVMe) protocol to provide storage in a SAN environment. The NVMe protocol is optimized for performance with solid state storage.

For NVMe, storage targets are called namespaces. An NVMe namespace is a quantity of non-volatile storage that can be formatted into logical blocks and presented to a host as a standard block device. You create namespaces and subsystems, and then map the namespaces to the subsystems, similar to the way LUNs are provisioned and mapped to igroups for FC and iSCSI.


NVMe targets are connected to the network through a standard FC infrastructure using FC switches and host-side adapters.

Learn more about [NVMe](#).

## Provision NVMe storage for SUSE Linux

Create namespaces to provide storage for a SUSE Linux server using the NVMe protocol. Namespaces appear to Linux as SCSI disk devices.

This procedure creates new namespaces on an existing storage VM. Your storage VM must be configured for NVME, and your FC transport should already be set up.





Beginning in ONTAP 9.8, when you provision storage, QoS is enabled by default. You can disable QoS or choose a custom QoS policy during the provisioning process or at a later time.

## Steps

1. In ONTAP System Manager, click **Storage > NVMe Namespaces** and then click **Add**.

If you need to create a new subsystem, click **More Options**.

- a. If you are running ONTAP 9.8 or later and you want to disable QoS or choose a custom QoS policy, click **More Options** and then, under **Storage and Optimization** select **Performance Service Level**.
1. Zone your FC switches by WWPN. Use one zone per initiator and include all target ports in each zone.
  2. On your Linux server, discover the new namespaces.
  3. Initialize the namespace and optionally format it with a file system.
  4. Verify the Linux server can write and read data on the namespace.

## Copyright Information

Copyright © 2021 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system-without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

## Trademark Information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.