



## NE8MC-1

Cable connector carrier consists of a shell, fixing disk, chuck and boot. The boot (same as XLR X-Series) is suitable for cable diameters from 3.5 - 8 mm. For non pre-assembled cables only. Cable connector carrier does not include a RJ45 plug.

The etherCON cable connector carrier upgrades a conventional RJ45 connector to an extremely robust lockable solution.

Attention! Does not intermate with the CAT6 chassis connectors NE8FDY-C6 and NE8FDY-C6-B.

## **Features & Benefits**

sealing kit

The RJ45 system for harsh and Cable connector carrier accepts the most demanding environment common RJ45 plugs (see list at downloads) Rugged diecast shell and unique chuck Protects Ethernet connections in a variety type strain relief of commercial type applications and is designed to prevent breakage of the fragile components of standard RJ 45 connectors Accessories include color coded boots in O-ring gasket to achieve IP54 water protection in combination with SE8FD 9 standard colors



## **Technical Information**

Product	
Title	NE8MC-1
Gender	male

Mechanical	
Cable O.D.	max. 8 mm 0.315'
Insertion force	≤ 20 N
Withdrawal force	≤ 20 N
Lifetime	> 1000 mating cycles
Wiresize	

Material	
Boot	Polyamide (PA 6)
Shell	Zinc diecast (ZnAl4Cu1)
Strain relief	Polyacetal (POM)
Shell plating	Chromium

Environmental	
Temperature range	-30 °C to +80 °C