

# A Proposal for Stripe's Data Architecture

Stripe is a financial services company which provides payment processing solutions through APIs that web developers can use in their websites or mobile applications. The company processes billions of transactions annually, supporting millions of merchants worldwide.

The sensitive nature of the data managed by Stripe, along with the need of efficient

## Online Transaction Processing Model

Our proposed OLTP database architecture is presented in figure 1. The core of the database is a registry of all financial transactions occurring within Stripe scope. Additional tables contain information about merchants and customers. Fraud indicators are stored in a dedicated table in a one-to-one correspondence with the main transactions table. The rationale behind this choice is that fraud indicators do not originate from the same source as transactions, and are not produced at the same time.

Table 1: Data dictionary for the **transactions** OLTP schema.

Field Name	Type	Description	Example
<b>transactions table</b>			
transaction_id	bigint	Unique transaction id	123456789
merchant_id	bigint	Merchant id	12345
customer_id	bigint	Customer id	234567
time	datetime	UTC transaction timestamp	2023-11-18 17:43:02.4
amount	decimal(10,2)	Transaction amount (in currency unit)	43.15
currency_code	char(3)	Currency code (ISO 4217)	'GBP'
payment_method	varchar(16)	Payment method	'credit_card'
device_type	varchar(16)	Device used for payment	'mobile'
status	varchar(16)	Transaction status	'sucess'
ip_latitude	float	IP-based geolocation latitude	49.6833300
ip_longitude	float	IP-based geolocation longitude	10.5333300
<b>merchants table</b>			
merchant_id	bigint	Unique merchant id	12345
name	varchar	Merchant name	'Amazon UK'
iban	varchar	Merchant IBAN	'GB82WEST12345678765432'
country_code	char(2)	Merchant registration country code	'GB'
<b>customers table</b>			
customer_id	bigint	Unique customer id	234567
name	varchar	Customer name	'John Doe'
iban	varchar	Customer IBAN	'GB82WEST12345678765432'
country_code	char(2)	Customer country code	'GB'
<b>fraud_indicators table</b>			
transaction_id	bigint	Transaction id	123456789
fraud_probability	float	Fraud probability	0.12




Figure 1: Proposed OLTP database structure.

## Online Analytical Processing Model

## NoSQL Model

## Security and Compliance

The company stores sensitive user data such as banking information. Il est important de sécuriser ces données pour deux raisons. D'une part, pour être en accord avec la législation locale (eg GDPR). D'autre part, la fuite de ces données impacterait la confiance accordée à l'entreprise par ses clients, avec en conséquence une baisse potentielle des revenus. Afin de limiter la surface d'attaque possible, les données sensibles sont confinées dans la base OLTP, et chiffrées à l'intérieur de celle-ci.

Il est nécessaire de reporter en partie de ces données dans la base OLAP, notamment pour l'étude des délits financiers (fraude, blanchiment, etc). Afin de limiter les risques, la base OLAP ne contient que des éléments anonymisés de ces données, telles que la localisation ou le nom de la banque. Afin de maintenir la performance du système, ces données ne sont pas chiffrées et on se limitera à en sécuriser l'accès et le transfert (définition de rôles pour limiter l'accès, etc).

Enfin, la base NoSQL incorpore potentiellement des fichiers sensibles (reçus bancaires par exemple). Ces fichiers sont stockés chiffrés dans un datalake dont l'accès est contrôlé. Aucune donnée sensible n'est stockée directement dans la base NoSQL, celle-ci ne contient que des identifiants indiquant l'emplacement des fichiers dans le datalake.

Des backups chiffrés sont mis à jour à intervalles réguliers afin d'assurer le rétablissement du service en cas d'incident majeur.

Enfin, un système de log est mis en place afin d'enregistrer tous les accès aux données, les requêtes effectuées, etc.

## References




Figure 2: Proposed OLAP database structure.

Table 2: Data dictionary for the main tables in **transactions** OLAP schema.

Field Name	Type	Description	Example
<b>transactions table</b>			
transaction_id	bigint	Unique transaction id	123456789
time_id	bigint	Transaction time id	123456789
merchant_id	bigint	Merchant id	12345
customer_id	bigint	Customer id	234567
currency_code	char(3)	Currency code (ISO 4217)	'GBP'
ip_geo_id	bigint	IP geolocalization id	1234567
payment_method_id	integer	Payment method id	1
payment_status_id	integer	Payment status id	2
device_type_id	integer	Device id	3
amount	decimal(10,2)	Transaction amount (in currency unit)	43.15
<b>time table</b>			
time_id	bigint	Unique transaction time id	123456789
timestamp	datetime	UTC transaction timestamp	2023-11-18 17:43:02.4
timezone	integer	Timezone offset in minutes	-120 for UTC-02:00
date	date	Transaction date	2023-11-18
time	time	UTC transaction time	17:43:02.4
year	mediumint	Transaction year	2023
month	tinyint	Transaction month	11
week_day	tinyint	Transaction week day (0 is sunday)	6 (saturday)
quarter	tinyint	Transaction quarter	4
<b>merchants table</b>			
merchant_id	bigint	Unique merchant id	12345
country_code	char(2)	Merchant registration country code	'GB'
<b>customers table</b>			
customer_id	bigint	Unique customer id	234567
country_code	char(2)	Customer country code	'GB'
<b>fraud_indicators table</b>			
transaction_id	bigint	Transaction id	123456789
fraud_probability	float	Fraud probability	0.12
<b>ip_geography table</b>			
ip_geo_id	bigint	Geolocation id	123456789
latitude	float	IP-based geolocation latitude	49.6833300
longitude	float	IP-based geolocation longitude	10.5333300
country_code	char(2)	country code (ISO 3166-1 alpha-2)	'DE'
province	varchar(255)	Province name	'Darmstadt'

Table 3: Data dictionary for the reference tables in **transactions** OLAP schema.

Field Name	Type	Description	Example
<b>currencies</b> table			
currency_code	char(3)	Currency code (ISO 4217)	'GBP'
currency_name	varchar(255)	Currency name	'Pound sterling'
usd_change_rate	decimal(6,4)	currency/USD change rate	1.2479
<b>currencies</b> table			
country_code	char(3)	Country code (ISO 3166-1 alpha-2)	'GB'
country_name	varchar(255)	Country name	'United Kingdom'
<b>payment_methods</b> table			
payment_method_id	integer	Unique payment method id	1
payment_method	varchar(16)	Payment method	'credit_card'
<b>payment_statuses</b> table			
payment_status_id	integer	Unique payment status id	1
payment_status	varchar(16)	Payment status	'sucessful'
<b>device_types</b> table			
device_type_id	integer	Unique device type id	1
device_type	varchar(16)	Device type	'mobile'
<b>months</b> table			
month	tinyint	Month number	11
payment_status	varchar(9)	Month name	'november'
<b>week_days</b> table			
week_day	tinyint	Week day number	6
week_day_name	varchar(9)	Day name	'saturday'