MISTACORN

DORHAN COMMONWEALTH · RED · 50 HZ

PLANT	DIESEL ELECTRIC
ERA	2008 · GEN 3
ENGINES	1× 4-stroke 6 cyl, 600–975 ERPM
MOTOR	48 slots
PROPULSOR	1 shaft · 4 blades
TPK	pending catalog
MAX SPEED	SUB 9 kt · SURF 6.8 kt · SNORT 5.9 kt · BATT 4.5 kt
QUIET	2.1–3.5 kt
CAVITATION	onset ≈ 10 kt at surface, later with depth

LINES BY MODE

SURF	CSR, CFR, EFR, EDA, generator, PSR, BR (DEMON), motor, MSR
SNORT	CSR, CFR, EFR, EDA, generator, PSR, BR (DEMON), motor, MSR, snorkel flow
D/E	CSR, CFR, EFR, EDA, generator (charging), PSR, BR (DEMON), motor, MSR
BATT	PSR, BR (DEMON), motor, MSR, no engine lines

ID KEYS

- CFR = CSR × 3 (4-stroke, 6 cyl)
- EFR = CSR ÷ 2 (4-stroke)
- BR = PSR × 4
- MSR = shaft rate × 48 slots
- DEMON: Shaft line with 4-blade BR harmonics

PEBBLEWISP

DORHAN COMMONWEALTH · RED · 50 HZ

PLANT	DIESEL ELECTRIC
ERA	2007 · GEN 4
ENGINES	2× 4-stroke 6 cyl, 600–975 ERPM
MOTOR	36 slots
PROPULSOR	1 shaft · 4 blades
TPK	pending catalog
MAX SPEED	SUB 14 kt · SURF 10.5 kt · SNORT 9.1 kt · BATT 5 kt
QUIET	2.4–4 kt
CAVITATION	onset ≈ 10 kt at surface, later with depth

LINES BY MODE

SURF	CSR, CFR, EFR, EDA, generator, PSR, BR (DEMON), motor, MSR
SNORT	CSR, CFR, EFR, EDA, generator, PSR, BR (DEMON), motor, MSR, snorkel flow
D/E	CSR, CFR, EFR, EDA, generator (charging), PSR, BR (DEMON), motor, MSR
BATT	PSR, BR (DEMON), motor, MSR, no engine lines

ID KEYS

- CFR = CSR × 3 (4-stroke, 6 cyl)
- EFR = CSR ÷ 2 (4-stroke)
- BR = PSR × 4
- MSR = shaft rate × 36 slots
- DEMON: Shaft line with 4-blade BR harmonics

GLOAMSPIRAL

KAELUN REPUBLIC · RED · 50 HZ

PLANT	DIESEL ELECTRIC + STIRLING BACKUP
ERA	2005 · GEN 4
ENGINES	2× 4-stroke 6 cyl, 600–975 ERPM
MOTOR	60 slots
PROPULSOR	1 shaft · 7 blades
TPK	pending catalog
MAX SPEED	SUB 22 kt · SURF 16.5 kt · SNORT 14.3 kt · BATT 8 kt · AIP 5 kt
QUIET	4.8–8 kt
CAVITATION	onset ≈ 10 kt at surface, later with depth

LINES BY MODE

SURF	CSR, CFR, EFR, EDA, generator, PSR, BR (DEMON), motor, MSR
SNORT	CSR, CFR, EFR, EDA, generator, PSR, BR (DEMON), motor, MSR, snorkel flow
D/E	CSR, CFR, EFR, EDA, generator (charging), PSR, BR (DEMON), motor, MSR
BATT	PSR, BR (DEMON), motor, MSR, no engine lines
AIP	PSR, BR (DEMON), motor, MSR, AIP auxiliaries, no engine lines

ID KEYS

- CFR = CSR × 3 (4-stroke, 6 cyl)
- EFR = CSR ÷ 2 (4-stroke)
- BR = PSR × 7
- MSR = shaft rate × 60 slots
- DEMON: Shaft line with 7-blade BR harmonics

LANTERNMOSS

KAELUN REPUBLIC · RED · 50 HZ

PLANT	DIESEL ELECTRIC
ERA	2006 · GEN 3
ENGINES	3× 4-stroke 8 cyl, 600–975 ERPM
MOTOR	48 slots
PROPULSOR	1 shaft · 7 blades
TPK	pending catalog
MAX SPEED	SUB 22 kt · SURF 16.5 kt · SNORT 14.3 kt · BATT 8 kt
QUIET	4.8–8 kt
CAVITATION	onset ≈ 10 kt at surface, later with depth

LINES BY MODE

SURF	CSR, CFR, EFR, EDA, generator, PSR, BR (DEMON), motor, MSR
SNORT	CSR, CFR, EFR, EDA, generator, PSR, BR (DEMON), motor, MSR, snorkel flow
D/E	CSR, CFR, EFR, EDA, generator (charging), PSR, BR (DEMON), motor, MSR
BATT	PSR, BR (DEMON), motor, MSR, no engine lines

ID KEYS

- CFR = CSR × 4 (4-stroke, 8 cyl)
- EFR = CSR ÷ 2 (4-stroke)
- BR = PSR × 7
- MSR = shaft rate × 48 slots
- DEMON: Shaft line with 7-blade BR harmonics

TWILIGHTWEFT

KAELUN REPUBLIC · RED · 50 HZ

PLANT	NUCLEAR N/GR
ERA	2005 · GEN 4
GEARING	19.99:1
PROPULSOR	2 shafts · 8 blades
TPK	pending catalog
MAX SPEED	SUB 30 kt · SURF 19.5 kt
QUIET	5.4–9 kt
CAVITATION	onset ≈ 11 kt at surface, later with depth

LINES BY MODE

NUC	PSR, BR (DEMON), reactor coolant pumps, turbine-generator, gear mesh, grid Hz family

ID KEYS

- PSR = CSR ÷ 19.99:1
- BR = PSR × 8
- 2 shafts: shaft-line doublets
- DEMON: Shaft doublet with 8-blade BR harmonics

VELVETSHOAL

KAELUN REPUBLIC · RED · 50 HZ

PLANT	NUCLEAR N/GR
ERA	2014 · GEN 3
GEARING	3.55:1
PROPULSOR	2 shafts · 8 blades
TPK	pending catalog
MAX SPEED	SUB 30 kt · SURF 19.5 kt
QUIET	5.4–9 kt
CAVITATION	onset ≈ 11 kt at surface, later with depth

LINES BY MODE

NUC	PSR, BR (DEMON), reactor coolant pumps, turbine-generator, gear mesh, grid Hz family

ID KEYS

- PSR = CSR ÷ 3.55:1
- BR = PSR × 8
- 2 shafts: shaft-line doublets
- DEMON: Shaft doublet with 8-blade BR harmonics

FROSTWHORL

VARKESHNA FEDERATION · RED · 50 HZ

PLANT	NUCLEAR NEL + FUELCELL BACKUP
ERA	2012 · GEN 3
MOTOR	48 slots
PROPULSOR	2 shafts · 9 blades
TPK	pending catalog
MAX SPEED	SUB 27 kt · SURF 17.6 kt · AIP 4 kt
QUIET	5.4–9 kt
CAVITATION	onset ≈ 11 kt at surface, later with depth

LINES BY MODE

NUC	PSR, BR (DEMON), reactor coolant pumps, turbine-generator, motor, MSR, grid Hz family
AIP	PSR, BR (DEMON), motor, MSR, AIP auxiliaries, no reactor lines

ID KEYS

- BR = PSR × 9
- MSR = shaft rate × 48 slots
- 2 shafts: shaft-line doublets
- DEMON: Shaft doublet with 9-blade BR harmonics

IVORYCOIL

VARKESHNA FEDERATION · RED · 50 HZ

PLANT	NUCLEAR N/GR
ERA	1980 · GEN 2
GEARING	19.99:1
PROPULSOR	2 shafts · 8 blades
BACKUP	3-blade emergency propulsor, ≤3 kt (off unless ordered)
TPK	pending catalog
MAX SPEED	SUB 30 kt · SURF 19.5 kt
QUIET	5.4–9 kt
CAVITATION	onset ≈ 11 kt at surface, later with depth

LINES BY MODE

NUC	PSR, BR (DEMON), reactor coolant pumps, turbine-generator, gear mesh, grid Hz family

ID KEYS

- PSR = CSR ÷ 19.99:1
- BR = PSR × 8
- 2 shafts: shaft-line doublets
- DEMON: Shaft doublet with 8-blade BR harmonics

MARIGOLDRIFT

VARKESHNA FEDERATION · RED · 50 HZ

PLANT	DIESEL ELECTRIC
ERA	2013 · GEN 4
ENGINES	2× 4-stroke 12 cyl, 600–975 ERPM
MOTOR	60 slots
PROPULSOR	1 shaft · 7 blades
TPK	pending catalog
MAX SPEED	SUB 22 kt · SURF 16.5 kt · SNORT 14.3 kt · BATT 8 kt
QUIET	4.8–8 kt
CAVITATION	onset ≈ 10 kt at surface, later with depth

LINES BY MODE

SURF	CSR, CFR, EFR, EDA, generator, PSR, BR (DEMON), motor, MSR
SNORT	CSR, CFR, EFR, EDA, generator, PSR, BR (DEMON), motor, MSR, snorkel flow
D/E	CSR, CFR, EFR, EDA, generator (charging), PSR, BR (DEMON), motor, MSR
BATT	PSR, BR (DEMON), motor, MSR, no engine lines

ID KEYS

- CFR = CSR × 6 (4-stroke, 12 cyl)
- EFR = CSR ÷ 2 (4-stroke)
- BR = PSR × 7
- MSR = shaft rate × 60 slots
- DEMON: Shaft line with 7-blade BR harmonics

SABLEQUILL

VARKESHNA FEDERATION · RED · 50 HZ

PLANT	NUCLEAR N/GR
ERA	2006 · GEN 3
GEARING	3.55:1
PROPULSOR	2 shafts · 8 blades
TPK	pending catalog
MAX SPEED	SUB 30 kt · SURF 19.5 kt
QUIET	5.4–9 kt
CAVITATION	onset ≈ 11 kt at surface, later with depth

LINES BY MODE

NUC	PSR, BR (DEMON), reactor coolant pumps, turbine-generator, gear mesh, grid Hz family

ID KEYS

- PSR = CSR ÷ 3.55:1
- BR = PSR × 8
- 2 shafts: shaft-line doublets
- DEMON: Shaft doublet with 8-blade BR harmonics

CINDERLILT

ZAHRESTAN · RED · 50 HZ

PLANT	DIESEL D/D
ERA	2013 · GEN 4
ENGINES	1× 2-stroke 6 cyl, 36–240 ERPM
MOTOR	36 slots
PROPULSOR	1 shaft · 5 blades
TPK	pending catalog
MAX SPEED	SUB 19 kt · SURF 14.3 kt · SNORT 12.4 kt · BATT 7 kt
QUIET	3.6–6 kt
CAVITATION	onset ≈ 8 kt at surface, later with depth

LINES BY MODE

SURF	CSR, CFR, EFR, EDA, PSR, BR (DEMON)
SNORT	CSR, CFR, EFR, EDA, PSR, BR (DEMON), snorkel flow
D/E	CSR, CFR, EFR, EDA, generator (charging)
BATT	PSR, BR (DEMON), motor, MSR, no engine lines

ID KEYS

- CFR = CSR × 6 (2-stroke, 6 cyl)
- EFR = CSR (2-stroke)
- PSR = CSR when engines coupled
- BR = PSR × 5
- MSR = shaft rate × 36 slots
- DEMON: Shaft line with 5-blade BR harmonics

EMBERBRAID

ZAHRESTAN · RED · 50 HZ

PLANT	DIESEL D/GR
ERA	2014 · GEN 3
ENGINES	1× 4-stroke 16 cyl, 292.9133126934984–1952.7554179566564 ERPM
GEARING	8.88:1
MOTOR	48 slots
PROPULSOR	1 shaft · 6 blades
TPK	pending catalog
MAX SPEED	SUB 21 kt · SURF 15.8 kt · SNORT 13.7 kt · BATT 8 kt
QUIET	4.2–7 kt
CAVITATION	onset ≈ 9 kt at surface, later with depth

LINES BY MODE

SURF	CSR, CFR, EFR, EDA, PSR, BR (DEMON), gear mesh
SNORT	CSR, CFR, EFR, EDA, PSR, BR (DEMON), gear mesh, snorkel flow
D/E	CSR, CFR, EFR, EDA, generator (charging)
BATT	PSR, BR (DEMON), motor, MSR, no engine lines

ID KEYS

- CFR = CSR × 8 (4-stroke, 16 cyl)
- EFR = CSR ÷ 2 (4-stroke)
- PSR = CSR ÷ 8.88:1
- BR = PSR × 6
- MSR = shaft rate × 48 slots
- DEMON: Shaft line with 6-blade BR harmonics

QUARTZWHORL

NORRLAND UNION · BLUE · 60 HZ

PLANT	NUCLEAR NEL
ERA	2008 · GEN 3
MOTOR	72 slots
PROPULSOR	2 shafts · 9 blades
TPK	pending catalog
MAX SPEED	SUB 27 kt · SURF 17.6 kt
QUIET	5.4–9 kt
CAVITATION	onset ≈ 11 kt at surface, later with depth

LINES BY MODE

NUC	PSR, BR (DEMON), reactor coolant pumps, turbine-generator, motor, MSR, grid Hz family

ID KEYS

- BR = PSR × 9
- MSR = shaft rate × 72 slots
- 2 shafts: shaft-line doublets
- DEMON: Shaft doublet with 9-blade BR harmonics

VELLUMWAKE

NORRLAND UNION · BLUE · 60 HZ

PLANT	NUCLEAR N/GR
ERA	2007 · GEN 4
GEARING	19.99:1
PROPULSOR	2 shafts · 7 blades
TPK	pending catalog
MAX SPEED	SUB 29 kt · SURF 18.9 kt
QUIET	4.8–8 kt
CAVITATION	onset ≈ 10 kt at surface, later with depth

LINES BY MODE

NUC	PSR, BR (DEMON), reactor coolant pumps, turbine-generator, gear mesh, grid Hz family

ID KEYS

- PSR = CSR ÷ 19.99:1
- BR = PSR × 7
- 2 shafts: shaft-line doublets
- DEMON: Shaft doublet with 7-blade BR harmonics

BRINDLEFLUX

OSTMARK LEAGUE · BLUE · 60 HZ

PLANT	DIESEL D/D
ERA	2005 · GEN 4
ENGINES	1× 2-stroke 6 cyl, 31.5–210 ERPM
MOTOR	36 slots
PROPULSOR	1 shaft · 5 blades
TPK	pending catalog
MAX SPEED	SUB 18 kt · SURF 13.5 kt · SNORT 11.7 kt · BATT 7 kt
QUIET	3.6–6 kt
CAVITATION	onset ≈ 8 kt at surface, later with depth

LINES BY MODE

SURF	CSR, CFR, EFR, EDA, PSR, BR (DEMON)
SNORT	CSR, CFR, EFR, EDA, PSR, BR (DEMON), snorkel flow
D/E	CSR, CFR, EFR, EDA, generator (charging)
BATT	PSR, BR (DEMON), motor, MSR, no engine lines

ID KEYS

- CFR = CSR × 6 (2-stroke, 6 cyl)
- EFR = CSR (2-stroke)
- PSR = CSR when engines coupled
- BR = PSR × 5
- MSR = shaft rate × 36 slots
- DEMON: Shaft line with 5-blade BR harmonics

COPPERLUNE

OSTMARK LEAGUE · BLUE · 60 HZ

PLANT	NUCLEAR N/GR
ERA	2009 · GEN 4
GEARING	19.99:1
PROPULSOR	2 shafts · 7 blades
TPK	pending catalog
MAX SPEED	SUB 29 kt · SURF 18.9 kt
QUIET	4.8–8 kt
CAVITATION	onset ≈ 10 kt at surface, later with depth

LINES BY MODE

NUC	PSR, BR (DEMON), reactor coolant pumps, turbine-generator, gear mesh, grid Hz family

ID KEYS

- PSR = CSR ÷ 19.99:1
- BR = PSR × 7
- 2 shafts: shaft-line doublets
- DEMON: Shaft doublet with 7-blade BR harmonics

ORBELUNE

OSTMARK LEAGUE · BLUE · 60 HZ

PLANT	DIESEL ELECTRIC
ERA	2006 · GEN 3
ENGINES	3× 4-stroke 8 cyl, 720–1170 ERPM
MOTOR	48 slots
PROPULSOR	1 shaft · 7 blades
TPK	pending catalog
MAX SPEED	SUB 22 kt · SURF 16.5 kt · SNORT 14.3 kt · BATT 8 kt
QUIET	4.2–7 kt
CAVITATION	onset ≈ 9 kt at surface, later with depth

LINES BY MODE

SURF	CSR, CFR, EFR, EDA, generator, PSR, BR (DEMON), motor, MSR
SNORT	CSR, CFR, EFR, EDA, generator, PSR, BR (DEMON), motor, MSR, snorkel flow
D/E	CSR, CFR, EFR, EDA, generator (charging), PSR, BR (DEMON), motor, MSR
BATT	PSR, BR (DEMON), motor, MSR, no engine lines

ID KEYS

- CFR = CSR × 4 (4-stroke, 8 cyl)
- EFR = CSR ÷ 2 (4-stroke)
- BR = PSR × 7
- MSR = shaft rate × 48 slots
- DEMON: Shaft line with 7-blade BR harmonics

OPALWEFT

MERIDIA · GREEN · 60 HZ

PLANT	DIESEL ELECTRIC
ERA	2012 · GEN 3
ENGINES	3× 4-stroke 10 cyl, 720–1170 ERPM
MOTOR	72 slots
PROPULSOR	1 shaft · 7 blades
TPK	pending catalog
MAX SPEED	SUB 23 kt · SURF 17.3 kt · SNORT 15 kt · BATT 8 kt
QUIET	4.2–7 kt
CAVITATION	onset ≈ 9 kt at surface, later with depth

LINES BY MODE

SURF	CSR, CFR, EFR, EDA, generator, PSR, BR (DEMON), motor, MSR
SNORT	CSR, CFR, EFR, EDA, generator, PSR, BR (DEMON), motor, MSR, snorkel flow
D/E	CSR, CFR, EFR, EDA, generator (charging), PSR, BR (DEMON), motor, MSR
BATT	PSR, BR (DEMON), motor, MSR, no engine lines

ID KEYS

- CFR = CSR × 5 (4-stroke, 10 cyl)
- EFR = CSR ÷ 2 (4-stroke)
- BR = PSR × 7
- MSR = shaft rate × 72 slots
- DEMON: Shaft line with 7-blade BR harmonics

RUSSETWAKE

MERIDIA · GREEN · 60 HZ

PLANT	DIESEL D/GR
ERA	2010 · GEN 3
ENGINES	1× 4-stroke 6 cyl, 306.2275541795666–2041.5170278637772 ERPM
GEARING	8.88:1
MOTOR	72 slots
PROPULSOR	1 shaft · 6 blades
TPK	pending catalog
MAX SPEED	SUB 20 kt · SURF 15 kt · SNORT 13 kt · BATT 7 kt
QUIET	3.6–6 kt
CAVITATION	onset ≈ 8 kt at surface, later with depth

LINES BY MODE

SURF	CSR, CFR, EFR, EDA, PSR, BR (DEMON), gear mesh
SNORT	CSR, CFR, EFR, EDA, PSR, BR (DEMON), gear mesh, snorkel flow
D/E	CSR, CFR, EFR, EDA, generator (charging)
BATT	PSR, BR (DEMON), motor, MSR, no engine lines

ID KEYS

- CFR = CSR × 3 (4-stroke, 6 cyl)
- EFR = CSR ÷ 2 (4-stroke)
- PSR = CSR ÷ 8.88:1
- BR = PSR × 6
- MSR = shaft rate × 72 slots
- DEMON: Shaft line with 6-blade BR harmonics

FENNELGLINT

TARSIAN REPUBLIC · GREEN · 60 HZ

PLANT	DIESEL ELECTRIC
ERA	2010 · GEN 3
ENGINES	3× 4-stroke 6 cyl, 720–1170 ERPM
MOTOR	48 slots
PROPULSOR	1 shaft · 7 blades
TPK	pending catalog
MAX SPEED	SUB 23 kt · SURF 17.3 kt · SNORT 15 kt · BATT 8 kt
QUIET	4.2–7 kt
CAVITATION	onset ≈ 9 kt at surface, later with depth

LINES BY MODE

SURF	CSR, CFR, EFR, EDA, generator, PSR, BR (DEMON), motor, MSR
SNORT	CSR, CFR, EFR, EDA, generator, PSR, BR (DEMON), motor, MSR, snorkel flow
D/E	CSR, CFR, EFR, EDA, generator (charging), PSR, BR (DEMON), motor, MSR
BATT	PSR, BR (DEMON), motor, MSR, no engine lines

ID KEYS

- CFR = CSR × 3 (4-stroke, 6 cyl)
- EFR = CSR ÷ 2 (4-stroke)
- BR = PSR × 7
- MSR = shaft rate × 48 slots
- DEMON: Shaft line with 7-blade BR harmonics

MORROWCOIL

TARSIAN REPUBLIC · GREEN · 60 HZ

PLANT	DIESEL D/GR
ERA	2009 · GEN 4
ENGINES	1× 4-stroke 16 cyl, 122.475–816.5 ERPM
GEARING	3.55:1
MOTOR	36 slots
PROPULSOR	1 shaft · 6 blades
TPK	pending catalog
MAX SPEED	SUB 20 kt · SURF 15 kt · SNORT 13 kt · BATT 7 kt
QUIET	3.6–6 kt
CAVITATION	onset ≈ 8 kt at surface, later with depth

LINES BY MODE

SURF	CSR, CFR, EFR, EDA, PSR, BR (DEMON), gear mesh
SNORT	CSR, CFR, EFR, EDA, PSR, BR (DEMON), gear mesh, snorkel flow
D/E	CSR, CFR, EFR, EDA, generator (charging)
BATT	PSR, BR (DEMON), motor, MSR, no engine lines

ID KEYS

- CFR = CSR × 8 (4-stroke, 16 cyl)
- EFR = CSR ÷ 2 (4-stroke)
- PSR = CSR ÷ 3.55:1
- BR = PSR × 6
- MSR = shaft rate × 36 slots
- DEMON: Shaft line with 6-blade BR harmonics

THISTLEDRIFT

TARSIAN REPUBLIC · GREEN · 60 HZ

PLANT	NUCLEAR N/GR
ERA	2011 · GEN 4
GEARING	19.99:1
PROPULSOR	2 shafts · 8 blades
TPK	pending catalog
MAX SPEED	SUB 28 kt · SURF 18.2 kt
QUIET	4.8–8 kt
CAVITATION	onset ≈ 10 kt at surface, later with depth

LINES BY MODE

NUC	PSR, BR (DEMON), reactor coolant pumps, turbine-generator, gear mesh, grid Hz family

ID KEYS

- PSR = CSR ÷ 19.99:1
- BR = PSR × 8
- 2 shafts: shaft-line doublets
- DEMON: Shaft doublet with 8-blade BR harmonics

All classes, nations and signatures are fictional. Values shown are class ranges and ratios; each hull is seeded with its own jitter.