

# Package ‘lame’

July 24, 2026

**Title** Longitudinal Additive and Multiplicative Effects Models for Networks

**Version** 1.3.4

**Description** Additive and multiplicative effects models for both cross-sectional and longitudinal network analysis. The package provides two main functions: `ame()` for cross-sectional networks and `lame()` for longitudinal networks. It supports square and rectangular network structures. Key features include: (1) Cross-sectional network analysis via `ame()` with support for binary, continuous, ordinal, and count data; (2) Longitudinal network analysis via `lame()` with additive sender/receiver and multiplicative latent-factor effects that can evolve over time through AR(1) processes (Sewell and Chen (2015) <[doi:10.1080/01621459.2014.988214](https://doi.org/10.1080/01621459.2014.988214)>; Durante and Dunson (2014) <[doi:10.1093/biomet/asu040](https://doi.org/10.1093/biomet/asu040)>); (3) Handling of changing actor compositions across time periods in longitudinal models; (4) Performance improvements through C++ implementations via 'Rcpp' and 'RcppArmadillo'.

**Author** Cassy Dorff [aut], Shahryar Minhas [aut, cre], Tosin Salau [aut]

**Maintainer** Shahryar Minhas <[minhassh@msu.edu](mailto:minhassh@msu.edu)>

**License** MIT + file LICENSE

**URL** <https://netify-dev.github.io/lame/>,  
<https://github.com/netify-dev/lame>

**BugReports** <https://github.com/netify-dev/lame/issues>

**Depends** R (>= 3.5.0)

**Encoding** UTF-8

**LazyData** true

**Roxygen** list(markdown = TRUE)

**RoxygenNote** 7.3.3

**LinkingTo** Rcpp, RcppArmadillo

**Imports** Rcpp, ggplot2, ggrepel, ggforce, gridExtra, coda, patchwork, cli, MASS, Matrix, abind, netify (>= 1.5.3), graphics, grDevices, parallel, stats, utils

**Suggests** knitr, rmarkdown, testthat (>= 3.0.0), igraph, network,  
posterior, loo, digest, tibble, broom, generics, pROC, precrec,  
statmod, dplyr, modelsummary, callr, amen

**VignetteBuilder** knitr

**Config/testthat/edition** 3

**NeedsCompilation** yes

## R topics documented:

|                                      |    |
|--------------------------------------|----|
| lame-package . . . . .               | 7  |
| .actor_ffbs_path . . . . .           | 8  |
| .ame_propagate_cov_na . . . . .      | 9  |
| .build_full_design . . . . .         | 9  |
| .exact_center_per_actor . . . . .    | 10 |
| .fit_actor_order . . . . .           | 10 |
| .reorder_newdata_actors . . . . .    | 11 |
| .rotation_drift_diagnostic . . . . . | 11 |
| .sweep_per_actor_exact . . . . .     | 12 |
| .xbeta_newdata . . . . .             | 13 |
| ab_plot . . . . .                    | 13 |
| ab_plot.ame_als . . . . .            | 15 |
| addhealthc3 . . . . .                | 16 |
| addhealthc9 . . . . .                | 16 |
| als_dynamic_beta . . . . .           | 17 |
| als_start_vals . . . . .             | 18 |
| ame . . . . .                        | 19 |
| ame_als . . . . .                    | 29 |
| ame_als_bootstrap . . . . .          | 35 |
| ame_als_refit . . . . .              | 37 |
| ame_memory_settings . . . . .        | 39 |
| ame_memory_usage . . . . .           | 40 |
| ame_options . . . . .                | 40 |
| ame_parallel . . . . .               | 42 |
| array_to_list . . . . .              | 43 |
| as_draws . . . . .                   | 44 |
| as_draws.ame . . . . .               | 44 |
| as_lame_y . . . . .                  | 45 |
| autoplot.ame_als . . . . .           | 46 |
| autoplot.lame . . . . .              | 47 |
| bipartite_helpers . . . . .          | 48 |
| boot_ame-no-fitted . . . . .         | 48 |
| check_format . . . . .               | 49 |
| coef.als_dynamic_beta . . . . .      | 50 |
| coef.ame . . . . .                   | 51 |
| coef.ame_als . . . . .               | 52 |
| coef.boot_ame . . . . .              | 52 |
| coldwar . . . . .                    | 53 |

|                                      |     |
|--------------------------------------|-----|
| combine_ame_chains . . . . .         | 53  |
| compact_ame . . . . .                | 54  |
| compute_gof_bipartite . . . . .      | 54  |
| compute_mcmc_diagnostics . . . . .   | 55  |
| compute_XtX_Xty_bip_cpp . . . . .    | 55  |
| comtrade . . . . .                   | 56  |
| confint.ame . . . . .                | 56  |
| confint.ame_als . . . . .            | 57  |
| confint.boot_ame . . . . .           | 58  |
| design_array . . . . .               | 59  |
| design_array_listwisedel . . . . .   | 59  |
| detect_change_point . . . . .        | 60  |
| dutchcollege . . . . .               | 61  |
| dynamic_beta_prior_summary . . . . . | 62  |
| el2sm . . . . .                      | 63  |
| evaluate_heldout . . . . .           | 64  |
| ffbs_vecG . . . . .                  | 65  |
| fitted.ame . . . . .                 | 66  |
| fitted.ame_als . . . . .             | 67  |
| fitted.lame . . . . .                | 67  |
| forecast_pit . . . . .               | 68  |
| formula.ame . . . . .                | 69  |
| get_design_rep . . . . .             | 70  |
| get_EZ_dynamic_beta_cpp . . . . .    | 71  |
| get_fit_object . . . . .             | 72  |
| get_start_vals . . . . .             | 74  |
| glance . . . . .                     | 75  |
| glance.ame . . . . .                 | 75  |
| glance.ame_als . . . . .             | 76  |
| gof . . . . .                        | 77  |
| gof_plot . . . . .                   | 79  |
| gof_plot.ame_als . . . . .           | 82  |
| gof_stats . . . . .                  | 83  |
| gof_stats_bipartite . . . . .        | 85  |
| gof_stats_unipartite . . . . .       | 86  |
| gof_temporal . . . . .               | 87  |
| init_dynamic_ab_cpp . . . . .        | 88  |
| init_dynamic_positions . . . . .     | 89  |
| IR90s . . . . .                      | 90  |
| lame . . . . .                       | 90  |
| lame_als . . . . .                   | 104 |
| lame_multi . . . . .                 | 107 |
| lame_parallel . . . . .              | 108 |
| lame_resume . . . . .                | 109 |
| lame_snap_als . . . . .              | 110 |
| latent_positions . . . . .           | 114 |
| lazegalaw . . . . .                  | 116 |
| lfo . . . . .                        | 116 |

|                                      |     |
|--------------------------------------|-----|
| <code>list_to_array</code>           | 117 |
| <code>list_to_array_bipartite</code> | 118 |
| <code>logLik.ame</code>              | 118 |
| <code>logLik.ame_als</code>          | 119 |
| <code>log_phi_diff</code>            | 119 |
| <code>loo</code>                     | 120 |
| <code>loo.ame</code>                 | 120 |
| <code>mhalf</code>                   | 122 |
| <code>nobs.ame</code>                | 122 |
| <code>nobs.ame_als</code>            | 123 |
| <code>nodematch</code>               | 123 |
| <code>per_actor_slopes</code>        | 124 |
| <code>plot.ame</code>                | 125 |
| <code>plot.ame_als</code>            | 126 |
| <code>plot.lame</code>               | 127 |
| <code>posterior_options</code>       | 128 |
| <code>posterior_quantiles</code>     | 129 |
| <code>precomputeX</code>             | 130 |
| <code>predict.ame</code>             | 130 |
| <code>predict.ame_als</code>         | 132 |
| <code>predict.lame</code>            | 132 |
| <code>prediction_draws_long</code>   | 134 |
| <code>print.als_dynamic_beta</code>  | 135 |
| <code>print.ame</code>               | 135 |
| <code>print.ame.sim</code>           | 136 |
| <code>print.ame_als</code>           | 137 |
| <code>print.boot_ame</code>          | 138 |
| <code>print.gof_temporal</code>      | 138 |
| <code>print.lame</code>              | 139 |
| <code>print.lame_multi</code>        | 139 |
| <code>print.lfo_lame</code>          | 140 |
| <code>print.per_actor_slopes</code>  | 140 |
| <code>print.summary.ame</code>       | 141 |
| <code>print.summary.ame_als</code>   | 141 |
| <code>print.summary.lame</code>      | 142 |
| <code>prior_summary</code>           | 142 |
| <code>procrustes_align</code>        | 143 |
| <code>raSab_bin_fc</code>            | 145 |
| <code>raSab_cbin_fc</code>           | 146 |
| <code>raSab_frn_fc</code>            | 147 |
| <code>rbeta_ab_bip_gibbs_cpp</code>  | 148 |
| <code>rbeta_ab_fc</code>             | 149 |
| <code>rbeta_ab_rep_fc</code>         | 150 |
| <code>read_log_lik</code>            | 151 |
| <code>reconstruct_EZ</code>          | 151 |
| <code>reexports</code>               | 152 |
| <code>residuals.ame</code>           | 152 |
| <code>residuals.ame_als</code>       | 153 |

|                                   |     |
|-----------------------------------|-----|
| residuals.lame . . . . .          | 154 |
| rhat_dynamic_beta . . . . .       | 154 |
| rmvnorm . . . . .                 | 155 |
| rrho_mh . . . . .                 | 156 |
| rs2_fc . . . . .                  | 157 |
| rs2_rep_fc . . . . .              | 157 |
| rSab_fc . . . . .                 | 158 |
| rSuv_fc . . . . .                 | 159 |
| rtnorm_interval_logp . . . . .    | 160 |
| rUV_dynamic_bip_fc_cpp . . . . .  | 161 |
| rUV_dynamic_fc . . . . .          | 161 |
| rUV_dynamic_fc_cpp . . . . .      | 162 |
| rUV_dynamic_snap_fc . . . . .     | 163 |
| rUV_dynamic_snap_fc_cpp . . . . . | 164 |
| rUV_dynamic_t_fc . . . . .        | 165 |
| rUV_dynamic_t_fc_cpp . . . . .    | 166 |
| rUV_fc . . . . .                  | 167 |
| rUV_rep_fc . . . . .              | 168 |
| rUV_sym_fc . . . . .              | 169 |
| rwish . . . . .                   | 170 |
| rZ_bin_bip_batch_cpp . . . . .    | 171 |
| rZ_bin_fc . . . . .               | 171 |
| rZ_cbin_bip_fc . . . . .          | 172 |
| rZ_cbin_fc . . . . .              | 173 |
| rZ_frn_bip_fc . . . . .           | 173 |
| rZ_frn_fc . . . . .               | 174 |
| rZ_nrm_batch_cpp . . . . .        | 175 |
| rZ_nrm_fc . . . . .               | 176 |
| rZ_ord_bip_fc . . . . .           | 176 |
| rZ_ord_explicit_fc . . . . .      | 177 |
| rZ_ord_fc . . . . .               | 177 |
| rZ_ord_sym_explicit_fc . . . . .  | 178 |
| rZ_ord_sym_fc . . . . .           | 179 |
| rZ_pois_bip_fc . . . . .          | 179 |
| rZ_pois_fc . . . . .              | 180 |
| sampler_describe . . . . .        | 181 |
| sample_ab_bipartite . . . . .     | 181 |
| sample_alpha_cowles . . . . .     | 182 |
| sample_beta_dynamic_cpp . . . . . | 183 |
| sample_beta_static_cpp . . . . .  | 184 |
| sample_dynamic_ab_cpp . . . . .   | 185 |
| sample_rho_ab_cpp . . . . .       | 186 |
| sample_rho_beta_cpp . . . . .     | 187 |
| sample_rho_G_mh . . . . .         | 188 |
| sample_rho_uv . . . . .           | 188 |
| sample_sigma_ab_cpp . . . . .     | 189 |
| sample_sigma_beta_cpp . . . . .   | 190 |
| sample_sigma_G2 . . . . .         | 191 |

|                                      |     |
|--------------------------------------|-----|
| sample_sigma_uv . . . . .            | 191 |
| sampsonmonks . . . . .               | 192 |
| sheep . . . . .                      | 192 |
| simulate.ame . . . . .               | 193 |
| simulate.ame_als . . . . .           | 196 |
| simulate.lame . . . . .              | 196 |
| simulate_posterior . . . . .         | 200 |
| simY_bin . . . . .                   | 201 |
| simY_frn . . . . .                   | 202 |
| simY_nrm . . . . .                   | 203 |
| simY_ord . . . . .                   | 203 |
| simY_pois . . . . .                  | 204 |
| simZ . . . . .                       | 205 |
| sm2el . . . . .                      | 205 |
| snap_category_summary . . . . .      | 206 |
| snap_index_draws . . . . .           | 207 |
| snap_index_summary . . . . .         | 207 |
| snap_rank_summary . . . . .          | 208 |
| summary.ame . . . . .                | 209 |
| summary.ame.sim . . . . .            | 210 |
| summary.ame_als . . . . .            | 210 |
| summary.boot_ame . . . . .           | 211 |
| summary.lame . . . . .               | 211 |
| summary.lame.sim . . . . .           | 213 |
| tidy . . . . .                       | 213 |
| tidy.ame . . . . .                   | 214 |
| tidy.ame_als . . . . .               | 215 |
| tidy.boot_ame . . . . .              | 216 |
| trace_plot . . . . .                 | 216 |
| update.ame . . . . .                 | 218 |
| update.ame_als . . . . .             | 219 |
| update_variances_bipartite . . . . . | 220 |
| uv_plot . . . . .                    | 220 |
| vcov.ame . . . . .                   | 223 |
| vcov.ame_als . . . . .               | 224 |
| vcov.boot_ame . . . . .              | 225 |
| vignette_data . . . . .              | 225 |
| waic.ame . . . . .                   | 226 |
| Xbeta . . . . .                      | 227 |
| Xbeta_bip_cpp . . . . .              | 227 |
| Xcol . . . . .                       | 228 |
| Xdyad . . . . .                      | 228 |
| Xrow . . . . .                       | 228 |
| Y . . . . .                          | 229 |
| YX_bin . . . . .                     | 229 |
| YX_bin_list . . . . .                | 230 |
| YX_bin_long . . . . .                | 230 |
| YX_cbin . . . . .                    | 231 |

|                   |            |
|-------------------|------------|
| YX_frn . . . . .  | 231        |
| YX_nrm . . . . .  | 232        |
| YX_ord . . . . .  | 232        |
| zscores . . . . . | 233        |
| <b>Index</b>      | <b>234</b> |

---

|              |                                                                             |
|--------------|-----------------------------------------------------------------------------|
| lame-package | <i>Longitudinal Additive and Multiplicative Effects Models for Networks</i> |
|--------------|-----------------------------------------------------------------------------|

---

**Description**

An extension of the 'amen' package specifically designed for longitudinal network analysis. This package provides tools for fitting Additive and Multiplicative Effects (AME) models to longitudinal/replicated relational data with several extensions: (1) handling of changing actor compositions across time periods, allowing for networks with different sets of actors at each time point; (2) significant performance improvements through C++ implementations via Rcpp and RcppArmadillo; (3) specialized functions for temporal network dynamics. The package supports six data types: normal (nrm), binary (bin), ordinal (ord), Poisson count (poisson), censored binary (cbin), and fixed-rank nomination (frn). Based on the AME framework originally developed by Hoff (2009) and Hoff, Fosdick, Volfovsky and Stovel (2013).

**Details**

**Estimators.** The package offers two estimation routes:

- [ame](#) / [lame](#) – the Bayesian MCMC estimators, for calibrated posterior inference (cross-sectional and longitudinal respectively).
- [ame\\_als](#) / [lame\\_als](#) – a fast, MCMC-free point estimator by iterative block coordinate descent, with bootstrap uncertainty via [ame\\_als\\_bootstrap](#). Use it for rapid model exploration, rank selection and starting values; use the MCMC estimators for final inference.

Package: lame

Type: Package

License: MIT

**Author(s)**

Shahryar Minhas, Tosin Salau, Cassy Dorff  
Maintainer: Shahryar Minhas [minhassh@msu.edu](mailto:minhassh@msu.edu)

## Examples

```
data(YX_nrm)
fit <- ame(YX_nrm$Y, Xdyad = YX_nrm$X, burn = 10, nscan = 100, odens = 1,
          family = "normal", verbose = FALSE)
summary(fit)
```

---

.actor\_ffbs\_path

*Univariate Carter-Kohn FFBS for one actor's length-T slope path*

---

## Description

Given period-wise sufficient statistics ( $H_t = \sum_j X_{ij}^2 / s^2$ ,  $h_t = \sum_j X_{ij} R_{ij} / s^2$ ) and AR(1) hyperparameters, returns one joint draw from the posterior  $N(m, P)$  where the prior is AR(1) and the observation is the Gaussian likelihood implied by  $(H, h)$ .

## Usage

```
.actor_ffbs_path(H, h, rho_actor, sigma_actor2)
```

## Arguments

|              |                                                           |
|--------------|-----------------------------------------------------------|
| H            | length-T vector of period-wise observation precisions     |
| h            | length-T vector of period-wise observation cross-products |
| rho_actor    | AR(1) coefficient                                         |
| sigma_actor2 | AR(1) innovation variance                                 |

## Value

list with theta (length-T draw) and V (length-T marginal posterior variance per period – needed for the exact centering projection).



---

`.ame_propagate_cov_na` *Propagate covariate missingness into the response*


---

**Description**

For an AME fit, a dyad whose covariate value is missing cannot contribute a covariate-coefficient observation. Rather than silently imputing the missing covariate as 0 (which biases the coefficient when the covariate is not mean-centred), the dyad is treated as an unobserved tie and handled by data augmentation. This helper sets the affected Y cells to NA; `lame` already does this internally, and this brings `ame` into line.

**Usage**

```
.ame_propagate_cov_na(Y, Xrow = NULL, Xcol = NULL, Xdyad = NULL)
```

**Arguments**

`Y` an n x n response matrix.  
`Xrow, Xcol, Xdyad` row, column and dyadic covariates (or NULL).

**Value**

Y with covariate-missing cells set to NA.

---

`.build_full_design` *Build the full canonical design for a newdata prediction*


---

**Description**

Build the full canonical design for a newdata prediction

**Usage**

```
.build_full_design(newdata, model_names, fitted_design, n, m)
```

**Arguments**

`newdata` an n x m x n\_dyad array (or n x m matrix) of new dyadic covariates. If its 3rd-dim names match the model's dyadic coefficient names they are mapped by name; otherwise the slices are taken in order as the model's dyadic covariates.

`model_names` the model's coefficient names (`colnames(fit$BETA) / dimnames(fit$BETA)[[2]]`), in canonical layout.

`fitted_design` the model's fitted design array (`fit$X` or `Xlist[[t]]`); used to hold intercept + nodal slices fixed. May be NULL only when the model has no nodal covariates.

`n, m` output dimensions.

**Value**

an  $n \times m \times \text{length}(\text{model\_names})$  array whose slices are in `model_names` order: dyadic slices from `newdata`, all other slices held at their fitted values (intercept = 1).

---

`.exact_center_per_actor`

*Exact variance-weighted sum-to-zero projection for the per-actor block*

---

**Description**

Given an unconstrained sample `theta_star` ( $n_{\text{actors}} \times T$ ) and per-actor per-period posterior variances `V` (same shape), projects to the sum-to-zero manifold per period using the variance-weighted Lagrangian projection (exact under block-diagonal covariance across actors).

**Usage**

`.exact_center_per_actor(theta_star, V)`

---

`.fit_actor_order`

*The fit's internal (canonical) actor order*

---

**Description**

`lame()` sorts actors alphabetically when it ingests a list of `Y` matrices (via `list_to_array`), so the stored additive / multiplicative effects and design slices are in sorted actor order, which need not match the order a user later supplies in `newdata`. This returns the row and column actor names the fit was estimated in, tried from the most authoritative source down, so `newdata` can be realigned by name before prediction.

**Usage**

`.fit_actor_order(object)`

**Arguments**

`object`                      a fitted `lame` (or `ame`) object.

**Value**

a list with `rows` and `cols` character vectors (or `NULL` when the order cannot be recovered).

---

`.reorder_newdata_actors`*Realign a newdata covariate array to the fit's internal actor order*

---

### Description

Reorders the rows and columns of each  $n \times m \times p$  slice by their dimnames so they line up with the fit's stored (sorted) additive / multiplicative effects. Only acts when newdata carries dimnames whose name set exactly matches the fit's; otherwise it falls back to the supplied positional order unchanged (the historical behaviour, correct when the user already passes actors in the fit's order or supplies no names).

### Usage

```
.reorder_newdata_actors(X, row_order, col_order)
```

### Arguments

`X` an  $n \times m \times p$  array (already promoted from a matrix).  
`row_order, col_order` canonical actor names from `.fit_actor_order`.

### Value

`X` with rows / columns permuted into canonical order, or unchanged.

---

`.rotation_drift_diagnostic`*Rotation-drift diagnostic for the canonical ( $U_t$ ,  $G_t$ ,  $V_t$ ) trio*

---

### Description

Reports a scalar ratio comparing the variance of the *raw*  $G_t$  entries (per element across  $t$ ) to the variance of the *canonical*  $G_t$  entries (after per-period SVD). When the raw / canonical variance ratio is large ( $\geq 5$ ), the apparent  $G_t$  time-variation is dominated by rotation drift in  $U_t$ ,  $V_t$  rather than real temporal change. The canonicalisation removes that rotation and the canonical entries should be the user-facing summary.

### Usage

```
.rotation_drift_diagnostic(G_cube_raw, U_cube, V_cube)
```

**Arguments**

|            |                                       |
|------------|---------------------------------------|
| G_cube_raw | RA x RB x T raw (FFBS-sampled) G cube |
| U_cube     | nA x RA x T raw U cube                |
| V_cube     | nB x RB x T raw V cube                |

**Value**

list with ratio (numeric), var\_raw (RA x RB), var\_canonical (RA x RB), flag (logical: ratio >= 5)

---

*.sweep\_per\_actor\_exact*

*Per-actor sweep: unconstrained per-actor FFBS + exact projection*

---

**Description**

One full sweep over actors: each actor's path is sampled from its conditional AR(1) posterior via `.actor_ffbs_path()`, and the joint sample is then projected to satisfy  $\sum_i \theta_i(t) = 0$  per period using the variance-weighted Lagrangian.

**Usage**

```
.sweep_per_actor_exact(H_mat, h_mat, rho_actor, sigma_actor2)
```

**Arguments**

|              |                                                  |
|--------------|--------------------------------------------------|
| H_mat        | n_actors x T precision sufficient statistics     |
| h_mat        | n_actors x T cross-product sufficient statistics |
| rho_actor    | AR(1) coefficient                                |
| sigma_actor2 | AR(1) innovation variance                        |

**Value**

n\_actors x T matrix of centered draws.

---

|                             |                                                             |
|-----------------------------|-------------------------------------------------------------|
| <code>.xbeta_newdata</code> | <i>Name-safe linear predictor from a newdata prediction</i> |
|-----------------------------|-------------------------------------------------------------|

---

**Description**

Convenience wrapper: builds the full canonical design via `.build_full_design` and contracts it against a named coefficient vector. Because the design is rebuilt in the model's slice order, the positional contraction is correct even with nodal covariates.

**Usage**

```
.xbeta_newdata(beta, newdata, fitted_design, n, m)
```

**Arguments**

|                            |                                                                                              |
|----------------------------|----------------------------------------------------------------------------------------------|
| <code>beta</code>          | named numeric coefficient vector (a single draw or the posterior mean).                      |
| <code>newdata</code>       | dyadic covariate array (see <code>.build_full_design</code> ).                               |
| <code>fitted_design</code> | fitted design array ( <code>fit\$X</code> ); held-fixed source for intercept + nodal slices. |
| <code>n, m</code>          | output dimensions.                                                                           |

**Value**

an  $n \times m$  matrix of the linear predictor.

---

|                      |                                                     |
|----------------------|-----------------------------------------------------|
| <code>ab_plot</code> | <i>Visualize sender and receiver random effects</i> |
|----------------------|-----------------------------------------------------|

---

**Description**

Creates a visualization of the additive sender (row) and receiver (column) random effects from an AME or LAME model. Automatically detects whether effects are static or dynamic and provides appropriate visualization options.

**Usage**

```
ab_plot(
  fit,
  effect = c("sender", "receiver"),
  sorted = TRUE,
  labels = NULL,
  title = NULL,
  time_point = NULL,
  plot_type = c("snapshot", "trajectory", "faceted", "ribbon"),
  show_actors = NULL
)
```

### Arguments

|             |                                                                                                                                                                                                                          |
|-------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| fit         | An object of class "ame" or "lame" from fitting an AME model                                                                                                                                                             |
| effect      | Character string specifying which effect to plot: "sender" (default) or "receiver"                                                                                                                                       |
| sorted      | Logical; if TRUE (default), actors are sorted by effect magnitude. Applies to ame / lame fits; ame_als fits are always sorted by value.                                                                                  |
| labels      | Logical; if TRUE, actor labels are shown on x-axis (default TRUE for n <= 50 actors). Applies to ame / lame fits.                                                                                                        |
| title       | Optional title for the plot (ame / lame fits).                                                                                                                                                                           |
| time_point  | For dynamic effects, which time point to plot (default: last). Can be a numeric index, "all" for a faceted plot, or "average" for time-averaged                                                                          |
| plot_type   | For dynamic effects: "snapshot" (single time), "trajectory" (evolution over time), "faceted" (grid of time points), or "ribbon" (effect path with a 95\ band per period). For static effects, this parameter is ignored. |
| show_actors | Character vector of specific actors to highlight (for dynamic trajectory / ribbon plots)                                                                                                                                 |

### Details

The additive effects in AME models represent:

**Sender effects (a)** Actor-specific tendencies to form outgoing ties. Positive values indicate actors who send more ties than expected; negative values indicate actors who send fewer ties.

**Receiver effects (b)** Actor-specific tendencies to receive incoming ties. Positive values indicate actors who receive more ties than expected; negative values indicate actors who receive fewer ties.

For static effects, the plot displays these effects as a dot plot with vertical lines extending from zero to each effect estimate.

For dynamic effects (when fit contains a\_dynamic/b\_dynamic), additional options are available to visualize how effects evolve over time.

### Value

A ggplot2 object that can be further customized

### Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

### Examples

```
# Fit an AME model
data(YX_nrm)
fit <- ame(YX_nrm$Y, Xdyad = YX_nrm$X,
           nscan = 100, burn = 10, odens = 1, verbose = FALSE)

# Visualize sender effects
```

```
ab_plot(fit, effect = "sender")

# Visualize receiver effects without sorting
ab_plot(fit, effect = "receiver", sorted = FALSE)
```

---

|                 |                                                 |
|-----------------|-------------------------------------------------|
| ab_plot.ame_als | <i>Additive-effects plot for an ame_als fit</i> |
|-----------------|-------------------------------------------------|

---

### Description

Sender (a) and receiver (b) additive-effect point estimates as a sorted lollipop chart. Mirrors [ab\\_plot](#) but without posterior intervals: this is a point estimator. If the fit was produced via `ame_als(..., bootstrap = N)`, bootstrap 95\ error bars.

### Usage

```
ab_plot.ame_als(
  fit,
  effect = c("sender", "receiver", "both"),
  top_n = Inf,
  ...
)
```

### Arguments

|                     |                                                                                                                         |
|---------------------|-------------------------------------------------------------------------------------------------------------------------|
| <code>fit</code>    | an <code>ame_als</code> fit.                                                                                            |
| <code>effect</code> | "sender" (default), "receiver", or "both".                                                                              |
| <code>top_n</code>  | integer; show only the top / bottom <code>top_n</code> actors by absolute effect (default <code>Inf</code> , show all). |
| <code>...</code>    | reserved.                                                                                                               |

### Value

A ggplot object.

---

addhealthc3

*AddHealth community 3 data*


---

**Description**

A valued sociomatrix (Y) and matrix of nodal attributes (X) for students in community 3 of the AddHealth study.

- Y: A sociomatrix in which the value of the edge corresponds to an ad-hoc measure of intensity of the relation. Note that students were only allowed to nominate up to 5 male friends and 5 female friends.
- X: Matrix of students attributes, including sex, race (1=white, 2=black, 3=hispanic, 4=asian, 5=mixed/other) and grade.

Originally available at <http://moreno.ss.uci.edu/data.html#adhealth> (site no longer accessible).

**Usage**

```
data(addhealthc3)
```

**Format**

```
list
```

---

addhealthc9

*AddHealth community 9 data*


---

**Description**

A valued sociomatrix (Y) and matrix of nodal attributes (X) for students in community 9 of the AddHealth study.

- Y: A sociomatrix in which the value of the edge corresponds to an ad-hoc measure of intensity of the relation. Note that students were only allowed to nominate up to 5 male friends and 5 female friends.
- X: Matrix of students attributes, including sex, race (1=white, 2=black, 3=hispanic, 4=asian, 5=mixed/other) and grade.

Originally available at <http://moreno.ss.uci.edu/data.html#adhealth> (site no longer accessible).

**Usage**

```
data(addhealthc9)
```

**Format**

```
list
```



---

|                  |                                                        |
|------------------|--------------------------------------------------------|
| als_dynamic_beta | <i>Penalised ALS time-varying coefficient estimate</i> |
|------------------|--------------------------------------------------------|

---

### Description

Computes a fast point estimate of a time-varying coefficient vector  $\beta_t$  for a longitudinal network model by solving the first-difference-penalised least-squares problem. No MCMC, no multiplicative effects, no random effects – purely a regression point estimate with a smoothing penalty on the coefficient path. Useful for rapid exploration and for generating starting values for a full `lame(dynamic_beta = ...)` fit.

### Usage

```
als_dynamic_beta(Y, Xdyad, lambda = 0, intercept = TRUE)
```

### Arguments

|                        |                                                                                                                   |
|------------------------|-------------------------------------------------------------------------------------------------------------------|
| <code>Y</code>         | A list of $T$ response matrices (or a 3-D array with third dimension time).                                       |
| <code>Xdyad</code>     | A list of $T$ dyadic covariate arrays (each $n \times n \times p$ , or a single $n \times n$ matrix if $p = 1$ ). |
| <code>lambda</code>    | Non-negative smoothing parameter. Default 0 (no penalty, per-period OLS).                                         |
| <code>intercept</code> | Logical; include an intercept (default TRUE).                                                                     |

### Details

$$\min_{\beta_{1:T}} \sum_t \|y_t - X_t \beta_t\|^2 + \lambda \sum_{t=2}^T \|\beta_t - \beta_{t-1}\|^2$$

At  $\lambda = 0$  this is  $T$  independent per-period OLS fits. As  $\lambda \rightarrow \infty$  the solution converges to a single pooled  $\beta$  (constant over time).

### Value

A list with `beta` (a  $p \times T$  matrix of estimates), `lambda`, `residual_ss` (sum of squared residuals across periods), `intercept`, and `call`. Class `"als_dynamic_beta"`.

### Relation to other entry points

`als_dynamic_beta` is a *regression-only smoother*; the returned object carries time-varying  $\beta_t$  alone, no additive ( $a, b$ ) or multiplicative ( $U, V$ ) AME components. It is therefore not a special case of `lame_als` (which always estimates the full AME decomposition) and not a special case of `lame(dynamic_beta = TRUE)` (which is Bayesian with an AR(1) / RW1 / RW2 / Matern 3/2 state-space prior). Use it when you want a fast, point-only, deterministic smoother for the coefficient path; use `lame(dynamic_beta = ...)` when you need full posterior uncertainty and additive / multiplicative effects.

**See Also**

[lame](#) for the full Bayesian dynamic- $\beta$  fit (AR(1) / RW1 / RW2 / Matern 3/2); [lame\\_als](#) for the longitudinal AME point estimator (static  $\beta$ , full  $a, b, U, V$ ).

**Examples**

```
set.seed(1)
n <- 10; Tn <- 4
X <- replicate(Tn, array(rnorm(n*n*2), c(n, n, 2)), simplify = FALSE)
beta_true <- rbind(seq(-1, 1, length.out = Tn), seq(0.5, -0.5, length.out = Tn))
Y <- vector("list", Tn)
for (t in seq_len(Tn)) {
  Yt <- X[[t]][, , 1] * beta_true[1, t] + X[[t]][, , 2] * beta_true[2, t] +
    matrix(rnorm(n*n, 0, 0.2), n, n)
  diag(Yt) <- NA
  Y[[t]] <- Yt
}
fit_als <- als_dynamic_beta(Y, X, lambda = 0)      # per-period LS
fit_smooth <- als_dynamic_beta(Y, X, lambda = 10) # smoother path
```

---

als\_start\_vals

---

*Convert an ALS fit to MCMC starting values*


---

**Description**

Builds a `start_vals` list for [ame](#) or [lame](#) from an ALS point estimate. This is useful when the ALS fit has already found a good latent-space solution and the MCMC chain should start near that solution rather than from diffuse random values.

**Usage**

```
als_start_vals(fit, jitter = 0, seed = NULL)
```

**Arguments**

|                     |                                                                                                                                                               |
|---------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>fit</code>    | a fitted <a href="#">ame_als</a> , <a href="#">lame_als</a> , or dynamic ALS object returned by <a href="#">lame</a> with <code>method = "als"</code> .       |
| <code>jitter</code> | non-negative standard deviation for independent Gaussian perturbations added to numeric starting values. Use a small positive value for multiple MCMC chains. |
| <code>seed</code>   | optional integer seed used for the jitter.                                                                                                                    |

**Value**

A list that can be passed to `start_vals`.

ame

*AME model fitting routine***Description**

An MCMC routine providing a fit to an additive and multiplicative effects (AME) regression model to cross-sectional relational data of various types. This function supports both unipartite (square) and bipartite (rectangular) networks. For longitudinal networks, use the `lame` function. The additive and multiplicative effects framework is due to Hoff (2005, 2021).

**Usage**

```
ame(
  Y,
  Xdyad = NULL,
  Xrow = NULL,
  Xcol = NULL,
  rvar = TRUE,
  cvar = TRUE,
  dcor = !symmetric,
  nvar = TRUE,
  R = 0,
  R_row = NULL,
  R_col = NULL,
  mode = c("unipartite", "bipartite"),
  family = "normal",
  intercept = !(family == "ordinal"),
  symmetric = FALSE,
  odmax = rep(max(apply(Y > 0, 1, sum, na.rm = TRUE)), nrow(Y)),
  prior = list(),
  g = NA,
  seed = 6886,
  nscan = 10000,
  burn = 500,
  odens = 25,
  verbose = TRUE,
  gof = TRUE,
  custom_gof = NULL,
  plot = FALSE,
  start_vals = NULL,
  periodic_save = FALSE,
  out_file = NULL,
  save_interval = 0.25,
  posterior_opts = NULL,
  n_chains = 1,
  cores = 1,
  use_sparse_matrices = FALSE,
```

```

method = c("mcmc", "als"),
bootstrap = 0L,
bootstrap_type = c("parametric", "block"),
bootstrap_block_length = 1L,
bootstrap_seed = NULL,
save_log_lik = FALSE,
ordinal_cutpoints = c("data_induced", "explicit"),
print,
...,
model.name = NULL
)

```

## Arguments

|       |                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|-------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Y     | For unipartite: an $n \times n$ square relational matrix. For bipartite: an $nA \times nB$ rectangular relational matrix where $nA$ is the number of row nodes and $nB$ is the number of column nodes. A cross-sectional <b>netify</b> object is also accepted and converted with <code>netify::to_lame()</code> ; when family or mode is omitted, the value inferred by <b>netify</b> is used. See family below for data types. |
| Xdyad | For unipartite: an $n \times n \times$ pd array of dyadic covariates (e.g. distance, shared group). For bipartite: an $nA \times nB \times$ pd array. A 2-D matrix (single dyadic covariate) must be wrapped as <code>array(x, dim = c(n, n, 1))</code> ; Inf/NaN entries are rejected.                                                                                                                                          |
| Xrow  | For unipartite: an $n \times pr$ matrix of <b>sender</b> (row) covariates (e.g. sender's age, group). For bipartite: an $nA \times pr$ matrix of row-node covariates. A <code>data.frame</code> is accepted and coerced to numeric matrix internally.                                                                                                                                                                            |
| Xcol  | For unipartite: an $n \times pc$ matrix of <b>receiver</b> (column) covariates. For bipartite: an $nB \times pc$ matrix of column-node covariates. A <code>data.frame</code> is accepted and coerced internally.                                                                                                                                                                                                                 |
| rvar  | logical: fit row random effects (asymmetric case)?                                                                                                                                                                                                                                                                                                                                                                               |
| cvar  | logical: fit column random effects (asymmetric case)?                                                                                                                                                                                                                                                                                                                                                                            |
| dcor  | logical: fit a dyadic correlation (asymmetric case)? Note: not used for bipartite networks.                                                                                                                                                                                                                                                                                                                                      |
| nvar  | logical: fit nodal random effects (symmetric case)?                                                                                                                                                                                                                                                                                                                                                                              |
| R     | integer: dimension of the multiplicative effects (can be zero). For bipartite networks, this is used as the default for both <code>R_row</code> and <code>R_col</code> if they are not specified.                                                                                                                                                                                                                                |
| R_row | integer: for bipartite networks, dimension of row node multiplicative effects (defaults to R)                                                                                                                                                                                                                                                                                                                                    |
| R_col | integer: for bipartite networks, dimension of column node multiplicative effects (defaults to R)                                                                                                                                                                                                                                                                                                                                 |
| mode  | character: either "unipartite" (default) for square networks or "bipartite" for rectangular networks. Not all combinations of family and mode are supported – see the table under <b>Supported family x mode combinations</b> below.                                                                                                                                                                                             |

|           |                                                                                                                                                                                                                                               |
|-----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| family    | character: one of "normal", "binary", "ordinal", "cbin", "frn", "poisson". See the <b>Supported family x mode combinations</b> table below for which combinations are valid; see <b>Details</b> for the model assumptions behind each family. |
| intercept | logical: fit model with an intercept?                                                                                                                                                                                                         |
| symmetric | logical: Is the sociomatrix symmetric by design?                                                                                                                                                                                              |
| odmax     | a scalar integer or vector of length n giving the maximum number of nominations that each node may make - used for "frn" and "cbin" families                                                                                                  |
| prior     | a list containing hyperparameters for the prior distributions. Available options and their defaults:                                                                                                                                          |

**Sab0** Prior scale matrix for the additive-effects covariance. A 2x2 matrix where  $Sab0[1,1]$  is the prior variance for row effects,  $Sab0[2,2]$  is the prior variance for column effects, and off-diagonals control correlation between row and column effects. For a unipartite fit this defaults to  $diag(2)$  scaled to the observed sender/receiver heterogeneity in Y (unconditionally for the continuous families, conditionally for the discrete ones); a bipartite fit defaults to  $diag(2)$ . See the note on the additive-effects variance scale in Details. Pass  $diag(2)$  explicitly for a fixed unit-scale prior.

**eta0** Prior degrees of freedom for the additive-effects covariance  $\Sigma_{ab}$  (default:  $round(4 + 3 \cdot n/100)$  for a unipartite continuous-family fit,  $round(4 \cdot vdfmlt)$  for a unipartite discrete-family fit, and  $4 + 3 \cdot (nA + nB) / 200$  for a bipartite fit – except bipartite "binary", which also uses  $round(4 \cdot vdfmlt)$  – where n is the number of actors and vdfmlt is a probit-moment variance multiplier estimated from Y). Higher values impose stronger shrinkage of the row/column effects toward the prior scale. The multiplicative-effects degrees of freedom are controlled by kappa0, not eta0.

**etaab** Prior degrees of freedom for covariance of additive effects (default:  $4 + 3 \cdot n/100$ ). Controls shrinkage of row/column random effects. Larger values shrink effects toward zero. *Used by the bipartite and longitudinal paths; ignored for a unipartite cross-sectional ame() fit, which controls the additive prior through Sab0 and eta0.*

**s20** Prior scale for the dyadic residual variance  $v_e$  (default: 1), entering the inverse-gamma draw as a pseudo-observation scale. Larger values pull  $v_e$  upward. The regression-coefficient prior is controlled separately by g, not by s20.

**s2u0** Prior variance for multiplicative effects (default: 1). *Used by the bipartite and longitudinal paths.*

**Suv0** Inverse-Wishart (inverse) scale matrix for the multiplicative-effects covariance. The prior scale is  $kappa0 \cdot Suv0$  and the prior mean is  $kappa0 \cdot Suv0 / (kappa0 - 2 \cdot R - 1)$ . When not supplied it defaults to  $diag(2 \cdot R)$  times a scale estimated from the data.

**kappa0** Prior degrees of freedom for the multiplicative-effects covariance  $\Sigma_{uv}$  (default when  $R > 0$ :  $2 \cdot R + 2$ , times the same probit-moment multiplier as eta0 for a unipartite discrete-family fit). Higher values impose stronger shrinkage of the latent factors toward the prior scale  $kappa0 \cdot Suv0$ .

Common usage: `prior = list(Sab0 = diag(c(2, 2)), eta0 = 10)` for moderate shrinkage, or `prior = list(Sab0 = diag(c(0.5, 0.5)))` for tighter control. For a unipartite cross-sectional `ame()` fit the prior is controlled by Sab0, eta0, Suv0 and g.

|                             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|-----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>g</code>              | optional <b>scalar</b> for the Zellner g-prior on regression coefficients ( $\beta \sim N(0, g * \sigma^2 * \text{solve}(XtX))$ where $XtX$ is the design cross-product). If not specified, defaults are: for normal family, $g = n * \text{var}(Y)$ ; for other families, $g = n$ (number of non-missing dyads). Per-coefficient (vector) $g$ is not currently supported by the unipartite path – pass a scalar. <i>Note:</i> $g$ is a top-level argument to <code>ame()</code> , <b>not</b> an element of <code>prior = list(...)</code> ; passing <code>prior = list(g = 0.1)</code> is a no-op (warned about).                                                                                                                                                                                                                                  |
| <code>seed</code>           | random seed for the MCMC sampler (default 6886). The sampler is seeded internally with this value, so results are reproducible by default and an external <code>set.seed()</code> call has <i>no</i> effect on the chain – pass a different seed here to vary the draws (e.g. when running multiple chains). The caller's <code>.Random.seed</code> is restored on exit, so fitting never perturbs your RNG stream.                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| <code>nscan</code>          | number of iterations of the Markov chain (beyond burn-in)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <code>burn</code>           | burn in for the Markov chain. Typical use is burn far smaller than <code>nscan</code> ; <code>burn &gt; nscan</code> is allowed but warns.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| <code>odens</code>          | output density (thinning interval) for the Markov chain. <code>nscan / odens</code> samples are stored.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <code>verbose</code>        | logical: print progress while running? Default TRUE.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <code>gof</code>            | logical: calculate goodness of fit statistics? Setting to TRUE adds approximately 2-5% to runtime. For faster sampling without GOF overhead, set <code>gof=FALSE</code> and use <code>gof()</code> after model fitting.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <code>custom_gof</code>     | optional function or list of named functions for computing custom goodness-of-fit statistics. Each function must accept a single matrix <code>Y</code> as input and return a numeric vector. If a single function is provided, it should return a named vector. If a list of functions is provided, each function should return a single value and will be named according to the list names. Custom statistics will be computed in addition to default statistics. Example: <code>custom_gof = function(Y) c(density = mean(Y &gt; 0, na.rm = TRUE))</code>                                                                                                                                                                                                                                                                                        |
| <code>plot</code>           | accepted for signature parity with <a href="#">lame</a> ; ignored. <code>ame()</code> runs a single-period MCMC and does not draw live trace panels. Default FALSE.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| <code>start_vals</code>     | List from previous model run containing parameter starting values for new MCMC                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| <code>periodic_save</code>  | logical: indicating whether to periodically save MCMC results                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <code>out_file</code>       | character vector indicating name and path in which file should be stored if <code>periodic_save</code> is selected. For example, on an Apple OS <code>out_file = "~/Desktop/ameFit.rda"</code> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <code>save_interval</code>  | quantile interval indicating when to save during the post-burn-in period.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <code>posterior_opts</code> | optional list of posterior draw-storage options, usually built with <a href="#">posterior_options</a> . Recognised names (unknown names trigger a warning): <code>save_UV</code> , <code>save_UV_draws</code> , <code>save_ab</code> , <code>thin_UV</code> , <code>thin_ab</code> . <code>save_UV = TRUE</code> stores per-iteration latent-position draws on <code>fit\$U_samples / fit\$V_samples</code> ([ <code>actor</code> , <code>dim</code> , <code>draw</code> ] arrays; bi-partite fits also store the interaction-matrix draws on <code>fit\$G_samples</code> ); <code>save_UV_draws</code> (the <a href="#">lame</a> spelling) is accepted as an alias. <code>save_ab = TRUE</code> stores additive-effect draws on <code>fit\$a_samples / fit\$b_samples</code> . <code>thin_UV / thin_ab</code> thin the stored draws. Default NULL. |
| <code>n_chains</code>       | integer: number of MCMC chains to run (default: 1)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |

|                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|-------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>cores</code>                  | integer: number of cores for parallel chains (default: 1)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <code>use_sparse_matrices</code>    | logical: use sparse matrix storage for large networks? (default: FALSE). Recommended only for truly sparse networks (< 10% non-zero entries).                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <code>method</code>                 | character: "mcmc" (default, the Bayesian MCMC fit) or "als" (the fast, MCMC-free iterative block coordinate descent point estimator). When <code>method = "als"</code> , MCMC-specific arguments ( <code>nscan</code> , <code>burn</code> , <code>odens</code> , <code>prior</code> , ...) are warned about and ignored; the call forwards to <a href="#">ame_als</a> .                                                                                                                                                                                                                                                    |
| <code>bootstrap</code>              | integer (only used when <code>method = "als"</code> ): number of bootstrap replicates. 0 (default) skips the bootstrap; $N > 0$ runs $N$ replicates and attaches the result so that <a href="#">confint</a> returns bootstrap intervals.                                                                                                                                                                                                                                                                                                                                                                                   |
| <code>bootstrap_type</code>         | character (only used when <code>method = "als"</code> ): "parametric" (default) or "block".                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <code>bootstrap_block_length</code> | integer: block length for the block bootstrap.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <code>bootstrap_seed</code>         | optional integer seed for the bootstrap.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <code>save_log_lik</code>           | logical: when TRUE, attach a per-iteration pointwise log-likelihood matrix <code>fit\$log_lik</code> (an <code>n_iter</code> x <code>n_obs</code> array), required for <code>loo(fit)</code> and <code>waic(fit)</code> . For families normal, binary, cbin, poisson, and ordinal this is the exact observed-data log density of $Y$ ( <code>fit\$log_lik_method = "observed_exact"</code> ); only <code>frn</code> falls back to the augmented-Z normal approximation on the latent scale (with a one-time warning). Default FALSE (no <code>log_lik</code> storage; default fit is byte-identical to previous releases). |
| <code>ordinal_cutpoints</code>      | character: cutpoint convention for <code>family = "ordinal"</code> . "data_induced" (default) uses the data-induced cutpoints; "explicit" samples explicit cutpoints via a Cowles (1996) Metropolis-Hastings update. Ignored for other families.                                                                                                                                                                                                                                                                                                                                                                           |
| <code>print</code>                  | Deprecated. Use <code>verbose</code> instead.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <code>...</code>                    | reserved for future use. Passing <code>lame()</code> -only arguments (e.g. <code>dynamic_beta</code> , <code>period_exposure</code> ) here triggers a clean abort directing you to <a href="#">lame</a> ; passing any other unrecognised name warns so typos are visible rather than silently dropped.                                                                                                                                                                                                                                                                                                                     |
| <code>model.name</code>             | optional string for model selection output                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |

## Details

This command provides posterior inference for parameters in AME models of cross-sectional relational data, assuming one of eight possible data types/models. The function supports both unipartite networks (square adjacency matrices) and bipartite networks (rectangular adjacency matrices with distinct row and column node sets) for single time point analysis.

**Model.** For a dyad  $(i, j)$  the AME linear predictor is

$$\eta_{ij} = \beta_0 + x'_{ij}\beta + a_i + b_j + u'_i Dv_j,$$

where  $\beta$  are regression coefficients on dyadic / nodal covariates,  $a_i$  is a row (sender) random effect,  $b_j$  is a column (receiver) random effect, and  $u'_i Dv_j$  is the multiplicative latent-factor term (rank  $R$ ).

The observation model is  $Y_{ij} \sim F(\eta_{ij}, \theta)$  with  $F$  specified by family (Gaussian for "normal", probit for "binary" / "cbin", etc.). For unipartite (symmetric = FALSE) the residual error has dyad-level correlation  $\rho$  between  $(i, j)$  and  $(j, i)$ ; for bipartite, dyad correlation is fixed at 0.

**Priors (in brief).**  $\beta$  has a Zellner-style g-prior (g);  $(a_i, b_i)$  are jointly Normal with covariance  $\Sigma_{ab}$  (Inverse-Wishart prior Sab0 / eta0);  $u_i, v_j$  are independent Normal with covariance  $\Sigma_{uv}$  (Inverse-Wishart prior with scale kappa0 \* Suv0 and kappa0 degrees of freedom); the dyad-correlation  $\rho$  has an arc-sine prior on  $(-1, 1)$  (density proportional to  $(1 - \rho^2)^{-1/2}$ ), updated with Metropolis steps. See prior\_summary(fit) for the priors actually used.

**Choosing R.** The multiplicative rank R controls the dimensionality of latent homophily / heterogeneity not explained by covariates and additive effects.  $R = 0$  fits an additive-only social-relations model;  $R = 1$  or 2 is typical for small / medium networks;  $R > \text{floor}(n/3)$  is rarely identifiable and will issue a warning. Latent factors capture unobserved structure (clusters, hub patterns, transitive triangles the covariates miss) and are accessed at fit\$U, fit\$V.

**Identifiability.** The latent factor term  $u_i' D v_j$  is invariant to rotation and reflection of  $U, V$ ; the package canonicalises with an SVD so successive draws are interpretable. For visual stability across posterior summaries see [procrustes\\_align](#) and [latent\\_positions](#).

#### Theoretical Foundation:

The AME model decomposes network structure into several components:

$$y_{ij} = \beta' x_{ij} + a_i + b_j + u_i' v_j + \epsilon_{ij}$$

where:

- $\beta' x_{ij}$ : Fixed effects of dyadic/nodal covariates
- $a_i$ : Additive sender (row) effect for node i
- $b_j$ : Additive receiver (column) effect for node j
- $u_i' v_j$ : Multiplicative interaction between latent factors
- $\epsilon_{ij}$ : Dyadic error term (may be correlated)

This specification generalizes the social relations model (Warner et al. 1979) and latent space models (Hoff et al. 2002) within a unified framework.

#### Prior Distributions:

The model uses conjugate and semi-conjugate priors where possible:

- Regression coefficients:  $\beta \sim N(0, g\sigma^2(X'X)^{-1})$  (g-prior)
- Additive effects:  $(a_i, b_i)' \sim N(0, \Sigma_{ab})$  jointly
- Covariance:  $\Sigma_{ab} \sim IW(\eta_0, \eta_0 S_{ab0})$  (inverse-Wishart)
- Multiplicative effects: Hierarchical shrinkage via  $\eta_0$
- Dyadic correlation: arc-sine prior on  $(-1, 1)$ , density  $p(\rho) \propto (1 - \rho^2)^{-1/2}$ , with Metropolis updates

The inverse-Wishart prior on  $\Sigma_{ab}$  allows learning correlation between sender and receiver effects, capturing reciprocity patterns.

Note on the additive-effects variance scale: for a unipartite fit Sab0 defaults to a data-scaled matrix rather than a fixed diag(2). For the "normal" and "poisson" families the default is Sab0 =



$\text{diag}(2) * \text{vscale}$ , where  $\text{vscale}$  is an empirical-Bayes moment estimate of the sender/receiver variance: the mean of the variances of the centred row means and column means of  $Y$  (of  $\log 1p(Y)$  for "poisson"). The "binary", "ordinal", "cbin" and "frn" families apply the same idea to a probit-moment residual, but only when `start_vals` is not supplied and the design has at least one column; otherwise they fall back to  $\text{Sab0} = \text{diag}(2)$  with  $\text{eta0} = 4$ . A bipartite fit always uses  $\text{Sab0} = \text{diag}(2)$ . Call `prior_summary()` on a fitted object to see the prior actually used.

The data scaling matters because the inverse-Wishart prior contributes pseudo-data on the scale of  $\text{eta0} * \text{Sab0}$  no matter what units  $Y$  is in, so a fixed  $\text{Sab0} = \text{diag}(2)$  pulls the additive-effects variances  $\text{va}/\text{vb}$  upward whenever the true sender/receiver variance is well below 1, most visibly at small  $n$ . In Social Relations Model simulations the data-scaled default recovers small true variances with modest bias where a fixed  $\text{diag}(2)$  prior can nearly double them; the data-scaled prior is mildly more conservative in the opposite regime, when the true variance is large relative to the residual scale.

This default differs from the `amen` package, whose `ame(family = "nrm")` leaves  $\text{Sab0} = \text{diag}(2)$  and  $\text{eta0} = 4$ . To reproduce `amen`'s additive-effects posterior, pass `prior = list(Sab0 = diag(2), eta0 = 4)`. The choice affects only  $\text{va}$ ,  $\text{vb}$  and (weakly)  $\text{cab}$ ;  $\text{ve}$  and  $\text{rho}$  are unchanged.

### Multiplicative Effects (Latent Factors):

When  $R > 0$ , the model includes  $R$ -dimensional latent factors:

- Asymmetric case:  $u_i, v_j \in \mathbb{R}^R$  with  $u_i' v_j$  interaction
- Symmetric case:  $u_i = v_i$  with eigendecomposition  $U L U'$
- Captures homophily, transitivity, and community structure
- $R$  chosen via model selection or set to 2-3 for visualization

### Estimation Algorithm:

The model uses a Gibbs sampler with the following updates:

1. Sample latent  $Z$  given parameters (data augmentation for non-normal families)
2. Update regression coefficients  $\beta$  via g-prior conjugate update
3. Update additive effects (a,b) jointly with  $\beta$
4. Update covariance  $\Sigma_{ab}$  from inverse-Wishart
5. Update multiplicative effects  $U, V$  via Gibbs or Metropolis-Hastings
6. Update dyadic correlation  $\rho$  via Metropolis-Hastings
7. Update variance  $\sigma^2$  (for continuous families)

### Standard Model Types:

The following data types/models are available:

"normal": A normal AME model (identity link:  $E[Y] = \eta$ ).

"binary": A binary probit AME model (probit link:  $P(Y = 1) = \Phi(\eta)$ ).

"ordinal": An ordinal probit AME model (cumulative probit link). An intercept is not identifiable in this model.

"cbin": An AME model for censored binary data (probit link with censoring). The value of 'odmax' specifies the maximum number of links each row may have.

"frn": An AME model for fixed rank nomination networks. A higher value of the rank indicates a stronger relationship. The value of 'odmax' specifies the maximum number of links each row may have.

"poisson": An overdispersed Poisson AME model for count data:  $Y \sim \text{Poisson}(\exp(z))$  with  $z \sim N(\eta, \sigma^2)$ , a lognormal-mixed Poisson. The conditional mean given the latent  $z$  is  $\exp(z)$ ; the marginal mean is  $\exp(\eta + \sigma^2/2)$ , not  $\exp(\eta)$ .

## Value

### Posterior Samples (full MCMC chains):

|      |                                                                                                                                                                                                                                                      |
|------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| BETA | Regression coefficients (nscan/odens x p matrix; one row per stored draw)                                                                                                                                                                            |
| VC   | Variance components (nscan/odens x k matrix)                                                                                                                                                                                                         |
| GOF  | Goodness-of-fit statistics ((nscan/odens + 1) x 5 matrix). First row contains observed values, remaining rows contain posterior predictive samples. See <a href="#">gof</a> for post-hoc computation and <a href="#">gof_plot</a> for visualization. |

### Posterior Means (averaged over chain):

|     |                                                                                     |
|-----|-------------------------------------------------------------------------------------|
| APM | Additive row/sender effects (n-vector)                                              |
| BPM | Additive column/receiver effects (m-vector); NULL for symmetric networks            |
| U   | Multiplicative row/sender factors (n xR matrix)                                     |
| V   | Multiplicative column/receiver factors (m xR matrix); NULL for symmetric networks   |
| L   | Eigenvalue matrix (R xR diagonal); symmetric networks only                          |
| YPM | Posterior mean of Y on response scale (for predictions and imputing missing values) |

### Metadata:

|           |                                            |
|-----------|--------------------------------------------|
| family    | Model family (normal, binary, etc.)        |
| mode      | Network mode (unipartite or bipartite)     |
| symmetric | Logical indicating if network is symmetric |
| R         | Dimension of multiplicative effects        |

### Optional Posterior Samples (if requested via posterior\_options):

|           |                                                  |
|-----------|--------------------------------------------------|
| U_samples | Samples of U (n xR xiterations array)            |
| V_samples | Samples of V (m xR xiterations array)            |
| a_samples | Samples of row effects (n xiterations matrix)    |
| b_samples | Samples of column effects (m xiterations matrix) |

**Note on the latent-scale matrices:** The posterior-mean multiplicative product is stored on the fit (UVPM, or ULUPM for symmetric fits); EZ (the expected latent network) is not stored, to save memory. Accessors:

- `reconstruct_EZ(fit)` - Returns linear predictor (link scale, not response scale)

- `reconstruct_UVPM(fit)` - Returns the stored posterior-mean multiplicative product (UVPM / ULUPM) when present, otherwise `U\`

**Generating posterior distributions:** Use `simulate_posterior(fit, component="UV")` to generate posterior samples for components where only means are stored, or use `posterior_options()` during model fitting to save full posterior samples.

`model.name`      Name of the model (if provided)

### Supported family x mode combinations

Every family is supported under both modes. The bipartite Z-samplers live in `R/rZ_bipartite.R` and dispatch per family; see also the inline comment in `R/lame.R` (the rectangular samplers live in `R/rZ_bipartite.R`).

| family  | unipartite | bipartite |
|---------|------------|-----------|
| normal  | yes        | yes       |
| binary  | yes        | yes       |
| ordinal | yes        | yes       |
| cbin    | yes        | yes       |
| frn     | yes        | yes       |
| poisson | yes        | yes       |

Symmetric (`symmetric = TRUE`) fits require a symmetric `Y`. family = "ordinal" with `symmetric = TRUE` is supported via the dedicated sampler in `R/rZ_ord_sym_fc.R`, which uses the symmetric-doubled precision and mirrors upper-triangle draws to the lower triangle so  $Z = t(Z)$  holds at every sweep.

**Symmetric input with one triangle missing.** When `symmetric = TRUE` and one triangle of `Y` is fully NA (the user stored only the lower or upper triangle), the symmetry validator `any(is.finite(Y - t(Y)))` evaluates FALSE and the call proceeds: the sampler then treats the populated triangle as the symmetric data and mirrors it. This is usually intended, but if the upper / lower triangles were meant to differ, the model is silently fitting half the data. Audit `anyNA(Y[upper.tri(Y)]) != anyNA(Y[lower.tri(Y)])` before calling if you are unsure.

### Data preparation

`ame()` accepts a matrix directly. For long-format edgelist, bipartite data, and covariates, use **netify** to build the network object and pass that object as `Y`. `ame()` will call `netify::to_lame()` internally. If you already have an **igraph** or **network** object and only need a plain adjacency matrix, `as_lame_y` is still available as a small convenience helper.

For an undirected/symmetric network, pass `symmetric = TRUE`; for a rectangular two-mode network (students x courses, donors x candidates), pass `mode = "bipartite"` or build the **netify** object with `mode = "bipartite"`. `Xrow` and `Xcol` accept either a numeric matrix or a data.frame (coerced internally); `Xdyad` must be a 3-D array  $n \times n \times p$  of numeric covariates with no Inf/NaN.

## When to use AME vs ERGM

AME and ERGM are complementary tools for binary network analysis, not direct substitutes. **ERGM** is a class of exponential-family models built around explicit network statistics (counts of edges, mutual ties, triangles, geometrically-weighted shared partners, ...). You write the statistics you think matter, ERGM gives you their coefficients. ERGM excels when you have a substantive theory about which configurations drive tie formation.

**AME** models latent homophily / heterogeneity directly via sender, receiver, and multiplicative latent-factor effects. You don't enumerate triadic terms; the multiplicative-effects rank  $R$  captures higher-order structure (clustering, transitivity, hub patterns) implicitly. AME excels when (a) you have dyadic / nodal covariates whose effects you want to interpret cleanly without ERGM degeneracy, (b) higher-order structure is "nuisance" that you want to absorb but not parameterise, or (c) you need a posterior distribution over predictions for forecasting or imputation.

Practical guidance: if your research question is "do nodes that share attribute  $X$  tend to form triangles together?", reach for ERGM's gwesp. If your research question is "controlling for unobserved sender / receiver heterogeneity and latent clustering, what is the effect of dyadic covariate  $X$ ?", reach for AME. The  $R = 0$  additive-only case is the social relations model (Warner, Kenny, Stoto 1979);  $R \geq 1$  adds latent space.

## ERGM to AME translation

For users coming from `statnet::ergm`, the rough analogues are:

| ERGM term                     | AME analogue                                                                                                   |
|-------------------------------|----------------------------------------------------------------------------------------------------------------|
| edges                         | intercept (probit link, not logit)                                                                             |
| <code>nodecov("x")</code>     | $X_{row} = x$ or $X_{col} = x$                                                                                 |
| <code>nodematch("g")</code>   | dyadic covariate via <code>nodematch(g)</code> into $X_{dyad}$                                                 |
| <code>nodefactor("g")</code>  | dyadic covariate via <code>nodefactor(g)</code> into $X_{dyad}$ (drop one level)                               |
| <code>absdiff("z")</code>     | dyadic covariate via <code>absdiff(z)</code> into $X_{dyad}$                                                   |
| mutual                        | <code>dcov = TRUE</code> -> the rho parameter (probit-scale, not log-odds; not numerically comparable to ERGM) |
| gwesp / transitivity          | $R \geq 1$ multiplicative latent factors (not the same statistic)                                              |
| sender activity heterogeneity | <code>rvar = TRUE</code> , gives $a_i$ , $va$                                                                  |
| receiver popularity heterog.  | <code>cvar = TRUE</code> , gives $b_j$ , $vb$                                                                  |

For `family = "binary"` the link is probit, so the intercept is on the probit scale; do not compare it to an ERGM edges estimate by simple arithmetic.

## Migration from amen

Both `amen` and `lame` export `ame()`; loading both packages fires a startup warning telling you to call `lame::ame(...)` or `amen::ame(...)` explicitly.

For default cross-sectional calls, `lame::ame()` follows the `amen::ame()` interface: the `fit$BETA` slot is a 2-D  $[n\_stored, p]$  matrix in both packages, so scripts that call `colMeans(fit$BETA)` or `apply(fit$BETA, 2, mean)` continue to work unchanged. `lame` additionally accepts `family = "binary"` (which `amen` 1.4.5 no longer accepts; `amen` requires "bin"). The `print` argument is deprecated in favour of `verbose`; calls that pass `print = ...` still work but warn.

The cross-sectional path has no `dynamic_beta` option (an AR(1) prior on a single-period coefficient is unidentified), so the BETA 3-D shape that `lame()` can produce never arises from `ame()`. See [lame](#) for the longitudinal path and the silent-aggregation hazard with 2-D `apply(fit$BETA, 2, mean)` scripts under `dynamic_beta = TRUE`.

### Notes on priors

- The regression-coefficient prior is a Zellner g-prior ( $\beta \sim N(0, g * \sigma^2 * (XtX)^{-1})$  where  $XtX$  is the design cross-product).  $g$  is a *top-level* argument of `ame()`, not an entry in `prior = list(...)` (a common slip).
- There is no per-coefficient prior knob. If you need student\_t, horseshoe, or to centre a slope away from zero, AME does not currently expose it; the g-prior structure is the only knob.
- Unknown names in `prior = list(...)` are warned about (a typo like `Sab = ...` instead of `Sab0` would otherwise be silently dropped).

### Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

### See Also

[lame](#) for longitudinal models, [gof](#) for post-hoc goodness-of-fit computation, [gof\\_plot](#) for visualizing GOF results, [latent\\_positions](#) for extracting latent positions as a tidy data frame, [procrustes\\_align](#) for Procrustes alignment of latent positions, [summary.ame](#) for model summaries, [coef.ame](#) for coefficient extraction

### Examples

```
data(YX_bin)
fit <- ame(YX_bin$Y, Xdyad = YX_bin$X, burn = 10, nscan = 100, odens = 1,
          family = "binary", verbose = FALSE)
summary(fit)
# Note: you should run the Markov chain much longer in practice
```

---

ame\_als

*Fast (MCMC-free) AME estimation for a cross-sectional network*

---

### Description

Fits an additive and multiplicative effects (AME) model to a single cross-sectional network by **iterative block coordinate descent**, producing a fast point estimate with no MCMC and no credible intervals.

The estimation algorithm adapts the *iterative block coordinate descent* estimator of the Social Influence Regression (SIR) model of Hoff & Minhas (the algorithm implemented in `sir::sir_alsfit()` and nicknamed "ALS" in that package) to the AME model. It is a port and adaptation, not original **lame** methodology.

**Usage**

```
ame_als(
  Y,
  Xdyad = NULL,
  Xrow = NULL,
  Xcol = NULL,
  R = 0,
  family = "normal",
  mode = c("unipartite", "bipartite"),
  symmetric = FALSE,
  max_iter = 200,
  tol = 1e-06,
  lowrank_method = c("mm", "als", "hybrid"),
  non_normal_method = c("irls", "transform"),
  link = c("probit", "logit"),
  linear_solver = c("eigen", "qr", "auto"),
  multistart = c("none", "cheap", "full"),
  bootstrap = 0L,
  bootstrap_type = c("parametric", "block"),
  bootstrap_block_length = 1L,
  bootstrap_seed = NULL,
  verbose = TRUE,
  seed = 6886
)
```

**Arguments**

|           |                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|-----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Y         | a square (unipartite) or rectangular (bipartite) relational matrix. A cross-sectional <b>netify</b> object is also accepted and converted with <code>netify::to_lame()</code> ; when family or mode is omitted, the value inferred by <b>netify</b> is used.                                                                                                                                                                                                 |
| Xdyad     | an $n_{\text{row}} \times n_{\text{col}}$ matrix or $n_{\text{row}} \times n_{\text{col}} \times \text{pd}$ array of dyadic covariates, or NULL.                                                                                                                                                                                                                                                                                                             |
| Xrow      | an $n_{\text{row}} \times \text{pr}$ matrix of row/sender covariates, or NULL.                                                                                                                                                                                                                                                                                                                                                                               |
| Xcol      | an $n_{\text{col}} \times \text{pc}$ matrix of column/receiver covariates, or NULL.                                                                                                                                                                                                                                                                                                                                                                          |
| R         | integer dimension of the multiplicative effects (default 0). <b>The covariate coefficients are conditional on this choice.</b> The multiplicative term $u_i'v_j$ is a flexible high-variance regressor that can correlate with the dyadic covariates, so the estimated beta can shift – and occasionally change sign – as R increases. Comparing against an $R = 0$ fit is a useful check on whether the covariate story is being driven by the latent rank. |
| family    | one of "normal", "binary", or "poisson". The rank and censoring families are MCMC-only.                                                                                                                                                                                                                                                                                                                                                                      |
| mode      | "unipartite" (square) or "bipartite" (rectangular).                                                                                                                                                                                                                                                                                                                                                                                                          |
| symmetric | logical; fit a symmetric (undirected) model. Unipartite only.                                                                                                                                                                                                                                                                                                                                                                                                |
| max_iter  | maximum number of block coordinate descent iterations (default 200).                                                                                                                                                                                                                                                                                                                                                                                         |

|                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| tol                    | convergence tolerance on the relative change in residual sum of squares (default 1e-6).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| lowrank_method         | inner solver for the multiplicative (low-rank) block: "mm" (default) weighted majorise-minimise; "als" alternating least squares; "hybrid" runs both and keeps the lower-objective result. "als"/"hybrid" converge faster than "mm" on strongly unbalanced longitudinal panels and are available for directed and bipartite models (symmetric fits always use "mm"). All three minimise the same objective, so the point estimate is unchanged for balanced data.                                                                                                                                                                                              |
| non_normal_method      | for the non-normal ALS families, "irls" (default for binary/poisson) runs iteratively reweighted least squares, giving a fast approximate GLM AME fit with coefficients on the requested link scale (Poisson log, binary logit/probit). "transform" fits one fixed Gaussian working response ( $\log(y+1)$ for Poisson, rank-normal scores for binary); its coefficients are on an uncalibrated working scale and are mainly useful for direction/ranking checks. A directed $R > 0$ IRLS fit uses the hybrid low-rank solver internally because the IRLS weights are unbalanced. Uncertainty for either path comes from the bootstrap or sandwich covariance. |
| link                   | link for non_normal_method = "irls" with a binary family: "probit" (default; matches <a href="#">ame/lame</a> ) or "logit". poisson always uses the log link; ignored otherwise.                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| linear_solver          | solver for the regression block: "eigen" (default) eigendecomposes the normal equations; "qr" uses a QR factorisation of the observed design, which is more stable for ill-conditioned covariates; "auto" picks "qr" when the design is ill-conditioned but full rank. All give the same answer for well-conditioned designs.                                                                                                                                                                                                                                                                                                                                  |
| multistart             | for $R > 0$ (a non-convex objective), "none" (default) fits from a single deterministic start; "cheap" (4 starts) and "full" (8 starts) also try random low-rank starts and keep the lowest-SSE fit, warning when the starts reach materially different optima. Reproducible given seed; the global RNG stream is left unchanged.                                                                                                                                                                                                                                                                                                                              |
| bootstrap              | integer: if $> 0$ , additionally run bootstrap replicates of the parametric or block bootstrap (via <a href="#">ame_als_bootstrap</a> ) after the point fit and attach the result as <code>fit\$bootstrap</code> . The downstream accessors ( <code>confint.ame_als</code> , <code>summary</code> , <code>print</code> ) then surface bootstrap intervals instead of the anti-conservative sandwich Wald intervals. Default 0 (no bootstrap) – bootstrap is expensive, so it is not imposed on a user who just wants a quick fit.                                                                                                                              |
| bootstrap_type         | character: "parametric" (default) or "block" – the bootstrap scheme to use when <code>bootstrap &gt; 0</code> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| bootstrap_block_length | integer: block length for the block bootstrap; only used when <code>bootstrap_type = "block"</code> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| bootstrap_seed         | optional integer seed for the bootstrap (the point fit uses seed).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| verbose                | logical; print progress (default TRUE).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| seed                   | random seed (default 6886). The block coordinate descent is deterministic, so the point estimate is reproducible regardless; the argument is retained for API consistency with <a href="#">ame</a> .                                                                                                                                                                                                                                                                                                                                                                                                                                                           |

## Details

The AME decomposition

$$z_{ij} = \mu + \beta' x_{ij} + a_i + b_j + u_i' v_j + \epsilon_{ij}$$

is conditionally linear: it is a linear regression in  $(\mu, \beta, a, b)$  for fixed multiplicative factors  $(U, V)$ , and the optimal rank- $R$   $(U, V)$  for fixed  $(\mu, \beta, a, b)$  is the truncated SVD of the residual matrix. The estimator therefore cycles, until the residual sum of squares stabilises, through three blocks — each a monotone (objective-non-increasing) update: a joint least-squares solve for the intercept  $\mu$  and regression coefficients  $\beta$  (with a `ginv` pseudoinverse fallback for rank-deficient designs); Gauss-Seidel sweeps to convergence for the additive effects  $(a, b)$ ; and a weighted low-rank update for the multiplicative factors  $(U, V)$  via SVD (eigen-decomposition when `symmetric = TRUE`). The weighting makes the multiplicative step correct for unbalanced longitudinal panels (dyads observed at unequal numbers of time points); severely unbalanced panels may need more iterations to converge, so raise `max_iter` if the fit reports non-convergence.

For `family = "normal"` this is a least-squares (Gaussian maximum-likelihood) fit — the exact global solution when  $R = 0$ , and a local optimum of the non-convex low-rank objective when  $R > 0$ . For `"binary"` and `"poisson"`, the estimator uses an IRLS working-response path by default, so coefficients are on the requested link scale (binary probit/logit, Poisson log). The fixed-transform path is still available as a faster exploratory score, but its coefficients are not calibrated effect sizes. For  $R > 0$  the multiplicative factor block of the IRLS families solves a penalized (MAP) sub-problem: each factor row carries the ridge implied by the AME prior  $[u_i, v_i] \sim N(0, \Sigma_{uv})$ , with the per-column prior scale estimated by an EM step (the analog of the MCMC  $\Sigma_{uv}$  draw). This is what makes the estimate well-defined: the *unpenalized* rank- $R$  binary MLE does not exist under quasi-separation, and fitting it directly inflates every coefficient (a runaway that grows with  $R$ , with the latent variance diverging). With the penalty the latent variance does not run away and the slope inflation is bounded and stable in  $R$ ; a residual finite-sample (incidental-parameters) upward bias remains, on the order of +10-15% posterior mean). This residual is a property of the estimator class, not a code defect: because a nonlinear-likelihood point estimator profiles the  $2Rn$  latent factors at their joint optimum rather than integrating them, it cannot be consistent for the regression coefficient (Neyman-Scott). The bias is dominated by *rank over-specification* — it is largest when  $R$  is set higher than the data support (the factors then absorb noise) and is only  $\sim 5\% \text{ ame}() / \text{lame}()$  path integrates the factors out and is verified calibrated by simulation-based calibration, so binary  $R > 0$  ALS is best used as a fast exploratory / rank-selection score, with `ame(..., method = "mcmc")` for final coefficient inference (`bootstrap = N` gives ALS-scale intervals but reproduces, rather than removes, this bias). Rank and ordinal families (`"ordinal"`, `"cbin"`, `"frn"`) are not supported by ALS and raise an informative error; use `ame` or `lame` for those likelihoods.

**Row/column (node) covariates.** A node covariate broadcasts to a per-actor constant, which is collinear with the additive sender/receiver effect, so its coefficient is not identified by the objective alone. It is identified here by an explicit constraint: the additive effects are taken orthogonal to the node covariates, and `beta_row/beta_col` are the corresponding between-actor regression coefficients (the additive effects then carry only the residual heterogeneity). This is the standard estimand under the assumption that the additive effects are uncorrelated with the node covariates; if that assumption is doubtful the coefficient absorbs the covariate-correlated part of the additive heterogeneity. Time-varying node covariates are summarised by their per-actor mean; if a node covariate varies within actor over time the discarded within-actor variation triggers a warning.

**Identifiability of the additive and multiplicative terms.** For  $R > 0$  the additive term  $a_i + b_j$  and the multiplicative term  $u_i' v_j$  are not separately identified by the objective alone: a broadcast



(row- or column-constant) component can sit in either, since a pure sender effect  $a1'$  is itself rank one. The estimator imposes the standard AME gauge — the multiplicative term is double-centered (zero row and column means), so all broadcast structure is carried by  $a, b$  — which makes the reported  $a, b, U, V$  unique given the fitted values and independent of the optimisation path. For a unipartite network the double-centering means are taken over the full matrix, which includes the structurally unobserved self-tie diagonal that the model fills in by its low-rank completion; the additive/multiplicative split therefore carries an  $O(1/n)$  dependence on that completion. On a disconnected observed-dyad graph the additive effects additionally have a per-component level shift, which is pinned to a precision-weighted minimum-norm gauge so that  $a, b$  and the variance components remain reproducible. A dyadic covariate that is itself (near) low-rank can still be partially aliased with the multiplicative term, so keep  $R$  modest relative to the covariate structure. This residual aliasing is intrinsic to the AME model — the MCMC estimator resolves it only through its priors.

**Choosing  $R$ .** There is no automatic order-selection criterion (the working-response objective has no likelihood, so AIC/BIC do not apply). Fit a few values — e.g. `lapply(0:4, function(r) ame_als(Y, R = r, ...))` — and inspect deviance (the residual sum of squares): it falls steeply while real multiplicative signal is being captured and then flattens, so the “elbow” of that curve is a reasonable choice. With  $R > 0$  the objective is non-convex; use `multistart` to guard against local optima.

Uncertainty is obtained separately, by the bootstrap; see [ame\\_als\\_bootstrap](#). (The SIR paper’s own primary standard errors are Hessian-based, classical and sandwich/robust. For AME a Hessian-based variance is awkward on two counts: without an explicit gauge fix the rotational invariance of the multiplicative factors leaves the joint Hessian rank-deficient, and even with a gauge fixed the Gaussian working-response approximation used for the non-normal families leaves a Hessian-based variance miscalibrated. The bootstrap side-steps both, so it is preferred here.)

## Value

An object of class “`ame_als`”: a list with the point estimates  $\mu, \beta, a, b, U, V$  (L for symmetric models), the linear predictor  $EZ$ , response-scale fitted values, working-scale residuals, convergence information, and the variance-component vector  $VC$  with five descriptive entries:

`va, vb` empirical variances of the sender and receiver additive effects.

`cab` covariance of the sender and receiver effects (NA for symmetric or bipartite models).

`rho` dyadic residual reciprocity — the correlation between the residuals of  $(i, j)$  and  $(j, i)$  — not the sender/receiver correlation `cor(a, b)`.

`ve` residual variance, on the model’s own scale and degrees-of-freedom-corrected ( $SSE/(n_{obs} - df)$ ) so it matches the MCMC posterior-mean  $s^2$ . For a binary IRLS fit the probit/logit model fixes the latent error variance at 1 by identification, so `ve` is reported as 1; the working-scale GLM dispersion (about 1 under correct specification) is kept separately as `ve_working`.

These are descriptive summaries of the point estimates, not random-effect variance components. See [ame\\_als\\_bootstrap](#) for uncertainty and `vcov.ame_als` for a fast analytic covariance of the regression coefficients.

## Coverage relative to `ame` / `lame`

The ALS estimator is a fast, frequentist point estimator. It covers most static AME workflows, and the top-level `lame(..., method = “als”)` dispatcher covers several dynamic workflows, but

posterior-specific features still require the MCMC estimator:

- **Families.** ALS supports normal, binary, and poisson. For ordinal, cbin, and frn, fall back to [ame](#) / [lame](#).
- **Dynamic effects.** [lame\\_als](#) itself fits a static model pooled across time slices. The top-level dispatcher `lame(..., method = "als")` routes supported dynamic requests to a dynamic point estimator for normal, binary, and poisson panels, including named panels where actors enter or exit: `dynamic_ab`, selected intercept/dyadic/node `dynamic_beta`, and AR(1) or Student-t `dynamic_uv` for directed, symmetric, and bipartite panels. The snap-only `dynamic_uv = TRUE`, `dynamic_uv_kind = "snap"` case routes to [lame\\_snap\\_als](#) for supported normal unipartite and bipartite panels. Node-covariate coefficients use the same orthogonal additive-effect decomposition as [lame\\_als](#); dynamic node coefficients use period-specific node values when selected by `dynamic_beta`, while static node coefficients use per-actor means. bipartite `dynamic_g` is available on the dynamic als path for normal, binary, and poisson panels. changing actor composition requires row and column names on every slice so actors can be aligned; smoothing penalties are broken across actor-entry gaps. rank/censored dynamic families remain on the mcmc path. static `ame_als()` / `lame_als()` fits still use a single latent rank  $R$ ; the dynamic bipartite ALS dispatcher honours separate `R_row` and `R_col` values.
- **Priors.** ALS has no priors. `prior = list(...)` and `g = ...` are MCMC-only; the dispatcher `ame(..., method = "als")` warns and ignores them.
- **Posterior quantities.** No  $\$BETA$  /  $\$VC$  posterior draws on the point fit. Use `bootstrap = N` for a sampling distribution analogue; the draws are bootstrap, not Bayesian.
- **Multi-chain.** Not applicable; `n_chains` is dropped.
- **Convergence diagnostics.** No  $Rhat$  /  $ESS$  / [trace\\_plot](#).

Features that work the same on ALS fits: `coef`, `vcov` (sandwich on regression block), `confint` (auto-routes bootstrap intervals when present, sandwich Wald otherwise), `predict`, `fitted`, `residuals`, `summary`, `print`, `nobs`, [simulate.ame\\_als](#), [gof\\_plot.ame\\_als](#), [ab\\_plot.ame\\_als](#), [uv\\_plot](#), [latent\\_positions](#).

## Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

## References

Minhas, S. and Hoff, P. D. (2025). Decomposing Network Dynamics: Social Influence Regression. *Political Analysis*. The iterative block coordinate descent estimator adapted here originates with that work (implemented in `sir::sir_alsfit()`).

## See Also

[lame\\_als](#) for longitudinal networks, [ame\\_als\\_bootstrap](#) for bootstrap uncertainty, [ame](#) for the full MCMC estimator.

## Examples

```
Y <- matrix(rnorm(400), 20, 20); diag(Y) <- NA
fit <- ame_als(Y, R = 1, family = "normal", verbose = FALSE)
coef(fit)
```

---

ame\_als\_bootstrap

*Bootstrap uncertainty for the fast AME estimator*


---

## Description

Computes bootstrap standard errors and percentile confidence intervals for a fast AME fit produced by [ame\\_als](#) or [lame\\_als](#). Two strategies are available:

**parametric** (default) Simulates fresh outcomes from the fitted model and refits. For normal and IRLS (binary, poisson) fits the simulation is on the calibrated response scale; for a non-normal transform fit – whose estimator is a Gaussian fit to a fixed transformed response – it is on the Gaussian working scale. The fitted residual variance is df-corrected (mean-model degrees of freedom) at fit time, so simulating with it keeps the replicates centred on the point estimate. Available for both cross-sectional and longitudinal fits.

**block** Resamples time slices with replacement. With `block_length = 1` slices are resampled independently; `block_length > 1` draws contiguous blocks (a moving-block bootstrap), which preserves short-run temporal dependence. Longitudinal fits only (requires  $T > 1$ ); with few slices its intervals are necessarily coarse.

Every replicate is refit by [ame\\_als\\_refit](#), warm-started from the original point estimate so that replicates do not drift to different local optima. Replicates that error or return non-finite values are dropped and counted (`n_valid / n_total`). Standard errors are replicate column standard deviations; confidence intervals use the percentile method.

## Usage

```
ame_als_bootstrap(
  object,
  R = 200,
  type = c("parametric", "block"),
  block_length = 1,
  seed = NULL,
  verbose = TRUE
)

boot_ame(
  object,
  R = 200,
  type = c("parametric", "block"),
  block_length = 1,
  seed = NULL,
  verbose = TRUE
)
```

## Arguments

|              |                                                                                                                                                                                                                                                                                                 |
|--------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| object       | an ame_als object from <a href="#">ame_als</a> or <a href="#">lame_als</a> .                                                                                                                                                                                                                    |
| R            | integer number of bootstrap replicates (default 200).                                                                                                                                                                                                                                           |
| type         | "parametric" (default) or "block"; see Description.                                                                                                                                                                                                                                             |
| block_length | block length for the block bootstrap: 1 (default) resamples time slices independently; an integer > 1 draws contiguous blocks of that many slices (a moving-block bootstrap), appropriate when the series has short-run temporal dependence. Capped at T; ignored for the parametric bootstrap. |
| seed         | optional integer random seed.                                                                                                                                                                                                                                                                   |
| verbose      | logical; print progress (default TRUE).                                                                                                                                                                                                                                                         |

## Details

**Choice of inference.** The Social Influence Regression paper of Hoff & Minhas (2025) derives its primary standard errors from the observed Hessian (classical  $-H^{-1}$  and the sandwich/robust estimator  $H^{-1}SH^{-1}$ ). Two features of the AME model make a Hessian-based variance awkward here. First, without an explicit gauge fix the rank-R multiplicative term is identified only up to a full  $R \times R$  rotation/reflection ( $U \rightarrow UR, V \rightarrow VR^{-\top}$ ), leaving the joint Hessian rank-deficient. Second, even with a gauge fixed, the non-normal families are fit on a Gaussian working response, so a Hessian computed from that working objective is not calibrated to the family likelihood. The bootstrap side-steps both issues and is the recommended uncertainty tool here, mirroring `sir::boot_sir()`.

**Alignment-sensitive quantities.** The regression coefficients beta, the additive effects a, b and the variance components are rotation-invariant and are aggregated directly. The multiplicative factors U, V are *not*: each replicate is Procrustes-aligned to the original fit before its standard errors are computed. The object stores both the raw and aligned replicate factors so the effect of alignment can be inspected. The alignment is well-determined only when the multiplicative singular values are well separated; with near-equal singular values the per-column U/V standard errors reflect an unstable rotation, and the subspace — or, for symmetric models, the eigenvalues L — is the summary of record. For a symmetric model the eigenvalues L of the multiplicative term are aggregated and reported as the primary multiplicative-uncertainty summary.

**The parametric bootstrap** is a full parametric bootstrap of the AME model: each replicate draws fresh additive random effects a, b from their fitted dispersion (va, vb, cab) and fresh residuals, holding mu, beta and the multiplicative term fixed. Regenerating the additive effects (rather than holding the fitted a, b fixed) is what gives the intercept and node-covariate standard errors their actor-level sampling-variability component.

**Assumptions.** The block bootstrap treats the time slices as exchangeable replicates of the static-effects model — appropriate for that model, but not for strongly trended or serially dependent series (use the dynamic [lame](#) there); with only a few time slices it is necessarily coarse, its intervals correspondingly imprecise and somewhat anti-conservative, so parametric is the default. A variance component fit with  $R > 0$  can still carry a small residual parametric-bootstrap bias (the low-rank refit re-absorbs simulated noise); `summary()` flags any point estimate that falls outside its interval. A binary IRLS fit can carry a finite-sample (incidental-parameters) bias in the point estimator itself, which the bootstrap reproduces rather than removes. The MCMC [ame](#) / [lame](#) path gives posterior summaries when that is the target.

**Value**

An object of class "boot\_ame" with components including `coefs` (replicate intercept + regression coefficients), `se`, `ci_lo`, `ci_hi`, `point_est`, `param_names`; `vc_*` for the variance components; `a_coefs`, `b_coefs`, `se_a`, `se_b`; `U_aligned`, `V_aligned`, `U_raw`, `V_raw`, `se_U`, `se_V` (when  $R > 0$ ); and `n_valid`, `n_total`, `type`, `family`.

**Author(s)**

Cassy Dorff, Shahryar Minhas, Tosin Salau

**References**

Minhas, S. and Hoff, P. D. (2025). Decomposing Network Dynamics: Social Influence Regression. *Political Analysis*. The block and parametric bootstrap follow the inference scheme of `sir::boot_sir()` developed for the SIR estimator.

**See Also**

[ame\\_als](#) and [lame\\_als](#), both of which accept `bootstrap = N`, `bootstrap_type`, `bootstrap_block_length`, `bootstrap_seed` to do this work in a single call when you are about to fit the model anyway. `ame_als_bootstrap()` is the post-hoc path (bootstrap an *already-fit* object without refitting from scratch). [ame\\_als\\_refit](#) for warm-start refits; [confint.boot\\_ame](#) for the bootstrap CI extractor.

**Examples**

```
Y <- replicate(6, { m <- matrix(rnorm(225), 15, 15); diag(m) <- NA; m },
                  simplify = FALSE)
fit <- lame_als(Y, R = 1, family = "normal", verbose = FALSE)
# post-hoc bootstrap of an existing fit:
bt <- ame_als_bootstrap(fit, R = 50, type = "block",
                      seed = 1, verbose = FALSE)

# equivalent one-shot call:
# fit_b <- lame_als(Y, R = 1, family = "normal", verbose = FALSE,
#                  bootstrap = 50, bootstrap_type = "block",
#                  bootstrap_seed = 1)
print(bt)
```

---

ame\_als\_refit

---

*Refit a fast AME model with a warm start*


---

**Description**

Refits an AME model by iterative block coordinate descent, initialised (“warm-started”) from an existing `ame_als` fit. This is the workhorse of [ame\\_als\\_bootstrap](#): every bootstrap replicate is refit from the original point estimate rather than from a cold random start, which prevents replicates from converging to different local optima or rotations and is essential for meaningful bootstrap standard errors.

**Usage**

```
ame_als_refit(
  object,
  Y_new = NULL,
  X_new = NULL,
  Z_new = NULL,
  max_iter = 30,
  tol = 1e-05,
  verbose = FALSE
)
```

**Arguments**

|          |                                                                                                                                                                                                                                                                                                                                                                                                                  |
|----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| object   | an ame_als object supplying the warm-start values ( $\mu$ , $\beta$ , $a$ , $b$ , $U$ , $V$ ) and the model configuration (family, mode, symmetric, R).                                                                                                                                                                                                                                                          |
| Y_new    | optional canonical outcome array [n_row, n_col, T] to refit on. Defaults to object\$Y.                                                                                                                                                                                                                                                                                                                           |
| X_new    | optional canonical design array [n_row, n_col, p, T]. Defaults to object\$X.                                                                                                                                                                                                                                                                                                                                     |
| Z_new    | optional canonical <i>working-response</i> array [n_row, n_col, T]. When supplied, the model is refit by a Gaussian block coordinate descent directly on Z_new, bypassing the family transform / IRLS reweighting. This is used by the parametric bootstrap of a non-normal transform fit, whose estimator is a Gaussian fit to a fixed transformed response. Y_new is still used for the observed-cell pattern. |
| max_iter | maximum block coordinate descent iterations (default 30; fewer are needed than for a cold start).                                                                                                                                                                                                                                                                                                                |
| tol      | convergence tolerance (default 1e-5).                                                                                                                                                                                                                                                                                                                                                                            |
| verbose  | logical; print progress (default FALSE).                                                                                                                                                                                                                                                                                                                                                                         |

**Details**

The estimation algorithm is the iterative block coordinate descent estimator of the Social Influence Regression model of Hoff & Minhas (`sir::sir_alsfit()`), adapted to the AME model, with each bootstrap replicate warm-started from the original point estimate.

**Value**

An object of class "ame\_als"; see [ame\\_als](#).

**Author(s)**

Cassy Dorff, Shahryar Minhas, Tosin Salau

**References**

Minhas, S. and Hoff, P. D. (2025). Decomposing Network Dynamics: Social Influence Regression. *Political Analysis*. The iterative block coordinate descent estimator refit here originates with that work (implemented in `sir::sir_alsfit()`).

**See Also**

[ame\\_als](#), [ame\\_als\\_bootstrap](#).

**Examples**

```
Y <- matrix(rnorm(400), 20, 20); diag(Y) <- NA
fit <- ame_als(Y, R = 1, family = "normal", verbose = FALSE)
refit <- ame_als_refit(fit, verbose = FALSE)
coef(refit)
```

---

ame\_memory\_settings      *Display memory usage information for AME models*

---

**Description**

Shows estimated memory usage for networks of given size. Memory optimization is automatic, so this is informational only.

**Usage**

```
ame_memory_settings(n_nodes, R = 2)
```

**Arguments**

|         |                                             |
|---------|---------------------------------------------|
| n_nodes | Number of nodes in network                  |
| R       | Rank of multiplicative effects (default: 2) |

**Details**

Memory levers available in the package:

- Run `compact_ame()` on a fitted model to drop empty slots and, for genuinely sparse posterior means, use sparse storage via `use_sparse_matrices = TRUE`
- Increase `odens` in `ame()/lame()` to store fewer posterior draws
- Pass `posterior_opts = list(thin_UV = ..., thin_ab = ...)` to thin the stored latent-factor and additive-effect draws

**Value**

Invisibly returns memory estimates

**Author(s)**

Cassy Dorff, Shahryar Minhas, Tosin Salau

---

|                  |                                                       |
|------------------|-------------------------------------------------------|
| ame_memory_usage | <i>Calculate memory usage of AME model components</i> |
|------------------|-------------------------------------------------------|

---

**Description**

Calculate memory usage of AME model components

**Usage**

```
ame_memory_usage(fit = NULL, detailed = TRUE)
```

**Arguments**

|          |                                                 |
|----------|-------------------------------------------------|
| fit      | Fitted AME model                                |
| detailed | Logical; show detailed breakdown (default TRUE) |

**Value**

Invisibly returns data.frame with memory usage

**Author(s)**

Cassy Dorff, Shahryar Minhas, Tosin Salau

---

|             |                                  |
|-------------|----------------------------------|
| ame_options | <i>AME model fitting options</i> |
|-------------|----------------------------------|

---

**Description**

Configure options for fitting AME models. Memory efficiency is now handled automatically based on network size.

**Usage**

```
ame_options(
  parallel_chains = 1,
  verbose = TRUE,
  odens = 25,
  use_sparse_matrices = FALSE
)
```



**Arguments**

|                     |                                                                                                                                                                   |
|---------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| parallel_chains     | Number of parallel chains to run (default: 1)                                                                                                                     |
| verbose             | Logical; print progress information (default: TRUE)                                                                                                               |
| odens               | Output density - save every odens iterations (default: 25)                                                                                                        |
| use_sparse_matrices | Logical; use sparse matrices for storing results (default: FALSE). Set to TRUE if your network is actually sparse (many zero/NA entries) and memory is a concern. |

**Details**

Memory optimization features:

- Redundant matrices (EZ, UVPD) are never stored - they can be reconstructed if needed
- use\_sparse\_matrices = TRUE: Converts large matrices to sparse format
- Posterior samples are always thinned appropriately

When to use sparse matrices:

- Your network has  $< 10^4$
- Memory usage is a critical concern
- You're willing to trade computational speed for memory efficiency

Note: For dense networks (most edges observed), sparse matrices will be slower and may use more memory than dense storage.

**Value**

List of options to pass to ame()

**Author(s)**

Cassy Dorff, Shahryar Minhas, Tosin Salau

**Examples**

```
# Configure options
opts <- ame_options(verbose = TRUE, odens = 25)
opts
```

ame\_parallel

*Run AME model with multiple parallel chains***Description**

Run AME model with multiple parallel chains

**Usage**

```
ame_parallel(
  Y,
  n_chains = 4,
  cores = n_chains,
  combine_method = c("pool", "list"),
  fitter = c("auto", "ame", "lame"),
  ...
)
```

**Arguments**

|                |                                                                                                                                                                                                                                            |
|----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Y              | Network data matrix                                                                                                                                                                                                                        |
| n_chains       | Number of parallel chains to run (default = 4)                                                                                                                                                                                             |
| cores          | Number of CPU cores to use for parallel processing. Default is n_chains. Use 1 for sequential processing.                                                                                                                                  |
| combine_method | Method for combining chains: "pool" (default) or "list"                                                                                                                                                                                    |
| fitter         | Which fitter to use: "auto" (default; pick <a href="#">lame</a> when Y is a list / 3-D array with >1 time slice, else <a href="#">ame</a> ), "ame" (force cross-sectional), or "lame" (force longitudinal – required for dynamic_* flags). |
| ...            | Additional arguments passed to <code>ame()</code> or <code>lame()</code> .                                                                                                                                                                 |

**Value**

If `combine_method = "pool"`: A single `ame` object with pooled chains  
 If `combine_method = "list"`: A list of `ame` objects, one per chain

**Author(s)**

Cassy Dorff, Shahryar Minhas, Tosin Salau

**See Also**

[lame\\_multi](#) for the unrelated multi-*panel* wrapper that fits K *distinct* networks with shared regression coefficients. `ame_parallel` / `lame_parallel` run K MCMC chains of the *same* model (for R-hat / ESS diagnostics); `lame_multi` runs one chain across K panels with pooled beta.

**Examples**

```
# Run 2 chains sequentially
data(YX_nrm)
fit_parallel <- ame_parallel(YX_nrm$Y, Xdyad = YX_nrm$X,
                             n_chains = 2, cores = 1,
                             nscan = 100, burn = 10, odens = 1,
                             verbose = FALSE)
```

---

|               |                               |
|---------------|-------------------------------|
| array_to_list | <i>Convert array to list.</i> |
|---------------|-------------------------------|

---

**Description**

Convert array to list.

**Usage**

```
array_to_list(arrayObj, actorList, sliceLabel)
```

**Arguments**

|            |                         |
|------------|-------------------------|
| arrayObj   | 3d array object         |
| actorList  | list of actor names     |
| sliceLabel | labels for array slices |

**Value**

array in list format

**Author(s)**

Shahryar Minhas

as\_draws

*Generic dispatcher for posterior::as\_draws on lame fits***Description**

Lightweight S3 generic so calls of the form `as_draws(fit)` dispatch through R's S3 system even when the **posterior** package is not loaded. When **posterior** is loaded, its generic of the same name is resolved first by R's namespace search; this fallback only fires for bare-namespace use.

**Usage**

```
as_draws(x, ...)
```

**Arguments**

`x` a fitted ame or lame object.  
`...` passed to the relevant method.

**Value**

An object dispatched by the relevant method (typically a `posterior::draws_array` for an ame / lame fit).

as\_draws.ame

*Convert an AME / LAME fit to a posterior draws object***Description**

Reshapes the BETA + VC posterior draws stored on an ame or lame fit into a `posterior::draws_array` (or `draws_df`-equivalent) suitable for downstream packages that consume that representation. Multi-chain fits (`ame(..., n_chains = N)`) are reshaped with chain as a separate dimension; single-chain fits are returned as a single-chain `draws_array`.

**Usage**

```
## S3 method for class 'ame'
as_draws(x, include = c("beta", "vc"), ...)

## S3 method for class 'lame'
as_draws(x, include = c("beta", "vc"), ...)

## S3 method for class 'ame_als'
as_draws(x, ...)
```

**Arguments**

|         |                                                                                                                                   |
|---------|-----------------------------------------------------------------------------------------------------------------------------------|
| x       | an ame or lame fit.                                                                                                               |
| include | character; which parameter blocks to include. Default c("beta", "vc"); can also include "rho_uv", "rho_ab" for dynamic LAME fits. |
| ...     | ignored.                                                                                                                          |

**Details**

The reshape uses `fit$chain_indicator` (set when `n_chains > 1`) to keep chain identity separate so within-chain Rhat / ESS estimates and chain-coloured traceplots resolve correctly.

**Value**

A `posterior::draws_array` (when **posterior** is available) or otherwise a plain 3-D array with named dimnames.

---

|           |                                                                |
|-----------|----------------------------------------------------------------|
| as_lame_y | <i>Convert a graph object to a lame-ready adjacency matrix</i> |
|-----------|----------------------------------------------------------------|

---

**Description**

Convenience wrapper that takes an **igraph** or **network** object and returns the kind of matrix that [ame](#) / [lame](#) expect: a numeric adjacency matrix with NA on the diagonal (self-ties not modelled) and (if available) actor names preserved on the row/column dimnames.

**Usage**

```
as_lame_y(x, na_diag = TRUE)
```

**Arguments**

|         |                                                                                                                                               |
|---------|-----------------------------------------------------------------------------------------------------------------------------------------------|
| x       | an igraph, network, matrix, or data.frame representing an adjacency / sociomatrix.                                                            |
| na_diag | logical: replace the diagonal with NA? Defaults to TRUE for square (unipartite) matrices and is ignored for rectangular (bipartite) matrices. |

**Details**

Plain matrices and data.frames are accepted too; data.frames are coerced to a numeric matrix and only the diagonal is rewritten to NA.

**Value**

A numeric matrix suitable to pass as Y to [ame](#) / [lame](#).

## Examples

```
# plain matrices are returned with the diagonal set to NA
m <- matrix(rbinom(25, 1, 0.4), 5, 5,
            dimnames = list(letters[1:5], letters[1:5]))
as_lame_y(m)

if (requireNamespace("igraph", quietly = TRUE)) {
  g <- igraph::sample_gnp(8, 0.3)
  Y <- as_lame_y(g)
  dim(Y)
}
```

---

|                  |                                     |
|------------------|-------------------------------------|
| autoplot.ame_als | <i>autoplot method for ALS fits</i> |
|------------------|-------------------------------------|

---

## Description

Coefficient point-and-interval plot for an [ame\\_als](#) or [lame\\_als](#) fit. The body builds the same frame [autoplot.lame](#) uses, sourcing the point estimate from `coef(fit)` and the interval from `confint(fit)` (sandwich or bootstrap, depending on which is available). `which = "beta"` is the only mode supported; `which = "uv" / "ab"` return an informative error.

## Usage

```
## S3 method for class 'ame_als'
autoplot(object, which = c("beta", "uv", "ab"), conf.level = 0.95, ...)

## S3 method for class 'lame_als'
autoplot(object, which = c("beta", "uv", "ab"), conf.level = 0.95, ...)
```

## Arguments

|                         |                                                                                                        |
|-------------------------|--------------------------------------------------------------------------------------------------------|
| <code>object</code>     | A fitted <code>ame_als</code> / <code>lame_als</code> object.                                          |
| <code>which</code>      | One of "beta" (currently the only supported value).                                                    |
| <code>conf.level</code> | Confidence level for the interval. Default 0.95.                                                       |
| <code>...</code>        | Passed to <a href="#">vcov.ame_als</a> / <a href="#">confint.ame_als</a> (e.g. <code>cluster</code> ). |

## Value

A ggplot object.

autoplot.lame

*Ribbon plot of time-varying coefficients (or coefplot for static fits)***Description**

For a lame fit with `dynamic_beta` on, returns a faceted ggplot of the posterior mean coefficient path per period with a 95 percent credible-interval ribbon. For a static fit (no `dynamic_beta`), falls back to a `tidy()`-driven horizontal `coefplot` with posterior-mean point estimate and credible-interval bars so that `autoplot(fit)` returns a ggplot regardless of fit type.

**Usage**

```
## S3 method for class 'lame'
autoplot(
  object,
  which = c("beta", "ab", "uv"),
  probs = c(0.025, 0.5, 0.975),
  coefs = NULL,
  ...
)

## S3 method for class 'ame'
autoplot(
  object,
  which = c("beta", "ab", "uv"),
  probs = c(0.025, 0.5, 0.975),
  coefs = NULL,
  ...
)
```

**Arguments**

|                     |                                                                                                                                                                                                                            |
|---------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>object</code> | A fitted <code>ame</code> / <code>lame</code> object.                                                                                                                                                                      |
| <code>which</code>  | One of "beta" (default; coefficient plot – ribbon when dynamic, <code>coefplot</code> when static), "ab" (sender / receiver effects when <code>dynamic_ab</code> ), "uv" (latent positions when <code>dynamic_uv</code> ). |
| <code>probs</code>  | Length-3 vector of quantiles to plot. Default <code>c(0.025, 0.5, 0.975)</code> for 95 percent intervals.                                                                                                                  |
| <code>coefs</code>  | Optional character vector of coefficient names to subset.                                                                                                                                                                  |
| <code>...</code>    | Ignored.                                                                                                                                                                                                                   |

**Value**

A `ggplot2` object that can be further customised.

**Examples**

```

data(YX_bin_list)
fit <- lame(YX_bin_list$Y, YX_bin_list$X, family = "binary", R = 0,
           dynamic_beta = "dyad",
           nscan = 60, burn = 15, odens = 5, verbose = FALSE)
if (requireNamespace("ggplot2", quietly = TRUE)) {
  autoplot(fit)
}

```

---

|                   |                                           |
|-------------------|-------------------------------------------|
| bipartite_helpers | <i>Bipartite network helper functions</i> |
|-------------------|-------------------------------------------|

---

**Description**

Bipartite network helper functions

**Usage**

```

init_bipartite_startvals(
  Y,
  family,
  nA,
  nB,
  RA,
  RB,
  Tn,
  Xlist = NULL,
  odmax = NULL
)

```

**Value**

List of starting values for bipartite MCMC

---

|                    |                                                                |
|--------------------|----------------------------------------------------------------|
| boot_ame-no-fitted | <i>fitted/residuals are not defined for a bootstrap object</i> |
|--------------------|----------------------------------------------------------------|

---

**Description**

A `boot_ame` stores replicate-level distributional summaries, not per-cell predictions or residuals. These methods exist only to refuse the call clearly (instead of falling through to `stats::fitted.default` / `stats::residuals.default`, which would silently return `NULL`). Apply [fitted](#) / [residuals](#) to the underlying `ame_als` fit instead.



**Usage**

```
## S3 method for class 'boot_ame'
fitted(object, ...)

## S3 method for class 'boot_ame'
residuals(object, ...)
```

**Arguments**

object            a boot\_ame object.  
 ...              ignored.

**Value**

Never returns; raises an error.

---

|              |                                                     |
|--------------|-----------------------------------------------------|
| check_format | <i>Validate input data format for lame function</i> |
|--------------|-----------------------------------------------------|

---

**Description**

Internal validation function that checks the format and consistency of input data for longitudinal AME models. Ensures that network data and covariates are properly formatted as lists with consistent dimensions across time periods.

**Usage**

```
check_format(Y, Xdyad=NULL, Xrow=NULL, Xcol=NULL)
```

**Arguments**

Y                    a list of T network matrices, where T is the number of time periods. Each element should be an n x m matrix representing the network at time t.

Xdyad                an optional list of T dyadic covariates. Each element can be either an n x m matrix (single covariate) or an n x m x p array (p covariates). Must have the same length as Y if provided.

Xrow                an optional list of T matrices of row/sender covariates. Each element should be an n x pr matrix where pr is the number of row covariates. Must have the same length as Y if provided.

Xcol                an optional list of T matrices of column/receiver covariates. Each element should be an m x pc matrix where pc is the number of column covariates. Must have the same length as Y if provided.

**Details**

Validates input data for longitudinal network analysis:

- Verifying  $Y$  is a non-empty list of matrices
- Checking that all covariates (if provided) are lists of appropriate length
- Validating data types for all elements
- Warning about dimension inconsistencies across time periods

The function uses informative error messages via the cli package to help users identify and correct data formatting issues.

**Value**

Invisible TRUE if all checks pass. Throws an error with an informative message if any validation fails.

**Note**

This is an internal function primarily used by lame() but exported for advanced users who want to validate their data before model fitting.

**Author(s)**

Cassy Dorff, Shahryar Minhas, Tosin Salau

---

coef.als\_dynamic\_beta *Extract beta path from a penalised-ALS object*

---

**Description**

Extract beta path from a penalised-ALS object

**Usage**

```
## S3 method for class 'als_dynamic_beta'
coef(object, ...)
```

**Arguments**

|        |                             |
|--------|-----------------------------|
| object | An als_dynamic_beta object. |
| ...    | Ignored.                    |

**Value**

The  $p \times T$  matrix of estimates.

coef.ame

*Extract model coefficients from AME model***Description**

Returns posterior means of regression coefficients from a fitted AME or LAME model.

**Usage**

```
## S3 method for class 'ame'
coef(object, ...)

## S3 method for class 'lame'
coef(object, ...)
```

**Arguments**

object            Fitted AME model (class "ame" or "lame").  
 ...              Additional arguments (ignored).

**Details**

For a static fit (the default, and any model with `dynamic_beta = FALSE`), coefficients are returned as a named numeric vector computed as `colMeans(fit$BETA)`.

For a dynamic fit (`lame(..., dynamic_beta = ...)` where some coefficient is time-varying), `fit$BETA` is a 3-dimensional array `[n_stored, p, T]` and `coef.lame` returns a `[p, T]` matrix of per-period posterior means. Rownames are the coefficient names; colnames are the period labels (from `names(Y)` or `t1, t2, ...`). Static coefficients in a dynamic fit are constant across the columns.

For binary models, these are on the probit (latent) scale. Use `predict.ame` with `type = "response"` to get predicted probabilities.

**What `coef()` does not return.** The multiplicative latent positions  $U, V$  are not part of the coefficient vector; they live on `fit$U` and `fit$V` (or as 3-D arrays `[n, R, T]` when `dynamic_uv` is on). The additive sender / receiver effects  $a, b$  are on `fit$APM` and `fit$BPM`. For a tidy frame of latent positions use `latent_positions`; for sender / receiver lollipops use `ab_plot`.

**Value**

Named numeric vector (static fit) or  $p \times T$  matrix (dynamic\_beta fit) of posterior mean coefficients.

**See Also**

`vcov.ame` for the posterior covariance matrix, `confint.ame` for credible intervals, `summary.ame` for a full summary table

---

|              |                                                 |
|--------------|-------------------------------------------------|
| coef.ame_als | <i>Extract coefficients from a fast AME fit</i> |
|--------------|-------------------------------------------------|

---

**Description**

Returns the point-estimated regression coefficients (intercept first) of an `ame_als` fit. There is no posterior here; for uncertainty use [ame\\_als\\_bootstrap](#).

**Usage**

```
## S3 method for class 'ame_als'
coef(object, ...)
```

**Arguments**

|                     |                                 |
|---------------------|---------------------------------|
| <code>object</code> | an <code>ame_als</code> object. |
| <code>...</code>    | ignored.                        |

**Value**

A named numeric vector of coefficients.

---

|               |                                                  |
|---------------|--------------------------------------------------|
| coef.boot_ame | <i>Point estimates from a fast AME bootstrap</i> |
|---------------|--------------------------------------------------|

---

**Description**

Returns the intercept and regression coefficient point estimates carried by a `boot_ame` object (the estimates the bootstrap quantifies). For their bootstrap standard errors and intervals see [confint.boot\\_ame](#) and [vcov.boot\\_ame](#).

**Usage**

```
## S3 method for class 'boot_ame'
coef(object, ...)
```

**Arguments**

|                     |                                 |
|---------------------|---------------------------------|
| <code>object</code> | a <code>boot_ame</code> object. |
| <code>...</code>    | ignored.                        |

**Value**

A named numeric vector of coefficient point estimates.

---

|         |                      |
|---------|----------------------|
| coldwar | <i>Cold War data</i> |
|---------|----------------------|

---

**Description**

Positive and negative relations between countries during the cold war

**Format**

A list including the following dyadic and nodal variables:

- cc: a socioarray of ordinal levels of military cooperation (positive) and conflict (negative), every 5 years;
- distance: between-country distance (in thousands of kilometers);
- gdp: country gdp in dollars every 5 years;
- polity: country polity every 5 years.

**Source**

Xun Cao : <https://polisci.la.psu.edu/people/xuc11/>

---

|                    |                                    |
|--------------------|------------------------------------|
| combine_ame_chains | <i>Combine multiple AME chains</i> |
|--------------------|------------------------------------|

---

**Description**

Combine multiple AME chains

**Usage**

```
combine_ame_chains(chain_list, diagnostics = TRUE)
```

**Arguments**

|             |                                                                    |
|-------------|--------------------------------------------------------------------|
| chain_list  | List of ame fit objects from multiple chains                       |
| diagnostics | Logical; whether to compute convergence diagnostics (default TRUE) |

**Value**

A single ame object with combined chains

**Author(s)**

Cassy Dorff, Shahryar Minhas, Tosin Salau

---

|             |                                                        |
|-------------|--------------------------------------------------------|
| compact_ame | <i>Optimize AME model output for memory efficiency</i> |
|-------------|--------------------------------------------------------|

---

### Description

Optimizes AME model storage by converting matrices to sparse format.

### Usage

```
compact_ame(fit, use_sparse_matrices = FALSE)
```

### Arguments

|                     |                                                                |
|---------------------|----------------------------------------------------------------|
| fit                 | Fitted AME model                                               |
| use_sparse_matrices | Logical; whether to use sparse matrix storage (default: FALSE) |

### Details

When `use_sparse_matrices = TRUE`, the posterior-mean matrices YPM and EZ are converted to sparse storage via the **Matrix** package, but only when a matrix's nonzero density is below 0.5 – converting a dense posterior-mean matrix would *grow* memory, so denser matrices are left as ordinary dense matrices. For `lame` fits, where YPM/EZ are per-period lists, the check and conversion are applied per element. The additive-effect summaries APM/BPM are named numeric vectors and are never converted. Names and dimnames are preserved.

### Value

Memory-optimized AME model object

### Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

---

|                       |                                                      |
|-----------------------|------------------------------------------------------|
| compute_gof_bipartite | <i>Compute GOF statistics for bipartite networks</i> |
|-----------------------|------------------------------------------------------|

---

### Description

Compute GOF statistics for bipartite networks

### Usage

```
compute_gof_bipartite(Y_obs, Y_sim, family)
```

### Value

List of observed and simulated GOF statistics

---

compute\_mcmc\_diagnostics

*Compute MCMC convergence diagnostics for multiple chains*


---

### Description

Computes Gelman-Rubin R-hat and effective sample size (ESS) across two or more independently-seeded chains, for both the regression coefficients (BETA) and the variance components (VC). ESS is computed on the pooled draws, so genuinely non-converged chains report a low ESS rather than an inflated one.

### Usage

```
compute_mcmc_diagnostics(chain_list)
```

### Arguments

chain\_list      a list of fitted ame/lame objects, one per chain (each must carry a BETA matrix).

### Value

A list with rhat, ess, param\_names (over BETA and VC), n\_chains and n\_samples.

### Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

---

compute\_XtX\_Xty\_bip\_cpp

*Compute X'X and X'y for bipartite covariate regression*


---

### Description

Replaces the  $O(T \times p^2 \times n^2)$  nested R loop for bipartite XtX and Xty computation with a single C++ call.

### Usage

```
compute_XtX_Xty_bip_cpp(Xlist, resid, p)
```

### Arguments

|       |                                    |
|-------|------------------------------------|
| Xlist | List of T arrays, each nA x nB x p |
| resid | 3D array of residuals nA x nB x T  |
| p     | Number of covariates               |

Value

List with XtX (p x p) and Xty (p vector)

---

|          |                      |
|----------|----------------------|
| comtrade | <i>Comtrade data</i> |
|----------|----------------------|

---

Description

Eleven years of import and export data between 229 countries. The data use the SITC Rev. 1 commodity classification, aggregated at the first level (AG1).

Format

A list consisting of a socioarray Trade and a vector dollars2010 of inflation rates. The socioarray gives yearly trade volume (exports and imports) in dollars for 10 different commodity classes for eleven years between 229 countries. This gives a five-way array. The first index is the reporting country, so Trade[i, j, t, k, 1] is what i reports for exports to j, but in general this is not the same as Trade[j, i, t, k, 2], what j reports as importing from i.

Source

<https://comtrade.un.org/>, <https://www.measuringworth.com/>

---

|             |                                                             |
|-------------|-------------------------------------------------------------|
| confint.ame | <i>Bayesian credible intervals for AME model parameters</i> |
|-------------|-------------------------------------------------------------|

---

Description

Returns posterior **equal-tailed quantile-based** credible intervals (not highest-posterior-density, HPD). Built directly from quantile(object\$BETA, c(alpha/2, 1-alpha/2)) and quantile(object\$VC, ...). These are Bayesian credible intervals, not frequentist confidence intervals.

Usage

```
## S3 method for class 'ame'
confint(object, parm = NULL, level = 0.95, ...)

## S3 method for class 'lame'
confint(object, parm = NULL, level = 0.95, ...)
```



**Arguments**

|        |                                                                                                                                                                                                                                                                           |
|--------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| object | fitted AME / LAME model.                                                                                                                                                                                                                                                  |
| parm   | character vector of parameter names, or numeric indices. When parm is character, both BETA names (e.g. "intercept", "x1_dyad") and variance-component names ("va", "vb", "cab", "rho", "ve") are accepted. NULL (default) returns intervals for all available parameters. |
| level  | credible level (default 0.95).                                                                                                                                                                                                                                            |
| ...    | additional arguments (ignored).                                                                                                                                                                                                                                           |

**Value**

Matrix with one row per parameter and two columns (e.g. "2.5%", "97.5%").

**Note on interval type**

These are equal-tailed quantile intervals, not HPD. For an HPD interval use e.g. `coda::HPDinterval` on the columns of `object$BETA` and `object$VC` directly.

---

|                 |                                                |
|-----------------|------------------------------------------------|
| confint.ame_als | <i>Confidence intervals for a fast AME fit</i> |
|-----------------|------------------------------------------------|

---

**Description**

Wald confidence intervals for the intercept and dyadic-covariate coefficients of an [ame\\_als](#) fit, built from the conditional sandwich covariance ([vcov.ame\\_als](#)).

**Usage**

```
## S3 method for class 'ame_als'
confint(object, parm = NULL, level = 0.95, ...)
```

**Arguments**

|        |                                                                                                                     |
|--------|---------------------------------------------------------------------------------------------------------------------|
| object | an <code>ame_als</code> fit.                                                                                        |
| parm   | character vector of parameter names, or integer indices; if NULL (default) all available coefficients are returned. |
| level  | confidence level (default 0.95).                                                                                    |
| ...    | passed to <a href="#">vcov.ame_als</a> (e.g. <code>cluster</code> ).                                                |

**Details**

These intervals are a fast convenience. They are **conditional** (the additive and multiplicative effects are held fixed) and therefore anti-conservative, and they cover only the regression coefficients the sandwich covariance is defined for – not the node-covariate, additive or multiplicative parameters. For fully-propagated intervals on all parameters, use [ame\\_als\\_bootstrap](#) and [confint.boot\\_ame](#).

Value

A matrix with one row per coefficient and lower/upper bound columns.

See Also

[ame\\_als\\_bootstrap](#) for bootstrap intervals on all parameters.

---

|                  |                                                       |
|------------------|-------------------------------------------------------|
| confint.boot_ame | <i>Confidence intervals from a fast AME bootstrap</i> |
|------------------|-------------------------------------------------------|

---

Description

Bootstrap confidence intervals for the intercept and regression coefficients of a fast AME fit.

Usage

```
## S3 method for class 'boot_ame'
confint(
  object,
  parm = NULL,
  level = 0.95,
  ci_type = c("percentile", "basic"),
  which = c("all", "beta", "vc", "a", "b", "U", "V"),
  ...
)
```

Arguments

|         |                                                                                                                                                                                                                                                                                                                                                                         |
|---------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| object  | a boot_ame object.                                                                                                                                                                                                                                                                                                                                                      |
| parm    | character vector of parameter names, or integer indices. If NULL (default), all coefficients are returned.                                                                                                                                                                                                                                                              |
| level   | confidence level (default 0.95).                                                                                                                                                                                                                                                                                                                                        |
| ci_type | interval type: "percentile" (default) uses the replicate quantiles directly and matches the intervals reported by summary() and tidy() on the same fit; "basic" reflects the replicate quantiles about the point estimate ( $2\hat{\theta} - q$ ), which corrects first-order bias and can be preferable for the IRLS binary/Poisson point estimators on small samples. |
| which   | which uncertainty channel to return: "all" (default, intercept + regression coefficients + variance components + sender effects <ul style="list-style-type: none"><li>• receiver effects + multiplicative U/V), or a single channel: "beta", "vc", "a", "b", "U", "V".</li></ul>                                                                                        |
| ...     | ignored.                                                                                                                                                                                                                                                                                                                                                                |

Value

A matrix with one row per parameter and lower/upper bound columns.

---

|              |                                                               |
|--------------|---------------------------------------------------------------|
| design_array | <i>Assemble the dyadic design socioarray for an AME model</i> |
|--------------|---------------------------------------------------------------|

---

**Description**

Stacks the row, column and dyadic covariates into a single  $n \times n \times p$  array in which slice  $k$  holds the dyad-level values of the  $k$ th predictor. A sender attribute is broadcast down the rows, a receiver attribute is broadcast across the columns, and a dyadic covariate is copied verbatim. An intercept slice of ones is prepended unless it is switched off or would duplicate an already-constant predictor.

**Usage**

```
design_array(Xrow=NULL,Xcol=NULL,Xdyad=NULL,intercept=TRUE,n,warn=TRUE)
```

**Arguments**

|           |                                                                                                                                                                 |
|-----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Xrow      | an $n \times pr$ matrix of row (sender) covariates                                                                                                              |
| Xcol      | an $n \times pc$ matrix of column (receiver) covariates                                                                                                         |
| Xdyad     | an $n \times n \times pd$ array of dyadic covariates                                                                                                            |
| intercept | logical; prepend a constant slice of ones                                                                                                                       |
| n         | number of rows/columns                                                                                                                                          |
| warn      | logical; warn when missing covariate values are zero-filled (default TRUE). Set FALSE when the caller has already propagated the missingness into the response. |

**Value**

an  $n \times n \times (pr+pc+pd+intercept)$  3-way array

**Author(s)**

lame authors

---

|                          |                                                           |
|--------------------------|-----------------------------------------------------------|
| design_array_listwisedel | <i>Computes the design socioarray of covariate values</i> |
|--------------------------|-----------------------------------------------------------|

---

**Description**

Computes the design socioarray of covariate values for an AME fit

**Usage**

```
design_array_listwisedel(Xrow=NULL,Xcol=NULL,Xdyad=NULL,intercept=TRUE,n)
```

**Arguments**

|           |                                          |
|-----------|------------------------------------------|
| Xrow      | an n x pr matrix of row covariates       |
| Xcol      | an n x pc matrix of column covariates    |
| Xdyad     | an n x n x pd array of dyadic covariates |
| intercept | logical                                  |
| n         | number of rows/columns                   |

**Value**

an n x n x (pr+pc+pd+intercept) 3-way array

**Author(s)**

Cassy Dorff, Shahryar Minhas, Tosin Salau

---

|                     |                                                                        |
|---------------------|------------------------------------------------------------------------|
| detect_change_point | <i>Detect potential change points in a dynamic_beta posterior path</i> |
|---------------------|------------------------------------------------------------------------|

---

**Description**

For each dynamic coefficient in a dynamic\_beta fit, compares the posterior distribution of the maximum scaled first-difference  $M = \max_t |\beta_t - \beta_{t-1}| / \sigma_\beta$  to a Monte-Carlo approximation of the same statistic under the AR(1) prior. The returned bf column is the tail-ratio score  $\Pr(M^{post} > m^*) / 0.05$ , where  $m^*$  is the 95\ quantile of  $M^{prior}$ . It is kept under the historical column name for compatibility, but it is not a marginal-likelihood Bayes factor. Use it to surface posterior temporal jumps that the AR(1) prior cannot comfortably accommodate.

**Usage**

```
detect_change_point(
  fit,
  coefs = NULL,
  n_prior_sims = 2000L,
  threshold_bf = 10,
  seed = NULL
)
```

**Arguments**

|              |                                                                                                            |
|--------------|------------------------------------------------------------------------------------------------------------|
| fit          | A fitted lame object with dynamic_beta.                                                                    |
| coefs        | Optional character vector of coefficient names to check. Defaults to every dynamic coefficient on the fit. |
| n_prior_sims | Number of prior simulations for the null distribution. Default 2000.                                       |
| threshold_bf | Cutoff for the "warn" column. Default 10; lower to 5 if the false-positive rate on AR(1) data is too high. |
| seed         | Optional seed for reproducibility.                                                                         |

**Value**

A data frame with one row per dynamic coefficient: `coef`, `bf` (the heuristic tail-ratio score), `m_post_mean` (posterior mean of  $M$ ), `m_prior_q95` (95\  $M$ ), `t_hat` (period of the largest scaled jump), `warn` (logical, `bf > threshold_bf`).

**Examples**

```
data(YX_bin_list)
fit <- lame(YX_bin_list$Y, YX_bin_list$X, family = "binary", R = 0,
           dynamic_beta = "dyad",
           nscan = 60, burn = 15, odens = 5, verbose = FALSE)
detect_change_point(fit)
```

---

dutchcollege

*Dutch college data*


---

**Description**

Longitudinal relational measurements and nodal characteristics of Dutch college students, described in van de Bunt, van Duijn, and Snijders (1999). The time interval between the first four measurements was three weeks, whereas the interval between the last three was six weeks.

**Format**

A list consisting of a socioarray `Y` and a matrix `X` of static nodal attributes. The relational measurements range from -1 to 4, indicating the following:

- -1 a troubled or negative relationship
- 0 don't know
- 1 neutral relationship
- 2 friendly
- 3 friendship
- 4 best friends

**Source**

Originally available at <http://moreno.ss.uci.edu/data.html#vdb> (site no longer accessible).

---

dynamic\_beta\_prior\_summary

*Summarise the implied prior on a time-varying coefficient path*


---

## Description

Draws `ndraws` sample paths of length `n_periods` from the `dynamic_beta` prior (given a `kind`, AR(1) hyperparameters, and an inverse-gamma on the innovation variance) and reports the implied distribution of common summary statistics: maximum absolute first difference, roughness (sum of squared first differences), path range, and correlation with time. Use this before fitting to confirm that your prior is loose / tight enough.

## Usage

```
dynamic_beta_prior_summary(
  n_periods = 10L,
  ndraws = 5000L,
  kind = c("ar1", "rw1", "rw2", "matern32"),
  rho_mean = 0.8,
  rho_sd = 0.15,
  rho_lower = 0,
  rho_upper = 0.999,
  sigma_shape = 2,
  sigma_scale = 1,
  matern32_length_scale = 2,
  threshold = 1,
  seed = NULL
)
```

## Arguments

|                                                     |                                                                                                                                                                                                                            |
|-----------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>n_periods</code>                              | Length of the path (default 10).                                                                                                                                                                                           |
| <code>ndraws</code>                                 | Number of paths to draw (default 5000).                                                                                                                                                                                    |
| <code>kind</code>                                   | One of "ar1", "rw1", "rw2", "matern32". Default "ar1". For "matern32" the path is drawn from a continuous-time Matérn-3/2 GP with length scale <code>matern32_length_scale</code> and marginal variance $\sigma_\beta^2$ . |
| <code>rho_mean</code> , <code>rho_sd</code>         | Prior mean/SD on $\rho$ (AR(1) only). Used to parameterise a Beta prior on the standardised $\rho$ .                                                                                                                       |
| <code>rho_lower</code> , <code>rho_upper</code>     | Truncation bounds (AR(1) only). Default <code>[0, 0.999]</code> .                                                                                                                                                          |
| <code>sigma_shape</code> , <code>sigma_scale</code> | Inverse-Gamma shape / scale on $\sigma_\beta^2$ . Defaults shape = 2, scale = 1.                                                                                                                                           |
| <code>matern32_length_scale</code>                  | Length scale for the Matérn-3/2 covariance ( <code>kind = "matern32"</code> only). Default 2.                                                                                                                              |

threshold      Cutoff for the prob\_max\_diff\_gt\_threshold summary. Default 1.  
 seed            Optional integer seed for reproducibility.

### Details

For kind = "ar1", rho\_mean/rho\_sd are translated to a Beta prior on the standardised  $(\rho - \rho_{lower}) / (\rho_{upper} - \rho_{lower})$ . For kind = "rw1",  $\rho = 1$  is fixed and only  $\sigma_\beta^2$  is sampled. For kind = "rw2", the second-difference variance is sampled and the first two values use a diffuse  $N(0, 10)$  initial prior.

### Value

A list with components:

summary   Data frame with quantile rows for max-first-diff, roughness, path range, trend correlation.  
 prob\_max\_diff\_gt\_threshold   Empirical probability that the maximum absolute first difference exceeds threshold.  
 rho   Length ndraws vector of sampled rho values (NA for kinds with fixed rho).  
 sigma   Length ndraws vector of sampled sigma values.  
 paths   ndraws x n\_periods matrix of sample paths.

### Examples

```
# Default prior: AR(1) with rho_mean = 0.8, rho_sd = 0.15
s <- dynamic_beta_prior_summary(n_periods = 10, ndraws = 2000, seed = 1)
s$summary
# what's the probability that consecutive beta_t differ by more than 1?
s$prob_max_diff_gt_threshold

# Tighter prior on innovation variance
s_tight <- dynamic_beta_prior_summary(sigma_scale = 0.1, seed = 1)
s_tight$summary
```

---

el2sm

---

*Edgelist to sociomatrix*


---

### Description

Construct a sociomatrix from an edgelist. Each row of e1 gives the two endpoints of an edge and, optionally, a weight in a third column (unweighted edges default to 1).

### Usage

```
el2sm(e1, directed=TRUE, nadiag=all(e1[,1]!=e1[,2]))
```

**Arguments**

|          |                                                                                                          |
|----------|----------------------------------------------------------------------------------------------------------|
| e1       | a matrix in which each row contains the indices of an edge and possibly the weight for the edge          |
| directed | if FALSE, then a relation is placed in both entry ij and ji of the sociomatrix, for each edge ij (or ji) |
| nadiag   | put NAs on the diagonal                                                                                  |

**Value**

a sociomatrix

**Author(s)**

lame authors

**Examples**

```
Y<-matrix(rpois(10*10,.5),10,10) ; diag(Y)<-NA
E<-sm2el(Y)
el2sm(E) - Y
```

---

evaluate\_heldout

*Held-out predictive evaluation for an ame / lame fit*

---

**Description**

Computes family-appropriate held-out predictive scores given a fit and a logical mask of cells to score. The function does not split the data for you: it expects you to have either (a) refit on a training subset and now want to score the held-out cells of the same matrix, or (b) have predicted probabilities you want scored. Both AUROC and PR-AUC are reported when applicable, alongside Brier and mean log density.

**Usage**

```
evaluate_heldout(y_obs, y_pred, mask, family = "binary")
```

**Arguments**

|        |                                                                                                                                               |
|--------|-----------------------------------------------------------------------------------------------------------------------------------------------|
| y_obs  | Observed outcomes. For longitudinal fits, a list of per-period matrices; for cross-sectional, a single matrix. Cells not in mask are ignored. |
| y_pred | Predicted probabilities / means on the response scale. Same shape as y_obs.                                                                   |
| mask   | Logical mask of the same shape as y_obs marking cells to score (TRUE = include in evaluation).                                                |
| family | Family string; used to pick the scoring rule. Defaults to "binary".                                                                           |



## Details

**Workflow.** The typical pattern is: mask a random sample of dyads to NA in Y, refit (`lame()` handles NA internally via data augmentation), call `predict(fit, type = "response")`, then pass that prediction alongside the original Y and the held-out mask to this function. See the examples.

**Dependencies.** AUROC / PR-AUC use **precrec** when available; if not installed, only Brier and mean log-density are computed and a one-line note is emitted.

## Value

A one-row data frame with columns appropriate to the family: `n_eval`, plus `auroc` + `auprc` + `brier` + `logloss` (binary / cbin), or `rmse` + `mae` + `mean_logdens` (normal), or `mean_logdens` + `rmse` (poisson).

## Examples

```
set.seed(1)
n <- 25; Y <- matrix(rbinom(n*n, 1, 0.3), n, n); diag(Y) <- NA
rownames(Y) <- colnames(Y) <- paste0("a", sprintf("%02d", 1:n))
# mask 20% of dyads
mask <- matrix(FALSE, n, n)
obs_idx <- which(!is.na(Y))
set.seed(1)
mask[sample(obs_idx, floor(0.2 * length(obs_idx)))] <- TRUE
Y_train <- Y; Y_train[mask] <- NA
fit <- ame(Y_train, R = 0, family = "binary",
          burn = 15, nscan = 60, odens = 5, verbose = FALSE, plot = FALSE)
y_pred <- predict(fit, type = "response")
evaluate_heldout(Y, y_pred, mask, family = "binary")
```

ffbs\_vecG

*Forward-filter / backward-sample for vec(G\_t) under AR(1) state prior*

## Description

One Carter-Kohn sweep over the per-period observations of the form  $\text{vec}(E_t) = H_t g_t + \text{eps}_t$ , with state transition  $g_t = \rho * g_{t-1} + \text{eta}_t$ .

## Usage

```
ffbs_vecG(E_cube, U_cube, V_cube, s2, rho_G, sigma_G2)
```

## Arguments

|        |                                                        |
|--------|--------------------------------------------------------|
| E_cube | nA x nB x T residual cube (Z minus base - a - b - UV') |
| U_cube | nA x RA x T latent row factor cube                     |
| V_cube | nB x RB x T latent column factor cube                  |

|          |                                                                                                                      |
|----------|----------------------------------------------------------------------------------------------------------------------|
| s2       | scalar observation variance                                                                                          |
| rho_G    | AR(1) coefficient in $(-1, 1)$ (use $\rho = 1$ for the RW1 limit; the forward variance is clamped via a tiny floor). |
| sigma_G2 | state innovation variance                                                                                            |

**Value**

list with G\_cube (RA x RB x T) and vecG\_path (p x T draws of the vectorised state).

---

|            |                                             |
|------------|---------------------------------------------|
| fitted.ame | <i>Extract fitted values from AME model</i> |
|------------|---------------------------------------------|

---

**Description**

Returns the posterior mean of the network on the response scale (YPM). For binary models, these are predicted probabilities between 0 and 1. For normal models, these are predicted continuous values. For Poisson models, these are predicted counts.

**Usage**

```
## S3 method for class 'ame'  
fitted(object, ...)
```

**Arguments**

|        |                                        |
|--------|----------------------------------------|
| object | Fitted AME model object (class "ame"). |
| ...    | Additional arguments (not used).       |

**Value**

An n x n matrix (unipartite) or nA x nB matrix (bipartite) of fitted values on the response scale. Diagonal entries are NA for unipartite networks.

**Author(s)**

Cassy Dorff, Shahryar Minhas, Tosin Salau

**See Also**

[predict.ame](#) for predictions with type control, [residuals.ame](#) for residuals

---

|                |                                                  |
|----------------|--------------------------------------------------|
| fitted.ame_als | <i>Extract fitted values from a fast AME fit</i> |
|----------------|--------------------------------------------------|

---

**Description**

Returns response-scale fitted values: a single matrix for a cross-sectional (ame\_als) fit, or a list of matrices for a longitudinal (lame\_als) fit.

**Usage**

```
## S3 method for class 'ame_als'
fitted(object, ...)
```

**Arguments**

|        |                    |
|--------|--------------------|
| object | an ame_als object. |
| ...    | ignored.           |

**Value**

A matrix or list of matrices of fitted values.

---

|             |                                              |
|-------------|----------------------------------------------|
| fitted.lame | <i>Extract fitted values from LAME model</i> |
|-------------|----------------------------------------------|

---

**Description**

Extract fitted values from LAME model

**Usage**

```
## S3 method for class 'lame'
fitted(object, ...)
```

**Arguments**

|        |                      |
|--------|----------------------|
| object | Fitted LAME model    |
| ...    | Additional arguments |

**Value**

List of fitted value matrices (one per time point)

forecast\_pit

*Probability-integral-transform calibration check for h-step forecasts***Description**

For a fit with at least one dynamic component, evaluates how well the h-step posterior-predictive distribution covers the actually observed outcomes at the corresponding period(s). A well-calibrated forecast produces approximately Uniform(0, 1) PIT values.

**Usage**

```
forecast_pit(fit, y_future, h = NULL, n_draws = NULL)
```

**Arguments**

|                       |                                                                                                                                                             |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>fit</code>      | A fitted <code>lame</code> object trained on the first $T - h$ periods (the function does not refit; the user is responsible for the train/forecast split). |
| <code>y_future</code> | A list of length $h$ of held-out observed matrices, one per forecast period. The same shape as <code>fit\$YPM[[t]]</code> elements.                         |
| <code>h</code>        | The forecast horizon (length of <code>y_future</code> ). Inferred from <code>length(y_future)</code> when not supplied.                                     |
| <code>n_draws</code>  | Number of posterior draws to use for the forecast. Default uses all stored draws.                                                                           |

**Details**

Workflow: fit on periods  $1:(T - h)$ , forecast  $h$  steps ahead, score against the held-out  $T - h + 1 : T$  observations. Returns a numeric vector of PIT values (one per observed dyad in the held-out periods), plus a one-row summary with the Kolmogorov-Smirnov statistic against Uniform(0, 1) and a fraction-of-observed-dyads coverage diagnostic.

**Families.** For `family = "normal"`, the PIT is computed analytically from the per-draw forecast variance. For discrete families (`"binary"`, `"poisson"`, `"ordinal"`) the randomised PIT of Czado, Gneiting & Held (2009) is used. For rank families (`"cbin"`, `"frn"`) PIT is not implemented; the function returns `NULL` with an informational note.

**Plotting.** The companion `plot()` method on the returned object renders a histogram with a uniform reference line. Use `ggplot2::ggplot(pit$pit) + geom_histogram()` for custom plots.

**Value**

A list of class `forecast_pit` with components `pit` (numeric vector), `ks_stat` (KS statistic against Uniform), `ks_p` (KS p-value), `cover_95` (fraction of PIT values in  $[0.025, 0.975]$ ).

**References**

Czado, C., Gneiting, T., & Held, L. (2009). Predictive model assessment for count data. *Biometrics*, 65(4), 1254-1261.

**Examples**

```

data(YX_bin_list)
Y_train <- YX_bin_list$Y[1:3]
Y_test <- YX_bin_list$Y[4]
X_train <- YX_bin_list$X[1:3]
fit <- lame(Y_train, Xdyad = X_train,
            family = "binary", R = 0,
            dynamic_beta = "dyad",
            nscan = 60, burn = 15, odens = 5, verbose = FALSE)
pit <- forecast_pit(fit, y_future = Y_test)
pit$ks_p
plot(pit)

```

---

formula.ame

*formula() is not defined for an ame() / lame() fit*


---

**Description**

ame() and lame() use named arguments (Xrow, Xcol, Xdyad, symmetric, etc.) rather than a formula interface. The summary() output renders a pseudo-formula for diagnostic display, but it is not a valid R formula and cannot be passed back to a fitting function.

**Usage**

```

## S3 method for class 'ame'
formula(x, ...)

## S3 method for class 'lame'
formula(x, ...)

```

**Arguments**

|     |                     |
|-----|---------------------|
| x   | an ame or lame fit. |
| ... | ignored.            |

**Value**

Never returns; raises an error.

---

|                |                                               |
|----------------|-----------------------------------------------|
| get_design_rep | <i>Create design array for replicate data</i> |
|----------------|-----------------------------------------------|

---

**Description**

Create design array for replicate data

**Usage**

```
get_design_rep(Y, Xdyad, Xrow, Xcol, actorSet, intercept, n, N, pr, pc, pd)
```

**Arguments**

|           |                                                 |
|-----------|-------------------------------------------------|
| Y         | dependent variable in array format              |
| Xdyad     | dyadic covariates in array format               |
| Xrow      | sender covariates in array format               |
| Xcol      | receiver covariates in array format             |
| actorSet  | vector of actors                                |
| intercept | logical indicating whether to include intercept |
| n         | number of actors                                |
| N         | number of replicates                            |
| pr        | number of receiver covariates                   |
| pc        | number of sender covariates                     |
| pd        | number of dyadic covariates                     |

**Value**

returns list of design array values necessary for ame\_repL

**Author(s)**

Shahryar Minhas

---

get\_EZ\_dynamic\_beta\_cpp

*Compute EZ when beta is time-varying*


---

## Description

Rebuild the ( $n \times n \times T$ ) or ( $n_A \times n_B \times T$ ) EZ cube using a per-period beta vector. Mirrors get\_EZ\_cpp / get\_EZ\_bip\_cpp but accepts a ( $T \times p$ ) beta matrix where each row is the beta for that period.

## Usage

```
get_EZ_dynamic_beta_cpp(
  Xlist,
  beta_full_path,
  a_mat,
  b_mat,
  U_cube,
  V_cube,
  G,
  bipartite,
  symmetric
)
```

## Arguments

|                |                                                                                                                                                                         |
|----------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Xlist          | T-length list of design arrays (each $n \times n \times p$ or $n_A \times n_B \times p$ ).                                                                              |
| beta_full_path | ( $T \times p$ ) matrix of per-period beta. For coefficients that are not in the dynamic block, the rows are identical (the static beta replicated across all periods). |
| a_mat          | ( $n_a \times T$ ) row effects (or repmat-ed static effects).                                                                                                           |
| b_mat          | ( $n_b \times T$ ) column effects.                                                                                                                                      |
| U_cube         | ( $n_u \times R \times T$ ) row latent positions (or replicated-static).                                                                                                |
| V_cube         | ( $n_v \times R \times T$ ) column latent positions.                                                                                                                    |
| G              | ( $R \times R$ or $R_A \times R_B$ ) interaction matrix (bipartite); identity for unipartite.                                                                           |
| bipartite      | TRUE/FALSE.                                                                                                                                                             |
| symmetric      | TRUE/FALSE.                                                                                                                                                             |

## Value

$n_a \times n_b \times T$  cube of EZ values.

---

|                |                                            |
|----------------|--------------------------------------------|
| get_fit_object | <i>Get fitted object from MCMC results</i> |
|----------------|--------------------------------------------|

---

### Description

Get fitted object from MCMC results

### Usage

```
get_fit_object(
  APS,
  BPS,
  UVPS,
  YPS,
  BETA,
  VC,
  GOF,
  Xlist,
  actorByYr,
  colActorByYr = NULL,
  start_vals,
  symmetric,
  tryErrorChecks,
  model.name = NULL,
  U = NULL,
  V = NULL,
  dynamic_uv = FALSE,
  dynamic_ab = FALSE,
  bip = FALSE,
  rho_ab = NULL,
  rho_uv = NULL,
  family = NULL,
  odmax = NULL,
  nA = NULL,
  nB = NULL,
  n_time = NULL,
  Y_obs = NULL,
  G = NULL,
  dynamic_beta = FALSE,
  beta_dynamic_mask = NULL,
  beta_dynamic_groups = NULL,
  rho_beta = NULL,
  sigma_beta = NULL,
  RHO_BETA = NULL,
  SIGMA_BETA = NULL,
  dynamic_rho = FALSE,
  RHO = NULL,
```



```

    rho_path = NULL
)

```

### Arguments

|                   |                                                                                          |
|-------------------|------------------------------------------------------------------------------------------|
| APS               | summed additive sender random effects (or matrix for dynamic)                            |
| BPS               | summed additive receiver random effects (or matrix for dynamic)                          |
| UVPS              | summed multiplicative random effects                                                     |
| YPS               | summed Y posterior predictive values                                                     |
| BETA              | Matrix of draws for regression coefficient estimates                                     |
| VC                | Matrix of draws for variance estimates                                                   |
| GOF               | Matrix of draws for goodness of fit calculations                                         |
| Xlist             | List based version of design array                                                       |
| actorByYr         | List of actors by time point. In bipartite mode this is the per-year list of row actors. |
| colActorByYr      | Bipartite only. List of column actors by time point; defaults to NULL (unipartite).      |
| start_vals        | start_vals for future model run                                                          |
| symmetric         | logical indicating whether model is symmetric                                            |
| tryErrorChecks    | list with counts of MCMC errors                                                          |
| model.name        | Name of the model (optional)                                                             |
| U                 | Latent sender positions (optional, for dynamic UV)                                       |
| V                 | Latent receiver positions (optional, for dynamic UV)                                     |
| dynamic_uv        | logical indicating whether UV effects are dynamic                                        |
| dynamic_ab        | logical indicating whether additive effects are dynamic                                  |
| bip               | logical indicating whether the network is bipartite                                      |
| rho_ab            | temporal correlation parameter for additive effects (optional)                           |
| rho_uv            | temporal correlation parameter for multiplicative effects (optional)                     |
| family            | character string specifying the model family (e.g., "binary", "normal", "poisson")       |
| odmax             | vector of maximum ranks for ordinal or fixed rank nomination families                    |
| nA                | number of actors in first mode (for bipartite networks)                                  |
| nB                | number of actors in second mode (for bipartite networks)                                 |
| n_time            | number of time periods (for longitudinal models)                                         |
| Y_obs             | original observed network (stored for residuals computation)                             |
| G                 | bipartite interaction matrix mapping row to column latent spaces                         |
| dynamic_beta      | logical or scalar; whether the BETA storage is 3-D (dynamic_beta path). Default FALSE.   |
| beta_dynamic_mask | logical vector marking which coefficients are dynamic.                                   |

|                     |                                                                                                                   |
|---------------------|-------------------------------------------------------------------------------------------------------------------|
| beta_dynamic_groups | character vector of per-coefficient block labels ("intercept", "dyad", "row", "col"); "" for static coefficients. |
| rho_beta            | named numeric vector of per-block AR(1) rho values (one per dynamic block).                                       |
| sigma_beta          | named numeric vector of per-block AR(1) innovation standard deviations.                                           |
| RHO_BETA            | matrix of per-iteration rho_beta draws (rows = MCMC draw, cols = dynamic block).                                  |
| SIGMA_BETA          | matrix of per-iteration sigma_beta draws.                                                                         |
| dynamic_rho         | logical indicating whether residual dyadic reciprocity varies by period.                                          |
| RHO                 | matrix of per-iteration, per-period dyadic reciprocity draws.                                                     |
| rho_path            | numeric vector of period-specific dyadic reciprocity values.                                                      |

**Value**

Fitted AME object

**Author(s)**

Shahryar Minhas

---

|                |                                            |
|----------------|--------------------------------------------|
| get_start_vals | <i>Get fitted object from MCMC results</i> |
|----------------|--------------------------------------------|

---

**Description**

Get fitted object from MCMC results

**Usage**

```
get_start_vals(start_vals, Y, family, xP, rvar, cvar, R, odmax = NULL)
```

**Arguments**

|            |                                                               |
|------------|---------------------------------------------------------------|
| start_vals | List object that is null or contains starting values          |
| Y          | dependent variable in array format                            |
| family     | character vector (e.g. 'bin', 'nrm') specifying family type   |
| xP         | number of exogenous covariates                                |
| rvar       | logical indicating whether to include sender random effects   |
| cvar       | logical indicating whether to include receiver random effects |
| R          | Number of dimensions for multiplicative effects               |
| odmax      | vector of maximum ranks for cbin/frn families (optional)      |

**Value**

List of starting values for MCMC

**Author(s)**

Shahryar Minhas

---

|        |                              |
|--------|------------------------------|
| glance | <i>S3 generic for glance</i> |
|--------|------------------------------|

---

**Description**

Light-weight fallback so `glance(fit)` dispatches through S3 even when **broom** or **generics** is not loaded.

**Usage**

```
glance(x, ...)
```

**Arguments**

|     |                         |
|-----|-------------------------|
| x   | An object to glance at. |
| ... | Passed to the method.   |

**Value**

A one-row data frame.

---

|            |                                                    |
|------------|----------------------------------------------------|
| glance.ame | <i>Glance method for fitted ame / lame objects</i> |
|------------|----------------------------------------------------|

---

**Description**

One-row data frame summarising model-level statistics, in the **broom** idiom. Used by `modelsummary::modelsummary()` and similar tabling tools to populate the lower goodness-of-fit panel of a regression table.

**Usage**

```
## S3 method for class 'ame'  
glance(x, ...)  
  
## S3 method for class 'lame'  
glance(x, ...)
```

**Arguments**

|     |                             |
|-----|-----------------------------|
| x   | A fitted ame / lame object. |
| ... | Ignored.                    |

**Value**

A one-row data frame with columns:

- nobs – number of observed dyads (NA cells excluded).
- n\_actors – number of distinct actors; for bipartite fits this is the row-actor count (a 12 x 9 fit reports 12).
- n\_row\_actors, n\_col\_actors – row and column actor counts for bipartite fits (NA for unipartite).
- n\_periods – number of time periods (1 for ame).
- n\_stored – number of stored MCMC draws.
- family – outcome family, such as "normal" or "binary".
- mode – "unipartite" or "bipartite".
- R – latent-space dimension (or max of R\_row, R\_col for bipartite).
- dynamic\_uv, dynamic\_ab, dynamic\_beta – logicals; whether each component is time-varying.
- elpd\_loo – leave-one-out expected log predictive density. Populated only when a loo object has been cached on the fit: fit with save\_log\_lik = TRUE, then attach it via fit\$loo <- loo(fit). NA otherwise (calling loo(fit) alone does not modify the fit object).

**Examples**

```
data(YX_bin_list)
fit <- lame(YX_bin_list$Y, YX_bin_list$X, family = "binary", R = 0,
            nscan = 100, burn = 20, odens = 5, verbose = FALSE)
glance(fit)
```

---

glance.ame\_als

*Glance method for fitted ame\_als / lame\_als objects*


---

**Description**

One-row data frame summarising an ALS fit, compatible with **broom** / **modelsummary**. Reports observation count, actor count, latent dimension, family, mode, ALS convergence flag, and iteration count.

**Usage**

```
## S3 method for class 'ame_als'
glance(x, ...)
```

```
## S3 method for class 'lame_als'
glance(x, ...)
```

**Arguments**

`x`                    A fitted `ame_als` / `lame_als` object.

`...`                Ignored.

**Value**

One-row data frame with columns `nobs`, `n_actors`, `n_periods`, `family`, `mode`, `R`, `converged`, `iterations`, `se_source`.

**Examples**

```
data(YX_bin_list)
Y1 <- 1 * (YX_bin_list$Y[[1]] > 0); diag(Y1) <- NA
fit <- ame_als(Y = Y1, Xdyad = YX_bin_list$X[[1]],
              family = "binary", R = 1, verbose = FALSE)
glance(fit)
```

gof

*Compute GOF statistics from saved posterior samples***Description**

Computes goodness-of-fit statistics after model estimation by generating posterior predictive networks from the saved MCMC samples. This is useful when the model was fitted with `gof = FALSE` to speed up MCMC sampling, or when you want to evaluate custom GOF statistics without re-running the model.

**Usage**

```
gof(fit, Y = NULL, custom_gof = NULL, nsim = 100, verbose = TRUE)
```

**Arguments**

`fit`                    An `ame` model object that was run with posterior sampling enabled

`Y`                      Original data. For `ame` objects, an `n x n` matrix (or `nA x nB` for bipartite). For `lame` objects, a list of matrices (one per time period). If `NULL`, extracted from the `fit` object.

`custom_gof`           Optional custom GOF function(s) - same format as for `ame()`

`nsim`                  Number of posterior predictive simulations to generate (default 100). If `NULL`, uses all available posterior samples.

`verbose`               Logical; print progress information

## Details

This function requires that the model was estimated with posterior sampling of the parameters needed to generate posterior predictive datasets. Specifically, it needs:

- BETA: regression coefficients
- VC: variance components
- For models with random effects: samples of a, b
- For models with latent factors: U\_samples, V\_samples

To enable posterior sampling during model estimation, use: `posterior_opts = posterior_options(save_UV = TRUE, save_ab = TRUE)`

Computing GOF post-hoc has several advantages:

- Faster MCMC sampling (no GOF overhead)
- Can experiment with different GOF statistics without re-running model
- Can control number of posterior predictive simulations independently

## Value

A matrix of GOF statistics with the same format as if `gof=TRUE` was used during model estimation. First row contains observed statistics, subsequent rows contain posterior predictive statistics.

## Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

## See Also

[ame](#), [lame](#), [gof\\_plot](#)

## Examples

```
# Run model without GOF during fitting
data(YX_nrm)
fit <- ame(YX_nrm$Y, Xdyad = YX_nrm$X, R = 2, gof = FALSE,
          nscan = 100, burn = 10, odens = 1, verbose = FALSE)

# Compute GOF post-hoc
gof_result <- gof(fit)
```

gof\_plot

*Visualize goodness-of-fit statistics for AME and LAME models***Description**

Plots observed network statistics against their posterior predictive distributions to assess model fit.

**Usage**

```
gof_plot(
  fit,
  type = c("auto", "static", "longitudinal"),
  statistics = NULL,
  credible.level = 0.95,
  ncol = 2,
  point.size = 2,
  line.size = 1,
  title = NULL,
  ...
)
```

**Arguments**

|                             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|-----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>fit</code>            | An object of class "ame" or "lame" containing GOF statistics                                                                                                                                                                                                                                                                                                                                                                                                                 |
| <code>type</code>           | Character string: "auto" (default), "static", or "longitudinal". If "auto", determined by model class.                                                                                                                                                                                                                                                                                                                                                                       |
| <code>statistics</code>     | Character vector of statistics to plot, or NULL (default) for the standard panels plus any custom GOF columns. Unipartite names: "sd.row", "sd.col", "dyad.dep", "triad.dep", "trans.dep"; bipartite names: "sd.row", "sd.col", "four.cycles". The internal GOF column names reported by <code>names(fit\$GOF)</code> ("sd.rowmean", "sd.colmean", "cycle.dep") are accepted as equivalents; custom GOF columns may also be named. Unknown names are dropped with a warning. |
| <code>credible.level</code> | Numeric between 0 and 1; credible interval level for longitudinal plots (default 0.95)                                                                                                                                                                                                                                                                                                                                                                                       |
| <code>ncol</code>           | Number of columns for faceted plot layout (default 2)                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <code>point.size</code>     | Size of points in longitudinal plots (default 2)                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <code>line.size</code>      | Width of lines in plots (default 1)                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| <code>title</code>          | Optional title for the plot                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <code>...</code>            | Additional arguments forwarded to the ALS-specific <code>gof_plot.ame_als</code> when <code>fit</code> inherits from <code>ame_als</code> ( <code>nsim</code> , <code>seed</code> ).                                                                                                                                                                                                                                                                                         |

## Details

### Overview:

Goodness-of-fit (GOF) assessment is crucial for network models because standard residual diagnostics are often inadequate for capturing network dependencies. This function implements posterior predictive checking by:

1. Computing key network statistics from the observed data
2. Generating multiple networks from the model's posterior predictive distribution
3. Computing the same statistics on simulated networks
4. Visualizing the comparison to identify model inadequacies

### Network Statistics Evaluated:

*For unipartite (square) networks:*

- sd.row (Out-degree heterogeneity)** Standard deviation of row means. High values indicate substantial variation in how active nodes are as senders/initiators. If the model underestimates this, it may be missing important sender effects or covariates.
- sd.col (In-degree heterogeneity)** Standard deviation of column means. High values indicate substantial variation in node popularity as receivers. Underestimation suggests missing receiver effects or popularity-related covariates.
- dyad.dep (Reciprocity/Mutuality)** Correlation between  $Y[i, j]$  and  $Y[j, i]$ . Positive values indicate reciprocity (mutual ties are more likely). The AME model captures this through the dyadic correlation parameter  $\rho$ . Poor fit here points to adjusting the  $dcor$  parameter.
- triad.dep (Transitivity/Clustering)** Measures tendency for triadic closure (friend of a friend is a friend). Calculated as correlation between  $Y[i, j]$  and  $\sum(Y[i, k]*Y[k, j])/sqrt(n-2)$ . AME captures this through multiplicative effects (U,V). Poor fit suggests increasing the latent dimension R.

*For bipartite (rectangular) networks:*

- sd.row (Type A activity variation)** Standard deviation of row means for Type A nodes. Indicates heterogeneity in how actively Type A nodes connect to Type B nodes.
- sd.col (Type B popularity variation)** Standard deviation of column means for Type B nodes. Indicates heterogeneity in how popular Type B nodes are with Type A nodes.
- four.cycles (Bipartite clustering)** Count of 4-cycles (rectangular paths A1-B1-A2-B2-A1). High values indicate that pairs of Type A nodes tend to connect to the same Type B nodes. Captured through bipartite multiplicative effects with appropriate  $R_{row}$ ,  $R_{col}$ .

### Interpretation Guide:

*Histogram plots (static models):*

- Dashed orange vertical line (Okabe-Ito #D55E00): observed statistic value (dual-encoded on colour and linetype)
- Grey histogram: distribution from posterior predictive simulations
- Good fit: orange line falls within the bulk of the histogram
- Poor fit: orange line in the tail or outside the distribution



*Common model inadequacies and solutions:*

**Observed sd.row/sd.col too high** Model underestimates degree heterogeneity. Solutions: Add row/column covariates (Xrow, Xcol), enable random effects (rvar=TRUE, cvar=TRUE), or increase their variance.

**Observed dyad.dep outside distribution** Reciprocity not captured well. Solutions: For positive reciprocity, ensure dcor=TRUE. For negative, consider transformation or different family.

**Observed triad.dep too high** Clustering/transitivity underestimated. Solutions: Increase latent dimension R, add network covariates that capture homophily, or consider including community structure covariates.

**Multiple statistics showing poor fit** Fundamental model misspecification. Solutions: Change family, add missing covariates, or consider different model class.

**Mathematical Details:**

The posterior predictive p-value for statistic  $s$  is:

$$p = P(s(Y_{rep}) \geq s(Y_{obs}) | Y_{obs})$$

where  $Y_{rep}$  is drawn from the posterior predictive distribution. Values near 0 or 1 indicate poor fit. The function visualizes the full distribution rather than just p-values for richer diagnostics.

**Customization:**

The function accepts custom GOF statistics through the model's custom\_gof argument. These are automatically included in the plot. Custom statistics should capture network features important for your specific application.

**Computational Notes:**

GOF computation involves simulating multiple networks, which can be computationally intensive. The model uses the networks simulated during MCMC if gof=TRUE was specified. For post-hoc GOF, use the gof() function which generates new simulations.

Good model fit is indicated when:

- Observed statistics fall within the central 95% of posterior predictive distributions
- No systematic patterns of over/underestimation across statistics
- Custom statistics (if provided) also show adequate fit
- For longitudinal models, observed trajectories track within credible bands

**Value**

A ggplot2 object that can be further customized

**Author(s)**

Cassy Dorff, Shahryar Minhas, Tosin Salau

## Examples

```
# Fit an AME model
data(YX_nrm)
fit_ame <- ame(YX_nrm$Y, Xdyad = YX_nrm$X, gof = TRUE,
              nscan = 100, burn = 10, odens = 1, verbose = FALSE)

# Basic GOF plot
gof_plot(fit_ame)

# Plot only degree-related statistics
gof_plot(fit_ame, statistics = c("sd.row", "sd.col"))
```

---

|                  |                                                 |
|------------------|-------------------------------------------------|
| gof_plot.ame_als | <i>Goodness-of-fit check for an ame_als fit</i> |
|------------------|-------------------------------------------------|

---

## Description

Bootstrap-style analogue of the MCMC [gof\\_plot](#): draws `nsim` simulated networks from the fitted ALS model, computes the standard network statistics (`sd.rowmean`, `sd.colmean`, `dyad.dep`, `cycle.dep`, `trans.dep` for unipartite; `sd.rowmean`, `sd.colmean`, `four.cycles` for bipartite) on each replicate, and overlays the observed value on a histogram of replicate values.

## Usage

```
gof_plot.ame_als(fit, nsim = 100, seed = NULL, ...)
```

## Arguments

|                   |                                              |
|-------------------|----------------------------------------------|
| <code>fit</code>  | an <code>ame_als</code> fit.                 |
| <code>nsim</code> | integer; number of replicates (default 100). |
| <code>seed</code> | optional RNG seed.                           |
| <code>...</code>  | reserved.                                    |

## Details

Uses [simulate.ame\\_als](#) for the replicates and is therefore conditional on the fitted point estimates: the noise is resampled, but  $\mu$ ,  $\beta$ ,  $a$ ,  $b$ ,  $U$ ,  $V$  are held fixed. The MCMC `gof_plot.ame` also averages over posterior movement in those parameters.

## Value

A `ggplot` (or `patchwork`) object.

---

|           |                                   |
|-----------|-----------------------------------|
| gof_stats | <i>Goodness of fit statistics</i> |
|-----------|-----------------------------------|

---

**Description**

Calculates goodness of fit statistics for relational data matrices, evaluating second-order (dyadic) and third-order (triadic) dependence patterns. Can handle both unipartite and bipartite networks.

**Usage**

```
gof_stats(Y, mode = NULL, custom_gof = NULL)
```

**Arguments**

|            |                                                                                                                                                                                                                                                                                                                                                                         |
|------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Y          | a relational data matrix. For unipartite networks, a square $n \times n$ matrix where $Y[i,j]$ represents the relationship from node $i$ to node $j$ . For bipartite networks, an $nA \times nB$ matrix where $Y[i,j]$ represents the relationship from node $i$ in set $A$ to node $j$ in set $B$ . Missing values (NA) are allowed and will be handled appropriately. |
| mode       | character string specifying the network type: "unipartite" or "bipartite". If NULL (default), attempts to infer from matrix dimensions (rectangular = bipartite, square = unipartite). Note: square bipartite networks must specify mode="bipartite".                                                                                                                   |
| custom_gof | optional function or list of functions to compute custom GOF statistics. Each function should take Y as input and return a named numeric value or vector. Custom statistics will be added to the standard statistics.                                                                                                                                                   |

**Details**

The function computes network statistics that capture different aspects of network structure beyond simple density. These statistics are particularly useful for:

- Model checking: comparing observed statistics to those from simulated networks
- Model selection: choosing between models that better capture network dependencies
- Descriptive analysis: summarizing key structural features of the network

For bipartite networks with square dimensions ( $nA = nB$ ), you must explicitly specify mode="bipartite" to ensure correct statistics are calculated.

Missing values in Y are handled by pairwise deletion for correlations and are excluded from matrix products in triadic calculations.

**Value**

A named numeric vector containing goodness-of-fit statistics. For unipartite networks:

**sd.rowmean** Standard deviation of row means. Measures the heterogeneity in out-degree centrality (sender effects).

**sd.colmean** Standard deviation of column means. Measures the heterogeneity in in-degree centrality (receiver effects).

**dyad.dep** Dyadic dependence/reciprocity correlation.

**cycle.dep** Cyclic/transitive triadic dependence.

**trans.dep** Transitive triadic dependence.

For bipartite networks:

**sd.rowmean** Standard deviation of row means (sender heterogeneity).

**sd.colmean** Standard deviation of column means (receiver heterogeneity).

**four.cycles** Count of four-cycles in the bipartite network.

If `custom_gof` is provided, additional statistics will be included with their user-specified names.

**Naming note.** The columns above are the internal names used by `gof_stats()` and stored on `fit$GOF`. `gof_plot` exposes a shorter user-facing alias for some of them; the mapping is:

| internal (this column)  | gof_plot alias |
|-------------------------|----------------|
| sd.rowmean              | sd.row         |
| sd.colmean              | sd.col         |
| dyad.dep                | dyad.dep       |
| cycle.dep               | triad.dep      |
| trans.dep               | trans.dep      |
| four.cycles (bipartite) | four.cycles    |

## Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

## Examples

```
data(YX_nrm)

# Auto-detect unipartite
gof_stats(YX_nrm$Y)

# Bipartite (rectangular) networks are auto-detected; mode can also
# be given explicitly (required when a bipartite network is square)
Y_bip <- matrix(rnorm(120), 10, 12)
gof_stats(Y_bip, mode = "bipartite")

# Custom GOF function
my_stat <- function(Y) { c(my_measure = sum(Y > 0, na.rm = TRUE)) }
gof_stats(YX_nrm$Y, custom_gof = my_stat)
```

---

gof\_stats\_bipartite     *Goodness of fit statistics for bipartite networks*


---

## Description

Calculates goodness of fit statistics specifically designed for bipartite networks, evaluating degree heterogeneity and higher-order dependencies.

## Usage

```
gof_stats_bipartite(Y, warn_square = TRUE)
```

## Arguments

|             |                                                                                                                                                                                                                        |
|-------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Y           | a bipartite relational data matrix (nA x nB rectangular matrix) where $Y[i,j]$ represents the relationship from node i in set A to node j in set B. Missing values (NA) are allowed and will be handled appropriately. |
| warn_square | logical; if TRUE (default) a warning is issued when Y is square (a possible unipartite matrix passed by mistake). Set FALSE for a genuinely square bipartite network.                                                  |

## Details

For bipartite networks, reciprocity and triadic closure are not meaningful concepts since edges only exist between the two node sets. Instead, this function focuses on:

- Degree heterogeneity in both node sets
- Four-cycles as the simplest higher-order dependence pattern

## Value

A named numeric vector containing bipartite-specific goodness-of-fit statistics:

**sd.rowmean** Standard deviation of row means. Measures the heterogeneity in out-degree from set A nodes (sender effects). Higher values indicate more variation in how active A nodes are.

**sd.colmean** Standard deviation of column means. Measures the heterogeneity in in-degree to set B nodes (receiver effects). Higher values indicate more variation in how popular B nodes are.

**four.cycles** Count of four-cycles (also called 4-paths or squares) in the bipartite network. A four-cycle occurs when two nodes from set A (e.g., i and k) both connect to the same two nodes in set B (e.g., j and l), forming a closed path:  $i \rightarrow j \rightarrow k \rightarrow l \rightarrow i$ . This measures the tendency for pairs of A-nodes to share multiple common B-node connections, capturing a form of clustering specific to bipartite networks. High four-cycle counts indicate that connections are not random but show patterns of shared preferences or co-occurrence. For example, in a user-item network, many four-cycles suggest that users who like one item tend to also like other items that co-occur with it.

**Author(s)**

Cassy Dorff, Shahryar Minhas, Tosin Salau

**Examples**

```
# Create a random bipartite network
Y <- matrix(rnorm(10*12), 10, 12)

# Calculate GOF statistics
gof_stats_bipartite(Y)
```

---

gof\_stats\_unipartite    *Goodness of fit statistics for unipartite networks*

---

**Description**

Calculates goodness of fit statistics specifically for unipartite (square) networks, evaluating second-order (dyadic) and third-order (triadic) dependence patterns.

**Usage**

```
gof_stats_unipartite(Y)
```

**Arguments**

**Y**                      a square  $n \times n$  relational data matrix where  $Y[i, j]$  represents the relationship from node  $i$  to node  $j$ . Missing values (NA) are allowed and will be handled appropriately. Diagonal values are typically NA for non-self-loop networks.

**Details**

This function computes network statistics that capture different aspects of network structure beyond simple density. These statistics are particularly useful for evaluating how well a model captures the observed network patterns.

The dyadic dependence statistic captures reciprocity - the tendency for relationships to be mutual. The triadic statistics capture different forms of triadic closure that are common in social networks.

Missing values in **Y** are handled by pairwise deletion for correlations and are excluded from matrix products in triadic calculations.

**Value**

A named numeric vector containing five goodness-of-fit statistics:

**sd.rowmean** Standard deviation of row means. Measures the heterogeneity in out-degree centrality (sender effects).

**sd.colmean** Standard deviation of column means. Measures the heterogeneity in in-degree centrality (receiver effects).

**dyad.dep** Dyadic dependence/reciprocity correlation. Measures the correlation between  $Y[i, j]$  and  $Y[j, i]$ , capturing reciprocity patterns.

**cycle.dep** Cyclic triadic dependence. Measures the tendency for directed cycles ( $i \rightarrow j \rightarrow k \rightarrow i$ ) in the network.

**trans.dep** Transitive triadic dependence. Measures the tendency for transitivity (if  $i \rightarrow j$  and  $j \rightarrow k$ , then  $i \rightarrow k$ ) in the network.

### Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

### Examples

```
# Create a random unipartite network
Y <- matrix(rnorm(100), 10, 10)
diag(Y) <- NA
gof_stats_unipartite(Y)
```

---

gof\_temporal

*Posterior-predictive temporal-trend test*

---

### Description

For a fitted `lame` object, computes a network statistic (density, reciprocity, or transitivity) at each observed period, fits a least-squares linear trend on period index, and compares the observed slope to slopes from posterior-predictive replicates. The two-sided value is  $p_{pp} = 2 * \min(p_{up}, 1 - p_{up})$ , which runs from 0 (observed slope in the extreme tail) to 1 (observed slope dead-centre). A static fit on truly trending data yields  $p_{pp}$  near 0; a dynamic fit that captures the trend yields  $p_{pp}$  near 1.

### Usage

```
gof_temporal(
  fit,
  stat = c("auto", "density", "mean", "reciprocity", "transitivity"),
  n_rep = 500,
  seed = NULL
)
```

**Arguments**

|                    |                                                                                                                                                                                                                                                                                                                             |
|--------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>fit</code>   | A fitted lame object.                                                                                                                                                                                                                                                                                                       |
| <code>stat</code>  | One of "auto" (default; picks "reciprocity" for unipartite directed fits with $T \geq 3$ and family normal / poisson, where "density" is constant and uninformative; otherwise "density"), "density", "mean" (mean of off-diagonal Y; the right "density" analogue for continuous outcomes), "reciprocity", "transitivity". |
| <code>n_rep</code> | Number of posterior-predictive replicates to draw (each replicate is a full $T$ -period network from <code>simulate(fit)</code> ).                                                                                                                                                                                          |
| <code>seed</code>  | Optional RNG seed.                                                                                                                                                                                                                                                                                                          |

**Value**

A list with

- `stat` (chosen statistic name),
- `slope_obs` (observed slope of `stat` on period index),
- `slope_rep` (length-`n_rep` vector of replicate slopes),
- `p_pp` (two-sided posterior-predictive p-value),
- `stat_obs_by_t`, `stat_rep_by_t` (per-period statistics)

**Examples**

```
data(YX_bin_list)
fit <- lame(YX_bin_list$Y, YX_bin_list$X, family = "binary", R = 0,
           dynamic_beta = "dyad",
           nscan = 60, burn = 15, odens = 5, verbose = FALSE)
gof_temporal(fit, stat = "density", n_rep = 50)
```

---

|                                  |                                                                 |
|----------------------------------|-----------------------------------------------------------------|
| <code>init_dynamic_ab_cpp</code> | <i>Initialize dynamic additive effects with AR(1) structure</i> |
|----------------------------------|-----------------------------------------------------------------|

---

**Description**

Initialize dynamic additive effects with AR(1) structure

**Usage**

```
init_dynamic_ab_cpp(n, Tn, rho_ab, sigma_ab, mean_a = 0, mean_b = 0)
```



**Arguments**

|          |                               |
|----------|-------------------------------|
| n        | Number of actors              |
| Tn       | Number of time points         |
| rho_ab   | AR(1) parameter               |
| sigma_ab | Innovation standard deviation |
| mean_a   | Mean for row effects          |
| mean_b   | Mean for column effects       |

**Value**

List with initialized a and b matrices

---

init\_dynamic\_positions

*Initialize dynamic latent positions with AR(1) structure*

---

**Description**

Initialize dynamic latent positions with AR(1) structure

**Usage**

```
init_dynamic_positions(n, R, Tn, rho_uv, sigma_uv)
```

**Arguments**

|          |                               |
|----------|-------------------------------|
| n        | Number of actors              |
| R        | Latent dimension              |
| Tn       | Number of time points         |
| rho_uv   | AR(1) parameter               |
| sigma_uv | Innovation standard deviation |

**Value**

3D array of latent positions (n x R x Tn)

---

 IR90s

---

*International relations in the 90s*


---

### Description

A relational dataset recording a variety of nodal and dyadic variables on countries in the 1990s, including information on conflicts, trade and other variables. Except for the conflict variable, the variables are averages across the decade.

### Format

A list consisting of a socioarray dyadvars of dyadic variables and matrix nodevars of nodal variables. The dyadic variables include

- total number of conflicts;
- exports (in billions of dollars);
- distance (in thousands of kilometers);
- number of shared IGOs (averages across the years);
- polity interaction.

The nodal variables include

- population (in millions);
- gdp (in billions of dollars);
- polity

### Source

Michael Ward.

---

 lame

---

*AME model fitting routine for longitudinal relational data*


---

### Description

An MCMC routine providing a fit to an additive and multiplicative effects (AME) regression model to longitudinal (time-series) relational data of various types. Supports both unipartite (square) and bipartite (rectangular) network structures. For cross-sectional (single time point) networks, use the `ame` function.

**Usage**

```

lame(
  Y,
  Xdyad = NULL,
  Xrow = NULL,
  Xcol = NULL,
  rvar = TRUE,
  cvar = TRUE,
  dcor = !symmetric,
  nvar = TRUE,
  R = 0,
  R_row = NULL,
  R_col = NULL,
  mode = c("unipartite", "bipartite"),
  dynamic_uv = FALSE,
  dynamic_ab = FALSE,
  dynamic_G = FALSE,
  dynamic_beta = FALSE,
  dynamic_rho = FALSE,
  dynamic_beta_kind = c("ar1", "rw1", "rw2", "matern32"),
  dynamic_uv_kind = c("ar1", "snap", "t"),
  family = "normal",
  intercept = !(family == "ordinal"),
  symmetric = FALSE,
  odmax = NULL,
  prior = list(),
  g = NA,
  seed = 6886,
  nscan = 10000,
  burn = 500,
  odens = 25,
  plot = FALSE,
  verbose = FALSE,
  gof = TRUE,
  start_vals = NULL,
  periodic_save = FALSE,
  out_file = NULL,
  save_interval = 0.25,
  model.name = NULL,
  save_log_lik = FALSE,
  posterior_opts = NULL,
  log_lik_path = NULL,
  log_lik_chunk_size = 10000L,
  keep_snap_draws = c("none", "summary", "draws", "chunked"),
  freeze_call = FALSE,
  dynamic_beta_pool = c("none", "rho", "sigma", "both"),
  dynamic_beta_per_actor = NULL,
  per_actor_covariate_idx = 1L,

```

```

per_actor_identifiability = c("center", "exact_center", "drop_population"),
keep_per_actor = c("auto", "draws", "summary", "none"),
time_index = NULL,
period_exposure = NULL,
max_seconds = Inf,
checkpoint_path = NULL,
checkpoint_every = 100L,
log_lik_method = c("observed_exact", "observed_ghk", "augmented"),
ordinal_cutpoints = c("data_induced", "explicit"),
method = c("mcmc", "als"),
als_stability = c("none", "quick", "validation"),
als_max_iter = 1000L,
als_tol = NULL,
bootstrap = 0L,
bootstrap_type = c("parametric", "block"),
bootstrap_block_length = 1L,
bootstrap_seed = NULL,
resume_from = NULL,
print
)

```

## Arguments

|            |                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Y          | a T length list of relational matrices, or a 3D array of dimensions [n_row, n_col, T], where T is the number of time periods. Named lists may have changing actor composition; actors are aligned by row and column names. A longitudinal <b>netify</b> object is also accepted and converted with <code>netify::to_lame(lame = TRUE)</code> . When family or mode is omitted, the value inferred by <b>netify</b> is used. See family below for data types. |
| Xdyad      | a T length list of n x n x pd arrays of covariates                                                                                                                                                                                                                                                                                                                                                                                                           |
| Xrow       | a T length list of n x pr matrices of nodal row covariates                                                                                                                                                                                                                                                                                                                                                                                                   |
| Xcol       | a T length list of n x pc matrices of nodal column covariates                                                                                                                                                                                                                                                                                                                                                                                                |
| rvar       | logical: fit row random effects (asymmetric case)?                                                                                                                                                                                                                                                                                                                                                                                                           |
| cvar       | logical: fit column random effects (asymmetric case)?                                                                                                                                                                                                                                                                                                                                                                                                        |
| dcor       | logical: fit a dyadic correlation (asymmetric case)?                                                                                                                                                                                                                                                                                                                                                                                                         |
| nvar       | logical: fit nodal random effects (symmetric case)?                                                                                                                                                                                                                                                                                                                                                                                                          |
| R          | integer: dimension of the multiplicative effects (can be zero)                                                                                                                                                                                                                                                                                                                                                                                               |
| R_row      | integer: for bipartite networks, dimension of row node multiplicative effects (defaults to R)                                                                                                                                                                                                                                                                                                                                                                |
| R_col      | integer: for bipartite networks, dimension of column node multiplicative effects (defaults to R)                                                                                                                                                                                                                                                                                                                                                             |
| mode       | character: either "unipartite" (default) for square networks or "bipartite" for rectangular networks                                                                                                                                                                                                                                                                                                                                                         |
| dynamic_uv | logical: fit dynamic multiplicative effects (latent factors). The transition model is selected by <code>dynamic_uv_kind</code> . <code>fit\$U</code> / <code>fit\$V</code> store only the posterior-mean                                                                                                                                                                                                                                                     |

trajectory cubes; draw-level trajectory uncertainty requires refitting with `posterior_opts = list(save_UV_draws = TRUE)`, which attaches the per-iteration cubes as `fit$U_draws / fit$V_draws`. Default FALSE.

- `dynamic_ab` logical: fit dynamic additive effects (sender/receiver effects) that evolve over time using AR(1) processes. When TRUE, the row effects (a) and column effects (b) become time-varying, following  $a_{i,t} = \rho_{ab}a_{i,t-1} + \epsilon_{i,t}$ . This captures temporal heterogeneity in actors' baseline propensities to send and receive ties, allowing for smooth changes in activity levels and popularity over time. For example, an actor's tendency to form outgoing ties might gradually increase or decrease across observation periods. The AR(1) specification ensures temporal smoothness while allowing for actor-specific evolution patterns. Implementation uses conjugate updates where possible and C++ for computational efficiency. Default FALSE.
- `dynamic_G` logical (bipartite only). When TRUE the bipartite interaction matrix  $G_t$  in  $U_t G_t V_t'$  varies by period and is returned as `fit$G_cube`, an  $R_{\text{row}} \times R_{\text{col}} \times T$  array. MCMC fits also return posterior summaries for this cube; ALS fits return the penalized point path using the same storage names. The marginal bilinear predictor is identified under the package's canonicalization conventions, while individual entries of  $G_t$  can move under equivalent rotations and scalings of  $U_t$  and  $V_t$ . Default FALSE.
- `dynamic_beta` logical, character, integer, or logical-vector flag selecting which regression coefficients evolve over time via independent AR(1) processes. Default FALSE keeps every coefficient static (the historical behaviour). Accepted forms:
- FALSE / NULL: no coefficient is dynamic.
  - TRUE: every coefficient is dynamic.
  - character vector of block shortcuts ("intercept", "dyad", "row", "col") or specific coefficient names from `colnames(BETA)` – those become dynamic.
  - integer vector: 1-based column indices into `colnames(BETA)`.
  - logical vector of length p: per-coefficient mask.

Each dynamic-coefficient block (one per distinct intercept / dyad / row / col label that has at least one dynamic coefficient) gets its own AR(1) parameters  $\rho_\beta$  (truncated-Normal prior, default mean 0.8, bounded between 0 and 0.999) and  $\sigma_\beta^2$  (inverse-Gamma prior, defaults shape 2 / scale 1). The joint posterior over the time path  $\beta_t$  is drawn by Forward-Filter / Backward-Sample (FFBS) inside the MCMC loop, conditional on the current static-block beta and on (a, b, U, V). When the intercept or a nodal coefficient is dynamic, a sum-to-zero contrast basis is applied to the additive-effect sampler to keep  $a_i + \text{intercept}_t$  identified. Requires at least 2 time periods. `dynamic_beta` composes with multiplicative latent factors ( $R > 0$ ) and additive random effects for every family, across unipartite/bipartite and directed/symmetric panels and in combination with `dynamic_ab` / `dynamic_uv`. Note: with a single dynamic coefficient block and small  $T$ , the AR(1) parameter  $\rho_\beta$  sees only  $T - 1$  transitions and is strongly informed by its default truncated-Normal prior (mean 0.8, sd 0.15) rather than the data; if  $\rho_\beta$  itself is of interest, check prior sensitivity (see [dynamic\\_beta\\_prior\\_summary](#)). With `method = "als"`, selected intercept, dyadic, row-node, and column-node coefficients are supported on normal,

|                                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|--------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                | binary, and Poisson panels, including named panels where actors enter or exit. Dynamic ALS uses period-specific <code>Xrow</code> or <code>Xcol</code> values for selected dynamic node coefficients; static node coefficients still use per-actor means. Dynamic intercepts are unavailable when <code>family = "ordinal"</code> . Default FALSE.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <code>dynamic_rho</code>       | logical. For directed unipartite normal models, allow the residual dyadic reciprocity parameter $\rho_t$ to vary by period instead of using one pooled dyadic correlation across the whole panel. MCMC fits store per-draw paths in <code>fit\$RHO</code> and the posterior mean path in <code>fit\$rho_path</code> . ALS dynamic fits report a residual <code>rho_path</code> that can be passed to MCMC with <a href="#">als_start_vals</a> . Default FALSE.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <code>dynamic_beta_kind</code> | character: state-space prior on the dynamic coefficient block(s). <code>"ar1"</code> (default) gives mean-reverting AR(1) with a truncated-Normal prior on $\rho_\beta$ . <code>"rw1"</code> gives a random walk ( $\rho_\beta$ pinned at 1, no truncation), appropriate when you expect permanent drift with no mean reversion – e.g. trade-gravity coefficients in a permanently changing world economy. The alias <code>"random_walk"</code> is also accepted for <code>"rw1"</code> . When the stationarity warning in <code>summary(fit)</code> fires under the default AR(1), refit with <code>dynamic_beta_kind = "rw1"</code> for cleaner inference. Decision tree: <b>mean-reverting?</b> AR(1). <b>Permanent / unit-root drift?</b> RW1. <b>Smooth with curvature?</b> <code>"rw2"</code> (second-order random walk). <b>Smooth with a known length-scale?</b> <code>"matern32"</code> (Matern 3/2). Note: <code>"rw2"</code> and <code>"matern32"</code> use an R-level joint Gaussian sampler and run substantially slower per iteration than the C++ FFBS used for <code>"ar1"</code> / <code>"rw1"</code> (roughly 2-4x on $n = 100$ , $T = 10$ ). |
| <code>dynamic_uv_kind</code>   | Character string selecting the transition model for dynamic multiplicative latent positions when <code>dynamic_uv = TRUE</code> . <code>"ar1"</code> uses Gaussian AR(1) drift, <code>"snap"</code> uses a mixture of AR(1) drift and discontinuous reset transitions, and <code>"t"</code> uses heavy-tailed Student-t innovations represented by local transition scales. On the MCMC path, <code>"snap"</code> and <code>"t"</code> are currently supported for unipartite directed and symmetric models only. With <code>method = "als"</code> , <code>"snap"</code> is also supported for normal bipartite panels when it is the only dynamic block and $G$ is static. With <code>method = "als"</code> , <code>"t"</code> is supported for bipartite normal, binary, and Poisson panels. ALS Student-t dynamic UV fits attach the final local transition-weight matrices as <code>fit\$lambda_u</code> and <code>fit\$lambda_v</code> .                                                                                                                                                                                                                    |
| <code>family</code>            | character: one of <code>"normal"</code> , <code>"binary"</code> , <code>"ordinal"</code> , <code>"cbin"</code> , <code>"frn"</code> , <code>"poisson"</code> - see the details below                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <code>intercept</code>         | logical: fit model with an intercept?                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <code>symmetric</code>         | logical: is the sociomatrix symmetric?                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <code>odmax</code>             | a scalar integer or vector of length $n$ giving the maximum number of nominations that each node may make - used for <code>"frn"</code> and <code>"cbin"</code> families                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <code>prior</code>             | a list containing hyperparameters for the prior distributions. Available options and their defaults:<br><br><b>Sab0</b> Prior scale matrix for the additive-effects covariance. A 2x2 matrix where <code>Sab0[1,1]</code> is the prior variance for row effects, <code>Sab0[2,2]</code> is the prior variance for column effects, and off-diagonals control correlation between row and column effects. For the <code>"normal"</code> and <code>"poisson"</code> families, and for unipartite <code>"binary"</code> , this defaults to <code>diag(2)</code> scaled to the observed                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |

sender/receiver heterogeneity in  $Y$  rather than to a fixed  $\text{diag}(2)$ ; see [ame](#) for the rationale. Pass  $\text{diag}(2)$  explicitly for a fixed unit-scale prior.

- eta0** Prior degrees of freedom for the additive-effects covariance  $\Sigma_{ab}$  (default:  $\text{round}(4 \setminus * \text{vdfmlt})$  for "binary" fits, where  $\text{vdfmlt}$  is a probit-moment variance multiplier estimated from  $Y$ , and  $\text{round}(4 + 3 \setminus * n/100)$  otherwise, where  $n$  is the number of actors). Higher values impose stronger shrinkage of the row/column effects toward the prior scale. The multiplicative-effects prior is fixed in the longitudinal sampler;  $\text{Suv0}$  and  $\text{kappa0}$  apply to [ame](#) only.
- etaab** Prior degrees of freedom for covariance of additive effects (default:  $4 + 3 \setminus * n/100$ ). Controls shrinkage of row/column random effects.
- ab\_min\_observed** Minimum observed sender/receiver cells used before a static additive effect is left unshrunk (default:  $\max(10, T)$ ). Actors with less support are pulled toward the prior mean for that role.
- rho\_uv\_mean** For  $\text{dynamic\_uv}=\text{TRUE}$ : Prior mean for UV AR(1) parameter (default: 0.9). Values close to 1 indicate high temporal persistence.
- rho\_uv\_sd** For  $\text{dynamic\_uv}=\text{TRUE}$ : Prior SD for UV AR(1) parameter (default: 0.1). Controls uncertainty about temporal dependence.
- sigma\_uv\_shape** For  $\text{dynamic\_uv}=\text{TRUE}$ : Shape parameter for inverse-gamma prior on UV innovation variance (default: 2).
- sigma\_uv\_scale** For  $\text{dynamic\_uv}=\text{TRUE}$ : Scale parameter for inverse-gamma prior on UV innovation variance (default: 1).
- uv\_max\_abs** For  $\text{dynamic\_uv}=\text{TRUE}$ : loose bound on the raw latent coordinate scale after the product-preserving normalization step (default: 50). This guards the unidentified coordinate scale without changing the fitted  $U_t V_t'$  bilinear term.
- rho\_ab\_mean** For  $\text{dynamic\_ab}=\text{TRUE}$ : Prior mean for additive effects AR(1) parameter (default: 0.8). Controls temporal smoothness of sender/receiver effects.
- rho\_ab\_sd** For  $\text{dynamic\_ab}=\text{TRUE}$ : Prior SD for additive effects AR(1) parameter (default: 0.15).
- sigma\_ab\_shape** For  $\text{dynamic\_ab}=\text{TRUE}$ : Shape parameter for inverse-gamma prior on additive effects innovation variance (default: 2).
- sigma\_ab\_scale** For  $\text{dynamic\_ab}=\text{TRUE}$ : Scale parameter for inverse-gamma prior on additive effects innovation variance (default: 1).
- rho\_beta\_mean** For  $\text{dynamic\_beta}$ : Prior mean for the per-block AR(1) parameter on time-varying regression coefficients (default: 0.8). Closer to 1 = smoother evolution.
- rho\_beta\_sd** For  $\text{dynamic\_beta}$ : Prior SD for the per-block AR(1) parameter (default: 0.15).
- rho\_beta\_lower** For  $\text{dynamic\_beta}$ : Lower truncation bound on the AR(1) parameter (default: 0). Pass a negative value to allow negative autoregression.
- rho\_beta\_upper** For  $\text{dynamic\_beta}$ : Upper truncation bound (default: 0.999). Closer to 1 admits near-unit-root behaviour.
- sigma\_beta\_shape** For  $\text{dynamic\_beta}$ : Shape parameter for the inverse-Gamma prior on the per-block innovation variance (default: 2).

|                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                | <b>sigma_beta_scale</b> For dynamic_beta: Scale parameter for the inverse-Gamma prior (default: 1).                                                                                                                                                                                                                                                                                                                                                                                                           |
|                | <b>sigma_beta_init</b> For dynamic_beta: Initial value of the per-block innovation standard deviation (default: 0.25). Affects mixing, not the stationary distribution.                                                                                                                                                                                                                                                                                                                                       |
|                | <b>beta0_mean</b> For dynamic_beta: Mean of the Gaussian prior on the dynamic coefficients at $t = 0$ (default: 0).                                                                                                                                                                                                                                                                                                                                                                                           |
|                | <b>beta0_var</b> For dynamic_beta: Variance of the Gaussian prior on the dynamic coefficients at $t = 0$ (default: 10). Weakly informative.                                                                                                                                                                                                                                                                                                                                                                   |
|                | Common usage: <code>prior = list(Sab0 = diag(c(1, 1)), eta0 = 10)</code> for stronger shrinkage, or <code>prior = list(rho_uv_mean = 0.95)</code> for higher temporal persistence, or <code>prior = list(rho_beta_mean = 0.95, sigma_beta_scale = 0.1)</code> for very smooth time-varying coefficients with tight innovations.                                                                                                                                                                               |
| g              | optional scalar or vector for g-prior on regression coefficients. Default is $p^2$ where $p$ is the number of regression parameters. The g-prior controls the variance of regression coefficients: larger values allow for larger coefficient values. Can be a vector of length $p$ for parameter-specific control.                                                                                                                                                                                           |
| seed           | random seed for the MCMC sampler (default 6886). The sampler is seeded internally with this value, so results are reproducible by default and an external <code>set.seed()</code> call has <i>no</i> effect on the chain – pass a different seed here to vary the draws (e.g. when running multiple chains). The caller's <code>.Random.seed</code> is restored on exit, so fitting never perturbs your RNG stream.                                                                                           |
| nscan          | number of iterations of the Markov chain (beyond burn-in)                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| burn           | burn in for the Markov chain                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| odens          | output density for the Markov chain                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| plot           | logical: plot results while running?                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| verbose        | logical: print progress while running? Default FALSE.                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| gof            | logical: calculate goodness of fit statistics?                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| start_vals     | list of parameter starting values for the MCMC chain. Use <a href="#">als_start_vals</a> to start MCMC from an ALS fit.                                                                                                                                                                                                                                                                                                                                                                                       |
| periodic_save  | logical: indicating whether to periodically save MCMC results                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| out_file       | character vector indicating name and path in which file should be stored if <code>periodic_save</code> is selected. For example, on an Apple OS <code>out_file = "~/Desktop/ameFit.rda"</code> .                                                                                                                                                                                                                                                                                                              |
| save_interval  | quantile interval indicating when to save during the post-burn-in period.                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| model.name     | optional string for model selection output                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| save_log_lik   | one of FALSE (default), TRUE, or "chunked". When TRUE, stores the per-iteration pointwise log-likelihood matrix on <code>fit\$log_lik</code> (an $[n\_stored, n\_obs]$ double matrix). When "chunked", streams the log-lik values to per-column-chunk binary files under <code>log_lik_path</code> so the in-memory cost during MCMC is just one chunk's width; the chunks are recovered later via <code>read_log_lik(fit)</code> . Required for <code>loo::loo(fit)</code> and <code>loo::waic(fit)</code> . |
| posterior_opts | optional list of posterior draw-storage options, usually built with <a href="#">posterior_options</a> . Recognised names (unknown names trigger a warning): <code>save_UV</code> , <code>save_UV_draws</code> ,                                                                                                                                                                                                                                                                                               |



- save\_ab, thin\_UV, thin\_ab. save\_UV = TRUE (the [ame](#) spelling) and save\_UV\_draws = TRUE are aliases on this path. With dynamic\_uv = TRUE they store the per-iteration dynamic latent-position cubes at every stored (odens) iteration on fit\$U\_draws / fit\$V\_draws, each an [actor, dim, period, draw] array. On a static fit with a positive multiplicative rank they store the per-iteration latent-position matrices on fit\$U\_samples / fit\$V\_samples ([actor, dim, draw] arrays, as [ame](#) does). Bipartite fits with positive latent ranks additionally store the interaction-matrix draws on fit\$G\_samples ([R\_row, R\_col, draw]), except under dynamic\_G = TRUE whose per-period cube already gets posterior summaries. save\_ab is not available on the longitudinal path and is ignored with a warning; thin\_UV / thin\_ab are accepted for [posterior\\_options](#) compatibility but not applied here (odens already thins the stored chain). Requesting latent draw storage with a zero multiplicative rank warns and stores nothing. Default NULL.
- log\_lik\_path      directory to write log-lik chunks to when save\_log\_lik = "chunked". Default NULL creates a session-scoped subdirectory under tempdir().
- log\_lik\_chunk\_size      column-width of each on-disk chunk when save\_log\_lik = "chunked". Larger chunks mean fewer files (and one readBin per chunk on read) but more memory during MCMC. Default 10000L.
- keep\_snap\_draws      controls storage of post-burn-in MCMC snap-shift indicators when dynamic\_uv = TRUE and dynamic\_uv\_kind = "snap". "none" keeps only the posterior mean snap probabilities. "summary" stores cell-level count, mean, and variance summaries. "draws" stores retained binary indicator arrays as fit\$snap\_draws and, for directed fits, fit\$snap\_draws\_v, with dimensions draw x actor x time and first period set to NA. "chunked" currently stores the same arrays in memory and labels the storage mode for downstream tooling.
- freeze\_call      logical: if TRUE, store a snapshot of the evaluated Y, Xdyad, Xrow, Xcol on fit\$data\_snapshot so that a later update(fit, ...) refits against the same data even if the caller has mutated those objects in their workspace. Memory cost equals the size of the data; default FALSE.
- dynamic\_beta\_pool      one of "none" (default), "rho", "sigma", or "both". When two or more coefficient blocks are dynamic, non-"none" values update shared hyperparameters across blocks for the selected persistence and / or innovation-scale component. With a single dynamic block the value is recorded but there is no other block to pool against.
- dynamic\_beta\_per\_actor      optional, one of NULL (default), "row", or "col". When non-NULL, fits actor-specific time-varying deviations for one dyadic covariate on the selected margin. The default per\_actor\_identifiability = "center" keeps the population coefficient in coef(fit) and enforces a per-period sum-to-zero constraint on the actor deviations. Draws are stored in fit\$THETA\_ACTOR when retained; summary mode stores fit\$theta\_actor\_mean and fit\$theta\_actor\_sd.
- per\_actor\_covariate\_idx      positive integer; index into the dyadic covariate cube to slope on for the per-actor extension. Default 1L.

|                                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|----------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>per_actor_identifiability</code> | one of "center" (default) or "drop_population". "center" preserves the population coefficient and constrains per-actor deviations to sum to zero per period via pairwise contrast FFBS. "drop_population" is reserved and currently falls back to "center".                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <code>keep_per_actor</code>            | one of "auto" (default; full draws when memory cost < 250 MB else streaming summary), "draws" (full $[n\_iter, n\_actors, T]$ cube), "summary" (streaming posterior mean + sd only), or "none" (only hyperparameter chains).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <code>time_index</code>                | optional numeric vector of length $T$ giving observation times. Default NULL treats periods as equally spaced. Strictly-increasing values are required when supplied. Unequal gaps scale the AR(1) / RW1 transition variance and are also used by the RW2 and Matérn 3/2 dynamic-beta precision builders.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <code>period_exposure</code>           | optional non-negative numeric vector of length $T$ giving period-level exposure offsets. <b>Wired for Poisson:</b> when supplied with any value $\neq 1$ , the Poisson observation likelihood becomes $Y_{ij,t} \sim \text{Poisson}(e_t \cdot \exp(Z_{ij,t}))$ , while the latent $Z$ retains its existing semantic of "unexposed log-rate". For other families, non-trivial <code>period_exposure</code> is an error (rescale $Y$ or use a covariate offset). NULL (default) or all-ones uses the unscaled likelihood path.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <code>max_seconds</code>               | optional positive scalar; if the MCMC wall-clock time exceeds this many seconds, the chain terminates cleanly and <code>fit\$terminated_early</code> is set to TRUE.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| <code>checkpoint_path</code>           | optional file path. When set, the chain periodically writes a snapshot of BETA, VC, the RNG state, and the original call to this file. Use <a href="#">lame_resume</a> or pass the same path back as <code>resume_from = path</code> to continue.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <code>checkpoint_every</code>          | positive integer; iterations between checkpoint writes. Default 100L.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <code>log_lik_method</code>            | one of "observed_exact" (default), "observed_ghk", or "augmented". Selects the argument for selecting which pointwise log-lik is stored on <code>fit\$log_lik</code> . "observed_exact" uses the closed-form marginal log-likelihood for normal, binary, cbin, poisson, and ordinal fits. "observed_ghk" uses a randomized-Halton GHK Monte Carlo marginal for rank-family fits ("frn") and the exact observed likelihood when no GHK step is needed. "augmented" uses the augmented-data Gaussian-on- $Z$ contribution. Note the GHK cost grows exponentially with the per-row dimension $D$ (the number of observed dyads in a sender row): the per-row Monte Carlo budget escalates to $\min(2048, \max(64, 8 * 2^D))$ draws across a bank of 8 randomized Halton sequences, once per stored draw, so "observed_ghk" on a unipartite "frn" fit with more than roughly 12 actors (where $D = n - 1$ ) is expensive; rows with $D > 15$ fall back to a fast pairwise-normal approximation. Power users can fix the per-row budget exactly via <code>prior\$ghk_n_mc</code> (a single positive integer), which both raises the 2048 ceiling and lowers the $8 * 2^D$ accuracy floor; lower budgets increase the downward Jensen bias of the log-lik estimate. |
| <code>ordinal_cutpoints</code>         | character: cutpoint convention for family = "ordinal". "data_induced" (default) uses the data-induced cutpoints; "explicit" samples explicit cutpoints via a Cowles (1996) Metropolis-Hastings update. Ignored for other families.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |

|                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| method                 | character: "mcmc" (default, the Bayesian MCMC fit) or "als" (the fast, MCMC-free point-estimation path). With no dynamic arguments, method = "als" uses the pooled-static <a href="#">lame_als</a> estimator. For normal, binary, and Poisson panels, method = "als" also supports a dynamic penalized point-estimation path for dynamic_ab, selected dynamic_beta, smooth AR(1) dynamic_uv in directed, symmetric, and bipartite panels, bipartite dynamic_G, and Student-t dynamic_uv in directed, symmetric, and bipartite panels. The snap-only dynamic_uv = TRUE, dynamic_uv_kind = "snap" case routes to <a href="#">lame_snap_als</a> for supported normal unipartite and bipartite panels. Node-covariate coefficients use the same orthogonal additive-effect decomposition as <a href="#">lame_als</a> ; dynamic node coefficients use period-specific node values when selected by dynamic_beta, while static node coefficients use per-actor means. Named changing-composition panels are aligned to the union actor set and actor-entry gaps break the dynamic smoothing penalties. Posterior draws, rank/censored families, and bipartite snap-shift fits with node covariates, dynamic coefficients, or dynamic G_t are not handled by the snap ALS shortcut. |
| als_stability          | character (only used when method = "als" and a dynamic ALS path is selected): "none" (default), "quick", or "validation". The non-"none" presets rerun the dynamic ALS fit from jittered starts and attach fit\$stability. Smooth dynamic ALS fits report fitted-surface and coefficient-path differences across starts; snap ALS fits report snap-score, snap-class, top-period, and fitted-surface differences.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| als_max_iter           | positive integer (only used when method = "als"): maximum block-coordinate iterations for the ALS fit. Default 1000.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| als_tol                | optional positive scalar (only used when method = "als"): convergence tolerance for the ALS objective and fitted values. NULL keeps each ALS estimator's built-in default.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| bootstrap              | integer (only used when method = "als"): number of bootstrap replicates. 0 (default) skips the bootstrap; N > 0 runs N replicates and attaches the result so that <a href="#">confint</a> returns bootstrap intervals.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| bootstrap_type         | character (only used when method = "als"): "parametric" (default) or "block".                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| bootstrap_block_length | integer: block length for the block bootstrap.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| bootstrap_seed         | optional integer seed for the bootstrap.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| resume_from            | optional path to a checkpoint file produced by a previous <code>lame(..., checkpoint_path = path)</code> call. When non-NULL, <code>lame()</code> short-circuits all other input parsing and delegates to <a href="#">lame_resume</a> with the user-supplied overrides forwarded. Pass <code>nscan = K</code> to request K additional stored draws on the continuation. Note: <code>checkpoint_path</code> and <code>max_seconds</code> cannot currently be overridden on a resume (they are stripped before re-evaluating the saved call); open both at the original <code>lame()</code> call if you need iterative checkpointing or a time budget on a chain of resumes. Pass <code>verbose = FALSE</code> on resume (the sampling progress bar is gated on <code>burn != 0</code> and the continuation forces <code>burn = 0</code> ). Default NULL.                                                                                                                                                                                                                                                                                                                                                                                                                      |
| print                  | Deprecated. Use <code>verbose</code> instead.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |

## Details

This command provides posterior inference for parameters in AME models of longitudinal relational data, assuming one of eight possible data types/models. The model supports both unipartite networks (square adjacency matrices) and bipartite networks (rectangular adjacency matrices with distinct row and column node sets) across multiple time points.

### Dynamic Effects Implementation:

The `dynamic_uv` and `dynamic_ab` parameters enable time-varying latent representations through autoregressive processes. These extensions are particularly useful for understanding how network structure evolves over time.

*Dynamic Multiplicative Effects* (`dynamic_uv=TRUE`): The latent factors  $U$  and  $V$  evolve according to the transition selected by `dynamic_uv_kind`. The default "ar1" model uses Gaussian AR(1) drift:

$$U_{i,k,t} = \rho_{uv}U_{i,k,t-1} + \epsilon_{i,k,t}$$

where  $\epsilon_{i,k,t} \sim N(0, \sigma_{uv}^2)$ ,  $i$  indexes actors,  $k$  indexes latent dimensions, and  $t$  indexes time. The parameter  $\rho_{uv}$  controls temporal persistence (values near 1 indicate slow evolution). This captures time-varying homophily, latent community structure, and transitivity dynamics. The "snap" transition uses a mixture of AR(1) drift and discontinuous reset transitions, while "t" uses heavy-tailed Student-t innovations represented by local transition scales. On the MCMC path, snap and t transitions are supported for unipartite directed and symmetric models. With `method = "als"`, Student-t dynamic UV is also supported for bipartite normal, binary, and Poisson panels, and snap ALS is supported for normal unipartite and bipartite panels, including named panels where actors enter or exit.

Key references:

- Sewell & Chen (2015): Introduced dynamic latent space models with actor-specific evolution rates
- Durante & Dunson (2014): Nonparametric Bayesian approach allowing flexible evolution of network structure
- Hoff (2011): Hierarchical multilinear models providing theoretical foundation for temporal dependencies

*Dynamic Additive Effects* (`dynamic_ab=TRUE`): The sender (a) and receiver (b) effects evolve as:

$$a_{i,t} = \rho_{ab}a_{i,t-1} + \epsilon_{i,t}$$

$$b_{i,t} = \rho_{ab}b_{i,t-1} + \eta_{i,t}$$

where  $\epsilon_{i,t}, \eta_{i,t} \sim N(0, \sigma_{ab}^2)$ . This models time-varying individual activity levels (outdegree) and popularity (indegree).

Dynamic additive effects are useful when sender activity and receiver popularity change over time rather than staying fixed across the whole panel. A `dynamic_ab` fit returns the posterior-mean paths on `fit$a_dynamic / fit$b_dynamic` (actor x period) and their per-period posterior standard deviations on `fit$a_dynamic_sd / fit$b_dynamic_sd`; `ab_plot(fit, plot_type = "ribbon")` uses the latter to draw a credible band around each actor's path.

*Prior Specification for Dynamic Parameters:*

- $\rho_{uv}, \rho_{ab} \sim \text{TruncNormal}(\text{mean}, \text{sd}, 0, 1)$ : Ensures stationarity of AR(1) process

- $\sigma_{uv}^2, \sigma_{ab}^2 \sim \text{InverseGamma}(\text{shape}, \text{scale})$ : Controls innovation variance
- Default priors ( $\rho_{uv}$  mean=0.9,  $\rho_{ab}$  mean=0.8) favor smooth evolution
- Adjust rho\_\*\_mean closer to 1 for slower evolution, closer to 0 for more rapid changes

*Computational Considerations:*

- Dynamic effects increase computation by roughly 30 to 50 percent per iteration
- Memory usage scales as  $O(nRT)$  for dynamic\_uv,  $O(n*T)$  for dynamic\_ab
- C++ implementation is substantially faster than a pure R loop
- Convergence diagnostics: Monitor rho and sigma parameters carefully
- Effective sample sizes typically lower due to temporal correlation
- Recommend burn  $\geq 1000$  and nscan  $\geq 20000$  for dynamic models

*Model Selection Guidelines:* Use both dynamic\_uv and dynamic\_ab when:

- Networks show clear temporal trends in density or clustering
- Individual node behavior changes systematically over time
- Community structure evolves (merging, splitting, drift)

Use only dynamic\_uv when:

- Latent structure/communities change but individual effects are stable
- Focus is on evolving homophily or clustering patterns
- Network shows structural reconfiguration over time

Use only dynamic\_ab when:

- Individual heterogeneity varies but overall structure is stable
- Actors' activity/popularity changes over observation period
- Focus is on individual-level temporal dynamics

**Bipartite Network Models:**

When mode="bipartite", the model handles rectangular adjacency matrices  $Y$  with dimensions  $n_A \times n_B$ , where  $n_A$  and  $n_B$  represent the number of row and column nodes respectively.

*Static Bipartite Case:* The model uses separate latent factor matrices:

- $U$ :  $n_A \times R_{\text{row}}$  matrix of row node latent positions
- $V$ :  $n_B \times R_{\text{col}}$  matrix of column node latent positions
- $G$ :  $R_{\text{row}} \times R_{\text{col}}$  interaction matrix mapping between latent spaces
- Multiplicative term:  $U G V'$  captures bipartite community structure

*Dynamic Bipartite Case:* When dynamic\_uv=TRUE for bipartite networks:

$$U_{i,k,t} = \rho_{uv} U_{i,k,t-1} + \epsilon_{i,k,t}$$

$$V_{j,k,t} = \rho_{uv} V_{j,k,t-1} + \eta_{j,k,t}$$

where  $i$  indexes row nodes,  $j$  indexes column nodes,  $k$  indexes latent dimensions.

When `dynamic_G = TRUE` the bipartite interaction matrix  $G_t$  varies by period (a separate  $R_{\text{row}} \times R_{\text{col}}$  matrix at every time slice) and is returned as `fit$G_cube`. The MCMC estimator samples  $G_t$  with a Carter-Kohn/FFBS update; `method = "als"` estimates a penalized point path for normal, binary, and Poisson bipartite panels, including named changing-composition panels. The marginal  $U_t G_t V_t'$  linear predictor is the identified object; individual  $G_t$  entries can shift under equivalent rotations and scalings of  $U_t$  and  $V_t$ . `dynamic_G = TRUE` is bipartite only.

*Key Differences from Unipartite Models:*

- No dyadic correlation ( $\rho$ ): Bipartite edges are inherently directed
- Separate dimensions: `R_row` and `R_col` can differ for row/column spaces
- Rectangular structure: Network density patterns differ from square matrices
- Community interpretation: Captures affiliation patterns between node types

### Standard AME Model Types:

The following describes the six standard data types/models available:

"normal": A normal AME model.

"binary": A binary probit AME model.

"ordinal": An ordinal probit AME model. An intercept is not identifiable in this model.

"cbin": An AME model for censored binary data. The value of '`odmax`' specifies the maximum number of links each row may have.

"frn": An AME model for fixed rank nomination networks. A higher value of the rank indicates a stronger relationship. The value of '`odmax`' specifies the maximum number of links each row may have.

"poisson": An overdispersed Poisson AME model for count data:  $Y \sim \text{Poisson}(\exp(z))$  with  $z \sim N(\eta, \sigma^2)$ , a lognormal-mixed Poisson. The conditional mean given the latent  $z$  is  $\exp(z)$ ; the marginal mean is  $\exp(\eta + \sigma^2/2)$ , not  $\exp(\eta)$ .

### Value

**BETA** posterior samples of regression coefficients. A 2-dimensional matrix `[n_stored, p]` when all coefficients are static. When `dynamic_beta` flags any coefficient as time-varying, **BETA** is a 3-dimensional array `[n_stored, p, T]` whose third dimension is the time period. Static coefficients are still present with their values replicated across the third dimension. `coef(fit)` collapses this to a `[p, T]` posterior-mean matrix.

**Migration from amen.** Under `amen::ame()` the **BETA** slot was always 2-D. Scripts that compute `apply(fit$BETA, 2, mean)` on an `amen` fit will silently aggregate across periods when run against a `lame()` fit with `dynamic_beta` active (the second margin is the coefficient index in both shapes; the new third margin is time). Use `length(dim(fit$BETA))` to detect the shape, or call `coef(fit)` which returns a `[p, T]` matrix in either case.

**VC** posterior samples of the variance parameters

**APM** posterior mean of additive row effects `a`

**BPM** posterior mean of additive column effects `b`

|            |                                                                                                                                                                                                                                                                                                                                                                                                                 |
|------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| U          | posterior mean of multiplicative row effects u. For <code>dynamic_uv=TRUE</code> , this is a 3D array (n x R x T)                                                                                                                                                                                                                                                                                               |
| V          | posterior mean of multiplicative column effects v (asymmetric case). For <code>dynamic_uv=TRUE</code> , this is a 3D array (n x R x T)                                                                                                                                                                                                                                                                          |
| UVPM       | posterior mean of UV                                                                                                                                                                                                                                                                                                                                                                                            |
| ULUPM      | posterior mean of ULU (symmetric case)                                                                                                                                                                                                                                                                                                                                                                          |
| L          | posterior mean of L (symmetric case)                                                                                                                                                                                                                                                                                                                                                                            |
| EZ         | estimate of expectation of Z matrix. For <code>mode = "bipartite"</code> , EZ is a list of per-period matrices whose row/column dimnames are currently NULL. Use <code>names(fit\$APM) / names(fit\$BPM)</code> (or <code>dimnames(fit\$YPM[[t]])</code> ) to recover the row/column actor ordering, which is the lexicographic sort of the input actor names (so "r10" sorts before "r2" unless you zero-pad). |
| YPM        | posterior mean of Y (for imputing missing values)                                                                                                                                                                                                                                                                                                                                                               |
| GOF        | observed (first row) and posterior predictive (remaining rows) values of four goodness-of-fit statistics. See <a href="#">gof</a> for post-hoc computation and <a href="#">gof_plot</a> for visualization.                                                                                                                                                                                                      |
| start_vals | Final parameter values from MCMC, can be used as the input for a future model run.                                                                                                                                                                                                                                                                                                                              |
| model.name | Name of the model (if provided)                                                                                                                                                                                                                                                                                                                                                                                 |

### Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

### See Also

[ame](#) for cross-sectional models, [lame\\_als](#) for the fast MCMC-free point estimator, [lame\\_snap\\_als](#) for the approximate dynamic snap-shift point estimator, [als\\_dynamic\\_beta](#) for a regression-only penalised smoother on the time-varying coefficient path, [lame\\_resume](#) for resuming saved checkpoints, [gof](#) for post-hoc goodness-of-fit computation, [gof\\_plot](#) for visualizing GOF results, [latent\\_positions](#) for extracting latent positions as a tidy data frame, [procrustes\\_align](#) for Procrustes alignment of latent positions, [summary.lame](#) for model summaries, [coef.lame](#) for coefficient extraction. Long-format edgelist and covariates can be prepared with `netify::netify()` and passed directly to `lame()`, or converted explicitly with `netify::to_lame(lame = TRUE)`.

### Examples

```
data(YX_bin_list)
fit<-lame(YX_bin_list$Y,YX_bin_list$X,burn=5,nscan=5,odens=1,family="binary")
# you should run the Markov chain much longer than this

## Time-varying regression coefficients (dynamic_beta).
## Make every dyadic coefficient evolve as an AR(1):
fit_dyn <- lame(YX_bin_list$Y, YX_bin_list$X,
               family = "binary", R = 0,
               nscan = 60, burn = 15, odens = 5,
```

```

dynamic_beta = "dyad")
dim(fit_dyn$BETA)      # [n_stored, p, T] -- 3-D when dynamic
coef(fit_dyn)          # [p, T] posterior-mean coefficient paths
confint(fit_dyn)       # per-period 95% credible intervals
summary(fit_dyn)       # prints a "Dynamic coefficients per period" block

```

---

lame\_als

*Fast (MCMC-free) AME estimation for a longitudinal network*


---

## Description

Fits an additive and multiplicative effects (AME) model to a longitudinal (replicated) network by **iterative block coordinate descent**, producing a fast point estimate with no MCMC and no credible intervals. This is the longitudinal counterpart of [ame\\_als](#); the estimated effects ( $\mu$ ,  $\beta$ ,  $a$ ,  $b$ ,  $U$ ,  $V$ ) are *static* (pooled across time), as in a non-dynamic [lame](#) fit.

The estimation algorithm adapts the iterative block coordinate descent estimator of the Social Influence Regression model of Hoff & Minhas (`sir::sir_alsfit()`) to the AME model; it is a port and adaptation, not original **lame** methodology. See [ame\\_als](#) for the algorithm details.

## Usage

```

lame_als(
  Y,
  Xdyad = NULL,
  Xrow = NULL,
  Xcol = NULL,
  R = 0,
  family = "normal",
  mode = c("unipartite", "bipartite"),
  symmetric = FALSE,
  max_iter = 200,
  tol = 1e-06,
  lowrank_method = c("mm", "als", "hybrid"),
  non_normal_method = c("irls", "transform"),
  link = c("probit", "logit"),
  linear_solver = c("eigen", "qr", "auto"),
  multistart = c("none", "cheap", "full"),
  bootstrap = 0L,
  bootstrap_type = c("parametric", "block"),
  bootstrap_block_length = 1L,
  bootstrap_seed = NULL,
  verbose = TRUE,
  seed = 6886
)

```



**Arguments**

|                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|-------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Y                 | a list of $t$ relational matrices, or a 3d array $[n\_row, n\_col, t]$ . A named list may have changing actor composition; every slice must carry row and column names so actors can be aligned to the union panel. Unnamed lists and arrays are treated positionally and must have one fixed layout. A longitudinal <b>netify</b> object is also accepted and converted with <code>netify::to_lame(lame = TRUE)</code> .                                                                                                                                                                                                                                      |
| Xdyad             | a list of $T$ dyadic covariate matrices/arrays, or NULL.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Xrow              | a list of $T$ row/sender covariate matrices, or NULL.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Xcol              | a list of $T$ column/receiver covariate matrices, or NULL.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| R                 | integer dimension of the multiplicative effects (default 0). <b>The covariate coefficients are conditional on this choice.</b> The multiplicative term $u_i'v_j$ is a flexible high-variance regressor that can correlate with the dyadic covariates, so the estimated beta can shift – and occasionally change sign – as $R$ increases. Comparing against an $R = 0$ fit is a useful check on whether the covariate story is being driven by the latent rank.                                                                                                                                                                                                 |
| family            | one of "normal", "binary", or "poisson". The rank and censoring families are MCMC-only.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| mode              | "unipartite" (square) or "bipartite" (rectangular).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| symmetric         | logical; fit a symmetric (undirected) model. Unipartite only.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| max_iter          | maximum number of block coordinate descent iterations (default 200).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| tol               | convergence tolerance on the relative change in residual sum of squares (default $1e-6$ ).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| lowrank_method    | inner solver for the multiplicative (low-rank) block: "mm" (default) weighted majorise-minimise; "als" alternating least squares; "hybrid" runs both and keeps the lower-objective result. "als"/"hybrid" converge faster than "mm" on strongly unbalanced longitudinal panels and are available for directed and bipartite models (symmetric fits always use "mm"). All three minimise the same objective, so the point estimate is unchanged for balanced data.                                                                                                                                                                                              |
| non_normal_method | for the non-normal ALS families, "irls" (default for binary/poisson) runs iteratively reweighted least squares, giving a fast approximate GLM AME fit with coefficients on the requested link scale (Poisson log, binary logit/probit). "transform" fits one fixed Gaussian working response ( $\log(y+1)$ for Poisson, rank-normal scores for binary); its coefficients are on an uncalibrated working scale and are mainly useful for direction/ranking checks. A directed $R > 0$ IRLS fit uses the hybrid low-rank solver internally because the IRLS weights are unbalanced. Uncertainty for either path comes from the bootstrap or sandwich covariance. |
| link              | link for non_normal_method = "irls" with a binary family: "probit" (default; matches <a href="#">ame/lame</a> ) or "logit". poisson always uses the log link; ignored otherwise.                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| linear_solver     | solver for the regression block: "eigen" (default) eigendecomposes the normal equations; "qr" uses a QR factorisation of the observed design, which is more stable for ill-conditioned covariates; "auto" picks "qr" when the design                                                                                                                                                                                                                                                                                                                                                                                                                           |

|                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                        | is ill-conditioned but full rank. All give the same answer for well-conditioned designs.                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| multistart             | for $R > 0$ (a non-convex objective), "none" (default) fits from a single deterministic start; "cheap" (4 starts) and "full" (8 starts) also try random low-rank starts and keep the lowest-SSE fit, warning when the starts reach materially different optima. Reproducible given seed; the global RNG stream is left unchanged.                                                                                                                                                                                                 |
| bootstrap              | integer: if $> 0$ , additionally run bootstrap replicates of the parametric or block bootstrap (via <a href="#">ame_als_bootstrap</a> ) after the point fit and attach the result as <code>fit\$bootstrap</code> . The downstream accessors ( <code>confint.ame_als</code> , <code>summary</code> , <code>print</code> ) then surface bootstrap intervals instead of the anti-conservative sandwich Wald intervals. Default 0 (no bootstrap) – bootstrap is expensive, so it is not imposed on a user who just wants a quick fit. |
| bootstrap_type         | character: "parametric" (default) or "block" – the bootstrap scheme to use when <code>bootstrap &gt; 0</code> .                                                                                                                                                                                                                                                                                                                                                                                                                   |
| bootstrap_block_length | integer: block length for the block bootstrap; only used when <code>bootstrap_type = "block"</code> .                                                                                                                                                                                                                                                                                                                                                                                                                             |
| bootstrap_seed         | optional integer seed for the bootstrap (the point fit uses seed).                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| verbose                | logical; print progress (default TRUE).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| seed                   | random seed (default 6886). The block coordinate descent is deterministic, so the point estimate is reproducible regardless; the argument is retained for API consistency with <a href="#">ame</a> .                                                                                                                                                                                                                                                                                                                              |

## Value

An object of class "ame\_als"; see [ame\\_als](#).

## Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

## References

Minhas, S. and Hoff, P. D. (2025). Decomposing Network Dynamics: Social Influence Regression. *Political Analysis*. The iterative block coordinate descent estimator adapted here originates with that work (implemented in `sir::sir_alsfit()`).

## See Also

[ame\\_als](#), [ame\\_als\\_bootstrap](#), [lame](#) for the full MCMC estimator, [lame\\_snap\\_als](#) for the approximate dynamic snap-shift point estimator, [als\\_dynamic\\_beta](#) for a regression-only smoother that estimates *only* a time-varying  $\beta_t$  (no  $a, b, U, V$ ; not a special case of this function).

**Examples**

```
Y <- replicate(4, { m <- matrix(rnorm(400), 20, 20); diag(m) <- NA; m },
  simplify = FALSE)
fit <- lame_als(Y, R = 1, family = "normal", verbose = FALSE)
coef(fit)
```

---

|            |                                                    |
|------------|----------------------------------------------------|
| lame_multi | <i>Multi-panel lame() with shared coefficients</i> |
|------------|----------------------------------------------------|

---

**Description**

Fits  $K$  independent `lame()` models (one per panel) and pools the per-panel beta posteriors into a precision-weighted shared posterior. Returns a list with the per-panel fits, the pooled beta posterior, and the panel-specific deviations.

**Usage**

```
lame_multi(Y_list, Xdyad_list, ...)
```

**Arguments**

|                         |                                                                                                                                                                                                                                                                                                                                                                           |
|-------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>Y_list</code>     | A list of length $K$ , each element a list (or 3-D array) of $T$ per-panel network observations.                                                                                                                                                                                                                                                                          |
| <code>Xdyad_list</code> | A list of length $K$ , each element a list of $T$ dyadic covariate arrays.                                                                                                                                                                                                                                                                                                |
| <code>...</code>        | Arguments forwarded to <code>lame()</code> (e.g. <code>family</code> , <code>R</code> , <code>mode</code> , <code>nscan</code> , <code>burn</code> , <code>odens</code> , <code>dynamic_beta</code> , <code>dynamic_beta_kind</code> ). The pooled beta posterior is always returned, per-period when <code>dynamic_beta</code> is active (detected from the panel fits). |

**Details**

This is an R-level wrapper: it fits each panel with its own MCMC and pools the results afterwards. The pooling is exact when the panels are conditionally independent given beta, which is the standard assumption.

**Value**

A list with

- `fits`: list of  $K$  per-panel `lame` fits.
- `beta_shared`: pooled posterior mean of beta (per-period when dynamic).
- `beta_deviations`: list of  $K$  panel-specific deviations from `beta_shared`.
- `K`: number of panels.

Class "`lame_multi`".

See Also

[lame\\_parallel](#) for the unrelated multi-chain wrapper that runs K MCMC chains of the *same* model (used for R-hat / ESS diagnostics and pooled effective sample size). `lame_multi` is for K *distinct* panels with shared regression coefficients; `lame_parallel` is for K chains of one model.

Examples

```
data(YX_bin_list)
fit_multi <- lame_multi(
  Y_list = list(YX_bin_list$Y, YX_bin_list$Y),
  Xdyad_list = list(YX_bin_list$X, YX_bin_list$X),
  family = "binary", R = 0,
  nscan = 100, burn = 25, odens = 5, verbose = FALSE)
dim(fit_multi$beta_shared)
```

---

|               |                                                           |
|---------------|-----------------------------------------------------------|
| lame_parallel | Run LAME (longitudinal AME) with multiple parallel chains |
|---------------|-----------------------------------------------------------|

---

Description

Thin wrapper around [ame\\_parallel](#) that forces `fitter = "lame"`. Use this for longitudinal data; in particular, multi-chain `dynamic_beta` / `dynamic_uv` / `dynamic_ab` fits are reached through here. The combined fit's `$BETA` is a 3-D array when `dynamic_beta` is on, and `posterior::rhat(as_draws(fit))` gives R-hat across chains for every per-period coefficient.

Usage

```
lame_parallel(
  Y,
  n_chains = 4,
  cores = n_chains,
  combine_method = c("pool", "list"),
  ...
)
```

Arguments

- `Y` Longitudinal network: list of T relational matrices, or a 3-D array [n, n, T].
- `n_chains` Number of parallel chains (default 4).
- `cores` CPU cores to use (default `n_chains`; 1 = sequential).
- `combine_method` "pool" (default) or "list".
- `...` Additional arguments forwarded to [lame](#), including `dynamic_beta`, `dynamic_uv`, `dynamic_ab`, `family`, `nscan`, `burn`, `odens`, etc.

**Value**

Same as `ame_parallel`: a combined lame fit (when `combine_method = "pool"`) or a list of fits.

**Examples**

```
data(YX_bin_list)
fit_pll <- lame_parallel(YX_bin_list$Y, Xdyad = YX_bin_list$X,
                        family = "binary", n_chains = 2, cores = 1,
                        nscan = 50, burn = 10, odens = 5,
                        dynamic_beta = "dyad", verbose = FALSE)
dim(fit_pll$BETA)      # [iter * n_chains, p, T]
fit_pll$chain_indicator # length iter * n_chains
if (requireNamespace("posterior", quietly = TRUE)) {
  posterior::summarise_draws(posterior::as_draws(fit_pll))
}
```

lame\_resume

*Resume a lame() MCMC run from a checkpoint***Description**

For a fit started with `lame(..., checkpoint_path = "X.rds")` that terminated early (either via `max_seconds` or an external interruption), continues the chain from the most recent checkpoint. The implementation is pragmatic: it loads the saved RNG state and re-invokes `lame()` with the original call arguments. The result is a fresh fit that picks up where the previous one left off in the random-number stream; the underlying MCMC counter restarts at 1.

**Usage**

```
lame_resume(path, nscan_more = NULL, ..., .envir = NULL)
```

**Arguments**

|                         |                                                                                                                                                               |
|-------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>path</code>       | Checkpoint file path (the one passed as <code>checkpoint_path</code> to <code>lame()</code> ).                                                                |
| <code>nscan_more</code> | Optional integer, the new <code>nscan</code> for the continuation. If <code>NULL</code> , the original <code>nscan</code> is used.                            |
| <code>...</code>        | Additional arguments forwarded to <code>lame()</code> (override the saved values).                                                                            |
| <code>.envir</code>     | Environment in which to evaluate the saved call's data arguments. Defaults to the caller's frame; used internally when <code>lame()</code> forwards a resume. |

## Details

**Equivalent consolidated entry point.** `lame(resume_from = path, ...)` short-circuits to this function with the user-supplied overrides forwarded; pass `nscan = K` on the resume call to request `K` additional stored draws. Both call shapes are supported. The `lame_resume(path, ...)` form is safer for nested calls: the consolidated form re-evaluates the saved `lame()` call in `parent.frame()`, which is the `lame()` frame whose required formal arguments (`Y`, `Xdyad`, etc.) were not supplied on the resume call. Prefer `lame_resume(path, ...)` when calling from inside other functions or from non-global scopes.

Use `nscan_more = K` to override the `nscan` value to `K` for the continuation. Other arguments can be overridden by passing them to `...`

## Value

A fitted lame object.

## Examples

```
ck <- tempfile(fileext = ".rds")
data(YX_bin_list)
# short run with very-aggressive max_seconds to force early termination
fit1 <- lame(YX_bin_list$Y, YX_bin_list$X, family = "binary", R = 0,
            nscan = 5000, burn = 50, odens = 5,
            checkpoint_path = ck, checkpoint_every = 50L,
            max_seconds = 0.5, verbose = FALSE)
if (isTRUE(fit1$terminated_early)) {
  fit2 <- lame_resume(ck, nscan_more = 200)
  dim(fit2$BETA)
}
```

---

lame\_snap\_als

*Fast approximate dynamic snap-shift AME estimator*


---

## Description

Fits a fast point-estimator approximation to the dynamic snap-shift latent-factor model for longitudinal normal-valued networks. It targets the same drift-versus-reset transition estimand as [lame](#) with `dynamic_uv = TRUE` and `dynamic_uv_kind = "snap"`, but returns ALS snap scores rather than MCMC draws.

## Usage

```
lame_snap_als(
  Y,
  Xdyad = NULL,
  Xrow = NULL,
  Xcol = NULL,
```

```

R = 2L,
R_row = NULL,
R_col = NULL,
family = "normal",
mode = c("unipartite", "bipartite"),
symmetric = FALSE,
max_iter = 200L,
tol = 1e-06,
snap_kappa = 2,
snap_pi_prior = c(a = 1, b = 9),
snap_update = c("soft", "hard", "annealed"),
snap_damping = 0.7,
estimate_rho_uv = TRUE,
estimate_sigma_uv = TRUE,
rho_uv = NULL,
sigma_uv = NULL,
hyper_update = c("robust", "em"),
drift_quantile = 0.05,
drift_min_transitions = 50,
rho_prior_mean = 0.98,
rho_prior_weight = 25,
align = c("sequential", "global", "none"),
threshold = 0.5,
min_sigma = 1e-04,
sigma_floor_fraction = 0.75,
ridge = 1e-08,
snap_stability_tol = 0.05,
snap_convergence = c("quantile", "max", "classification"),
snap_delta_quantile = 0.95,
snap_class_change_tol = 0.005,
unstable_top_n = 10L,
stability = c("none", "quick", "validation"),
verbose = TRUE,
seed = 6886
)

```

## Arguments

|            |                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Y          | a list of relational matrices, or a 3D array. Unipartite fits use $[n, n, T]$ panels. Bipartite fits use rectangular $[n\_row, n\_col, T]$ panels. For named lists, slices may have changing actor composition; the estimator pads to the union actor set and treats absent actor-periods as unobserved and snap-ineligible. A longitudinal <b>netify</b> object is also accepted and converted with <code>netify::to_lame(lame = TRUE)</code> . |
| Xdyad      | optional list of dyadic covariate matrices/arrays, or NULL.                                                                                                                                                                                                                                                                                                                                                                                      |
| Xrow, Xcol | not supported by this fast snap-shift estimator; pass NULL. Use <code>lame</code> with method = "mcmc" for node-covariate dynamic snap models.                                                                                                                                                                                                                                                                                                   |

|                                    |                                                                                                                                                                                                                                                                                 |
|------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| R                                  | positive integer latent rank. For bipartite fits, used as the default for R_row and R_col.                                                                                                                                                                                      |
| R_row, R_col                       | positive integer latent ranks for bipartite row and column positions. Defaults to R.                                                                                                                                                                                            |
| family                             | currently only "normal".                                                                                                                                                                                                                                                        |
| mode                               | "unipartite" or "bipartite".                                                                                                                                                                                                                                                    |
| symmetric                          | logical; if TRUE, fit a symmetric latent-factor approximation and report one snap-probability matrix.                                                                                                                                                                           |
| max_iter                           | maximum block-coordinate iterations.                                                                                                                                                                                                                                            |
| tol                                | convergence tolerance on the relative change of the tracked $-2 \times$ variational free energy (see Details).                                                                                                                                                                  |
| snap_kappa                         | diffuse snap-prior standard deviation.                                                                                                                                                                                                                                          |
| snap_pi_prior                      | length-two vector $c(a, b)$ for the beta prior used to regularize the snap rate.                                                                                                                                                                                                |
| snap_update                        | one of "soft", "hard", or "annealed".                                                                                                                                                                                                                                           |
| snap_damping                       | scalar in $(0, 1]$ ; damping applied to soft snap-score updates. Values below 1 mix the new score with the previous score to reduce oscillation on large panels. Ignored for snap_update = "hard".                                                                              |
| estimate_rho_uv, estimate_sigma_uv | logical flags for updating the AR drift persistence and innovation scale.                                                                                                                                                                                                       |
| rho_uv, sigma_uv                   | optional fixed/initial AR drift parameters.                                                                                                                                                                                                                                     |
| hyper_update                       | one of "robust" or "em". The default "robust" estimates drift hyperparameters from the lower tail of transition innovations, which prevents broad ruptures from being absorbed into an overly diffuse drift process. "em" uses the untrimmed soft-classification moment update. |
| drift_quantile                     | lower-tail transition quantile used by hyper_update = "robust" for estimating smooth-drift hyperparameters.                                                                                                                                                                     |
| drift_min_transitions              | minimum effective number of transitions retained by the lower-tail update. This keeps the default from overfitting the smooth-drift scale on small panels.                                                                                                                      |
| rho_prior_mean, rho_prior_weight   | weak regularization for the persistence estimate. The defaults encode the snap-shift model's intended persistent, low-innovation drift baseline.                                                                                                                                |
| align                              | initialization alignment mode; "global" aligns each period to the pooled static ALS fit, "sequential" aligns each period to the previous initialized period, and "none" leaves per-period factors unaligned.                                                                    |
| threshold                          | hard-classification threshold for snap_class.                                                                                                                                                                                                                                   |
| min_sigma                          | lower bound for the drift scale.                                                                                                                                                                                                                                                |
| sigma_floor_fraction               | for robust hyperparameter updates, the iterative drift scale cannot fall below this fraction of the initial sigma_uv. This prevents broad snap assignments from collapsing the smooth-drift variance to min_sigma.                                                              |
| ridge                              | small ridge added to latent-position normal equations.                                                                                                                                                                                                                          |



|                       |                                                                                                                                                                                                                                                                                                          |
|-----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| snap_stability_tol    | tolerance for declaring soft snap scores stable. This is separate from tol, which tracks the penalized objective.                                                                                                                                                                                        |
| snap_convergence      | convergence criterion for snap scores. "quantile" uses snap_delta_quantile of the absolute score changes plus the class-change share; "max" uses the worst actor-period score change; "classification" uses only class-change stability. The worst-case max is always stored and warned about when high. |
| snap_delta_quantile   | quantile of actor-period score changes used by snap_convergence = "quantile".                                                                                                                                                                                                                            |
| snap_class_change_tol | maximum share of eligible actor-periods whose snap_class may change between iterations while still declaring snap convergence.                                                                                                                                                                           |
| unstable_top_n        | number of largest actor-period snap-score changes to store in convergence diagnostics.                                                                                                                                                                                                                   |
| stability             | optional start-sensitivity preset. "none" runs one fit. "quick" and "validation" rerun the same estimator from additional seeds and attach fit\$stability with snap-score, classification, top-period, and fitted-surface comparisons.                                                                   |
| verbose               | logical; print progress.                                                                                                                                                                                                                                                                                 |
| seed                  | integer seed for initialization perturbations.                                                                                                                                                                                                                                                           |

## Details

The raw snap-ALS intercept  $\mu$  is *not* separately identified from the uncentered multiplicative term: a constant level can be absorbed into  $\text{mean}(U_t V_t')$  (bipartite:  $\text{mean}(U_t G V_t')$ ), so `fit$mu` on its own is arbitrary. After convergence the estimator therefore computes a post-hoc identified level: `fit$mu_t` stores the per-period level  $\mu + \text{mean}(U_t V_t')$  (named by period) and `fit$mu_identified` is the mean of `fit$mu_t`. Interpret the network level through `mu_identified`; the latent trajectories and the covariate coefficients are unaffected by this shift and remain reliable outputs of this estimator.

On longer panels, the default `align = "sequential"` keeps the period-to-period movement in view. `align = "global"` can help on very short panels, but on longer panels it can pull each period back toward the pooled static fit and make early jumps look too strong. If you have a fixed drift scale, pass `rho_uv` and `sigma_uv` with `estimate_rho_uv = FALSE` and `estimate_sigma_uv = FALSE`.

The convergence output separates the usual score summary from the worst moving actor-period. By default, convergence uses the 95th percentile of score changes and the share of class changes. `final_max_snap_delta` and `unstable_transitions` still show the largest local moves. Read `snap_prob` as an ALS snap score. It is useful for rankings and heuristic classifications; it is not a Bayesian posterior probability.

For unipartite fits, the tracked objective (`fit$objective_trace`, `fit$convergence$final_objective`) is the exact  $-2 \times$  variational free energy of the snap/drift mixture model, including the Gaussian log-normalizers, the responsibility entropy, and the beta prior on the snap rate. The exact block updates descend it monotonically; small increases can come from damped snap scores or the robust hyperparameter updates. Because it carries log-variance normalizers it can be negative and is not a deviance; `fit$param_trace$sse` tracks raw data fit directly.

In bipartite mode, the fitted multiplicative term is  $U_t G V_t'$  with one static interaction matrix  $G$ . The returned `snap_prob` matrix contains row-actor snap scores and `snap_prob_v` contains column-actor snap scores. Bipartite snap ALS does not estimate node covariates, dynamic coefficients, or a dynamic  $G_t$ ; those combinations need a separate model.

### Value

An object of class "lame\_snap\_als" with dynamic latent positions, snap scores, fitted values, residuals, and convergence diagnostics.

### Examples

```
set.seed(1)
Y_bip <- lapply(seq_len(3), function(t) {
  m <- matrix(rnorm(6 * 5), 6, 5)
  rownames(m) <- paste0("r", seq_len(6))
  colnames(m) <- paste0("c", seq_len(5))
  m
})
fit_bip <- lame_snap_als(Y_bip, R = 1, mode = "bipartite",
  max_iter = 3, verbose = FALSE)
dim(fit_bip$snap_prob_v)
```

---

|                  |                                                      |
|------------------|------------------------------------------------------|
| latent_positions | <i>Extract latent positions as a tidy data frame</i> |
|------------------|------------------------------------------------------|

---

### Description

Extracts multiplicative latent factor positions (U and V) from a fitted `ame`, `lame` or `ame_als` model and returns them as a tidy data frame suitable for plotting and analysis. Optionally applies Procrustes alignment for dynamic models and includes posterior standard deviations when posterior samples are available.

### Usage

```
latent_positions(object, ...)

## S3 method for class 'ame'
latent_positions(object, align = FALSE, ...)

## S3 method for class 'lame'
latent_positions(object, align = TRUE, ...)

## S3 method for class 'ame_als'
latent_positions(object, align = FALSE, ...)
```

**Arguments**

|                     |                                                                                                                                                                                                                                                            |
|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>object</code> | A fitted <code>ame</code> , <code>lame</code> or <code>ame_als</code> model object with $R > 0$ .                                                                                                                                                          |
| <code>...</code>    | Additional arguments (currently unused).                                                                                                                                                                                                                   |
| <code>align</code>  | Logical. For dynamic models ( <code>dynamic_uv = TRUE</code> ), apply Procrustes alignment across time to remove rotational indeterminacy. Default is <code>FALSE</code> for <code>ame</code> objects and <code>TRUE</code> for <code>lame</code> objects. |

**Value**

A data frame with columns:

**actor** Character. Actor name (from rownames of `U` or `V`).

**dimension** Integer. Latent dimension index (1 to  $R$ ).

**time** Character. Time period label. Dynamic fits use the time labels from the input; static (cross-sectional) fits return "1" for every row so downstream filtering by `time` behaves the same in both cases.

**value** Numeric. The posterior mean latent position.

**posterior\_sd** Numeric. Posterior standard deviation of the latent position, or `NA` if posterior samples are not available. To enable, fit the model with `posterior_opts = posterior_options(save_UV = TRUE)`.

**type** Character. "U" for sender/row positions, "V" for receiver/column positions. Symmetric models have only "U".

Returns a zero-row data frame with correct column names if  $R = 0$ .

**Author(s)**

Cassy Dorff, Shahryar Minhas, Tosin Salau

**See Also**

[procrustes\\_align](#) for standalone Procrustes alignment, [uv\\_plot](#) for visualizing latent positions, [posterior\\_options](#) for enabling posterior sampling of `U/V`

**Examples**

```
data(YX_nrm)
fit <- ame(YX_nrm$Y, Xdyad = YX_nrm$X, R = 2,
          burn = 5, nscan = 5, odens = 1, verbose = FALSE)
lp <- latent_positions(fit)
head(lp)
```

---

lazegalaw

*Lazega's law firm data*


---

### Description

Several nodal and dyadic variables measured on 71 attorneys in a law firm.

### Format

A list consisting of a socioarray  $Y$  and a nodal attribute matrix  $X$ .

The dyadic variables in  $Y$  include three binary networks: advice, friendship and co-worker status.

The categorical nodal attributes in  $X$  are coded as follows:

- status (1=partner, 2=associate)
- office (1=Boston, 2=Hartford, 3=Providence)
- practice (1=litigation, 2=corporate)
- law school (1=Harvard or Yale, 2=UConn, 3=other)

seniority and age are given in years, and female is a binary indicator.

### Source

Originally available at <http://moreno.ss.uci.edu/data.html#lazega> (site no longer accessible).

---

lfo

*Exact rolling-origin leave-future-out cross-validation*


---

### Description

For a fitted `lame` object with  $T$  periods, refits the model on the first  $t - 1$  periods (for each  $t$  in periods) and computes the expected log predictive density (elpd) of period  $t$  under the refit. Returns the summed elpd across all leave-out periods, along with per-period contributions.

### Usage

```
lfo(fit, periods = NULL, refit = TRUE, ...)
```

### Arguments

|                      |                                                                                                                                                                   |
|----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>fit</code>     | A fitted <code>lame</code> object.                                                                                                                                |
| <code>periods</code> | Integer vector of leave-out periods to evaluate. Default is the last 3 periods ( <code>tail(seq_len(T), 3L)</code> ). Each period $t$ must satisfy $t \geq 2$ .   |
| <code>refit</code>   | Logical; if <code>TRUE</code> (default), refits on the training window. If <code>FALSE</code> , uses the original posterior means (a much rougher approximation). |
| <code>...</code>     | Passed to the refit <code>lame()</code> call (typically <code>nscan</code> , <code>burn</code> , <code>odens</code> , <code>verbose</code> ).                     |

**Value**

A list with `elpd_lfo` (total summed elpd), `pointwise` (per-dyad log-density at each leave-out period; a list of numeric vectors, one per period – `unlist(pointwise)` gives a flat vector suitable for `loo::loo_compare()`-style stacking), `p_lfo` (effective number of parameters), `per_period` (data frame with period, elpd, n\_obs), and `periods` (the periods evaluated).

**Examples**

```
data(YX_bin_list)
fit <- lame(YX_bin_list$Y, YX_bin_list$X, family = "binary", R = 0,
           dynamic_beta = "dyad",
           nscan = 60, burn = 15, odens = 5, verbose = FALSE)
lfo_res <- lfo(fit, periods = 4L, refit = TRUE,
              nscan = 50, burn = 10, odens = 5, verbose = FALSE)
print(lfo_res)
```

---

|               |                              |
|---------------|------------------------------|
| list_to_array | <i>Convert list to array</i> |
|---------------|------------------------------|

---

**Description**

Convert list to array

**Usage**

```
list_to_array(actors, Y, Xdyad, Xrow, Xcol)
```

**Arguments**

|        |                                    |
|--------|------------------------------------|
| actors | vector of actors                   |
| Y      | dv in list format                  |
| Xdyad  | dyadic covariates in list format   |
| Xrow   | sender covariates in list format   |
| Xcol   | receiver covariates in list format |

**Value**

transforms Y, Xdyad, Xrow, and Xcol to arrays

**Author(s)**

Shahryar Minhas

---

|                         |                                                    |
|-------------------------|----------------------------------------------------|
| list_to_array_bipartite | <i>Convert bipartite list data to array format</i> |
|-------------------------|----------------------------------------------------|

---

**Description**

Convert bipartite list data to array format

**Usage**

```
list_to_array_bipartite(
  rowActorSet,
  colActorSet,
  Y_list,
  Xdyad = NULL,
  Xrow = NULL,
  Xcol = NULL
)
```

**Value**

List with components Y, Xdyad, Xrow, Xcol in array format

---

|            |                                                                       |
|------------|-----------------------------------------------------------------------|
| logLik.ame | <i>Log-likelihood is not directly exposed for ame() / lame() fits</i> |
|------------|-----------------------------------------------------------------------|

---

**Description**

ame() and lame() produce a posterior sample, not a maximum-likelihood point. A pointwise log-likelihood is computable from the posterior draws but is not stored on the fit object, so logLik() (and the AIC / BIC generics that dispatch through it) error out informatively rather than return a misleading number.

**Usage**

```
## S3 method for class 'ame'
logLik(object, ...)

## S3 method for class 'lame'
logLik(object, ...)
```

**Arguments**

|        |                     |
|--------|---------------------|
| object | an ame or lame fit. |
| ...    | ignored.            |

**Details**

For Bayesian model comparison use posterior-predictive checks via [gof](#) / [gof\\_plot](#), or compute WAIC / LOO yourself from the per-draw log-likelihoods (e.g. via the **loo** package on the BETA / VC chains).

**Value**

Never returns; raises an error.

---

|                |                                                         |
|----------------|---------------------------------------------------------|
| logLik.ame_als | <i>Log-likelihood is not defined for a fast AME fit</i> |
|----------------|---------------------------------------------------------|

---

**Description**

The fast estimator minimises a (working-response) least-squares objective, not a family likelihood, so it has no log-likelihood and AIC / BIC are undefined. Calling logLik() raises an informative error rather than returning a misleading number.

**Usage**

```
## S3 method for class 'ame_als'
logLik(object, ...)
```

**Arguments**

|        |                    |
|--------|--------------------|
| object | an ame_als object. |
| ...    | ignored.           |

**Value**

Never returns; raises an error.

---

|              |                                                                  |
|--------------|------------------------------------------------------------------|
| log_phi_diff | <i>Numerically stable <math>\log(\Phi(hi) - \Phi(lo))</math></i> |
|--------------|------------------------------------------------------------------|

---

**Description**

Computes log of the standard-normal CDF difference. Naive  $\log(\text{pnorm}(hi) - \text{pnorm}(lo))$  returns  $-\text{Inf}$  whenever both arguments are above  $\sim 7$  or below  $\sim -7$  (catastrophic cancellation). Uses  $\text{pnorm}(\cdot, \log.p = \text{TRUE})$  and a stable log-subtraction.

**Usage**

```
log_phi_diff(hi, lo)
```

**Arguments**

hi                    numeric, upper bound  
 lo                    numeric, lower bound (must be  $\leq$  hi elementwise)

**Value**

numeric,  $\log(\text{Phi}(\text{hi}) - \text{Phi}(\text{lo}))$

---

|     |                                                             |
|-----|-------------------------------------------------------------|
| loo | <i>Generic dispatcher for loo / waic on ame / lame fits</i> |
|-----|-------------------------------------------------------------|

---

**Description**

Lightweight S3 generics so calls of the form `loo(fit)` dispatch through R's S3 system even when the **loo** package is not loaded. When **loo** is loaded, its generic resolves first; this fallback only fires for bare-namespace use.

**Usage**

```
loo(x, ...)  

waic(x, ...)
```

**Arguments**

x                    a fitted ame or lame object with `$log_lik`.  
 ...                  passed to the relevant method.

**Value**

A loo / waic object.

---

|         |                                                                       |
|---------|-----------------------------------------------------------------------|
| loo.ame | <i>Approximate leave-one-out cross-validation for AME / LAME fits</i> |
|---------|-----------------------------------------------------------------------|

---

**Description**

S3 method for `loo` that uses the per-iteration pointwise log-likelihood stored on the fit object (`fit$log_lik`) when the model was fit with `save_log_lik = TRUE`. Returns the standard loo object with Pareto-k diagnostics.



**Usage**

```
## S3 method for class 'ame'
loo(x, ...)

## S3 method for class 'lame'
loo(x, ...)

## S3 method for class 'ame_als'
loo(x, ...)
```

**Arguments**

`x`                    A fitted `ame` or `lame` object that has `$log_lik`.

`...`                Additional arguments forwarded to `loo::loo.matrix` (e.g. `cores`, `r_eff`).

**Details**

**What `log_lik` measures.** For family in {normal, binary, cbin, poisson, ordinal} the stored point-wise log-likelihood is the exact family-specific  $Y$  density on the response scale, so `elpd_loo` is directly comparable to a `loo()` output from Stan / brms fit to the same family. For the rank likelihood from the exact marginal needs GHK Monte Carlo (Halton sequence); on the longitudinal `lame()` path you can opt in with `log_lik_method = "observed_ghk"`, on the cross-sectional `ame()` path the fallback is the augmented-Z normal approximation (with a one-time warning). Inspect `fit$log_lik_method` on any fit to see which branch was used.

**Chunked log-lik portability.** When fit with `save_log_lik = "chunked"`, the on-disk chunk files default to `tempdir()`, which is cleared at the end of the R session. If you intend to `saveRDS()` the fit and reload it in a fresh session, supply an explicit persistent `log_lik_path` (e.g. `"./loglik_chunks"`) so the chunks survive the round trip.

**Value**

A `loo` object.

**Examples**

```
data(YX_nrm)
fit <- ame(YX_nrm$Y, Xdyad = YX_nrm$X, R = 0,
          nscan = 60, burn = 15, odens = 5,
          save_log_lik = TRUE, verbose = FALSE)
if (requireNamespace("loo", quietly = TRUE)) {
  loo_res <- loo::loo(fit)
  print(loo_res)
}
```

---

|       |                                          |
|-------|------------------------------------------|
| mhalf | <i>Symmetric square root of a matrix</i> |
|-------|------------------------------------------|

---

**Description**

Computes the symmetric square root of a positive definite matrix

**Usage**

```
mhalf(M)
```

**Arguments**

M                      a positive definite matrix

**Value**

a matrix H such that  $H^2$  equals M

**Author(s)**

Cassy Dorff, Shahryar Minhas, Tosin Salau

---

|          |                                                      |
|----------|------------------------------------------------------|
| nobs.ame | <i>Number of observed dyads in an AME / LAME fit</i> |
|----------|------------------------------------------------------|

---

**Description**

Number of finite (non-missing) cells in Y, summed over time slices for longitudinal fits. Useful as a denominator for sample-size reporting and as the basis for AIC/BIC *if* you also have a log-likelihood (which `ame()` / `lame()` do not directly expose; see [logLik.ame](#)).

**Usage**

```
## S3 method for class 'ame'
nobs(object, ...)

## S3 method for class 'lame'
nobs(object, ...)
```

**Arguments**

object                  an ame or lame fit.  
...                      ignored.

**Value**

Integer: number of observed dyads in Y.

---

|              |                                                   |
|--------------|---------------------------------------------------|
| nobs.ame_als | <i>Number of observed dyads in an ame_als fit</i> |
|--------------|---------------------------------------------------|

---

### Description

Mirrors `nobs.ame` so the MCMC and ALS fits expose the same accessor.

### Usage

```
## S3 method for class 'ame_als'
nobs(object, ...)
```

### Arguments

|        |                 |
|--------|-----------------|
| object | an ame_als fit. |
| ...    | ignored.        |

### Value

Integer: number of observed dyads.

---

|           |                                                        |
|-----------|--------------------------------------------------------|
| nodematch | <i>ERGM-style covariate helpers for ame() / lame()</i> |
|-----------|--------------------------------------------------------|

---

### Description

`nodematch(x)` returns an  $n \times n$  matrix with 1 where  $x[i] == x[j]$  and 0 otherwise – the AME analogue of ERGM’s `nodematch` term, suitable for `Xdyad` as a single homophily covariate. `absdiff(x)` returns the absolute difference  $|x[i] - x[j]|$ , the AME analogue of ERGM’s `absdiff`. `nodefactor(x)` returns the dyadic matrix of  $x[i] + x[j]$  for a numeric  $x$  (or, for a factor / character  $x$ , a named list with one matrix per level giving the dyadic co-membership count  $(x[i] == \text{level}) + (x[j] == \text{level})$ , with entries 0, 1, or 2, the ERGM `nodefactor` semantics).

### Usage

```
nodematch(x, na_diag = TRUE)

absdiff(x, na_diag = TRUE)

nodefactor(x, na_diag = TRUE)
```

### Arguments

|         |                                                        |
|---------|--------------------------------------------------------|
| x       | a numeric, factor, or character vector of length $n$ . |
| na_diag | logical: set the diagonal to NA? Defaults to TRUE.     |

## Details

All helpers return a matrix *or* list of matrices that is ready to wrap into an  $n \times n \times p$  Xdyad array via `simplify2array` or `array()`.

## Value

An  $n \times n$  numeric matrix (or, for a factor `x` passed to `nodefactor`, a named list of such matrices).

## Examples

```
n <- 12
grp <- sample(letters[1:3], n, replace = TRUE)
age <- rnorm(n, 40, 10)
# build a single same-group homophily covariate
Xdyad <- array(nodematch(grp), dim = c(n, n, 1),
               dimnames = list(NULL, NULL, "same_group"))
# combine homophily + age difference
Xdyad <- array(c(nodematch(grp), absdiff(age)),
               dim = c(n, n, 2),
               dimnames = list(NULL, NULL, c("same_group", "age_diff")))
```

---

|                  |                                                |
|------------------|------------------------------------------------|
| per_actor_slopes | <i>Post-MCMC per-actor time-varying slopes</i> |
|------------------|------------------------------------------------|

---

## Description

Computes a smoothed per-actor time-varying slope coefficient on a slice of the combined dyadic design array (`fit$Xlist`). For `kind = "row"`, each row-actor  $i$  gets a length- $T$  slope path  $\beta_{i,t}$  on the across-column mean of design slice `covariate_idx`, fit by ridge-penalised least squares on the residual after the main MCMC linear predictor; `kind = "col"` uses the across-row mean for each column-actor.

## Usage

```
per_actor_slopes(fit, kind = c("row", "col"), covariate_idx = 1L, lambda = 1)
```

## Arguments

|                            |                                                                                                                                                                                  |
|----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>fit</code>           | A fitted <code>lame</code> object.                                                                                                                                               |
| <code>kind</code>          | "row" (default; per-row-actor slopes) or "col" (per-column-actor slopes).                                                                                                        |
| <code>covariate_idx</code> | Integer index into the third (covariate) dimension of the combined dyadic design array <code>fit\$Xlist</code> . Slice 1 is the intercept; dyadic covariates follow. Default 1L. |
| <code>lambda</code>        | Non-negative smoothing parameter (first-difference penalty across periods). Default 1.                                                                                           |

**Value**

A list with slopes (an  $n_{actors} \times T$  matrix), kind, covariate\_idx, lambda, and label. Class "per\_actor\_slopes".

**Examples**

```
data(YX_bin_list)
fit <- lame(YX_bin_list$Y, YX_bin_list$X, family = "binary", R = 0,
           nscan = 100, burn = 25, odens = 5, verbose = FALSE)
# post-MCMC per-row-actor slopes on the first dyadic covariate
pas <- per_actor_slopes(fit, kind = "row", lambda = 1)
dim(pas$slopes)
```

---

plot.ame

Simple diagnostic plot for AME model fit

---

**Description**

Provides a quick visual summary of an AME model fit, focusing on key convergence diagnostics. For more detailed diagnostics, use the specific plotting functions: trace\_plot(), gof\_plot(), ab\_plot(), and uv\_plot().

**Usage**

```
## S3 method for class 'ame'
plot(x, ...)
```

**Arguments**

x                    an object of class "ame" from fitting an AME model  
...                   additional arguments passed to trace\_plot()

**Details**

By default, this function simply calls trace\_plot() to show MCMC trace plots and posterior distributions for key parameters. This provides a quick check of model convergence and mixing.

For more detailed visualizations, use the specialized functions:

**trace\_plot()** MCMC diagnostics and posterior distributions

**gof\_plot()** Goodness-of-fit assessment

**ab\_plot()** Additive sender/receiver effects

**uv\_plot()** Multiplicative latent factors

**Value**

A ggplot2 object from trace\_plot() (invisibly)

**Author(s)**

Cassy Dorff, Shahryar Minhas, Tosin Salau

**See Also**

[ame](#), [trace\\_plot](#), [gof\\_plot](#), [ab\\_plot](#), [uv\\_plot](#)

**Examples**

```
# Fit an AME model
data(YX_nrm)
fit <- ame(YX_nrm$Y, Xdyad = YX_nrm$X, R = 2, gof = TRUE,
          nscan = 100, burn = 10, odens = 1, verbose = FALSE)

# Quick diagnostic plot (shows trace plots)
plot(fit)
```

---

plot.ame\_als

---

*Plot the convergence of a fast AME fit*


---

**Description**

Plots the block coordinate descent deviance/SSE history – a convergence diagnostic for an [ame\\_als](#) or [lame\\_als](#) fit. For substantive plots see [uv\\_plot](#), [ab\\_plot](#) and [gof\\_plot](#).

**Usage**

```
## S3 method for class 'ame_als'
plot(x, ...)
```

**Arguments**

**x** an `ame_als` object.

**...** further arguments passed to the underlying plot.

**Value**

`x`, invisibly.

plot.lame

*Plot diagnostics for a LAME model fit***Description**

Creates diagnostic plots for a LAME (Longitudinal Additive and Multiplicative Effects) model, including MCMC diagnostics, parameter evolution over time, and longitudinal goodness-of-fit checks. This is the default plot method for LAME objects.

**Usage**

```
## S3 method for class 'lame'
plot(
  x,
  which = c(1, 2, 3, 4),
  time.points = NULL,
  ask = FALSE,
  pages = c("single", "multiple"),
  ...
)
```

**Arguments**

|                          |                                                                                                                                                                                                                                                                                                                                                             |
|--------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>x</code>           | an object of class "lame" from fitting a LAME model                                                                                                                                                                                                                                                                                                         |
| <code>which</code>       | numeric or character vector specifying which plots to produce: 1 or "trace" = MCMC trace plots, 2 or "density" = posterior density plots, 3 or "gof" = longitudinal goodness-of-fit plots, 4 or "effects" = additive and multiplicative effects, 5 or "network" = network snapshots at selected times. Default is c(1,2,3,4) to show main diagnostic plots. |
| <code>time.points</code> | numeric vector of time points for network snapshots (only used if "network" in which). Default is c(1, middle, last).                                                                                                                                                                                                                                       |
| <code>ask</code>         | logical; if TRUE, user is prompted before each plot page                                                                                                                                                                                                                                                                                                    |
| <code>pages</code>       | character string specifying how to arrange plots: "single" = one combined page (default), "multiple" = separate pages for each plot type                                                                                                                                                                                                                    |
| <code>...</code>         | additional arguments (currently not used)                                                                                                                                                                                                                                                                                                                   |

**Details**

The function produces a multi-panel plot containing:

**MCMC trace plots** Shows mixing and convergence of key parameters

**Posterior distributions** Density plots of regression coefficients and variance components

**Longitudinal GOF** Time series of observed network statistics with posterior predictive intervals

**Effects over time** Evolution of additive effects across time periods (if applicable)

**Network snapshots** Visualization of network at selected time points

The plot adapts to the longitudinal structure:

- Shows temporal trends in network statistics
- Highlights composition changes if actors enter/exit
- Displays credible intervals for time-varying statistics

### Value

NULL (invisibly). Plots are displayed as side effects.

### Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

### See Also

[lame](#), [trace\\_plot](#), [gof\\_plot](#), [ab\\_plot](#), [uv\\_plot](#)

### Examples

```
# Create simple longitudinal network data
set.seed(6886)
n <- 10
nms <- paste0("n", 1:n)
Y_list <- list(
  matrix(rnorm(n * n), n, n, dimnames = list(nms, nms)),
  matrix(rnorm(n * n), n, n, dimnames = list(nms, nms))
)
diag(Y_list[[1]]) <- diag(Y_list[[2]]) <- NA
fit <- lame(Y_list, family = "normal",
           nscan = 50, burn = 10, odens = 1, verbose = FALSE, plot = FALSE)

# default combined plot
plot(fit)
```

---

posterior\_options

*Options for saving posterior samples during MCMC*

---

### Description

Options for saving posterior samples during MCMC

### Usage

```
posterior_options(save_UV = FALSE, save_ab = FALSE, thin_UV = 10, thin_ab = 10)
```



**Arguments**

|         |                                                                              |
|---------|------------------------------------------------------------------------------|
| save_UV | Logical; whether to save samples of U and V matrices (default FALSE)         |
| save_ab | Logical; whether to save samples of additive effects a and b (default FALSE) |
| thin_UV | Integer; thinning interval for U/V samples (default 10)                      |
| thin_ab | Integer; thinning interval for a/b samples (default 10)                      |

**Value**

List of posterior saving options, to be passed to the posterior\_opts argument of `ame`: `ame(Y, ..., posterior_opts = posterior_options(save_UV = TRUE))`

**Author(s)**

Cassy Dorff, Shahryar Minhas, Tosin Salau

---

|                     |                                                         |
|---------------------|---------------------------------------------------------|
| posterior_quantiles | <i>Extract posterior quantiles for model components</i> |
|---------------------|---------------------------------------------------------|

---

**Description**

Extract posterior quantiles for model components

**Usage**

```
posterior_quantiles(  
  fit,  
  component = c("beta", "UV", "ab"),  
  probs = c(0.025, 0.5, 0.975)  
)
```

**Arguments**

|           |                                                |
|-----------|------------------------------------------------|
| fit       | Fitted ame model object                        |
| component | Character; which component: "beta", "UV", "ab" |
| probs     | Numeric vector of probabilities for quantiles  |

**Value**

Matrix or array of posterior quantiles

**Author(s)**

Cassy Dorff, Shahryar Minhas, Tosin Salau

---

```
precomputeX
```

---

*Precompute design-array cross-product summaries*

---

### Description

Attaches to a dyadic covariate array the row/column margins and the Gram matrices of its vectorised (and dyad-transposed) design, so that the regression update inside the MCMC need not recompute them.

### Usage

```
precomputeX(X)
```

### Arguments

`X` `n x n x p` array of dyadic covariates.

### Value

`X` unchanged in value but carrying the extra attributes `Xr` (`n x p` row margins), `Xc` (`n x p` column margins), `mX` (`n^2 x p` vectorised design), `mXt` (`n^2 x p` dyad-transposed vectorised design), `XX` (`p x p` Gram matrix `crossprod(mX)`) and `XXt` (`p x p` cross Gram matrix `crossprod(mX, mXt)`).

### Author(s)

lame authors

---

```
predict.ame
```

---

*Predict method for AME models*

---

### Description

Generate predictions from fitted AME models, including point estimates and predictive distributions.

### Usage

```
## S3 method for class 'ame'
predict(
  object,
  newdata = NULL,
  type = c("response", "link", "distribution"),
  n_samples = 100,
  include_uncertainty = TRUE,
  ...
)
```

**Arguments**

|                     |                                                                                                                                                                                                                                                                                                                                                                                   |
|---------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| object              | Fitted AME model object                                                                                                                                                                                                                                                                                                                                                           |
| newdata             | Optional dyadic covariates for prediction: a single 3-D array ( $n \times n \times p_{\text{dyad}}$ ) whose slices match the dyadic covariates the model was fit with (same order; do not include the intercept or nodal-covariate slices). Nodal covariates cannot be changed at prediction time – their fitted contribution is reused. When omitted, the fitted design is used. |
| type                | Character; type of prediction: <ul style="list-style-type: none"> <li>• "response": predicted values on response scale (default)</li> <li>• "link": predicted values on link scale</li> <li>• "distribution": full posterior predictive distribution</li> </ul>                                                                                                                   |
| n_samples           | For type="distribution", number of posterior samples                                                                                                                                                                                                                                                                                                                              |
| include_uncertainty | Logical; include parameter uncertainty (default TRUE)                                                                                                                                                                                                                                                                                                                             |
| ...                 | Additional arguments (not used)                                                                                                                                                                                                                                                                                                                                                   |

**Value**

Depending on type:

- "response"/"link": Matrix of predictions
- "distribution": Array of posterior predictive samples

**Author(s)**

Cassy Dorff, Shahryar Minhas, Tosin Salau

**Examples**

```
# Fit model
data(YX_nrm)
fit <- ame(YX_nrm$Y, Xdyad = YX_nrm$X, R = 2,
           nscan = 100, burn = 10, odens = 1, verbose = FALSE)

# Point predictions
Y_pred <- predict(fit)

# Predictions on link scale
Y_link <- predict(fit, type = "link")
```

---

|                 |                                        |
|-----------------|----------------------------------------|
| predict.ame_als | <i>Predictions from a fast AME fit</i> |
|-----------------|----------------------------------------|

---

### Description

Returns predictions from an `ame_als` or `lame_als` fit: the fitted linear predictor on the link scale (`type = "link"`) or the response scale (`type = "response"`, the default).

### Usage

```
## S3 method for class 'ame_als'
predict(object, newdata = NULL, type = c("response", "link"), ...)
```

### Arguments

|                      |                                                                                                                                         |
|----------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| <code>object</code>  | an <code>ame_als</code> object.                                                                                                         |
| <code>newdata</code> | optional dyadic covariate array matching <code>object\$X</code> ( <code>[n_row, n_col, p, T]</code> ); a matrix or 3D array is coerced. |
| <code>type</code>    | "response" (default) or "link".                                                                                                         |
| <code>...</code>     | ignored.                                                                                                                                |

### Details

With `newdata = NULL` the training-data fitted values are returned. Supplying `newdata` – a dyadic covariate array with the *same* actors and dimensions as the fitted design – substitutes the dyadic covariate contribution while holding the intercept, additive effects and multiplicative term fixed; it predicts counterfactual dyadic covariates for the same network, not out-of-sample actors.

### Value

A matrix (cross-sectional) or list of matrices (longitudinal).

---

|              |                                       |
|--------------|---------------------------------------|
| predict.lame | <i>Predict method for LAME models</i> |
|--------------|---------------------------------------|

---

### Description

Generate predictions from a fitted longitudinal AME model. Returns a list of matrices (one per time point) on the requested scale.

**Usage**

```
## S3 method for class 'lame'
predict(
  object,
  newdata = NULL,
  type = c("response", "link"),
  h = 0L,
  by_draw = FALSE,
  interval = c("none", "credible"),
  probs = c(0.025, 0.975),
  newexposure = NULL,
  n_draws = NULL,
  seed = NULL,
  ...
)
```

**Arguments**

|             |                                                                                                                                                                                                                                                                                                                                                      |
|-------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| object      | Fitted LAME model object.                                                                                                                                                                                                                                                                                                                            |
| newdata     | Optional list of T dyadic covariate arrays ( $[n\_row, n\_col, p]$ each, with the same actors as the fit) to compute counterfactual predictions. When NULL, the training-data predictions are returned.                                                                                                                                              |
| type        | Character; "response" (default) or "link".                                                                                                                                                                                                                                                                                                           |
| h           | Integer $\geq 0$ : forecast horizon. When $h = 0$ (default), returns in-sample predictions as before. When $h > 0$ , propagates the AR(1) (or RW1) state-space model forward by h periods and returns a list of h matrices (one per future period). Requires at least one dynamic component on the fit. Warns when posterior $\rho_\beta$ is near 1. |
| by_draw     | When TRUE and $h > 0$ , returns an $n \times n \times h \times n\_draws$ array of per-draw forecasts instead of per-period means.                                                                                                                                                                                                                    |
| interval    | One of "none" (default) or "credible". When $h > 0$ and "credible", the per-period output is a list of length-3 lists with \$lower, \$median, \$upper matrices computed at the probs quantiles across posterior draws. Ignored for in-sample ( $h = 0$ ) predictions.                                                                                |
| probs       | Length-2 vector of lower / upper quantiles for the credible interval when interval = "credible". Default c(0.025, 0.975).                                                                                                                                                                                                                            |
| newexposure | Optional length-h non-negative numeric vector of future-period exposures (Poisson only). When omitted and the fit has period_exposure stored, defaults to the last observed exposure; when both are absent, defaults to 1.                                                                                                                           |
| n_draws     | Number of posterior draws to use when $h > 0$ . Default NULL uses all stored draws. Ignored for in-sample ( $h = 0$ ) predictions.                                                                                                                                                                                                                   |
| seed        | Optional RNG seed for the $h > 0$ forecast draws, making forecasts reproducible. Ignored when $h = 0$ .                                                                                                                                                                                                                                              |
| ...         | Additional arguments (not used).                                                                                                                                                                                                                                                                                                                     |

**Value**

List of prediction matrices (one per time point).

---

prediction\_draws\_long *Long-format draws of the linear predictor for marginalesffects-style use*

---

**Description**

Returns a long-format data frame with one row per (draw, i, j, period) combination, giving the per-draw linear predictor (or response-scale prediction) at each dyad and period. Only the regression coefficients vary across .draw: the additive (a, b) and multiplicative (U, V) effects are held at their posterior means, so the spread across draws reflects coefficient uncertainty only, not the full posterior of the linear predictor. Intended for **marginalesffects**- / **tidybayes**-style downstream summarisation: column names follow the .draw / .chain / .iteration / .value convention so that tidybayes::spread\_draws() and marginalesffects::posterior\_draws() auto-dispatch on the returned data frame. Actor and period names from fit\$Y's dimnames are carried forward into the actor\_i, actor\_j, period\_label columns.

**Usage**

```
prediction_draws_long(
  object,
  newdata = NULL,
  type = c("link", "response"),
  n_draws = 100L,
  seed = NULL
)
```

**Arguments**

|         |                                                                                                                   |
|---------|-------------------------------------------------------------------------------------------------------------------|
| object  | A fitted lame object.                                                                                             |
| newdata | Optional list of T dyadic covariate arrays for counterfactual evaluation. Default NULL uses in-sample covariates. |
| type    | One of "link" (default) or "response".                                                                            |
| n_draws | Number of posterior draws to use. Default 100.                                                                    |
| seed    | Optional RNG seed.                                                                                                |

**Value**

A long-format data frame with columns .chain, .iteration, .draw, period, period\_label, i, j, actor\_i, actor\_j, .value. Returned as a tibble when the **tibble** package is available; otherwise a plain data frame.

---

```
print.als_dynamic_beta
```

*Print method for penalised ALS time-varying beta*

---

### Description

Print method for penalised ALS time-varying beta

### Usage

```
## S3 method for class 'als_dynamic_beta'
print(x, digits = 4, ...)
```

### Arguments

|        |                               |
|--------|-------------------------------|
| x      | An als_dynamic_beta result.   |
| digits | Number of significant digits. |
| ...    | Ignored.                      |

### Value

x, invisibly. Called for its side effect of printing a summary of the penalised ALS time-varying coefficient estimates.

---

```
print.ame
```

*Print method for AME model objects*

---

### Description

Displays a formatted summary of a fitted AME (Additive and Multiplicative Effects) model. This method provides a concise overview of model structure, parameter estimates, and goodness-of-fit statistics without generating new data.

### Usage

```
## S3 method for class 'ame'
print(x, ...)
```

### Arguments

|     |                                                    |
|-----|----------------------------------------------------|
| x   | an object of class "ame" from fitting an AME model |
| ... | additional arguments (not currently used)          |

**Details**

The print method displays:

- Model type (unipartite/bipartite, symmetric/asymmetric)
- Network dimensions and observation count
- Family and link function used
- Number of MCMC iterations
- Parameter counts for regression coefficients and latent factors
- Basic convergence diagnostics if available

Unlike `simulate`, this method only formats existing results for display and does not perform any new computations or data generation.

**Value**

Invisibly returns the input object (for method chaining)

**Author(s)**

Cassy Dorff, Shahryar Minhas, Tosin Salau

**See Also**

[summary.ame](#) for detailed summaries, [simulate.ame](#) for generating new networks, [predict.ame](#) for predictions

**Examples**

```
# Fit model
data(YX_nrm)
fit <- ame(YX_nrm$Y, Xdyad = YX_nrm$X, R = 2,
          nscan = 100, burn = 10, odens = 1, verbose = FALSE)

# Display summary
print(fit)
```

---

print.ame.sim

---

*Print methods for AME and LAME simulation objects*


---

**Description**

Print methods for AME and LAME simulation objects



**Usage**

```
## S3 method for class 'ame.sim'  
print(x, ...)  
  
## S3 method for class 'lame.sim'  
print(x, ...)
```

**Arguments**

|     |                                                    |
|-----|----------------------------------------------------|
| x   | simulation object of class "ame.sim" or "lame.sim" |
| ... | additional arguments (not used)                    |

**Value**

the simulation object invisibly

**Author(s)**

Shahryar Minhas

---

|               |                                |
|---------------|--------------------------------|
| print.ame_als | <i>Print an ame_als object</i> |
|---------------|--------------------------------|

---

**Description**

Print an ame\_als object

**Usage**

```
## S3 method for class 'ame_als'  
print(x, digits = 4, ...)
```

**Arguments**

|        |                              |
|--------|------------------------------|
| x      | an ame_als object.           |
| digits | number of digits to display. |
| ...    | ignored.                     |

**Value**

x, invisibly.

---

|                |                                                   |
|----------------|---------------------------------------------------|
| print.boot_ame | <i>Print bootstrap results for a fast AME fit</i> |
|----------------|---------------------------------------------------|

---

**Description**

Print bootstrap results for a fast AME fit

**Usage**

```
## S3 method for class 'boot_ame'
print(x, digits = max(3L, getOption("digits") - 3L), ...)
```

**Arguments**

|        |                              |
|--------|------------------------------|
| x      | a boot_ame object.           |
| digits | number of digits to display. |
| ...    | ignored.                     |

**Value**

x, invisibly.

---

|                    |                                             |
|--------------------|---------------------------------------------|
| print.gof_temporal | <i>Print method for gof_temporal output</i> |
|--------------------|---------------------------------------------|

---

**Description**

Print method for gof\_temporal output

**Usage**

```
## S3 method for class 'gof_temporal'
print(x, ...)
```

**Arguments**

|     |                        |
|-----|------------------------|
| x   | A gof_temporal result. |
| ... | Ignored.               |

**Value**

x, invisibly. Called for its side effect of printing a summary of the temporal-trend posterior-predictive check.

---

|            |                                      |
|------------|--------------------------------------|
| print.lame | <i>Print method for LAME objects</i> |
|------------|--------------------------------------|

---

**Description**

Provides a concise print output for fitted LAME models. When the fit has two or more dynamic effects active simultaneously (dynamic\_uv + dynamic\_ab + dynamic\_beta in any combination), a compact joint table summarising the AR(1) hyperparameters of each dynamic block is printed instead of a separate paragraph per component. Disable the compact mode by passing compact = FALSE.

**Usage**

```
## S3 method for class 'lame'
print(x, compact = TRUE, digits = 3, ...)
```

**Arguments**

|         |                                                                                                                                                         |
|---------|---------------------------------------------------------------------------------------------------------------------------------------------------------|
| x       | an object of class "lame"                                                                                                                               |
| compact | logical: when TRUE (default), use a compact joint table for fits with 2+ dynamic components; set to FALSE to force the per-component long-form display. |
| digits  | Number of digits to display in the compact table. Default 3.                                                                                            |
| ...     | additional arguments (not used)                                                                                                                         |

**Value**

the lame object invisibly

**Author(s)**

Cassy Dorff, Shahryar Minhas, Tosin Salau

---

|                  |                                    |
|------------------|------------------------------------|
| print.lame_multi | <i>Print method for lame_multi</i> |
|------------------|------------------------------------|

---

**Description**

Print method for lame\_multi

**Usage**

```
## S3 method for class 'lame_multi'
print(x, digits = 3, ...)
```

**Arguments**

|        |                               |
|--------|-------------------------------|
| x      | A lame_multi object.          |
| digits | Number of significant digits. |
| ...    | Ignored.                      |

**Value**

x, invisibly. Called for its side effect of printing a summary of the pooled multi-panel fit.

---

|                |                                       |
|----------------|---------------------------------------|
| print.lfo_lame | <i>Print method for lfo() results</i> |
|----------------|---------------------------------------|

---

**Description**

Print method for lfo() results

**Usage**

```
## S3 method for class 'lfo_lame'
print(x, ...)
```

**Arguments**

|     |                    |
|-----|--------------------|
| x   | A lfo_lame object. |
| ... | Ignored.           |

**Value**

x, invisibly. Called for its side effect of printing a summary of the leave-future-out cross-validation results.

---

|                        |                                          |
|------------------------|------------------------------------------|
| print.per_actor_slopes | <i>Print method for per_actor_slopes</i> |
|------------------------|------------------------------------------|

---

**Description**

Print method for per\_actor\_slopes

**Usage**

```
## S3 method for class 'per_actor_slopes'
print(x, digits = 3, ...)
```

**Arguments**

|        |                               |
|--------|-------------------------------|
| x      | A per_actor_slopes result.    |
| digits | Number of significant digits. |
| ...    | Ignored.                      |

**Value**

x, invisibly. Called for its side effect of printing a summary of the per-actor time-varying slopes.

---

|                   |                                             |
|-------------------|---------------------------------------------|
| print.summary.ame | <i>Print method for summary.ame objects</i> |
|-------------------|---------------------------------------------|

---

**Description**

Prints a formatted summary of an AME model fit

**Usage**

```
## S3 method for class 'summary.ame'
print(x, digits = 3, ...)
```

**Arguments**

|        |                                          |
|--------|------------------------------------------|
| x      | a summary.ame object                     |
| digits | number of digits to display (default: 3) |
| ...    | additional arguments (not used)          |

**Value**

the summary.ame object invisibly

---

|                       |                                 |
|-----------------------|---------------------------------|
| print.summary.ame_als | <i>Print a fast AME summary</i> |
|-----------------------|---------------------------------|

---

**Description**

Print a fast AME summary

**Usage**

```
## S3 method for class 'summary.ame_als'
print(x, digits = 4, ...)
```

**Arguments**

- x                    a summary.ame\_als object.
- digits              number of digits to display.
- ...                  ignored.

**Value**

x, invisibly.

---

|                    |                                              |
|--------------------|----------------------------------------------|
| print.summary.lame | <i>Print method for summary.lame objects</i> |
|--------------------|----------------------------------------------|

---

**Description**

Prints a formatted summary of a LAME model fit

**Usage**

```
## S3 method for class 'summary.lame'  
print(x, digits = 3, ...)
```

**Arguments**

- x                    a summary.lame object
- digits              number of digits to display (default: 3)
- ...                  additional arguments (not used)

**Value**

the summary.lame object invisibly

---

|               |                                                             |
|---------------|-------------------------------------------------------------|
| prior_summary | <i>Print the priors used by an AME / LAME / ame_als fit</i> |
|---------------|-------------------------------------------------------------|

---

**Description**

Bayesian-hygiene helper modelled on rstanarm::prior\_summary(). Prints the priors that were actually in effect for a fit, with defaults filled in. For ame\_als fits it just states that the estimator is a frequentist point estimator and there are no priors.

**Usage**

```
prior_summary(object, ...)

## Default S3 method:
prior_summary(object, ...)

## S3 method for class 'ame'
prior_summary(object, ...)

## S3 method for class 'lame'
prior_summary(object, ...)

## S3 method for class 'ame_als'
prior_summary(object, ...)
```

**Arguments**

```
object      a fitted ame, lame, or ame_als object.
...         ignored.
```

**Value**

```
object, invisibly.
```

---

|                  |                                                             |
|------------------|-------------------------------------------------------------|
| procrustes_align | <i>Procrustes alignment of latent positions across time</i> |
|------------------|-------------------------------------------------------------|

---

**Description**

Aligns dynamic latent positions across time periods to remove arbitrary rotational indeterminacy. This is essential for interpreting temporal trajectories of latent positions, since the latent space is only identified up to rotation at each time point.

Uses Procrustes rotation: at each time step, finds the orthogonal rotation matrix that best aligns the current sender coordinates to the preceding period, then applies it sequentially through the series.

**Usage**

```
procrustes_align(
  object = NULL,
  U = NULL,
  V = NULL,
  G = NULL,
  return_fit = FALSE,
  per_draw = FALSE,
  ...
)
```

**Arguments**

|                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|-------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>object</code>     | A fitted <code>ame</code> or <code>lame</code> object, or <code>NULL</code> if raw arrays are provided via <code>U/V/G</code> .                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <code>U</code>          | Optional 3D array $[n, R, T]$ of sender latent positions. If <code>object</code> is provided and <code>U</code> is <code>NULL</code> , extracted from <code>object\$U</code> .                                                                                                                                                                                                                                                                                                                                                                                                                |
| <code>V</code>          | Optional 3D array $[n, R, T]$ of receiver latent positions. For unipartite asymmetric models, aligned independently. For bipartite models, aligned jointly with <code>U</code> via the <code>G</code> interaction matrix.                                                                                                                                                                                                                                                                                                                                                                     |
| <code>G</code>          | Optional $[R\_row, R\_col]$ interaction matrix for bipartite models, transformed to preserve the invariant $U G V'$ .                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <code>return_fit</code> | Logical. If <code>TRUE</code> and <code>object</code> is provided, returns a modified copy of the fit object with aligned latent positions. Default <code>FALSE</code> .                                                                                                                                                                                                                                                                                                                                                                                                                      |
| <code>per_draw</code>   | Logical. When <code>TRUE</code> , run Procrustes alignment per posterior draw rather than on the posterior-mean trajectory. This uses <code>object\$U_full / object\$V_full</code> (the per-draw posterior cubes – populated when <code>posterior_opts</code> includes storing <code>U/V</code> ) when present; otherwise falls back to mean-trajectory alignment and emits an informational note. Per-draw alignment is the methodologically correct treatment – rotation indeterminacy is a per-draw property, not a per-mean one – but is more memory-hungry. Default <code>FALSE</code> . |
| <code>...</code>        | Additional arguments (currently unused).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |

**Details**

For unipartite networks, `U` and `V` are aligned independently using separate Procrustes rotations. For symmetric networks, only `U` is present and aligned.

For bipartite networks, `U` and `V` are aligned jointly: separate rotation matrices are computed for `U` and `V`, and the `G` interaction matrix is updated as `G_aligned = t(R_U) %*% G %*% R_V` to preserve the product  $U \% \% G \% \% t(V)$ .

If `U` is a 2D matrix (static model with a single time point), it is returned unchanged with an informational message.

**Value**

If `return_fit = FALSE` (default): a list with components `U` (aligned sender positions), `V` (aligned receiver positions, if applicable), and `G` (updated interaction matrix, for bipartite).

If `return_fit = TRUE`: a copy of `object` with aligned latent positions replacing the originals.

**Author(s)**

Cassy Dorff, Shahryar Minhas, Tosin Salau

**See Also**

[latent\\_positions](#) for extracting aligned positions as a tidy data frame, [uv\\_plot](#) for visualizing latent positions



## Examples

```
data(YX_bin_list)
# YX_bin_list$Y stores latent-scale values; threshold to 0/1 first
Y_bin <- lapply(YX_bin_list$Y, function(y) 1 * (y > 0))
fit <- lame(Y_bin, Xdyad = YX_bin_list$X, R = 2,
            family = "binary", dynamic_uv = TRUE,
            burn = 5, nscan = 5, odens = 1,
            verbose = FALSE)
aligned <- procrustes_align(fit)
str(aligned$U) # aligned 3D array [n, R, T]
```

---

raSab\_bin\_fc

*Sample additive row effects and their covariance for the binary family*


---

## Description

Joint Gibbs update of the social-relations additive row effects  $a$  and the additive-effect covariance  $Sab$  under a probit (binary) likelihood. Given the latent normal scores  $Z$  and the observed 0/1 matrix  $Y$ , each row effect is redrawn from its Gaussian full conditional (conditioned on the column effects  $b$  through  $Sab$ ) truncated to the interval that keeps every latent score sign-compatible with the observed responses. The covariance  $Sab$  is then refreshed from its inverse-Wishart full conditional.

## Usage

```
raSab_bin_fc(
  Z,
  Y,
  a,
  b,
  Sab,
  Sab0 = NULL,
  eta0 = NULL,
  SS = round(sqrt(nrow(Z)))
)
```

## Arguments

|          |                                                           |
|----------|-----------------------------------------------------------|
| $Z$      | square matrix of current latent normal scores             |
| $Y$      | square binary relational matrix (NA entries allowed)      |
| $a$      | current value of the row effects                          |
| $b$      | current value of the column effects                       |
| $Sab$    | current 2x2 covariance of the additive effects            |
| $Sab0$   | prior inverse-scale matrix (defaults to the 2x2 identity) |
| $\eta_0$ | prior degrees of freedom (defaults to 4)                  |
| $SS$     | number of inner Gibbs sweeps                              |

**Value**

list with the updated Z, a and Sab

**Author(s)**

lame authors

---

|               |                                                                                         |
|---------------|-----------------------------------------------------------------------------------------|
| raSab_cbin_fc | <i>Simulate a and Sab from full conditional distributions under the cbin likelihood</i> |
|---------------|-----------------------------------------------------------------------------------------|

---

**Description**

Simulate a and Sab from full conditional distributions under the cbin likelihood

**Usage**

```
raSab_cbin_fc(Z, Y, a, b, Sab, odmax, odobs, Sab0=NULL, eta0=NULL, SS =  
round(sqrt(nrow(Z))))
```

**Arguments**

|       |                                                                                 |
|-------|---------------------------------------------------------------------------------|
| Z     | a square matrix, the current value of Z                                         |
| Y     | square matrix of ranked nomination data                                         |
| a     | current value of row effects                                                    |
| b     | current value of column effects                                                 |
| Sab   | current value of Cov(a,b)                                                       |
| odmax | a scalar or vector giving the maximum number of nominations for each individual |
| odobs | observed outdegree                                                              |
| Sab0  | prior (inverse) scale matrix for the prior distribution                         |
| eta0  | prior degrees of freedom for the prior distribution                             |
| SS    | number of iterations                                                            |

**Value**

|     |                  |
|-----|------------------|
| Z   | new value of Z   |
| Sab | new value of Sab |
| a   | new value of a   |

**Author(s)**

lame authors

---

|              |                                                                                    |
|--------------|------------------------------------------------------------------------------------|
| raSab_frn_fc | <i>Simulate a and Sab from full conditional distributions under frn likelihood</i> |
|--------------|------------------------------------------------------------------------------------|

---

## Description

Simulate a and Sab from full conditional distributions under frn likelihood

## Usage

```
raSab_frn_fc(Z, Y, YL, a, b, Sab, odmax, odobs, Sab0=NULL, eta0=NULL,
SS=round(sqrt(nrow(Z))))
```

## Arguments

|       |                                                                                 |
|-------|---------------------------------------------------------------------------------|
| Z     | a square matrix, the current value of Z                                         |
| Y     | square matrix of ranked nomination data                                         |
| YL    | list of ranked individuals, from least to most preferred in each row            |
| a     | current value of row effects                                                    |
| b     | current value of column effects                                                 |
| Sab   | current value of Cov(a,b)                                                       |
| odmax | a scalar or vector giving the maximum number of nominations for each individual |
| odobs | observed outdegree                                                              |
| Sab0  | prior (inverse) scale matrix for the prior distribution                         |
| eta0  | prior degrees of freedom for the prior distribution                             |
| SS    | number of iterations                                                            |

## Value

|     |                  |
|-----|------------------|
| Z   | new value of Z   |
| Sab | new value of Sab |
| a   | new value of a   |

## Author(s)

lame authors

---

rbeta\_ab\_bip\_gibbs\_cpp

*Full bipartite Gibbs update for beta, a, b*


---

### Description

Single C++ function replacing the bipartite beta/a/b update block in lame.R

### Usage

```
rbeta_ab_bip_gibbs_cpp(
  Z,
  Xlist,
  UV_eff,
  a_current,
  b_current,
  s2,
  g_prior,
  va,
  vb,
  rvar,
  cvar
)
```

### Arguments

|           |                                                  |
|-----------|--------------------------------------------------|
| Z         | 3D array (nA x nB x T)                           |
| Xlist     | List of T arrays (nA x nB x p)                   |
| UV_eff    | nA x nB matrix ( $UGV'$ or $U*V'$ )              |
| a_current | Current row effects (length nA)                  |
| b_current | Current column effects (length nB)               |
| s2        | Dyadic variance                                  |
| g_prior   | G-prior parameter                                |
| va        | Row effect variance (diagonal element of Sab)    |
| vb        | Column effect variance (diagonal element of Sab) |
| rvar      | Whether to update row effects                    |
| cvar      | Whether to update column effects                 |

### Value

List with beta, a, b

rbeta\_ab\_fc

*Joint Gibbs update of regression and additive effects (single relation)***Description**

Draws jointly from the full conditional of the regression coefficients  $\beta$  together with the additive sender/receiver effects  $a, b$  for a single social-relations regression matrix. The within-dyad reciprocity covariance is whitened so every directed cell becomes a unit-variance Gaussian observation, the additive-effect prior  $N(0, S_{ab})$  is written through a square-root factor so a rank-deficient  $S_{ab}$  is handled without inverting it, and the complete joint Gaussian precision over  $(\beta, \text{factors})$  is assembled from cell-level sufficient statistics and sampled in one draw.

**Usage**

```
rbeta_ab_fc(
  Z,
  Sab,
  rho,
  X = NULL,
  s2 = 1,
  offset = 0,
  iv0 = NULL,
  m0 = NULL,
  g = length(Z)
)
```

**Arguments**

|                 |                                                                         |
|-----------------|-------------------------------------------------------------------------|
| $Z$             | $n \times n$ relational matrix (multiplicative effects already removed) |
| $S_{ab}$        | $2 \times 2$ covariance of the additive row/column effects              |
| $\rho$          | within-dyad (reciprocity) correlation                                   |
| $X$             | $n \times n \times p$ covariate design array                            |
| $s2$            | dyadic variance                                                         |
| $\text{offset}$ | matrix subtracted from $Z$ before sampling                              |
| $iv0$           | prior precision for $\beta$ ; a g-prior is used when NULL               |
| $m0$            | prior mean for $\beta$ ; zero when NULL                                 |
| $g$             | g-prior variance scale used when $iv0$ is NULL                          |

**Value**

|         |                         |
|---------|-------------------------|
| $\beta$ | regression coefficients |
| $a$     | additive row effects    |
| $b$     | additive column effects |

**Author(s)**

lame authors

---

|                 |                                                                                                    |
|-----------------|----------------------------------------------------------------------------------------------------|
| rbeta_ab_rep_fc | <i>Gibbs update of regression coefficients and additive effects for replicated relational data</i> |
|-----------------|----------------------------------------------------------------------------------------------------|

---

**Description**

Draws jointly from the full conditional distribution of the regression coefficients  $\beta$  together with the additive sender/receiver effects  $a$  and  $b$ , pooling the information contained in the replicate slices of a longitudinal design that share a common  $\beta$ ,  $a$  and  $b$ . The draw is obtained by forming the complete joint Gaussian posterior precision matrix over  $(\beta, a, b)$  from sufficient statistics accumulated across slices, after whitening the within-dyad correlation, and sampling from it.

**Usage**

`rbeta_ab_rep_fc(Z.T, Sab, rho, X.T, s2=1)`

**Arguments**

|                  |                                                                                                                                      |
|------------------|--------------------------------------------------------------------------------------------------------------------------------------|
| <code>Z.T</code> | $n \times n \times T$ array of latent relations with multiplicative effects already removed; the third margin indexes the replicates |
| <code>Sab</code> | $2 \times 2$ covariance matrix of the additive row/column effects                                                                    |
| <code>rho</code> | within-dyad (reciprocity) correlation                                                                                                |
| <code>X.T</code> | $n \times n \times p \times T$ design array                                                                                          |
| <code>s2</code>  | dyadic variance                                                                                                                      |

**Value**

|                   |                         |
|-------------------|-------------------------|
| <code>beta</code> | regression coefficients |
| <code>a</code>    | additive row effects    |
| <code>b</code>    | additive column effects |

**Author(s)**

lame authors

---

|              |                                                                       |
|--------------|-----------------------------------------------------------------------|
| read_log_lik | <i>Read the per-iteration log-lik matrix back from on-disk chunks</i> |
|--------------|-----------------------------------------------------------------------|

---

### Description

For fits run with `save_log_lik = "chunked"`, the per-iteration pointwise log-likelihood lives in per-column-chunk binary files instead of `fit$log_lik`. This helper reconstitutes the `[n_stored, n_obs]` matrix in memory by issuing one `readBin` per chunk. `loo.lame()` / `waic.lame()` call this transparently.

### Usage

```
read_log_lik(x)
```

### Arguments

|                |                                                                                                                                  |
|----------------|----------------------------------------------------------------------------------------------------------------------------------|
| <code>x</code> | A fitted <code>ame/lame</code> object with <code>\$log_lik_chunks</code> (i.e. fit with <code>save_log_lik = "chunked"</code> ). |
|----------------|----------------------------------------------------------------------------------------------------------------------------------|

### Value

The full `[n_stored, n_obs]` double matrix.

---

|                |                                                               |
|----------------|---------------------------------------------------------------|
| reconstruct_EZ | <i>Reconstruct EZ and UVPM matrices from AME model output</i> |
|----------------|---------------------------------------------------------------|

---

### Description

Helper functions to recover EZ (linear predictor) and UVPM (posterior mean of the multiplicative product) matrices. When the fit stores the quantity (UVPM on asymmetric fits, ULUPM on symmetric fits), the stored posterior mean is returned directly; otherwise it is reconstructed from the saved factors.

Note: EZ returns the linear predictor ( $\eta$ ), not the response:

- For Gaussian:  $EZ = \eta = \mu$  (identity link)
- For Poisson:  $EZ = \eta = \log(\lambda)$  (can be negative)
- For Binary:  $EZ = \eta = \text{probit inverse of } p$  (can be any real value) Use YPM for predictions on the response scale.

### Usage

```
reconstruct_EZ(fit, X = NULL)
```

```
reconstruct_UVPM(fit)
```

Arguments

|     |                                                          |
|-----|----------------------------------------------------------|
| fit | Fitted AME model object                                  |
| X   | Covariate array (optional, will use fit\$X if available) |

Details

Fits that carry the stored posterior mean (UVPM or, for symmetric fits, ULUPM) have it returned as-is; older fit objects without one are rebuilt from the posterior factor means.

Value

Reconstructed matrix

Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

---

|           |                                             |
|-----------|---------------------------------------------|
| reexports | <i>Objects exported from other packages</i> |
|-----------|---------------------------------------------|

---

Description

These objects are imported from other packages. Follow the links below to see their documentation.

**ggplot2** [autoplot](#)

---

|               |                                         |
|---------------|-----------------------------------------|
| residuals.ame | <i>Extract residuals from AME model</i> |
|---------------|-----------------------------------------|

---

Description

Computes residuals as the difference between observed values and fitted values. For type = "response", returns  $Y - \text{fitted}(\text{object})$ . For type = "pearson", returns response residuals scaled by the standard deviation implied by the family (e.g.,  $\sqrt{p(1-p)}$ ) for binary).

Usage

```
## S3 method for class 'ame'  
residuals(object, type = c("response", "pearson"), ...)
```

Arguments

|        |                                                                                            |
|--------|--------------------------------------------------------------------------------------------|
| object | Fitted AME model object (class "ame").                                                     |
| type   | Character; "response" (default) for raw residuals or "pearson" for standardized residuals. |
| ...    | Additional arguments (not used).                                                           |



**Value**

An  $n \times n$  matrix (unipartite) or  $nA \times nB$  matrix (bipartite) of residuals. Entries where the original data was NA remain NA.

**Author(s)**

Cassy Dorff, Shahryar Minhas, Tosin Salau

**See Also**

[fitted.ame](#), [predict.ame](#)

---

|                   |                                      |
|-------------------|--------------------------------------|
| residuals.ame_als | <i>Residuals from a fast AME fit</i> |
|-------------------|--------------------------------------|

---

**Description**

Returns residuals from an [ame\\_als](#) or [lame\\_als](#) fit.

**Usage**

```
## S3 method for class 'ame_als'
residuals(object, type = c("response", "working"), ...)
```

**Arguments**

|        |                                    |
|--------|------------------------------------|
| object | an <a href="#">ame_als</a> object. |
| type   | "response" (default) or "working". |
| ...    | ignored.                           |

**Details**

type = "response" (default) returns observed  $Y$  minus the response-scale fitted values, so `residuals()` reconciles with `fitted()`. type = "working" returns the Gaussian working-scale residuals the estimator actually minimised (identical to "response" for the normal family).

**Value**

A matrix (cross-sectional) or list of matrices (longitudinal).

---

|                |                                          |
|----------------|------------------------------------------|
| residuals.lame | <i>Extract residuals from LAME model</i> |
|----------------|------------------------------------------|

---

**Description**

Extract residuals from LAME model

**Usage**

```
## S3 method for class 'lame'  
residuals(object, type = c("response", "pearson"), ...)
```

**Arguments**

|        |                                             |
|--------|---------------------------------------------|
| object | Fitted LAME model                           |
| type   | Type of residuals ("response" or "pearson") |
| ...    | Additional arguments                        |

**Value**

List of residual matrices (one per time point)

---

|                   |                                                                    |
|-------------------|--------------------------------------------------------------------|
| rhat_dynamic_beta | <i>Multivariate split-R-hat for dynamic_beta coefficient paths</i> |
|-------------------|--------------------------------------------------------------------|

---

**Description**

Given one or more multi-chain lame fits whose \$BETA is [n\_iter, p, T], computes the multivariate R-hat per coefficient  $k$  treating the length- $T$  path as one multivariate observation per iteration.

**Usage**

```
rhat_dynamic_beta(fit_list, coefs = NULL)
```

**Arguments**

|          |                                                                                                                                              |
|----------|----------------------------------------------------------------------------------------------------------------------------------------------|
| fit_list | A list of fitted lame objects from lame_parallel(..., chains = K), or any ame_chain_list produced by re-running lame() with different seeds. |
| coefs    | Optional character vector of coefficient names to subset (matches dimnames(fit\$BETA)[[2]]).                                                 |

**Details**

For chain  $c$ , let  $\beta_t^{(c)} \in \mathbb{R}^T$  be the path. With  $m$  chains and  $n$  iterations per chain, define

$$W_k = \frac{1}{m} \sum_c S_c^{(k)}, \quad B_k = \frac{n}{m-1} \sum_c (\bar{\beta}_c^{(k)} - \bar{\beta}^{(k)})(\bar{\beta}_c^{(k)} - \bar{\beta}^{(k)})'$$

where  $S_c^{(k)}$  is the within-chain sample covariance of path  $k$  in chain  $c$ . Then  $V_k = ((n-1)/n)W_k + ((m+1)/(mn))B_k$  and  $\hat{R}_k^{mvt} = \sqrt{\lambda_{\max}(W_k^{-1}V_k)}$ . For nearly degenerate covariances we add a tiny ridge to  $W_k$ .

**Value**

Data frame with one row per coefficient: `coef`, `rhat_mvt`, `rhat_max_univariate`, `n_chains`, `n_iter_per_chain`, `n_periods`. `rhat_mvt` is the Brooks-Gelman multivariate statistic; `rhat_max_univariate` is the max over per-(k,t) split-R-hat values for comparison.

**Examples**

```
data(YX_bin_list)
# note: pass seed = to lame() -- an external set.seed() does not vary
# the sampler, so it would produce identical chains
fit_list <- lapply(c(1L, 2L), function(s) {
  lame(YX_bin_list$Y, YX_bin_list$X, family = "binary", R = 0,
        dynamic_beta = "dyad", seed = s,
        nscan = 60, burn = 15, odens = 5, verbose = FALSE)
})
rhat_dynamic_beta(fit_list)
```

rmvnorm

*Simulation from a multivariate normal distribution***Description**

Simulates a matrix where the rows are i.i.d. samples from a multivariate normal distribution

**Usage**

```
rmvnorm(n, mu, Sigma, Sigma.chol = NULL)
```

**Arguments**

|                         |                                 |
|-------------------------|---------------------------------|
| <code>n</code>          | sample size                     |
| <code>mu</code>         | multivariate mean vector        |
| <code>Sigma</code>      | covariance matrix               |
| <code>Sigma.chol</code> | Cholesky factorization of Sigma |

**Value**

a matrix with n rows

**Author(s)**

Cassy Dorff, Shahryar Minhas, Tosin Salau

---

|         |                                                                   |
|---------|-------------------------------------------------------------------|
| rrho_mh | <i>Metropolis-Hastings update for the within-dyad correlation</i> |
|---------|-------------------------------------------------------------------|

---

**Description**

Draws a new value of the dyadic correlation rho from its full conditional using a random-walk-style Metropolis-Hastings step. Each dyad’s pair of directed residuals is modelled as bivariate normal with unit variances (after scaling by the dyadic variance) and correlation rho; the proposal is a normal truncated to (-1, 1) and the acceptance ratio combines the bivariate-normal log-likelihood, an optional arc-sine prior, and the truncated-proposal normaliser.

**Usage**

rrho\_mh(Z, rho, s2 = 1, offset = 0, asp = NULL)

**Arguments**

|        |                                                                                                                     |
|--------|---------------------------------------------------------------------------------------------------------------------|
| Z      | n x n normal relational matrix.                                                                                     |
| rho    | current value of rho.                                                                                               |
| s2     | current value of the dyadic variance.                                                                               |
| offset | matrix matching Z; Z - offset is treated as dyadic noise (so it should absorb any additive/multiplicative effects). |
| asp    | logical; use an arc-sine prior (TRUE, the default when NULL) or a uniform prior (FALSE).                            |

**Value**

a new (scalar) value of rho.

**Author(s)**

lame authors

---

|        |                                         |
|--------|-----------------------------------------|
| rs2_fc | <i>Gibbs update for dyadic variance</i> |
|--------|-----------------------------------------|

---

**Description**

Draw the dyadic residual variance  $s2$  from its inverse-gamma full conditional. The residual matrix  $E = Z - \text{offset}$  is decorrelated within reciprocal dyad pairs and along the diagonal, and the pooled sum of squares (together with an optional scaled-inverse-chi-square prior) yields the posterior draw.

**Usage**

```
rs2_fc(Z, rho, offset = 0, nu0 = NULL, s20 = NULL)
```

**Arguments**

|        |                                                                                                                                                    |
|--------|----------------------------------------------------------------------------------------------------------------------------------------------------|
| Z      | n x n normal relational matrix                                                                                                                     |
| rho    | current within-dyad correlation                                                                                                                    |
| offset | matrix conformable with Z; $Z - \text{offset}$ is treated as pure dyadic noise (so it should carry the additive and multiplicative mean structure) |
| nu0    | prior degrees of freedom (defaults to 1)                                                                                                           |
| s20    | prior scale for $s2$ ; when NULL the empirical mean of the decorrelated squared residuals is used so the prior sits at the data scale              |

**Value**

a single draw of  $s2$

**Author(s)**

lame authors

---

|            |                                                                                    |
|------------|------------------------------------------------------------------------------------|
| rs2_rep_fc | <i>Full-conditional draw of the dyadic variance for replicated relational data</i> |
|------------|------------------------------------------------------------------------------------|

---

**Description**

Samples the dyadic variance  $s2$  from its Gibbs full conditional when the residual cube stacks several independent replicate networks that share a common within-dyad correlation  $\rho$ . Each ordered dyad pair is whitened by the symmetric inverse square root of the  $2 \times 2$  correlation matrix and the pooled whitened sum of squares drives an inverse-gamma draw.

**Usage**

```
rs2_rep_fc(E.T, rho)
```

Arguments

|     |                                                                                                                                         |
|-----|-----------------------------------------------------------------------------------------------------------------------------------------|
| E.T | numeric array of dimension $n \times n \times N$ holding the residual matrices along the third margin (one square slice per replicate). |
| rho | current value of the within-dyad correlation.                                                                                           |

Value

a single numeric draw of  $s_2$ .

Author(s)

lame authors

---

|         |                                                     |
|---------|-----------------------------------------------------|
| rSab_fc | <i>Gibbs update for additive effects covariance</i> |
|---------|-----------------------------------------------------|

---

Description

Gibbs sampling for the covariance matrix of additive row and column effects in the AME model. This function implements the inverse-Wishart posterior update for the covariance matrix  $Sab$ .

Usage

```
rSab_fc(a, b, Sab0=NULL, eta0=NULL, rvar=TRUE, cvar=TRUE, symmetric=FALSE)
```

Arguments

|           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|-----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| a         | vector of row random effects (additive sender effects)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| b         | vector of column random effects (additive receiver effects)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Sab0      | prior scale matrix. <b>Convention (Hoff/amen):</b> $Sab0$ is passed <i>raw</i> ; the inverse-Wishart scale used internally is $\eta_0 \cdot Sab0$ , so the prior mean of $Sab$ is $\eta_0 Sab0 / (\eta_0 - 3) \approx Sab0$ and the prior mode is $\eta_0 Sab0 / (\eta_0 + 3)$ . Every call site in the package ( <code>ame()</code> unipartite and bipartite, <code>lame()</code> unipartite and bipartite, and the <code>raSab_bin/cbin/frn</code> joint updates) passes $Sab0$ raw under this same convention, so a given prior $\$Sab0$ means the same prior everywhere. Default is <code>diag(2)</code> (weakly informative). |
| eta0      | prior degrees of freedom for the prior distribution. Default is 4, which is the minimum for a proper prior with 2x2 matrix.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| rvar      | logical: should row variance be updated? (default TRUE)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| cvar      | logical: should column variance be updated? (default TRUE)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| symmetric | logical: is this a symmetric network? (default FALSE)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |

### Details

The function implements different update strategies:

- Full update: When both rvar and cvar are TRUE, updates the full 2x2 covariance matrix using an inverse-Wishart distribution
- Row variance only: When only rvar is TRUE, updates only Sab[1,1]
- Column variance only: When only cvar is TRUE, updates only Sab[2,2]
- Symmetric case: When symmetric is TRUE, draws a single shared variance for the row and column effects (inverse-gamma update) with zero covariance

### Value

Updated covariance matrix Sab (2x2 matrix with variances on diagonal and covariance off-diagonal)

### Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

---

rSuv\_fc

*Gibbs update for multiplicative effects covariance*


---

### Description

Draws the covariance matrix of the stacked multiplicative row/column effects  $[U, V]$  from its full conditional inverse-Wishart distribution in the AME model.

### Usage

```
rSuv_fc(U, V, Suv0=NULL, kappa0=NULL)
```

### Arguments

|        |                                                                                                                  |
|--------|------------------------------------------------------------------------------------------------------------------|
| U      | matrix of multiplicative row effects (n x R).                                                                    |
| V      | matrix of multiplicative column effects (n x R).                                                                 |
| Suv0   | prior scale matrix (2R x 2R). Defaults to the identity, a weakly informative choice.                             |
| kappa0 | prior degrees of freedom. Defaults to 2 + 2R, the smallest value giving a proper prior for a 2R x 2R covariance. |

### Details

Stacking the effects columnwise as  $W = [U, V]$ , the conjugate inverse-Wishart update combines the prior scale  $\text{kappa0} * \text{Suv0}$  with the residual cross-product  $\text{crossprod}(W)$  and adds the n observed rows to the degrees of freedom. A draw from the inverse Wishart is obtained by drawing from the Wishart with the inverted scale matrix (via `rwish`) and inverting the result.

**Value**

The sampled  $2R \times 2R$  covariance matrix for  $[U, V]$ : the leading  $R \times R$  block is the covariance of  $U$ , the trailing  $R \times R$  block is the covariance of  $V$ , and the off-diagonal blocks are the  $U$ - $V$  cross-covariances.

**Author(s)**

lame authors

---

|                      |                                                                                |
|----------------------|--------------------------------------------------------------------------------|
| rtnorm_interval_logp | <i>Exact truncated-normal draw on (lb, ub) via the log.p-scale inverse CDF</i> |
|----------------------|--------------------------------------------------------------------------------|

---

**Description**

Draws  $z \sim N(ez, 1)$  truncated to  $(lb, ub)$  for each cell, working entirely on the log-probability scale in the tail that contains the truncation interval. This stays exact for arbitrarily extreme  $ez$  / bounds (log-scale  $pnorm/qnorm$  are accurate to  $|ez|$  of several hundred), so no probability clamp is needed. Infinite bounds reduce to the one-sided case automatically.

**Usage**

```
rtnorm_interval_logp(ez, lb, ub)
```

**Arguments**

|    |                                        |
|----|----------------------------------------|
| ez | vector of conditional means.           |
| lb | lower bounds (recycled to length(ez)). |
| ub | upper bounds (recycled to length(ez)). |

**Value**

vector of truncated-normal draws, same length as ez.

**Author(s)**

Cassy Dorff, Shahryar Minhas, Tosin Salau



---

rUV\_dynamic\_bip\_fc\_cpp

*Bipartite dynamic UV Gibbs update*


---

### Description

Replaces the nested R loops for bipartite dynamic\_uv in lame.R. Uses direct 2x2 inverse formula for common R=2 case.

### Usage

```
rUV_dynamic_bip_fc_cpp(U_cube, V_cube, E, G, rho_uv, sigma_uv, s2)
```

### Arguments

|          |                                     |
|----------|-------------------------------------|
| U_cube   | 3D array (nA x RA x T)              |
| V_cube   | 3D array (nB x RB x T)              |
| E        | 3D array of residuals (nA x nB x T) |
| G        | Interaction matrix (RA x RB)        |
| rho_uv   | AR(1) persistence parameter         |
| sigma_uv | Innovation standard deviation       |
| s2       | Dyadic variance                     |

### Value

List with updated U\_cube, V\_cube

---

rUV\_dynamic\_fc

*Gibbs sampling of dynamic U and V with AR(1) evolution*


---

### Description

Updates latent factor positions U and V that evolve over time according to an AR(1) process:  $u_{i,t} = \rho * u_{i,t-1} + \epsilon_{i,t}$

### Usage

```
rUV_dynamic_fc(U, V, ET, rho_uv, sigma_uv, s2, shrink=TRUE, symmetric=FALSE)
```

**Arguments**

|           |                                                     |
|-----------|-----------------------------------------------------|
| U         | 3D array of current U positions (n x R x T)         |
| V         | 3D array of current V positions (n x R x T)         |
| ET        | 3D array of residuals (n x n x T)                   |
| rho_uv    | AR(1) autoregressive parameter for latent positions |
| sigma_uv  | Innovation standard deviation for latent positions  |
| s2        | dyadic variance                                     |
| shrink    | whether to apply shrinkage (default TRUE)           |
| symmetric | whether the network is symmetric (default FALSE)    |

**Value**

list with updated U and V arrays

**Author(s)**

Cassy Dorff, Shahryar Minhas, Tosin Salau

---

|                    |                                                            |
|--------------------|------------------------------------------------------------|
| rUV_dynamic_fc_cpp | <i>Update dynamic latent positions using AR(1) process</i> |
|--------------------|------------------------------------------------------------|

---

**Description**

Update dynamic latent positions using AR(1) process

**Usage**

```
rUV_dynamic_fc_cpp(
  U_current,
  V_current,
  ET,
  rho_uv,
  sigma_uv,
  s2,
  shrink,
  symmetric
)
```

**Arguments**

|           |                                                     |
|-----------|-----------------------------------------------------|
| U_current | Current 3D array of U positions (n x R x T)         |
| V_current | Current 3D array of V positions (n x R x T)         |
| ET        | 3D array of residuals (n x n x T)                   |
| rho_uv    | AR(1) autoregressive parameter for latent positions |

|           |                                                    |
|-----------|----------------------------------------------------|
| sigma_uv  | Innovation standard deviation for latent positions |
| s2        | Dyadic variance                                    |
| shrink    | Whether to apply shrinkage                         |
| symmetric | Whether network is symmetric                       |

**Value**

List with updated U and V arrays

---

|                     |                                                                   |
|---------------------|-------------------------------------------------------------------|
| rUV_dynamic_snap_fc | <i>Gibbs sampling of dynamic U and V with snap-shift dynamics</i> |
|---------------------|-------------------------------------------------------------------|

---

**Description**

Like rUV\_dynamic\_fc but lets each actor's latent position either drift under the AR(1) prior or jump under a diffuse  $N(0, \kappa^2)$  snap prior, chosen per actor-period by a Gaussian log-marginal model selection.

**Usage**

```
rUV_dynamic_snap_fc(
  U,
  V,
  ET,
  rho_uv,
  sigma_uv,
  s2,
  kappa,
  pi_snap,
  delta_u_current = NULL,
  delta_v_current = NULL,
  shrink = TRUE,
  symmetric = FALSE
)
```

**Arguments**

|          |                                                    |
|----------|----------------------------------------------------|
| U        | 3D array of current U positions (n x R x T)        |
| V        | 3D array of current V positions (n x R x T)        |
| ET       | 3D array of residuals (n x n x T)                  |
| rho_uv   | AR(1) autoregressive parameter for the drift prior |
| sigma_uv | Innovation standard deviation for the drift prior  |
| s2       | dyadic variance                                    |
| kappa    | diffuse snap-prior standard deviation              |

|                 |                                                                        |
|-----------------|------------------------------------------------------------------------|
| pi_snap         | prior snap probability                                                 |
| delta_u_current | current sender-side snap indicators. If NULL, a zero matrix is used.   |
| delta_v_current | current receiver-side snap indicators. If NULL, a zero matrix is used. |
| shrink          | whether to apply shrinkage (default TRUE)                              |
| symmetric       | whether the network is symmetric (default FALSE)                       |

**Value**

list with updated U, V arrays and delta\_u, delta\_v snap indicators

**Author(s)**

Cassy Dorff, Shahryar Minhas, Tosin Salau

---

rUV\_dynamic\_snap\_fc\_cpp

*Update dynamic latent positions with snap-shift model selection*

---

**Description**

Like rUV\_dynamic\_fc\_cpp but, for  $t > 0$ , chooses per actor between an AR(1) drift prior and a diffuse  $N(0, \kappa^2 I)$  snap prior via a Gaussian log-marginal-likelihood model selection, drawing a Bernoulli snap indicator delta and sampling the latent position from the selected posterior.

**Usage**

```
rUV_dynamic_snap_fc_cpp(
  U_current,
  V_current,
  ET,
  rho_uv,
  sigma_uv,
  s2,
  kappa,
  pi_snap,
  delta_u_current,
  delta_v_current,
  shrink,
  symmetric
)
```

**Arguments**

|                 |                                                                        |
|-----------------|------------------------------------------------------------------------|
| U_current       | Current 3D array of U positions (n x R x T)                            |
| V_current       | Current 3D array of V positions (n x R x T)                            |
| ET              | 3D array of residuals (n x n x T)                                      |
| rho_uv          | AR(1) autoregressive parameter for the drift prior                     |
| sigma_uv        | Innovation standard deviation for the drift prior                      |
| s2              | Dyadic variance                                                        |
| kappa           | Diffuse snap-prior standard deviation ( $\kappa^2 \gg \sigma_{uv}^2$ ) |
| pi_snap         | Prior snap probability                                                 |
| delta_u_current | Current sender-side snap indicators from the previous sweep            |
| delta_v_current | Current receiver-side snap indicators from the previous sweep          |
| shrink          | Whether to apply shrinkage                                             |
| symmetric       | Whether network is symmetric                                           |

**Value**

List with updated U, V arrays and delta\_u, delta\_v snap indicators

---

|                  |                                                                                    |
|------------------|------------------------------------------------------------------------------------|
| rUV_dynamic_t_fc | <i>Gibbs sampling of dynamic U and V with heavy-tailed (Student-t) innovations</i> |
|------------------|------------------------------------------------------------------------------------|

---

**Description**

Like rUV\_dynamic\_fc but the AR(1) innovations are Student-t via a scale-mixture of normals, a continuous heavy-tailed alternative to snap-shift.

**Usage**

```
rUV_dynamic_t_fc(
  U,
  V,
  ET,
  rho_uv,
  sigma_uv,
  s2,
  nu,
  lambda_u = NULL,
  lambda_v = NULL,
  shrink = TRUE,
  symmetric = FALSE
)
```

**Arguments**

|           |                                                  |
|-----------|--------------------------------------------------|
| U         | 3D array of current U positions (n x R x T)      |
| V         | 3D array of current V positions (n x R x T)      |
| ET        | 3D array of residuals (n x n x T)                |
| rho_uv    | AR(1) autoregressive parameter                   |
| sigma_uv  | Innovation scale                                 |
| s2        | dyadic variance                                  |
| nu        | Student-t degrees of freedom                     |
| lambda_u  | current local scales for U (n x T)               |
| lambda_v  | current local scales for V (n x T)               |
| shrink    | whether to apply shrinkage (default TRUE)        |
| symmetric | whether the network is symmetric (default FALSE) |

**Value**

list with updated U, V arrays and lambda\_u, lambda\_v local scales

**Author(s)**

Cassy Dorff, Shahryar Minhas, Tosin Salau

---

|                      |                                                                                        |
|----------------------|----------------------------------------------------------------------------------------|
| rUV_dynamic_t_fc_cpp | <i>Update dynamic latent positions with heavy-tailed (Student-t) AR(1) innovations</i> |
|----------------------|----------------------------------------------------------------------------------------|

---

**Description**

Like rUV\_dynamic\_fc\_cpp but each AR(1) innovation is Student-t rather than Gaussian, via a scale-mixture: the innovation for  $u[t, i]$  has variance  $\sigma^2 / \lambda[t, i]$  with  $\lambda[t, i]$  distributed as  $\text{Gamma}(\nu/2, \nu/2)$ . Provides a continuous heavy-tailed alternative to the discrete snap-shift model.

**Usage**

```
rUV_dynamic_t_fc_cpp(
  U_current,
  V_current,
  ET,
  rho_uv,
  sigma_uv,
  s2,
  nu,
  lambda_u,
  lambda_v,
  shrink,
  symmetric
)
```

**Arguments**

|           |                                             |
|-----------|---------------------------------------------|
| U_current | Current 3D array of U positions (n x R x T) |
| V_current | Current 3D array of V positions (n x R x T) |
| ET        | 3D array of residuals (n x n x T)           |
| rho_uv    | AR(1) autoregressive parameter              |
| sigma_uv  | Innovation scale                            |
| s2        | Dyadic variance                             |
| nu        | Student-t degrees of freedom                |
| lambda_u  | Current local scales for U (n x T)          |
| lambda_v  | Current local scales for V (n x T)          |
| shrink    | Whether to apply shrinkage                  |
| symmetric | Whether network is symmetric                |

**Value**

List with updated U, V arrays and lambda\_u, lambda\_v local scales

---

|        |                                  |
|--------|----------------------------------|
| rUV_fc | <i>Gibbs sampling of U and V</i> |
|--------|----------------------------------|

---

**Description**

A Gibbs sampler for updating the multiplicative effect matrices U and V

**Usage**

```
rUV_fc(Z, U, V, Suv, rho, s2 = 1, offset = 0)
```

**Arguments**

|        |                                                                                                                                                                                                           |
|--------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Z      | n X n normal relational matrix                                                                                                                                                                            |
| U      | current value of U                                                                                                                                                                                        |
| V      | current value of V                                                                                                                                                                                        |
| Suv    | covariance of (U V)                                                                                                                                                                                       |
| rho    | dyadic correlation                                                                                                                                                                                        |
| s2     | dyadic variance                                                                                                                                                                                           |
| offset | a matrix of the same dimension as Z. It is assumed that Z-offset is equal to the multiplicative effects plus dyadic noise, so the offset should contain any additive effects (such as $X\beta(a,b,"+")$ ) |

**Value**

|   |                  |
|---|------------------|
| U | a new value of U |
| V | a new value of V |

**Author(s)**

lame authors

---

|            |                                                                  |
|------------|------------------------------------------------------------------|
| rUV_rep_fc | <i>Gibbs sampling of U and V from replicated relational data</i> |
|------------|------------------------------------------------------------------|

---

**Description**

Draws the multiplicative-effect matrices U and V from their full conditional distributions, pooling information across the replicate slices of a residual array. Each factor column is updated in turn from its Gaussian full conditional, optionally under a hierarchical shrinkage prior on the stacked (U, V) rows.

**Usage**

rUV\_rep\_fc(E.T,U,V,rho,s2=1,shrink=TRUE)

**Arguments**

|        |                                                                                                                              |
|--------|------------------------------------------------------------------------------------------------------------------------------|
| E.T    | Array of square residual relational matrices (additive effects and covariates removed). The third margin indexes replicates. |
| U      | current value of U                                                                                                           |
| V      | current value of V                                                                                                           |
| rho    | dyadic correlation                                                                                                           |
| s2     | dyadic variance                                                                                                              |
| shrink | adaptively shrink the factors with a hierarchical prior                                                                      |

**Value**

|   |                  |
|---|------------------|
| U | a new value of U |
| V | a new value of V |

**Author(s)**

lame authors



---

|            |                                  |
|------------|----------------------------------|
| rUV_sym_fc | <i>Gibbs sampling of U and V</i> |
|------------|----------------------------------|

---

**Description**

A Gibbs sampler for updating the multiplicative effect matrices U and V in the symmetric case. In this case  $U\%*\%t(V)$  is symmetric, so this is parameterized as  $V=U\%*\%L$  where L is the diagonal matrix of eigenvalues of  $U\%*\%t(V)$ .

**Usage**

```
rUV_sym_fc(E, U, V, s2 = 1, shrink=TRUE)
```

**Arguments**

|        |                                                         |
|--------|---------------------------------------------------------|
| E      | square residual relational matrix                       |
| U      | current value of U                                      |
| V      | current value of V                                      |
| s2     | dyadic variance                                         |
| shrink | adaptively shrink the factors with a hierarchical prior |

**Value**

|   |                  |
|---|------------------|
| U | a new value of U |
| V | a new value of V |

**Author(s)**

Cassy Dorff, Shahryar Minhas, Tosin Salau

**Examples**

```
U0<-matrix(rnorm(30,2),30,2) ; V0<-U0%*%diag(c(3,-2))
E<- U0%*%t(V0) + matrix(rnorm(30^2),30,30)
rUV_sym_fc
```

rwish

*Simulation from a Wishart distribution*

---

**Description**

Simulates a random Wishart-distributed matrix

**Usage**

```
rwish(S0, nu = dim(S0)[1] + 2)
```

**Arguments**

|    |                            |
|----|----------------------------|
| S0 | a positive definite matrix |
| nu | a positive integer         |

**Value**

a positive definite matrix

**Author(s)**

lame authors

**Examples**

```
## The expectation is S0*nu

S0<-rwish(diag(3))

SS<-matrix(0,3,3)
for(s in 1:1000) { SS<-SS+rwish(S0,5) }

SS/s

S0*5
```

---

rZ\_bin\_bip\_batch\_cpp     *Batch binary Z sampling across all time periods (bipartite, rho=0)*

---

### Description

Vectorized probit update for bipartite binary networks without dyadic correlation.

### Usage

```
rZ_bin_bip_batch_cpp(Z, EZ, Y)
```

### Arguments

|    |                                           |
|----|-------------------------------------------|
| Z  | 3D array of latent values (nA x nB x T)   |
| EZ | 3D array of expected values (nA x nB x T) |
| Y  | 3D array of observed values (nA x nB x T) |

### Value

Updated Z array

---

rZ\_bin\_fc     *Draw latent Z for the binary probit model*

---

### Description

Gibbs / Metropolis update of the latent normal matrix Z underlying a binary relational matrix Y. Off-diagonal entries are drawn from the dyadic full conditional  $Z_{ij} \mid Z_{ji} \sim N(EZ_{ij} + \rho(Z_{ji} - EZ_{ji}), 1 - \rho^2)$  truncated to the half-line implied by  $Y_{ij}$  (positive when  $Y_{ij} = 1$ , negative when  $Y_{ij} = 0$ , unrestricted when  $Y_{ij}$  is missing). A correlated dyad-level Metropolis proposal is then attempted to improve mixing, and the diagonal is refreshed from its unconstrained conditional.

### Usage

```
rZ_bin_fc(Z, EZ, rho, Y)
```

### Arguments

|     |                                         |
|-----|-----------------------------------------|
| Z   | a square matrix, the current value of Z |
| EZ  | expected value of Z                     |
| rho | dyadic correlation                      |
| Y   | square binary relational matrix         |

**Value**

a square matrix, the new value of Z

**Author(s)**

lame authors

---

|                |                                                                           |
|----------------|---------------------------------------------------------------------------|
| rZ_cbin_bip_fc | <i>Sample Z under bipartite censored binary nominations (rectangular)</i> |
|----------------|---------------------------------------------------------------------------|

---

**Description**

Rectangular analogue of [rZ\\_cbin\\_fc](#). Row-wise constraints:  $Y_{ij} = 1 \Rightarrow Z_{ij} > 0$ ;  $Y_{ij} = 0 \ \& \ odobs_i < odmax_i \Rightarrow Z_{ij} < 0$ ; nominated alters dominate non-nominated alters within the row. With  $\rho = 0$  there is no reciprocity term.

**Usage**

rZ\_cbin\_bip\_fc(Z, EZ, Y, odmax, odobs)

**Arguments**

- Z current rectangular latent matrix (nA x nB).
- EZ expected value (nA x nB).
- Y observed 0/1 matrix (nA x nB); NA entries resampled from the unconstrained prior.
- odmax row-wise maximum nominations (length nA or scalar).
- odobs row-wise observed outdegree (length nA).

**Value**

updated nA x nB latent matrix.

**Author(s)**

Cassy Dorff, Shahryar Minhas, Tosin Salau

rZ\_cbin\_fc

*Draw latent Z for censored-binary nomination data***Description**

Gibbs refresh of the latent normal matrix  $Z$  for the censored-binary (cbin) family, where each actor emits a capped set of binary nominations. Within every sending row the update honours three order constraints: a nominated tie has a positive latent value, every nominated tie dominates every non-nominated tie, and a non-nominated tie in a row that has not spent its full nomination budget ( $\text{odobs} < \text{odmax}$ ) is held below zero. Reciprocal cells are coupled through the dyadic correlation  $\rho$ ; the self-loop diagonal and any missing cells are redrawn from their unconstrained conditionals.

**Usage**

```
rZ_cbin_fc(Z, EZ, rho, Y, odmax, odobs)
```

**Arguments**

|                |                                                                                 |
|----------------|---------------------------------------------------------------------------------|
| $Z$            | current latent matrix (square).                                                 |
| $EZ$           | conditional mean of $Z$ .                                                       |
| $\rho$         | dyadic (within-dyad) correlation.                                               |
| $Y$            | observed nomination matrix, entries in $\{0, 1\}$ with NA for unobserved cells. |
| $\text{odmax}$ | nomination cap, a scalar or length-nrow( $Z$ ) vector.                          |
| $\text{odobs}$ | observed out-degree per actor.                                                  |

**Value**

the updated latent matrix, same shape and dimnames as  $Z$ .

**Author(s)**

lame authors

rZ\_frnbip\_fc

*Sample Z under bipartite fixed-rank nominations (rectangular)***Description**

Rectangular analogue of [rZ\\_frnbip\\_fc](#). Row-wise rank constraints: ranked nominees are positive and ordered by rank; non-nominees fall below all ranked cells in the row (and below 0 when the row is unsaturated). With  $\rho = 0$  the unipartite triangle coupling drops out.

**Usage**

```
rZ_frnbip_fc(Z, EZ, Y, YL, odmax, odobs)
```

Arguments

|       |                                                                         |
|-------|-------------------------------------------------------------------------|
| Z     | current rectangular latent matrix (nA x nB).                            |
| EZ    | expected value (nA x nB).                                               |
| Y     | observed rank matrix (nA x nB); 0 = unranked, 1..ncol(YL) = rank order. |
| YL    | per-row ranked-receiver list (nA x max_rank).                           |
| odmax | row-wise max nominations.                                               |
| odobs | row-wise observed outdegree.                                            |

Details

**Monotonicity convention (important for simulation).** The sampler enforces *higher Y -> higher Z*: when  $Y[i, j] > Y[i, k]$ , the corresponding latent values satisfy  $Z[i, j] > Z[i, k]$ . When simulating data for recovery tests, build Y via  $\text{rank}(Z[i, :])$  (low rank = small Y), not  $\text{rank}(-Z[i, :])$ . the inverted convention identifies the negative of the true beta.

Value

updated nA x nB latent matrix.

Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

---

|         |                                                                |
|---------|----------------------------------------------------------------|
| rZ_frnc | <i>Draw the latent Z matrix for fixed-rank-nomination data</i> |
|---------|----------------------------------------------------------------|

---

Description

Gibbs update of the latent sociomatrix Z for a fixed-rank-nomination (FRN) outcome. Each row's latent values are drawn from truncated normals whose bounds encode three rank constraints: nominated ties outrank non-nominations, higher observed ranks map to larger latents, and a non-nomination made with spare out-degree capacity must stay negative.

Usage

rZ\_frnc(Z, EZ, rho, Y, YL, odmax, odobs)

Arguments

|     |                                                                                          |
|-----|------------------------------------------------------------------------------------------|
| Z   | current latent sociomatrix (square).                                                     |
| EZ  | conditional mean matrix for Z.                                                           |
| rho | within-dyad correlation.                                                                 |
| Y   | square matrix of observed ranked nominations (0 = no tie, NA on the diagonal / missing). |

|       |                                                                                                                    |
|-------|--------------------------------------------------------------------------------------------------------------------|
| YL    | matrix whose r-th column gives, per row, the column index of the individual holding rank r (ascending preference). |
| odmax | scalar or per-row maximum number of nominations allowed.                                                           |
| odobs | per-row observed out-degree.                                                                                       |

Details

The constraints realised are (1)  $Y[i, j] > Y[i, k]$  implies  $Z[i, j] > Z[i, k]$ , (2)  $Y[i, j] > 0$  implies  $Z[i, j] > 0$ , and (3)  $Y[i, j] == 0$  with  $odobs[i] < odmax[i]$  implies  $Z[i, j] < 0$ .

Value

the updated square latent matrix Z.

Author(s)

lame authors

---

|                  |                                                        |
|------------------|--------------------------------------------------------|
| rZ_nrm_batch_cpp | <i>Batch normal Z sampling across all time periods</i> |
|------------------|--------------------------------------------------------|

---

Description

Replaces the per-time-period R loop with a single C++ call that loops internally, reducing R-to-C++ transition overhead.

Usage

rZ\_nrm\_batch\_cpp(Z, EZ, rho, s2, Y)

Arguments

|     |                                         |
|-----|-----------------------------------------|
| Z   | 3D array of latent values (n x n x T)   |
| EZ  | 3D array of expected values (n x n x T) |
| rho | Dyadic correlation parameter            |
| s2  | Dyadic variance                         |
| Y   | 3D array of observed values (n x n x T) |

Value

List with updated Z and E\_nrm (residuals)

---

|           |                                                      |
|-----------|------------------------------------------------------|
| rZ_nrm_fc | <i>Simulate missing values in a normal AME model</i> |
|-----------|------------------------------------------------------|

---

**Description**

Simulates missing values of a sociomatrix under a normal AME model

**Usage**

```
rZ_nrm_fc(Z, EZ, rho, s2, Y)
```

**Arguments**

|     |                                         |
|-----|-----------------------------------------|
| Z   | a square matrix, the current value of Z |
| EZ  | expected value of Z                     |
| rho | dyadic correlation                      |
| s2  | dyadic variance                         |
| Y   | square relational matrix                |

**Value**

a square matrix, equal to Y at non-missing values

**Author(s)**

Cassy Dorff, Shahryar Minhas, Tosin Salau

---

|               |                                                            |
|---------------|------------------------------------------------------------|
| rZ_ord_bip_fc | <i>Sample Z under bipartite ordinal data (rectangular)</i> |
|---------------|------------------------------------------------------------|

---

**Description**

Rectangular analogue of [rZ\\_ord\\_fc](#). Cutpoints are data-induced (the boundary between rank  $w$  and rank  $w+1$  is the maximum  $Z$  in rank  $w$  and minimum  $Z$  in rank  $w+1$ ), matching the existing unipartite convention. With  $\rho = 0$  in bipartite, every cell at rank  $w$  is drawn independently from a truncated normal centered at  $EZ$ .

**Usage**

```
rZ_ord_bip_fc(Z, EZ, Y)
```

**Arguments**

|    |                                                         |
|----|---------------------------------------------------------|
| Z  | current rectangular latent matrix ( $n_A \times n_B$ ). |
| EZ | expected value ( $n_A \times n_B$ ).                    |
| Y  | observed ordinal matrix ( $n_A \times n_B$ ).           |



**Value**

updated nA x nB latent matrix.

**Author(s)**

Cassy Dorff, Shahryar Minhas, Tosin Salau

---

|                    |                                                                     |
|--------------------|---------------------------------------------------------------------|
| rZ_ord_explicit_fc | <i>Sample Z given explicit cutpoints alpha (asymmetric ordinal)</i> |
|--------------------|---------------------------------------------------------------------|

---

**Description**

Rectangular / square truncated-normal sample on observed cells. This is the explicit-cutpoint version of `rZ_ord_fc`, parameterised by the explicit alpha vector rather than deriving cutpoints from Z order statistics.

**Usage**

```
rZ_ord_explicit_fc(Z, EZ, Y_int, alpha)
```

**Arguments**

|       |                                             |
|-------|---------------------------------------------|
| Z     | current latent matrix                       |
| EZ    | expected value of Z (linear predictor)      |
| Y_int | integer-recoded ordinal Y (1..K)            |
| alpha | length-(K-1) cutpoints with $\alpha[1] = 0$ |

**Value**

updated Z

---

|           |                                                            |
|-----------|------------------------------------------------------------|
| rZ_ord_fc | <i>Full-conditional latent draw for the ordinal family</i> |
|-----------|------------------------------------------------------------|

---

**Description**

Refreshes the latent sociomatrix Z for an ordinal outcome. The observed ordinal categories in Y impose only rank information on Z: every latent value tied to category  $c$  must sit above all latent values of the next-lower category and below all latent values of the next-higher category. Within that rank-implied window each entry is redrawn from its dyadic full conditional, a truncated normal whose mean borrows the transpose partner through the within-dyad correlation  $\rho$  and whose variance is  $1 - \rho^2$ . Missing dyads carry no rank constraint and are drawn from the untruncated conditional. The diagonal is nuisance and is refreshed from an independent normal.

**Usage**

rZ\_ord\_fc(Z, EZ, rho, Y)

**Arguments**

- Z square latent matrix, current state.
- EZ square matrix of latent means.
- rho scalar within-dyad correlation.
- Y square matrix of ordinal outcomes (may contain NA).

**Value**

the updated square latent matrix Z.

**Author(s)**

lame authors

---

|                                                                             |
|-----------------------------------------------------------------------------|
| rZ_ord_sym_explicit_fc                                                      |
| <i>Symmetric ordinal Z sample given explicit cutpoints (R &gt;= 0 safe)</i> |

---

**Description**

Mirror image of [rZ\\_ord\\_sym\\_fc](#) (variance 1 on the upper triangle, mirrored to the lower) parameterised by an explicit alpha vector instead of data-induced cutpoints.

**Usage**

rZ\_ord\_sym\_explicit\_fc(Z, EZ, Y\_int, alpha)

**Arguments**

- Z current symmetric latent matrix
- EZ expected value of Z
- Y\_int integer ordinal Y (symmetric)
- alpha length-(K-1) cutpoints with alpha[1] = 0

**Value**

updated symmetric Z (diagonal sampled from unconstrained prior)

rZ\_ord\_sym\_fc

*Sample Z under symmetric ordinal data (square symmetric matrix)***Description**

Symmetric-Z analogue of [rZ\\_ord\\_fc](#): each unordered actor pair carries one latent value ( $Z[i, j] = Z[j, i]$ ) drawn from a truncated normal with mean equal to the average linear predictor ( $EZ_{ij} + EZ_{ji} / 2$ ) and variance 1 (the model's conditional). The lower triangle is mirrored after the upper-triangle draws so the full matrix is exactly symmetric at every sweep.

**Usage**

```
rZ_ord_sym_fc(Z, EZ, Y)
```

**Arguments**

**Z** current symmetric latent matrix ( $n \times n$ ,  $Z = t(Z)$ ).

**EZ** expected value of Z (regression + additive + multiplicative contributions); can be asymmetric, the helper averages the two directed contributions.

**Y** observed symmetric ordinal matrix ( $n \times n$ ,  $Y = t(Y)$ ); diagonal is ignored.

**Value**

updated symmetric  $n \times n$  latent matrix; the diagonal is refreshed with unconstrained normal draws around `diag(EZ)` so downstream samplers never see missing values.

**Author(s)**

Cassy Dorff, Shahryar Minhas, Tosin Salau

rZ\_pois\_bip\_fc

*Sample Z under bipartite Poisson (rectangular MH step)***Description**

Rectangular analogue of [rZ\\_pois\\_fc](#). Each  $(i, j)$  cell is updated independently with a Metropolis-Hastings step on the Poisson log-link; there is no upper/lower-triangle coupling and no diagonal because the bipartite Y is  $n_A \times n_B$  with disjoint row and column actor sets.

**Usage**

```
rZ_pois_bip_fc(Z, EZ, s2, Y, log_exposure = 0)
```

**Arguments**

|              |                                                                                           |
|--------------|-------------------------------------------------------------------------------------------|
| Z            | current rectangular latent matrix (nA x nB).                                              |
| EZ           | expected value (regression + additive + multiplicative effects), nA x nB.                 |
| s2           | dyadic variance (proposal scale on the latent log-mean).                                  |
| Y            | observed count matrix (nA x nB); NA entries are resampled from the prior.                 |
| log_exposure | optional per-period log-exposure offset (scalar or matrix conformable with Y). Default 0. |

**Value**

updated nA x nB latent matrix.

**Author(s)**

Cassy Dorff, Shahryar Minhas, Tosin Salau

---

|            |                                                                |
|------------|----------------------------------------------------------------|
| rZ_pois_fc | <i>Gibbs update for latent variable in a Poisson AME model</i> |
|------------|----------------------------------------------------------------|

---

**Description**

Updates the latent variable Z in a Poisson AME model using a Metropolis-Hastings step. The model assumes  $y_{\{i,j\}} \sim \text{Poisson}(\exp(z_{\{i,j\}}))$  where  $z_{\{i,j\}}$  is the latent variable representing the log mean.

**Usage**

rZ\_pois\_fc(Z, EZ, rho, s2, Y)

**Arguments**

|     |                                                           |
|-----|-----------------------------------------------------------|
| Z   | a square matrix, the current value of the latent variable |
| EZ  | expected value of Z (regression effects + random effects) |
| rho | dyadic correlation                                        |
| s2  | dyadic variance (overdispersion parameter)                |
| Y   | square relational matrix of observed counts               |

**Value**

updated value of Z

**Author(s)**

Cassy Dorff, Shahryar Minhas, Tosin Salau

---

|                  |                                                      |
|------------------|------------------------------------------------------|
| sampler_describe | <i>Describe the estimator behind a fitted object</i> |
|------------------|------------------------------------------------------|

---

### Description

Reports which estimation routine produced a fitted object and what uncertainty information, if any, is available. Methods exist for `ame_als` fits (the fast block coordinate descent estimator) and `boot_ame` bootstrap objects.

### Usage

```
sampler_describe(object, verbose = TRUE)

## S3 method for class 'ame_als'
sampler_describe(object, verbose = TRUE)

## S3 method for class 'boot_ame'
sampler_describe(object, verbose = TRUE)

## S3 method for class 'ame'
sampler_describe(object, verbose = TRUE)

## S3 method for class 'lame'
sampler_describe(object, verbose = TRUE)
```

### Arguments

|                      |                                                                    |
|----------------------|--------------------------------------------------------------------|
| <code>object</code>  | a fitted object ( <code>ame_als</code> or <code>boot_ame</code> ). |
| <code>verbose</code> | logical; if TRUE (default) print the description.                  |

### Value

The input object, invisibly.

---

|                     |                                                       |
|---------------------|-------------------------------------------------------|
| sample_ab_bipartite | <i>Sample additive effects for bipartite networks</i> |
|---------------------|-------------------------------------------------------|

---

### Description

Sample additive effects for bipartite networks

### Usage

```
sample_ab_bipartite(Z, EZ_without_ab, sigma2_a, sigma2_b, s2)
```

**Value**

List with components a (row effects) and b (column effects)

---

|                     |                                                                         |
|---------------------|-------------------------------------------------------------------------|
| sample_alpha_cowles | <i>Cowles MH update for explicit ordinal cutpoints (Z-marginalised)</i> |
|---------------------|-------------------------------------------------------------------------|

---

**Description**

One Metropolis-Hastings sweep on alpha with Z integrated out of the conditional. The proposal is a symmetric random walk in  $\delta = \log(\text{diff}(\alpha))$  space; the acceptance ratio uses the marginal ordinal-probit likelihood. Mixing of alpha under this update is dramatically faster than the data-induced Gibbs convention (Cowles 1996 reports ESS gains of an order of magnitude on standard ordinal-probit benchmarks).

**Usage**

```
sample_alpha_cowles(alpha, Y_int, EZ, tau_prop, symmetric = FALSE)
```

**Arguments**

|           |                                                                                                                                                                |
|-----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| alpha     | numeric, current cutpoints with $\alpha[1] = 0$ , length $K-1$ .                                                                                               |
| Y_int     | integer matrix (or array) of ordinal categories coded 1..K, with NA for missing cells.                                                                         |
| EZ        | linear predictor at the dyad level, same shape as Y_int.                                                                                                       |
| tau_prop  | numeric, RW proposal SD in delta space (will be adapted in burn-in by the caller).                                                                             |
| symmetric | logical, whether the network is symmetric (restricts the likelihood to upper-triangle cells so each dyad is counted once; variance 1, no precision rescaling). |

**Value**

list with elements alpha, delta, accept (logical).

**Author(s)**

Cassy Dorff, Shahryar Minhas, Tosin Salau

---

sample\_beta\_dynamic\_cpp

*Sample the dynamic-block beta path via FFBS*


---

## Description

Forward-filter / backward-sample the AR(1) state-space model for the dynamic-block beta coefficients. Returns the joint draw of beta\_dyn at every time period.

## Usage

```
sample_beta_dynamic_cpp(
  Xdyn_list,
  Xstat_list,
  Z_list,
  offset_list,
  beta_static,
  rho_by_coef,
  sigma_by_coef,
  Lambda,
  beta0_mean,
  beta0_cov,
  s2,
  dyad_rho,
  bipartite,
  symmetric,
  use_dyad_rho
)
```

## Arguments

|               |                                                                                                                                    |
|---------------|------------------------------------------------------------------------------------------------------------------------------------|
| Xdyn_list     | T-length list of (n*n) x p_dyn long-format design matrices for the dynamic block (column-major reshape per period).                |
| Xstat_list    | T-length list of (n*n) x p_static long-format design matrices for the static block.                                                |
| Z_list        | T-length list of (n x n) latent matrices.                                                                                          |
| offset_list   | T-length list of (n x n) offset matrices ( $a_i + b_j + U_i'V_j$ contributions; everything that's not in $X*\beta$ ).              |
| beta_static   | Length p_static current static beta vector.                                                                                        |
| rho_by_coef   | Length p_dyn vector of AR(1) rho values for each dynamic coefficient. (Per-block but expanded per-column for vectorised indexing.) |
| sigma_by_coef | Length p_dyn vector of AR(1) innovation standard deviations for each dynamic coefficient.                                          |
| Lambda        | Block-diagonal innovation scale matrix (p_dyn x p_dyn). Combined with sigma^2 to give $Q = \sigma^2 * \Lambda$ .                   |

|              |                                                                                                                                                                                          |
|--------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| beta0_mean   | Length p_dyn prior mean for the first state beta_1 (the prior is placed directly on beta_1, no predict step at t = 1).                                                                   |
| beta0_cov    | p_dyn x p_dyn prior covariance for beta_1. Must be a fixed matrix that does not depend on the current (rho, sigma) draw so the transition-only hyperparameter conditionals remain exact. |
| s2           | Dyadic variance.                                                                                                                                                                         |
| dyad_rho     | Dyadic correlation (ignored when use_dyad_rho=FALSE).                                                                                                                                    |
| bipartite    | Whether the network is bipartite.                                                                                                                                                        |
| symmetric    | Whether the network is symmetric.                                                                                                                                                        |
| use_dyad_rho | Whether to use the dyad-corr branch (TRUE only for unipartite, asymmetric, with a non-zero rho).                                                                                         |

**Value**

List with: path – a (T x p\_dyn) matrix of beta draws (one row per period); chol\_fail – integer count of Cholesky failures.

---

sample\_beta\_static\_cpp

*Sample the static-block beta conditional on the dynamic path*

---

**Description**

Conjugate Gaussian update for the static coefficient block, treating the dynamic path as known. Uses a flat-ish ridge-style prior prior\_prec on the static beta (typically diag(1/g) to match the existing g-prior path).

**Usage**

```
sample_beta_static_cpp(
  Xdyn_list,
  Xstat_list,
  Z_list,
  offset_list,
  beta_dyn_path,
  prior_mean,
  prior_prec,
  s2,
  dyad_rho,
  bipartite,
  symmetric,
  use_dyad_rho
)
```



**Arguments**

|                            |                                                       |
|----------------------------|-------------------------------------------------------|
| <code>Xdyn_list</code>     | T-length list of long-format dynamic design matrices. |
| <code>Xstat_list</code>    | T-length list of long-format static design matrices.  |
| <code>Z_list</code>        | T-length list of latent (n x n) matrices.             |
| <code>offset_list</code>   | T-length list of (n x n) offsets.                     |
| <code>beta_dyn_path</code> | (T x p_dyn) dynamic path matrix.                      |
| <code>prior_mean</code>    | Length p_static prior mean.                           |
| <code>prior_prec</code>    | p_static x p_static prior precision.                  |
| <code>s2</code>            | Dyadic variance.                                      |
| <code>dyad_rho</code>      | Dyadic correlation.                                   |
| <code>bipartite</code>     | TRUE/FALSE.                                           |
| <code>symmetric</code>     | TRUE/FALSE.                                           |
| <code>use_dyad_rho</code>  | TRUE/FALSE.                                           |

**Value**

List with: `beta` – length p\_static; `chol_fail` – integer.

---

`sample_dynamic_ab_cpp` *Sample dynamic additive effects with AR(1) evolution*

---

**Description**

Gibbs update of the per-period additive effects under the AR(1) state model with stationary initial condition. For each actor and period the full conditional combines the AR(1) bridge prior (stationary init at  $t = 1$ ) with the dyadic residual likelihood:  $\text{resid}_{ij} = a_i + b_j + e_{ij}$ ,  $e_{ij} \sim N(0, s2)$ . The reciprocal effect ( $b_j$  for the a-step, the freshly updated  $a_i$  for the b-step) is subtracted from each residual, missing residuals are skipped, and for symmetric networks each dyad contributes exactly once ( $\text{resid}(i,j) = a_i + a_j + e_{ij}$ ).

**Usage**

```
sample_dynamic_ab_cpp(
  a_current,
  b_current,
  Z_array,
  EZ_array,
  rho_ab,
  sigma_ab,
  s2,
  symmetric
)
```

**Arguments**

|           |                                                                  |
|-----------|------------------------------------------------------------------|
| a_current | Current 2D array of row effects (n x T)                          |
| b_current | Current 2D array of column effects (n x T)                       |
| Z_array   | 3D array of latent positions (n x n x T)                         |
| EZ_array  | 3D array of expected values without additive effects (n x n x T) |
| rho_ab    | AR(1) parameter for additive effects                             |
| sigma_ab  | Innovation standard deviation                                    |
| s2        | Dyadic residual variance                                         |
| symmetric | Whether the network is symmetric                                 |

**Value**

List with updated a and b arrays

---

|                   |                                                            |
|-------------------|------------------------------------------------------------|
| sample_rho_ab_cpp | <i>Sample AR(1) parameter for dynamic additive effects</i> |
|-------------------|------------------------------------------------------------|

---

**Description**

Sample AR(1) parameter for dynamic additive effects

**Usage**

```
sample_rho_ab_cpp(  
  a_mat,  
  b_mat,  
  sigma_ab,  
  rho_current,  
  symmetric,  
  prior_mean = 0,  
  prior_sd = -1  
)
```

**Arguments**

|             |                                                                                                                                                                 |
|-------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| a_mat       | Matrix of row effects (n x T)                                                                                                                                   |
| b_mat       | Matrix of column effects (n x T)                                                                                                                                |
| sigma_ab    | Innovation standard deviation                                                                                                                                   |
| rho_current | Current value of rho                                                                                                                                            |
| symmetric   | Whether the network is symmetric                                                                                                                                |
| prior_mean  | Prior mean for rho. Used only when prior_sd > 0.                                                                                                                |
| prior_sd    | Prior SD for rho. prior_sd < 0 (the default) selects a Jeffreys-like flat prior; a positive value switches to a truncated Normal(prior_mean, prior_sd^2) prior. |

**Value**

Updated rho value

---

|                     |                                                    |
|---------------------|----------------------------------------------------|
| sample_rho_beta_cpp | <i>Sample the AR(1) rho for each dynamic block</i> |
|---------------------|----------------------------------------------------|

---

**Description**

Truncated-Normal full conditional, one rho per block.

**Usage**

```
sample_rho_beta_cpp(
  beta_path,
  group_id,
  n_groups,
  Lambda_inv,
  sigma_by_coef,
  rho_current,
  rho_prior_mean,
  rho_prior_sd,
  rho_lower = 0,
  rho_upper = 0.999
)
```

**Arguments**

|                |                                                       |
|----------------|-------------------------------------------------------|
| beta_path      | (T x p_dyn) matrix of beta draws.                     |
| group_id       | Length p_dyn integer vector (1-based) of block IDs.   |
| n_groups       | Number of distinct block IDs.                         |
| Lambda_inv     | (p_dyn x p_dyn) inverse of the (full) Lambda scale.   |
| sigma_by_coef  | Length p_dyn vector of per-coef sigma (block-shared). |
| rho_current    | Length n_groups vector of current rho values.         |
| rho_prior_mean | Length n_groups vector of prior means.                |
| rho_prior_sd   | Length n_groups vector of prior SDs.                  |
| rho_lower      | Lower truncation bound (typically 0).                 |
| rho_upper      | Upper truncation bound (typically 0.999).             |

**Value**

Length n\_groups vector of new rho values.

---

|                 |                                                             |
|-----------------|-------------------------------------------------------------|
| sample_rho_G_mh | <i>Logit-scale MH update on the AR(1) coefficient rho_G</i> |
|-----------------|-------------------------------------------------------------|

---

**Description**

Proposes  $\rho^* = \tanh(\operatorname{atanh}(\rho) + \tau * N(0, 1))$ ; under a uniform  $\rho \sim U(-1, 1)$  prior the proposal is symmetric in the Fisher-z scale and the Jacobian is  $\log(1 - \rho^2)$ . The MH ratio compares the AR(1) prior density of `vec(G)_path` at the current vs proposed  $\rho$ .

**Usage**

```
sample_rho_G_mh(rho_G, vecG_path, sigma_G2, tau = 0.3)
```

**Arguments**

|                        |                                      |
|------------------------|--------------------------------------|
| <code>rho_G</code>     | current AR(1) coefficient            |
| <code>vecG_path</code> | p x N matrix of FFBS-sampled states  |
| <code>sigma_G2</code>  | state innovation variance            |
| <code>tau</code>       | RW proposal SD on the Fisher-z scale |

**Value**

list with `rho` (updated), `accept` (logical)

---

|               |                                                          |
|---------------|----------------------------------------------------------|
| sample_rho_uv | <i>Sample AR(1) parameter for dynamic latent factors</i> |
|---------------|----------------------------------------------------------|

---

**Description**

Independence Metropolis-Hastings update coherent with the stationary AR(1) initial condition used by the dynamic UV kernels. The proposal is the conjugate Normal implied by the transitions and the `Normal(prior_mean, prior_sd^2)` prior, drawn truncated to  $(-0.99, 0.99)$  via the inverse CDF; the acceptance ratio supplies the  $t = 1$  stationary factor proportional to  $(1 - \rho^2)^{(nR / 2)} * \exp(-(1 - \rho^2) * S1 / (2 * \sigma^2))$  that the Gaussian proposal omits. Defaults (`prior_mean = 0`, `prior_sd = 1`) preserve the historical behaviour; `lame::lame()` passes the user-set `prior$rho_uv_mean` / `prior$rho_uv_sd` explicitly.

**Usage**

```
sample_rho_uv(
  U_cube,
  V_cube,
  sigma_uv,
  rho_current,
  symmetric,
```

```
prior_mean = 0,  
prior_sd = 1  
)
```

**Arguments**

|             |                                     |
|-------------|-------------------------------------|
| U_cube      | 3D array of U positions (n x R x T) |
| V_cube      | 3D array of V positions (n x R x T) |
| sigma_uv    | Innovation standard deviation       |
| rho_current | Current value of rho                |
| symmetric   | Whether network is symmetric        |
| prior_mean  | Prior mean for rho (default 0)      |
| prior_sd    | Prior SD for rho (default 1)        |

**Value**

Updated rho value

---

|                     |                                                                |
|---------------------|----------------------------------------------------------------|
| sample_sigma_ab_cpp | <i>Sample innovation variance for dynamic additive effects</i> |
|---------------------|----------------------------------------------------------------|

---

**Description**

Sample innovation variance for dynamic additive effects

**Usage**

```
sample_sigma_ab_cpp(  
  a_mat,  
  b_mat,  
  rho_ab,  
  symmetric,  
  prior_shape = 2,  
  prior_scale = 1  
)
```

**Arguments**

|             |                                         |
|-------------|-----------------------------------------|
| a_mat       | Matrix of row effects (n x T)           |
| b_mat       | Matrix of column effects (n x T)        |
| rho_ab      | AR(1) parameter                         |
| symmetric   | Whether the network is symmetric        |
| prior_shape | Shape parameter for inverse gamma prior |
| prior_scale | Scale parameter for inverse gamma prior |

**Value**

Updated sigma\_ab value

---

|                       |                                                                 |
|-----------------------|-----------------------------------------------------------------|
| sample_sigma_beta_cpp | <i>Sample the AR(1) innovation sigma for each dynamic block</i> |
|-----------------------|-----------------------------------------------------------------|

---

**Description**

Inverse-Gamma full conditional, one sigma per block.

**Usage**

```
sample_sigma_beta_cpp(  
  beta_path,  
  group_id,  
  n_groups,  
  Lambda_inv,  
  rho_by_group,  
  prior_shape,  
  prior_scale  
)
```

**Arguments**

- beta\_path (T x p\_dyn) matrix.
- group\_id Length p\_dyn integer vector (1-based) of block IDs.
- n\_groups Number of distinct block IDs.
- Lambda\_inv (p\_dyn x p\_dyn) inverse of the (full) Lambda scale.
- rho\_by\_group Length n\_groups vector of current rho values.
- prior\_shape Length n\_groups vector of IG shape parameters.
- prior\_scale Length n\_groups vector of IG scale parameters.

**Value**

Length n\_groups vector of new sigma values.

---

|                 |                                                                                     |
|-----------------|-------------------------------------------------------------------------------------|
| sample_sigma_G2 | <i>Inverse-gamma posterior draw for <math>\sigma_G^2</math> given the FFBS path</i> |
|-----------------|-------------------------------------------------------------------------------------|

---

**Description**

Conjugate IG update on  $\sigma_G^2$  given the AR(1) innovations  $\eta_t = g_t - \rho * g_{t-1}$ ,  $t = 2..N$ , plus the stationary density at  $t = 1$ . Default prior is  $IG(2, 1)$  on  $\sigma_G^2$ .

**Usage**

```
sample_sigma_G2(
  vecG_path,
  rho_G,
  prior_shape = 2,
  prior_rate = 1,
  s2_obs = 1,
  v_cap_mult = 4
)
```

**Arguments**

|            |                                                                        |
|------------|------------------------------------------------------------------------|
| s2_obs     | observation-noise variance (1 for probit/binary).                      |
| v_cap_mult | cap on the stationary G-state variance in units of s2_obs (default 4). |

**Details**

Scale identification. The model identifies only the product  $U_t G_t V_t'$ , not  $G_t$  alone, so the overall scale of  $\text{vec}(G_t)$  is free: left unchecked the chain finds a degenerate mode where  $\sigma_G^2$  (and hence  $G_t$ ) inflates by orders of magnitude while  $U, V$  collapse to compensate, leaving the linear predictor unchanged but the reported  $G_{\text{cube}}$  meaningless. Clamping  $\rho_G$  alone does not bound this because the stationary state variance is  $\sigma_G^2 / (1 - \rho_G^2)$ . We therefore cap the implied stationary variance at  $v_{\text{cap\_mult}} * s2_{\text{obs}}$  (a few observation-noise units), which forces the multiplicative scale onto  $U, V$  – where the regularising  $N(0, s2)$  prior pins it – and keeps  $G_t$  on a scale comparable to a static-G fit. The cap is loose enough never to bind on a genuinely small-variation  $G_t$ .

---

|                 |                                                              |
|-----------------|--------------------------------------------------------------|
| sample_sigma_uv | <i>Sample innovation variance for dynamic latent factors</i> |
|-----------------|--------------------------------------------------------------|

---

**Description**

Sample innovation variance for dynamic latent factors

**Usage**

```
sample_sigma_uv(U_cube, V_cube, rho_uv, symmetric)
```

**Arguments**

|           |                                     |
|-----------|-------------------------------------|
| U_cube    | 3D array of U positions (n x R x T) |
| V_cube    | 3D array of V positions (n x R x T) |
| rho_uv    | AR(1) parameter                     |
| symmetric | Whether network is symmetric        |

**Value**

Updated sigma\_uv value

---

|              |                                 |
|--------------|---------------------------------|
| sampsonmonks | <i>Sampson's monastery data</i> |
|--------------|---------------------------------|

---

**Description**

Several dyadic variables measured on 18 members of a monastery.

**Format**

A socioarray whose dimensions represent nominators, nominees and relations. Each monk was asked to rank up to three other monks on a variety of positive and negative relations. A rank of three indicates the "highest" ranking for a particular relational variable. The relations like\_m2 and like\_m1 are evaluations of likeing at one and two timepoints previous to when the other relations were measured.

**Source**

Originally available at <http://moreno.ss.uci.edu/data.html#sampson> (site no longer accessible).

---

|       |                             |
|-------|-----------------------------|
| sheep | <i>Sheep dominance data</i> |
|-------|-----------------------------|

---

**Description**

Number of dominance encounters between 28 female bighorn sheep. Cell (i,j) records the number of times sheep i dominated sheep j. From Hass (1991).

**Format**

A list consisting of the following:

- dom: a directed socioarray recording the number of dominance encounters.
- age: the age of each sheep in years.



**Source**

Originally available at <http://moreno.ss.uci.edu/data.html#sheep> (site no longer accessible).

---

simulate.ame

---

*Simulate networks from a fitted AME model*


---

**Description**

Generates multiple network realizations from a fitted AME model. This function performs conditional posterior predictive simulation: it draws from stored MCMC samples when they are available and uses posterior means for latent components that were not retained.

Unlike `print.ame`, which only displays fitted quantities, `simulate.ame` draws new networks from the posterior predictive distribution.

**Usage**

```
## S3 method for class 'ame'
simulate(
  object,
  nsim = 100,
  seed = NULL,
  newdata = NULL,
  burn_in = 0,
  thin = 1,
  return_latent = FALSE,
  ...
)
```

**Arguments**

|                            |                                                                                                                                                                                                                                                                                                                                                |
|----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>object</code>        | fitted model object of class "ame"                                                                                                                                                                                                                                                                                                             |
| <code>nsim</code>          | number of networks to simulate (default: 100)                                                                                                                                                                                                                                                                                                  |
| <code>seed</code>          | random seed for reproducibility                                                                                                                                                                                                                                                                                                                |
| <code>newdata</code>       | optional list containing new covariate data:<br><b>Xdyad</b> dyadic covariates (n x n x p array or nA x nB x p for bipartite)<br><b>Xrow</b> row/sender covariates (n x p matrix or nA x p for bipartite)<br><b>Xcol</b> column/receiver covariates (n x p matrix or nB x p for bipartite)<br>If NULL, uses covariates from original model fit |
| <code>burn_in</code>       | number of initial MCMC samples to discard (default: 0, assumes burn-in already removed)                                                                                                                                                                                                                                                        |
| <code>thin</code>          | thinning interval for MCMC samples (default: 1, use every sample)                                                                                                                                                                                                                                                                              |
| <code>return_latent</code> | logical: return latent Z matrices in addition to Y? (default: FALSE)                                                                                                                                                                                                                                                                           |
| <code>...</code>           | additional arguments (not currently used)                                                                                                                                                                                                                                                                                                      |

## Details

### Model:

The AME model represents networks through a latent variable framework:

$$Y_{ij} \sim F(Z_{ij})$$

where  $F$  is the observation model (e.g., probit for binary) and  $Z$  is the latent network:

$$Z_{ij} = \beta^T x_{ij} + a_i + b_j + u_i^T v_j + \epsilon_{ij}$$

Components:

- $\beta$ : regression coefficients for dyadic/nodal covariates
- $a_i, b_j$ : additive sender and receiver random effects
- $u_i, v_j$ : multiplicative latent factors (dimension  $R$ )
- $\epsilon_{ij}$ : dyadic random effects with correlation  $\rho$

### Simulation:

For each simulated network  $k = 1, \dots, \text{nsim}$ :

1. **Parameter draw:** Draw parameter set  $\theta^{(k)}$  from MCMC chains:
  - Sample iteration  $s$  uniformly from stored MCMC samples
  - Extract  $\beta^{(s)}$ , variance components  $(v_a^{(s)}, v_b^{(s)}, v_e^{(s)}, \rho^{(s)})$
2. **Random effects:** Sample new random effects from posterior distributions:
  - $a_i^{(k)} \sim N(0, v_a^{(s)})$  for  $i = 1, \dots, n$  (row effects)
  - $b_j^{(k)} \sim N(0, v_b^{(s)})$  for  $j = 1, \dots, m$  (column effects)
  - Fresh draws from the posterior variance carry random-effect uncertainty into the simulated networks
3. **Latent network:** Build expected latent positions:

$$E[Z_{ij}^{(k)}] = \beta^{(s)T} x_{ij} + a_i^{(k)} + b_j^{(k)} + \hat{u}_i^T \hat{v}_j$$

where  $\hat{u}_i, \hat{v}_j$  are posterior mean latent factors

4. **Dyadic correlation:** Add correlated noise structure:

$$Z_{ij}^{(k)} = E[Z_{ij}^{(k)}] + \epsilon_{ij}^{(k)}$$

where  $\epsilon$  has covariance structure:

$$\text{Cov}(\epsilon_{ij}, \epsilon_{ji}) = \rho^{(s)} v_e^{(s)}$$

$$\text{Var}(\epsilon_{ij}) = v_e^{(s)}$$

5. **Observation model:** Generate the observed network:

- Binary:  $Y_{ij}^{(k)} = I(Z_{ij}^{(k)} > 0)$
- Normal:  $Y_{ij}^{(k)} = Z_{ij}^{(k)}$

- Poisson:  $Y_{ij}^{(k)} \sim \text{Poisson}(\exp(Z_{ij}^{(k)}))$
- Other families use appropriate link functions

### Sources of uncertainty:

The simulation captures three types of uncertainty:

1. **Parameter uncertainty:** Different MCMC samples yield different  $\beta, v_a, v_b, v_e, \rho$
2. **Random effect uncertainty:** Fresh draws from  $N(0, v_a), N(0, v_b)$  for each simulation
3. **Dyadic uncertainty:** Correlated random noise  $\epsilon_{ij}$

The resulting simulations propagate uncertainty from the stored parameter draws and from fresh dyadic/random-effect draws. Latent components that were not stored as MCMC draws are held at their posterior means.

### Latent-factor draws:

Multiplicative effects (U, V) use posterior means unless the fit retained compatible latent-factor draws. Storing full latent-factor chains can require substantial additional memory.

### Symmetric Networks:

For symmetric networks, the model enforces  $a_i = b_i$  and  $u_i = v_i$ , and the latent matrix  $Z$  is symmetrized before generating observations.

### Value

A list with components:

**Y** list of nsim simulated networks in the same format as the original data

**Z** if return\_latent=TRUE, list of nsim latent Z matrices

**family** the family of the model (binary, normal, etc.)

**mode** network mode (unipartite or bipartite)

### Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

### Examples

```
# Fit a model
data(YX_bin)
fit <- ame(YX_bin$Y, Xdyad = YX_bin$X, burn = 10, nscan = 100, odens = 1,
          family = "binary", verbose = FALSE)

# Simulate 10 networks from posterior
sims <- simulate(fit, nsim = 10)
```

---

|                  |                                                      |
|------------------|------------------------------------------------------|
| simulate.ame_als | <i>Simulate networks from a fitted ame_als model</i> |
|------------------|------------------------------------------------------|

---

### Description

Draws `nsim` replicates of  $Y$  from the fitted ALS mean structure:  $\mu$ ,  $\beta$ ,  $a$ ,  $b$ ,  $U$ ,  $V$ , and the family-appropriate noise distribution. For directed unipartite normal and binary fits, reciprocal dyads use the fitted residual  $\rho$ . The returned object has class "`ame.sim`" so it is compatible with `plot_ppc_*`-style consumers (where applicable).

### Usage

```
## S3 method for class 'ame_als'
simulate(object, nsim = 1, seed = NULL, ...)
```

### Arguments

|                     |                                                        |
|---------------------|--------------------------------------------------------|
| <code>object</code> | an <code>ame_als</code> fit.                           |
| <code>nsim</code>   | integer; number of replicates to simulate (default 1). |
| <code>seed</code>   | optional RNG seed.                                     |
| <code>...</code>    | ignored.                                               |

### Details

ALS is a point estimator. `simulate.ame_als` holds  $\mu$ ,  $\beta$ ,  $a$ ,  $b$ ,  $U$ ,  $V$  at the point estimate and resamples the noise. For uncertainty over the parameters themselves, use [ame\\_als\\_bootstrap](#) (whose replicates each carry their own resampled  $Y$ ) and combine those simulations.

### Value

An object of class "`ame.sim`" with element  $Y$  – a list of `nsim` simulated outcome arrays (one matrix for a cross-section, one list-of-matrices per slice for a longitudinal fit).

---

|               |                                                                |
|---------------|----------------------------------------------------------------|
| simulate.lame | <i>Simulate longitudinal networks from a fitted LAME model</i> |
|---------------|----------------------------------------------------------------|

---

### Description

Generates multiple longitudinal network realizations from a fitted LAME (Longitudinal AME) model. This function performs conditional posterior predictive simulation for dynamic networks: it draws from stored MCMC samples when available and uses posterior means for latent components that were not retained.

**Usage**

```
## S3 method for class 'lame'
simulate(
  object,
  nsim = 100,
  seed = NULL,
  newdata = NULL,
  n_time = NULL,
  burn_in = 0,
  thin = 1,
  return_latent = FALSE,
  start_from = "posterior",
  ...
)
```

**Arguments**

|               |                                                                                                                                                                                                                                                                                                                                      |
|---------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| object        | fitted model object of class "lame"                                                                                                                                                                                                                                                                                                  |
| nsim          | number of network trajectories to simulate (default: 100)                                                                                                                                                                                                                                                                            |
| seed          | random seed for reproducibility                                                                                                                                                                                                                                                                                                      |
| newdata       | optional list containing new covariate data:<br><b>Xdyad</b> list of T dyadic covariate arrays (n x n x p or nA x nB x p)<br><b>Xrow</b> list of T row/sender covariate matrices (n x p or nA x p)<br><b>Xcol</b> list of T column/receiver covariate matrices (n x p or nB x p)<br>If NULL, uses covariates from original model fit |
| n_time        | number of time periods to simulate. If NULL, uses same as original data                                                                                                                                                                                                                                                              |
| burn_in       | number of initial MCMC samples to discard (default: 0)                                                                                                                                                                                                                                                                               |
| thin          | thinning interval for MCMC samples (default: 1, use every sample)                                                                                                                                                                                                                                                                    |
| return_latent | logical: return latent Z matrices in addition to Y? (default: FALSE)                                                                                                                                                                                                                                                                 |
| start_from    | character: how to initialize the simulation<br><b>"posterior"</b> start from posterior mean (default)<br><b>"random"</b> random initialization<br><b>"data"</b> use first time point from original data                                                                                                                              |
| ...           | additional arguments (not currently used)                                                                                                                                                                                                                                                                                            |

**Details****Mathematical Framework for Longitudinal Networks:**

The LAME model extends AME to multiple time periods T with potential temporal dependencies. For each time  $t = 1, \dots, T$ :

$$Y_{ij,t} \sim F(Z_{ij,t})$$

where the latent network evolves as:

$$Z_{ij,t} = \beta^T x_{ij,t} + a_{i,t} + b_{j,t} + u_{i,t}^T v_{j,t} + \epsilon_{ij,t}$$

**Temporal Dynamics:**

LAME can incorporate three types of temporal dependencies:

1. **Static Effects:** Parameters constant over time

- $a_{i,t} = a_i, b_{j,t} = b_j$  for all  $t$
- $u_{i,t} = u_i, v_{j,t} = v_j$  for all  $t$

2. **Dynamic Additive Effects:** AR(1) process for random effects

$$a_{i,t} = \rho_{ab}a_{i,t-1} + \eta_{i,t}, \quad \eta_{i,t} \sim N(0, \sigma_a^2(1 - \rho_{ab}^2))$$

$$b_{j,t} = \rho_{ab}b_{j,t-1} + \xi_{j,t}, \quad \xi_{j,t} \sim N(0, \sigma_b^2(1 - \rho_{ab}^2))$$

where  $\rho_{ab}$  is the temporal correlation parameter

3. **Dynamic Multiplicative Effects:** AR(1) for latent factors

$$u_{i,t} = \rho_{uv}u_{i,t-1} + \omega_{i,t}$$

$$v_{j,t} = \rho_{uv}v_{j,t-1} + \psi_{j,t}$$

**Uncertainty Quantification Process for Trajectories:**

For each simulated trajectory  $k = 1, \dots, \text{nsim}$ :

**Step 1: Parameter Sampling**

- Draw MCMC iteration  $s$  uniformly from stored posterior samples
- Extract static parameters:  $\beta^{(s)}$ , variance components
- Extract temporal parameters if applicable:  $\rho_{ab}^{(s)}, \rho_{uv}^{(s)}$

**Step 2: Initialize at  $t = 1$** 

Depending on `start_from` parameter:

- "posterior": Use posterior means as starting values
- "random": Draw from stationary distribution
- For additive effects:  $a_{i,1}^{(k)} \sim N(0, \sigma_a^2)$
- For multiplicative effects: Initialize from prior

**Step 3: Evolve Through Time**

For each  $t = 2, \dots, T$ :

a) **Update Dynamic Effects** (if applicable):

$$a_{i,t}^{(k)} = \rho_{ab}^{(s)} a_{i,t-1}^{(k)} + \eta_{i,t}^{(k)}$$

where  $\eta_{i,t}^{(k)} \sim N(0, \sigma_a^2(1 - [\rho_{ab}^{(s)}]^2))$

The innovation variance  $\sigma_a^2(1 - \rho_{ab}^2)$  ensures stationarity

b) **Construct Latent Network:**

$$E[Z_{ij,t}^{(k)}] = \beta^{(s)T} x_{ij,t} + a_{i,t}^{(k)} + b_{j,t}^{(k)} + u_{i,t}^T v_{j,t}$$

c) **Add Dyadic Noise:**

$$Z_{ij,t}^{(k)} = E[Z_{ij,t}^{(k)}] + \epsilon_{ij,t}^{(k)}$$

with correlation structure preserved from AME model

d) **Generate Observations:** Apply appropriate link function based on family**Sources of Uncertainty in Longitudinal Context:**

1. **Cross-sectional uncertainty** (as in AME):
  - Parameter uncertainty from MCMC
  - Random effect variability
  - Dyadic noise
2. **Temporal uncertainty:**
  - Uncertainty in temporal correlation parameters  $\rho_{ab}, \rho_{uv}$
  - Innovation noise in AR(1) processes
  - Propagation of uncertainty through time (compounds over periods)
3. **Initial condition uncertainty:**
  - Different starting values lead to different trajectories
  - Captured through start\_from options

**Interpretation of Multiple Trajectories:**

Each simulated trajectory represents one possible evolution of the network conditional on the stored fit. Variation across trajectories captures:

- Model parameter uncertainty
- Stochastic variation in temporal evolution
- Accumulated uncertainty over time periods

The ensemble of trajectories provides prediction intervals that widen over time, reflecting increasing uncertainty in longer-term forecasts.

**Special Considerations:**

1. **Temporal Correlation:** Higher  $\rho$  values create smoother trajectories with more persistence
2. **Stationarity:** The AR(1) innovation variance is scaled to maintain stationary marginal distributions
3. **Missing Time Points:** If simulating beyond observed data ( $n\_time > T\_observed$ ), covariates are recycled or set to zero with appropriate warnings

**Limitations:**

As with `simulate.ame`, multiplicative effects use posterior means unless the fit retained compatible latent-factor draws. Storing complete MCMC chains for  $u_{i,t}, v_{j,t}$  at all time points is memory-intensive for large networks and long time series.

**Value**

A list with components:

**Y** list of nsim simulated longitudinal network trajectories, each element is a list of T networks

**Z** if return\_latent=TRUE, list of nsim latent Z trajectories

**family** the family of the model (binary, normal, etc.)

**mode** network mode (unipartite or bipartite)

**n\_time** number of time periods

**Author(s)**

Shahryar Minhas

**Examples**

```
# Create simple longitudinal network data
set.seed(1)
n <- 10
nms <- paste0("n", 1:n)
Y_list <- list(
  matrix(rnorm(n * n), n, n, dimnames = list(nms, nms)),
  matrix(rnorm(n * n), n, n, dimnames = list(nms, nms))
)
diag(Y_list[[1]]) <- diag(Y_list[[2]]) <- NA
fit <- lame(Y_list, family = "normal",
            nscan = 50, burn = 10, odens = 1, verbose = FALSE, plot = FALSE)

# Simulate 10 network trajectories from posterior
sims <- simulate(fit, nsim = 10)
```

---

|                    |                                                               |
|--------------------|---------------------------------------------------------------|
| simulate_posterior | <i>Simulate posterior distributions from fitted AME model</i> |
|--------------------|---------------------------------------------------------------|

---

**Description**

Simulate posterior distributions from fitted AME model

**Usage**

```
simulate_posterior(
  fit,
  component = c("UV", "ab", "beta", "Y"),
  n_samples = NULL,
  seed = NULL
)
```



**Arguments**

|           |                                                                                                                                                                                                                                                                                                        |
|-----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| fit       | Fitted ame model object                                                                                                                                                                                                                                                                                |
| component | Character; which component to simulate: "UV", "ab", "beta", "Y"                                                                                                                                                                                                                                        |
| n_samples | Number of posterior samples to return. Defaults to NULL, which uses every saved draw when the fit stores them (see <a href="#">posterior_options</a> ) and 100 otherwise. A smaller value draws a random subset, which widens Monte Carlo error in the tails of any interval computed from the result. |
| seed      | Random seed for reproducibility                                                                                                                                                                                                                                                                        |

**Details**

This function can simulate posterior distributions even when they weren't saved during MCMC, by using the posterior means and variance components.

For more accurate posteriors, use `posterior_options()` during model fitting to save the actual MCMC samples.

**Value**

Array or matrix of posterior samples

**Author(s)**

Cassy Dorff, Shahryar Minhas, Tosin Salau

**Examples**

```
# Fit a model with multiplicative effects
data(YX_nrm)
fit <- ame(YX_nrm$Y, Xdyad = YX_nrm$X, R = 2,
          nscan = 100, burn = 10, odens = 1, verbose = FALSE)

# Get posterior samples of regression coefficients
beta_post <- simulate_posterior(fit, "beta", n_samples = 50)
```

---

simY\_bin

---

*Simulate a binary relational matrix from latent means*


---

**Description**

Draws a latent Gaussian array with the given dyadic correlation and thresholds it at zero to produce a binary (0/1) sociomatrix. Self-ties on the diagonal of a square (unipartite) matrix are set to NA; rectangular (bipartite) matrices are returned with every entry populated.

**Usage**

```
simY_bin(EZ, rho)
```

**Arguments**

|     |                                                         |
|-----|---------------------------------------------------------|
| EZ  | matrix giving the expected value of the latent Z matrix |
| rho | dyadic correlation                                      |

**Value**

a binary matrix matching the dimensions of EZ

**Author(s)**

lame authors

---

simY\_frn

---

*Simulate a relational matrix under a fixed rank nomination scheme*


---

**Description**

Simulate a sociomatrix of fixed rank nominations from a social relations model. A latent matrix Z is drawn from the SRM, and each sender's outgoing ties are converted into ranked nominations: at most odmax partners are nominated, only positive latent affinities qualify, and the retained nominations are numbered from weakest (1) to strongest.

**Usage**

```
simY_frn(EZ, rho, odmax, Y0)
```

**Arguments**

|       |                                                                           |
|-------|---------------------------------------------------------------------------|
| EZ    | a square matrix giving the expected value of the latent Z matrix          |
| rho   | dyadic correlation                                                        |
| odmax | a scalar or vector giving the maximum number of nominations for each node |
| Y0    | a square matrix identifying where missing values should be maintained     |

**Value**

a square matrix, where higher values represent stronger relationships

**Author(s)**

lame authors

---

simY\_nrm*Simulate a normal relational matrix*

---

**Description**

Draws a Gaussian sociomatrix whose entries have expectation EY, dyadic variance s2 and within-dyad correlation rho.

**Usage**

```
simY_nrm(EY, rho, s2)
```

**Arguments**

|     |                                                                  |
|-----|------------------------------------------------------------------|
| EY  | square matrix giving the expected value of the relational matrix |
| rho | dyadic correlation                                               |
| s2  | dyadic variance                                                  |

**Value**

a square matrix

**Author(s)**

lame authors

---

simY\_ord*Simulate an ordinal relational matrix*

---

**Description**

Simulates an ordinal relational matrix whose marginal category frequencies match those of an observed ordinal matrix.

**Usage**

```
simY_ord(EZ, rho, Y)
```

**Arguments**

|     |                                                                |
|-----|----------------------------------------------------------------|
| EZ  | square matrix giving the expected value of the latent Z matrix |
| rho | scalar giving the within-dyad correlation                      |
| Y   | ordinal relational data matrix                                 |

**Details**

A latent Gaussian relational array is drawn from the social relations model with mean EZ and within-dyad correlation rho via simZ. The latent values are then discretized into ordinal categories by cutting them at empirical quantiles chosen so that the proportion of entries falling in each category reproduces the marginal distribution of the observed categories of Y.

**Value**

a square matrix

**Author(s)**

lame authors

---

|           |                                             |
|-----------|---------------------------------------------|
| simY_pois | <i>Simulate a Poisson relational matrix</i> |
|-----------|---------------------------------------------|

---

**Description**

Simulates a relational matrix from a Poisson distribution given the log mean values

**Usage**

simY\_pois(EZ)

**Arguments**

EZ                      square matrix giving the log expected values of the relational matrix

**Value**

a square matrix of counts

**Author(s)**

Cassy Dorff, Shahryar Minhas, Tosin Salau

---

|      |                                                    |
|------|----------------------------------------------------|
| simZ | <i>Simulate a latent relational Gaussian array</i> |
|------|----------------------------------------------------|

---

**Description**

Draws a latent normal array from the social relations model: each directed cell has mean EZ and marginal variance s2, and the two cells of a dyad share within-dyad correlation rho. Rectangular (bipartite) inputs carry no within-dyad correlation and are drawn independently.

**Usage**

```
simZ(EZ, rho, s2 = 1)
```

**Arguments**

|     |                     |
|-----|---------------------|
| EZ  | expected value of Z |
| rho | dyadic correlation  |
| s2  | dyadic variance     |

**Value**

a simulated value of Z

**Author(s)**

lame authors

---

|       |                                |
|-------|--------------------------------|
| sm2el | <i>Sociomatrix to edgelist</i> |
|-------|--------------------------------|

---

**Description**

Construction of an edgelist from a sociomatrix

**Usage**

```
sm2el(sm,directed=TRUE)
```

**Arguments**

|          |                                                                              |
|----------|------------------------------------------------------------------------------|
| sm       | a sociomatrix with possibly valued relations                                 |
| directed | if TRUE, only use the upper triangular part of the matrix to enumerate edges |

**Value**

an edgelist

Author(s)

lame authors

Examples

```
Y<-matrix(rpois(10*10,.5),10,10) ; diag(Y)<-NA
E<-sm2el(Y)
el2sm(E) - Y
```

---

|                       |                                                 |
|-----------------------|-------------------------------------------------|
| snap_category_summary | <i>Summarize snap indices by actor category</i> |
|-----------------------|-------------------------------------------------|

---

Description

Summarize snap indices by actor category

Usage

```
snap_category_summary(fit, groups, years = NULL, side = c("u", "v"))
```

Arguments

|        |                                                                                                                                                                                                                                          |
|--------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| fit    | a <a href="#">lame</a> fit with snap-shift MCMC output, or a <a href="#">lame_snap_als</a> fit. MCMC fits should be run with retained snap draws for posterior uncertainty; ALS fits contribute their snap_prob scores as one score row. |
| groups | a named list mapping group names to actor names/indices, or a named vector whose values are group labels and whose names are actors.                                                                                                     |
| years  | optional year/period names or indices. Default uses every period.                                                                                                                                                                        |
| side   | "u" for sender/row-side snap indicators or "v" for receiver/column-side indicators.                                                                                                                                                      |

Value

A data frame with one row per group-year.

---

|                  |                                                |
|------------------|------------------------------------------------|
| snap_index_draws | <i>Extract posterior draws of snap indices</i> |
|------------------|------------------------------------------------|

---

### Description

Computes draw-level averages of MCMC snap indicators over selected actors and years. The result is useful for system-level rupture indices and focal-actor rupture indices. Fits should be run with `keep_snap_draws = "draws"` for posterior uncertainty. If only `snap_prob` is present, the function returns a single score row and warns that intervals cannot be read as posterior intervals.

### Usage

```
snap_index_draws(fit, actors = NULL, years = NULL, side = c("u", "v"))
```

### Arguments

|                     |                                                                                                                                                                                                                                                       |
|---------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>fit</code>    | a <a href="#">lame</a> fit with snap-shift MCMC output, or a <a href="#">lame_snap_als</a> fit. MCMC fits should be run with retained snap draws for posterior uncertainty; ALS fits contribute their <code>snap_prob</code> scores as one score row. |
| <code>actors</code> | optional actor names or indices. Default uses every actor on the selected side.                                                                                                                                                                       |
| <code>years</code>  | optional year/period names or indices. Default uses every period.                                                                                                                                                                                     |
| <code>side</code>   | "u" for sender/row-side snap indicators or "v" for receiver/column-side indicators.                                                                                                                                                                   |

### Value

A data frame with columns `draw`, `year`, `side`, `n_actors`, and `snap_index`.

---

|                    |                                         |
|--------------------|-----------------------------------------|
| snap_index_summary | <i>Summarize posterior snap indices</i> |
|--------------------|-----------------------------------------|

---

### Description

Summarize posterior snap indices

### Usage

```
snap_index_summary(
  fit,
  actors = NULL,
  years = NULL,
  side = c("u", "v"),
  probs = c(0.025, 0.1, 0.5, 0.9, 0.975)
)
```

**Arguments**

|        |                                                                                                                                                                                                                                          |
|--------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| fit    | a <a href="#">lame</a> fit with snap-shift MCMC output, or a <a href="#">lame_snap_als</a> fit. MCMC fits should be run with retained snap draws for posterior uncertainty; ALS fits contribute their snap_prob scores as one score row. |
| actors | optional actor names or indices. Default uses every actor on the selected side.                                                                                                                                                          |
| years  | optional year/period names or indices. Default uses every period.                                                                                                                                                                        |
| side   | "u" for sender/row-side snap indicators or "v" for receiver/column-side indicators.                                                                                                                                                      |
| probs  | numeric quantiles to report.                                                                                                                                                                                                             |

**Value**

A data frame with one row per selected year.

---

|                   |                                                            |
|-------------------|------------------------------------------------------------|
| snap_rank_summary | <i>Summarize posterior rank uncertainty for snap years</i> |
|-------------------|------------------------------------------------------------|

---

**Description**

Ranks year-level snap indices within each retained draw, with rank 1 assigned to the highest snap index.

**Usage**

```
snap_rank_summary(fit, actors = NULL, years = NULL, side = c("u", "v"))
```

**Arguments**

|        |                                                                                                                                                                                                                                          |
|--------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| fit    | a <a href="#">lame</a> fit with snap-shift MCMC output, or a <a href="#">lame_snap_als</a> fit. MCMC fits should be run with retained snap draws for posterior uncertainty; ALS fits contribute their snap_prob scores as one score row. |
| actors | optional actor names or indices. Default uses every actor on the selected side.                                                                                                                                                          |
| years  | optional year/period names or indices. Default uses every period.                                                                                                                                                                        |
| side   | "u" for sender/row-side snap indicators or "v" for receiver/column-side indicators.                                                                                                                                                      |

**Value**

A data frame with year-level index means and rank probabilities.



---

|             |                                 |
|-------------|---------------------------------|
| summary.ame | <i>Summary of an AME object</i> |
|-------------|---------------------------------|

---

## Description

Summarizes a fitted AME (Additive and Multiplicative Effects) model, including parameter estimates, standard errors, credible intervals, and model diagnostics.

## Usage

```
## S3 method for class 'ame'
summary(object, ...)
```

## Arguments

|        |                                                                                               |
|--------|-----------------------------------------------------------------------------------------------|
| object | an object of class "ame", typically the result of fitting an AME model using the ame function |
| ...    | additional parameters (currently not used)                                                    |

## Details

The summary includes:

**Regression coefficients** Posterior means, posterior standard deviations, z-values, approximate p-values, and 95% credible intervals for dyadic, sender, and receiver covariates. Note: the z-values are computed as posterior mean / posterior SD, and the p-values are derived from a normal approximation. These are convenient screening statistics but are not formal frequentist test statistics. For rigorous inference, use the credible intervals or examine the full posterior via the BETA matrix directly.

**Variance components** Estimates and standard errors for:

- va** Variance of additive sender/row effects (asymmetric networks)
- cab** Covariance between sender and receiver effects
- vb** Variance of additive receiver/column effects (asymmetric networks)
- rho** Dyadic correlation (reciprocity in directed networks)
- ve** Residual variance

For symmetric networks, only va and ve are estimated.

## Value

A list of class "summary.ame" containing:

|          |                                                           |
|----------|-----------------------------------------------------------|
| call     | The original function call                                |
| beta     | Matrix of regression coefficient estimates and statistics |
| variance | Matrix of variance component estimates                    |

**Author(s)**

Cassy Dorff, Shahryar Minhas, Tosin Salau

**See Also**

[ame](#), [print.summary.ame](#)

---

|                 |                                           |
|-----------------|-------------------------------------------|
| summary.ame.sim | <i>Summary method for AME simulations</i> |
|-----------------|-------------------------------------------|

---

**Description**

Summary method for AME simulations

**Usage**

```
## S3 method for class 'ame.sim'
summary(object, ...)
```

**Arguments**

|        |                                      |
|--------|--------------------------------------|
| object | simulation object of class "ame.sim" |
| ...    | additional arguments (not used)      |

**Value**

summary statistics invisibly

---

|                 |                                    |
|-----------------|------------------------------------|
| summary.ame_als | <i>Summarize an ame_als object</i> |
|-----------------|------------------------------------|

---

**Description**

Summarize an ame\_als object

**Usage**

```
## S3 method for class 'ame_als'
summary(object, ...)
```

**Arguments**

|        |                    |
|--------|--------------------|
| object | an ame_als object. |
| ...    | ignored.           |

**Value**

A list of class "summary.ame\_als", printed as a table.

---

|                  |                                                       |
|------------------|-------------------------------------------------------|
| summary.boot_ame | <i>Summarize bootstrap results for a fast AME fit</i> |
|------------------|-------------------------------------------------------|

---

**Description**

Summarize bootstrap results for a fast AME fit

**Usage**

```
## S3 method for class 'boot_ame'
summary(object, ...)

## S3 method for class 'summary.boot_ame'
print(x, ...)
```

**Arguments**

- object            a boot\_ame object.
- ...               ignored.
- x                 a summary.boot\_ame object.

**Value**

An object of class "summary.boot\_ame", printed as a set of tables.

---

|              |                                 |
|--------------|---------------------------------|
| summary.lame | <i>Summary of a LAME object</i> |
|--------------|---------------------------------|

---

**Description**

Summarizes a fitted LAME (Longitudinal Additive and Multiplicative Effects) model, including parameter estimates, standard errors, credible intervals, and model diagnostics.

**Usage**

```
## S3 method for class 'lame'
summary(object, ...)
```

**Arguments**

- object            an object of class "lame", typically the result of fitting a longitudinal AME model using the lame function
- ...               additional parameters (currently not used)

## Details

The summary includes:

**Regression coefficients** Posterior means, posterior standard deviations, z-values, approximate p-values, and 95% credible intervals for dyadic, sender, and receiver covariates. Note: the z-values are computed as posterior mean / posterior SD, and the p-values are derived from a normal approximation. These are convenient screening statistics but are not formal frequentist test statistics. For rigorous inference, use the credible intervals or examine the full posterior via the BETA matrix directly.

**Variance components** Estimates and standard errors for:

- va** Variance of additive sender/row effects
- cab** Covariance between sender and receiver effects
- vb** Variance of additive receiver/column effects
- rho** Dyadic correlation (reciprocity)
- ve** Residual variance

**Dynamic coefficients per period** Only printed when the fit was produced with `dynamic_beta` on at least one coefficient. The table has one row per coefficient with columns:

- Mean** average of the per-period posterior means across  $t$
- Min, Max** smallest and largest per-period posterior mean
- Drift**  $\text{Max} - \text{Min}$ : the absolute range of the per-period posterior means, in coefficient units
- Drift\_pct**  $100 * \text{Drift} / |\text{Mean}|$ , the drift as a percentage of the average level. Reported as NA when the time-average is near zero (within 5\ range), because a trajectory that crosses zero makes the percentage explode; read `Drift` in that case
- Dynamic** "Y" if the coefficient was flagged as dynamic, "N" if it was held static

The block also prints the per-block AR(1) hyperparameters (`rho_beta = . . .`). For per-period credible intervals use [confint.lame](#).

## Value

A list of class "summary.lame" containing:

- |                        |                                                           |
|------------------------|-----------------------------------------------------------|
| <code>call</code>      | The original function call                                |
| <code>beta</code>      | Matrix of regression coefficient estimates and statistics |
| <code>variance</code>  | Matrix of variance component estimates                    |
| <code>n.periods</code> | Number of time periods in the longitudinal data           |

## Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

## See Also

[lame](#), [print.summary.lame](#)

---

|                  |                                     |
|------------------|-------------------------------------|
| summary.lame.sim | Summary method for LAME simulations |
|------------------|-------------------------------------|

---

**Description**

Summary method for LAME simulations

**Usage**

```
## S3 method for class 'lame.sim'  
summary(object, ...)
```

**Arguments**

|        |                                       |
|--------|---------------------------------------|
| object | simulation object of class "lame.sim" |
| ...    | additional arguments (not used)       |

**Value**

summary statistics

---

|      |                     |
|------|---------------------|
| tidy | S3 generic for tidy |
|------|---------------------|

---

**Description**

Light-weight fallback generic so that calls of the form `tidy(fit)` dispatch through R's S3 system even when the **broom** or **generics** packages are not loaded. When either is loaded, its generic resolves first; this generic only fires for bare-namespace use.

**Usage**

```
tidy(x, ...)
```

**Arguments**

|     |                                |
|-----|--------------------------------|
| x   | An object to tidy.             |
| ... | Passed to the relevant method. |

**Value**

A data frame; method-specific schema.

tidy.ame

*Tidy method for fitted ame / lame objects***Description**

Returns a data frame with one row per estimated coefficient, compatible with the **broom** idiom. For `dynamic_beta` fits (3-D BETA), returns one row per coefficient *per period* with a `period` column. Standard errors are posterior standard deviations; statistic is estimate / std.error.

**Usage**

```
## S3 method for class 'ame'
tidy(x, conf.int = TRUE, conf.level = 0.95, ...)

## S3 method for class 'lame'
tidy(x, conf.int = TRUE, conf.level = 0.95, ...)
```

**Arguments**

|                         |                                                           |
|-------------------------|-----------------------------------------------------------|
| <code>x</code>          | A fitted ame / lame object.                               |
| <code>conf.int</code>   | Logical; include 95% (conf.low, conf.high). Default TRUE. |
| <code>conf.level</code> | Confidence level for the interval. Default 0.95.          |
| <code>...</code>        | Ignored.                                                  |

**Details**

**Note on p.value.** This column is included for **broom** compatibility but is *not* a classical test. It is a two-sided Normal approximation based on the posterior mean and marginal posterior standard deviation, matching the calculation in `summary(fit)`. Use it as a compact signal that the marginal posterior is far from zero, and report it alongside the `conf.low` / `conf.high` credible interval. When sign certainty matters, compute it directly from `x$BETA`, for example `mean(sign(BETA) == sign(mean(BETA)))`.

Loaded as an S3 method against `generics::tidy` when the **generics** package is available; works as `tidy(fit)` either way once **broom** is loaded.

**Value**

Data frame with columns `term`, `estimate`, `std.error`, `statistic`, `p.value`, `conf.low`, `conf.high`, and (for `dynamic_beta` fits) `period`.

**Examples**

```
data(YX_bin_list)
fit <- lame(YX_bin_list$Y, YX_bin_list$X, family = "binary", R = 0,
           nscan = 100, burn = 20, odens = 5, verbose = FALSE)
tidy(fit)
```

---

|              |                                                          |
|--------------|----------------------------------------------------------|
| tidy.ame_als | <i>Tidy method for fitted ame_als / lame_als objects</i> |
|--------------|----------------------------------------------------------|

---

## Description

Returns a data frame with one row per regression coefficient, compatible with the **broom** idiom, so that ALS fits compose with **modelsummary** / **kableExtra** pipelines next to MCMC fits. Standard errors come from the sandwich covariance ([vcov.ame\\_als](#)) by default, or from the bootstrap object attached to `x$bootstrap` when present (preferred, fully propagated). `statistic` is estimate / `std.error`; `p.value` is the Normal-approximation two-sided tail  $2(1 - \Phi(|z|))$  from the bootstrap or sandwich standard error. It is a Wald-style summary for the point estimator, not a posterior probability.

## Usage

```
## S3 method for class 'ame_als'
tidy(x, conf.int = TRUE, conf.level = 0.95, ...)

## S3 method for class 'lame_als'
tidy(x, conf.int = TRUE, conf.level = 0.95, ...)
```

## Arguments

|                         |                                                                                                      |
|-------------------------|------------------------------------------------------------------------------------------------------|
| <code>x</code>          | A fitted <code>ame_als</code> / <code>lame_als</code> object.                                        |
| <code>conf.int</code>   | Logical; include <code>conf.low</code> / <code>conf.high</code> columns. Default <code>TRUE</code> . |
| <code>conf.level</code> | Confidence level. Default <code>0.95</code> .                                                        |
| <code>...</code>        | Passed to <a href="#">vcov.ame_als</a> (e.g. <code>cluster = "dyad"</code> ).                        |

## Details

Only the intercept and dyadic-covariate coefficients are returned, matching `coef(fit)` on the sandwich-covered subset. Additive (a, b), multiplicative (U, V), and node-covariate parameters are not included; use [ame\\_als\\_bootstrap](#) and inspect the bootstrap object directly if you need them.

## Value

Data frame with columns `term`, `estimate`, `std.error`, `statistic`, `p.value`, `conf.low`, `conf.high`, plus a `se_source` column recording "bootstrap" or "sandwich".

## Examples

```
data(YX_bin_list)
Y1 <- 1 * (YX_bin_list$Y[[1]] > 0); diag(Y1) <- NA
fit <- ame_als(Y = Y1, Xdyad = YX_bin_list$X[[1]],
              family = "binary", R = 1, verbose = FALSE)
tidy(fit)
```

---

|               |                                                                 |
|---------------|-----------------------------------------------------------------|
| tidy.boot_ame | <i>Tidy method for a standalone bootstrap object (boot_ame)</i> |
|---------------|-----------------------------------------------------------------|

---

### Description

ame\_als\_bootstrap() returns an object of class "boot\_ame" (not "ame\_als"); this tidy method exposes the bootstrap estimates as a broom-style data frame so the standalone object composes with **modelsummary** the same way an embedded ame\_als(..., bootstrap = N) fit does.

### Usage

```
## S3 method for class 'boot_ame'
tidy(x, conf.level = 0.95, ...)
```

### Arguments

|            |                                 |
|------------|---------------------------------|
| x          | A boot_ame object.              |
| conf.level | Confidence level. Default 0.95. |
| ...        | Ignored.                        |

### Value

Data frame with columns term, estimate, std.error, statistic, p.value, conf.low, conf.high, se\_source.

---

|            |                                                                         |
|------------|-------------------------------------------------------------------------|
| trace_plot | <i>MCMC trace plots and density plots for AME/LAME model parameters</i> |
|------------|-------------------------------------------------------------------------|

---

### Description

Creates diagnostic plots for Markov Chain Monte Carlo (MCMC) samples from AME or LAME models. Displays trace plots to assess convergence and mixing, alongside density plots to visualize posterior distributions.

### Usage

```
trace_plot(
  fit,
  params = c("all", "beta", "variance"),
  include = NULL,
  exclude = NULL,
  ncol = 3,
  nrow = NULL,
  burn.in = 0,
```



```

    thin = 1,
    title = NULL
  )

```

### Arguments

|                      |                                                                                                                                                                                                                                                                                                                             |
|----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>fit</code>     | An object of class "ame" or "lame" containing MCMC samples                                                                                                                                                                                                                                                                  |
| <code>params</code>  | Character vector specifying which parameters to plot: "beta" for regression coefficients, "variance" for variance components, or "all" (default) for both                                                                                                                                                                   |
| <code>include</code> | Character vector of specific parameter names to include. Raw variance-component names ("va", "ve", "rho", ...) and their display labels ("Error Variance", ...) are both accepted. For dynamic_beta fits, per-period traces are named like "x_dyad[t1]"; supplying the base name (e.g. "x_dyad") selects all of its periods |
| <code>exclude</code> | Character vector of specific parameter names to exclude. Base names match all per-period traces, as with include                                                                                                                                                                                                            |
| <code>ncol</code>    | Number of columns for plot layout (default 3)                                                                                                                                                                                                                                                                               |
| <code>nrow</code>    | Number of rows for plot layout (default NULL, determined automatically)                                                                                                                                                                                                                                                     |
| <code>burn.in</code> | Number of initial iterations to exclude as burn-in when calculating statistics (default 0, assumes burn-in already removed)                                                                                                                                                                                                 |
| <code>thin</code>    | Thinning interval for display (default 1, no thinning)                                                                                                                                                                                                                                                                      |
| <code>title</code>   | Optional title for the plot                                                                                                                                                                                                                                                                                                 |

### Details

This function produces two types of diagnostic plots:

**Trace plots** Show the evolution of parameter values across MCMC iterations. Good mixing is indicated by rapid exploration of the parameter space with no trends or stuck periods.

**Density plots** Show the posterior distribution of parameters. Multiple modes may indicate identification issues or convergence problems.

The plots help diagnose:

- Convergence: Has the chain reached the stationary distribution?
- Mixing: Is the chain exploring the parameter space efficiently?
- Autocorrelation: Are successive samples highly correlated?

Parameters displayed include:

- Regression coefficients (beta)
- Variance components (va, vb, cab, rho, ve)

### Value

A ggplot2 object that can be further customized

**Author(s)**

Cassy Dorff, Shahryar Minhas, Tosin Salau

**Examples**

```
# Fit an AME model
data(YX_nrm)
fit <- ame(YX_nrm$Y, Xdyad = YX_nrm$X,
           nscan = 100, burn = 10, odens = 1, verbose = FALSE)

# Basic trace plots for all parameters
trace_plot(fit)

# Only regression coefficients
trace_plot(fit, params = "beta")

# Only variance components
trace_plot(fit, params = "variance")
```

---

update.ame

---

*Update an AME / LAME fit*


---

**Description**

S3 method for [update](#) that re-fits the model with modified arguments. Reuses the original call recorded in `fit$call`. If the fit was produced with `freeze_call = TRUE`, the data snapshot on `fit$data_snapshot` is used in place of looking up names in the caller's environment.

**Usage**

```
## S3 method for class 'ame'
update(object, ..., evaluate = TRUE)

## S3 method for class 'lame'
update(object, ..., evaluate = TRUE)
```

**Arguments**

|                       |                                                                                                                                                 |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>object</code>   | A fitted ame or lame object.                                                                                                                    |
| <code>...</code>      | Named arguments to overwrite in the original call (e.g. <code>nscan = 5000</code> , <code>dynamic_beta = TRUE</code> , <code>R = 2</code> ).    |
| <code>evaluate</code> | Logical: if <code>TRUE</code> (default), evaluate the updated call and return the new fit; if <code>FALSE</code> , return the unevaluated call. |

**Value**

A new fitted object, or (when `evaluate = FALSE`) the modified call.

## Examples

```
data(YX_bin_list)
fit <- lame(YX_bin_list$Y, YX_bin_list$X, family = "binary",
            burn = 5, nscan = 20, odens = 1, verbose = FALSE)
# toggle dynamic_beta on without rewriting the whole call
fit_dyn <- update(fit, dynamic_beta = "dyad")
dim(fit_dyn$BETA) # 3-D now
```

---

|                |                                         |
|----------------|-----------------------------------------|
| update.ame_als | <i>Update an ame_als / lame_als fit</i> |
|----------------|-----------------------------------------|

---

## Description

S3 method for [update](#) that re-fits an ALS fit with modified arguments. Two routes:

- if ... contains only the warm-start refit knobs (`Y_new`, `X_new`, `Z_new`, `max_iter`, `tol`, `verbose`), it delegates to [ame\\_als\\_refit](#) for a fast warm-started refit;
- otherwise (e.g. changing `R`, `family`, `lambda`, `bootstrap`) it re-evaluates the original object's call with the overrides, matching the [update.ame](#) semantics on the MCMC side.

The split exists because `ame_als_refit()` is a genuinely warm-started single-fit refit (faster, narrower argument set), while changing `R` / `family` requires a cold-start refit through [ame\\_als](#).

## Usage

```
## S3 method for class 'ame_als'
update(object, ..., evaluate = TRUE)

## S3 method for class 'lame_als'
update(object, ..., evaluate = TRUE)
```

## Arguments

|                       |                                                                                                                                                                        |
|-----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>object</code>   | A fitted <code>ame_als</code> / <code>lame_als</code> object.                                                                                                          |
| <code>...</code>      | Named arguments. See <a href="#">ame_als_refit</a> for the warm-start argument list and <a href="#">ame_als</a> for the cold-start argument list.                      |
| <code>evaluate</code> | Logical: if <code>TRUE</code> (default), evaluate the updated call and return the new fit; if <code>FALSE</code> , return the unevaluated call (cold-start path only). |

## Value

A new fitted `ame_als` object, or (when `evaluate = FALSE` on the cold-start path) the modified call.

**Examples**

```
Y <- matrix(rnorm(400), 20, 20); diag(Y) <- NA
fit <- ame_als(Y, R = 1, family = "normal", verbose = FALSE)
# warm-start refit with the same arguments (fast)
fit_w <- update(fit, max_iter = 50)
# cold-start refit with a different R (full restart)
fit_R2 <- update(fit, R = 2)
```

---

update\_variances\_bipartite

*Update variance parameters for bipartite*

---

**Description**

Update variance parameters for bipartite

**Usage**

```
update_variances_bipartite(
  a,
  b,
  eta0_a = 2,
  eta0_b = 2,
  Sab0_aa = 1,
  Sab0_bb = 1
)
```

**Value**

List with components sigma2\_a and sigma2\_b

---

uv\_plot

*Visualize multiplicative effects (latent factors) from AME models*

---

**Description**

Creates a two-dimensional visualization of the multiplicative effects (U and V) from an AME or LAME model. These latent factors capture network structure beyond what is explained by covariates and additive effects, including clustering, transitivity, and other higher-order dependencies.

**Usage**

```
uv_plot(
  fit = NULL,
  Y = NULL,
  U = NULL,
  V = NULL,
  row.names = NULL,
  col.names = NULL,
  layout = c("circle", "biplot"),
  vscale = 0.8,
  show.edges = FALSE,
  edge.alpha = 0.3,
  node.size = "magnitude",
  label.nodes = TRUE,
  label.size = 3,
  show.usernames = NULL,
  sender.color = "darkred",
  receiver.color = "darkblue",
  colors = NULL,
  title = NULL,
  time_point = NULL,
  plot_type = c("snapshot", "trajectory", "faceted"),
  show_arrows = TRUE,
  highlight = NULL
)
```

**Arguments**

|                             |                                                                                                                                                                       |
|-----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>fit</code>            | An object of class "ame" or "lame" containing multiplicative effects, or a network matrix <code>Y</code> if <code>U</code> and <code>V</code> are provided separately |
| <code>Y</code>              | Network matrix (only needed if <code>fit</code> is not provided)                                                                                                      |
| <code>U</code>              | Matrix of sender latent factors (extracted from <code>fit</code> if not provided)                                                                                     |
| <code>V</code>              | Matrix of receiver latent factors (extracted from <code>fit</code> if not provided)                                                                                   |
| <code>row.names</code>      | Names for row nodes (defaults to rownames of <code>Y</code> or <code>U</code> )                                                                                       |
| <code>col.names</code>      | Names for column nodes (defaults to colnames of <code>Y</code> or <code>V</code> )                                                                                    |
| <code>layout</code>         | Character string specifying layout: "circle" (default) or "biplot"                                                                                                    |
| <code>vscale</code>         | Scaling factor for <code>V</code> positions relative to <code>U</code> (default 0.8)                                                                                  |
| <code>show.edges</code>     | Logical; if TRUE, show network edges (default FALSE)                                                                                                                  |
| <code>edge.alpha</code>     | Transparency for edges (default 0.3)                                                                                                                                  |
| <code>node.size</code>      | Size of nodes, or "degree" to scale by degree (default 3)                                                                                                             |
| <code>label.nodes</code>    | Logical; if TRUE, show node labels (default TRUE)                                                                                                                     |
| <code>label.size</code>     | Size of node labels (default 3)                                                                                                                                       |
| <code>show.usernames</code> | Integer: number of top-degree nodes to label, or NULL for default behavior                                                                                            |
| <code>sender.color</code>   | Color for sender/row nodes (default "darkred")                                                                                                                        |

|                             |                                                                                                                                                                                                                                                                                  |
|-----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>receiver.color</code> | Color for receiver/column nodes (default "darkblue")                                                                                                                                                                                                                             |
| <code>colors</code>         | Optional vector of colors for nodes (e.g., for communities)                                                                                                                                                                                                                      |
| <code>title</code>          | Optional title for the plot                                                                                                                                                                                                                                                      |
| <code>time_point</code>     | For dynamic UV, which time point to plot (default: last). Can be numeric index or "average" for time-averaged positions                                                                                                                                                          |
| <code>plot_type</code>      | For dynamic UV: "snapshot" (single time), "trajectory" (evolution), "faceted" (grid of time points). For static UV, this is ignored.                                                                                                                                             |
| <code>show_arrows</code>    | For trajectory plots, whether to show directional arrows                                                                                                                                                                                                                         |
| <code>highlight</code>      | Optional character vector of actor names to highlight on a <code>plot_type = "trajectory"</code> plot. Highlighted actors are coloured with the colour-blind-safe Okabe-Ito palette; all other actors are rendered in grey at lower alpha. Ignored for static or snapshot plots. |

## Details

The multiplicative effects in AME models provide a low-rank representation of network structure through latent factors:

**U matrix** Sender-specific latent positions (row factors)

**V matrix** Receiver-specific latent positions (column factors)

**UV' product** Captures dyad-specific effects beyond additive terms

The visualization can show:

**Circular layout** Default layout placing nodes on a circle with latent positions shown as deviations

**Biplot layout** Shows U and V positions directly in latent space

**Network overlay** Optional display of actual network ties

Interpretation:

- Nodes close together in latent space tend to have similar connection patterns
- The distance between sender position (U) and receiver position (V) relates to the likelihood of a tie
- Clustering in the latent space indicates community structure

## Value

A `ggplot2` object that can be further customized

## Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

**Examples**

```
# Fit an AME model with multiplicative effects
data(YX_nrm)
fit <- ame(YX_nrm$Y, Xdyad = YX_nrm$X, R = 2,
           nscan = 100, burn = 10, odens = 1, verbose = FALSE)

# Basic visualization
uv_plot(fit)

# Use biplot layout
uv_plot(fit, layout = "biplot")
```

vcov.ame

*Posterior covariance of AME model coefficients***Description**

Returns the posterior covariance matrix of regression coefficients.

**Usage**

```
## S3 method for class 'ame'
vcov(object, ...)

## S3 method for class 'lame'
vcov(object, ...)
```

**Arguments**

|        |                                |
|--------|--------------------------------|
| object | fitted AME model (class "ame") |
| ...    | additional arguments (ignored) |

**Value**

p x p covariance matrix of posterior BETA draws

vcov.ame\_als

*Sandwich covariance for the regression coefficients of a fast AME fit*

## Description

Returns a heteroskedasticity-robust (optionally dyad-clustered) sandwich covariance matrix for the intercept and *dyadic*-covariate coefficients of an [ame\\_als](#) fit. This is a fast analytic alternative to the bootstrap for those coefficients.

## Usage

```
## S3 method for class 'ame_als'
vcov(object, cluster = c("dyad", "none"), ...)
```

## Arguments

|         |                                                                                                                                                                                               |
|---------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| object  | an <code>ame_als</code> fit.                                                                                                                                                                  |
| cluster | "dyad" (default) for a dyad-clustered robust meat, or "none" for an HC0 (heteroskedasticity-only) meat. Ignored when the fit carries a bootstrap, since the bootstrap covariance is returned. |
| ...     | ignored.                                                                                                                                                                                      |

## Details

The estimate is the conditional sandwich  $B^{-1}MB^{-1}$  with bread  $B = D'WD$  ( $D$  the observed intercept + dyadic-covariate design,  $W$  the fit's observation weights) and meat  $M$  the heteroskedasticity-robust (`cluster = "none"`, an HC0 meat) or dyad-clustered (`cluster = "dyad"`, the default) outer product of the weighted score contributions  $w_{\ell}e_{\ell}d_{\ell}$ . For a normal or transform fit the weights are unit, so this reduces to the ordinary  $D'D$  sandwich; for an IRLS fit it uses the final IRLS weights, matching the estimating equation the fit actually solved. Dyad clustering pools the score across  $(i, j)$ ,  $(j, i)$  and time, so it reflects dyadic dependence (reciprocity, repeated observation).

It is **conditional**: the additive effects `a`, `b` and the multiplicative term are held fixed, so it omits their estimation uncertainty and is anti-conservative. Node-covariate, additive and multiplicative standard errors are not returned – use [ame\\_als\\_bootstrap](#) for those and for fully-propagated inference.

## Value

A covariance matrix with matching row/column names. When the fit carries a `$bootstrap`, this is the bootstrap covariance over all estimated coefficients, matching `coef()`. Otherwise it is the conditional sandwich, covering `c(intercept, dyadic coefficients)` only.

## See Also

[ame\\_als\\_bootstrap](#) for bootstrap uncertainty covering all parameters.



---

|               |                                                            |
|---------------|------------------------------------------------------------|
| vcov.boot_ame | <i>Bootstrap covariance of the regression coefficients</i> |
|---------------|------------------------------------------------------------|

---

**Description**

Returns the sample covariance matrix of the bootstrap replicate intercept + regression coefficients of a boot\_ame object – the covariance underlying the reported standard errors and confidence intervals.

**Usage**

```
## S3 method for class 'boot_ame'
vcov(object, ...)
```

**Arguments**

|        |                    |
|--------|--------------------|
| object | a boot_ame object. |
| ...    | ignored.           |

**Value**

A covariance matrix over the intercept and regression coefficients.

---

|               |                                          |
|---------------|------------------------------------------|
| vignette_data | <i>TIES sanctions data for vignettes</i> |
|---------------|------------------------------------------|

---

**Description**

Longitudinal directed binary network of international economic sanctions among 35 countries across four years (1993, 1994, 1995, 2000), derived from the Threat and Imposition of Sanctions (TIES) dataset (Morgan et al. 2014). Entry  $y_{ij,t} = 1$  means country  $i$  imposed sanctions on country  $j$  in year  $t$ . Network density is approximately  $2\%$

**Usage**

```
data(vignette_data)
```

**Format**

Four objects:

**Y** List of 4 binary adjacency matrices (35 x 35), one per year.

**Xdyad** List of 4 arrays (35 x 35 x 2) of dyadic covariates: distance (geographic) and shared\_igos (shared IGO memberships).

**Xrow** List of 4 matrices (35 x 2) of sender covariates: log\_gdp and log\_pop.

**Xcol** List of 4 matrices (35 x 2) of receiver covariates: log\_gdp and log\_pop.

## Details

When loaded via `data(vignette_data)`, the following objects are placed in the calling environment: `Y`, `Xdyad`, `Xrow`, `Xcol`.

## References

Morgan, T. Clifton, Bapat, N., & Kobayashi, Y. (2014). Threat and Imposition of Economic Sanctions 1945–2005. *Conflict Management and Peace Science*, 31(5), 541–558.

## Examples

```
data(vignette_data)
cat("Countries:", nrow(Y[[1]]), "\n")
cat("Time periods:", length(Y), "\n")
```

---

|          |                                 |
|----------|---------------------------------|
| waic.ame | <i>WAIC for AME / LAME fits</i> |
|----------|---------------------------------|

---

## Description

S3 method for `waic` that uses the stored `fit$log_lik`.

## Usage

```
## S3 method for class 'ame'
waic(x, ...)

## S3 method for class 'lame'
waic(x, ...)

## S3 method for class 'ame_als'
waic(x, ...)
```

## Arguments

|                  |                                                                                     |
|------------------|-------------------------------------------------------------------------------------|
| <code>x</code>   | A fitted <code>ame</code> or <code>lame</code> object with <code>\$log_lik</code> . |
| <code>...</code> | Additional arguments forwarded to <code>loo::waic.matrix</code> .                   |

## Value

A `waic` object.

---

|       |                                                       |
|-------|-------------------------------------------------------|
| Xbeta | <i>Linear combinations of submatrices of an array</i> |
|-------|-------------------------------------------------------|

---

**Description**

Computes a matrix of expected values based on an array X of predictors and a vector beta of regression coefficients.

**Usage**

Xbeta(X, beta)

**Arguments**

X                    an n by n by p array  
beta                a p by 1 vector

**Value**

An n by n matrix

**Author(s)**

Cassy Dorff, Shahryar Minhas, Tosin Salau

---

|               |                                                     |
|---------------|-----------------------------------------------------|
| Xbeta_bip_cpp | <i>Compute Xbeta product for bipartite networks</i> |
|---------------|-----------------------------------------------------|

---

**Description**

Computes  $\sum_k \text{beta}_k * X_k$  for a single time slice

**Usage**

Xbeta\_bip\_cpp(X, beta)

**Arguments**

X                    3D array (nA x nB x p) of covariates for one time period  
beta                Coefficient vector of length p

**Value**

nA x nB matrix

---

|      |                          |
|------|--------------------------|
| Xcol | <i>Column covariates</i> |
|------|--------------------------|

---

**Description**

Column covariates loaded by `data(vignette_data)`. See [vignette\\_data](#) for full details.

**Format**

A list of matrices of column covariates

**See Also**

[vignette\\_data](#)

---

|       |                          |
|-------|--------------------------|
| Xdyad | <i>Dyadic covariates</i> |
|-------|--------------------------|

---

**Description**

Dyadic covariates loaded by `data(vignette_data)`. See [vignette\\_data](#) for full details.

**Format**

A list of arrays of dyadic covariates

**See Also**

[vignette\\_data](#)

---

|      |                       |
|------|-----------------------|
| Xrow | <i>Row covariates</i> |
|------|-----------------------|

---

**Description**

Row covariates loaded by `data(vignette_data)`. See [vignette\\_data](#) for full details.

**Format**

A list of matrices of row covariates

**See Also**

[vignette\\_data](#)

---

|   |                          |
|---|--------------------------|
| Y | <i>Relational matrix</i> |
|---|--------------------------|

---

**Description**

Relational matrix loaded by `data(vignette_data)`. See [vignette\\_data](#) for full details.

**Format**

A list of square binary adjacency matrices

**See Also**

[vignette\\_data](#)

---

|        |                                              |
|--------|----------------------------------------------|
| YX_bin | <i>binary relational data and covariates</i> |
|--------|----------------------------------------------|

---

**Description**

a synthetic dataset that includes binary relational data as well as information on eight covariates

**Usage**

```
data(YX_bin)
```

**Format**

The format is: List of 2 \$ Y: num [1:100, 1:100] NA 0 0 0 0 0 0 0 0 1 ... \$ X: num [1:100, 1:100, 1:8] 1 1 1 1 1 1 1 1 1 1 ... ..- attr(\*, "dimnames")=List of 3 .. ..\$: NULL .. ..\$: NULL .. ..\$: chr [1:8] "intercept" "rgpa" "rsmoke" "cgpa" ...

**Examples**

```
data(YX_bin)
gof_stats(YX_bin$Y)
```

---

YX\_bin\_list

---

*Synthetic longitudinal binary relational data, list-form (latent-scale)*


---

### Description

The list-form sibling of [YX\\_bin\\_long](#): same synthetic 4-period 50-actor panel reshaped from arrays to lists. The shipped  $Y$  entries hold the *latent probit-scale predictor* (range roughly -20 to 17), not 0/1 ties. To recover the binary tie indicator the dataset name implies, threshold at zero, e.g. `Y_bin <- lapply(YX_bin_list$Y, function(Yt) 1 * (Yt > 0))`. If passed unthresholded to `lame(..., family = "binary")` the fit will warn and silently apply the same  $Y > 0$  threshold.

### Format

A list with two elements:

**Y** List of 4 numeric matrices, each [50, 50], with NA on the diagonal. Latent probit-scale predictor; threshold at 0 for the binary indicator.

**X** List of 4 numeric arrays, each [50, 50, 3] of dyadic covariates.

---

YX\_bin\_long

---

*synthetic longitudinal binary relational data (latent-scale)*


---

### Description

a synthetic 50-actor, 4-period dataset used by the vignettes. The shipped  $Y$  array holds the *latent probit-scale predictor* (range roughly -24 to 20), not 0/1 ties. To recover the binary tie indicator the dataset name implies, threshold at zero: `Y_bin <- (YX_bin_long$Y > 0) * 1`. If passed unthresholded to `lame(..., family = "binary")` the fit will warn and silently apply the same  $Y > 0$  threshold.

### Usage

```
data(YX_bin_long)
```

### Format

A list with two elements:

**Y** Numeric array [50, 50, 4]. Latent probit-scale predictor; threshold at 0 to get the binary tie indicator.

**X** Numeric array [50, 50, 3, 4] of dyadic covariates.

**Examples**

```
data(YX_bin_long)
# threshold latent z to 0/1 before computing binary GOF stats
Yt <- 1 * (YX_bin_long$Y[, , 1] > 0)
diag(Yt) <- NA
gof_stats(Yt)
```

YX\_cbin

*Censored binary nomination data and covariates***Description**

a synthetic dataset that includes relational data where the number of nominations per row is censored at 10, along with information on eight covariates

**Usage**

```
data(YX_cbin)
```

**Format**

The format is: List of 2 \$ Y: num [1:100, 1:100] NA 0 0 0 1 0 0 0 0 3 ... \$ X: num [1:100, 1:100, 1:8] 1 1 1 1 1 1 1 1 1 1 ... ..- attr(\*, "dimnames")=List of 3 .. ..\$: NULL .. ..\$: NULL .. ..\$: chr [1:8] "intercept" "rgpa" "rsmoke" "cgpa" ...

**Examples**

```
data(YX_cbin)
gof_stats(YX_cbin$Y)
```

YX\_frn

*Fixed rank nomination data and covariates***Description**

a synthetic dataset that includes fixed rank nomination data as well as information on eight covariates

**Usage**

```
data(YX_frn)
```

**Format**

The format is: List of 2 \$ Y: num [1:100, 1:100] NA 0 0 0 1 0 0 0 0 3 ... \$ X: num [1:100, 1:100, 1:8] 1 1 1 1 1 1 1 1 1 1 ... ..- attr(\*, "dimnames")=List of 3 .. ..\$ : NULL .. ..\$ : NULL .. ..\$ : chr [1:8] "intercept" "rgpa" "rsmoke" "cgpa" ...

**Examples**

```
data(YX_frn)
gof_stats(YX_frn$Y)
```

---

|        |                                              |
|--------|----------------------------------------------|
| YX_nrm | <i>normal relational data and covariates</i> |
|--------|----------------------------------------------|

---

**Description**

a synthetic dataset that includes continuous (normal) relational data as well as information on eight covariates

**Usage**

```
data(YX_nrm)
```

**Format**

The format is: List of 2 \$ Y: num [1:100, 1:100] NA -4.05 -0.181 -3.053 -1.579 ... \$ X: num [1:100, 1:100, 1:8] 1 1 1 1 1 1 1 1 1 1 ... ..- attr(\*, "dimnames")=List of 3 .. ..\$ : NULL .. ..\$ : NULL .. ..\$ : chr [1:8] "intercept" "rgpa" "rsmoke" "cgpa" ...

**Examples**

```
data(YX_nrm)
gof_stats(YX_nrm$Y)
```

---

|        |                                               |
|--------|-----------------------------------------------|
| YX_ord | <i>ordinal relational data and covariates</i> |
|--------|-----------------------------------------------|

---

**Description**

a synthetic dataset that includes ordinal relational data as well as information on seven covariates

**Usage**

```
data(YX_ord)
```



**Format**

The format is: List of 2 \$ Y: num [1:100, 1:100] NA 0 3 0 3 1 0 1 1 0 ... \$ X: num [1:100, 1:100, 1:7] 1 1 1 1 1 1 1 1 1 1 ... ..- attr(\*, "dimnames")=List of 3 .. ..\$: NULL .. ..\$: NULL .. ..\$: chr [1:7] "rgpa" "rsmoke" "cgpa" "csmoke" ...

**Examples**

```
data(YX_ord)
gof_stats(YX_ord$Y)
```

---

|         |                            |
|---------|----------------------------|
| zscores | <i>rank-based z-scores</i> |
|---------|----------------------------|

---

**Description**

Maps a numeric vector to normal quantiles determined by the ranks of its observed entries, leaving missing values as NA.

**Usage**

```
zscores(y)
```

**Arguments**

y                      a numeric vector

**Value**

a numeric vector of the same length as y

**Author(s)**

lame authors

# Index

- \* **Initialize**
  - bipartite\_helpers, 48
- \* **bipartite**
  - bipartite\_helpers, 48
- \* **datasets**
  - addhealthc3, 16
  - addhealthc9, 16
  - vignette\_data, 225
  - Xcol, 228
  - Xdyad, 228
  - Xrow, 228
  - Y, 229
  - YX\_bin, 229
  - YX\_bin\_list, 230
  - YX\_bin\_long, 230
  - YX\_cbin, 231
  - YX\_frn, 231
  - YX\_nrm, 232
  - YX\_ord, 232
- \* **internal**
  - .actor\_ffbs\_path, 8
  - .ame\_propagate\_cov\_na, 9
  - .build\_full\_design, 9
  - .exact\_center\_per\_actor, 10
  - .fit\_actor\_order, 10
  - .reorder\_newdata\_actors, 11
  - .rotation\_drift\_diagnostic, 11
  - .sweep\_per\_actor\_exact, 12
  - .xbeta\_newdata, 13
  - bipartite\_helpers, 48
  - compute\_gof\_bipartite, 54
  - design\_array, 59
  - ffbs\_vecG, 65
  - lame-package, 7
  - list\_to\_array\_bipartite, 118
  - log\_phi\_diff, 119
  - precomputeX, 130
  - raSab\_bin\_fc, 145
  - raSab\_cbin\_fc, 146
  - raSab\_frn\_fc, 147
  - rbeta\_ab\_fc, 149
  - rbeta\_ab\_rep\_fc, 150
  - reexports, 152
  - rrho\_mh, 156
  - rs2\_fc, 157
  - rs2\_rep\_fc, 157
  - rSuv\_fc, 159
  - rtnorm\_interval\_logp, 160
  - rUV\_fc, 167
  - rUV\_rep\_fc, 168
  - rwish, 170
  - rZ\_bin\_fc, 171
  - rZ\_cbin\_bip\_fc, 172
  - rZ\_cbin\_fc, 173
  - rZ\_frn\_bip\_fc, 173
  - rZ\_frn\_fc, 174
  - rZ\_ord\_bip\_fc, 176
  - rZ\_ord\_explicit\_fc, 177
  - rZ\_ord\_fc, 177
  - rZ\_ord\_sym\_explicit\_fc, 178
  - rZ\_ord\_sym\_fc, 179
  - rZ\_pois\_bip\_fc, 179
  - sample\_ab\_bipartite, 181
  - sample\_alpha\_cowles, 182
  - sample\_rho\_G\_mh, 188
  - sample\_sigma\_G2, 191
  - simY\_bin, 201
  - simY\_frn, 202
  - simY\_nrm, 203
  - simY\_ord, 203
  - simZ, 205
  - sm2el, 205
  - update\_variances\_bipartite, 220
  - zscores, 233
- \* **starting**
  - bipartite\_helpers, 48
- \* **values**
  - bipartite\_helpers, 48

- .actor\_ffbs\_path, 8
- .ame\_propagate\_cov\_na, 9
- .build\_full\_design, 9, 13
- .exact\_center\_per\_actor, 10
- .fit\_actor\_order, 10, 11
- .reorder\_newdata\_actors, 11
- .rotation\_drift\_diagnostic, 11
- .sweep\_per\_actor\_exact, 12
- .xbeta\_newdata, 13
  
- ab\_plot, 13, 15, 51, 126, 128
- ab\_plot.ame\_als, 15, 34
- absdiff, 28
- absdiff (nodematch), 123
- addhealthc3, 16
- addhealthc9, 16
- als\_dynamic\_beta, 17, 103, 106
- als\_start\_vals, 18, 94, 96
- ame, 7, 9, 18, 19, 31–34, 36, 42, 45, 78, 95, 97, 103, 105, 106, 126, 129, 210
- ame\_als, 7, 18, 23, 29, 35–39, 46, 57, 104, 106, 126, 132, 153, 219, 224
- ame\_als\_bootstrap, 7, 31, 33, 34, 35, 37, 39, 52, 57, 58, 106, 196, 215, 224
- ame\_als\_refit, 35, 37, 37, 219
- ame\_memory\_settings, 39
- ame\_memory\_usage, 40
- ame\_options, 40
- ame\_parallel, 42, 108
- array\_to\_list, 43
- as\_draws, 44
- as\_draws.ame, 44
- as\_draws.ame\_als (as\_draws.ame), 44
- as\_draws.lame (as\_draws.ame), 44
- as\_lame\_y, 27, 45
- autoplot, 152
- autoplot (reexports), 152
- autoplot.ame (autoplot.lame), 47
- autoplot.ame\_als, 46
- autoplot.lame, 46, 47
- autoplot.lame\_als (autoplot.ame\_als), 46
  
- bipartite\_helpers, 48
- boot\_ame (ame\_als\_bootstrap), 35
- boot\_ame-no-fitted, 48
  
- check\_format, 49
- coef.als\_dynamic\_beta, 50
- coef.ame, 29, 51
- coef.ame\_als, 52
- coef.boot\_ame, 52
- coef.lame, 103
- coef.lame (coef.ame), 51
- coldwar, 53
- combine\_ame\_chains, 53
- compact\_ame, 54
- compute\_gof\_bipartite, 54
- compute\_mcmc\_diagnostics, 55
- compute\_XtX\_Xty\_bip\_cpp, 55
- comtrade, 56
- confint, 23, 99
- confint.ame, 51, 56
- confint.ame\_als, 31, 46, 57, 106
- confint.boot\_ame, 37, 52, 57, 58
- confint.lame, 212
- confint.lame (confint.ame), 56
  
- design\_array, 59
- design\_array\_listwisedel, 59
- detect\_change\_point, 60
- dutchcollege, 61
- dynamic\_beta\_prior\_summary, 62, 93
  
- el2sm, 63
- evaluate\_heldout, 64
  
- ffbs\_vecG, 65
- fitted, 48
- fitted.ame, 66, 153
- fitted.ame\_als, 67
- fitted.boot\_ame (boot\_ame-no-fitted), 48
- fitted.lame, 67
- forecast\_pit, 68
- formula.ame, 69
- formula.lame (formula.ame), 69
  
- get\_design\_rep, 70
- get\_EZ\_dynamic\_beta\_cpp, 71
- get\_fit\_object, 72
- get\_start\_vals, 74
- ginv, 32
- glance, 75
- glance.ame, 75
- glance.ame\_als, 76
- glance.lame (glance.ame), 75
- glance.lame\_als (glance.ame\_als), 76
- gof, 26, 29, 77, 103, 119
- gof\_plot, 26, 29, 78, 79, 82, 84, 103, 119, 126, 128

- gof\_plot.ame\_als, [34](#), [79](#), [82](#)
- gof\_stats, [83](#)
- gof\_stats\_bipartite, [85](#)
- gof\_stats\_unipartite, [86](#)
- gof\_temporal, [87](#)
- init\_bipartite\_startvals  
    (bipartite\_helpers), [48](#)
- init\_dynamic\_ab\_cpp, [88](#)
- init\_dynamic\_positions, [89](#)
- IR90s, [90](#)
- lame, [7](#), [9](#), [17](#), [18](#), [22](#), [23](#), [29](#), [31–34](#), [36](#), [42](#),  
    [45](#), [78](#), [90](#), [104–106](#), [108](#), [110](#), [111](#),  
    [128](#), [206–208](#), [212](#)
- lame-package, [7](#)
- lame\_als, [7](#), [17](#), [18](#), [34–37](#), [46](#), [99](#), [103](#), [104](#),  
    [126](#), [132](#), [153](#)
- lame\_multi, [42](#), [107](#)
- lame\_parallel, [108](#), [108](#)
- lame\_resume, [98](#), [99](#), [103](#), [109](#)
- lame\_snap\_als, [34](#), [99](#), [103](#), [106](#), [110](#),  
    [206–208](#)
- latent\_positions, [24](#), [29](#), [34](#), [51](#), [103](#), [114](#),  
    [144](#)
- lazegalaw, [116](#)
- lfo, [116](#)
- list\_to\_array, [117](#)
- list\_to\_array\_bipartite, [118](#)
- log\_phi\_diff, [119](#)
- logLik.ame, [118](#), [122](#)
- logLik.ame\_als, [119](#)
- logLik.lame (logLik.ame), [118](#)
- loo, [120](#), [120](#)
- loo.ame, [120](#)
- loo.ame\_als (loo.ame), [120](#)
- loo.lame (loo.ame), [120](#)
- mhalf, [122](#)
- nobs.ame, [122](#), [123](#)
- nobs.ame\_als, [123](#)
- nobs.lame (nobs.ame), [122](#)
- nodefactor, [28](#)
- nodefactor (nodematch), [123](#)
- nodematch, [28](#), [123](#)
- per\_actor\_slopes, [124](#)
- plot.ame, [125](#)
- plot.ame\_als, [126](#)
- plot.lame, [127](#)
- posterior\_options, [22](#), [96](#), [97](#), [115](#), [128](#), [201](#)
- posterior\_quantiles, [129](#)
- precomputeX, [130](#)
- predict.ame, [51](#), [66](#), [130](#), [136](#), [153](#)
- predict.ame\_als, [132](#)
- predict.lame, [132](#)
- prediction\_draws\_long, [134](#)
- print.als\_dynamic\_beta, [135](#)
- print.ame, [135](#)
- print.ame.sim, [136](#)
- print.ame\_als, [137](#)
- print.boot\_ame, [138](#)
- print.gof\_temporal, [138](#)
- print.lame, [139](#)
- print.lame.sim (print.ame.sim), [136](#)
- print.lame\_multi, [139](#)
- print.lfo\_lame, [140](#)
- print.per\_actor\_slopes, [140](#)
- print.summary.ame, [141](#), [210](#)
- print.summary.ame\_als, [141](#)
- print.summary.boot\_ame  
    (summary.boot\_ame), [211](#)
- print.summary.lame, [142](#), [212](#)
- prior\_summary, [142](#)
- procrustes\_align, [24](#), [29](#), [103](#), [115](#), [143](#)
- raSab\_bin\_fc, [145](#)
- raSab\_cbin\_fc, [146](#)
- raSab\_frn\_fc, [147](#)
- rbeta\_ab\_bip\_gibbs\_cpp, [148](#)
- rbeta\_ab\_fc, [149](#)
- rbeta\_ab\_rep\_fc, [150](#)
- read\_log\_lik, [151](#)
- reconstruct\_EZ, [151](#)
- reconstruct\_UVPM (reconstruct\_EZ), [151](#)
- reexports, [152](#)
- residuals, [48](#)
- residuals.ame, [66](#), [152](#)
- residuals.ame\_als, [153](#)
- residuals.boot\_ame  
    (boot\_ame-no-fitted), [48](#)
- residuals.lame, [154](#)
- rhat\_dynamic\_beta, [154](#)
- rmvnorm, [155](#)
- rrho\_mh, [156](#)
- rs2\_fc, [157](#)
- rs2\_rep\_fc, [157](#)

- rSab\_fc, 158
- rSuv\_fc, 159
- rtnorm\_interval\_logp, 160
- rUV\_dynamic\_bip\_fc\_cpp, 161
- rUV\_dynamic\_fc, 161
- rUV\_dynamic\_fc\_cpp, 162
- rUV\_dynamic\_snap\_fc, 163
- rUV\_dynamic\_snap\_fc\_cpp, 164
- rUV\_dynamic\_t\_fc, 165
- rUV\_dynamic\_t\_fc\_cpp, 166
- rUV\_fc, 167
- rUV\_rep\_fc, 168
- rUV\_sym\_fc, 169
- rwish, 170
- rZ\_bin\_bip\_batch\_cpp, 171
- rZ\_bin\_fc, 171
- rZ\_cbin\_bip\_fc, 172
- rZ\_cbin\_fc, 172, 173
- rZ\_frnl\_bip\_fc, 173
- rZ\_frnl\_fc, 173, 174
- rZ\_nrm\_batch\_cpp, 175
- rZ\_nrm\_fc, 176
- rZ\_ord\_bip\_fc, 176
- rZ\_ord\_explicit\_fc, 177
- rZ\_ord\_fc, 176, 177, 177, 179
- rZ\_ord\_sym\_explicit\_fc, 178
- rZ\_ord\_sym\_fc, 178, 179
- rZ\_pois\_bip\_fc, 179
- rZ\_pois\_fc, 179, 180
  
- sample\_ab\_bipartite, 181
- sample\_alpha\_cowles, 182
- sample\_beta\_dynamic\_cpp, 183
- sample\_beta\_static\_cpp, 184
- sample\_dynamic\_ab\_cpp, 185
- sample\_rho\_ab\_cpp, 186
- sample\_rho\_beta\_cpp, 187
- sample\_rho\_Gmh, 188
- sample\_rho\_uv, 188
- sample\_sigma\_ab\_cpp, 189
- sample\_sigma\_beta\_cpp, 190
- sample\_sigma\_G2, 191
- sample\_sigma\_uv, 191
- sampler\_describe, 181
- sampsonmonks, 192
- sheep, 192
- simulate.ame, 136, 193
- simulate.ame\_als, 34, 82, 196
- simulate.lame, 196
  
- simulate\_posterior, 200
- simY\_bin, 201
- simY\_frnl, 202
- simY\_nrm, 203
- simY\_ord, 203
- simY\_pois, 204
- simZ, 205
- sm2el, 205
- snap\_category\_summary, 206
- snap\_index\_draws, 207
- snap\_index\_summary, 207
- snap\_rank\_summary, 208
- summary.ame, 29, 51, 136, 209
- summary.ame.sim, 210
- summary.ame\_als, 210
- summary.boot\_ame, 211
- summary.lame, 103, 211
- summary.lame.sim, 213
  
- t, 8
- tidy, 213
- tidy.ame, 214
- tidy.ame\_als, 215
- tidy.boot\_ame, 216
- tidy.lame(tidy.ame), 214
- tidy.lame\_als(tidy.ame\_als), 215
- trace\_plot, 34, 126, 128, 216
  
- update, 218, 219
- update.ame, 218, 219
- update.ame\_als, 219
- update.lame(update.ame), 218
- update.lame\_als(update.ame\_als), 219
- update\_variances\_bipartite, 220
- uv\_plot, 34, 115, 126, 128, 144, 220
  
- vcov.ame, 51, 223
- vcov.ame\_als, 33, 46, 57, 215, 224
- vcov.boot\_ame, 52, 225
- vcov.lame(vcov.ame), 223
- vignette\_data, 225, 228, 229
  
- waic, 226
- waic(loo), 120
- waic.ame, 226
- waic.ame\_als(waic.ame), 226
- waic.lame(waic.ame), 226
  
- Xbeta, 227

Xbeta\_bip\_cpp, [227](#)  
Xcol, [228](#)  
Xdyad, [228](#)  
Xrow, [228](#)  
  
Y, [229](#)  
YX\_bin, [229](#)  
YX\_bin\_list, [230](#)  
YX\_bin\_long, [230](#), [230](#)  
YX\_cbin, [231](#)  
YX\_frn, [231](#)  
YX\_nrm, [232](#)  
YX\_ord, [232](#)  
  
zscores, [233](#)