

Package ‘lame’

July 12, 2026

Title Longitudinal Additive and Multiplicative Effects Models for Networks

Version 1.3.1

Description Tools for Additive and Multiplicative Effects (AME) models for both cross-sectional and longitudinal network analysis. The package provides two main functions: 'ame()' for cross-sectional networks and 'lame()' for longitudinal networks. Package supports unipartite (square) and bipartite (rectangular) network structures. Key features include: (1) Cross-sectional network analysis via 'ame()' with support for various data types (binary, continuous, ordinal, count); (2) Longitudinal network analysis via 'lame()' with dynamic effects modeling where both additive (sender/receiver) and multiplicative (latent factor) effects can be chosen to evolve over time via AR(1) processes (Sewell & Chen 2015 <[doi:10.1080/01621459.2014.988214](https://doi.org/10.1080/01621459.2014.988214)>, Durante & Dunson 2014 <[doi:10.1093/biomet/asu040](https://doi.org/10.1093/biomet/asu040)>); (3) Handling of changing actor compositions across time periods in longitudinal models; (4) Performance improvements through C++ implementations via 'Rcpp' and 'RcppArmadillo'.

Author Cassy Dorff [aut], Shahryar Minhas [aut, cre], Tosin Salau [aut]

Maintainer Shahryar Minhas <minhassh@msu.edu>

License MIT + file LICENSE

URL <https://netify-dev.github.io/lame/>,
<https://github.com/netify-dev/lame>

BugReports <https://github.com/netify-dev/lame/issues>

Depends R (>= 3.5.0)

Encoding UTF-8

LazyData true

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.3

LinkingTo Rcpp, RcppArmadillo

Imports Rcpp, ggplot2, ggrepel, ggforce, gridExtra, coda, patchwork, cli, MASS, Matrix, abind, netify (>= 1.5.3), graphics, grDevices, parallel, stats, utils

Suggests knitr, rmarkdown, testthat (>= 3.0.0), igraph, network,
posterior, loo, digest, tibble, broom, generics, pROC, precrec,
statmod, dplyr, modelsummary

VignetteBuilder knitr

Config/testthat/edition 3

NeedsCompilation yes

R topics documented:

lame-package	7
.actor_ffbs_path	8
.ame_propagate_cov_na	9
.build_full_design	9
.exact_center_per_actor	10
.fit_actor_order	10
.reorder_newdata_actors	11
.rotation_drift_diagnostic	11
.sweep_per_actor_exact	12
.xbeta_newdata	13
ab_plot	13
ab_plot.ame_als	15
addhealthc3	16
addhealthc9	16
als_dynamic_beta	17
als_start_vals	18
ame	19
ame_als	29
ame_als_bootstrap	34
ame_als_refit	37
ame_memory_settings	38
ame_memory_usage	39
ame_options	40
ame_parallel	41
array_to_list	42
as_draws	43
as_draws.ame	43
as_lame_y	44
autoplot.ame_als	45
autoplot.lame	46
bipartite_helpers	47
boot_ame-no-fitted	47
check_format	48
coef.als_dynamic_beta	49
coef.ame	50
coef.ame_als	51
coef.boot_ame	51
coldwar	52

combine_ame_chains	52
compact_ame	53
compute_gof_bipartite	53
compute_mcmc_diagnostics	54
compute_XtX_Xty_bip_cpp	54
comtrade	55
confint.ame	55
confint.ame_als	56
confint.boot_ame	57
design_array	58
design_array_listwisedel	58
detect_change_point	59
dutchcollege	60
dynamic_beta_prior_summary	61
el2sm	62
evaluate_heldout	63
ffbs_vecG	64
fitted.ame	65
fitted.ame_als	66
fitted.lame	66
forecast_pit	67
formula.ame	68
get_design_rep	69
get_EZ_dynamic_beta_cpp	70
get_fit_object	71
get_start_vals	73
glance	74
glance.ame	74
glance.ame_als	75
gof	76
gof_plot	78
gof_plot.ame_als	81
gof_stats	82
gof_stats_bipartite	84
gof_stats_unipartite	85
gof_temporal	86
init_dynamic_ab_cpp	87
init_dynamic_positions	88
IR90s	89
lame	89
lame_als	103
lame_multi	106
lame_parallel	107
lame_resume	108
lame_snap_als	109
latent_positions	113
lazegalaw	114
ldZgbme	115

lfo	116
list_to_array	117
list_to_array_bipartite	117
llsrmRho	118
logLik.ame	118
logLik.ame_als	119
log_phi_diff	120
loo	120
loo.ame	121
mhalf	122
nobs.ame	122
nobs.ame_als	123
nodematch	124
per_actor_slopes	125
plot.ame	126
plot.ame_als	127
plot.lame	127
posterior_options	129
posterior_quantiles	130
precomputeX	130
predict.ame	131
predict.ame_als	132
predict.lame	133
prediction_draws_long	134
print.als_dynamic_beta	135
print.ame	136
print.ame.sim	137
print.ame_als	138
print.boot_ame	138
print.gof_temporal	139
print.lame	139
print.lame_multi	140
print.lfo_lame	140
print.per_actor_slopes	141
print.summary.ame	141
print.summary.ame_als	142
print.summary.lame	142
prior_summary	143
procrustes_align	143
raSab_bin_fc	145
raSab_cbin_fc	146
raSab_frn_fc	147
rbeta_ab_bip_gibbs_cpp	148
rbeta_ab_fc	149
rbeta_ab_rep_fc	150
read_log_lik	150
reconstruct_EZ	151
reexports	152

residuals.ame	152
residuals.ame_als	153
residuals.lame	153
rhat_dynamic_beta	154
rmvnorm	155
rrho_fc	155
rrho_mh	156
rrho_mh_rep	157
rs2_fc	157
rs2_rep_fc	158
rSab_fc	159
rSuv_fc	160
rtnorm_interval_logp	161
rUV_dynamic_bip_fc_cpp	161
rUV_dynamic_fc	162
rUV_dynamic_fc_cpp	163
rUV_dynamic_snap_fc	164
rUV_dynamic_snap_fc_cpp	165
rUV_dynamic_t_fc	166
rUV_dynamic_t_fc_cpp	167
rUV_fc	168
rUV_rep_fc	169
rUV_sym_fc	169
rwish	170
rZ_bin_bip_batch_cpp	171
rZ_bin_fc	171
rZ_cbin_bip_fc	172
rZ_cbin_fc	173
rZ_frn_bip_fc	174
rZ_frn_fc	175
rZ_nrm_batch_cpp	176
rZ_nrm_fc	176
rZ_ord_bip_fc	177
rZ_ord_explicit_fc	178
rZ_ord_fc	178
rZ_ord_sym_explicit_fc	179
rZ_ord_sym_fc	179
rZ_pois_bip_fc	180
rZ_pois_fc	181
sampler_describe	181
sample_ab_bipartite	182
sample_alpha_cowles	183
sample_beta_dynamic_cpp	183
sample_beta_static_cpp	185
sample_dynamic_ab_cpp	186
sample_rho_ab_cpp	187
sample_rho_beta_cpp	187
sample_rho_G_mh	188

sample_rho_uv	189
sample_sigma_ab_cpp	190
sample_sigma_beta_cpp	191
sample_sigma_G2	191
sample_sigma_uv	192
sampsonmonks	193
sheep	193
simulate.ame	194
simulate.ame_als	197
simulate.lame	197
simulate_posterior	201
simY_bin	202
simY_frn	203
simY_nrm	204
simY_ord	204
simY_pois	205
simZ	205
sm2el	206
snap_category_summary	206
snap_index_draws	207
snap_index_summary	208
snap_rank_summary	208
summary.ame	209
summary.ame.sim	210
summary.ame_als	211
summary.boot_ame	211
summary.lame	212
summary.lame.sim	213
tidy	214
tidy.ame	214
tidy.ame_als	215
tidy.boot_ame	216
trace_plot	217
update.ame	219
update.ame_als	220
update_variances_bipartite	221
uv_plot	221
vcov.ame	224
vcov.ame_als	224
vcov.boot_ame	225
vignette_data	226
waic.ame	227
Xbeta	227
Xbeta_bip_cpp	228
Xcol	228
Xdyad	229
Xrow	229
Y	229

YX_bin	230
YX_bin_list	230
YX_bin_long	231
YX_cbin	231
YX_frn	232
YX_nrm	232
YX_ord	233
zscores	233
Index	235

lame-package	<i>Longitudinal Additive and Multiplicative Effects Models for Networks</i>
--------------	---

Description

An extension of the 'amen' package specifically designed for longitudinal network analysis. This package provides tools for fitting Additive and Multiplicative Effects (AME) models to longitudinal/replicated relational data with several extensions: (1) handling of changing actor compositions across time periods, allowing for networks with different sets of actors at each time point; (2) significant performance improvements through C++ implementations via Rcpp and RcppArmadillo; (3) specialized functions for temporal network dynamics. The package supports six data types: normal (nrm), binary (bin), ordinal (ord), Poisson count (poisson), censored binary (cbin), and fixed-rank nomination (frn). Based on the AME framework originally developed by Hoff (2009) and Hoff, Fosdick, Volfovsky and Stovel (2013).

Details

Estimators. The package offers two estimation routes:

- [ame](#) / [lame](#) – the Bayesian MCMC estimators, for calibrated posterior inference (cross-sectional and longitudinal respectively).
- [ame_als](#) / [lame_als](#) – a fast, MCMC-free point estimator by iterative block coordinate descent, with bootstrap uncertainty via [ame_als_bootstrap](#). Use it for rapid model exploration, rank selection and starting values; use the MCMC estimators for final inference.

Package: lame
Type: Package
License: MIT

Author(s)

Shahryar Minhas, Tosin Salau, Cassy Dorff
Maintainer: Shahryar Minhas minhassh@msu.edu

Examples

```
data(YX_nrm)
fit <- ame(YX_nrm$Y, Xdyad = YX_nrm$X, burn = 10, nscan = 100, odens = 1,
          family = "normal", verbose = FALSE)
summary(fit)
```

.actor_ffbs_path

Univariate Carter-Kohn FFBS for one actor's length-T slope path

Description

Given period-wise sufficient statistics ($H_t = \sum_j X_{ij}^2 / s^2$, $h_t = \sum_j X_{ij} R_{ij} / s^2$) and AR(1) hyperparameters, returns one joint draw from the posterior $N(m, P)$ where the prior is AR(1) and the observation is the Gaussian likelihood implied by (H, h) .

Usage

```
.actor_ffbs_path(H, h, rho_actor, sigma_actor2)
```

Arguments

H	length-T vector of period-wise observation precisions
h	length-T vector of period-wise observation cross-products
rho_actor	AR(1) coefficient
sigma_actor2	AR(1) innovation variance

Value

list with theta (length-T draw) and V (length-T marginal posterior variance per period – needed for the exact centering projection).

`.ame_propagate_cov_na` *Propagate covariate missingness into the response*

Description

For an AME fit, a dyad whose covariate value is missing cannot contribute a covariate-coefficient observation. Rather than silently imputing the missing covariate as 0 (which biases the coefficient when the covariate is not mean-centred), the dyad is treated as an unobserved tie and handled by data augmentation. This helper sets the affected Y cells to NA; `lame` already does this internally, and this brings `ame` into line.

Usage

```
.ame_propagate_cov_na(Y, Xrow = NULL, Xcol = NULL, Xdyad = NULL)
```

Arguments

`Y` an n x n response matrix.
`Xrow, Xcol, Xdyad` row, column and dyadic covariates (or NULL).

Value

Y with covariate-missing cells set to NA.

`.build_full_design` *Build the full canonical design for a newdata prediction*

Description

Build the full canonical design for a newdata prediction

Usage

```
.build_full_design(newdata, model_names, fitted_design, n, m)
```

Arguments

`newdata` an n x m x n_dyad array (or n x m matrix) of new dyadic covariates. If its 3rd-dim names match the model's dyadic coefficient names they are mapped by name; otherwise the slices are taken in order as the model's dyadic covariates.
`model_names` the model's coefficient names (`colnames(fit$BETA) / dimnames(fit$BETA)[[2]]`), in canonical layout.
`fitted_design` the model's fitted design array (`fit$X` or `Xlist[[t]]`); used to hold intercept + nodal slices fixed. May be NULL only when the model has no nodal covariates.
`n, m` output dimensions.

Value

an $n \times m \times \text{length}(\text{model_names})$ array whose slices are in `model_names` order: dyadic slices from `newdata`, all other slices held at their fitted values (`intercept = 1`).

`.exact_center_per_actor`

Exact variance-weighted sum-to-zero projection for the per-actor block

Description

Given an unconstrained sample `theta_star` ($n_{\text{actors}} \times T$) and per-actor per-period posterior variances `V` (same shape), projects to the sum-to-zero manifold per period using the variance-weighted Lagrangian projection (exact under block-diagonal covariance across actors).

Usage

`.exact_center_per_actor(theta_star, V)`

`.fit_actor_order`

The fit's internal (canonical) actor order

Description

`lame()` sorts actors alphabetically when it ingests a list of `Y` matrices (via `list_to_array`), so the stored additive / multiplicative effects and design slices are in sorted actor order, which need not match the order a user later supplies in `newdata`. This returns the row and column actor names the fit was estimated in, tried from the most authoritative source down, so `newdata` can be realigned by name before prediction.

Usage

`.fit_actor_order(object)`

Arguments

`object` a fitted `lame` (or `ame`) object.

Value

a list with `rows` and `cols` character vectors (or `NULL` when the order cannot be recovered).

`.reorder_newdata_actors`

Realign a newdata covariate array to the fit's internal actor order

Description

Reorders the rows and columns of each $n \times m \times p$ slice by their dimnames so they line up with the fit's stored (sorted) additive / multiplicative effects. Only acts when newdata carries dimnames whose name set exactly matches the fit's; otherwise it falls back to the supplied positional order unchanged (the historical behaviour, correct when the user already passes actors in the fit's order or supplies no names).

Usage

```
.reorder_newdata_actors(X, row_order, col_order)
```

Arguments

`X` an $n \times m \times p$ array (already promoted from a matrix).
`row_order, col_order` canonical actor names from `.fit_actor_order`.

Value

`X` with rows / columns permuted into canonical order, or unchanged.

`.rotation_drift_diagnostic`

Rotation-drift diagnostic for the canonical (U_t , G_t , V_t) trio

Description

Reports a scalar ratio comparing the variance of the *raw* G_t entries (per element across t) to the variance of the *canonical* G_t entries (after per-period SVD). When the raw / canonical variance ratio is large (≥ 5), the apparent G_t time-variation is dominated by rotation drift in U_t , V_t rather than real temporal change. The canonicalisation removes that rotation and the canonical entries should be the user-facing summary.

Usage

```
.rotation_drift_diagnostic(G_cube_raw, U_cube, V_cube)
```

Arguments

G_cube_raw	RA x RB x T raw (FFBS-sampled) G cube
U_cube	nA x RA x T raw U cube
V_cube	nB x RB x T raw V cube

Value

list with ratio (numeric), var_raw (RA x RB), var_canonical (RA x RB), flag (logical: ratio >= 5)

.sweep_per_actor_exact

Per-actor sweep: unconstrained per-actor FFBS + exact projection

Description

One full sweep over actors: each actor's path is sampled from its conditional AR(1) posterior via `.actor_ffbs_path()`, and the joint sample is then projected to satisfy $\sum_i \theta_i(t) = 0$ per period using the variance-weighted Lagrangian.

Usage

```
.sweep_per_actor_exact(H_mat, h_mat, rho_actor, sigma_actor2)
```

Arguments

H_mat	n_actors x T precision sufficient statistics
h_mat	n_actors x T cross-product sufficient statistics
rho_actor	AR(1) coefficient
sigma_actor2	AR(1) innovation variance

Value

n_actors x T matrix of centered draws.

<code>.xbeta_newdata</code>	<i>Name-safe linear predictor from a newdata prediction</i>
-----------------------------	---

Description

Convenience wrapper: builds the full canonical design via `.build_full_design` and contracts it against a named coefficient vector. Because the design is rebuilt in the model's slice order, the positional contraction is correct even with nodal covariates.

Usage

```
.xbeta_newdata(beta, newdata, fitted_design, n, m)
```

Arguments

<code>beta</code>	named numeric coefficient vector (a single draw or the posterior mean).
<code>newdata</code>	dyadic covariate array (see <code>.build_full_design</code>).
<code>fitted_design</code>	fitted design array (<code>fit\$X</code>); held-fixed source for intercept + nodal slices.
<code>n, m</code>	output dimensions.

Value

an $n \times m$ matrix of the linear predictor.

<code>ab_plot</code>	<i>Visualize sender and receiver random effects</i>
----------------------	---

Description

Creates a visualization of the additive sender (row) and receiver (column) random effects from an AME or LAME model. Automatically detects whether effects are static or dynamic and provides appropriate visualization options.

Usage

```
ab_plot(
  fit,
  effect = c("sender", "receiver"),
  sorted = TRUE,
  labels = NULL,
  title = NULL,
  time_point = NULL,
  plot_type = c("snapshot", "trajectory", "faceted", "ribbon"),
  show_actors = NULL
)
```

Arguments

fit	An object of class "ame" or "lame" from fitting an AME model
effect	Character string specifying which effect to plot: "sender" (default) or "receiver"
sorted	Logical; if TRUE (default), actors are sorted by effect magnitude
labels	Logical; if TRUE, actor labels are shown on x-axis (default TRUE for $n \leq 50$ actors)
title	Optional title for the plot
time_point	For dynamic effects, which time point to plot (default: last). Can be numeric index, "all" for faceted plot, or "average" for time-averaged
plot_type	For dynamic effects: "snapshot" (single time), "trajectory" (evolution over time), "faceted" (grid of time points), or "ribbon" (posterior credible bands over time). For static effects, this parameter is ignored.
show_actors	Character vector of specific actors to highlight (for dynamic trajectory/ribbon plots)

Details

The additive effects in AME models represent:

Sender effects (a) Actor-specific tendencies to form outgoing ties. Positive values indicate actors who send more ties than expected; negative values indicate actors who send fewer ties.

Receiver effects (b) Actor-specific tendencies to receive incoming ties. Positive values indicate actors who receive more ties than expected; negative values indicate actors who receive fewer ties.

For static effects, the plot displays these effects as a dot plot with vertical lines extending from zero to each effect estimate.

For dynamic effects (when fit contains a_dynamic/b_dynamic), additional options are available to visualize how effects evolve over time.

Value

A ggplot2 object that can be further customized

Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

Examples

```
# Fit an AME model
data(YX_nrm)
fit <- ame(YX_nrm$Y, Xdyad = YX_nrm$X,
           nscan = 100, burn = 10, odens = 1, verbose = FALSE)

# Visualize sender effects
ab_plot(fit, effect = "sender")
```

```
# Visualize receiver effects without sorting
ab_plot(fit, effect = "receiver", sorted = FALSE)
```

ab_plot.ame_als	<i>Additive-effects plot for an ame_als fit</i>
-----------------	---

Description

Sender (a) and receiver (b) additive-effect point estimates as a sorted lollipop chart. Mirrors [ab_plot](#) but without posterior intervals: this is a point estimator. If the fit was produced via `ame_als(..., bootstrap = N)`, bootstrap 95\ error bars.

Usage

```
ab_plot.ame_als(
  fit,
  effect = c("sender", "receiver", "both"),
  top_n = Inf,
  ...
)
```

Arguments

<code>fit</code>	an <code>ame_als</code> fit.
<code>effect</code>	"sender" (default), "receiver", or "both".
<code>top_n</code>	integer; show only the top / bottom <code>top_n</code> actors by absolute effect (default <code>Inf</code> , show all).
<code>...</code>	reserved.

Value

A `ggplot` object.

addhealthc3

AddHealth community 3 data

Description

A valued sociomatrix (Y) and matrix of nodal attributes (X) for students in community 3 of the AddHealth study.

- Y: A sociomatrix in which the value of the edge corresponds to an ad-hoc measure of intensity of the relation. Note that students were only allowed to nominate up to 5 male friends and 5 female friends.
- X: Matrix of students attributes, including sex, race (1=white, 2=black, 3=hispanic, 4=asian, 5=mixed/other) and grade.

Originally available at <http://moreno.ss.uci.edu/data.html#adhealth> (site no longer accessible).

Usage

```
data(addhealthc3)
```

Format

```
list
```

addhealthc9

AddHealth community 9 data

Description

A valued sociomatrix (Y) and matrix of nodal attributes (X) for students in community 9 of the AddHealth study.

- Y: A sociomatrix in which the value of the edge corresponds to an ad-hoc measure of intensity of the relation. Note that students were only allowed to nominate up to 5 male friends and 5 female friends.
- X: Matrix of students attributes, including sex, race (1=white, 2=black, 3=hispanic, 4=asian, 5=mixed/other) and grade.

Originally available at <http://moreno.ss.uci.edu/data.html#adhealth> (site no longer accessible).

Usage

```
data(addhealthc9)
```

Format

```
list
```

als_dynamic_beta	<i>Penalised ALS time-varying coefficient estimate</i>
------------------	--

Description

Computes a fast point estimate of a time-varying coefficient vector β_t for a longitudinal network model by solving the first-difference-penalised least-squares problem. No MCMC, no multiplicative effects, no random effects – purely a regression point estimate with a smoothing penalty on the coefficient path. Useful for rapid exploration and for generating starting values for a full `lame(dynamic_beta = ...)` fit.

Usage

```
als_dynamic_beta(Y, Xdyad, lambda = 0, intercept = TRUE)
```

Arguments

<code>Y</code>	A list of T response matrices (or a 3-D array with third dimension time).
<code>Xdyad</code>	A list of T dyadic covariate arrays (each $n \times n \times p$, or a single $n \times n$ matrix if $p = 1$).
<code>lambda</code>	Non-negative smoothing parameter. Default 0 (no penalty, per-period OLS).
<code>intercept</code>	Logical; include an intercept (default TRUE).

Details

$$\min_{\beta_{1:T}} \sum_t \|y_t - X_t \beta_t\|^2 + \lambda \sum_{t=2}^T \|\beta_t - \beta_{t-1}\|^2$$

At $\lambda = 0$ this is T independent per-period OLS fits. As $\lambda \rightarrow \infty$ the solution converges to a single pooled β (constant over time).

Value

A list with `beta` (a $p \times T$ matrix of estimates), `lambda`, `residual_ss` (sum of squared residuals across periods), `intercept`, and `call`. Class "`als_dynamic_beta`".

Relation to other entry points

`als_dynamic_beta` is a *regression-only smoother*; the returned object carries time-varying β_t alone, no additive (a, b) or multiplicative (U, V) AME components. It is therefore not a special case of `lame_als` (which always estimates the full AME decomposition) and not a special case of `lame(dynamic_beta = TRUE)` (which is Bayesian with an AR(1) / RW1 / RW2 / Matern 3/2 state-space prior). Use it when you want a fast, point-only, deterministic smoother for the coefficient path; use `lame(dynamic_beta = ...)` when you need full posterior uncertainty and additive / multiplicative effects.

See Also

[lame](#) for the full Bayesian dynamic- β fit (AR(1) / RW1 / RW2 / Matern 3/2); [lame_als](#) for the longitudinal AME point estimator (static β , full a, b, U, V).

Examples

```
set.seed(1)
n <- 10; T <- 4
X <- replicate(T, array(rnorm(n*n*2), c(n, n, 2)), simplify = FALSE)
beta_true <- rbind(seq(-1, 1, length.out = T), seq(0.5, -0.5, length.out = T))
Y <- vector("list", T)
for (t in seq_len(T)) {
  Yt <- X[[t]][, , 1] * beta_true[1, t] + X[[t]][, , 2] * beta_true[2, t] +
    matrix(rnorm(n*n, 0, 0.2), n, n)
  diag(Yt) <- NA
  Y[[t]] <- Yt
}
fit_als <- als_dynamic_beta(Y, X, lambda = 0)      # per-period LS
fit_smooth <- als_dynamic_beta(Y, X, lambda = 10) # smoother path
```

als_start_vals

Convert an ALS fit to MCMC starting values

Description

Builds a `start_vals` list for [ame](#) or [lame](#) from an ALS point estimate. This is useful when the ALS fit has already found a good latent-space solution and the MCMC chain should start near that solution rather than from diffuse random values.

Usage

```
als_start_vals(fit, jitter = 0, seed = NULL)
```

Arguments

<code>fit</code>	a fitted ame_als , lame_als , or dynamic ALS object returned by lame with <code>method = "als"</code> .
<code>jitter</code>	non-negative standard deviation for independent Gaussian perturbations added to numeric starting values. Use a small positive value for multiple MCMC chains.
<code>seed</code>	optional integer seed used for the jitter.

Value

A list that can be passed to `start_vals`.

ame

*AME model fitting routine***Description**

An MCMC routine providing a fit to an additive and multiplicative effects (AME) regression model to cross-sectional relational data of various types. This function supports both unipartite (square) and bipartite (rectangular) networks. For longitudinal networks, use the `lame` function. Original implementation by Peter Hoff.

Usage

```
ame(
  Y,
  Xdyad = NULL,
  Xrow = NULL,
  Xcol = NULL,
  rvar = TRUE,
  cvar = TRUE,
  dcor = !symmetric,
  nvar = TRUE,
  R = 0,
  R_row = NULL,
  R_col = NULL,
  mode = c("unipartite", "bipartite"),
  family = "normal",
  intercept = !(family == "ordinal"),
  symmetric = FALSE,
  odmax = rep(max(apply(Y > 0, 1, sum, na.rm = TRUE)), nrow(Y)),
  prior = list(),
  g = NA,
  seed = 6886,
  nscan = 10000,
  burn = 500,
  odens = 25,
  verbose = TRUE,
  gof = TRUE,
  custom_gof = NULL,
  plot = FALSE,
  start_vals = NULL,
  periodic_save = FALSE,
  out_file = NULL,
  save_interval = 0.25,
  posterior_opts = NULL,
  n_chains = 1,
  cores = 1,
  use_sparse_matrices = FALSE,
```

```

method = c("mcmc", "als"),
bootstrap = 0L,
bootstrap_type = c("parametric", "block"),
bootstrap_block_length = 1L,
bootstrap_seed = NULL,
save_log_lik = FALSE,
ordinal_cutpoints = c("data_induced", "explicit"),
print,
...,
model.name = NULL
)

```

Arguments

Y	For unipartite: an $n \times n$ square relational matrix. For bipartite: an $nA \times nB$ rectangular relational matrix where nA is the number of row nodes and nB is the number of column nodes. A cross-sectional netify object is also accepted and converted with <code>netify::to_lame()</code> ; when family or mode is omitted, the value inferred by netify is used. See family below for data types.
Xdyad	For unipartite: an $n \times n \times n$ pd array of dyadic covariates (e.g. distance, shared group). For bipartite: an $nA \times nB \times n$ pd array. A 2-D matrix (single dyadic covariate) must be wrapped as <code>array(x, dim = c(n, n, 1))</code> ; Inf/NaN entries are rejected.
Xrow	For unipartite: an $n \times pr$ matrix of sender (row) covariates (e.g. sender's age, group). For bipartite: an $nA \times pr$ matrix of row-node covariates. A <code>data.frame</code> is accepted and coerced to numeric matrix internally.
Xcol	For unipartite: an $n \times pc$ matrix of receiver (column) covariates. For bipartite: an $nB \times pc$ matrix of column-node covariates. A <code>data.frame</code> is accepted and coerced internally.
rvar	logical: fit row random effects (asymmetric case)?
cvar	logical: fit column random effects (asymmetric case)?
dcor	logical: fit a dyadic correlation (asymmetric case)? Note: not used for bipartite networks.
nvar	logical: fit nodal random effects (symmetric case)?
R	integer: dimension of the multiplicative effects (can be zero). For bipartite networks, this is used as the default for both <code>R_row</code> and <code>R_col</code> if they are not specified.
R_row	integer: for bipartite networks, dimension of row node multiplicative effects (defaults to R)
R_col	integer: for bipartite networks, dimension of column node multiplicative effects (defaults to R)
mode	character: either "unipartite" (default) for square networks or "bipartite" for rectangular networks. Not all combinations of family and mode are supported – see the table under Supported family x mode combinations below.

family	character: one of "normal", "binary", "ordinal", "cbin", "frn", "poisson". See the Supported family x mode combinations table below for which combinations are valid; see Details for the model assumptions behind each family.
intercept	logical: fit model with an intercept?
symmetric	logical: Is the sociomatrix symmetric by design?
odmax	a scalar integer or vector of length n giving the maximum number of nominations that each node may make - used for "frn" and "cbin" families
prior	a list containing hyperparameters for the prior distributions. Available options and their defaults: Sab0 Prior covariance matrix for additive effects (default: <code>diag(2)</code>). A 2x2 matrix where <code>Sab0[1,1]</code> is the prior variance for row effects, <code>Sab0[2,2]</code> is the prior variance for column effects, and off-diagonals control correlation between row and column effects. eta0 Prior degrees of freedom for covariance of multiplicative effects (default: $4 + 3 \cdot n/100$, where n is the number of actors). Higher values impose stronger shrinkage on the latent factors. Common values: 4-10 for weak shrinkage, 10-20 for moderate, >20 for strong shrinkage. etaab Prior degrees of freedom for covariance of additive effects (default: $4 + 3 \cdot n/100$). Controls shrinkage of row/column random effects. Larger values shrink effects toward zero. <i>Used by the bipartite and longitudinal paths; ignored for a unipartite cross-sectional <code>ame()</code> fit, which controls the additive prior through <code>Sab0</code> and <code>eta0</code>.</i> s20 Prior variance for regression coefficients (default: 1). Larger values allow for larger coefficient values. <i>Used by the bipartite and longitudinal paths; for a unipartite <code>ame()</code> fit the regression prior is controlled by g.</i> s2u0 Prior variance for multiplicative effects (default: 1). <i>Used by the bipartite and longitudinal paths.</i> Suv0 Prior covariance for multiplicative effects (default: identity matrix). Common usage: <code>prior = list(Sab0 = diag(c(2, 2)), eta0 = 10)</code> for moderate shrinkage, or <code>prior = list(Sab0 = diag(c(0.5, 0.5)))</code> for tighter control. For a unipartite cross-sectional <code>ame()</code> fit the prior is controlled by <code>Sab0</code> , <code>eta0</code> , <code>Suv0</code> and <code>g</code> .
g	optional scalar for the Zellner g-prior on regression coefficients ($\beta \sim N(0, g \cdot \sigma^2 \cdot \text{solve}(XtX))$ where <code>XtX</code> is the design cross-product). If not specified, defaults are: for normal family, $g = n \cdot \text{var}(Y)$; for other families, $g = n$ (number of non-missing dyads). Per-coefficient (vector) <code>g</code> is not currently supported by the unipartite path – pass a scalar. <i>Note: g is a top-level argument to <code>ame()</code>, not an element of <code>prior = list(...)</code>; passing <code>prior = list(g = 0.1)</code> is a no-op (warned about).</i>
seed	random seed for the MCMC sampler (default 6886). The sampler is seeded internally with this value, so results are reproducible by default and an external <code>set.seed()</code> call has <i>no</i> effect on the chain – pass a different seed here to vary the draws (e.g. when running multiple chains). The caller's <code>.Random.seed</code> is restored on exit, so fitting never perturbs your RNG stream.
nscan	number of iterations of the Markov chain (beyond burn-in)

burn	burn in for the Markov chain. Typical use is burn far smaller than nscan; burn > nscan is allowed but warns.
odens	output density (thinning interval) for the Markov chain. nscan / odens samples are stored.
verbose	logical: print progress while running? Default TRUE.
gof	logical: calculate goodness of fit statistics? Setting to TRUE adds approximately 2-5% to runtime. For faster sampling without GOF overhead, set gof=FALSE and use gof() after model fitting.
custom_gof	optional function or list of named functions for computing custom goodness-of-fit statistics. Each function must accept a single matrix Y as input and return a numeric vector. If a single function is provided, it should return a named vector. If a list of functions is provided, each function should return a single value and will be named according to the list names. Custom statistics will be computed in addition to default statistics. Example: custom_gof = function(Y) c(density = mean(Y > 0, na.rm = TRUE))
plot	accepted for signature parity with lame ; ignored. ame() runs a single-period MCMC and does not draw live trace panels. Default FALSE.
start_vals	List from previous model run containing parameter starting values for new MCMC
periodic_save	logical: indicating whether to periodically save MCMC results
out_file	character vector indicating name and path in which file should be stored if periodic_save is selected. For example, on an Apple OS out_file="~/Desktop/ameFit.rda".
save_interval	quantile interval indicating when to save during the post-burn-in period.
posterior_opts	optional list of posterior draw-storage options, usually built with posterior_options . Recognised names (unknown names trigger a warning): save_UV, save_UV_draws, save_ab, thin_UV, thin_ab. save_UV = TRUE stores per-iteration latent-position draws on fit\$U_samples / fit\$V_samples ([actor, dim, draw] arrays; bipartite fits also store the interaction-matrix draws on fit\$G_samples); save_UV_draws (the lame spelling) is accepted as an alias. save_ab = TRUE stores additive-effect draws on fit\$a_samples / fit\$b_samples. thin_UV / thin_ab thin the stored draws. Default NULL.
n_chains	integer: number of MCMC chains to run (default: 1)
cores	integer: number of cores for parallel chains (default: 1)
use_sparse_matrices	logical: use sparse matrix storage for large networks? (default: FALSE). Recommended only for truly sparse networks (< 10% non-zero entries).
method	character: "mcmc" (default, the Bayesian MCMC fit) or "als" (the fast, MCMC-free iterative block coordinate descent point estimator). When method = "als", MCMC-specific arguments (nscan, burn, odens, prior, ...) are warned about and ignored; the call forwards to ame_als .
bootstrap	integer (only used when method = "als"): number of bootstrap replicates. 0 (default) skips the bootstrap; N > 0 runs N replicates and attaches the result so that confint returns bootstrap intervals.
bootstrap_type	character (only used when method = "als"): "parametric" (default) or "block".

<code>bootstrap_block_length</code>	integer: block length for the block bootstrap.
<code>bootstrap_seed</code>	optional integer seed for the bootstrap.
<code>save_log_lik</code>	logical: when TRUE, attach a per-iteration pointwise log-likelihood matrix <code>fit\$log_lik</code> (an <code>n_iter</code> x <code>n_obs</code> array), required for <code>loo(fit)</code> and <code>waic(fit)</code> . For families normal, binary, cbin, poisson, and ordinal this is the exact observed-data log density of Y (<code>fit\$log_lik_method = "observed_exact"</code>); only <code>frn</code> falls back to the augmented-Z normal approximation on the latent scale (with a one-time warning). Default FALSE (no <code>log_lik</code> storage; default fit is byte-identical to previous releases).
<code>ordinal_cutpoints</code>	character: cutpoint convention for family = "ordinal". "data_induced" (default) uses the data-induced cutpoints; "explicit" samples explicit cutpoints via a Cowles (1996) Metropolis-Hastings update. Ignored for other families.
<code>print</code>	Deprecated. Use <code>verbose</code> instead.
<code>...</code>	reserved for future use. Passing <code>lame()</code> -only arguments (e.g. <code>dynamic_beta</code> , <code>period_exposure</code>) here triggers a clean abort directing you to lame ; passing any other unrecognised name warns so typos are visible rather than silently dropped.
<code>model.name</code>	optional string for model selection output

Details

This command provides posterior inference for parameters in AME models of cross-sectional relational data, assuming one of eight possible data types/models. The function supports both unipartite networks (square adjacency matrices) and bipartite networks (rectangular adjacency matrices with distinct row and column node sets) for single time point analysis.

Model. For a dyad (i, j) the AME linear predictor is

$$\eta_{ij} = \beta_0 + x'_{ij}\beta + a_i + b_j + u'_i Dv_j,$$

where β are regression coefficients on dyadic / nodal covariates, a_i is a row (sender) random effect, b_j is a column (receiver) random effect, and $u'_i Dv_j$ is the multiplicative latent-factor term (rank R). The observation model is $Y_{ij} \sim F(\eta_{ij}, \theta)$ with F specified by family (Gaussian for "normal", probit for "binary" / "cbin", etc.). For unipartite (`symmetric = FALSE`) the residual error has dyad-level correlation ρ between (i, j) and (j, i) ; for bipartite, dyad correlation is fixed at 0.

Priors (in brief). β has a Zellner-style g-prior (g); (a_i, b_i) are jointly Normal with covariance Σ_{ab} (Inverse-Wishart prior `Sab0 / eta0`); u_i, v_j are independent Normal with covariance Σ_{uv} (Inverse-Wishart prior `Suv0 / kappa0`); the dyad-correlation ρ has an arc-sine prior on $(-1, 1)$ (density proportional to $(1 - \rho^2)^{-1/2}$), updated with Metropolis steps. See `prior_summary(fit)` for the priors actually used.

Choosing R . The multiplicative rank R controls the dimensionality of latent homophily / heterogeneity not explained by covariates and additive effects. $R = 0$ fits an additive-only social-relations model; $R = 1$ or 2 is typical for small / medium networks; $R > \text{floor}(n/3)$ is rarely identifiable and will issue a warning. Latent factors capture unobserved structure (clusters, hub patterns, transitive triangles the covariates miss) and are accessed at `fit$U`, `fit$V`.

Identifiability. The latent factor term $u_i' D v_j$ is invariant to rotation and reflection of U, V ; the package canonicalises with an SVD so successive draws are interpretable. For visual stability across posterior summaries see [procrustes_align](#) and [latent_positions](#).

Theoretical Foundation:

The AME model decomposes network structure into several components:

$$y_{ij} = \beta' x_{ij} + a_i + b_j + u_i' v_j + \epsilon_{ij}$$

where:

- $\beta' x_{ij}$: Fixed effects of dyadic/nodal covariates
- a_i : Additive sender (row) effect for node i
- b_j : Additive receiver (column) effect for node j
- $u_i' v_j$: Multiplicative interaction between latent factors
- ϵ_{ij} : Dyadic error term (may be correlated)

This specification generalizes the social relations model (Warner et al. 1979) and latent space models (Hoff et al. 2002) within a unified framework.

Prior Distributions:

The model uses conjugate and semi-conjugate priors where possible:

- Regression coefficients: $\beta \sim N(0, g\sigma^2(X'X)^{-1})$ (g-prior)
- Additive effects: $(a_i, b_i)' \sim N(0, \Sigma_{ab})$ jointly
- Covariance: $\Sigma_{ab} \sim IW(\eta_0, \eta_0 S_{ab0})$ (inverse-Wishart)
- Multiplicative effects: Hierarchical shrinkage via η_0
- Dyadic correlation: arc-sine prior on $(-1, 1)$, density $p(\rho) \propto (1 - \rho^2)^{-1/2}$, with Metropolis updates

The inverse-Wishart prior on Σ_{ab} allows learning correlation between sender and receiver effects, capturing reciprocity patterns.

Note on the additive-effects variance scale: for the "normal" and "poisson" families the default `Sab0 = diag(2)` with `eta0 = round(4 + 3n/100)` pseudo-actors pulls the additive-effects variances `va/vb` toward 1 at small n (measured roughly +50\ variance is 0.3, and about +20\ families adaptively scale `Sab0` and do not have this issue. Pass `prior = list(Sab0 = ..., eta0 = ...)` when the magnitude of sender/receiver heterogeneity matters at n below roughly 100.

Multiplicative Effects (Latent Factors):

When $R > 0$, the model includes R -dimensional latent factors:

- Asymmetric case: $u_i, v_j \in \mathbb{R}^R$ with $u_i' v_j$ interaction
- Symmetric case: $u_i = v_i$ with eigendecomposition $U L U'$
- Captures homophily, transitivity, and community structure
- R chosen via model selection or set to 2-3 for visualization

Estimation Algorithm:

The model uses a Gibbs sampler with the following updates:

1. Sample latent Z given parameters (data augmentation for non-normal families)
2. Update regression coefficients β via g-prior conjugate update
3. Update additive effects (a,b) jointly with β
4. Update covariance Σ_{ab} from inverse-Wishart
5. Update multiplicative effects U, V via Gibbs or Metropolis-Hastings
6. Update dyadic correlation ρ via Metropolis-Hastings
7. Update variance σ^2 (for continuous families)

Standard Model Types:

The following data types/models are available:

"normal": A normal AME model (identity link: $E[Y] = \eta$).

"binary": A binary probit AME model (probit link: $P(Y = 1) = \Phi(\eta)$).

"ordinal": An ordinal probit AME model (cumulative probit link). An intercept is not identifiable in this model.

"cbin": An AME model for censored binary data (probit link with censoring). The value of 'odmax' specifies the maximum number of links each row may have.

"frn": An AME model for fixed rank nomination networks. A higher value of the rank indicates a stronger relationship. The value of 'odmax' specifies the maximum number of links each row may have.

"poisson": An overdispersed Poisson AME model for count data: $Y \sim \text{Poisson}(\exp(z))$ with $z \sim N(\eta, \sigma^2)$, a lognormal-mixed Poisson. The conditional mean given the latent z is $\exp(z)$; the marginal mean is $\exp(\eta + \sigma^2/2)$, not $\exp(\eta)$.

Value

Posterior Samples (full MCMC chains):

BETA	Regression coefficients (nscan/odens x p matrix; one row per stored draw)
VC	Variance components (nscan/odens x k matrix)
GOF	Goodness-of-fit statistics ((nscan/odens + 1) x 5 matrix). First row contains observed values, remaining rows contain posterior predictive samples. See gof for post-hoc computation and gof_plot for visualization.

Posterior Means (averaged over chain):

APM	Additive row/sender effects (n-vector)
BPM	Additive column/receiver effects (m-vector); NULL for symmetric networks
U	Multiplicative row/sender factors (n x R matrix)
V	Multiplicative column/receiver factors (m x R matrix); NULL for symmetric networks
L	Eigenvalue matrix (R x R diagonal); symmetric networks only
YPM	Posterior mean of Y on response scale (for predictions and imputing missing values)

Metadata:

family	Model family (normal, binary, etc.)
mode	Network mode (unipartite or bipartite)
symmetric	Logical indicating if network is symmetric
R	Dimension of multiplicative effects

Optional Posterior Samples (if requested via posterior_options):

U_samples	Samples of U (n x R x iterations array)
V_samples	Samples of V (m x R x iterations array)
a_samples	Samples of row effects (n x iterations matrix)
b_samples	Samples of column effects (m x iterations matrix)

Note on reconstructing removed matrices: To save memory, EZ (expected latent network) and UVPM/ULUPM (multiplicative products) are not stored but can be reconstructed using:

- `reconstruct_EZ(fit)` - Returns linear predictor (link scale, not response scale)
- `reconstruct_UVPM(fit)` - Returns U\

Generating posterior distributions: Use `simulate_posterior(fit, component="UV")` to generate posterior samples for components where only means are stored, or use `posterior_options()` during model fitting to save full posterior samples.

`model.name` Name of the model (if provided)

Supported family x mode combinations

Every family is supported under both modes. The bipartite Z-samplers live in `R/rZ_bipartite.R` and dispatch per family; see also the inline comment in `R/lame.R` (the rectangular samplers live in `R/rZ_bipartite.R`).

family	unipartite	bipartite
normal	yes	yes
binary	yes	yes
ordinal	yes	yes
cbin	yes	yes
frn	yes	yes
poisson	yes	yes

Symmetric (`symmetric = TRUE`) fits require a symmetric Y. `family = "ordinal"` with `symmetric = TRUE` is supported via the dedicated sampler in `R/rZ_ord_sym_fc.R`, which uses the symmetric-doubled precision and mirrors upper-triangle draws to the lower triangle so $Z = t(Z)$ holds at every sweep.

Symmetric input with one triangle missing. When `symmetric = TRUE` and one triangle of Y is fully NA (the user stored only the lower or upper triangle), the symmetry validator `any(is.finite(Y - t(Y)))` evaluates FALSE and the call proceeds: the sampler then treats the populated triangle as the symmetric data and mirrors it. This is usually intended, but if the upper / lower triangles were meant to differ, the model is silently fitting half the data. Audit `anyNA(Y[upper.tri(Y)]) != anyNA(Y[lower.tri(Y)])` before calling if you are unsure.

Data preparation

`ame()` accepts a matrix directly. For long-format edgelist, bipartite data, and covariates, use **netify** to build the network object and pass that object as `Y`. `ame()` will call `netify::to_lame()` internally. If you already have an **igraph** or **network** object and only need a plain adjacency matrix, `as_lame_y` is still available as a small convenience helper.

For an undirected/symmetric network, pass `symmetric = TRUE`; for a rectangular two-mode network (students x courses, donors x candidates), pass `mode = "bipartite"` or build the **netify** object with `mode = "bipartite"`. `Xrow` and `Xcol` accept either a numeric matrix or a `data.frame` (coerced internally); `Xdyad` must be a 3-D array $n \times n \times p$ of numeric covariates with no `Inf/NaN`.

When to use AME vs ERGM

AME and ERGM are complementary tools for binary network analysis, not direct substitutes. **ERGM** is a class of exponential-family models built around explicit network statistics (counts of edges, mutual ties, triangles, geometrically-weighted shared partners, ...). You write the statistics you think matter, ERGM gives you their coefficients. ERGM excels when you have a substantive theory about which configurations drive tie formation.

AME models latent homophily / heterogeneity directly via sender, receiver, and multiplicative latent-factor effects. You don't enumerate triadic terms; the multiplicative-effects rank `R` captures higher-order structure (clustering, transitivity, hub patterns) implicitly. AME excels when (a) you have dyadic / nodal covariates whose effects you want to interpret cleanly without ERGM degeneracy, (b) higher-order structure is "nuisance" that you want to absorb but not parameterise, or (c) you need a posterior distribution over predictions for forecasting or imputation.

Practical guidance: if your research question is "do nodes that share attribute `X` tend to form triangles together?", reach for ERGM's `gwesp`. If your research question is "controlling for unobserved sender / receiver heterogeneity and latent clustering, what is the effect of dyadic covariate `X`?", reach for AME. The `R = 0` additive-only case is the social relations model (Warner, Kenny, Stoto 1979); `R >= 1` adds latent space.

ERGM to AME translation

For users coming from `statnet::ergm`, the rough analogues are:

ERGM term	AME analogue
<code>edges</code>	intercept (probit link, not logit)
<code>nodecov("x")</code>	<code>Xrow = x</code> or <code>Xcol = x</code>
<code>nodematch("g")</code>	dyadic covariate via <code>nodematch(g)</code> into <code>Xdyad</code>
<code>nodefactor("g")</code>	dyadic covariate via <code>nodefactor(g)</code> into <code>Xdyad</code> (drop one level)
<code>absdiff("z")</code>	dyadic covariate via <code>absdiff(z)</code> into <code>Xdyad</code>
<code>mutual</code>	<code>dcov = TRUE</code> -> the <code>rho</code> parameter (probit-scale, not log-odds; not numerically comparable to ERGM)
<code>gwesp / transitivity</code>	<code>R >= 1</code> multiplicative latent factors (not the same statistic)
sender activity heterogeneity	<code>rvar = TRUE</code> , gives <code>a_i</code> , <code>va</code>
receiver popularity heterog.	<code>cvar = TRUE</code> , gives <code>b_j</code> , <code>vb</code>

For `family = "binary"` the link is probit, so the intercept is on the probit scale; do not compare it to an ERGM `edges` estimate by simple arithmetic.

Migration from amen

Both `amen` and `lame` export `ame()`; loading both packages fires a startup warning telling you to call `lame::ame(...)` or `amen::ame(...)` explicitly.

For default cross-sectional calls, `lame::ame()` follows the `amen::ame()` interface: the `fit$BETA` slot is a 2-D `[n_stored, p]` matrix in both packages, so scripts that call `colMeans(fit$BETA)` or `apply(fit$BETA, 2, mean)` continue to work unchanged. `lame` additionally accepts `family = "binary"` (which `amen` 1.4.5 no longer accepts; `amen` requires `"bin"`). The `print` argument is deprecated in favour of `verbose`; calls that pass `print = ...` still work but warn.

The cross-sectional path has no `dynamic_beta` option (an AR(1) prior on a single-period coefficient is unidentified), so the BETA 3-D shape that `lame()` can produce never arises from `ame()`. See [lame](#) for the longitudinal path and the silent-aggregation hazard with 2-D `apply(fit$BETA, 2, mean)` scripts under `dynamic_beta = TRUE`.

Notes on priors

- The regression-coefficient prior is a Zellner g-prior ($\beta \sim N(0, g * \sigma^2 * (XtX)^{-1})$ where XtX is the design cross-product). g is a *top-level* argument of `ame()`, not an entry in `prior = list(...)` (a common slip).
- There is no per-coefficient prior knob. If you need `student_t`, `horseshoe`, or to centre a slope away from zero, AME does not currently expose it; the g-prior structure is the only knob.
- Unknown names in `prior = list(...)` are warned about (a typo like `Sab = ...` instead of `Sab0` would otherwise be silently dropped).

Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

See Also

[lame](#) for longitudinal models, [gof](#) for post-hoc goodness-of-fit computation, [gof_plot](#) for visualizing GOF results, [latent_positions](#) for extracting latent positions as a tidy data frame, [procrustes_align](#) for Procrustes alignment of latent positions, [summary.ame](#) for model summaries, [coef.ame](#) for coefficient extraction

Examples

```
data(YX_bin)
fit <- ame(YX_bin$Y, Xdyad = YX_bin$X, burn = 10, nscan = 100, odens = 1,
          family = "binary", verbose = FALSE)
summary(fit)
# Note: you should run the Markov chain much longer in practice
```

ame_als

Fast (MCMC-free) AME estimation for a cross-sectional network

Description

Fits an additive and multiplicative effects (AME) model to a single cross-sectional network by **iterative block coordinate descent**, producing a fast point estimate with no MCMC and no credible intervals.

The estimation algorithm adapts the *iterative block coordinate descent* estimator of the Social Influence Regression (SIR) model of Hoff & Minhas (the algorithm implemented in `sir::sir_alsfit()` and nicknamed "ALS" in that package) to the AME model. It is a port and adaptation, not original **lame** methodology.

Usage

```
ame_als(
  Y,
  Xdyad = NULL,
  Xrow = NULL,
  Xcol = NULL,
  R = 0,
  family = "normal",
  mode = c("unipartite", "bipartite"),
  symmetric = FALSE,
  max_iter = 200,
  tol = 1e-06,
  lowrank_method = c("mm", "als", "hybrid"),
  non_normal_method = c("irls", "transform"),
  link = c("probit", "logit"),
  linear_solver = c("eigen", "qr", "auto"),
  multistart = c("none", "cheap", "full"),
  bootstrap = 0L,
  bootstrap_type = c("parametric", "block"),
  bootstrap_block_length = 1L,
  bootstrap_seed = NULL,
  verbose = TRUE,
  seed = 6886
)
```

Arguments

Y	a square (unipartite) or rectangular (bipartite) relational matrix. A cross-sectional netify object is also accepted and converted with <code>netify::to_lame()</code> ; when family or mode is omitted, the value inferred by netify is used.
Xdyad	an <code>n_row</code> x <code>n_col</code> matrix or <code>n_row</code> x <code>n_col</code> x <code>pd</code> array of dyadic covariates, or <code>NULL</code> .

Xrow	an n_row x pr matrix of row/sender covariates, or NULL.
Xcol	an n_col x pc matrix of column/receiver covariates, or NULL.
R	integer dimension of the multiplicative effects (default 0). The covariate coefficients are conditional on this choice. The multiplicative term $u_i'v_j$ is a flexible high-variance regressor that can correlate with the dyadic covariates, so the estimated beta can shift – and occasionally change sign – as R increases. Comparing against an R = 0 fit is a useful check on whether the covariate story is being driven by the latent rank.
family	one of "normal", "binary", or "poisson". The rank and censoring families are MCMC-only.
mode	"unipartite" (square) or "bipartite" (rectangular).
symmetric	logical; fit a symmetric (undirected) model. Unipartite only.
max_iter	maximum number of block coordinate descent iterations (default 200).
tol	convergence tolerance on the relative change in residual sum of squares (default 1e-6).
lowrank_method	inner solver for the multiplicative (low-rank) block: "mm" (default) weighted majorise-minimise; "als" alternating least squares; "hybrid" runs both and keeps the lower-objective result. "als"/"hybrid" converge faster than "mm" on strongly unbalanced longitudinal panels and are available for directed and bipartite models (symmetric fits always use "mm"). All three minimise the same objective, so the point estimate is unchanged for balanced data.
non_normal_method	for the non-normal ALS families, "irls" (default for binary/poisson) runs iteratively reweighted least squares, giving a fast approximate GLM AME fit with coefficients on the requested link scale (Poisson log, binary logit/probit). "transform" fits one fixed Gaussian working response (log(y+1) for Poisson, rank-normal scores for binary); its coefficients are on an uncalibrated working scale and are mainly useful for direction/ranking checks. A directed R > 0 IRLS fit uses the hybrid low-rank solver internally because the IRLS weights are unbalanced. Uncertainty for either path comes from the bootstrap or sandwich covariance.
link	link for non_normal_method = "irls" with a binary family: "probit" (default; matches ame/lame) or "logit". poisson always uses the log link; ignored otherwise.
linear_solver	solver for the regression block: "eigen" (default) eigendecomposes the normal equations; "qr" uses a QR factorisation of the observed design, which is more stable for ill-conditioned covariates; "auto" picks "qr" when the design is ill-conditioned but full rank. All give the same answer for well-conditioned designs.
multistart	for R > 0 (a non-convex objective), "none" (default) fits from a single deterministic start; "cheap" (4 starts) and "full" (8 starts) also try random low-rank starts and keep the lowest-SSE fit, warning when the starts reach materially different optima. Reproducible given seed; the global RNG stream is left unchanged.

bootstrap	integer: if > 0, additionally run bootstrap replicates of the parametric or block bootstrap (via <code>ame_als_bootstrap</code>) after the point fit and attach the result as <code>fit\$bootstrap</code> . The downstream accessors (<code>confint.ame_als</code> , <code>summary</code> , <code>print</code>) then surface bootstrap intervals instead of the anti-conservative sandwich Wald intervals. Default 0 (no bootstrap) – bootstrap is expensive, so it is not imposed on a user who just wants a quick fit.
bootstrap_type	character: "parametric" (default) or "block" – the bootstrap scheme to use when bootstrap > 0.
bootstrap_block_length	integer: block length for the block bootstrap; only used when bootstrap_type = "block".
bootstrap_seed	optional integer seed for the bootstrap (the point fit uses seed).
verbose	logical; print progress (default TRUE).
seed	random seed (default 6886). The block coordinate descent is deterministic, so the point estimate is reproducible regardless; the argument is retained for API consistency with <code>ame</code> .

Details

The AME decomposition

$$z_{ij} = \mu + \beta' x_{ij} + a_i + b_j + u_i' v_j + \epsilon_{ij}$$

is conditionally linear: it is a linear regression in (μ, β, a, b) for fixed multiplicative factors (U, V) , and the optimal rank- R (U, V) for fixed (μ, β, a, b) is the truncated SVD of the residual matrix. The estimator therefore cycles, until the residual sum of squares stabilises, through three blocks — each a monotone (objective-non-increasing) update: a joint least-squares solve for the intercept μ and regression coefficients β (with a `ginv` pseudoinverse fallback for rank-deficient designs); Gauss-Seidel sweeps to convergence for the additive effects (a, b) ; and a weighted low-rank update for the multiplicative factors (U, V) via SVD (eigen-decomposition when `symmetric = TRUE`). The weighting makes the multiplicative step correct for unbalanced longitudinal panels (dyads observed at unequal numbers of time points); severely unbalanced panels may need more iterations to converge, so raise `max_iter` if the fit reports non-convergence.

For `family = "normal"` this is a least-squares (Gaussian maximum-likelihood) fit — the exact global solution when $R = 0$, and a local optimum of the non-convex low-rank objective when $R > 0$. For "binary" and "poisson", the estimator uses an IRLS working-response path by default, so coefficients are on the requested link scale (binary probit/logit, Poisson log). The fixed-transform path is still available as a faster exploratory score, but its coefficients are not calibrated effect sizes. For $R > 0$ the multiplicative factor block of the IRLS families solves a penalized (MAP) sub-problem: each factor row carries the ridge implied by the AME prior $[u_i, v_i] \sim N(0, \Sigma_{uv})$, with the per-column prior scale estimated by an EM step (the analog of the MCMC Σ_{uv} draw). This is what makes the estimate well-defined: the *unpenalized* rank- R binary MLE does not exist under quasi-separation, and fitting it directly inflates every coefficient (a runaway that grows with R , with the latent variance diverging). With the penalty the latent variance does not run away and the slope inflation is bounded and stable in R ; a residual finite-sample (incidental-parameters) upward bias remains, on the order of +10-15% posterior mean). This residual is a property of the estimator class, not a code defect: because a nonlinear-likelihood point estimator profiles the $2Rn$ latent factors at

their joint optimum rather than integrating them, it cannot be consistent for the regression coefficient (Neyman-Scott). The bias is dominated by *rank over-specification* – it is largest when R is set higher than the data support (the factors then absorb noise) and is only $\sim 5 \setminus \text{ame}() / \text{lame}()$ path integrates the factors out and is verified calibrated by simulation-based calibration, so binary $R > 0$ ALS is best used as a fast exploratory / rank-selection score, with `ame(..., method = "mcmc")` for final coefficient inference (`bootstrap = N` gives ALS-scale intervals but reproduces, rather than removes, this bias). Rank and ordinal families ("ordinal", "cbin", "frn") are not supported by ALS and raise an informative error; use [ame](#) or [lame](#) for those likelihoods.

Row/column (node) covariates. A node covariate broadcasts to a per-actor constant, which is collinear with the additive sender/receiver effect, so its coefficient is not identified by the objective alone. It is identified here by an explicit constraint: the additive effects are taken orthogonal to the node covariates, and `beta_row/beta_col` are the corresponding between-actor regression coefficients (the additive effects then carry only the residual heterogeneity). This is the standard estimand under the assumption that the additive effects are uncorrelated with the node covariates; if that assumption is doubtful the coefficient absorbs the covariate-correlated part of the additive heterogeneity. Time-varying node covariates are summarised by their per-actor mean; if a node covariate varies within actor over time the discarded within-actor variation triggers a warning.

Identifiability of the additive and multiplicative terms. For $R > 0$ the additive term $a_i + b_j$ and the multiplicative term $u'_i v_j$ are not separately identified by the objective alone: a broadcast (row- or column-constant) component can sit in either, since a pure sender effect $a1'$ is itself rank one. The estimator imposes the standard AME gauge — the multiplicative term is double-centered (zero row and column means), so all broadcast structure is carried by a, b — which makes the reported a, b, U, V unique given the fitted values and independent of the optimisation path. For a unipartite network the double-centering means are taken over the full matrix, which includes the structurally unobserved self-tie diagonal that the model fills in by its low-rank completion; the additive/multiplicative split therefore carries an $O(1/n)$ dependence on that completion. On a disconnected observed-dyad graph the additive effects additionally have a per-component level shift, which is pinned to a precision-weighted minimum-norm gauge so that a, b and the variance components remain reproducible. A dyadic covariate that is itself (near) low-rank can still be partially aliased with the multiplicative term, so keep R modest relative to the covariate structure. This residual aliasing is intrinsic to the AME model — the MCMC estimator resolves it only through its priors.

Choosing R . There is no automatic order-selection criterion (the working-response objective has no likelihood, so AIC/BIC do not apply). Fit a few values — e.g. `lapply(0:4, function(r) ame_als(Y, R = r, ...))` — and inspect deviance (the residual sum of squares): it falls steeply while real multiplicative signal is being captured and then flattens, so the “elbow” of that curve is a reasonable choice. With $R > 0$ the objective is non-convex; use `multistart` to guard against local optima.

Uncertainty is obtained separately, by the bootstrap; see [ame_als_bootstrap](#). (The SIR paper’s own primary standard errors are Hessian-based, classical and sandwich/robust. For AME a Hessian-based variance is awkward on two counts: without an explicit gauge fix the rotational invariance of the multiplicative factors leaves the joint Hessian rank-deficient, and even with a gauge fixed the Gaussian working-response approximation used for the non-normal families leaves a Hessian-based variance miscalibrated. The bootstrap side-steps both, so it is preferred here.)

Value

An object of class "ame_als": a list with the point estimates μ , β , a , b , U , V (L for symmetric models), the linear predictor EZ , response-scale fitted values, working-scale residuals, convergence information, and the variance-component vector VC with five descriptive entries:

va , vb empirical variances of the sender and receiver additive effects.

cab covariance of the sender and receiver effects (NA for symmetric or bipartite models).

ρ dyadic residual reciprocity — the correlation between the residuals of (i, j) and (j, i) — not the sender/receiver correlation $\text{cor}(a, b)$.

ve residual variance, on the model's own scale and degrees-of-freedom-corrected ($SSE/(n_{obs} - df)$) so it matches the MCMC posterior-mean s^2 . For a binary IRLS fit the probit/logit model fixes the latent error variance at 1 by identification, so ve is reported as 1; the working-scale GLM dispersion (about 1 under correct specification) is kept separately as ve_{working} .

These are descriptive summaries of the point estimates, not random-effect variance components. See [ame_als_bootstrap](#) for uncertainty and [vcov.ame_als](#) for a fast analytic covariance of the regression coefficients.

Coverage relative to [ame](#) / [lame](#)

The ALS estimator is a fast, frequentist point estimator. It covers most static AME workflows, and the top-level `lame(..., method = "als")` dispatcher covers several dynamic workflows, but posterior-specific features still require the MCMC estimator:

- **Families.** ALS supports normal, binary, and poisson. For ordinal, cbin, and frn, fall back to [ame](#) / [lame](#).
- **Dynamic effects.** [lame_als](#) itself fits a static model pooled across time slices. The top-level dispatcher `lame(..., method = "als")` routes supported dynamic requests to a dynamic point estimator for normal, binary, and poisson panels, including named panels where actors enter or exit: `dynamic_ab`, selected intercept/dyadic/node `dynamic_beta`, and AR(1) or Student-t `dynamic_uv` for directed, symmetric, and bipartite panels. The snap-only `dynamic_uv = TRUE`, `dynamic_uv_kind = "snap"` case routes to [lame_snap_als](#) for supported normal unipartite and bipartite panels. Node-covariate coefficients use the same orthogonal additive-effect decomposition as [lame_als](#); dynamic node coefficients use period-specific node values when selected by `dynamic_beta`, while static node coefficients use per-actor means. bipartite `dynamic_g` is available on the dynamic als path for normal, binary, and poisson panels. changing actor composition requires row and column names on every slice so actors can be aligned; smoothing penalties are broken across actor-entry gaps. rank/censored dynamic families remain on the mcmc path. static `ame_als()` / `lame_als()` fits still use a single latent rank R ; the dynamic bipartite ALS dispatcher honours separate `R_row` and `R_col` values.
- **Priors.** ALS has no priors. `prior = list(...)` and `g = ...` are MCMC-only; the dispatcher `ame(..., method = "als")` warns and ignores them.
- **Posterior quantities.** No $\$BETA$ / $\$VC$ posterior draws on the point fit. Use `bootstrap = N` for a sampling distribution analogue; the draws are bootstrap, not Bayesian.
- **Multi-chain.** Not applicable; `n_chains` is dropped.
- **Convergence diagnostics.** No $Rhat$ / ESS / [trace_plot](#).

Features that work the same on ALS fits: `coef`, `vcov` (sandwich on regression block), `confint` (auto-routes bootstrap intervals when present, sandwich Wald otherwise), `predict`, `fitted`, `residuals`, `summary`, `print`, `nobs`, [simulate.ame_als](#), [gof_plot.ame_als](#), [ab_plot.ame_als](#), [uv_plot](#), [latent_positions](#).

Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

References

Minhas, S. and Hoff, P. D. (2025). Decomposing Network Dynamics: Social Influence Regression. *Political Analysis*. The iterative block coordinate descent estimator adapted here originates with that work (implemented in `sir::sir_alsfit()`).

See Also

[lame_als](#) for longitudinal networks, [ame_als_bootstrap](#) for bootstrap uncertainty, [ame](#) for the full MCMC estimator.

Examples

```
Y <- matrix(rnorm(400), 20, 20); diag(Y) <- NA
fit <- ame_als(Y, R = 1, family = "normal", verbose = FALSE)
coef(fit)
```

ame_als_bootstrap

Bootstrap uncertainty for the fast AME estimator

Description

Computes bootstrap standard errors and percentile confidence intervals for a fast AME fit produced by [ame_als](#) or [lame_als](#). Two strategies are available:

parametric (default) Simulates fresh outcomes from the fitted model and refits. For normal and IRLS (binary, poisson) fits the simulation is on the calibrated response scale; for a non-normal transform fit – whose estimator is a Gaussian fit to a fixed transformed response – it is on the Gaussian working scale. The fitted residual variance is df-corrected (mean-model degrees of freedom) at fit time, so simulating with it keeps the replicates centred on the point estimate. Available for both cross-sectional and longitudinal fits.

block Resamples time slices with replacement. With `block_length = 1` slices are resampled independently; `block_length > 1` draws contiguous blocks (a moving-block bootstrap), which preserves short-run temporal dependence. Longitudinal fits only (requires $T > 1$); with few slices its intervals are necessarily coarse.

Every replicate is refit by [ame_als_refit](#), warm-started from the original point estimate so that replicates do not drift to different local optima. Replicates that error or return non-finite values are dropped and counted (`n_valid / n_total`). Standard errors are replicate column standard deviations; confidence intervals use the percentile method.

Usage

```

ame_als_bootstrap(
  object,
  R = 200,
  type = c("parametric", "block"),
  block_length = 1,
  seed = NULL,
  verbose = TRUE
)

boot_ame(
  object,
  R = 200,
  type = c("parametric", "block"),
  block_length = 1,
  seed = NULL,
  verbose = TRUE
)

```

Arguments

object	an ame_als object from ame_als or lame_als .
R	integer number of bootstrap replicates (default 200).
type	"parametric" (default) or "block"; see Description.
block_length	block length for the block bootstrap: 1 (default) resamples time slices independently; an integer > 1 draws contiguous blocks of that many slices (a moving-block bootstrap), appropriate when the series has short-run temporal dependence. Capped at T; ignored for the parametric bootstrap.
seed	optional integer random seed.
verbose	logical; print progress (default TRUE).

Details

Choice of inference. The Social Influence Regression paper of Hoff & Minhas (2025) derives its primary standard errors from the observed Hessian (classical $-H^{-1}$ and the sandwich/robust estimator $H^{-1}SH^{-1}$). Two features of the AME model make a Hessian-based variance awkward here. First, without an explicit gauge fix the rank-R multiplicative term is identified only up to a full $R \times R$ rotation/reflection ($U \rightarrow UR, V \rightarrow VR^{-\top}$), leaving the joint Hessian rank-deficient. Second, even with a gauge fixed, the non-normal families are fit on a Gaussian working response, so a Hessian computed from that working objective is not calibrated to the family likelihood. The bootstrap side-steps both issues and is the recommended uncertainty tool here, mirroring `sir::boot_sir()`.

Alignment-sensitive quantities. The regression coefficients β , the additive effects a, b and the variance components are rotation-invariant and are aggregated directly. The multiplicative factors U, V are *not*: each replicate is Procrustes-aligned to the original fit before its standard errors are computed. The object stores both the raw and aligned replicate factors so the effect of alignment can be inspected. The alignment is well-determined only when the multiplicative singular values

are well separated; with near-equal singular values the per-column U/V standard errors reflect an unstable rotation, and the subspace — or, for symmetric models, the eigenvalues L — is the summary of record. For a symmetric model the eigenvalues L of the multiplicative term are aggregated and reported as the primary multiplicative-uncertainty summary.

The parametric bootstrap is a full parametric bootstrap of the AME model: each replicate draws fresh additive random effects a , b from their fitted dispersion (va , vb , cab) and fresh residuals, holding μ , β and the multiplicative term fixed. Regenerating the additive effects (rather than holding the fitted a , b fixed) is what gives the intercept and node-covariate standard errors their actor-level sampling-variability component.

Assumptions. The block bootstrap treats the time slices as exchangeable replicates of the static-effects model — appropriate for that model, but not for strongly trended or serially dependent series (use the dynamic [lame](#) there); with only a few time slices it is necessarily coarse, its intervals correspondingly imprecise and somewhat anti-conservative, so `parametric` is the default. A variance component fit with $R > 0$ can still carry a small residual parametric-bootstrap bias (the low-rank refit re-absorbs simulated noise); `summary()` flags any point estimate that falls outside its interval. A binary IRLS fit can carry a finite-sample (incidental-parameters) bias in the point estimator itself, which the bootstrap reproduces rather than removes. The MCMC [ame](#) / [lame](#) path gives posterior summaries when that is the target.

Value

An object of class "boot_ame" with components including `coefs` (replicate intercept + regression coefficients), `se`, `ci_lo`, `ci_hi`, `point_est`, `param_names`; `vc_*` for the variance components; `a_coefs`, `b_coefs`, `se_a`, `se_b`; `U_aligned`, `V_aligned`, `U_raw`, `V_raw`, `se_U`, `se_V` (when $R > 0$); and `n_valid`, `n_total`, `type`, `family`.

Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

References

Minhas, S. and Hoff, P. D. (2025). Decomposing Network Dynamics: Social Influence Regression. *Political Analysis*. The block and parametric bootstrap follow the inference scheme of `sir::boot_sir()` developed for the SIR estimator.

See Also

[ame_als](#) and [lame_als](#), both of which accept `bootstrap = N`, `bootstrap_type`, `bootstrap_block_length`, `bootstrap_seed` to do this work in a single call when you are about to fit the model anyway. `ame_als_bootstrap()` is the post-hoc path (bootstrap an *already-fit* object without refitting from scratch). [ame_als_refit](#) for warm-start refits; `confint.boot_ame` for the bootstrap CI extractor.

Examples

```
Y <- replicate(6, { m <- matrix(rnorm(225), 15, 15); diag(m) <- NA; m },
  simplify = FALSE)
fit <- lame_als(Y, R = 1, family = "normal", verbose = FALSE)
# post-hoc bootstrap of an existing fit:
```

```

bt <- ame_als_bootstrap(fit, R = 50, type = "block",
                        seed = 1, verbose = FALSE)
# equivalent one-shot call:
# fit_b <- lame_als(Y, R = 1, family = "normal", verbose = FALSE,
#                  bootstrap = 50, bootstrap_type = "block",
#                  bootstrap_seed = 1)
print(bt)

```

ame_als_refit

Refit a fast AME model with a warm start

Description

Refits an AME model by iterative block coordinate descent, initialised (“warm-started”) from an existing `ame_als` fit. This is the workhorse of `ame_als_bootstrap`: every bootstrap replicate is refit from the original point estimate rather than from a cold random start, which prevents replicates from converging to different local optima or rotations and is essential for meaningful bootstrap standard errors.

Usage

```

ame_als_refit(
  object,
  Y_new = NULL,
  X_new = NULL,
  Z_new = NULL,
  max_iter = 30,
  tol = 1e-05,
  verbose = FALSE
)

```

Arguments

<code>object</code>	an <code>ame_als</code> object supplying the warm-start values (μ , β , a , b , U , V) and the model configuration (<code>family</code> , <code>mode</code> , <code>symmetric</code> , <code>R</code>).
<code>Y_new</code>	optional canonical outcome array $[n_row, n_col, T]$ to refit on. Defaults to <code>object\$Y</code> .
<code>X_new</code>	optional canonical design array $[n_row, n_col, p, T]$. Defaults to <code>object\$X</code> .
<code>Z_new</code>	optional canonical <i>working-response</i> array $[n_row, n_col, T]$. When supplied, the model is refit by a Gaussian block coordinate descent directly on <code>Z_new</code> , bypassing the family transform / IRLS reweighting. This is used by the parametric bootstrap of a non-normal transform fit, whose estimator is a Gaussian fit to a fixed transformed response. <code>Y_new</code> is still used for the observed-cell pattern.
<code>max_iter</code>	maximum block coordinate descent iterations (default 30; fewer are needed than for a cold start).

tol convergence tolerance (default 1e-5).
 verbose logical; print progress (default FALSE).

Details

The estimation algorithm is the iterative block coordinate descent estimator of the Social Influence Regression model of Hoff & Minhas (`sir::sir_alsfit()`), adapted to the AME model, with each bootstrap replicate warm-started from the original point estimate.

Value

An object of class "ame_als"; see [ame_als](#).

Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

References

Minhas, S. and Hoff, P. D. (2025). Decomposing Network Dynamics: Social Influence Regression. *Political Analysis*. The iterative block coordinate descent estimator refit here originates with that work (implemented in `sir::sir_alsfit()`).

See Also

[ame_als](#), [ame_als_bootstrap](#).

Examples

```
Y <- matrix(rnorm(400), 20, 20); diag(Y) <- NA
fit <- ame_als(Y, R = 1, family = "normal", verbose = FALSE)
refit <- ame_als_refit(fit, verbose = FALSE)
coef(refit)
```

ame_memory_settings *Display memory usage information for AME models*

Description

Shows estimated memory usage for networks of given size. Memory optimization is automatic, so this is informational only.

Usage

```
ame_memory_settings(n_nodes, R = 2)
```

Arguments

n_nodes	Number of nodes in network
R	Rank of multiplicative effects (default: 2)

Details

Memory levers available in the package:

- Run `compact_ame()` on a fitted model to drop empty slots and, for genuinely sparse posterior means, use sparse storage via `use_sparse_matrices = TRUE`
- Increase `odens` in `ame()/lame()` to store fewer posterior draws
- Pass `posterior_opts = list(thin_UV = ..., thin_ab = ...)` to thin the stored latent-factor and additive-effect draws

Value

Invisibly returns memory estimates

Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

ame_memory_usage	<i>Calculate memory usage of AME model components</i>
------------------	---

Description

Calculate memory usage of AME model components

Usage

```
ame_memory_usage(fit = NULL, detailed = TRUE)
```

Arguments

fit	Fitted AME model
detailed	Logical; show detailed breakdown (default TRUE)

Value

Invisibly returns `data.frame` with memory usage

Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

ame_options

*AME model fitting options***Description**

Configure options for fitting AME models. Memory efficiency is now handled automatically based on network size.

Usage

```
ame_options(
  parallel_chains = 1,
  verbose = TRUE,
  odens = 25,
  use_sparse_matrices = FALSE
)
```

Arguments

parallel_chains	Number of parallel chains to run (default: 1)
verbose	Logical; print progress information (default: TRUE)
odens	Output density - save every odens iterations (default: 25)
use_sparse_matrices	Logical; use sparse matrices for storing results (default: FALSE). Set to TRUE if your network is actually sparse (many zero/NA entries) and memory is a concern.

Details

Memory optimization features:

- Redundant matrices (EZ, UVPM) are never stored - they can be reconstructed if needed
- use_sparse_matrices = TRUE: Converts large matrices to sparse format
- Posterior samples are always thinned appropriately

When to use sparse matrices:

- Your network has $< 10^5$
- Memory usage is a critical concern
- You're willing to trade computational speed for memory efficiency

Note: For dense networks (most edges observed), sparse matrices will be slower and may use more memory than dense storage.

Value

List of options to pass to ame()

Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

Examples

```
# Configure options
opts <- ame_options(verbose = TRUE, odens = 25)
opts
```

ame_parallel	<i>Run AME model with multiple parallel chains</i>
--------------	--

Description

Run AME model with multiple parallel chains

Usage

```
ame_parallel(
  Y,
  n_chains = 4,
  cores = n_chains,
  combine_method = c("pool", "list"),
  fitter = c("auto", "ame", "lame"),
  ...
)
```

Arguments

Y	Network data matrix
n_chains	Number of parallel chains to run (default = 4)
cores	Number of CPU cores to use for parallel processing. Default is n_chains. Use 1 for sequential processing.
combine_method	Method for combining chains: "pool" (default) or "list"
fitter	Which fitter to use: "auto" (default; pick lame when Y is a list / 3-D array with >1 time slice, else ame), "ame" (force cross-sectional), or "lame" (force longitudinal – required for dynamic_* flags).
...	Additional arguments passed to ame() or lame().

Value

If combine_method = "pool": A single ame object with pooled chains
 If combine_method = "list":
 A list of ame objects, one per chain

Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

See Also

`lame_multi` for the unrelated multi-panel wrapper that fits K *distinct* networks with shared regression coefficients. `ame_parallel` / `lame_parallel` run K MCMC chains of the *same* model (for R-hat / ESS diagnostics); `lame_multi` runs one chain across K panels with pooled beta.

Examples

```
# Run 2 chains sequentially
data(YX_nrm)
fit_parallel <- ame_parallel(YX_nrm$Y, Xdyad = YX_nrm$X,
                             n_chains = 2, cores = 1,
                             nscan = 100, burn = 10, odens = 1,
                             verbose = FALSE)
```

array_to_list

Convert array to list.

Description

Convert array to list.

Usage

```
array_to_list(arrayObj, actorList, sliceLabel)
```

Arguments

arrayObj	3d array object
actorList	list of actor names
sliceLabel	labels for array slices

Value

array in list format

Author(s)

Shahryar Minhas

as_draws

*Generic dispatcher for posterior::as_draws on lame fits***Description**

Lightweight S3 generic so calls of the form `as_draws(fit)` dispatch through R's S3 system even when the **posterior** package is not loaded. When **posterior** is loaded, its generic of the same name is resolved first by R's namespace search; this fallback only fires for bare-namespace use.

Usage

```
as_draws(x, ...)
```

Arguments

`x` a fitted `ame` or `lame` object.
`...` passed to the relevant method.

Value

An object dispatched by the relevant method (typically a `posterior::draws_array` for an `ame` / `lame` fit).

as_draws.ame

*Convert an AME / LAME fit to a posterior draws object***Description**

Reshapes the BETA + VC posterior draws stored on an `ame` or `lame` fit into a `posterior::draws_array` (or `draws_df`-equivalent) suitable for downstream packages that consume that representation. Multi-chain fits (`ame(..., n_chains = N)`) are reshaped with `chain` as a separate dimension; single-chain fits are returned as a single-chain `draws_array`.

Usage

```
## S3 method for class 'ame'
as_draws(x, include = c("beta", "vc"), ...)

## S3 method for class 'lame'
as_draws(x, include = c("beta", "vc"), ...)

## S3 method for class 'ame_als'
as_draws(x, ...)
```

Arguments

x	an ame or lame fit.
include	character; which parameter blocks to include. Default c("beta", "vc"); can also include "rho_uv", "rho_ab" for dynamic LAME fits.
...	ignored.

Details

The reshape uses `fit$chain_indicator` (set when `n_chains > 1`) to keep chain identity separate so within-chain Rhat / ESS estimates and chain-coloured traceplots resolve correctly.

Value

A `posterior::draws_array` (when **posterior** is available) or otherwise a plain 3-D array with named dimnames.

as_lame_y

Convert a graph object to a lame-ready adjacency matrix

Description

Convenience wrapper that takes an **igraph** or **network** object and returns the kind of matrix that [ame](#) / [lame](#) expect: a numeric adjacency matrix with NA on the diagonal (self-ties not modelled) and (if available) actor names preserved on the row/column dimnames.

Usage

```
as_lame_y(x, na_diag = TRUE)
```

Arguments

x	an igraph, network, matrix, or data.frame representing an adjacency / sociomatrix.
na_diag	logical: replace the diagonal with NA? Defaults to TRUE for square (unipartite) matrices and is ignored for rectangular (bipartite) matrices.

Details

Plain matrices and data.frames are accepted too; data.frames are coerced to a numeric matrix and only the diagonal is rewritten to NA.

Value

A numeric matrix suitable to pass as Y to [ame](#) / [lame](#).

Examples

```
# plain matrices are returned with the diagonal set to NA
m <- matrix(rbinom(25, 1, 0.4), 5, 5,
            dimnames = list(letters[1:5], letters[1:5]))
as_lame_y(m)

if (requireNamespace("igraph", quietly = TRUE)) {
  g <- igraph::sample_gnp(8, 0.3)
  Y <- as_lame_y(g)
  dim(Y)
}
```

autoplot.ame_als	<i>autoplot method for ALS fits</i>
------------------	-------------------------------------

Description

Coefficient point-and-interval plot for an [ame_als](#) or [lame_als](#) fit. The body builds the same frame [autoplot.lame](#) uses, sourcing the point estimate from `coef(fit)` and the interval from `confint(fit)` (sandwich or bootstrap, depending on which is available). `which = "beta"` is the only mode supported; `which = "uv" / "ab"` return an informative error.

Usage

```
## S3 method for class 'ame_als'
autoplot(object, which = c("beta", "uv", "ab"), conf.level = 0.95, ...)

## S3 method for class 'lame_als'
autoplot(object, which = c("beta", "uv", "ab"), conf.level = 0.95, ...)
```

Arguments

<code>object</code>	A fitted <code>ame_als</code> / <code>lame_als</code> object.
<code>which</code>	One of "beta" (currently the only supported value).
<code>conf.level</code>	Confidence level for the interval. Default 0.95.
<code>...</code>	Passed to <code>vcov.ame_als</code> / <code>confint.ame_als</code> (e.g. <code>cluster</code>).

Value

A ggplot object.

autoplot.lame

*Ribbon plot of time-varying coefficients (or coefplot for static fits)***Description**

For a lame fit with `dynamic_beta` on, returns a faceted ggplot of the posterior mean coefficient path per period with a 95 percent credible-interval ribbon. For a static fit (no `dynamic_beta`), falls back to a `tidy()`-driven horizontal `coefplot` with posterior-mean point estimate and credible-interval bars so that `autoplot(fit)` returns a ggplot regardless of fit type.

Usage

```
## S3 method for class 'lame'
autoplot(
  object,
  which = c("beta", "ab", "uv"),
  probs = c(0.025, 0.5, 0.975),
  coefs = NULL,
  ...
)

## S3 method for class 'ame'
autoplot(
  object,
  which = c("beta", "ab", "uv"),
  probs = c(0.025, 0.5, 0.975),
  coefs = NULL,
  ...
)
```

Arguments

<code>object</code>	A fitted <code>ame</code> / <code>lame</code> object.
<code>which</code>	One of "beta" (default; coefficient plot – ribbon when dynamic, <code>coefplot</code> when static), "ab" (sender / receiver effects when <code>dynamic_ab</code>), "uv" (latent positions when <code>dynamic_uv</code>).
<code>probs</code>	Length-3 vector of quantiles to plot. Default <code>c(0.025, 0.5, 0.975)</code> for 95 percent intervals.
<code>coefs</code>	Optional character vector of coefficient names to subset.
<code>...</code>	Ignored.

Value

A `ggplot2` object that can be further customised.

Examples

```
data(YX_bin_list)
fit <- lame(YX_bin_list$Y, YX_bin_list$X, family = "binary", R = 0,
           dynamic_beta = "dyad",
           nscan = 60, burn = 15, odens = 5, verbose = FALSE)
if (requireNamespace("ggplot2", quietly = TRUE)) {
  autoplot(fit)
}
```

bipartite_helpers	<i>Bipartite network helper functions</i>
-------------------	---

Description

Bipartite network helper functions

Usage

```
init_bipartite_startvals(
  Y,
  family,
  nA,
  nB,
  RA,
  RB,
  T,
  Xlist = NULL,
  odmax = NULL
)
```

Value

List of starting values for bipartite MCMC

boot_ame-no-fitted	<i>fitted/residuals are not defined for a bootstrap object</i>
--------------------	--

Description

A `boot_ame` stores replicate-level distributional summaries, not per-cell predictions or residuals. These methods exist only to refuse the call clearly (instead of falling through to `stats::fitted.default` / `stats::residuals.default`, which would silently return `NULL`). Apply [fitted](#) / [residuals](#) to the underlying `ame_als` fit instead.

Usage

```
## S3 method for class 'boot_ame'
fitted(object, ...)

## S3 method for class 'boot_ame'
residuals(object, ...)
```

Arguments

object a boot_ame object.
 ... ignored.

Value

Never returns; raises an error.

check_format	<i>Validate input data format for lame function</i>
--------------	---

Description

Internal validation function that checks the format and consistency of input data for longitudinal AME models. Ensures that network data and covariates are properly formatted as lists with consistent dimensions across time periods.

Usage

```
check_format(Y, Xdyad=NULL, Xrow=NULL, Xcol=NULL)
```

Arguments

Y a list of T network matrices, where T is the number of time periods. Each element should be an n x m matrix representing the network at time t.

Xdyad an optional list of T dyadic covariates. Each element can be either an n x m matrix (single covariate) or an n x m x p array (p covariates). Must have the same length as Y if provided.

Xrow an optional list of T matrices of row/sender covariates. Each element should be an n x pr matrix where pr is the number of row covariates. Must have the same length as Y if provided.

Xcol an optional list of T matrices of column/receiver covariates. Each element should be an m x pc matrix where pc is the number of column covariates. Must have the same length as Y if provided.

Details

Validates input data for longitudinal network analysis:

- Verifying Y is a non-empty list of matrices
- Checking that all covariates (if provided) are lists of appropriate length
- Validating data types for all elements
- Warning about dimension inconsistencies across time periods

The function uses informative error messages via the cli package to help users identify and correct data formatting issues.

Value

Invisible TRUE if all checks pass. Throws an error with an informative message if any validation fails.

Note

This is an internal function primarily used by lame() but exported for advanced users who want to validate their data before model fitting.

Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

coef.als_dynamic_beta *Extract beta path from a penalised-ALS object*

Description

Extract beta path from a penalised-ALS object

Usage

```
## S3 method for class 'als_dynamic_beta'
coef(object, ...)
```

Arguments

object	An als_dynamic_beta object.
...	Ignored.

Value

The $p \times T$ matrix of estimates.

coef.ame

*Extract model coefficients from AME model***Description**

Returns posterior means of regression coefficients from a fitted AME or LAME model.

Usage

```
## S3 method for class 'ame'
coef(object, ...)

## S3 method for class 'lame'
coef(object, ...)
```

Arguments

object Fitted AME model (class "ame" or "lame").
 ... Additional arguments (ignored).

Details

For a static fit (the default, and any model with `dynamic_beta = FALSE`), coefficients are returned as a named numeric vector computed as `colMeans(fit$BETA)`.

For a dynamic fit (`lame(..., dynamic_beta = ...)` where some coefficient is time-varying), `fit$BETA` is a 3-dimensional array `[n_stored, p, T]` and `coef.lame` returns a `[p, T]` matrix of per-period posterior means. Rownames are the coefficient names; colnames are the period labels (from `names(Y)` or `t1, t2, ...`). Static coefficients in a dynamic fit are constant across the columns.

For binary models, these are on the probit (latent) scale. Use [predict.ame](#) with `type = "response"` to get predicted probabilities.

What `coef()` does not return. The multiplicative latent positions U, V are not part of the coefficient vector; they live on `fit$U` and `fit$V` (or as 3-D arrays `[n, R, T]` when `dynamic_uv` is on). The additive sender / receiver effects a, b are on `fit$APM` and `fit$BPM`. For a tidy frame of latent positions use [latent_positions](#); for sender / receiver lollipops use [ab_plot](#).

Value

Named numeric vector (static fit) or $p \times T$ matrix (dynamic_beta fit) of posterior mean coefficients.

See Also

[vcov.ame](#) for the posterior covariance matrix, [confint.ame](#) for credible intervals, [summary.ame](#) for a full summary table

coef.ame_als	<i>Extract coefficients from a fast AME fit</i>
--------------	---

Description

Returns the point-estimated regression coefficients (intercept first) of an `ame_als` fit. There is no posterior here; for uncertainty use [ame_als_bootstrap](#).

Usage

```
## S3 method for class 'ame_als'
coef(object, ...)
```

Arguments

<code>object</code>	an <code>ame_als</code> object.
<code>...</code>	ignored.

Value

A named numeric vector of coefficients.

coef.boot_ame	<i>Point estimates from a fast AME bootstrap</i>
---------------	--

Description

Returns the intercept and regression coefficient point estimates carried by a `boot_ame` object (the estimates the bootstrap quantifies). For their bootstrap standard errors and intervals see [confint.boot_ame](#) and [vcov.boot_ame](#).

Usage

```
## S3 method for class 'boot_ame'
coef(object, ...)
```

Arguments

<code>object</code>	a <code>boot_ame</code> object.
<code>...</code>	ignored.

Value

A named numeric vector of coefficient point estimates.

coldwar

Cold War data

Description

Positive and negative relations between countries during the cold war

Format

A list including the following dyadic and nodal variables:

- cc: a socioarray of ordinal levels of military cooperation (positive) and conflict (negative), every 5 years;
- distance: between-country distance (in thousands of kilometers);
- gdp: country gdp in dollars every 5 years;
- polity: country polity every 5 years.

Source

Xun Cao : <https://polisci.la.psu.edu/people/xuc11/>

combine_ame_chains

Combine multiple AME chains

Description

Combine multiple AME chains

Usage

```
combine_ame_chains(chain_list, diagnostics = TRUE)
```

Arguments

chain_list	List of ame fit objects from multiple chains
diagnostics	Logical; whether to compute convergence diagnostics (default TRUE)

Value

A single ame object with combined chains

Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

compact_ame	<i>Optimize AME model output for memory efficiency</i>
-------------	--

Description

Optimizes AME model storage by converting matrices to sparse format.

Usage

```
compact_ame(fit, use_sparse_matrices = FALSE)
```

Arguments

fit	Fitted AME model
use_sparse_matrices	Logical; whether to use sparse matrix storage (default: FALSE)

Details

When `use_sparse_matrices = TRUE`, the posterior-mean matrices YPM and EZ are converted to sparse storage via the **Matrix** package, but only when a matrix's nonzero density is below 0.5 – converting a dense posterior-mean matrix would *grow* memory, so denser matrices are left as ordinary dense matrices. For `lame` fits, where YPM/EZ are per-period lists, the check and conversion are applied per element. The additive-effect summaries APM/BPM are named numeric vectors and are never converted. Names and dimnames are preserved.

Value

Memory-optimized AME model object

Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

compute_gof_bipartite	<i>Compute GOF statistics for bipartite networks</i>
-----------------------	--

Description

Compute GOF statistics for bipartite networks

Usage

```
compute_gof_bipartite(Y_obs, Y_sim, family)
```

Value

List of observed and simulated GOF statistics

```
compute_mcmc_diagnostics
```

Compute MCMC convergence diagnostics for multiple chains

Description

Computes Gelman-Rubin R-hat and effective sample size (ESS) across two or more independently-seeded chains, for both the regression coefficients (BETA) and the variance components (VC). ESS is computed on the pooled draws, so genuinely non-converged chains report a low ESS rather than an inflated one.

Usage

```
compute_mcmc_diagnostics(chain_list)
```

Arguments

`chain_list` a list of fitted `ame/lame` objects, one per chain (each must carry a BETA matrix).

Value

A list with `rhat`, `ess`, `param_names` (over BETA and VC), `n_chains` and `n_samples`.

Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

```
compute_XtX_Xty_bip_cpp
```

Compute $X'X$ and $X'y$ for bipartite covariate regression

Description

Replaces the $O(T \times p^2 \times n^2)$ nested R loop for bipartite XtX and Xty computation with a single C++ call.

Usage

```
compute_XtX_Xty_bip_cpp(Xlist, resid, p)
```

Arguments

<code>Xlist</code>	List of T arrays, each $n_A \times n_B \times p$
<code>resid</code>	3D array of residuals $n_A \times n_B \times T$
<code>p</code>	Number of covariates

Value

List with XtX (p x p) and Xty (p vector)

comtrade	<i>Comtrade data</i>
----------	----------------------

Description

Eleven years of import and export data between 229 countries. The data use the SITC Rev. 1 commodity classification, aggregated at the first level (AG1).

Format

A list consisting of a socioarray Trade and a vector dollars2010 of inflation rates. The socioarray gives yearly trade volume (exports and imports) in dollars for 10 different commodity classes for eleven years between 229 countries. This gives a five-way array. The first index is the reporting country, so Trade[i, j, t, k, 1] is what i reports for exports to j, but in general this is not the same as Trade[j, i, t, k, 2], what j reports as importing from i.

Source

<https://comtrade.un.org/>, <https://www.measuringworth.com/>

confint.ame	<i>Bayesian credible intervals for AME model parameters</i>
-------------	---

Description

Returns posterior **equal-tailed quantile-based** credible intervals (not highest-posterior-density, HPD). Built directly from quantile(object\$BETA, c(alpha/2, 1-alpha/2)) and quantile(object\$VC, ...). These are Bayesian credible intervals, not frequentist confidence intervals.

Usage

```
## S3 method for class 'ame'
confint(object, parm = NULL, level = 0.95, ...)

## S3 method for class 'lame'
confint(object, parm = NULL, level = 0.95, ...)
```

Arguments

object	fitted AME / LAME model.
parm	character vector of parameter names, or numeric indices. When parm is character, both BETA names (e.g. "intercept", "x1_dyad") and variance-component names ("va", "vb", "cab", "rho", "ve") are accepted. NULL (default) returns intervals for all available parameters.
level	credible level (default 0.95).
...	additional arguments (ignored).

Value

Matrix with one row per parameter and two columns (e.g. "2.5%", "97.5%").

Note on interval type

These are equal-tailed quantile intervals, not HPD. For an HPD interval use e.g. `coda::HPDinterval` on the columns of `object$BETA` and `object$VC` directly.

confint.ame_als

Confidence intervals for a fast AME fit

Description

Wald confidence intervals for the intercept and dyadic-covariate coefficients of an [ame_als](#) fit, built from the conditional sandwich covariance ([vcov.ame_als](#)).

Usage

```
## S3 method for class 'ame_als'
confint(object, parm = NULL, level = 0.95, ...)
```

Arguments

object	an <code>ame_als</code> fit.
parm	character vector of parameter names, or integer indices; if NULL (default) all available coefficients are returned.
level	confidence level (default 0.95).
...	passed to vcov.ame_als (e.g. <code>cluster</code>).

Details

These intervals are a fast convenience. They are **conditional** (the additive and multiplicative effects are held fixed) and therefore anti-conservative, and they cover only the regression coefficients the sandwich covariance is defined for – not the node-covariate, additive or multiplicative parameters. For fully-propagated intervals on all parameters, use [ame_als_bootstrap](#) and [confint.boot_ame](#).

Value

A matrix with one row per coefficient and lower/upper bound columns.

See Also

[ame_als_bootstrap](#) for bootstrap intervals on all parameters.

confint.boot_ame	<i>Confidence intervals from a fast AME bootstrap</i>
------------------	---

Description

Bootstrap confidence intervals for the intercept and regression coefficients of a fast AME fit.

Usage

```
## S3 method for class 'boot_ame'
confint(
  object,
  parm = NULL,
  level = 0.95,
  ci_type = c("percentile", "basic"),
  which = c("all", "beta", "vc", "a", "b", "U", "V"),
  ...
)
```

Arguments

object	a boot_ame object.
parm	character vector of parameter names, or integer indices. If NULL (default), all coefficients are returned.
level	confidence level (default 0.95).
ci_type	interval type: "percentile" (default) uses the replicate quantiles directly and matches the intervals reported by <code>summary()</code> and <code>tidy()</code> on the same fit; "basic" reflects the replicate quantiles about the point estimate ($2\hat{\theta} - q$), which corrects first-order bias and can be preferable for the IRLS binary/Poisson point estimators on small samples.
which	which uncertainty channel to return: "all" (default, intercept + regression coefficients + variance components + sender effects • receiver effects + multiplicative U/V), or a single channel: "beta", "vc", "a", "b", "U", "V".
...	ignored.

Value

A matrix with one row per parameter and lower/upper bound columns.

design_array	<i>Computes the design socioarray of covariate values</i>
--------------	---

Description

Computes the design socioarray of covariate values for an AME fit

Usage

```
design_array(Xrow=NULL,Xcol=NULL,Xdyad=NULL,intercept=TRUE,n,warn=TRUE)
```

Arguments

Xrow	an n x pr matrix of row covariates
Xcol	an n x pc matrix of column covariates
Xdyad	an n x n x pd array of dyadic covariates
intercept	logical
n	number of rows/columns
warn	logical; warn when missing covariate values are zero-filled (default TRUE). Set FALSE when the caller has already propagated the missingness into the response.

Value

an n x n x (pr+pc+pd+intercept) 3-way array

Author(s)

Peter Hoff

design_array_listwisedel	<i>Computes the design socioarray of covariate values</i>
--------------------------	---

Description

Computes the design socioarray of covariate values for an AME fit

Usage

```
design_array_listwisedel(Xrow=NULL,Xcol=NULL,Xdyad=NULL,intercept=TRUE,n)
```

Arguments

Xrow	an n x pr matrix of row covariates
Xcol	an n x pc matrix of column covariates
Xdyad	an n x n x pd array of dyadic covariates
intercept	logical
n	number of rows/columns

Value

an n x n x (pr+pc+pd+intercept) 3-way array

Author(s)

Peter Hoff

detect_change_point	<i>Detect potential change points in a dynamic_beta posterior path</i>
---------------------	--

Description

For each dynamic coefficient in a dynamic_beta fit, compares the posterior distribution of the maximum scaled first-difference $M = \max_t |\beta_t - \beta_{t-1}| / \sigma_\beta$ to a Monte-Carlo approximation of the same statistic under the AR(1) prior. The returned bf column is the tail-ratio score $\Pr(M^{post} > m^*) / 0.05$, where m^* is the 95\ quantile of M^{prior} . It is kept under the historical column name for compatibility, but it is not a marginal-likelihood Bayes factor. Use it to surface posterior temporal jumps that the AR(1) prior cannot comfortably accommodate.

Usage

```
detect_change_point(
  fit,
  coefs = NULL,
  n_prior_sims = 2000L,
  threshold_bf = 10,
  seed = NULL
)
```

Arguments

fit	A fitted lame object with dynamic_beta.
coefs	Optional character vector of coefficient names to check. Defaults to every dynamic coefficient on the fit.
n_prior_sims	Number of prior simulations for the null distribution. Default 2000.
threshold_bf	Cutoff for the "warn" column. Default 10; lower to 5 if the false-positive rate on AR(1) data is too high.
seed	Optional seed for reproducibility.

Value

A data frame with one row per dynamic coefficient: `coef`, `bf` (the heuristic tail-ratio score), `m_post_mean` (posterior mean of M), `m_prior_q95` (95\ M), `t_hat` (period of the largest scaled jump), `warn` (logical, `bf > threshold_bf`).

Examples

```
data(YX_bin_list)
fit <- lame(YX_bin_list$Y, YX_bin_list$X, family = "binary", R = 0,
           dynamic_beta = "dyad",
           nscan = 60, burn = 15, odens = 5, verbose = FALSE)
detect_change_point(fit)
```

dutchcollege

Dutch college data

Description

Longitudinal relational measurements and nodal characteristics of Dutch college students, described in van de Bunt, van Duijn, and Snijders (1999). The time interval between the first four measurements was three weeks, whereas the interval between the last three was six weeks.

Format

A list consisting of a socioarray `Y` and a matrix `X` of static nodal attributes. The relational measurements range from -1 to 4, indicating the following:

- -1 a troubled or negative relationship
- 0 don't know
- 1 neutral relationship
- 2 friendly
- 3 friendship
- 4 best friends

Source

Originally available at <http://moreno.ss.uci.edu/data.html#vdb> (site no longer accessible).

dynamic_beta_prior_summary

Summarise the implied prior on a time-varying coefficient path

Description

Draws `ndraws` sample paths of length `T` from the `dynamic_beta` prior (given a `kind`, AR(1) hyperparameters, and an inverse-gamma on the innovation variance) and reports the implied distribution of common summary statistics: maximum absolute first difference, roughness (sum of squared first differences), path range, and correlation with time. Use this before fitting to confirm that your prior is loose / tight enough.

Usage

```
dynamic_beta_prior_summary(
  T = 10L,
  ndraws = 5000L,
  kind = c("ar1", "rw1", "rw2", "matern32"),
  rho_mean = 0.8,
  rho_sd = 0.15,
  rho_lower = 0,
  rho_upper = 0.999,
  sigma_shape = 2,
  sigma_scale = 1,
  matern32_length_scale = 2,
  threshold = 1,
  seed = NULL
)
```

Arguments

<code>T</code>	Length of the path (default 10).
<code>ndraws</code>	Number of paths to draw (default 5000).
<code>kind</code>	One of "ar1", "rw1", "rw2", "matern32". Default "ar1". For "matern32" the path is drawn from a continuous-time Matérn-3/2 GP with length scale <code>matern32_length_scale</code> and marginal variance σ_β^2 .
<code>rho_mean</code> , <code>rho_sd</code>	Prior mean/SD on ρ (AR(1) only). Used to parameterise a Beta prior on the standardised ρ .
<code>rho_lower</code> , <code>rho_upper</code>	Truncation bounds (AR(1) only). Default <code>[0, 0.999]</code> .
<code>sigma_shape</code> , <code>sigma_scale</code>	Inverse-Gamma shape / scale on σ_β^2 . Defaults shape = 2, scale = 1.
<code>matern32_length_scale</code>	Length scale for the Matérn-3/2 covariance (<code>kind = "matern32"</code> only). Default 2.

threshold Cutoff for the prob_max_diff_gt_threshold summary. Default 1.
 seed Optional integer seed for reproducibility.

Details

For kind = "ar1", rho_mean/rho_sd are translated to a Beta prior on the standardised $(\rho - \rho_{lower}) / (\rho_{upper} - \rho_{lower})$. For kind = "rw1", $\rho = 1$ is fixed and only σ_β^2 is sampled. For kind = "rw2", the second-difference variance is sampled and the first two values use a diffuse $N(0, 10)$ initial prior.

Value

A list with components:

summary Data frame with quantile rows for max-first-diff, roughness, path range, trend correlation.
 prob_max_diff_gt_threshold Empirical probability that the maximum absolute first difference exceeds threshold.
 rho Length ndraws vector of sampled rho values (NA for kinds with fixed rho).
 sigma Length ndraws vector of sampled sigma values.
 paths ndraws x T matrix of sample paths.

Examples

```
# Default prior: AR(1) with rho_mean = 0.8, rho_sd = 0.15
s <- dynamic_beta_prior_summary(T = 10, ndraws = 2000, seed = 1)
s$summary
# what's the probability that consecutive beta_t differ by more than 1?
s$prob_max_diff_gt_threshold

# Tighter prior on innovation variance
s_tight <- dynamic_beta_prior_summary(sigma_scale = 0.1, seed = 1)
s_tight$summary
```

el2sm

Edgelist to sociomatrix

Description

Construction of a sociomatrix from an edgelist

Usage

```
el2sm(e1, directed=TRUE, nadiag=all(e1[,1]!=e1[,2]))
```

Arguments

e1	a matrix in which each row contains the indices of an edge and possibly the weight for the edge
directed	if FALSE, then a relation is placed in both entry ij and ji of the sociomatrix, for each edge ij (or ji)
nadiag	put NAs on the diagonal

Value

a sociomatrix

Author(s)

Peter Hoff

Examples

```
Y<-matrix(rpois(10*10,.5),10,10) ; diag(Y)<-NA
E<-sm2el(Y)
el2sm(E) - Y
```

evaluate_heldout

Held-out predictive evaluation for an ame / lame fit

Description

Computes family-appropriate held-out predictive scores given a fit and a logical mask of cells to score. The function does not split the data for you: it expects you to have either (a) refit on a training subset and now want to score the held-out cells of the same matrix, or (b) have predicted probabilities you want scored. Both AUROC and PR-AUC are reported when applicable, alongside Brier and mean log density.

Usage

```
evaluate_heldout(y_obs, y_pred, mask, family = "binary")
```

Arguments

y_obs	Observed outcomes. For longitudinal fits, a list of per-period matrices; for cross-sectional, a single matrix. Cells not in mask are ignored.
y_pred	Predicted probabilities / means on the response scale. Same shape as y_obs.
mask	Logical mask of the same shape as y_obs marking cells to score (TRUE = include in evaluation).
family	Family string; used to pick the scoring rule. Defaults to "binary".

Details

Workflow. The typical pattern is: mask a random sample of dyads to NA in Y, refit (`lame()` handles NA internally via data augmentation), call `predict(fit, type = "response")`, then pass that prediction alongside the original Y and the held-out mask to this function. See the examples.

Dependencies. AUROC / PR-AUC use **precrec** when available; if not installed, only Brier and mean log-density are computed and a one-line note is emitted.

Value

A one-row data frame with columns appropriate to the family: `n_eval`, plus `auroc` + `auprc` + `brier` + `logloss` (binary / cbin), or `rmse` + `mae` + `mean_logdens` (normal), or `mean_logdens` + `rmse` (poisson).

Examples

```
set.seed(1)
n <- 25; Y <- matrix(rbinom(n*n, 1, 0.3), n, n); diag(Y) <- NA
rownames(Y) <- colnames(Y) <- paste0("a", sprintf("%02d", 1:n))
# mask 20% of dyads
mask <- matrix(FALSE, n, n)
obs_idx <- which(!is.na(Y))
set.seed(1)
mask[sample(obs_idx, floor(0.2 * length(obs_idx)))] <- TRUE
Y_train <- Y; Y_train[mask] <- NA
fit <- ame(Y_train, R = 0, family = "binary",
          burn = 15, nscan = 60, odens = 5, verbose = FALSE, plot = FALSE)
y_pred <- predict(fit, type = "response")
evaluate_heldout(Y, y_pred, mask, family = "binary")
```

ffbs_vecG

Forward-filter / backward-sample for vec(G_t) under AR(1) state prior

Description

One Carter-Kohn sweep over the per-period observations of the form $\text{vec}(E_t) = H_t g_t + \text{eps}_t$, with state transition $g_t = \rho * g_{t-1} + \text{eta}_t$.

Usage

```
ffbs_vecG(E_cube, U_cube, V_cube, s2, rho_G, sigma_G2)
```

Arguments

E_cube	nA x nB x T residual cube (Z minus base - a - b - UV')
U_cube	nA x RA x T latent row factor cube
V_cube	nB x RB x T latent column factor cube

s2	scalar observation variance
rho_G	AR(1) coefficient in $(-1, 1)$ (use $\rho = 1$ for the RW1 limit; the forward variance is clamped via a tiny floor).
sigma_G2	state innovation variance

Value

list with G_cube (RA x RB x T) and vecG_path (p x T draws of the vectorised state).

fitted.ame	<i>Extract fitted values from AME model</i>
------------	---

Description

Returns the posterior mean of the network on the response scale (YPM). For binary models, these are predicted probabilities between 0 and 1. For normal models, these are predicted continuous values. For Poisson models, these are predicted counts.

Usage

```
## S3 method for class 'ame'
fitted(object, ...)
```

Arguments

object	Fitted AME model object (class "ame").
...	Additional arguments (not used).

Value

An $n \times n$ matrix (unipartite) or $nA \times nB$ matrix (bipartite) of fitted values on the response scale. Diagonal entries are NA for unipartite networks.

Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

See Also

[predict.ame](#) for predictions with type control, [residuals.ame](#) for residuals

fitted.ame_als	<i>Extract fitted values from a fast AME fit</i>
----------------	--

Description

Returns response-scale fitted values: a single matrix for a cross-sectional (ame_als) fit, or a list of matrices for a longitudinal (lame_als) fit.

Usage

```
## S3 method for class 'ame_als'
fitted(object, ...)
```

Arguments

object	an ame_als object.
...	ignored.

Value

A matrix or list of matrices of fitted values.

fitted.lame	<i>Extract fitted values from LAME model</i>
-------------	--

Description

Extract fitted values from LAME model

Usage

```
## S3 method for class 'lame'
fitted(object, ...)
```

Arguments

object	Fitted LAME model
...	Additional arguments

Value

List of fitted value matrices (one per time point)

forecast_pit	<i>Probability-integral-transform calibration check for h-step forecasts</i>
--------------	--

Description

For a fit with at least one dynamic component, evaluates how well the h -step posterior-predictive distribution covers the actually observed outcomes at the corresponding period(s). A well-calibrated forecast produces approximately Uniform(0, 1) PIT values.

Usage

```
forecast_pit(fit, y_future, h = NULL, n_draws = NULL)
```

Arguments

<code>fit</code>	A fitted <code>lame</code> object trained on the first $T - h$ periods (the function does not refit; the user is responsible for the train/forecast split).
<code>y_future</code>	A list of length h of held-out observed matrices, one per forecast period. The same shape as <code>fit\$YPM[[t]]</code> elements.
<code>h</code>	The forecast horizon (length of <code>y_future</code>). Inferred from <code>length(y_future)</code> when not supplied.
<code>n_draws</code>	Number of posterior draws to use for the forecast. Default uses all stored draws.

Details

Workflow: fit on periods $1:(T - h)$, forecast h steps ahead, score against the held-out $T - h + 1 : T$ observations. Returns a numeric vector of PIT values (one per observed dyad in the held-out periods), plus a one-row summary with the Kolmogorov-Smirnov statistic against Uniform(0, 1) and a fraction-of-observed-dyads coverage diagnostic.

Families. For `family = "normal"`, the PIT is computed analytically from the per-draw forecast variance. For discrete families (`"binary"`, `"poisson"`, `"ordinal"`) the randomised PIT of Czado, Gneiting & Held (2009) is used. For rank families (`"cbin"`, `"frn"`) PIT is not implemented; the function returns NULL with an informational note.

Plotting. The companion `plot()` method on the returned object renders a histogram with a uniform reference line. Use `ggplot2::ggplot(pit$pit) + geom_histogram()` for custom plots.

Value

A list of class `forecast_pit` with components `pit` (numeric vector), `ks_stat` (KS statistic against Uniform), `ks_p` (KS p-value), `cover_95` (fraction of PIT values in $[0.025, 0.975]$).

References

Czado, C., Gneiting, T., & Held, L. (2009). Predictive model assessment for count data. *Biometrics*, 65(4), 1254-1261.

Examples

```

data(YX_bin_list)
Y_train <- YX_bin_list$Y[1:3]
Y_test <- YX_bin_list$Y[4]
X_train <- YX_bin_list$X[1:3]
fit <- lame(Y_train, Xdyad = X_train,
            family = "binary", R = 0,
            dynamic_beta = "dyad",
            nscan = 60, burn = 15, odens = 5, verbose = FALSE)
pit <- forecast_pit(fit, y_future = Y_test)
pit$ks_p
plot(pit)

```

formula.ame

formula() is not defined for an ame() / lame() fit

Description

ame() and lame() use named arguments (Xrow, Xcol, Xdyad, symmetric, etc.) rather than a formula interface. The summary() output renders a pseudo-formula for diagnostic display, but it is not a valid R formula and cannot be passed back to a fitting function.

Usage

```

## S3 method for class 'ame'
formula(x, ...)

## S3 method for class 'lame'
formula(x, ...)

```

Arguments

x an ame or lame fit.

... ignored.

Value

Never returns; raises an error.

get_design_rep	Create design array for replicate data
----------------	--

Description

Create design array for replicate data

Usage

```
get_design_rep(Y, Xdyad, Xrow, Xcol, actorSet, intercept, n, N, pr, pc, pd)
```

Arguments

Y	dependent variable in array format
Xdyad	dyadic covariates in array format
Xrow	sender covariates in array format
Xcol	receiver covariates in array format
actorSet	vector of actors
intercept	logical indicating whether to include intercept
n	number of actors
N	number of replicates
pr	number of receiver covariates
pc	number of sender covariates
pd	number of dyadic covariates

Value

returns list of design array values necessary for ame_repL

Author(s)

Shahryar Minhas

```
get_EZ_dynamic_beta_cpp
```

Compute EZ when beta is time-varying

Description

Rebuild the ($n \times n \times T$) or ($n_A \times n_B \times T$) EZ cube using a per-period beta vector. Mirrors `get_EZ_cpp` / `get_EZ_bip_cpp` but accepts a ($T \times p$) beta matrix where each row is the beta for that period.

Usage

```
get_EZ_dynamic_beta_cpp(  
  Xlist,  
  beta_full_path,  
  a_mat,  
  b_mat,  
  U_cube,  
  V_cube,  
  G,  
  bipartite,  
  symmetric  
)
```

Arguments

<code>Xlist</code>	T-length list of design arrays (each $n \times n \times p$ or $n_A \times n_B \times p$).
<code>beta_full_path</code>	($T \times p$) matrix of per-period beta. For coefficients that are not in the dynamic block, the rows are identical (the static beta replicated across all periods).
<code>a_mat</code>	($n_a \times T$) row effects (or <code>repmat</code> -ed static effects).
<code>b_mat</code>	($n_b \times T$) column effects.
<code>U_cube</code>	($n_u \times R \times T$) row latent positions (or replicated-static).
<code>V_cube</code>	($n_v \times R \times T$) column latent positions.
<code>G</code>	($R \times R$ or $R_A \times R_B$) interaction matrix (bipartite); identity for unipartite.
<code>bipartite</code>	TRUE/FALSE.
<code>symmetric</code>	TRUE/FALSE.

Value

$n_a \times n_b \times T$ cube of EZ values.

get_fit_object	<i>Get fitted object from MCMC results</i>
----------------	--

Description

Get fitted object from MCMC results

Usage

```
get_fit_object(
  APS,
  BPS,
  UVPS,
  YPS,
  BETA,
  VC,
  GOF,
  Xlist,
  actorByYr,
  colActorByYr = NULL,
  start_vals,
  symmetric,
  tryErrorChecks,
  model.name = NULL,
  U = NULL,
  V = NULL,
  dynamic_uv = FALSE,
  dynamic_ab = FALSE,
  bip = FALSE,
  rho_ab = NULL,
  rho_uv = NULL,
  family = NULL,
  odmax = NULL,
  nA = NULL,
  nB = NULL,
  n_time = NULL,
  Y_obs = NULL,
  G = NULL,
  dynamic_beta = FALSE,
  beta_dynamic_mask = NULL,
  beta_dynamic_groups = NULL,
  rho_beta = NULL,
  sigma_beta = NULL,
  RHO_BETA = NULL,
  SIGMA_BETA = NULL,
  dynamic_rho = FALSE,
  RHO = NULL,
```

```

    rho_path = NULL
)

```

Arguments

APS	summed additive sender random effects (or matrix for dynamic)
BPS	summed additive receiver random effects (or matrix for dynamic)
UVPS	summed multiplicative random effects
YPS	summed Y posterior predictive values
BETA	Matrix of draws for regression coefficient estimates
VC	Matrix of draws for variance estimates
GOF	Matrix of draws for goodness of fit calculations
Xlist	List based version of design array
actorByYr	List of actors by time point. In bipartite mode this is the per-year list of row actors.
colActorByYr	Bipartite only. List of column actors by time point; defaults to NULL (unipartite).
start_vals	start_vals for future model run
symmetric	logical indicating whether model is symmetric
tryErrorChecks	list with counts of MCMC errors
model.name	Name of the model (optional)
U	Latent sender positions (optional, for dynamic UV)
V	Latent receiver positions (optional, for dynamic UV)
dynamic_uv	logical indicating whether UV effects are dynamic
dynamic_ab	logical indicating whether additive effects are dynamic
bip	logical indicating whether the network is bipartite
rho_ab	temporal correlation parameter for additive effects (optional)
rho_uv	temporal correlation parameter for multiplicative effects (optional)
family	character string specifying the model family (e.g., "binary", "normal", "poisson")
odmax	vector of maximum ranks for ordinal or fixed rank nomination families
nA	number of actors in first mode (for bipartite networks)
nB	number of actors in second mode (for bipartite networks)
n_time	number of time periods (for longitudinal models)
Y_obs	original observed network (stored for residuals computation)
G	bipartite interaction matrix mapping row to column latent spaces
dynamic_beta	logical or scalar; whether the BETA storage is 3-D (dynamic_beta path). Default FALSE.
beta_dynamic_mask	logical vector marking which coefficients are dynamic.

beta_dynamic_groups	character vector of per-coefficient block labels ("intercept", "dyad", "row", "col"); "" for static coefficients.
rho_beta	named numeric vector of per-block AR(1) rho values (one per dynamic block).
sigma_beta	named numeric vector of per-block AR(1) innovation standard deviations.
RHO_BETA	matrix of per-iteration rho_beta draws (rows = MCMC draw, cols = dynamic block).
SIGMA_BETA	matrix of per-iteration sigma_beta draws.
dynamic_rho	logical indicating whether residual dyadic reciprocity varies by period.
RHO	matrix of per-iteration, per-period dyadic reciprocity draws.
rho_path	numeric vector of period-specific dyadic reciprocity values.

Value

Fitted AME object

Author(s)

Shahryar Minhas

get_start_vals	<i>Get fitted object from MCMC results</i>
----------------	--

Description

Get fitted object from MCMC results

Usage

```
get_start_vals(start_vals, Y, family, xP, rvar, cvar, R, odmax = NULL)
```

Arguments

start_vals	List object that is null or contains starting values
Y	dependent variable in array format
family	character vector (e.g. 'bin', 'nrm') specifying family type
xP	number of exogenous covariates
rvar	logical indicating whether to include sender random effects
cvar	logical indicating whether to include receiver random effects
R	Number of dimensions for multiplicative effects
odmax	vector of maximum ranks for cbin/frn families (optional)

Value

List of starting values for MCMC

Author(s)

Shahryar Minhas

glance	<i>S3 generic for glance</i>
--------	------------------------------

Description

Light-weight fallback so `glance(fit)` dispatches through S3 even when **broom** or **generics** is not loaded.

Usage

```
glance(x, ...)
```

Arguments

<code>x</code>	An object to glance at.
<code>...</code>	Passed to the method.

Value

A one-row data frame.

glance.ame	<i>Glance method for fitted ame / lame objects</i>
------------	--

Description

One-row data frame summarising model-level statistics, in the **broom** idiom. Used by `modelsummary::modelsummary()` and similar tabling tools to populate the lower goodness-of-fit panel of a regression table.

Usage

```
## S3 method for class 'ame'
glance(x, ...)

## S3 method for class 'lame'
glance(x, ...)
```

Arguments

`x` A fitted ame / lame object.
`...` Ignored.

Value

A one-row data frame with columns:

- `nobs` – number of observed dyads (NA cells excluded).
- `n_actors` – number of distinct actors (for bipartite, row + column actors).
- `n_periods` – number of time periods (1 for ame).
- `n_stored` – number of stored MCMC draws.
- `family` – outcome family ("normal", "binary", ...).
- `mode` – "unipartite", "bipartite".
- `R` – latent-space dimension (or max of `R_row`, `R_col` for bipartite).
- `dynamic_uv`, `dynamic_ab`, `dynamic_beta` – logicals; whether each component is time-varying.
- `elpd_loo` – leave-one-out expected log predictive density. Populated only when a loo object has been cached on the fit: fit with `save_log_lik = TRUE`, then attach it via `fit$loo <- loo(fit)`. NA otherwise (calling `loo(fit)` alone does not modify the fit object).

Examples

```
data(YX_bin_list)
fit <- lame(YX_bin_list$Y, YX_bin_list$X, family = "binary", R = 0,
           nscan = 100, burn = 20, odens = 5, verbose = FALSE)
glance(fit)
```

glance.ame_als

Glance method for fitted ame_als / lame_als objects

Description

One-row data frame summarising an ALS fit, compatible with **broom** / **modelsummary**. Reports observation count, actor count, latent dimension, family, mode, ALS convergence flag, and iteration count.

Usage

```
## S3 method for class 'ame_als'
glance(x, ...)

## S3 method for class 'lame_als'
glance(x, ...)
```

Arguments

`x` A fitted `ame_als` / `lame_als` object.

`...` Ignored.

Value

One-row data frame with columns `nobs`, `n_actors`, `n_periods`, `family`, `mode`, `R`, `converged`, `iterations`, `se_source`.

Examples

```
data(YX_bin_list)
Y1 <- 1 * (YX_bin_list$Y[[1]] > 0); diag(Y1) <- NA
fit <- ame_als(Y = Y1, Xdyad = YX_bin_list$X[[1]],
              family = "binary", R = 1, verbose = FALSE)
glance(fit)
```

gof

Compute GOF statistics from saved posterior samples

Description

Computes goodness-of-fit statistics after model estimation by generating posterior predictive networks from the saved MCMC samples. This is useful when the model was fitted with `gof = FALSE` to speed up MCMC sampling, or when you want to evaluate custom GOF statistics without re-running the model.

Usage

```
gof(fit, Y = NULL, custom_gof = NULL, nsim = 100, verbose = TRUE)
```

Arguments

`fit` An `ame` model object that was run with posterior sampling enabled

`Y` Original data. For `ame` objects, an `n` x `n` matrix (or `nA` x `nB` for bipartite). For `lame` objects, a list of matrices (one per time period). If `NULL`, extracted from the `fit` object.

`custom_gof` Optional custom GOF function(s) - same format as for `ame()`

`nsim` Number of posterior predictive simulations to generate (default 100). If `NULL`, uses all available posterior samples.

`verbose` Logical; print progress information

Details

This function requires that the model was estimated with posterior sampling of the parameters needed to generate posterior predictive datasets. Specifically, it needs:

- BETA: regression coefficients
- VC: variance components
- For models with random effects: samples of a, b
- For models with latent factors: U_samples, V_samples

To enable posterior sampling during model estimation, use: `posterior_opts = posterior_options(save_UV = TRUE, save_ab = TRUE)`

Computing GOF post-hoc has several advantages:

- Faster MCMC sampling (no GOF overhead)
- Can experiment with different GOF statistics without re-running model
- Can control number of posterior predictive simulations independently

Value

A matrix of GOF statistics with the same format as if `gof=TRUE` was used during model estimation. First row contains observed statistics, subsequent rows contain posterior predictive statistics.

Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

See Also

[ame](#), [lame](#), [gof_plot](#)

Examples

```
# Run model without GOF during fitting
data(YX_nrm)
fit <- ame(YX_nrm$Y, Xdyad = YX_nrm$X, R = 2, gof = FALSE,
          nscan = 100, burn = 10, odens = 1, verbose = FALSE)

# Compute GOF post-hoc
gof_result <- gof(fit)
```

gof_plot

*Visualize goodness-of-fit statistics for AME and LAME models***Description**

Plots observed network statistics against their posterior predictive distributions to assess model fit.

Usage

```
gof_plot(
  fit,
  type = c("auto", "static", "longitudinal"),
  statistics = NULL,
  credible.level = 0.95,
  ncol = 2,
  point.size = 2,
  line.size = 1,
  title = NULL,
  ...
)
```

Arguments

<code>fit</code>	An object of class "ame" or "lame" containing GOF statistics
<code>type</code>	Character string: "auto" (default), "static", or "longitudinal". If "auto", determined by model class.
<code>statistics</code>	Character vector of statistics to plot, or NULL (default) for the standard panels plus any custom GOF columns. Unipartite names: "sd.row", "sd.col", "dyad.dep", "triad.dep", "trans.dep"; bipartite names: "sd.row", "sd.col", "four.cycles"; custom GOF columns may also be named. Unknown names are dropped with a warning.
<code>credible.level</code>	Numeric between 0 and 1; credible interval level for longitudinal plots (default 0.95)
<code>ncol</code>	Number of columns for faceted plot layout (default 2)
<code>point.size</code>	Size of points in longitudinal plots (default 2)
<code>line.size</code>	Width of lines in plots (default 1)
<code>title</code>	Optional title for the plot
<code>...</code>	Additional arguments forwarded to the ALS-specific <code>gof_plot.ame_als</code> when <code>fit</code> inherits from <code>ame_als</code> (<code>nsim</code> , <code>seed</code>).

Details**Overview:**

Goodness-of-fit (GOF) assessment is crucial for network models because standard residual diagnostics are often inadequate for capturing network dependencies. This function implements posterior predictive checking by:

1. Computing key network statistics from the observed data
2. Generating multiple networks from the model's posterior predictive distribution
3. Computing the same statistics on simulated networks
4. Visualizing the comparison to identify model inadequacies

Network Statistics Evaluated:

For unipartite (square) networks:

`sd.row` (**Out-degree heterogeneity**) Standard deviation of row means. High values indicate substantial variation in how active nodes are as senders/initiators. If the model underestimates this, it may be missing important sender effects or covariates.

`sd.col` (**In-degree heterogeneity**) Standard deviation of column means. High values indicate substantial variation in node popularity as receivers. Underestimation suggests missing receiver effects or popularity-related covariates.

`dyad.dep` (**Reciprocity/Mutuality**) Correlation between $Y[i, j]$ and $Y[j, i]$. Positive values indicate reciprocity (mutual ties are more likely). The AME model captures this through the dyadic correlation parameter ρ . Poor fit here points to adjusting the `dcor` parameter.

`triad.dep` (**Transitivity/Clustering**) Measures tendency for triadic closure (friend of a friend is a friend). Calculated as correlation between $Y[i, j]$ and $\text{sum}(Y[i, k] * Y[k, j]) / \sqrt{n-2}$. AME captures this through multiplicative effects (U,V). Poor fit suggests increasing the latent dimension R.

For bipartite (rectangular) networks:

`sd.row` (**Type A activity variation**) Standard deviation of row means for Type A nodes. Indicates heterogeneity in how actively Type A nodes connect to Type B nodes.

`sd.col` (**Type B popularity variation**) Standard deviation of column means for Type B nodes. Indicates heterogeneity in how popular Type B nodes are with Type A nodes.

`four.cycles` (**Bipartite clustering**) Count of 4-cycles (rectangular paths A1-B1-A2-B2-A1). High values indicate that pairs of Type A nodes tend to connect to the same Type B nodes. Captured through bipartite multiplicative effects with appropriate `R_row`, `R_col`.

Interpretation Guide:

Histogram plots (static models):

- Dashed orange vertical line (Okabe-Ito #D55E00): observed statistic value (dual-encoded on colour and linetype)
- Grey histogram: distribution from posterior predictive simulations
- Good fit: orange line falls within the bulk of the histogram
- Poor fit: orange line in the tail or outside the distribution

Common model inadequacies and solutions:

Observed `sd.row/sd.col` too high Model underestimates degree heterogeneity. Solutions: Add row/column covariates (`Xrow`, `Xcol`), enable random effects (`rvar=TRUE`, `cvar=TRUE`), or increase their variance.

Observed dyad.dep outside distribution Reciprocity not captured well. Solutions: For positive reciprocity, ensure dcor=TRUE. For negative, consider transformation or different family.

Observed triad.dep too high Clustering/transitivity underestimated. Solutions: Increase latent dimension R, add network covariates that capture homophily, or consider including community structure covariates.

Multiple statistics showing poor fit Fundamental model misspecification. Solutions: Change family, add missing covariates, or consider different model class.

Mathematical Details:

The posterior predictive p-value for statistic s is:

$$p = P(s(Y_{rep}) \geq s(Y_{obs}) | Y_{obs})$$

where Y_{rep} is drawn from the posterior predictive distribution. Values near 0 or 1 indicate poor fit. The function visualizes the full distribution rather than just p-values for richer diagnostics.

Customization:

The function accepts custom GOF statistics through the model's `custom_gof` argument. These are automatically included in the plot. Custom statistics should capture network features important for your specific application.

Computational Notes:

GOF computation involves simulating multiple networks, which can be computationally intensive. The model uses the networks simulated during MCMC if `gof=TRUE` was specified. For post-hoc GOF, use the `gof()` function which generates new simulations.

Good model fit is indicated when:

- Observed statistics fall within the central 95% of posterior predictive distributions
- No systematic patterns of over/underestimation across statistics
- Custom statistics (if provided) also show adequate fit
- For longitudinal models, observed trajectories track within credible bands

Value

A `ggplot2` object that can be further customized

Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

Examples

```
# Fit an AME model
data(YX_nrm)
fit_ame <- ame(YX_nrm$Y, Xdyad = YX_nrm$X, gof = TRUE,
              nscan = 100, burn = 10, odens = 1, verbose = FALSE)

# Basic GOF plot
gof_plot(fit_ame)
```



```
# Plot only degree-related statistics
gof_plot(fit_ame, statistics = c("sd.row", "sd.col"))
```

gof_plot.ame_als	<i>Goodness-of-fit check for an ame_als fit</i>
------------------	---

Description

Bootstrap-style analogue of the MCMC [gof_plot](#): draws `nsim` simulated networks from the fitted ALS model, computes the standard network statistics (`sd.rowmean`, `sd.colmean`, `dyad.dep`, `cycle.dep`, `trans.dep` for unipartite; `sd.rowmean`, `sd.colmean`, `four.cycles` for bipartite) on each replicate, and overlays the observed value on a histogram of replicate values.

Usage

```
gof_plot.ame_als(fit, nsim = 100, seed = NULL, ...)
```

Arguments

<code>fit</code>	an <code>ame_als</code> fit.
<code>nsim</code>	integer; number of replicates (default 100).
<code>seed</code>	optional RNG seed.
<code>...</code>	reserved.

Details

Uses [simulate.ame_als](#) for the replicates and is therefore conditional on the fitted point estimates: the noise is resampled, but `mu`, `beta`, `a`, `b`, `U`, `V` are held fixed. The MCMC `gof_plot.ame` also averages over posterior movement in those parameters.

Value

A `ggplot` (or `patchwork`) object.

gof_stats	<i>Goodness of fit statistics</i>
-----------	-----------------------------------

Description

Calculates goodness of fit statistics for relational data matrices, evaluating second-order (dyadic) and third-order (triadic) dependence patterns. Can handle both unipartite and bipartite networks.

Usage

```
gof_stats(Y, mode = NULL, custom_gof = NULL)
```

Arguments

Y	a relational data matrix. For unipartite networks, a square $n \times n$ matrix where $Y[i,j]$ represents the relationship from node i to node j . For bipartite networks, an $nA \times nB$ matrix where $Y[i,j]$ represents the relationship from node i in set A to node j in set B . Missing values (NA) are allowed and will be handled appropriately.
mode	character string specifying the network type: "unipartite" or "bipartite". If NULL (default), attempts to infer from matrix dimensions (rectangular = bipartite, square = unipartite). Note: square bipartite networks must specify mode="bipartite".
custom_gof	optional function or list of functions to compute custom GOF statistics. Each function should take Y as input and return a named numeric value or vector. Custom statistics will be added to the standard statistics.

Details

The function computes network statistics that capture different aspects of network structure beyond simple density. These statistics are particularly useful for:

- Model checking: comparing observed statistics to those from simulated networks
- Model selection: choosing between models that better capture network dependencies
- Descriptive analysis: summarizing key structural features of the network

For bipartite networks with square dimensions ($nA = nB$), you must explicitly specify mode="bipartite" to ensure correct statistics are calculated.

Missing values in Y are handled by pairwise deletion for correlations and are excluded from matrix products in triadic calculations.

Value

A named numeric vector containing goodness-of-fit statistics. For unipartite networks:

sd.rowmean Standard deviation of row means. Measures the heterogeneity in out-degree centrality (sender effects).

sd.colmean Standard deviation of column means. Measures the heterogeneity in in-degree centrality (receiver effects).

dyad.dep Dyadic dependence/reciprocity correlation.

cycle.dep Cyclic/transitive triadic dependence.

trans.dep Transitive triadic dependence.

For bipartite networks:

sd.rowmean Standard deviation of row means (sender heterogeneity).

sd.colmean Standard deviation of column means (receiver heterogeneity).

four.cycles Count of four-cycles in the bipartite network.

If `custom_gof` is provided, additional statistics will be included with their user-specified names.

Naming note. The columns above are the internal names used by `gof_stats()` and stored on `fit$GOF`. `gof_plot` exposes a shorter user-facing alias for some of them; the mapping is:

internal (this column)	gof_plot alias
sd.rowmean	sd.row
sd.colmean	sd.col
dyad.dep	dyad.dep
cycle.dep	triad.dep
trans.dep	trans.dep
four.cycles (bipartite)	four.cycles

Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

Examples

```
data(YX_nrm)

# Auto-detect unipartite
gof_stats(YX_nrm$Y)

# Bipartite (rectangular) networks are auto-detected; mode can also
# be given explicitly (required when a bipartite network is square)
Y_bip <- matrix(rnorm(120), 10, 12)
gof_stats(Y_bip, mode = "bipartite")

# Custom GOF function
my_stat <- function(Y) { c(my_measure = sum(Y > 0, na.rm = TRUE)) }
gof_stats(YX_nrm$Y, custom_gof = my_stat)
```

gof_stats_bipartite *Goodness of fit statistics for bipartite networks*

Description

Calculates goodness of fit statistics specifically designed for bipartite networks, evaluating degree heterogeneity and higher-order dependencies.

Usage

```
gof_stats_bipartite(Y, warn_square = TRUE)
```

Arguments

Y	a bipartite relational data matrix (nA x nB rectangular matrix) where $Y[i,j]$ represents the relationship from node i in set A to node j in set B. Missing values (NA) are allowed and will be handled appropriately.
warn_square	logical; if TRUE (default) a warning is issued when Y is square (a possible unipartite matrix passed by mistake). Set FALSE for a genuinely square bipartite network.

Details

For bipartite networks, reciprocity and triadic closure are not meaningful concepts since edges only exist between the two node sets. Instead, this function focuses on:

- Degree heterogeneity in both node sets
- Four-cycles as the simplest higher-order dependence pattern

Value

A named numeric vector containing bipartite-specific goodness-of-fit statistics:

sd.rowmean Standard deviation of row means. Measures the heterogeneity in out-degree from set A nodes (sender effects). Higher values indicate more variation in how active A nodes are.

sd.colmean Standard deviation of column means. Measures the heterogeneity in in-degree to set B nodes (receiver effects). Higher values indicate more variation in how popular B nodes are.

four.cycles Count of four-cycles (also called 4-paths or squares) in the bipartite network. A four-cycle occurs when two nodes from set A (e.g., i and k) both connect to the same two nodes in set B (e.g., j and l), forming a closed path: $i \rightarrow j \rightarrow k \rightarrow l \rightarrow i$. This measures the tendency for pairs of A-nodes to share multiple common B-node connections, capturing a form of clustering specific to bipartite networks. High four-cycle counts indicate that connections are not random but show patterns of shared preferences or co-occurrence. For example, in a user-item network, many four-cycles suggest that users who like one item tend to also like other items that co-occur with it.

Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

Examples

```
# Create a random bipartite network
Y <- matrix(rnorm(10*12), 10, 12)

# Calculate GOF statistics
gof_stats_bipartite(Y)
```

gof_stats_unipartite *Goodness of fit statistics for unipartite networks*

Description

Calculates goodness of fit statistics specifically for unipartite (square) networks, evaluating second-order (dyadic) and third-order (triadic) dependence patterns.

Usage

```
gof_stats_unipartite(Y)
```

Arguments

Y	a square n x n relational data matrix where $Y[i, j]$ represents the relationship from node i to node j. Missing values (NA) are allowed and will be handled appropriately. Diagonal values are typically NA for non-self-loop networks.
---	--

Details

This function computes network statistics that capture different aspects of network structure beyond simple density. These statistics are particularly useful for evaluating how well a model captures the observed network patterns.

The dyadic dependence statistic captures reciprocity - the tendency for relationships to be mutual. The triadic statistics capture different forms of triadic closure that are common in social networks.

Missing values in Y are handled by pairwise deletion for correlations and are excluded from matrix products in triadic calculations.

Value

A named numeric vector containing five goodness-of-fit statistics:

sd.rowmean Standard deviation of row means. Measures the heterogeneity in out-degree centrality (sender effects).

sd.colmean Standard deviation of column means. Measures the heterogeneity in in-degree centrality (receiver effects).

dyad.dep Dyadic dependence/reciprocity correlation. Measures the correlation between $Y[i, j]$ and $Y[j, i]$, capturing reciprocity patterns.

cycle.dep Cyclic triadic dependence. Measures the tendency for directed cycles ($i \rightarrow j \rightarrow k \rightarrow i$) in the network.

trans.dep Transitive triadic dependence. Measures the tendency for transitivity (if $i \rightarrow j$ and $j \rightarrow k$, then $i \rightarrow k$) in the network.

Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

Examples

```
# Create a random unipartite network
Y <- matrix(rnorm(100), 10, 10)
diag(Y) <- NA
gof_stats_unipartite(Y)
```

gof_temporal

Posterior-predictive temporal-trend test

Description

For a fitted `lame` object, computes a network statistic (density, reciprocity, or transitivity) at each observed period, fits a least-squares linear trend on period index, and compares the observed slope to slopes from posterior-predictive replicates. The two-sided value is $p_{pp} = 2 * \min(p_{up}, 1 - p_{up})$, which runs from 0 (observed slope in the extreme tail) to 1 (observed slope dead-centre). A static fit on truly trending data yields p_{pp} near 0; a dynamic fit that captures the trend yields p_{pp} near 1.

Usage

```
gof_temporal(
  fit,
  stat = c("auto", "density", "mean", "reciprocity", "transitivity"),
  n_rep = 500,
  seed = NULL
)
```

Arguments

fit	A fitted lame object.
stat	One of "auto" (default; picks "reciprocity" for unipartite directed fits with $T \geq 3$ and family normal / poisson, where "density" is constant and uninformative; otherwise "density"), "density", "mean" (mean of off-diagonal Y; the right "density" analogue for continuous outcomes), "reciprocity", "transitivity".
n_rep	Number of posterior-predictive replicates to draw (each replicate is a full T -period network from <code>simulate(fit)</code>).
seed	Optional RNG seed.

Value

A list with

- stat (chosen statistic name),
- slope_obs (observed slope of stat on period index),
- slope_rep (length-n_rep vector of replicate slopes),
- p_pp (two-sided posterior-predictive p-value),
- stat_obs_by_t, stat_rep_by_t (per-period statistics)

Examples

```
data(YX_bin_list)
fit <- lame(YX_bin_list$Y, YX_bin_list$X, family = "binary", R = 0,
           dynamic_beta = "dyad",
           nscan = 60, burn = 15, odens = 5, verbose = FALSE)
gof_temporal(fit, stat = "density", n_rep = 50)
```

init_dynamic_ab_cpp	<i>Initialize dynamic additive effects with AR(1) structure</i>
---------------------	---

Description

Initialize dynamic additive effects with AR(1) structure

Usage

```
init_dynamic_ab_cpp(n, T, rho_ab, sigma_ab, mean_a = 0, mean_b = 0)
```

Arguments

n	Number of actors
T	Number of time points
rho_ab	AR(1) parameter
sigma_ab	Innovation standard deviation
mean_a	Mean for row effects
mean_b	Mean for column effects

Value

List with initialized a and b matrices

init_dynamic_positions

Initialize dynamic latent positions with AR(1) structure

Description

Initialize dynamic latent positions with AR(1) structure

Usage

```
init_dynamic_positions(n, R, T, rho_uv, sigma_uv)
```

Arguments

n	Number of actors
R	Latent dimension
T	Number of time points
rho_uv	AR(1) parameter
sigma_uv	Innovation standard deviation

Value

3D array of latent positions (n x R x T)

IR90s

*International relations in the 90s***Description**

A relational dataset recording a variety of nodal and dyadic variables on countries in the 1990s, including information on conflicts, trade and other variables. Except for the conflict variable, the variables are averages across the decade.

Format

A list consisting of a socioarray dyadvars of dyadic variables and matrix nodevars of nodal variables. The dyadic variables include

- total number of conflicts;
- exports (in billions of dollars);
- distance (in thousands of kilometers);
- number of shared IGOs (averages across the years);
- polity interaction.

The nodal variables include

- population (in millions);
- gdp (in billions of dollars);
- polity

Source

Michael Ward.

lame

*AME model fitting routine for longitudinal relational data***Description**

An MCMC routine providing a fit to an additive and multiplicative effects (AME) regression model to longitudinal (time-series) relational data of various types. Supports both unipartite (square) and bipartite (rectangular) network structures. For cross-sectional (single time point) networks, use the `ame` function.

Usage

```

lame(
  Y,
  Xdyad = NULL,
  Xrow = NULL,
  Xcol = NULL,
  rvar = TRUE,
  cvar = TRUE,
  dcor = !symmetric,
  nvar = TRUE,
  R = 0,
  R_row = NULL,
  R_col = NULL,
  mode = c("unipartite", "bipartite"),
  dynamic_uv = FALSE,
  dynamic_ab = FALSE,
  dynamic_G = FALSE,
  dynamic_beta = FALSE,
  dynamic_rho = FALSE,
  dynamic_beta_kind = c("ar1", "rw1", "rw2", "matern32"),
  dynamic_uv_kind = c("ar1", "snap", "t"),
  family = "normal",
  intercept = !(family == "ordinal"),
  symmetric = FALSE,
  odmax = NULL,
  prior = list(),
  g = NA,
  seed = 6886,
  nscan = 10000,
  burn = 500,
  odens = 25,
  plot = FALSE,
  verbose = FALSE,
  gof = TRUE,
  start_vals = NULL,
  periodic_save = FALSE,
  out_file = NULL,
  save_interval = 0.25,
  model.name = NULL,
  save_log_lik = FALSE,
  posterior_opts = NULL,
  log_lik_path = NULL,
  log_lik_chunk_size = 10000L,
  keep_snap_draws = c("none", "summary", "draws", "chunked"),
  freeze_call = FALSE,
  dynamic_beta_pool = c("none", "rho", "sigma", "both"),
  dynamic_beta_per_actor = NULL,
  per_actor_covariate_idx = 1L,

```

```

per_actor_identifiability = c("center", "exact_center", "drop_population"),
keep_per_actor = c("auto", "draws", "summary", "none"),
time_index = NULL,
period_exposure = NULL,
max_seconds = Inf,
checkpoint_path = NULL,
checkpoint_every = 100L,
log_lik_method = c("observed_exact", "observed_ghk", "augmented"),
ordinal_cutpoints = c("data_induced", "explicit"),
method = c("mcmc", "als"),
als_stability = c("none", "quick", "validation"),
als_max_iter = 1000L,
als_tol = NULL,
bootstrap = 0L,
bootstrap_type = c("parametric", "block"),
bootstrap_block_length = 1L,
bootstrap_seed = NULL,
resume_from = NULL,
print
)

```

Arguments

Y	a T length list of relational matrices, or a 3D array of dimensions [n_row, n_col, T], where T is the number of time periods. Named lists may have changing actor composition; actors are aligned by row and column names. A longitudinal netify object is also accepted and converted with <code>netify::to_lame(lame = TRUE)</code> . When family or mode is omitted, the value inferred by netify is used. See family below for data types.
Xdyad	a T length list of n x n x pd arrays of covariates
Xrow	a T length list of n x pr matrices of nodal row covariates
Xcol	a T length list of n x pc matrices of nodal column covariates
rvar	logical: fit row random effects (asymmetric case)?
cvar	logical: fit column random effects (asymmetric case)?
dcor	logical: fit a dyadic correlation (asymmetric case)?
nvar	logical: fit nodal random effects (symmetric case)?
R	integer: dimension of the multiplicative effects (can be zero)
R_row	integer: for bipartite networks, dimension of row node multiplicative effects (defaults to R)
R_col	integer: for bipartite networks, dimension of column node multiplicative effects (defaults to R)
mode	character: either "unipartite" (default) for square networks or "bipartite" for rectangular networks
dynamic_uv	logical: fit dynamic multiplicative effects (latent factors). The transition model is selected by <code>dynamic_uv_kind</code> . <code>fit\$U</code> / <code>fit\$V</code> store only the posterior-mean

trajectory cubes; draw-level trajectory uncertainty requires refitting with `posterior_opts = list(save_UV_draws = TRUE)`, which attaches the per-iteration cubes as `fit$U_draws / fit$V_draws`. Default FALSE.

- `dynamic_ab` logical: fit dynamic additive effects (sender/receiver effects) that evolve over time using AR(1) processes. When TRUE, the row effects (a) and column effects (b) become time-varying, following $a_{i,t} = \rho_{ab}a_{i,t-1} + \epsilon_{i,t}$. This captures temporal heterogeneity in actors' baseline propensities to send and receive ties, allowing for smooth changes in activity levels and popularity over time. For example, an actor's tendency to form outgoing ties might gradually increase or decrease across observation periods. The AR(1) specification ensures temporal smoothness while allowing for actor-specific evolution patterns. Implementation uses conjugate updates where possible and C++ for computational efficiency. Default FALSE.
- `dynamic_G` logical (bipartite only). When TRUE the bipartite interaction matrix G_t in $U_t G_t V_t'$ varies by period and is returned as `fit$G_cube`, an $R_{\text{row}} \times R_{\text{col}} \times T$ array. MCMC fits also return posterior summaries for this cube; ALS fits return the penalized point path using the same storage names. The marginal bilinear predictor is identified under the package's canonicalization conventions, while individual entries of G_t can move under equivalent rotations and scalings of U_t and V_t . Default FALSE.
- `dynamic_beta` logical, character, integer, or logical-vector flag selecting which regression coefficients evolve over time via independent AR(1) processes. Default FALSE keeps every coefficient static (the historical behaviour). Accepted forms:
- FALSE / NULL: no coefficient is dynamic.
 - TRUE: every coefficient is dynamic.
 - character vector of block shortcuts ("intercept", "dyad", "row", "col") or specific coefficient names from `colnames(BETA)` – those become dynamic.
 - integer vector: 1-based column indices into `colnames(BETA)`.
 - logical vector of length p: per-coefficient mask.

Each dynamic-coefficient block (one per distinct intercept / dyad / row / col label that has at least one dynamic coefficient) gets its own AR(1) parameters ρ_β (truncated-Normal prior, default mean 0.8, bounded between 0 and 0.999) and σ_β^2 (inverse-Gamma prior, defaults shape 2 / scale 1). The joint posterior over the time path β_t is drawn by Forward-Filter / Backward-Sample (FFBS) inside the MCMC loop, conditional on the current static-block beta and on (a, b, U, V). When the intercept or a nodal coefficient is dynamic, a sum-to-zero contrast basis is applied to the additive-effect sampler to keep $a_i + \text{intercept}_t$ identified. Requires at least 2 time periods. `dynamic_beta` composes with multiplicative latent factors ($R > 0$) and additive random effects for every family, across unipartite/bipartite and directed/symmetric panels and in combination with `dynamic_ab` / `dynamic_uv`. Note: with a single dynamic coefficient block and small T , the AR(1) parameter ρ_β sees only $T - 1$ transitions and is strongly informed by its default truncated-Normal prior (mean 0.8, sd 0.15) rather than the data; if ρ_β itself is of interest, check prior sensitivity (see [dynamic_beta_prior_summary](#)). With `method = "als"`, selected intercept, dyadic, row-node, and column-node coefficients are supported on normal,

	binary, and Poisson panels, including named panels where actors enter or exit. Dynamic ALS uses period-specific <code>Xrow</code> or <code>Xcol</code> values for selected dynamic node coefficients; static node coefficients still use per-actor means. Dynamic intercepts are unavailable when <code>family = "ordinal"</code> . Default FALSE.
<code>dynamic_rho</code>	logical. For directed unipartite normal models, allow the residual dyadic reciprocity parameter ρ_t to vary by period instead of using one pooled dyadic correlation across the whole panel. MCMC fits store per-draw paths in <code>fit\$RHO</code> and the posterior mean path in <code>fit\$rho_path</code> . ALS dynamic fits report a residual <code>rho_path</code> that can be passed to MCMC with <code>als_start_vals</code> . Default FALSE.
<code>dynamic_beta_kind</code>	character: state-space prior on the dynamic coefficient block(s). "ar1" (default) gives mean-reverting AR(1) with a truncated-Normal prior on ρ_β . "rw1" gives a random walk (ρ_β pinned at 1, no truncation), appropriate when you expect permanent drift with no mean reversion – e.g. trade-gravity coefficients in a permanently changing world economy. The alias "random_walk" is also accepted for "rw1". When the stationarity warning in <code>summary(fit)</code> fires under the default AR(1), refit with <code>dynamic_beta_kind = "rw1"</code> for cleaner inference. Decision tree: mean-reverting? AR(1). Permanent / unit-root drift? RW1. Smooth with curvature? "rw2" (second-order random walk). Smooth with a known length-scale? "matern32" (Matern 3/2). Note: "rw2" and "matern32" use an R-level joint Gaussian sampler and run substantially slower per iteration than the C++ FFBS used for "ar1" / "rw1" (roughly 2-4x on $n = 100, T = 10$).
<code>dynamic_uv_kind</code>	Character string selecting the transition model for dynamic multiplicative latent positions when <code>dynamic_uv = TRUE</code> . "ar1" uses Gaussian AR(1) drift, "snap" uses a mixture of AR(1) drift and discontinuous reset transitions, and "t" uses heavy-tailed Student-t innovations represented by local transition scales. On the MCMC path, "snap" and "t" are currently supported for unipartite directed and symmetric models only. With <code>method = "als"</code> , "snap" is also supported for normal bipartite panels when it is the only dynamic block and G is static. With <code>method = "als"</code> , "t" is supported for bipartite normal, binary, and Poisson panels. ALS Student-t dynamic UV fits attach the final local transition-weight matrices as <code>fit\$lambda_u</code> and <code>fit\$lambda_v</code> .
<code>family</code>	character: one of "normal", "binary", "ordinal", "cbin", "frn", "poisson" - see the details below
<code>intercept</code>	logical: fit model with an intercept?
<code>symmetric</code>	logical: is the sociomatrix symmetric?
<code>odmax</code>	a scalar integer or vector of length n giving the maximum number of nominations that each node may make - used for "frn" and "cbin" families
<code>prior</code>	a list containing hyperparameters for the prior distributions. Available options and their defaults: Sab0 Prior covariance matrix for additive effects (default: <code>diag(2)</code>). A 2x2 matrix where <code>Sab0[1,1]</code> is the prior variance for row effects, <code>Sab0[2,2]</code> is the prior variance for column effects, and off-diagonals control correlation between row and column effects.

- eta0** Prior degrees of freedom for covariance of multiplicative effects (default: $4 + 3 \cdot n/100$, where n is the number of actors). Higher values impose stronger shrinkage on the latent factors.
- etaab** Prior degrees of freedom for covariance of additive effects (default: $4 + 3 \cdot n/100$). Controls shrinkage of row/column random effects.
- ab_min_observed** Minimum observed sender/receiver cells used before a static additive effect is left unshrunk (default: $\max(10, T)$). Actors with less support are pulled toward the prior mean for that role.
- rho_uv_mean** For `dynamic_uv=TRUE`: Prior mean for UV AR(1) parameter (default: 0.9). Values close to 1 indicate high temporal persistence.
- rho_uv_sd** For `dynamic_uv=TRUE`: Prior SD for UV AR(1) parameter (default: 0.1). Controls uncertainty about temporal dependence.
- sigma_uv_shape** For `dynamic_uv=TRUE`: Shape parameter for inverse-gamma prior on UV innovation variance (default: 2).
- sigma_uv_scale** For `dynamic_uv=TRUE`: Scale parameter for inverse-gamma prior on UV innovation variance (default: 1).
- uv_max_abs** For `dynamic_uv=TRUE`: loose bound on the raw latent coordinate scale after the product-preserving normalization step (default: 50). This guards the unidentified coordinate scale without changing the fitted $U_t V_t'$ bilinear term.
- rho_ab_mean** For `dynamic_ab=TRUE`: Prior mean for additive effects AR(1) parameter (default: 0.8). Controls temporal smoothness of sender/receiver effects.
- rho_ab_sd** For `dynamic_ab=TRUE`: Prior SD for additive effects AR(1) parameter (default: 0.15).
- sigma_ab_shape** For `dynamic_ab=TRUE`: Shape parameter for inverse-gamma prior on additive effects innovation variance (default: 2).
- sigma_ab_scale** For `dynamic_ab=TRUE`: Scale parameter for inverse-gamma prior on additive effects innovation variance (default: 1).
- rho_beta_mean** For `dynamic_beta`: Prior mean for the per-block AR(1) parameter on time-varying regression coefficients (default: 0.8). Closer to 1 = smoother evolution.
- rho_beta_sd** For `dynamic_beta`: Prior SD for the per-block AR(1) parameter (default: 0.15).
- rho_beta_lower** For `dynamic_beta`: Lower truncation bound on the AR(1) parameter (default: 0). Pass a negative value to allow negative autoregression.
- rho_beta_upper** For `dynamic_beta`: Upper truncation bound (default: 0.999). Closer to 1 admits near-unit-root behaviour.
- sigma_beta_shape** For `dynamic_beta`: Shape parameter for the inverse-Gamma prior on the per-block innovation variance (default: 2).
- sigma_beta_scale** For `dynamic_beta`: Scale parameter for the inverse-Gamma prior (default: 1).
- sigma_beta_init** For `dynamic_beta`: Initial value of the per-block innovation standard deviation (default: 0.25). Affects mixing, not the stationary distribution.

beta0_mean For `dynamic_beta`: Mean of the Gaussian prior on the dynamic coefficients at $t = 0$ (default: 0).

beta0_var For `dynamic_beta`: Variance of the Gaussian prior on the dynamic coefficients at $t = 0$ (default: 10). Weakly informative.

Common usage: `prior = list(Sab0 = diag(c(1, 1)), eta0 = 10)` for stronger shrinkage, or `prior = list(rho_uv_mean = 0.95)` for higher temporal persistence, or `prior = list(rho_beta_mean = 0.95, sigma_beta_scale = 0.1)` for very smooth time-varying coefficients with tight innovations.

<code>g</code>	optional scalar or vector for g-prior on regression coefficients. Default is p^2 where p is the number of regression parameters. The g-prior controls the variance of regression coefficients: larger values allow for larger coefficient values. Can be a vector of length p for parameter-specific control.
<code>seed</code>	random seed for the MCMC sampler (default 6886). The sampler is seeded internally with this value, so results are reproducible by default and an external <code>set.seed()</code> call has <i>no</i> effect on the chain – pass a different seed here to vary the draws (e.g. when running multiple chains). The caller's <code>.Random.seed</code> is restored on exit, so fitting never perturbs your RNG stream.
<code>nscan</code>	number of iterations of the Markov chain (beyond burn-in)
<code>burn</code>	burn in for the Markov chain
<code>odens</code>	output density for the Markov chain
<code>plot</code>	logical: plot results while running?
<code>verbose</code>	logical: print progress while running? Default FALSE.
<code>gof</code>	logical: calculate goodness of fit statistics?
<code>start_vals</code>	list of parameter starting values for the MCMC chain. Use <code>als_start_vals</code> to start MCMC from an ALS fit.
<code>periodic_save</code>	logical: indicating whether to periodically save MCMC results
<code>out_file</code>	character vector indicating name and path in which file should be stored if <code>periodic_save</code> is selected. For example, on an Apple OS <code>out_file = "~/Desktop/ameFit.rda"</code> .
<code>save_interval</code>	quantile interval indicating when to save during the post-burn-in period.
<code>model.name</code>	optional string for model selection output
<code>save_log_lik</code>	one of FALSE (default), TRUE, or "chunked". When TRUE, stores the per-iteration pointwise log-likelihood matrix on <code>fit\$log_lik</code> (an $[n_stored, n_obs]$ double matrix). When "chunked", streams the log-lik values to per-column-chunk binary files under <code>log_lik_path</code> so the in-memory cost during MCMC is just one chunk's width; the chunks are recovered later via <code>read_log_lik(fit)</code> . Required for <code>loo::loo(fit)</code> and <code>loo::waic(fit)</code> .
<code>posterior_opts</code>	optional list of posterior draw-storage options, usually built with <code>posterior_options</code> . Recognised names (unknown names trigger a warning): <code>save_UV</code> , <code>save_UV_draws</code> , <code>save_ab</code> , <code>thin_UV</code> , <code>thin_ab</code> . <code>save_UV = TRUE</code> (the <i>ame</i> spelling) and <code>save_UV_draws = TRUE</code> are aliases on this path. With <code>dynamic_uv = TRUE</code> they store the per-iteration dynamic latent-position cubes at every stored (<code>odens</code>) iteration on <code>fit\$U_draws</code> / <code>fit\$V_draws</code> , each an $[actor, dim, period, draw]$ array. On a static fit with a positive multiplicative rank they store the per-iteration latent-position

	matrices on <code>fit\$U_samples</code> / <code>fit\$V_samples</code> ([actor, dim, draw] arrays, as ame does). Bipartite fits with positive latent ranks additionally store the interaction-matrix draws on <code>fit\$G_samples</code> ([R_row, R_col, draw]), except under <code>dynamic_G = TRUE</code> whose per-period cube already gets posterior summaries. <code>save_ab</code> is not available on the longitudinal path and is ignored with a warning; <code>thin_UV</code> / <code>thin_ab</code> are accepted for posterior_options compatibility but not applied here (odens already thins the stored chain). Requesting latent draw storage with a zero multiplicative rank warns and stores nothing. Default NULL.
<code>log_lik_path</code>	directory to write log-lik chunks to when <code>save_log_lik = "chunked"</code> . Default NULL creates a session-scoped subdirectory under <code>tempdir()</code> .
<code>log_lik_chunk_size</code>	column-width of each on-disk chunk when <code>save_log_lik = "chunked"</code> . Larger chunks mean fewer files (and one <code>readBin</code> per chunk on read) but more memory during MCMC. Default 10000L.
<code>keep_snap_draws</code>	controls storage of post-burn-in MCMC snap-shift indicators when <code>dynamic_uv = TRUE</code> and <code>dynamic_uv_kind = "snap"</code> . "none" keeps only the posterior mean snap probabilities. "summary" stores cell-level count, mean, and variance summaries. "draws" stores retained binary indicator arrays as <code>fit\$snap_draws</code> and, for directed fits, <code>fit\$snap_draws_v</code> , with dimensions draw x actor x time and first period set to NA. "chunked" currently stores the same arrays in memory and labels the storage mode for downstream tooling.
<code>freeze_call</code>	logical: if TRUE, store a snapshot of the evaluated Y, Xdyad, Xrow, Xcol on <code>fit\$data_snapshot</code> so that a later <code>update(fit, ...)</code> refits against the same data even if the caller has mutated those objects in their workspace. Memory cost equals the size of the data; default FALSE.
<code>dynamic_beta_pool</code>	one of "none" (default), "rho", "sigma", or "both". When two or more coefficient blocks are dynamic, non-"none" values update shared hyperparameters across blocks for the selected persistence and / or innovation-scale component. With a single dynamic block the value is recorded but there is no other block to pool against.
<code>dynamic_beta_per_actor</code>	optional, one of NULL (default), "row", or "col". When non-NULL, fits actor-specific time-varying deviations for one dyadic covariate on the selected margin. The default <code>per_actor_identifiability = "center"</code> keeps the population coefficient in <code>coef(fit)</code> and enforces a per-period sum-to-zero constraint on the actor deviations. Draws are stored in <code>fit\$THETA_ACTOR</code> when retained; summary mode stores <code>fit\$theta_actor_mean</code> and <code>fit\$theta_actor_sd</code> .
<code>per_actor_covariate_idx</code>	positive integer; index into the dyadic covariate cube to slope on for the per-actor extension. Default 1L.
<code>per_actor_identifiability</code>	one of "center" (default) or "drop_population". "center" preserves the population coefficient and constrains per-actor deviations to sum to zero per period via pairwise contrast FFBS. "drop_population" is reserved and currently falls back to "center".

keep_per_actor	one of "auto" (default; full draws when memory cost < 250 MB else streaming summary), "draws" (full [n_iter, n_actors, T] cube), "summary" (streaming posterior mean + sd only), or "none" (only hyperparameter chains).
time_index	optional numeric vector of length T giving observation times. Default NULL treats periods as equally spaced. Strictly-increasing values are required when supplied. Unequal gaps scale the AR(1) / RW1 transition variance and are also used by the RW2 and Matérn 3/2 dynamic-beta precision builders.
period_exposure	optional non-negative numeric vector of length T giving period-level exposure offsets. Wired for Poisson: when supplied with any value $\neq 1$, the Poisson observation likelihood becomes $Y_{ij,t} \sim \text{Poisson}(e_t \cdot \exp(Z_{ij,t}))$, while the latent Z retains its existing semantic of "unexposed log-rate". For other families, non-trivial period_exposure is an error (rescale Y or use a covariate offset). NULL (default) or all-ones uses the unscaled likelihood path.
max_seconds	optional positive scalar; if the MCMC wall-clock time exceeds this many seconds, the chain terminates cleanly and <code>fit\$terminated_early</code> is set to TRUE.
checkpoint_path	optional file path. When set, the chain periodically writes a snapshot of BETA, VC, the RNG state, and the original call to this file. Use <code>lame_resume</code> or pass the same path back as <code>resume_from = path</code> to continue.
checkpoint_every	positive integer; iterations between checkpoint writes. Default 100L.
log_lik_method	one of "observed_exact" (default), "observed_ghk", or "augmented". Selects the argument for selecting which pointwise log-lik is stored on <code>fit\$log_lik</code> . "observed_exact" uses the closed-form marginal log-likelihood for normal, binary, cbin, poisson, and ordinal fits. "observed_ghk" uses a randomized-Halton GHK Monte Carlo marginal for rank-family fits ("frn") and the exact observed likelihood when no GHK step is needed. "augmented" uses the augmented-data Gaussian-on- Z contribution. Note the GHK cost grows exponentially with the per-row dimension D (the number of observed dyads in a sender row): the per-row Monte Carlo budget escalates to $\min(2048, \max(64, 8 * 2^D))$ draws across a bank of 8 randomized Halton sequences, once per stored draw, so "observed_ghk" on a unipartite "frn" fit with more than roughly 12 actors (where $D = n - 1$) is expensive; rows with $D > 15$ fall back to a fast pairwise-normal approximation. Power users can fix the per-row budget exactly via <code>prior\$ghk_n_mc</code> (a single positive integer), which both raises the 2048 ceiling and lowers the $8 * 2^D$ accuracy floor; lower budgets increase the downward Jensen bias of the log-lik estimate.
ordinal_cutpoints	character: cutpoint convention for family = "ordinal". "data_induced" (default) uses the data-induced cutpoints; "explicit" samples explicit cutpoints via a Cowles (1996) Metropolis-Hastings update. Ignored for other families.
method	character: "mcmc" (default, the Bayesian MCMC fit) or "als" (the fast, MCMC-free point-estimation path). With no dynamic arguments, <code>method = "als"</code> uses the pooled-static <code>lame_als</code> estimator. For normal, binary, and Poisson panels, <code>method = "als"</code> also supports a dynamic penalized point-estimation path for <code>dynamic_ab</code> , selected <code>dynamic_beta</code> , smooth AR(1) <code>dynamic_uv</code> in directed,

symmetric, and bipartite panels, bipartite dynamic_G, and Student-t dynamic_uv in directed, symmetric, and bipartite panels. The snap-only dynamic_uv = TRUE, dynamic_uv_kind = "snap" case routes to [lame_snap_als](#) for supported normal unipartite and bipartite panels. Node-covariate coefficients use the same orthogonal additive-effect decomposition as [lame_als](#); dynamic node coefficients use period-specific node values when selected by dynamic_beta, while static node coefficients use per-actor means. Named changing-composition panels are aligned to the union actor set and actor-entry gaps break the dynamic smoothing penalties. Posterior draws, rank/censored families, and bipartite snap-shift fits with node covariates, dynamic coefficients, or dynamic G_t are not handled by the snap ALS shortcut.

als_stability	character (only used when method = "als" and a dynamic ALS path is selected): "none" (default), "quick", or "validation". The non-"none" presets rerun the dynamic ALS fit from jittered starts and attach fit\$stability. Smooth dynamic ALS fits report fitted-surface and coefficient-path differences across starts; snap ALS fits report snap-score, snap-class, top-period, and fitted-surface differences.
als_max_iter	positive integer (only used when method = "als"): maximum block-coordinate iterations for the ALS fit. Default 200.
als_tol	optional positive scalar (only used when method = "als"): convergence tolerance for the ALS objective and fitted values. NULL keeps each ALS estimator's built-in default.
bootstrap	integer (only used when method = "als"): number of bootstrap replicates. 0 (default) skips the bootstrap; N > 0 runs N replicates and attaches the result so that confint returns bootstrap intervals.
bootstrap_type	character (only used when method = "als"): "parametric" (default) or "block".
bootstrap_block_length	integer: block length for the block bootstrap.
bootstrap_seed	optional integer seed for the bootstrap.
resume_from	optional path to a checkpoint file produced by a previous <code>lame(..., checkpoint_path = path)</code> call. When non-NULL, <code>lame()</code> short-circuits all other input parsing and delegates to lame_resume with the user-supplied overrides forwarded. Pass <code>nscan = K</code> to request K additional stored draws on the continuation. Note: <code>checkpoint_path</code> and <code>max_seconds</code> cannot currently be overridden on a resume (they are stripped before re-evaluating the saved call); open both at the original <code>lame()</code> call if you need iterative checkpointing or a time budget on a chain of resumes. Pass <code>verbose = FALSE</code> on resume (the sampling progress bar is gated on <code>burn != 0</code> and the continuation forces <code>burn = 0</code>). Default NULL.
print	Deprecated. Use <code>verbose</code> instead.

Details

This command provides posterior inference for parameters in AME models of longitudinal relational data, assuming one of eight possible data types/models. The model supports both unipartite networks (square adjacency matrices) and bipartite networks (rectangular adjacency matrices with distinct row and column node sets) across multiple time points.

Dynamic Effects Implementation:

The `dynamic_uv` and `dynamic_ab` parameters enable time-varying latent representations through autoregressive processes. These extensions are particularly useful for understanding how network structure evolves over time.

Dynamic Multiplicative Effects (`dynamic_uv=TRUE`): The latent factors U and V evolve according to the transition selected by `dynamic_uv_kind`. The default "ar1" model uses Gaussian AR(1) drift:

$$U_{i,k,t} = \rho_{uv} U_{i,k,t-1} + \epsilon_{i,k,t}$$

where $\epsilon_{i,k,t} \sim N(0, \sigma_{uv}^2)$, i indexes actors, k indexes latent dimensions, and t indexes time. The parameter ρ_{uv} controls temporal persistence (values near 1 indicate slow evolution). This captures time-varying homophily, latent community structure, and transitivity dynamics. The "snap" transition uses a mixture of AR(1) drift and discontinuous reset transitions, while "t" uses heavy-tailed Student-t innovations represented by local transition scales. On the MCMC path, snap and t transitions are supported for unipartite directed and symmetric models. With `method = "als"`, Student-t dynamic UV is also supported for bipartite normal, binary, and Poisson panels, and snap ALS is supported for normal unipartite and bipartite panels, including named panels where actors enter or exit.

Key references:

- Sewell & Chen (2015): Introduced dynamic latent space models with actor-specific evolution rates
- Durante & Dunson (2014): Nonparametric Bayesian approach allowing flexible evolution of network structure
- Hoff (2011): Hierarchical multilinear models providing theoretical foundation for temporal dependencies

Dynamic Additive Effects (`dynamic_ab=TRUE`): The sender (a) and receiver (b) effects evolve as:

$$a_{i,t} = \rho_{ab} a_{i,t-1} + \epsilon_{i,t}$$

$$b_{i,t} = \rho_{ab} b_{i,t-1} + \eta_{i,t}$$

where $\epsilon_{i,t}, \eta_{i,t} \sim N(0, \sigma_{ab}^2)$. This models time-varying individual activity levels (outdegree) and popularity (indegree).

Dynamic additive effects are useful when sender activity and receiver popularity change over time rather than staying fixed across the whole panel.

Prior Specification for Dynamic Parameters:

- $\rho_{uv}, \rho_{ab} \sim \text{TruncNormal}(\text{mean}, \text{sd}, 0, 1)$: Ensures stationarity of AR(1) process
- $\sigma_{uv}^2, \sigma_{ab}^2 \sim \text{InverseGamma}(\text{shape}, \text{scale})$: Controls innovation variance
- Default priors (ρ_{uv} mean=0.9, ρ_{ab} mean=0.8) favor smooth evolution
- Adjust `rho_*_mean` closer to 1 for slower evolution, closer to 0 for more rapid changes

Computational Considerations:

- Dynamic effects increase computation by roughly 30 to 50 percent per iteration
- Memory usage scales as $O(nRT)$ for `dynamic_uv`, $O(n*T)$ for `dynamic_ab`

- C++ implementation is substantially faster than a pure R loop
- Convergence diagnostics: Monitor rho and sigma parameters carefully
- Effective sample sizes typically lower due to temporal correlation
- Recommend burn ≥ 1000 and nscan ≥ 20000 for dynamic models

Model Selection Guidelines: Use both dynamic_uv and dynamic_ab when:

- Networks show clear temporal trends in density or clustering
- Individual node behavior changes systematically over time
- Community structure evolves (merging, splitting, drift)

Use only dynamic_uv when:

- Latent structure/communities change but individual effects are stable
- Focus is on evolving homophily or clustering patterns
- Network shows structural reconfiguration over time

Use only dynamic_ab when:

- Individual heterogeneity varies but overall structure is stable
- Actors' activity/popularity changes over observation period
- Focus is on individual-level temporal dynamics

Bipartite Network Models:

When mode="bipartite", the model handles rectangular adjacency matrices Y with dimensions $n_A \times n_B$, where n_A and n_B represent the number of row and column nodes respectively.

Static Bipartite Case: The model uses separate latent factor matrices:

- U : $n_A \times R_{\text{row}}$ matrix of row node latent positions
- V : $n_B \times R_{\text{col}}$ matrix of column node latent positions
- G : $R_{\text{row}} \times R_{\text{col}}$ interaction matrix mapping between latent spaces
- Multiplicative term: $U G V'$ captures bipartite community structure

Dynamic Bipartite Case: When dynamic_uv=TRUE for bipartite networks:

$$U_{i,k,t} = \rho_{uv} U_{i,k,t-1} + \epsilon_{i,k,t}$$

$$V_{j,k,t} = \rho_{uv} V_{j,k,t-1} + \eta_{j,k,t}$$

where i indexes row nodes, j indexes column nodes, k indexes latent dimensions.

When dynamic_G = TRUE the bipartite interaction matrix G_t varies by period (a separate $R_{\text{row}} \times R_{\text{col}}$ matrix at every time slice) and is returned as fit\$G_cube. The MCMC estimator samples G_t with a Carter-Kohn/FFBS update; method = "als" estimates a penalized point path for normal, binary, and Poisson bipartite panels, including named changing-composition panels. The marginal $U_t G_t V_t'$ linear predictor is the identified object; individual G_t entries can shift under equivalent rotations and scalings of U_t and V_t . dynamic_G = TRUE is bipartite only.

Key Differences from Unipartite Models:

- No dyadic correlation (rho): Bipartite edges are inherently directed
- Separate dimensions: R_row and R_col can differ for row/column spaces
- Rectangular structure: Network density patterns differ from square matrices
- Community interpretation: Captures affiliation patterns between node types

Standard AME Model Types:

The following describes the six standard data types/models available:

"normal": A normal AME model.

"binary": A binary probit AME model.

"ordinal": An ordinal probit AME model. An intercept is not identifiable in this model.

"cbin": An AME model for censored binary data. The value of 'odmax' specifies the maximum number of links each row may have.

"frn": An AME model for fixed rank nomination networks. A higher value of the rank indicates a stronger relationship. The value of 'odmax' specifies the maximum number of links each row may have.

"poisson": An overdispersed Poisson AME model for count data: $Y \sim \text{Poisson}(\exp(z))$ with $z \sim N(\eta, \sigma^2)$, a lognormal-mixed Poisson. The conditional mean given the latent z is $\exp(z)$; the marginal mean is $\exp(\eta + \sigma^2/2)$, not $\exp(\eta)$.

Value

BETA	posterior samples of regression coefficients. A 2-dimensional matrix [n_stored, p] when all coefficients are static. When dynamic_beta flags any coefficient as time-varying, BETA is a 3-dimensional array [n_stored, p, T] whose third dimension is the time period. Static coefficients are still present with their values replicated across the third dimension. <code>coef(fit)</code> collapses this to a [p, T] posterior-mean matrix. Migration from amen. Under <code>amen::ame()</code> the BETA slot was always 2-D. Scripts that compute <code>apply(fit\$BETA, 2, mean)</code> on an <code>amen</code> fit will silently aggregate across periods when run against a <code>lame()</code> fit with <code>dynamic_beta</code> active (the second margin is the coefficient index in both shapes; the new third margin is time). Use <code>length(dim(fit\$BETA))</code> to detect the shape, or call <code>coef(fit)</code> which returns a [p, T] matrix in either case.
VC	posterior samples of the variance parameters
APM	posterior mean of additive row effects a
BPM	posterior mean of additive column effects b
U	posterior mean of multiplicative row effects u. For <code>dynamic_uv=TRUE</code> , this is a 3D array (n x R x T)
V	posterior mean of multiplicative column effects v (asymmetric case). For <code>dynamic_uv=TRUE</code> , this is a 3D array (n x R x T)
UVPM	posterior mean of UV
ULUPM	posterior mean of ULU (symmetric case)
L	posterior mean of L (symmetric case)

EZ	estimate of expectation of Z matrix. For mode = "bipartite", EZ is a list of per-period matrices whose row/column dimnames are currently NULL. Use <code>names(fit\$APM) / names(fit\$BPM)</code> (or <code>dimnames(fit\$YPM[[t]])</code>) to recover the row/column actor ordering, which is the lexicographic sort of the input actor names (so "r10" sorts before "r2" unless you zero-pad).
YPM	posterior mean of Y (for imputing missing values)
GOF	observed (first row) and posterior predictive (remaining rows) values of four goodness-of-fit statistics. See gof for post-hoc computation and gof_plot for visualization.
start_vals	Final parameter values from MCMC, can be used as the input for a future model run.
model.name	Name of the model (if provided)

Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

See Also

[ame](#) for cross-sectional models, [lame_als](#) for the fast MCMC-free point estimator, [lame_snap_als](#) for the approximate dynamic snap-shift point estimator, [als_dynamic_beta](#) for a regression-only penalised smoother on the time-varying coefficient path, [lame_resume](#) for resuming saved checkpoints, [gof](#) for post-hoc goodness-of-fit computation, [gof_plot](#) for visualizing GOF results, [latent_positions](#) for extracting latent positions as a tidy data frame, [procrustes_align](#) for Procrustes alignment of latent positions, [summary.lame](#) for model summaries, [coef.lame](#) for coefficient extraction. Long-format edgelist and covariates can be prepared with `netify::netify()` and passed directly to `lame()`, or converted explicitly with `netify::to_lame(lame = TRUE)`.

Examples

```
data(YX_bin_list)
fit<-lame(YX_bin_list$Y,YX_bin_list$X,burn=5,nscan=5,odens=1,family="binary")
# you should run the Markov chain much longer than this

## Time-varying regression coefficients (dynamic_beta).
## Make every dyadic coefficient evolve as an AR(1):
fit_dyn <- lame(YX_bin_list$Y, YX_bin_list$X,
               family = "binary", R = 0,
               nscan = 60, burn = 15, odens = 5,
               dynamic_beta = "dyad")
dim(fit_dyn$BETA)      # [n_stored, p, T] -- 3-D when dynamic
coef(fit_dyn)          # [p, T] posterior-mean coefficient paths
confint(fit_dyn)       # per-period 95% credible intervals
summary(fit_dyn)       # prints a "Dynamic coefficients per period" block
```

lame_als

Fast (MCMC-free) AME estimation for a longitudinal network

Description

Fits an additive and multiplicative effects (AME) model to a longitudinal (replicated) network by **iterative block coordinate descent**, producing a fast point estimate with no MCMC and no credible intervals. This is the longitudinal counterpart of [ame_als](#); the estimated effects (μ , β , a , b , U , V) are *static* (pooled across time), as in a non-dynamic [lame](#) fit.

The estimation algorithm adapts the iterative block coordinate descent estimator of the Social Influence Regression model of Hoff & Minhas (`sir::sir_alsfit()`) to the AME model; it is a port and adaptation, not original **lame** methodology. See [ame_als](#) for the algorithm details.

Usage

```
lame_als(
  Y,
  Xdyad = NULL,
  Xrow = NULL,
  Xcol = NULL,
  R = 0,
  family = "normal",
  mode = c("unipartite", "bipartite"),
  symmetric = FALSE,
  max_iter = 200,
  tol = 1e-06,
  lowrank_method = c("mm", "als", "hybrid"),
  non_normal_method = c("irls", "transform"),
  link = c("probit", "logit"),
  linear_solver = c("eigen", "qr", "auto"),
  multistart = c("none", "cheap", "full"),
  bootstrap = 0L,
  bootstrap_type = c("parametric", "block"),
  bootstrap_block_length = 1L,
  bootstrap_seed = NULL,
  verbose = TRUE,
  seed = 6886
)
```

Arguments

Y a list of t relational matrices, or a 3d array $[n_row, n_col, t]$. A named list may have changing actor composition; every slice must carry row and column names so actors can be aligned to the union panel. Unnamed lists and arrays are treated positionally and must have one fixed layout. A longitudinal **netify** object is also accepted and converted with `netify::to_lame(lame = TRUE)`.

Xdyad	a list of T dyadic covariate matrices/arrays, or NULL.
Xrow	a list of T row/sender covariate matrices, or NULL.
Xcol	a list of T column/receiver covariate matrices, or NULL.
R	integer dimension of the multiplicative effects (default 0). The covariate coefficients are conditional on this choice. The multiplicative term $u_i'v_j$ is a flexible high-variance regressor that can correlate with the dyadic covariates, so the estimated beta can shift – and occasionally change sign – as R increases. Comparing against an R = 0 fit is a useful check on whether the covariate story is being driven by the latent rank.
family	one of "normal", "binary", or "poisson". The rank and censoring families are MCMC-only.
mode	"unipartite" (square) or "bipartite" (rectangular).
symmetric	logical; fit a symmetric (undirected) model. Unipartite only.
max_iter	maximum number of block coordinate descent iterations (default 200).
tol	convergence tolerance on the relative change in residual sum of squares (default 1e-6).
lowrank_method	inner solver for the multiplicative (low-rank) block: "mm" (default) weighted majorise-minimise; "als" alternating least squares; "hybrid" runs both and keeps the lower-objective result. "als"/"hybrid" converge faster than "mm" on strongly unbalanced longitudinal panels and are available for directed and bipartite models (symmetric fits always use "mm"). All three minimise the same objective, so the point estimate is unchanged for balanced data.
non_normal_method	for the non-normal ALS families, "irls" (default for binary/poisson) runs iteratively reweighted least squares, giving a fast approximate GLM AME fit with coefficients on the requested link scale (Poisson log, binary logit/probit). "transform" fits one fixed Gaussian working response (log(y+1) for Poisson, rank-normal scores for binary); its coefficients are on an uncalibrated working scale and are mainly useful for direction/ranking checks. A directed R > 0 IRLS fit uses the hybrid low-rank solver internally because the IRLS weights are unbalanced. Uncertainty for either path comes from the bootstrap or sandwich covariance.
link	link for non_normal_method = "irls" with a binary family: "probit" (default; matches ame/lame) or "logit". poisson always uses the log link; ignored otherwise.
linear_solver	solver for the regression block: "eigen" (default) eigendecomposes the normal equations; "qr" uses a QR factorisation of the observed design, which is more stable for ill-conditioned covariates; "auto" picks "qr" when the design is ill-conditioned but full rank. All give the same answer for well-conditioned designs.
multistart	for R > 0 (a non-convex objective), "none" (default) fits from a single deterministic start; "cheap" (4 starts) and "full" (8 starts) also try random low-rank starts and keep the lowest-SSE fit, warning when the starts reach materially different optima. Reproducible given seed; the global RNG stream is left unchanged.

bootstrap	integer: if > 0 , additionally run bootstrap replicates of the parametric or block bootstrap (via ame_als_bootstrap) after the point fit and attach the result as <code>fit\$bootstrap</code> . The downstream accessors (<code>confint.ame_als</code> , <code>summary</code> , <code>print</code>) then surface bootstrap intervals instead of the anti-conservative sandwich Wald intervals. Default $\emptyset$ (no bootstrap) – bootstrap is expensive, so it is not imposed on a user who just wants a quick fit.
bootstrap_type	character: "parametric" (default) or "block" – the bootstrap scheme to use when <code>bootstrap > 0</code> .
bootstrap_block_length	integer: block length for the block bootstrap; only used when <code>bootstrap_type = "block"</code> .
bootstrap_seed	optional integer seed for the bootstrap (the point fit uses seed).
verbose	logical; print progress (default TRUE).
seed	random seed (default 6886). The block coordinate descent is deterministic, so the point estimate is reproducible regardless; the argument is retained for API consistency with ame .

Value

An object of class "ame_als"; see [ame_als](#).

Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

References

Minhas, S. and Hoff, P. D. (2025). Decomposing Network Dynamics: Social Influence Regression. *Political Analysis*. The iterative block coordinate descent estimator adapted here originates with that work (implemented in `sir::sir_alsfit()`).

See Also

[ame_als](#), [ame_als_bootstrap](#), [lame](#) for the full MCMC estimator, [lame_snap_als](#) for the approximate dynamic snap-shift point estimator, [als_dynamic_beta](#) for a regression-only smoother that estimates *only* a time-varying β_t (no a, b, U, V ; not a special case of this function).

Examples

```
Y <- replicate(4, { m <- matrix(rnorm(400), 20, 20); diag(m) <- NA; m },
  simplify = FALSE)
fit <- lame_als(Y, R = 1, family = "normal", verbose = FALSE)
coef(fit)
```

lame_multi	<i>Multi-panel lame() with shared coefficients</i>
------------	--

Description

Fits K independent `lame()` models (one per panel) and pools the per-panel beta posteriors into a precision-weighted shared posterior. Returns a list with the per-panel fits, the pooled beta posterior, and the panel-specific deviations.

Usage

```
lame_multi(Y_list, Xdyad_list, ..., shared_dynamic_beta = TRUE)
```

Arguments

<code>Y_list</code>	A list of length K , each element a list (or 3-D array) of T per-panel network observations.
<code>Xdyad_list</code>	A list of length K , each element a list of T dyadic covariate arrays.
<code>...</code>	Arguments forwarded to <code>lame()</code> (e.g. <code>family</code> , <code>R</code> , <code>mode</code> , <code>nscan</code> , <code>burn</code> , <code>odens</code> , <code>dynamic_beta</code> , <code>dynamic_beta_kind</code>).
<code>shared_dynamic_beta</code>	Logical; if <code>TRUE</code> (default), the shared beta posterior is computed (per-period when <code>dynamic_beta</code> is active).

Details

This is an R-level wrapper: it fits each panel with its own MCMC and pools the results afterwards. The pooling is exact when the panels are conditionally independent given beta, which is the standard assumption.

Value

A list with

- `fits`: list of K per-panel `lame` fits.
- `beta_shared`: pooled posterior mean of beta (per-period when dynamic).
- `beta_deviations`: list of K panel-specific deviations from `beta_shared`.
- `K`: number of panels.

Class "`lame_multi`".

See Also

[lame_parallel](#) for the unrelated multi-*chain* wrapper that runs K MCMC chains of the *same* model (used for R-hat / ESS diagnostics and pooled effective sample size). `lame_multi` is for K *distinct* panels with shared regression coefficients; `lame_parallel` is for K chains of one model.

Examples

```
data(YX_bin_list)
fit_multi <- lame_multi(
  Y_list = list(YX_bin_list$Y, YX_bin_list$Y),
  Xdyad_list = list(YX_bin_list$X, YX_bin_list$X),
  family = "binary", R = 0,
  nscan = 100, burn = 25, odens = 5, verbose = FALSE)
dim(fit_multi$beta_shared)
```

lame_parallel

Run LAME (longitudinal AME) with multiple parallel chains

Description

Thin wrapper around [ame_parallel](#) that forces `fitter = "lame"`. Use this for longitudinal data; in particular, multi-chain `dynamic_beta` / `dynamic_uv` / `dynamic_ab` fits are reached through here. The combined fit's `$BETA` is a 3-D array when `dynamic_beta` is on, and `posterior::rhat(as_draws(fit))` gives R-hat across chains for every per-period coefficient.

Usage

```
lame_parallel(
  Y,
  n_chains = 4,
  cores = n_chains,
  combine_method = c("pool", "list"),
  ...
)
```

Arguments

<code>Y</code>	Longitudinal network: list of <code>T</code> relational matrices, or a 3-D array <code>[n, n, T]</code> .
<code>n_chains</code>	Number of parallel chains (default 4).
<code>cores</code>	CPU cores to use (default <code>n_chains</code> ; 1 = sequential).
<code>combine_method</code>	"pool" (default) or "list".
<code>...</code>	Additional arguments forwarded to lame , including <code>dynamic_beta</code> , <code>dynamic_uv</code> , <code>dynamic_ab</code> , <code>family</code> , <code>nscan</code> , <code>burn</code> , <code>odens</code> , etc.

Value

Same as `ame_parallel`: a combined `lame` fit (when `combine_method = "pool"`) or a list of fits.

Examples

```
data(YX_bin_list)
fit_pll <- lame_parallel(YX_bin_list$Y, Xdyad = YX_bin_list$X,
                        family = "binary", n_chains = 2, cores = 1,
                        nscan = 50, burn = 10, odens = 5,
                        dynamic_beta = "dyad", verbose = FALSE)
dim(fit_pll$BETA)      # [iter * n_chains, p, T]
fit_pll$chain_indicator # length iter * n_chains
if (requireNamespace("posterior", quietly = TRUE)) {
  posterior::summarise_draws(posterior::as_draws(fit_pll))
}
```

lame_resume

Resume a lame() MCMC run from a checkpoint

Description

For a fit started with `lame(..., checkpoint_path = "X.rds")` that terminated early (either via `max_seconds` or an external interruption), continues the chain from the most recent checkpoint. The implementation is pragmatic: it loads the saved RNG state and re-invokes `lame()` with the original call arguments. The result is a fresh fit that picks up where the previous one left off in the random-number stream; the underlying MCMC counter restarts at 1.

Usage

```
lame_resume(path, nscan_more = NULL, ..., .envir = NULL)
```

Arguments

<code>path</code>	Checkpoint file path (the one passed as <code>checkpoint_path</code> to <code>lame()</code>).
<code>nscan_more</code>	Optional integer, the new <code>nscan</code> for the continuation. If <code>NULL</code> , the original <code>nscan</code> is used.
<code>...</code>	Additional arguments forwarded to <code>lame()</code> (override the saved values).
<code>.envir</code>	Environment in which to evaluate the saved call's data arguments. Defaults to the caller's frame; used internally when <code>lame()</code> forwards a resume.

Details

Equivalent consolidated entry point. `lame(resume_from = path, ...)` short-circuits to this function with the user-supplied overrides forwarded; pass `nscan = K` on the resume call to request `K` additional stored draws. Both call shapes are supported. The `lame_resume(path, ...)` form is safer for nested calls: the consolidated form re-evaluates the saved `lame()` call in `parent.frame()`, which is the `lame()` frame whose required formal arguments (`Y`, `Xdyad`, etc.) were not supplied on the resume call. Prefer `lame_resume(path, ...)` when calling from inside other functions or from non-global scopes.

Use `nscan_more = K` to override the `nscan` value to `K` for the continuation. Other arguments can be overridden by passing them to `...`

Value

A fitted `lame` object.

Examples

```
ck <- tempfile(fileext = ".rds")
data(YX_bin_list)
# short run with very-aggressive max_seconds to force early termination
fit1 <- lame(YX_bin_list$Y, YX_bin_list$X, family = "binary", R = 0,
            nscan = 5000, burn = 50, odens = 5,
            checkpoint_path = ck, checkpoint_every = 50L,
            max_seconds = 0.5, verbose = FALSE)
if (isTRUE(fit1$terminated_early)) {
  fit2 <- lame_resume(ck, nscan_more = 200)
  dim(fit2$BETA)
}
```

lame_snap_als

Fast approximate dynamic snap-shift AME estimator

Description

Fits a fast point-estimator approximation to the dynamic snap-shift latent-factor model for longitudinal normal-valued networks. It targets the same drift-versus-reset transition estimand as [lame](#) with `dynamic_uv = TRUE` and `dynamic_uv_kind = "snap"`, but returns ALS snap scores rather than MCMC draws.

Usage

```
lame_snap_als(
  Y,
  Xdyad = NULL,
  Xrow = NULL,
  Xcol = NULL,
  R = 2L,
  R_row = NULL,
  R_col = NULL,
  family = "normal",
  mode = c("unipartite", "bipartite"),
  symmetric = FALSE,
  max_iter = 200L,
  tol = 1e-06,
```

```

snap_kappa = 2,
snap_pi_prior = c(a = 1, b = 9),
snap_update = c("soft", "hard", "annealed"),
snap_damping = 0.7,
estimate_rho_uv = TRUE,
estimate_sigma_uv = TRUE,
rho_uv = NULL,
sigma_uv = NULL,
hyper_update = c("robust", "em"),
drift_quantile = 0.05,
drift_min_transitions = 50,
rho_prior_mean = 0.98,
rho_prior_weight = 25,
align = c("sequential", "global", "none"),
threshold = 0.5,
min_sigma = 1e-04,
sigma_floor_fraction = 0.75,
ridge = 1e-08,
snap_stability_tol = 0.05,
snap_convergence = c("quantile", "max", "classification"),
snap_delta_quantile = 0.95,
snap_class_change_tol = 0.005,
unstable_top_n = 10L,
stability = c("none", "quick", "validation"),
verbose = TRUE,
seed = 6886
)

```

Arguments

Y	a list of relational matrices, or a 3D array. Unipartite fits use [n, n, T] panels. Bipartite fits use rectangular [n_row, n_col, T] panels. For named lists, slices may have changing actor composition; the estimator pads to the union actor set and treats absent actor-periods as unobserved and snap-ineligible. A longitudinal netify object is also accepted and converted with <code>netify::to_lame(lame = TRUE)</code> .
Xdyad	optional list of dyadic covariate matrices/arrays, or NULL.
Xrow, Xcol	not supported by this fast snap-shift estimator; pass NULL. Use <code>lame</code> with method = "mcmc" for node-covariate dynamic snap models.
R	positive integer latent rank. For bipartite fits, used as the default for R_row and R_col.
R_row, R_col	positive integer latent ranks for bipartite row and column positions. Defaults to R.
family	currently only "normal".
mode	"unipartite" or "bipartite".
symmetric	logical; if TRUE, fit a symmetric latent-factor approximation and report one snap-probability matrix.

max_iter	maximum block-coordinate iterations.
tol	convergence tolerance on the relative change of the tracked $-2\times$ variational free energy (see Details).
snap_kappa	diffuse snap-prior standard deviation.
snap_pi_prior	length-two vector $c(a, b)$ for the beta prior used to regularize the snap rate.
snap_update	one of "soft", "hard", or "annealed".
snap_damping	scalar in $(0, 1]$; damping applied to soft snap-score updates. Values below 1 mix the new score with the previous score to reduce oscillation on large panels. Ignored for snap_update = "hard".
estimate_rho_uv, estimate_sigma_uv	logical flags for updating the AR drift persistence and innovation scale.
rho_uv, sigma_uv	optional fixed/initial AR drift parameters.
hyper_update	one of "robust" or "em". The default "robust" estimates drift hyperparameters from the lower tail of transition innovations, which prevents broad ruptures from being absorbed into an overly diffuse drift process. "em" uses the untrimmed soft-classification moment update.
drift_quantile	lower-tail transition quantile used by hyper_update = "robust" for estimating smooth-drift hyperparameters.
drift_min_transitions	minimum effective number of transitions retained by the lower-tail update. This keeps the default from overfitting the smooth-drift scale on small panels.
rho_prior_mean, rho_prior_weight	weak regularization for the persistence estimate. The defaults encode the snap-shift model's intended persistent, low-innovation drift baseline.
align	initialization alignment mode; "global" aligns each period to the pooled static ALS fit, "sequential" aligns each period to the previous initialized period, and "none" leaves per-period factors unaligned.
threshold	hard-classification threshold for snap_class.
min_sigma	lower bound for the drift scale.
sigma_floor_fraction	for robust hyperparameter updates, the iterative drift scale cannot fall below this fraction of the initial sigma_uv. This prevents broad snap assignments from collapsing the smooth-drift variance to min_sigma.
ridge	small ridge added to latent-position normal equations.
snap_stability_tol	tolerance for declaring soft snap scores stable. This is separate from tol, which tracks the penalized objective.
snap_convergence	convergence criterion for snap scores. "quantile" uses snap_delta_quantile of the absolute score changes plus the class-change share; "max" uses the worst actor-period score change; "classification" uses only class-change stability. The worst-case max is always stored and warned about when high.

snap_delta_quantile	quantile of actor-period score changes used by snap_convergence = "quantile".
snap_class_change_tol	maximum share of eligible actor-periods whose snap_class may change between iterations while still declaring snap convergence.
unstable_top_n	number of largest actor-period snap-score changes to store in convergence diagnostics.
stability	optional start-sensitivity preset. "none" runs one fit. "quick" and "validation" rerun the same estimator from additional seeds and attach fit\$stability with snap-score, classification, top-period, and fitted-surface comparisons.
verbose	logical; print progress.
seed	integer seed for initialization perturbations.

Details

The raw snap-ALS intercept μ is *not* separately identified from the uncentered multiplicative term: a constant level can be absorbed into $\text{mean}(U_t V_t')$ (bipartite: $\text{mean}(U_t G V_t')$), so `fit$mu` on its own is arbitrary. After convergence the estimator therefore computes a post-hoc identified level: `fit$mu_t` stores the per-period level $\mu + \text{mean}(U_t V_t')$ (named by period) and `fit$mu_identified` is the mean of `fit$mu_t`. Interpret the network level through `mu_identified`; the latent trajectories and the covariate coefficients are unaffected by this shift and remain reliable outputs of this estimator.

On longer panels, the default `align = "sequential"` keeps the period-to-period movement in view. `align = "global"` can help on very short panels, but on longer panels it can pull each period back toward the pooled static fit and make early jumps look too strong. If you have a fixed drift scale, pass `rho_uv` and `sigma_uv` with `estimate_rho_uv = FALSE` and `estimate_sigma_uv = FALSE`.

The convergence output separates the usual score summary from the worst moving actor-period. By default, convergence uses the 95th percentile of score changes and the share of class changes. `final_max_snap_delta` and `unstable_transitions` still show the largest local moves. Read `snap_prob` as an ALS snap score. It is useful for rankings and heuristic classifications; it is not a Bayesian posterior probability.

For unipartite fits, the tracked objective (`fit$objective_trace`, `fit$convergence$final_objective`) is the exact $-2 \times$ variational free energy of the snap/drift mixture model, including the Gaussian log-normalizers, the responsibility entropy, and the beta prior on the snap rate. The exact block updates descend it monotonically; small increases can come from damped snap scores or the robust hyperparameter updates. Because it carries log-variance normalizers it can be negative and is not a deviance; `fit$param_trace$sse` tracks raw data fit directly.

In bipartite mode, the fitted multiplicative term is $U_t G V_t'$ with one static interaction matrix G . The returned `snap_prob` matrix contains row-actor snap scores and `snap_prob_v` contains column-actor snap scores. Bipartite snap ALS does not estimate node covariates, dynamic coefficients, or a dynamic G_t ; those combinations need a separate model.

Value

An object of class "lame_snap_als" with dynamic latent positions, snap scores, fitted values, residuals, and convergence diagnostics.

Examples

```

set.seed(1)
Y_bip <- lapply(seq_len(3), function(t) {
  m <- matrix(rnorm(6 * 5), 6, 5)
  rownames(m) <- paste0("r", seq_len(6))
  colnames(m) <- paste0("c", seq_len(5))
  m
})
fit_bip <- lame_snap_als(Y_bip, R = 1, mode = "bipartite",
  max_iter = 3, verbose = FALSE)
dim(fit_bip$snap_prob_v)

```

latent_positions	<i>Extract latent positions as a tidy data frame</i>
------------------	--

Description

Extracts multiplicative latent factor positions (U and V) from a fitted `ame`, `lame` or `ame_als` model and returns them as a tidy data frame suitable for plotting and analysis. Optionally applies Procrustes alignment for dynamic models and includes posterior standard deviations when posterior samples are available.

Usage

```

latent_positions(object, ...)

## S3 method for class 'ame'
latent_positions(object, align = FALSE, ...)

## S3 method for class 'lame'
latent_positions(object, align = TRUE, ...)

## S3 method for class 'ame_als'
latent_positions(object, align = FALSE, ...)

```

Arguments

<code>object</code>	A fitted <code>ame</code> , <code>lame</code> or <code>ame_als</code> model object with $R > 0$.
<code>...</code>	Additional arguments (currently unused).
<code>align</code>	Logical. For dynamic models (<code>dynamic_uv = TRUE</code>), apply Procrustes alignment across time to remove rotational indeterminacy. Default is <code>FALSE</code> for <code>ame</code> objects and <code>TRUE</code> for <code>lame</code> objects.

Value

A data frame with columns:

actor Character. Actor name (from rownames of U or V).

dimension Integer. Latent dimension index (1 to R).

time Character. Time period label. Dynamic fits use the time labels from the input; static (cross-sectional) fits return "1" for every row so downstream filtering by time behaves the same in both cases.

value Numeric. The posterior mean latent position.

posterior_sd Numeric. Posterior standard deviation of the latent position, or NA if posterior samples are not available. To enable, fit the model with `posterior_opts = posterior_options(save_UV = TRUE)`.

type Character. "U" for sender/row positions, "V" for receiver/column positions. Symmetric models have only "U".

Returns a zero-row data frame with correct column names if $R = 0$.

Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

See Also

[procrustes_align](#) for standalone Procrustes alignment, [uv_plot](#) for visualizing latent positions, [posterior_options](#) for enabling posterior sampling of U/V

Examples

```
data(YX_nrm)
fit <- ame(YX_nrm$Y, Xdyad = YX_nrm$X, R = 2,
           burn = 5, nscan = 5, odens = 1, verbose = FALSE)
lp <- latent_positions(fit)
head(lp)
```

lazegalaw

Lazega's law firm data

Description

Several nodal and dyadic variables measured on 71 attorneys in a law firm.

Format

A list consisting of a socioarray Y and a nodal attribute matrix X .

The dyadic variables in Y include three binary networks: advice, friendship and co-worker status.

The categorical nodal attributes in X are coded as follows:

- status (1=partner, 2=associate)
- office (1=Boston, 2=Hartford, 3=Providence)
- practice (1=litigation, 2=corporate)
- law school (1=Harvard or Yale, 2=UConn, 3=other)

seniority and age are given in years, and female is a binary indicator.

Source

Originally available at <http://moreno.ss.uci.edu/data.html#lazega> (site no longer accessible).

ldZgbme	<i>log density for GBME models</i>
---------	------------------------------------

Description

Calculation of the log conditional density of the latent AMEN matrix Z given observed data Y .

Usage

```
ldZgbme(Z, Y, l1YZ, EZ, rho, s2 = 1)
```

Arguments

Z	$n \times n$ latent relational matrix following an AMEN model
Y	$n \times n$ observed relational matrix
$l1YZ$	a vectorizable function taking two arguments, y and z . See details below.
EZ	$n \times n$ mean matrix for Z based on AMEN model (including additive effects)
ρ	dyadic correlation in AMEN model for Z
$s2$	residual variance in AMEN model for Z

Details

This function is used for updating dyadic pairs of the latent variable matrix Z based on Y and an AMEN model for Z . The function $l1YZ$ specifies the log likelihood for each single $z[i, j]$ based on $y[i, j]$, that is, $l1YZ$ gives the log probability density (or mass function) of $y[i, j]$ given $z[i, j]$.

Value

a symmetric matrix where entry i, j is proportional to the log conditional bivariate density of $z[i, j], z[j, i]$.

Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

Examples

```
## For (overdispersed) Poisson regression, use
llyz<-function(y,z){ dpois(y,z,log=TRUE) }
```

lfo

Exact rolling-origin leave-future-out cross-validation

Description

For a fitted lame object with T periods, refits the model on the first $t - 1$ periods (for each t in periods) and computes the expected log predictive density (elpd) of period t under the refit. Returns the summed elpd across all leave-out periods, along with per-period contributions.

Usage

```
lfo(fit, periods = NULL, refit = TRUE, ...)
```

Arguments

fit	A fitted lame object.
periods	Integer vector of leave-out periods to evaluate. Default is the last 3 periods (<code>tail(seq_len(T), 3L)</code>). Each period t must satisfy $t \geq 2$.
refit	Logical; if TRUE (default), refits on the training window. If FALSE, uses the original posterior means (a much rougher approximation).
...	Passed to the refit lame() call (typically nscan, burn, odens, verbose).

Value

A list with `elpd_lfo` (total summed elpd), `pointwise` (per-dyad log-density at each leave-out period; a list of numeric vectors, one per period – `unlist(pointwise)` gives a flat vector suitable for `loo::loo_compare()`-style stacking), `p_lfo` (effective number of parameters), `per_period` (data frame with period, elpd, n_obs), and `periods` (the periods evaluated).

Examples

```
data(YX_bin_list)
fit <- lame(YX_bin_list$Y, YX_bin_list$X, family = "binary", R = 0,
           dynamic_beta = "dyad",
           nscan = 60, burn = 15, odens = 5, verbose = FALSE)
lfo_res <- lfo(fit, periods = 4L, refit = TRUE,
              nscan = 50, burn = 10, odens = 5, verbose = FALSE)
print(lfo_res)
```

list_to_array	<i>Convert list to array</i>
---------------	------------------------------

Description

Convert list to array

Usage

```
list_to_array(actors, Y, Xdyad, Xrow, Xcol)
```

Arguments

actors	vector of actors
Y	dv in list format
Xdyad	dyadic covariates in list format
Xrow	sender covariates in list format
Xcol	receiver covariates in list format

Value

transforms Y, Xdyad, Xrow, and Xcol to arrays

Author(s)

Shahryar Minhas

list_to_array_bipartite	<i>Convert bipartite list data to array format</i>
-------------------------	--

Description

Convert bipartite list data to array format

Usage

```
list_to_array_bipartite(  
  rowActorSet,  
  colActorSet,  
  Y_list,  
  Xdyad = NULL,  
  Xrow = NULL,  
  Xcol = NULL  
)
```

Value

List with components Y, Xdyad, Xrow, Xcol in array format

llsrmRho	<i>SRM log likelihood evaluated on a grid of rho-values</i>
----------	---

Description

Calculation of the SRM log-likelihood over a grid of rho-values

Usage

```
llsrmRho(Y, Sab, rhos, s2 = 1)
```

Arguments

Y	sociomatrix assumed to follow a mean-zero SRM distribution
Sab	covariance matrix of additive effects
rhos	vector of rho-values at which to calculate the log-likelihood
s2	current value of s2

Value

a vector of log-likelihood values

Author(s)

Peter Hoff

logLik.ame	<i>Log-likelihood is not directly exposed for ame() / lame() fits</i>
------------	---

Description

ame() and lame() produce a posterior sample, not a maximum-likelihood point. A pointwise log-likelihood is computable from the posterior draws but is not stored on the fit object, so logLik() (and the AIC / BIC generics that dispatch through it) error out informatively rather than return a misleading number.

Usage

```
## S3 method for class 'ame'
logLik(object, ...)

## S3 method for class 'lame'
logLik(object, ...)
```

Arguments

object	an ame or lame fit.
...	ignored.

Details

For Bayesian model comparison use posterior-predictive checks via [gof](#) / [gof_plot](#), or compute WAIC / LOO yourself from the per-draw log-likelihoods (e.g. via the **loo** package on the BETA / VC chains).

Value

Never returns; raises an error.

logLik.ame_als	<i>Log-likelihood is not defined for a fast AME fit</i>
----------------	---

Description

The fast estimator minimises a (working-response) least-squares objective, not a family likelihood, so it has no log-likelihood and AIC / BIC are undefined. Calling logLik() raises an informative error rather than returning a misleading number.

Usage

```
## S3 method for class 'ame_als'
logLik(object, ...)
```

Arguments

object	an ame_als object.
...	ignored.

Value

Never returns; raises an error.

log_phi_diff	<i>Numerically stable $\log(\Phi(hi) - \Phi(lo))$</i>
--------------	--

Description

Computes log of the standard-normal CDF difference. Naive `log(pnorm(hi) - pnorm(lo))` returns `-Inf` whenever both arguments are above `~7` or below `~-7` (catastrophic cancellation). Uses `pnorm(, log.p = TRUE)` and a stable log-subtraction.

Usage

```
log_phi_diff(hi, lo)
```

Arguments

hi	numeric, upper bound
lo	numeric, lower bound (must be $\leq$ hi elementwise)

Value

numeric, $\log(\Phi(hi) - \Phi(lo))$

loo	<i>Generic dispatcher for loo / waic on ame / lame fits</i>
-----	---

Description

Lightweight S3 generics so calls of the form `loo(fit)` dispatch through R's S3 system even when the **loo** package is not loaded. When **loo** is loaded, its generic resolves first; this fallback only fires for bare-namespace use.

Usage

```
loo(x, ...)
waic(x, ...)
```

Arguments

x	a fitted ame or lame object with <code>\$log_lik</code> .
...	passed to the relevant method.

Value

A loo / waic object.

loo.ame*Approximate leave-one-out cross-validation for AME / LAME fits*

Description

S3 method for `loo` that uses the per-iteration pointwise log-likelihood stored on the fit object (`fit$log_lik`) when the model was fit with `save_log_lik = TRUE`. Returns the standard loo object with Pareto-k diagnostics.

Usage

```
## S3 method for class 'ame'  
loo(x, ...)  
  
## S3 method for class 'lame'  
loo(x, ...)  
  
## S3 method for class 'ame_als'  
loo(x, ...)
```

Arguments

<code>x</code>	A fitted <code>ame</code> or <code>lame</code> object that has <code>\$log_lik</code> .
<code>...</code>	Additional arguments forwarded to <code>loo::loo.matrix</code> (e.g. <code>cores</code> , <code>r_eff</code>).

Details

What `log_lik` measures. For family in `{normal, binary, cbin, poisson, ordinal}` the stored pointwise log-likelihood is the exact family-specific Y density on the response scale, so `elpd_loo` is directly comparable to a `loo()` output from Stan / brms fit to the same family. For the rank likelihood from the exact marginal needs GHK Monte Carlo (Halton sequence); on the longitudinal `lame()` path you can opt in with `log_lik_method = "observed_ghk"`, on the cross-sectional `ame()` path the fallback is the augmented-Z normal approximation (with a one-time warning). Inspect `fit$log_lik_method` on any fit to see which branch was used.

Chunked log-lik portability. When fit with `save_log_lik = "chunked"`, the on-disk chunk files default to `tempdir()`, which is cleared at the end of the R session. If you intend to `saveRDS()` the fit and reload it in a fresh session, supply an explicit persistent `log_lik_path` (e.g. `"./loglik_chunks"`) so the chunks survive the round trip.

Value

A loo object.

Examples

```
data(YX_nrm)
fit <- ame(YX_nrm$Y, Xdyad = YX_nrm$X, R = 0,
           nscan = 60, burn = 15, odens = 5,
           save_log_lik = TRUE, verbose = FALSE)
if (requireNamespace("loo", quietly = TRUE)) {
  loo_res <- loo::loo(fit)
  print(loo_res)
}
```

mhalf*Symmetric square root of a matrix*

Description

Computes the symmetric square root of a positive definite matrix

Usage

```
mhalf(M)
```

Arguments

M a positive definite matrix

Value

a matrix H such that H^2 equals M

Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

nobs.ame*Number of observed dyads in an AME / LAME fit*

Description

Number of finite (non-missing) cells in Y, summed over time slices for longitudinal fits. Useful as a denominator for sample-size reporting and as the basis for AIC/BIC *if* you also have a log-likelihood (which `ame()` / `lame()` do not directly expose; see [logLik.ame](#)).

Usage

```
## S3 method for class 'ame'
nobs(object, ...)

## S3 method for class 'lame'
nobs(object, ...)
```

Arguments

```
object      an ame or lame fit.
...         ignored.
```

Value

Integer: number of observed dyads in Y.

nobs.ame_als	<i>Number of observed dyads in an ame_als fit</i>
--------------	---

Description

Mirrors [nobs.ame](#) so the MCMC and ALS fits expose the same accessor.

Usage

```
## S3 method for class 'ame_als'
nobs(object, ...)
```

Arguments

```
object      an ame_als fit.
...         ignored.
```

Value

Integer: number of observed dyads.

nodematch

*ERGM-style covariate helpers for ame() / lame()***Description**

`nodematch(x)` returns an $n \times n$ matrix with 1 where $x[i] == x[j]$ and 0 otherwise – the AME analogue of ERGM’s `nodematch` term, suitable for `Xdyad` as a single homophily covariate. `absdiff(x)` returns the absolute difference $|x[i] - x[j]|$, the AME analogue of ERGM’s `absdiff`. `nodefactor(x)` returns the dyadic matrix of $x[i] + x[j]$ for a numeric x (or a list of per-level binary dyadic indicators for a factor / character x).

Usage

```
nodematch(x, na_diag = TRUE)
```

```
absdiff(x, na_diag = TRUE)
```

```
nodefactor(x, na_diag = TRUE)
```

Arguments

`x` a numeric, factor, or character vector of length n .

`na_diag` logical: set the diagonal to NA? Defaults to TRUE.

Details

All helpers return a matrix *or* list of matrices that is ready to wrap into an $n \times n \times p$ `Xdyad` array via `simplify2array` or `array()`.

Value

An $n \times n$ numeric matrix (or, for a factor x passed to `nodefactor`, a named list of such matrices).

Examples

```
n <- 12
grp <- sample(letters[1:3], n, replace = TRUE)
age <- rnorm(n, 40, 10)
# build a single same-group homophily covariate
Xdyad <- array(nodematch(grp), dim = c(n, n, 1),
               dimnames = list(NULL, NULL, "same_group"))
# combine homophily + age difference
Xdyad <- array(c(nodematch(grp), absdiff(age)),
               dim = c(n, n, 2),
               dimnames = list(NULL, NULL, c("same_group", "age_diff")))
```

per_actor_slopes	<i>Post-MCMC per-actor time-varying slopes</i>
------------------	--

Description

Computes a smoothed per-actor time-varying slope coefficient on a nodal covariate slice. For `kind = "row"`, each row-actor i gets a length- T slope path $\beta_{i,t}$ on `Xrow[i, covariate_idx, t]`, fit by ridge-penalised least squares on the residual after the main MCMC linear predictor.

Usage

```
per_actor_slopes(fit, kind = c("row", "col"), covariate_idx = 1L, lambda = 1)
```

Arguments

<code>fit</code>	A fitted <code>lame</code> object.
<code>kind</code>	"row" (default; per-row-actor slopes) or "col" (per-column-actor slopes).
<code>covariate_idx</code>	Integer column index into the chosen nodal covariate (<code>Xrow</code> or <code>Xcol</code>). Default 1L.
<code>lambda</code>	Non-negative smoothing parameter (first-difference penalty across periods). Default 1.

Value

A list with `slopes` (an $n_{actors} \times T$ matrix), `kind`, `covariate_idx`, `lambda`, and `label`. Class "per_actor_slopes".

Examples

```
data(YX_bin_list)
fit <- lame(YX_bin_list$Y, YX_bin_list$X, family = "binary", R = 0,
           nscan = 100, burn = 25, odens = 5, verbose = FALSE)
# post-MCMC per-row-actor slopes on the first dyadic covariate
pas <- per_actor_slopes(fit, kind = "row", lambda = 1)
dim(pas$slopes)
```

plot.ame*Simple diagnostic plot for AME model fit*

Description

Provides a quick visual summary of an AME model fit, focusing on key convergence diagnostics. For more detailed diagnostics, use the specific plotting functions: `trace_plot()`, `gof_plot()`, `ab_plot()`, and `uv_plot()`.

Usage

```
## S3 method for class 'ame'  
plot(x, ...)
```

Arguments

<code>x</code>	an object of class "ame" from fitting an AME model
<code>...</code>	additional arguments passed to <code>trace_plot()</code>

Details

By default, this function simply calls `trace_plot()` to show MCMC trace plots and posterior distributions for key parameters. This provides a quick check of model convergence and mixing.

For more detailed visualizations, use the specialized functions:

trace_plot() MCMC diagnostics and posterior distributions

gof_plot() Goodness-of-fit assessment

ab_plot() Additive sender/receiver effects

uv_plot() Multiplicative latent factors

Value

A ggplot2 object from `trace_plot()` (invisibly)

Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

See Also

[ame](#), [trace_plot](#), [gof_plot](#), [ab_plot](#), [uv_plot](#)

Examples

```
# Fit an AME model
data(YX_nrm)
fit <- ame(YX_nrm$Y, Xdyad = YX_nrm$X, R = 2, gof = TRUE,
           nscan = 100, burn = 10, odens = 1, verbose = FALSE)

# Quick diagnostic plot (shows trace plots)
plot(fit)
```

plot.ame_als	<i>Plot the convergence of a fast AME fit</i>
--------------	---

Description

Plots the block coordinate descent deviance/SSE history – a convergence diagnostic for an [ame_als](#) or [lame_als](#) fit. For substantive plots see [uv_plot](#), [ab_plot](#) and [gof_plot](#).

Usage

```
## S3 method for class 'ame_als'
plot(x, ...)
```

Arguments

`x` an `ame_als` object.

`...` further arguments passed to the underlying plot.

Value

`x`, invisibly.

plot.lame	<i>Plot diagnostics for a LAME model fit</i>
-----------	--

Description

Creates diagnostic plots for a LAME (Longitudinal Additive and Multiplicative Effects) model, including MCMC diagnostics, parameter evolution over time, and longitudinal goodness-of-fit checks. This is the default plot method for LAME objects.

Usage

```
## S3 method for class 'lame'
plot(
  x,
  which = c(1, 2, 3, 4),
  time.points = NULL,
  ask = FALSE,
  pages = c("single", "multiple"),
  ...
)
```

Arguments

<code>x</code>	an object of class "lame" from fitting a LAME model
<code>which</code>	numeric or character vector specifying which plots to produce: 1 or "trace" = MCMC trace plots, 2 or "density" = posterior density plots, 3 or "gof" = longitudinal goodness-of-fit plots, 4 or "effects" = additive and multiplicative effects, 5 or "network" = network snapshots at selected times. Default is <code>c(1,2,3,4)</code> to show main diagnostic plots.
<code>time.points</code>	numeric vector of time points for network snapshots (only used if "network" in <code>which</code>). Default is <code>c(1, middle, last)</code> .
<code>ask</code>	logical; if TRUE, user is prompted before each plot page
<code>pages</code>	character string specifying how to arrange plots: "single" = one combined page (default), "multiple" = separate pages for each plot type
<code>...</code>	additional arguments (currently not used)

Details

The function produces a multi-panel plot containing:

MCMC trace plots Shows mixing and convergence of key parameters

Posterior distributions Density plots of regression coefficients and variance components

Longitudinal GOF Time series of observed network statistics with posterior predictive intervals

Effects over time Evolution of additive effects across time periods (if applicable)

Network snapshots Visualization of network at selected time points

The plot adapts to the longitudinal structure:

- Shows temporal trends in network statistics
- Highlights composition changes if actors enter/exit
- Displays credible intervals for time-varying statistics

Value

NULL (invisibly). Plots are displayed as side effects.

Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

See Also

[lame](#), [trace_plot](#), [gof_plot](#), [ab_plot](#), [uv_plot](#)

Examples

```
# Create simple longitudinal network data
set.seed(6886)
n <- 10
nms <- paste0("n", 1:n)
Y_list <- list(
  matrix(rnorm(n * n), n, n, dimnames = list(nms, nms)),
  matrix(rnorm(n * n), n, n, dimnames = list(nms, nms))
)
diag(Y_list[[1]]) <- diag(Y_list[[2]]) <- NA
fit <- lame(Y_list, family = "normal",
            nscan = 50, burn = 10, odens = 1, verbose = FALSE, plot = FALSE)

# default combined plot
plot(fit)
```

posterior_options	<i>Options for saving posterior samples during MCMC</i>
-------------------	---

Description

Options for saving posterior samples during MCMC

Usage

```
posterior_options(save_UV = FALSE, save_ab = FALSE, thin_UV = 10, thin_ab = 10)
```

Arguments

save_UV	Logical; whether to save samples of U and V matrices (default FALSE)
save_ab	Logical; whether to save samples of additive effects a and b (default FALSE)
thin_UV	Integer; thinning interval for U/V samples (default 10)
thin_ab	Integer; thinning interval for a/b samples (default 10)

Value

List of posterior saving options, to be passed to the posterior_opts argument of [ame](#): `ame(Y, ..., posterior_opts = posterior_options(save_UV = TRUE))`

Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

posterior_quantiles	<i>Extract posterior quantiles for model components</i>
---------------------	---

Description

Extract posterior quantiles for model components

Usage

```
posterior_quantiles(
  fit,
  component = c("beta", "UV", "ab"),
  probs = c(0.025, 0.5, 0.975)
)
```

Arguments

fit	Fitted ame model object
component	Character; which component: "beta", "UV", "ab"
probs	Numeric vector of probabilities for quantiles

Value

Matrix or array of posterior quantiles

Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

precomputeX	<i>Precompute design matrix statistics</i>
-------------	--

Description

Precomputes summary statistics of the design array X to speed up MCMC calculations in the AME model

Usage

```
precomputeX(X)
```

Arguments

X n x n x p covariate array

Value

The input array with precomputed statistics as attributes:

Xr	row sums
Xc	column sums
mX	matricized version
mXt	dyad-transposed matricized version
XX	regression sums of squares
XXt	crossproduct sums of squares

Author(s)

Peter Hoff

predict.ame	<i>Predict method for AME models</i>
-------------	--------------------------------------

Description

Generate predictions from fitted AME models, including point estimates and predictive distributions.

Usage

```
## S3 method for class 'ame'
predict(
  object,
  newdata = NULL,
  type = c("response", "link", "distribution"),
  n_samples = 100,
  include_uncertainty = TRUE,
  ...
)
```

Arguments

object	Fitted AME model object
newdata	Optional dyadic covariates for prediction: a single 3-D array (n x n x p_dyad) whose slices match the dyadic covariates the model was fit with (same order; do not include the intercept or nodal-covariate slices). Nodal covariates cannot be changed at prediction time – their fitted contribution is reused. When omitted, the fitted design is used.

type	Character; type of prediction: • "response": predicted values on response scale (default) • "link": predicted values on link scale • "distribution": full posterior predictive distribution
n_samples	For type="distribution", number of posterior samples
include_uncertainty	Logical; include parameter uncertainty (default TRUE)
...	Additional arguments (not used)

Value

Depending on type:

- "response"/"link": Matrix of predictions
- "distribution": Array of posterior predictive samples

Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

Examples

```
# Fit model
data(YX_nrm)
fit <- ame(YX_nrm$Y, Xdyad = YX_nrm$X, R = 2,
           nscan = 100, burn = 10, odens = 1, verbose = FALSE)

# Point predictions
Y_pred <- predict(fit)

# Predictions on link scale
Y_link <- predict(fit, type = "link")
```

predict.ame_als	<i>Predictions from a fast AME fit</i>
-----------------	--

Description

Returns predictions from an [ame_als](#) or [lame_als](#) fit: the fitted linear predictor on the link scale (type = "link") or the response scale (type = "response", the default).

Usage

```
## S3 method for class 'ame_als'
predict(object, newdata = NULL, type = c("response", "link"), ...)
```

Arguments

object	an ame_als object.
newdata	optional dyadic covariate array matching object\$X ([n_row, n_col, p, T]); a matrix or 3D array is coerced.
type	"response" (default) or "link".
...	ignored.

Details

With newdata = NULL the training-data fitted values are returned. Supplying newdata – a dyadic covariate array with the *same* actors and dimensions as the fitted design – substitutes the dyadic covariate contribution while holding the intercept, additive effects and multiplicative term fixed; it predicts counterfactual dyadic covariates for the same network, not out-of-sample actors.

Value

A matrix (cross-sectional) or list of matrices (longitudinal).

predict.lame	<i>Predict method for LAME models</i>
--------------	---------------------------------------

Description

Generate predictions from a fitted longitudinal AME model. Returns a list of matrices (one per time point) on the requested scale.

Usage

```
## S3 method for class 'lame'
predict(
  object,
  newdata = NULL,
  type = c("response", "link"),
  h = 0L,
  by_draw = FALSE,
  interval = c("none", "credible"),
  probs = c(0.025, 0.975),
  newexposure = NULL,
  n_draws = NULL,
  seed = NULL,
  ...
)
```

Arguments

object	Fitted LAME model object.
newdata	Optional list of T dyadic covariate arrays ([n_row, n_col, p] each, with the same actors as the fit) to compute counterfactual predictions. When NULL, the training-data predictions are returned.
type	Character; "response" (default) or "link".
h	Integer ≥ 0 : forecast horizon. When $h = 0$ (default), returns in-sample predictions as before. When $h > 0$, propagates the AR(1) (or RW1) state-space model forward by h periods and returns a list of h matrices (one per future period). Requires at least one dynamic component on the fit. Warns when posterior ρ_β is near 1.
by_draw	When TRUE and $h > 0$, returns an $n \times n \times h \times n_{\text{draws}}$ array of per-draw forecasts instead of per-period means.
interval	One of "none" (default) or "credible". When $h > 0$ and "credible", the per-period output is a list of length-3 lists with \$lower, \$median, \$upper matrices computed at the probs quantiles across posterior draws. Ignored for in-sample ($h = 0$) predictions.
probs	Length-2 vector of lower / upper quantiles for the credible interval when interval = "credible". Default c(0.025, 0.975).
newexposure	Optional length-h non-negative numeric vector of future-period exposures (Poisson only). When omitted and the fit has period_exposure stored, defaults to the last observed exposure; when both are absent, defaults to 1.
n_draws	Number of posterior draws to use when $h > 0$. Default NULL uses all stored draws. Ignored for in-sample ($h = 0$) predictions.
seed	Optional RNG seed for the $h > 0$ forecast draws, making forecasts reproducible. Ignored when $h = 0$.
...	Additional arguments (not used).

Value

List of prediction matrices (one per time point).

prediction_draws_long *Long-format draws of the linear predictor for marginalesffects-style use*

Description

Returns a long-format data frame with one row per (draw, i, j, period) combination, giving the per-draw linear predictor (or response-scale prediction) at each dyad and period. Intended for **marginalesffects-** / **tidybayes**-style downstream summarisation: column names follow the .draw / .chain / .iteration / .value convention so that tidybayes::spread_draws() and marginalesffects::posterior_draw auto-dispatch on the returned data frame. Actor and period names from fit\$Y's dimnames are carried forward into the actor_i, actor_j, period_label columns.

Usage

```
prediction_draws_long(
  object,
  newdata = NULL,
  type = c("link", "response"),
  n_draws = 100L,
  seed = NULL
)
```

Arguments

object	A fitted lame object.
newdata	Optional list of T dyadic covariate arrays for counterfactual evaluation. Default NULL uses in-sample covariates.
type	One of "link" (default) or "response".
n_draws	Number of posterior draws to use. Default 100.
seed	Optional RNG seed.

Value

A long-format data frame with columns .chain, .iteration, .draw, period, period_label, i, j, actor_i, actor_j, .value. Returned as a tibble when the **tibble** package is available; otherwise a plain data frame.

```
print.als_dynamic_beta
```

Print method for penalised ALS time-varying beta

Description

Print method for penalised ALS time-varying beta

Usage

```
## S3 method for class 'als_dynamic_beta'
print(x, digits = 4, ...)
```

Arguments

x	An als_dynamic_beta result.
digits	Number of significant digits.
...	Ignored.

Value

x, invisibly. Called for its side effect of printing a summary of the penalised ALS time-varying coefficient estimates.

print.ame

Print method for AME model objects

Description

Displays a formatted summary of a fitted AME (Additive and Multiplicative Effects) model. This method provides a concise overview of model structure, parameter estimates, and goodness-of-fit statistics without generating new data.

Usage

```
## S3 method for class 'ame'
print(x, ...)
```

Arguments

`x` an object of class "ame" from fitting an AME model
`...` additional arguments (not currently used)

Details

The print method displays:

- Model type (unipartite/bipartite, symmetric/asymmetric)
- Network dimensions and observation count
- Family and link function used
- Number of MCMC iterations
- Parameter counts for regression coefficients and latent factors
- Basic convergence diagnostics if available

Unlike `simulate`, this method only formats existing results for display and does not perform any new computations or data generation.

Value

Invisibly returns the input object (for method chaining)

Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

See Also

[summary.ame](#) for detailed summaries, [simulate.ame](#) for generating new networks, [predict.ame](#) for predictions

Examples

```
# Fit model
data(YX_nrm)
fit <- ame(YX_nrm$Y, Xdyad = YX_nrm$X, R = 2,
           nscan = 100, burn = 10, odens = 1, verbose = FALSE)

# Display summary
print(fit)
```

print.ame.sim	<i>Print methods for AME and LAME simulation objects</i>
---------------	--

Description

Print methods for AME and LAME simulation objects

Usage

```
## S3 method for class 'ame.sim'
print(x, ...)

## S3 method for class 'lame.sim'
print(x, ...)
```

Arguments

x	simulation object of class "ame.sim" or "lame.sim"
...	additional arguments (not used)

Value

the simulation object invisibly

Author(s)

Shahryar Minhas

print.ame_als	<i>Print an ame_als object</i>
---------------	--------------------------------

Description

Print an ame_als object

Usage

```
## S3 method for class 'ame_als'  
print(x, digits = 4, ...)
```

Arguments

x	an ame_als object.
digits	number of digits to display.
...	ignored.

Value

x, invisibly.

print.boot_ame	<i>Print bootstrap results for a fast AME fit</i>
----------------	---

Description

Print bootstrap results for a fast AME fit

Usage

```
## S3 method for class 'boot_ame'  
print(x, digits = max(3L, getOption("digits") - 3L), ...)
```

Arguments

x	a boot_ame object.
digits	number of digits to display.
...	ignored.

Value

x, invisibly.

print.gof_temporal	<i>Print method for gof_temporal output</i>
--------------------	---

Description

Print method for gof_temporal output

Usage

```
## S3 method for class 'gof_temporal'
print(x, ...)
```

Arguments

x	A gof_temporal result.
...	Ignored.

Value

x, invisibly. Called for its side effect of printing a summary of the temporal-trend posterior-predictive check.

print.lame	<i>Print method for LAME objects</i>
------------	--------------------------------------

Description

Provides a concise print output for fitted LAME models. When the fit has two or more dynamic effects active simultaneously (dynamic_uv + dynamic_ab + dynamic_beta in any combination), a compact joint table summarising the AR(1) hyperparameters of each dynamic block is printed instead of a separate paragraph per component. Disable the compact mode by passing compact = FALSE.

Usage

```
## S3 method for class 'lame'
print(x, compact = TRUE, digits = 3, ...)
```

Arguments

x	an object of class "lame"
compact	logical: when TRUE (default), use a compact joint table for fits with 2+ dynamic components; set to FALSE to force the per-component long-form display.
digits	Number of digits to display in the compact table. Default 3.
...	additional arguments (not used)

Value

the lame object invisibly

Author(s)

Peter Hoff, Cassy Dorff, Shahryar Minhas

<code>print.lame_multi</code>	<i>Print method for lame_multi</i>
-------------------------------	------------------------------------

Description

Print method for lame_multi

Usage

```
## S3 method for class 'lame_multi'
print(x, digits = 3, ...)
```

Arguments

<code>x</code>	A lame_multi object.
<code>digits</code>	Number of significant digits.
<code>...</code>	Ignored.

Value

x, invisibly. Called for its side effect of printing a summary of the pooled multi-panel fit.

<code>print.lfo_lame</code>	<i>Print method for lfo() results</i>
-----------------------------	---------------------------------------

Description

Print method for lfo() results

Usage

```
## S3 method for class 'lfo_lame'
print(x, ...)
```

Arguments

<code>x</code>	A lfo_lame object.
<code>...</code>	Ignored.

Value

x, invisibly. Called for its side effect of printing a summary of the leave-future-out cross-validation results.

```
print.per_actor_slopes
```

Print method for per_actor_slopes

Description

Print method for per_actor_slopes

Usage

```
## S3 method for class 'per_actor_slopes'
print(x, digits = 3, ...)
```

Arguments

x	A per_actor_slopes result.
digits	Number of significant digits.
...	Ignored.

Value

x, invisibly. Called for its side effect of printing a summary of the per-actor time-varying slopes.

```
print.summary.ame
```

Print method for summary.ame objects

Description

Prints a formatted summary of an AME model fit

Usage

```
## S3 method for class 'summary.ame'
print(x, digits = 3, ...)
```

Arguments

x	a summary.ame object
digits	number of digits to display (default: 3)
...	additional arguments (not used)

Value

the summary.ame object invisibly

```
print.summary.ame_als Print a fast AME summary
```

Description

Print a fast AME summary

Usage

```
## S3 method for class 'summary.ame_als'
print(x, digits = 4, ...)
```

Arguments

x	a summary.ame_als object.
digits	number of digits to display.
...	ignored.

Value

x, invisibly.

```
print.summary.lame Print method for summary.lame objects
```

Description

Prints a formatted summary of a LAME model fit

Usage

```
## S3 method for class 'summary.lame'
print(x, digits = 3, ...)
```

Arguments

x	a summary.lame object
digits	number of digits to display (default: 3)
...	additional arguments (not used)

Value

the summary.lame object invisibly

prior_summary	<i>Print the priors used by an AME / LAME / ame_als fit</i>
---------------	---

Description

Bayesian-hygiene helper modelled on `rstanarm::prior_summary()`. Prints the priors that were actually in effect for a fit, with defaults filled in. For `ame_als` fits it just states that the estimator is a frequentist point estimator and there are no priors.

Usage

```
prior_summary(object, ...)

## Default S3 method:
prior_summary(object, ...)

## S3 method for class 'ame'
prior_summary(object, ...)

## S3 method for class 'lame'
prior_summary(object, ...)

## S3 method for class 'ame_als'
prior_summary(object, ...)
```

Arguments

<code>object</code>	a fitted <code>ame</code> , <code>lame</code> , or <code>ame_als</code> object.
<code>...</code>	ignored.

Value

`object`, invisibly.

<code>procrustes_align</code>	<i>Procrustes alignment of latent positions across time</i>
-------------------------------	---

Description

Aligns dynamic latent positions across time periods to remove arbitrary rotational indeterminacy. This is essential for interpreting temporal trajectories of latent positions, since the latent space is only identified up to rotation at each time point.

Uses Procrustes rotation: at each time step t , finds the orthogonal rotation matrix that best aligns U_t to U_{t-1} (minimizing Frobenius norm), then applies it sequentially from $t=2$ to T .

Usage

```
procrustes_align(
  object = NULL,
  U = NULL,
  V = NULL,
  G = NULL,
  return_fit = FALSE,
  per_draw = FALSE,
  ...
)
```

Arguments

<code>object</code>	A fitted <code>ame</code> or <code>lame</code> object, or <code>NULL</code> if raw arrays are provided via <code>U/V/G</code> .
<code>U</code>	Optional 3D array <code>[n, R, T]</code> of sender latent positions. If <code>object</code> is provided and <code>U</code> is <code>NULL</code> , extracted from <code>object\$U</code> .
<code>V</code>	Optional 3D array <code>[n, R, T]</code> of receiver latent positions. For unipartite asymmetric models, aligned independently. For bipartite models, aligned jointly with <code>U</code> via the <code>G</code> interaction matrix.
<code>G</code>	Optional <code>[R_row, R_col]</code> interaction matrix for bipartite models, transformed to preserve the invariant $U G V'$.
<code>return_fit</code>	Logical. If <code>TRUE</code> and <code>object</code> is provided, returns a modified copy of the fit object with aligned latent positions. Default <code>FALSE</code> .
<code>per_draw</code>	Logical. When <code>TRUE</code> , run Procrustes alignment per posterior draw rather than on the posterior-mean trajectory. This uses <code>object\$U_full / object\$V_full</code> (the per-draw posterior cubes – populated when <code>posterior_opts</code> includes storing <code>U/V</code>) when present; otherwise falls back to mean-trajectory alignment and emits an informational note. Per-draw alignment is the methodologically correct treatment – rotation indeterminacy is a per-draw property, not a per-mean one – but is more memory-hungry. Default <code>FALSE</code> .
<code>...</code>	Additional arguments (currently unused).

Details

For unipartite networks, `U` and `V` are aligned independently using separate Procrustes rotations. For symmetric networks, only `U` is present and aligned.

For bipartite networks, `U` and `V` are aligned jointly: separate rotation matrices are computed for `U` and `V`, and the `G` interaction matrix is updated as $G_{aligned} = t(R_U) \% \% G \% \% R_V$ to preserve the product $U \% \% G \% \% t(V)$.

If `U` is a 2D matrix (static model with a single time point), it is returned unchanged with an informational message.

Value

If `return_fit = FALSE` (default): a list with components `U` (aligned sender positions), `V` (aligned receiver positions, if applicable), and `G` (updated interaction matrix, for bipartite).

If `return_fit = TRUE`: a copy of `object` with aligned latent positions replacing the originals.

Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

See Also

[latent_positions](#) for extracting aligned positions as a tidy data frame, [uv_plot](#) for visualizing latent positions

Examples

```
data(YX_bin_list)
# YX_bin_list$Y stores latent-scale values; threshold to 0/1 first
Y_bin <- lapply(YX_bin_list$Y, function(y) 1 * (y > 0))
fit <- lame(Y_bin, Xdyad = YX_bin_list$X, R = 2,
            family = "binary", dynamic_uv = TRUE,
            burn = 5, nscan = 5, odens = 1,
            verbose = FALSE)
aligned <- procrustes_align(fit)
str(aligned$U) # aligned 3D array [n, R, T]
```

raSab_bin_fc	<i>Simulate a and Sab from full conditional distributions under bin likelihood</i>
--------------	--

Description

Simulate a and Sab from full conditional distributions under bin likelihood

Usage

```
raSab_bin_fc(Z, Y, a, b, Sab, Sab0=NULL, eta0=NULL, SS = round(sqrt(nrow(Z))))
```

Arguments

- Z a square matrix, the current value of Z
- Y square binary relational matrix
- a current value of row effects
- b current value of column effects
- Sab current value of Cov(a,b)
- Sab0 prior (inverse) scale matrix for the prior distribution
- eta0 prior degrees of freedom for the prior distribution
- SS number of iterations

Value

Z	new value of Z
Sab	new value of Sab
a	new value of a

Author(s)

Peter Hoff

raSab_cbin_fc	<i>Simulate a and Sab from full conditional distributions under the cbin likelihood</i>
---------------	---

Description

Simulate a and Sab from full conditional distributions under the cbin likelihood

Usage

```
raSab_cbin_fc(Z, Y, a, b, Sab, odmax, odobs, Sab0=NULL, eta0=NULL, SS =  
round(sqrt(nrow(Z))))
```

Arguments

Z	a square matrix, the current value of Z
Y	square matrix of ranked nomination data
a	current value of row effects
b	current value of column effects
Sab	current value of Cov(a,b)
odmax	a scalar or vector giving the maximum number of nominations for each individual
odobs	observed outdegree
Sab0	prior (inverse) scale matrix for the prior distribution
eta0	prior degrees of freedom for the prior distribution
SS	number of iterations

Value

Z	new value of Z
Sab	new value of Sab
a	new value of a

Author(s)

Peter Hoff

raSab_frn_fc	<i>Simulate a and Sab from full conditional distributions under frn likelihood</i>
--------------	--

Description

Simulate a and Sab from full conditional distributions under frn likelihood

Usage

```
raSab_frn_fc(Z, Y, YL, a, b, Sab, odmax, odobs, Sab0=NULL, eta0=NULL,
SS=round(sqrt(nrow(Z))))
```

Arguments

Z	a square matrix, the current value of Z
Y	square matrix of ranked nomination data
YL	list of ranked individuals, from least to most preferred in each row
a	current value of row effects
b	current value of column effects
Sab	current value of Cov(a,b)
odmax	a scalar or vector giving the maximum number of nominations for each individual
odobs	observed outdegree
Sab0	prior (inverse) scale matrix for the prior distribution
eta0	prior degrees of freedom for the prior distribution
SS	number of iterations

Value

Z	new value of Z
Sab	new value of Sab
a	new value of a

Author(s)

Peter Hoff

rbeta_ab_bip_gibbs_cpp

Full bipartite Gibbs update for beta, a, b

Description

Single C++ function replacing the bipartite beta/a/b update block in lame.R

Usage

```
rbeta_ab_bip_gibbs_cpp(
  Z,
  Xlist,
  UV_eff,
  a_current,
  b_current,
  s2,
  g_prior,
  va,
  vb,
  rvar,
  cvar
)
```

Arguments

Z	3D array (nA x nB x T)
Xlist	List of T arrays (nA x nB x p)
UV_eff	nA x nB matrix (UGV' or $U*V'$)
a_current	Current row effects (length nA)
b_current	Current column effects (length nB)
s2	Dyadic variance
g_prior	G-prior parameter
va	Row effect variance (diagonal element of Sab)
vb	Column effect variance (diagonal element of Sab)
rvar	Whether to update row effects
cvar	Whether to update column effects

Value

List with beta, a, b

rbeta_ab_fc

Conditional simulation of additive effects and regression coefficients

Description

Simulates from the joint full conditional distribution of (beta,a,b) in a social relations regression model

Usage

```
rbeta_ab_fc(
  Z,
  Sab,
  rho,
  X = NULL,
  s2 = 1,
  offset = 0,
  iV0 = NULL,
  m0 = NULL,
  g = length(Z)
)
```

Arguments

Z	n X n normal relational matrix
Sab	row and column covariance
rho	dyadic correlation
X	n x n x p covariate array
s2	dyadic variance
offset	a matrix of the same dimension as Z. It is assumed that Z-offset follows a SRRM, so the offset should contain any multiplicative effects (such as $U \otimes t(V)$)
iV0	prior precision matrix for regression parameters
m0	prior mean vector for regression parameters
g	prior variance scale for g-prior when iV0 is unspecified

Value

beta	regression coefficients
a	additive row effects
b	additive column effects

Author(s)

Peter Hoff

rbeta_ab_rep_fc	<i>Gibbs sampling of additive row and column effects and regression coefficient with independent replicate relational data</i>
-----------------	--

Description

Simulates from the joint full conditional distribution of (a,b,beta), assuming same additive row and column effects and regression coefficient across replicates.

Usage

rbeta_ab_rep_fc(Z.T, Sab, rho, X.T, s2=1)

Arguments

Z.T	n x n x T array, with the third dimension for replicates. Each slice of the array is a (latent) normal relational matrix, with multiplicative effects subtracted out
Sab	row and column covariance
rho	dyadic correlation
X.T	n x n x p x T covariate array
s2	dyadic variance

Value

beta	regression coefficients
a	additive row effects
b	additive column effects

Author(s)

Peter Hoff, Yanjun He

read_log_lik	<i>Read the per-iteration log-lik matrix back from on-disk chunks</i>
--------------	---

Description

For fits run with save_log_lik = "chunked", the per-iteration pointwise log-likelihood lives in per-column-chunk binary files instead of fit\$log_lik. This helper reconstitutes the [n_stored, n_obs] matrix in memory by issuing one readBin per chunk. loo.lame() / waic.lame() call this transparently.

Usage

read_log_lik(x)

Arguments

`x` A fitted `ame/lame` object with `$log_lik_chunks` (i.e. fit with `save_log_lik = "chunked"`).

Value

The full `[n_stored, n_obs]` double matrix.

reconstruct_EZ

Reconstruct EZ and UVPM matrices from AME model output

Description

Helper functions to recover EZ (linear predictor) and UVPM (posterior mean of the multiplicative product) matrices. When the fit already stores the quantity (as `lame()` fits do for UVPM), the stored posterior mean is returned directly; otherwise it is reconstructed from the saved factors.

Note: EZ returns the linear predictor (η), not the response:

- For Gaussian: $EZ = \eta = \mu$ (identity link)
- For Poisson: $EZ = \eta = \log(\lambda)$ (can be negative)
- For Binary: $EZ = \eta = \text{probit inverse of } p$ (can be any real value) Use YPM for predictions on the response scale.

Usage

```
reconstruct_EZ(fit, X = NULL)
```

```
reconstruct_UVPM(fit)
```

Arguments

`fit` Fitted AME model object

`X` Covariate array (optional, will use `fit$X` if available)

Details

`ame()` fits do not store these matrices (to save memory), so they are rebuilt from the posterior factor means. `lame()` fits store UVPM, which is returned as-is.

Value

Reconstructed matrix

Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

reexports	<i>Objects exported from other packages</i>
-----------	---

Description

These objects are imported from other packages. Follow the links below to see their documentation.

[ggplot2](#) [autoplot](#)

residuals.ame	<i>Extract residuals from AME model</i>
---------------	---

Description

Computes residuals as the difference between observed values and fitted values. For type = "response", returns $Y - \text{fitted}(\text{object})$. For type = "pearson", returns response residuals scaled by the standard deviation implied by the family (e.g., $\sqrt{p(1-p)}$) for binary).

Usage

```
## S3 method for class 'ame'  
residuals(object, type = c("response", "pearson"), ...)
```

Arguments

object	Fitted AME model object (class "ame").
type	Character; "response" (default) for raw residuals or "pearson" for standardized residuals.
...	Additional arguments (not used).

Value

An $n \times n$ matrix (unipartite) or $nA \times nB$ matrix (bipartite) of residuals. Entries where the original data was NA remain NA.

Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

See Also

[fitted.ame](#), [predict.ame](#)

residuals.ame_als	<i>Residuals from a fast AME fit</i>
-------------------	--------------------------------------

Description

Returns residuals from an `ame_als` or `lame_als` fit.

Usage

```
## S3 method for class 'ame_als'
residuals(object, type = c("response", "working"), ...)
```

Arguments

<code>object</code>	an <code>ame_als</code> object.
<code>type</code>	"response" (default) or "working".
<code>...</code>	ignored.

Details

`type = "response"` (default) returns observed Y minus the response-scale fitted values, so `residuals()` reconciles with `fitted()`. `type = "working"` returns the Gaussian working-scale residuals the estimator actually minimised (identical to "response" for the normal family).

Value

A matrix (cross-sectional) or list of matrices (longitudinal).

residuals.lame	<i>Extract residuals from LAME model</i>
----------------	--

Description

Extract residuals from LAME model

Usage

```
## S3 method for class 'lame'
residuals(object, type = c("response", "pearson"), ...)
```

Arguments

<code>object</code>	Fitted LAME model
<code>type</code>	Type of residuals ("response" or "pearson")
<code>...</code>	Additional arguments

Value

List of residual matrices (one per time point)

rhat_dynamic_beta	<i>Multivariate split-R-hat for dynamic_beta coefficient paths</i>
-------------------	--

Description

Given one or more multi-chain lame fits whose \$BETA is [n_iter, p, T], computes the multivariate R-hat per coefficient k treating the length- T path as one multivariate observation per iteration.

Usage

```
rhat_dynamic_beta(fit_list, coefs = NULL)
```

Arguments

fit_list A list of fitted lame objects from lame_parallel(..., chains = K), or any ame_chain_list produced by re-running lame() with different seeds.

coefs Optional character vector of coefficient names to subset (matches dimnames(fit\$BETA)[[2]]).

Details

For chain c , let $\beta_t^{(c)} \in \mathbb{R}^T$ be the path. With m chains and n iterations per chain, define

$$W_k = \frac{1}{m} \sum_c S_c^{(k)}, \quad B_k = \frac{n}{m-1} \sum_c (\bar{\beta}_c^{(k)} - \bar{\beta}^{(k)})(\bar{\beta}_c^{(k)} - \bar{\beta}^{(k)})'$$

where $S_c^{(k)}$ is the within-chain sample covariance of path k in chain c . Then $V_k = ((n-1)/n)W_k + ((m+1)/(mn))B_k$ and $\hat{R}_k^{mvt} = \sqrt{\lambda_{\max}(W_k^{-1}V_k)}$. For nearly degenerate covariances we add a tiny ridge to W_k .

Value

Data frame with one row per coefficient: coef, rhat_mvt, rhat_max_univariate, n_chains, n_iter_per_chain, T. rhat_mvt is the Brooks-Gelman multivariate statistic; rhat_max_univariate is the max over per-(k,t) split-R-hat values for comparison.

Examples

```
data(YX_bin_list)
# note: pass seed = to lame() -- an external set.seed() does not vary
# the sampler, so it would produce identical chains
fit_list <- lapply(c(1L, 2L), function(s) {
  lame(YX_bin_list$Y, YX_bin_list$X, family = "binary", R = 0,
    dynamic_beta = "dyad", seed = s,
    nscan = 60, burn = 15, odens = 5, verbose = FALSE)
```

```
  })
  rhat_dynamic_beta(fit_list)
```

rmvnorm

Simulation from a multivariate normal distribution

Description

Simulates a matrix where the rows are i.i.d. samples from a multivariate normal distribution

Usage

```
rmvnorm(n, mu, Sigma, Sigma.chol = NULL)
```

Arguments

n	sample size
mu	multivariate mean vector
Sigma	covariance matrix
Sigma.chol	Cholesky factorization of Sigma

Value

a matrix with n rows

Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

rrho_fc

Griddy Gibbs update for dyadic correlation

Description

Simulation of dyadic correlation from its approximate full conditional distribution using griddy Gibbs sampling

Usage

```
rrho_fc(Z, Sab, s2 = 1, offset = 0, ngp = 100, asp = NULL)
```

Arguments

Z	n X n normal relational matrix
Sab	covariance of additive effects
s2	residual variance
offset	matrix of the same dimension as Z. It is assumed that Z-offset follows an SRM distribution, so the offset should contain any regression terms and multiplicative effects (such as $X\beta + U\epsilon(V)$)
ngp	the number of points for an unevenly-spaced grid on which to approximate the full conditional distribution
asp	use arc sine prior (TRUE) or uniform prior (FALSE)

Value

a value of rho

Author(s)

Peter Hoff

rrho_mh	<i>Metropolis update for dyadic correlation</i>
---------	---

Description

Metropolis update for dyadic correlation

Usage

rrho_mh(Z, rho, s2 = 1, offset=0, asp=NULL)

Arguments

Z	n X n normal relational matrix
rho	current value of rho
s2	current value of s2
offset	matrix of the same dimension as Z. It is assumed that Z-offset is equal to dyadic noise, so the offset should contain any additive and multiplicative effects (such as $X\beta + U\epsilon(V) + \text{outer}(a,b, "+")$)
asp	use arc sine prior (TRUE) or uniform prior (FALSE)

Value

a new value of rho

Author(s)

Peter Hoff

rrho_mh_rep	<i>Metropolis update for dyadic correlation with independent replicate data</i>
-------------	---

Description

Metropolis update for dyadic correlation with independent replicate data.

Usage

```
rrho_mh_rep(E.T, rho, s2 = 1)
```

Arguments

E.T	Array of square residual relational matrix series. The third dimension of the array is for different replicates. Each slice of the array according to the third dimension is a square residual relational matrix.
rho	current value of rho
s2	current value of s2

Value

a new value of rho

Author(s)

Peter Hoff, Yanjun He

rs2_fc	<i>Gibbs update for dyadic variance</i>
--------	---

Description

Gibbs update for dyadic variance

Usage

```
rs2_fc(Z, rho, offset=0, nu0=NULL, s20=NULL)
```

Arguments

Z	n X n normal relational matrix
rho	current value of rho
offset	matrix of the same dimension as Z. It is assumed that Z-offset is equal to dyadic noise, so the offset should contain any additive and multiplicative effects (such as $X\beta(X, \beta + U \cdot t(V) + \text{outer}(a, b, "+"))$)
nu0	prior degrees of freedom
s20	prior estimate of s2; when NULL (default) the empirical mean-square residual is used, so the prior carries nu0 pseudo-observations at the scale of the data rather than an absolute guess of 1 (which corrupts s2 – and through it rho – whenever Y is not on unit scale)

Value

a new value of s2

Author(s)

Peter Hoff

rs2_rep_fc	<i>Gibbs update for dyadic variance with independent replicate relational data</i>
------------	--

Description

Gibbs update for dyadic variance with independent replicate relational data

Usage

rs2_rep_fc(E.T, rho)

Arguments

E.T	Array of square residual relational matrix series. The third dimension of the array is for different replicates. Each slice of the array according to the third dimension is a square residual relational matrix
rho	current value of rho

Value

a new value of s2

Author(s)

Peter Hoff, Yanjun He

rSab_fc

*Gibbs update for additive effects covariance***Description**

Gibbs sampling for the covariance matrix of additive row and column effects in the AME model. This function implements the inverse-Wishart posterior update for the covariance matrix Sab.

Usage

```
rSab_fc(a, b, Sab0=NULL, eta0=NULL, rvar=TRUE, cvar=TRUE, symmetric=FALSE)
```

Arguments

a	vector of row random effects (additive sender effects)
b	vector of column random effects (additive receiver effects)
Sab0	prior scale matrix. Convention (Hoff/amen): Sab0 is passed <i>raw</i> ; the inverse-Wishart scale used internally is $\eta_0 \cdot \text{Sab0}$, so the prior mean of Sab is $\eta_0 \text{Sab0} / (\eta_0 - 3) \approx \text{Sab0}$ and the prior mode is $\eta_0 \text{Sab0} / (\eta_0 + 3)$. Every call site in the package (ame() unipartite and bipartite, lame() unipartite and bipartite, and the raSab_bin/cbin/frn joint updates) passes Sab0 raw under this same convention, so a given prior\$Sab0 means the same prior everywhere. Default is diag(2) (weakly informative).
eta0	prior degrees of freedom for the prior distribution. Default is 4, which is the minimum for a proper prior with 2x2 matrix.
rvar	logical: should row variance be updated? (default TRUE)
cvar	logical: should column variance be updated? (default TRUE)
symmetric	logical: is this a symmetric network? (default FALSE)

Details

The function implements different update strategies:

- Full update: When both rvar and cvar are TRUE, updates the full 2x2 covariance matrix using an inverse-Wishart distribution
- Row variance only: When only rvar is TRUE, updates only Sab[1,1]
- Column variance only: When only cvar is TRUE, updates only Sab[2,2]
- Symmetric case: When symmetric is TRUE, draws a single shared variance for the row and column effects (inverse-gamma update) with zero covariance

Value

Updated covariance matrix Sab (2x2 matrix with variances on diagonal and covariance off-diagonal)

Author(s)

Peter Hoff, Shahryar Minhas

rSuv_fc

*Gibbs update for multiplicative effects covariance***Description**

Gibbs sampling for the covariance matrix of multiplicative effects U and V in the AME model. This function implements the inverse-Wishart posterior update for the covariance matrix of the stacked UV effects.

Usage

```
rSuv_fc(U, V, Suv0=NULL, kappa0=NULL)
```

Arguments

U	matrix of multiplicative row effects (n x R matrix where n is the number of nodes and R is the dimension of multiplicative effects)
V	matrix of multiplicative column effects (n x R matrix)
Suv0	prior (inverse) scale matrix for the prior distribution. Default is identity matrix of dimension 2R x 2R, providing a weakly informative prior.
kappa0	prior degrees of freedom for the prior distribution. Default is 2 + 2R, which is the minimum for a proper prior with a 2R x 2R covariance matrix.

Details

The function updates the full covariance matrix for multiplicative effects using an inverse-Wishart distribution. The posterior distribution is:

$$Suv \sim IW(kappa0 * Suv0 + t(UV) \% * \%UV, n + kappa0)$$

where $UV = cbind(U, V)$ is the stacked matrix of effects.

This hierarchical prior allows for adaptive shrinkage of the multiplicative effects, with the amount of shrinkage determined by the data through the posterior update.

Value

Updated covariance matrix Suv (2R x 2R matrix) for the stacked effects [U, V]. The first R x R block contains covariances for U, the last R x R block contains covariances for V, and the off-diagonal blocks contain cross-covariances between U and V.

Author(s)

Peter Hoff, Shahryar Minhas

rtnorm_interval_logp	<i>Exact truncated-normal draw on (lb, ub) via the log.p-scale inverse CDF</i>
----------------------	--

Description

Draws $z \sim N(ez, 1)$ truncated to (lb, ub) for each cell, working entirely on the log-probability scale in the tail that contains the truncation interval. This stays exact for arbitrarily extreme ez / bounds (log-scale pnorm/qnorm are accurate to |ez| of several hundred), so no probability clamp is needed. Infinite bounds reduce to the one-sided case automatically.

Usage

```
rtnorm_interval_logp(ez, lb, ub)
```

Arguments

ez	vector of conditional means.
lb	lower bounds (recycled to length(ez)).
ub	upper bounds (recycled to length(ez)).

Value

vector of truncated-normal draws, same length as ez.

Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

rUV_dynamic_bip_fc_cpp	<i>Bipartite dynamic UV Gibbs update</i>
------------------------	--

Description

Replaces the nested R loops for bipartite dynamic_uv in lame.R. Uses direct 2x2 inverse formula for common R=2 case.

Usage

```
rUV_dynamic_bip_fc_cpp(U_cube, V_cube, E, G, rho_uv, sigma_uv, s2)
```

Arguments

U_cube	3D array (nA x RA x T)
V_cube	3D array (nB x RB x T)
E	3D array of residuals (nA x nB x T)
G	Interaction matrix (RA x RB)
rho_uv	AR(1) persistence parameter
sigma_uv	Innovation standard deviation
s2	Dyadic variance

Value

List with updated U_cube, V_cube

rUV_dynamic_fc	<i>Gibbs sampling of dynamic U and V with AR(1) evolution</i>
----------------	---

Description

Updates latent factor positions U and V that evolve over time according to an AR(1) process: $u_{i,t} = \rho * u_{i,t-1} + \epsilon_{i,t}$

Usage

```
rUV_dynamic_fc(U, V, ET, rho_uv, sigma_uv, s2, shrink=TRUE, symmetric=FALSE)
```

Arguments

U	3D array of current U positions (n x R x T)
V	3D array of current V positions (n x R x T)
ET	3D array of residuals (n x n x T)
rho_uv	AR(1) autoregressive parameter for latent positions
sigma_uv	Innovation standard deviation for latent positions
s2	dyadic variance
shrink	whether to apply shrinkage (default TRUE)
symmetric	whether the network is symmetric (default FALSE)

Value

list with updated U and V arrays

Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

rUV_dynamic_fc_cpp	<i>Update dynamic latent positions using AR(1) process</i>
--------------------	--

Description

Update dynamic latent positions using AR(1) process

Usage

```
rUV_dynamic_fc_cpp(  
  U_current,  
  V_current,  
  ET,  
  rho_uv,  
  sigma_uv,  
  s2,  
  shrink,  
  symmetric  
)
```

Arguments

U_current	Current 3D array of U positions (n x R x T)
V_current	Current 3D array of V positions (n x R x T)
ET	3D array of residuals (n x n x T)
rho_uv	AR(1) autoregressive parameter for latent positions
sigma_uv	Innovation standard deviation for latent positions
s2	Dyadic variance
shrink	Whether to apply shrinkage
symmetric	Whether network is symmetric

Value

List with updated U and V arrays

rUV_dynamic_snap_fc *Gibbs sampling of dynamic U and V with snap-shift dynamics*

Description

Like rUV_dynamic_fc but lets each actor's latent position either drift under the AR(1) prior or jump under a diffuse $N(0, \kappa^2)$ snap prior, chosen per actor-period by a Gaussian log-marginal model selection.

Usage

```
rUV_dynamic_snap_fc(
  U,
  V,
  ET,
  rho_uv,
  sigma_uv,
  s2,
  kappa,
  pi_snap,
  delta_u_current = NULL,
  delta_v_current = NULL,
  shrink = TRUE,
  symmetric = FALSE
)
```

Arguments

U	3D array of current U positions (n x R x T)
V	3D array of current V positions (n x R x T)
ET	3D array of residuals (n x n x T)
rho_uv	AR(1) autoregressive parameter for the drift prior
sigma_uv	Innovation standard deviation for the drift prior
s2	dyadic variance
kappa	diffuse snap-prior standard deviation
pi_snap	prior snap probability
delta_u_current	current sender-side snap indicators. If NULL, a zero matrix is used.
delta_v_current	current receiver-side snap indicators. If NULL, a zero matrix is used.
shrink	whether to apply shrinkage (default TRUE)
symmetric	whether the network is symmetric (default FALSE)

Value

list with updated U, V arrays and delta_u, delta_v snap indicators

Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

rUV_dynamic_snap_fc_cpp

Update dynamic latent positions with snap-shift model selection

Description

Like rUV_dynamic_fc_cpp but, for $t > 0$, chooses per actor between an AR(1) drift prior and a diffuse $N(0, \kappa^2 I)$ snap prior via a Gaussian log-marginal-likelihood model selection, drawing a Bernoulli snap indicator δ and sampling the latent position from the selected posterior.

Usage

```
rUV_dynamic_snap_fc_cpp(
  U_current,
  V_current,
  ET,
  rho_uv,
  sigma_uv,
  s2,
  kappa,
  pi_snap,
  delta_u_current,
  delta_v_current,
  shrink,
  symmetric
)
```

Arguments

U_current	Current 3D array of U positions ($n \times R \times T$)
V_current	Current 3D array of V positions ($n \times R \times T$)
ET	3D array of residuals ($n \times n \times T$)
rho_uv	AR(1) autoregressive parameter for the drift prior
sigma_uv	Innovation standard deviation for the drift prior
s2	Dyadic variance
kappa	Diffuse snap-prior standard deviation ($\kappa^2 \gg \sigma_{uv}^2$)
pi_snap	Prior snap probability

delta_u_current	Current sender-side snap indicators from the previous sweep
delta_v_current	Current receiver-side snap indicators from the previous sweep
shrink	Whether to apply shrinkage
symmetric	Whether network is symmetric

Value

List with updated U, V arrays and delta_u, delta_v snap indicators

rUV_dynamic_t_fc	<i>Gibbs sampling of dynamic U and V with heavy-tailed (Student-t) innovations</i>
------------------	--

Description

Like rUV_dynamic_fc but the AR(1) innovations are Student-t via a scale-mixture of normals, a continuous heavy-tailed alternative to snap-shift.

Usage

```
rUV_dynamic_t_fc(  
  U,  
  V,  
  ET,  
  rho_uv,  
  sigma_uv,  
  s2,  
  nu,  
  lambda_u = NULL,  
  lambda_v = NULL,  
  shrink = TRUE,  
  symmetric = FALSE  
)
```

Arguments

U	3D array of current U positions (n x R x T)
V	3D array of current V positions (n x R x T)
ET	3D array of residuals (n x n x T)
rho_uv	AR(1) autoregressive parameter
sigma_uv	Innovation scale
s2	dyadic variance
nu	Student-t degrees of freedom

lambda_u	current local scales for U (n x T)
lambda_v	current local scales for V (n x T)
shrink	whether to apply shrinkage (default TRUE)
symmetric	whether the network is symmetric (default FALSE)

Value

list with updated U, V arrays and lambda_u, lambda_v local scales

Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

rUV_dynamic_t_fc_cpp	<i>Update dynamic latent positions with heavy-tailed (Student-t) AR(1) innovations</i>
----------------------	--

Description

Like rUV_dynamic_fc_cpp but each AR(1) innovation is Student-t rather than Gaussian, via a scale-mixture: the innovation for $u_{t,i}$ has variance $\sigma^2 / \lambda_{t,i}$ with $\lambda_{t,i} \sim \text{Gamma}(\nu/2, \nu/2)$. Provides a continuous heavy-tailed alternative to the discrete snap-shift model.

Usage

```
rUV_dynamic_t_fc_cpp(
  U_current,
  V_current,
  ET,
  rho_uv,
  sigma_uv,
  s2,
  nu,
  lambda_u,
  lambda_v,
  shrink,
  symmetric
)
```

Arguments

U_current	Current 3D array of U positions (n x R x T)
V_current	Current 3D array of V positions (n x R x T)
ET	3D array of residuals (n x n x T)
rho_uv	AR(1) autoregressive parameter
sigma_uv	Innovation scale

s2	Dyadic variance
nu	Student-t degrees of freedom
lambda_u	Current local scales for U (n x T)
lambda_v	Current local scales for V (n x T)
shrink	Whether to apply shrinkage
symmetric	Whether network is symmetric

Value

List with updated U, V arrays and lambda_u, lambda_v local scales

rUV_fc	<i>Gibbs sampling of U and V</i>
--------	----------------------------------

Description

A Gibbs sampler for updating the multiplicative effect matrices U and V

Usage

rUV_fc(Z, U, V, Suv, rho, s2 = 1, offset = 0)

Arguments

Z	n X n normal relational matrix
U	current value of U
V	current value of V
Suv	covariance of (U V)
rho	dyadic correlation
s2	dyadic variance
offset	a matrix of the same dimension as Z. It is assumed that Z-offset is equal to the multiplicative effects plus dyadic noise, so the offset should contain any additive effects (such as Xbeta(X,beta+ outer(a,b,"+"))

Value

U	a new value of U
V	a new value of V

Author(s)

Peter Hoff

rUV_rep_fc	<i>Gibbs sampling of U and V</i>
------------	----------------------------------

Description

A Gibbs sampler for updating the multiplicative effect matrices U and V, assuming they are the same across replicates.

Usage

```
rUV_rep_fc(E.T,U,V,rho,s2=1,shrink=TRUE)
```

Arguments

E.T	Array of square residual relational matrix series with additive effects and covariates subtracted out. The third dimension of the array is for different replicates. Each slice of the array according to the third dimension is a square residual relational matrix.
U	current value of U
V	current value of V
rho	dyadic correlation
s2	dyadic variance
shrink	adaptively shrink the factors with a hierarchical prior

Value

U	a new value of U
V	a new value of V

Author(s)

Peter Hoff, Yanjun He

rUV_sym_fc	<i>Gibbs sampling of U and V</i>
------------	----------------------------------

Description

A Gibbs sampler for updating the multiplicative effect matrices U and V in the symmetric case. In this case $U\%*\%t(V)$ is symmetric, so this is parameterized as $V=U\%*\%L$ where L is the diagonal matrix of eigenvalues of $U\%*\%t(V)$.

Usage

```
rUV_sym_fc(E, U, V, s2 = 1, shrink=TRUE)
```

Arguments

E	square residual relational matrix
U	current value of U
V	current value of V
s2	dyadic variance
shrink	adaptively shrink the factors with a hierarchical prior

Value

U	a new value of U
V	a new value of V

Author(s)

Peter Hoff

Examples

```
U0<-matrix(rnorm(30,2),30,2) ; V0<-U0%%diag(c(3,-2))
E<- U0%%t(V0) + matrix(rnorm(30^2),30,30)
rUV_sym_fc
```

rwish	<i>Simulation from a Wishart distribution</i>
-------	---

Description

Simulates a random Wishart-distributed matrix

Usage

```
rwish(S0, nu = dim(S0)[1] + 2)
```

Arguments

S0	a positive definite matrix
nu	a positive integer

Value

a positive definite matrix

Author(s)

Peter Hoff

Examples

```
## The expectation is S0*nu

S0<-rwish(diag(3))

SS<-matrix(0,3,3)
for(s in 1:1000) { SS<-SS+rwish(S0,5) }

SS/s

S0*5
```

rZ_bin_bip_batch_cpp *Batch binary Z sampling across all time periods (bipartite, rho=0)*

Description

Vectorized probit update for bipartite binary networks without dyadic correlation.

Usage

```
rZ_bin_bip_batch_cpp(Z, EZ, Y)
```

Arguments

Z	3D array of latent values (nA x nB x T)
EZ	3D array of expected values (nA x nB x T)
Y	3D array of observed values (nA x nB x T)

Value

Updated Z array

rZ_bin_fc *Simulate Z based on a probit model*

Description

Simulates a random latent matrix Z given its expectation, dyadic correlation and a binary relational matrix Y

Usage

```
rZ_bin_fc(Z, EZ, rho, Y)
```

Arguments

- Z a square matrix, the current value of Z
- EZ expected value of Z
- rho dyadic correlation
- Y square binary relational matrix

Value

a square matrix , the new value of Z

Author(s)

Peter Hoff

rZ_cbin_bip_fc	<i>Sample Z under bipartite censored binary nominations (rectangular)</i>
----------------	---

Description

Rectangular analogue of [rZ_cbin_fc](#). Row-wise constraints: $Y_{ij} = 1 \Rightarrow Z_{ij} > 0$; $Y_{ij} = 0 \ \& \ odobs_i < odmax_i \Rightarrow Z_{ij} < 0$; nominated alters dominate non-nominated alters within the row. With $\rho = 0$ there is no reciprocity term.

Usage

rZ_cbin_bip_fc(Z, EZ, Y, odmax, odobs)

Arguments

- Z current rectangular latent matrix (nA x nB).
- EZ expected value (nA x nB).
- Y observed 0/1 matrix (nA x nB); NA entries resampled from the unconstrained prior.
- odmax row-wise maximum nominations (length nA or scalar).
- odobs row-wise observed outdegree (length nA).

Value

updated nA x nB latent matrix.

Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

rZ_cbin_fc

*Simulate Z given fixed rank nomination data***Description**

Simulates a random latent matrix Z given its expectation, dyadic correlation and censored binary nomination data

Usage

```
rZ_cbin_fc(Z, EZ, rho, Y, odmax, odobs)
```

Arguments

Z	a square matrix, the current value of Z
EZ	expected value of Z
ρ	dyadic correlation
Y	square matrix of ranked nomination data
$odmax$	a scalar or vector giving the maximum number of nominations for each individual
$odobs$	observed outdegree

Details

simulates Z under the constraints (1) $Y[i,j]=1, Y[i,k]=0 \Rightarrow Z[i,j]>Z[i,k]$, (2) $Y[i,j]=1 \Rightarrow Z[i,j]>0$, (3) $Y[i,j]=0 \& odobs[i]<odmax[i] \Rightarrow Z[i,j]<0$

Value

a square matrix, the new value of Z

Author(s)

Peter Hoff

rZ_frnbip_fc	<i>Sample Z under bipartite fixed-rank nominations (rectangular)</i>
--------------	--

Description

Rectangular analogue of [rZ_frnb_fc](#). Row-wise rank constraints: ranked nominees are positive and ordered by rank; non-nominees fall below all ranked cells in the row (and below 0 when the row is unsaturated). With $\rho = 0$ the unipartite triangle coupling drops out.

Usage

```
rZ_frnbip_fc(Z, EZ, Y, YL, odmax, odobs)
```

Arguments

Z	current rectangular latent matrix (nA x nB).
EZ	expected value (nA x nB).
Y	observed rank matrix (nA x nB); 0 = unranked, 1..ncol(YL) = rank order.
YL	per-row ranked-receiver list (nA x max_rank).
odmax	row-wise max nominations.
odobs	row-wise observed outdegree.

Details

Monotonicity convention (important for simulation). The sampler enforces *higher Y -> higher Z*: when $Y[i, j] > Y[i, k]$, the corresponding latent values satisfy $Z[i, j] > Z[i, k]$. When simulating data for recovery tests, build Y via $\text{rank}(Z[i, :])$ (low rank = small Y), not $\text{rank}(-Z[i, :])$. the inverted convention identifies the negative of the true beta.

Value

updated nA x nB latent matrix.

Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

rZ_frnc

*Simulate Z given fixed rank nomination data***Description**

Simulates a random latent matrix Z given its expectation, dyadic correlation and fixed rank nomination data

Usage

```
rZ_frnc(Z, EZ, rho, Y, YL, odmax, odobs)
```

Arguments

Z	a square matrix, the current value of Z
EZ	expected value of Z
ρ	dyadic correlation
Y	square matrix of ranked nomination data
YL	list of ranked individuals, from least to most preferred in each row
$odmax$	a scalar or vector giving the maximum number of nominations for each individual
$odobs$	observed outdegree

Details

simulates Z under the constraints (1) $Y[i,j] > Y[i,k] \Rightarrow Z[i,j] > Z[i,k]$, (2) $Y[i,j] > 0 \Rightarrow Z[i,j] > 0$, (3) $Y[i,j] = 0$ & $odobs[i] < odmax[i] \Rightarrow Z[i,j] < 0$

Value

a square matrix, the new value of Z

Author(s)

Peter Hoff

rZ_nrm_batch_cpp	<i>Batch normal Z sampling across all time periods</i>
------------------	--

Description

Replaces the per-time-period R loop with a single C++ call that loops internally, reducing R-to-C++ transition overhead.

Usage

rZ_nrm_batch_cpp(Z, EZ, rho, s2, Y)

Arguments

- Z 3D array of latent values (n x n x T)
- EZ 3D array of expected values (n x n x T)
- rho Dyadic correlation parameter
- s2 Dyadic variance
- Y 3D array of observed values (n x n x T)

Value

List with updated Z and E_nrm (residuals)

rZ_nrm_fc	<i>Simulate missing values in a normal AME model</i>
-----------	--

Description

Simulates missing values of a sociomatrix under a normal AME model

Usage

rZ_nrm_fc(Z, EZ, rho,s2, Y)

Arguments

- Z a square matrix, the current value of Z
- EZ expected value of Z
- rho dyadic correlation
- s2 dyadic variance
- Y square relational matrix

Value

a square matrix, equal to Y at non-missing values

Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

rZ_ord_bip_fc	<i>Sample Z under bipartite ordinal data (rectangular)</i>
---------------	--

Description

Rectangular analogue of [rZ_ord_fc](#). Cutpoints are data-induced (the boundary between rank w and rank w+1 is the maximum Z in rank w and minimum Z in rank w+1), matching the existing unipartite convention. With rho = 0 in bipartite, every cell at rank w is drawn independently from a truncated normal centered at EZ.

Usage

rZ_ord_bip_fc(Z, EZ, Y)

Arguments

- Z current rectangular latent matrix (nA x nB).
- EZ expected value (nA x nB).
- Y observed ordinal matrix (nA x nB).

Value

updated nA x nB latent matrix.

Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

rZ_ord_explicit_fc	<i>Sample Z given explicit cutpoints alpha (asymmetric ordinal)</i>
--------------------	---

Description

Rectangular / square truncated-normal sample on observed cells. This is the explicit-cutpoint version of [rZ_ord_fc](#), parameterised by the explicit alpha vector rather than deriving cutpoints from Z order statistics.

Usage

```
rZ_ord_explicit_fc(Z, EZ, Y_int, alpha)
```

Arguments

- Z current latent matrix
- EZ expected value of Z (linear predictor)
- Y_int integer-recoded ordinal Y (1..K)
- alpha length-(K-1) cutpoints with alpha[1] = 0

Value

updated Z

rZ_ord_fc	<i>Simulate Z given the partial ranks</i>
-----------	---

Description

Simulates a random latent matrix Z given its expectation, dyadic correlation and partial rank information provided by W

Usage

```
rZ_ord_fc(Z, EZ, rho, Y)
```

Arguments

- Z a square matrix, the current value of Z
- EZ expected value of Z
- rho dyadic correlation
- Y matrix of ordinal data

Value

a square matrix, the new value of Z

Author(s)

Peter Hoff

rZ_ord_sym_explicit_fc	<i>Symmetric ordinal Z sample given explicit cutpoints (R >= 0 safe)</i>
------------------------	---

Description

Mirror image of [rZ_ord_sym_fc](#) (variance 1 on the upper triangle, mirrored to the lower) parameterised by an explicit alpha vector instead of data-induced cutpoints.

Usage

```
rZ_ord_sym_explicit_fc(Z, EZ, Y_int, alpha)
```

Arguments

- | | |
|-------|--|
| Z | current symmetric latent matrix |
| EZ | expected value of Z |
| Y_int | integer ordinal Y (symmetric) |
| alpha | length-(K-1) cutpoints with alpha[1] = 0 |

Value

updated symmetric Z (diagonal sampled from unconstrained prior)

rZ_ord_sym_fc	<i>Sample Z under symmetric ordinal data (square symmetric matrix)</i>
---------------	--

Description

Symmetric-Z analogue of [rZ_ord_fc](#): each unordered dyad i, j carries a single latent value ($Z_{ij} = Z_{ji}$) drawn from a truncated normal with mean equal to the average linear predictor ($EZ_{ij} + EZ_{ji}$) / 2 and variance 1 (the model's conditional). The lower triangle is mirrored after the upper-triangle draws so the full matrix is exactly symmetric at every sweep.

Usage

```
rZ_ord_sym_fc(Z, EZ, Y)
```

Arguments

- Z current symmetric latent matrix (n x n, $Z = t(Z)$).
- EZ expected value of Z (regression + additive + multiplicative contributions); can be asymmetric, the helper averages the two directed contributions.
- Y observed symmetric ordinal matrix (n x n, $Y = t(Y)$); diagonal is ignored.

Value

updated symmetric n x n latent matrix with NA on the diagonal.

Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

rZ_pois_bip_fc	<i>Sample Z under bipartite Poisson (rectangular MH step)</i>
----------------	---

Description

Rectangular analogue of [rZ_pois_fc](#). Each (i, j) cell is updated independently with a Metropolis-Hastings step on the Poisson log-link; there is no upper/lower-triangle coupling and no diagonal because the bipartite Y is nA x nB with disjoint row and column actor sets.

Usage

```
rZ_pois_bip_fc(Z, EZ, s2, Y, log_exposure = 0)
```

Arguments

- Z current rectangular latent matrix (nA x nB).
- EZ expected value (regression + additive + multiplicative effects), nA x nB.
- s2 dyadic variance (proposal scale on the latent log-mean).
- Y observed count matrix (nA x nB); NA entries are resampled from the prior.
- log_exposure optional per-period log-exposure offset (scalar or matrix conformable with Y). Default 0.

Value

updated nA x nB latent matrix.

Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

rZ_pois_fc

*Gibbs update for latent variable in a Poisson AME model***Description**

Updates the latent variable Z in a Poisson AME model using a Metropolis-Hastings step. The model assumes $y_{\{i,j\}} \sim \text{Poisson}(\exp(z_{\{i,j\}}))$ where $z_{\{i,j\}}$ is the latent variable representing the log mean.

Usage

```
rZ_pois_fc(Z, EZ, rho, s2, Y)
```

Arguments

Z	a square matrix, the current value of the latent variable
EZ	expected value of Z (regression effects + random effects)
ρ	dyadic correlation
$s2$	dyadic variance (overdispersion parameter)
Y	square relational matrix of observed counts

Value

updated value of Z

Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

sampler_describe

*Describe the estimator behind a fitted object***Description**

Reports which estimation routine produced a fitted object and what uncertainty information, if any, is available. Methods exist for `ame_als` fits (the fast block coordinate descent estimator) and `boot_ame` bootstrap objects.

Usage

```
sampler_describe(object, verbose = TRUE)

## S3 method for class 'ame_als'
sampler_describe(object, verbose = TRUE)

## S3 method for class 'boot_ame'
sampler_describe(object, verbose = TRUE)

## S3 method for class 'ame'
sampler_describe(object, verbose = TRUE)

## S3 method for class 'lame'
sampler_describe(object, verbose = TRUE)
```

Arguments

object	a fitted object (ame_als or boot_ame).
verbose	logical; if TRUE (default) print the description.

Value

The input object, invisibly.

sample_ab_bipartite	<i>Sample additive effects for bipartite networks</i>
---------------------	---

Description

Sample additive effects for bipartite networks

Usage

```
sample_ab_bipartite(Z, EZ_without_ab, sigma2_a, sigma2_b, s2)
```

Value

List with components a (row effects) and b (column effects)

sample_alpha_cowles	<i>Cowles MH update for explicit ordinal cutpoints (Z-marginalised)</i>
---------------------	---

Description

One Metropolis-Hastings sweep on alpha with Z integrated out of the conditional. The proposal is a symmetric random walk in $\delta = \log(\text{diff}(\alpha))$ space; the acceptance ratio uses the marginal ordinal-probit likelihood. Mixing of alpha under this update is dramatically faster than the data-induced Gibbs convention (Cowles 1996 reports ESS gains of an order of magnitude on standard ordinal-probit benchmarks).

Usage

```
sample_alpha_cowles(alpha, Y_int, EZ, tau_prop, symmetric = FALSE)
```

Arguments

alpha	numeric, current cutpoints with $\alpha[1] = 0$, length K-1.
Y_int	integer matrix (or array) of ordinal categories coded 1..K, with NA for missing cells.
EZ	linear predictor at the dyad level, same shape as Y_int.
tau_prop	numeric, RW proposal SD in delta space (will be adapted in burn-in by the caller).
symmetric	logical, whether the network is symmetric (restricts the likelihood to upper-triangle cells so each dyad is counted once; variance 1, no precision rescaling).

Value

list with elements alpha, delta, accept (logical).

Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

sample_beta_dynamic_cpp	<i>Sample the dynamic-block beta path via FFBS</i>
-------------------------	--

Description

Forward-filter / backward-sample the AR(1) state-space model for the dynamic-block beta coefficients. Returns the joint draw of beta_dyn at every time period.

Usage

```
sample_beta_dynamic_cpp(
  Xdyn_list,
  Xstat_list,
  Z_list,
  offset_list,
  beta_static,
  rho_by_coef,
  sigma_by_coef,
  Lambda,
  beta0_mean,
  beta0_cov,
  s2,
  dyad_rho,
  bipartite,
  symmetric,
  use_dyad_rho
)
```

Arguments

Xdyn_list	T-length list of (n*n) x p_dyn long-format design matrices for the dynamic block (column-major reshape per period).
Xstat_list	T-length list of (n*n) x p_static long-format design matrices for the static block.
Z_list	T-length list of (n x n) latent matrices.
offset_list	T-length list of (n x n) offset matrices ($a_i + b_j + U_i'V_j$ contributions; everything that's not in $X \cdot \text{beta}$).
beta_static	Length p_static current static beta vector.
rho_by_coef	Length p_dyn vector of AR(1) rho values for each dynamic coefficient. (Per-block but expanded per-column for vectorised indexing.)
sigma_by_coef	Length p_dyn vector of AR(1) innovation standard deviations for each dynamic coefficient.
Lambda	Block-diagonal innovation scale matrix (p_dyn x p_dyn). Combined with σ^2 to give $Q = \sigma^2 * \text{Lambda}$.
beta0_mean	Length p_dyn prior mean for the first state beta_1 (the prior is placed directly on beta_1, no predict step at t = 1).
beta0_cov	p_dyn x p_dyn prior covariance for beta_1. Must be a fixed matrix that does not depend on the current (rho, sigma) draw so the transition-only hyperparameter conditionals remain exact.
s2	Dyadic variance.
dyad_rho	Dyadic correlation (ignored when use_dyad_rho=FALSE).
bipartite	Whether the network is bipartite.
symmetric	Whether the network is symmetric.
use_dyad_rho	Whether to use the dyad-corr branch (TRUE only for unipartite, asymmetric, with a non-zero rho).

Value

List with: path – a ($T \times p_{\text{dyn}}$) matrix of beta draws (one row per period); chol_fail – integer count of Cholesky failures.

sample_beta_static_cpp

Sample the static-block beta conditional on the dynamic path

Description

Conjugate Gaussian update for the static coefficient block, treating the dynamic path as known. Uses a flat-ish ridge-style prior prior_prec on the static beta (typically $\text{diag}(1/g)$ to match the existing g-prior path).

Usage

```
sample_beta_static_cpp(
  Xdyn_list,
  Xstat_list,
  Z_list,
  offset_list,
  beta_dyn_path,
  prior_mean,
  prior_prec,
  s2,
  dyad_rho,
  bipartite,
  symmetric,
  use_dyad_rho
)
```

Arguments

Xdyn_list	T-length list of long-format dynamic design matrices.
Xstat_list	T-length list of long-format static design matrices.
Z_list	T-length list of latent ($n \times n$) matrices.
offset_list	T-length list of ($n \times n$) offsets.
beta_dyn_path	($T \times p_{\text{dyn}}$) dynamic path matrix.
prior_mean	Length p_{static} prior mean.
prior_prec	$p_{\text{static}} \times p_{\text{static}}$ prior precision.
s2	Dyadic variance.
dyad_rho	Dyadic correlation.
bipartite	TRUE/FALSE.
symmetric	TRUE/FALSE.
use_dyad_rho	TRUE/FALSE.

Value

List with: beta – length p_static; chol_fail – integer.

sample_dynamic_ab_cpp *Sample dynamic additive effects with AR(1) evolution*

Description

Gibbs update of the per-period additive effects under the AR(1) state model with stationary initial condition. For each actor and period the full conditional combines the AR(1) bridge prior (stationary init at $t = 1$) with the dyadic residual likelihood: $\text{resid}_{ij} = a_i + b_j + e_{ij}$, $e_{ij} \sim N(0, s^2)$. The reciprocal effect (b_j for the a-step, the freshly updated a_i for the b-step) is subtracted from each residual, missing residuals are skipped, and for symmetric networks each dyad contributes exactly once ($\text{resid}(i,j) = a_i + a_j + e_{ij}$).

Usage

```
sample_dynamic_ab_cpp(
  a_current,
  b_current,
  Z_array,
  EZ_array,
  rho_ab,
  sigma_ab,
  s2,
  symmetric
)
```

Arguments

a_current	Current 2D array of row effects (n x T)
b_current	Current 2D array of column effects (n x T)
Z_array	3D array of latent positions (n x n x T)
EZ_array	3D array of expected values without additive effects (n x n x T)
rho_ab	AR(1) parameter for additive effects
sigma_ab	Innovation standard deviation
s2	Dyadic residual variance
symmetric	Whether the network is symmetric

Value

List with updated a and b arrays

sample_rho_ab_cpp	<i>Sample AR(1) parameter for dynamic additive effects</i>
-------------------	--

Description

Sample AR(1) parameter for dynamic additive effects

Usage

```
sample_rho_ab_cpp(  
  a_mat,  
  b_mat,  
  sigma_ab,  
  rho_current,  
  symmetric,  
  prior_mean = 0,  
  prior_sd = -1  
)
```

Arguments

a_mat	Matrix of row effects (n x T)
b_mat	Matrix of column effects (n x T)
sigma_ab	Innovation standard deviation
rho_current	Current value of rho
symmetric	Whether the network is symmetric
prior_mean	Prior mean for rho. Used only when prior_sd > 0.
prior_sd	Prior SD for rho. prior_sd < 0 (the default) selects a Jeffreys-like flat prior; a positive value switches to a truncated Normal(prior_mean, prior_sd^2) prior.

Value

Updated rho value

sample_rho_beta_cpp	<i>Sample the AR(1) rho for each dynamic block</i>
---------------------	--

Description

Truncated-Normal full conditional, one rho per block.

Usage

```
sample_rho_beta_cpp(  
  beta_path,  
  group_id,  
  n_groups,  
  Lambda_inv,  
  sigma_by_coef,  
  rho_current,  
  rho_prior_mean,  
  rho_prior_sd,  
  rho_lower = 0,  
  rho_upper = 0.999  
)
```

Arguments

- beta_path (T x p_dyn) matrix of beta draws.
- group_id Length p_dyn integer vector (1-based) of block IDs.
- n_groups Number of distinct block IDs.
- Lambda_inv (p_dyn x p_dyn) inverse of the (full) Lambda scale.
- sigma_by_coef Length p_dyn vector of per-coef sigma (block-shared).
- rho_current Length n_groups vector of current rho values.
- rho_prior_mean Length n_groups vector of prior means.
- rho_prior_sd Length n_groups vector of prior SDs.
- rho_lower Lower truncation bound (typically 0).
- rho_upper Upper truncation bound (typically 0.999).

Value

Length n_groups vector of new rho values.

sample_rho_G_mh	<i>Logit-scale MH update on the AR(1) coefficient rho_G</i>
-----------------	---

Description

Proposes $\rho^* = \tanh(\operatorname{atanh}(\rho) + \tau * N(0, 1))$; under a uniform $\rho \sim U(-1, 1)$ prior the proposal is symmetric in the Fisher-z scale and the Jacobian is $\log(1 - \rho^2)$. The MH ratio compares the AR(1) prior density of `vec(G)_path` at the current vs proposed ρ .

Usage

```
sample_rho_G_mh(rho_G, vecG_path, sigma_G2, tau = 0.3)
```

Arguments

rho_G	current AR(1) coefficient
vecG_path	p x N matrix of FFBS-sampled states
sigma_G2	state innovation variance
tau	RW proposal SD on the Fisher-z scale

Value

list with rho (updated), accept (logical)

sample_rho_uv	<i>Sample AR(1) parameter for dynamic latent factors</i>
---------------	--

Description

Independence Metropolis-Hastings update coherent with the stationary AR(1) initial condition used by the dynamic UV kernels. The proposal is the conjugate Normal implied by the transitions and the Normal(prior_mean, prior_sd^2) prior, drawn truncated to (-0.99, 0.99) via the inverse CDF; the acceptance ratio supplies the $t = 1$ stationary factor $f_1(\rho) = (1 - \rho^2)^{nR/2} \exp(-(1 - \rho^2) S_1 / (2 \sigma^2))$ that the Gaussian proposal omits. Defaults (prior_mean = 0, prior_sd = 1) preserve the historical behaviour; lame::lame() passes the user-set prior\$rho_uv_mean / prior\$rho_uv_sd explicitly.

Usage

```
sample_rho_uv(  
  U_cube,  
  V_cube,  
  sigma_uv,  
  rho_current,  
  symmetric,  
  prior_mean = 0,  
  prior_sd = 1  
)
```

Arguments

U_cube	3D array of U positions (n x R x T)
V_cube	3D array of V positions (n x R x T)
sigma_uv	Innovation standard deviation
rho_current	Current value of rho
symmetric	Whether network is symmetric
prior_mean	Prior mean for rho (default 0)
prior_sd	Prior SD for rho (default 1)

Value

Updated rho value

sample_sigma_ab_cpp	<i>Sample innovation variance for dynamic additive effects</i>
---------------------	--

Description

Sample innovation variance for dynamic additive effects

Usage

```
sample_sigma_ab_cpp(  
  a_mat,  
  b_mat,  
  rho_ab,  
  symmetric,  
  prior_shape = 2,  
  prior_scale = 1  
)
```

Arguments

- | | |
|-------------|---|
| a_mat | Matrix of row effects (n x T) |
| b_mat | Matrix of column effects (n x T) |
| rho_ab | AR(1) parameter |
| symmetric | Whether the network is symmetric |
| prior_shape | Shape parameter for inverse gamma prior |
| prior_scale | Scale parameter for inverse gamma prior |

Value

Updated sigma_ab value

sample_sigma_beta_cpp *Sample the AR(1) innovation sigma for each dynamic block*

Description

Inverse-Gamma full conditional, one sigma per block.

Usage

```
sample_sigma_beta_cpp(
  beta_path,
  group_id,
  n_groups,
  Lambda_inv,
  rho_by_group,
  prior_shape,
  prior_scale
)
```

Arguments

beta_path	(T x p_dyn) matrix.
group_id	Length p_dyn integer vector (1-based) of block IDs.
n_groups	Number of distinct block IDs.
Lambda_inv	(p_dyn x p_dyn) inverse of the (full) Lambda scale.
rho_by_group	Length n_groups vector of current rho values.
prior_shape	Length n_groups vector of IG shape parameters.
prior_scale	Length n_groups vector of IG scale parameters.

Value

Length n_groups vector of new sigma values.

sample_sigma_G2 *Inverse-gamma posterior draw for sigma_G^2 given the FFBS path*

Description

Conjugate IG update on sigma_G^2 given the AR(1) innovations $\eta_t = g_t - \rho * g_{t-1}$, $t = 2..N$, plus the stationary density at $t = 1$. Default prior is IG(2, 1) on sigma_G^2.

Usage

```
sample_sigma_G2(  
  vecG_path,  
  rho_G,  
  prior_shape = 2,  
  prior_rate = 1,  
  s2_obs = 1,  
  v_cap_mult = 4  
)
```

Arguments

- s2_obs observation-noise variance (1 for probit/binary).
- v_cap_mult cap on the stationary G-state variance in units of s2_obs (default 4).

Details

Scale identification. The model identifies only the product $U_t G_t V_t'$, not G_t alone, so the overall scale of $\text{vec}(G_t)$ is free: left unchecked the chain finds a degenerate mode where σ_G^2 (and hence G_t) inflates by orders of magnitude while U, V collapse to compensate, leaving the linear predictor unchanged but the reported G_{cube} meaningless. Clamping ρ_G alone does not bound this because the stationary state variance is $\sigma_G^2 / (1 - \rho_G^2)$. We therefore cap the implied stationary variance at $v_{\text{cap_mult}} * s2_{\text{obs}}$ (a few observation-noise units), which forces the multiplicative scale onto U, V – where the regularising $N(0, s2)$ prior pins it – and keeps G_t on a scale comparable to a static- G fit. The cap is loose enough never to bind on a genuinely small-variation G_t .

sample_sigma_uv	<i>Sample innovation variance for dynamic latent factors</i>
-----------------	--

Description

Sample innovation variance for dynamic latent factors

Usage

```
sample_sigma_uv(U_cube, V_cube, rho_uv, symmetric)
```

Arguments

- U_cube 3D array of U positions (n x R x T)
- V_cube 3D array of V positions (n x R x T)
- rho_uv AR(1) parameter
- symmetric Whether network is symmetric

Value

Updated sigma_uv value

sampsonmonks

Sampson's monastery data

Description

Several dyadic variables measured on 18 members of a monastery.

Format

A socioarray whose dimensions represent nominators, nominees and relations. Each monk was asked to rank up to three other monks on a variety of positive and negative relations. A rank of three indicates the "highest" ranking for a particular relational variable. The relations like_m2 and like_m1 are evaluations of likeing at one and two timepoints previous to when the other relations were measured.

Source

Originally available at <http://moreno.ss.uci.edu/data.html#sampson> (site no longer accessible).

sheep

Sheep dominance data

Description

Number of dominance encounters between 28 female bighorn sheep. Cell (i,j) records the number of times sheep i dominated sheep j. From Hass (1991).

Format

A list consisting of the following:

- dom: a directed socioarray recording the number of dominance encounters.
- age: the age of each sheep in years.

Source

Originally available at <http://moreno.ss.uci.edu/data.html#sheep> (site no longer accessible).

simulate.ame

Simulate networks from a fitted AME model

Description

Generates multiple network realizations from a fitted AME model. This function performs conditional posterior predictive simulation: it draws from stored MCMC samples when they are available and uses posterior means for latent components that were not retained.

Unlike `print.ame`, which only displays fitted quantities, `simulate.ame` draws new networks from the posterior predictive distribution.

Usage

```
## S3 method for class 'ame'
simulate(
  object,
  nsim = 100,
  seed = NULL,
  newdata = NULL,
  burn_in = 0,
  thin = 1,
  return_latent = FALSE,
  ...
)
```

Arguments

<code>object</code>	fitted model object of class "ame"
<code>nsim</code>	number of networks to simulate (default: 100)
<code>seed</code>	random seed for reproducibility
<code>newdata</code>	optional list containing new covariate data: Xdyad dyadic covariates ($n \times n \times p$ array or $nA \times nB \times p$ for bipartite) Xrow row/sender covariates ($n \times p$ matrix or $nA \times p$ for bipartite) Xcol column/receiver covariates ($n \times p$ matrix or $nB \times p$ for bipartite) If NULL, uses covariates from original model fit
<code>burn_in</code>	number of initial MCMC samples to discard (default: 0, assumes burn-in already removed)
<code>thin</code>	thinning interval for MCMC samples (default: 1, use every sample)
<code>return_latent</code>	logical: return latent Z matrices in addition to Y? (default: FALSE)
<code>...</code>	additional arguments (not currently used)

Details

Model:

The AME model represents networks through a latent variable framework:

$$Y_{ij} \sim F(Z_{ij})$$

where F is the observation model (e.g., probit for binary) and Z is the latent network:

$$Z_{ij} = \beta^T x_{ij} + a_i + b_j + u_i^T v_j + \epsilon_{ij}$$

Components:

- β : regression coefficients for dyadic/nodal covariates
- a_i, b_j : additive sender and receiver random effects
- u_i, v_j : multiplicative latent factors (dimension R)
- ϵ_{ij} : dyadic random effects with correlation ρ

Simulation:

For each simulated network $k = 1, \dots, \text{nsim}$:

1. **Parameter draw:** Draw parameter set $\theta^{(k)}$ from MCMC chains:
 - Sample iteration s uniformly from stored MCMC samples
 - Extract $\beta^{(s)}$, variance components $(v_a^{(s)}, v_b^{(s)}, v_e^{(s)}, \rho^{(s)})$
2. **Random effects:** Sample new random effects from posterior distributions:
 - $a_i^{(k)} \sim N(0, v_a^{(s)})$ for $i = 1, \dots, n$ (row effects)
 - $b_j^{(k)} \sim N(0, v_b^{(s)})$ for $j = 1, \dots, m$ (column effects)
 - Fresh draws from the posterior variance carry random-effect uncertainty into the simulated networks
3. **Latent network:** Build expected latent positions:

$$E[Z_{ij}^{(k)}] = \beta^{(s)T} x_{ij} + a_i^{(k)} + b_j^{(k)} + \hat{u}_i^T \hat{v}_j$$

where $\hat{u}_i, \hat{v}_j$ are posterior mean latent factors

4. **Dyadic correlation:** Add correlated noise structure:

$$Z_{ij}^{(k)} = E[Z_{ij}^{(k)}] + \epsilon_{ij}^{(k)}$$

where ϵ has covariance structure:

$$\text{Cov}(\epsilon_{ij}, \epsilon_{ji}) = \rho^{(s)} v_e^{(s)}$$

$$\text{Var}(\epsilon_{ij}) = v_e^{(s)}$$

5. **Observation model:** Generate the observed network:

- Binary: $Y_{ij}^{(k)} = I(Z_{ij}^{(k)} > 0)$
- Normal: $Y_{ij}^{(k)} = Z_{ij}^{(k)}$

- Poisson: $Y_{ij}^{(k)} \sim \text{Poisson}(\exp(Z_{ij}^{(k)}))$
- Other families use appropriate link functions

Sources of uncertainty:

The simulation captures three types of uncertainty:

1. **Parameter uncertainty:** Different MCMC samples yield different $\beta, v_a, v_b, v_e, \rho$
2. **Random effect uncertainty:** Fresh draws from $N(0, v_a), N(0, v_b)$ for each simulation
3. **Dyadic uncertainty:** Correlated random noise ϵ_{ij}

The resulting simulations propagate uncertainty from the stored parameter draws and from fresh dyadic/random-effect draws. Latent components that were not stored as MCMC draws are held at their posterior means.

Latent-factor draws:

Multiplicative effects (U, V) use posterior means unless the fit retained compatible latent-factor draws. Storing full latent-factor chains can require substantial additional memory.

Symmetric Networks:

For symmetric networks, the model enforces $a_i = b_i$ and $u_i = v_i$, and the latent matrix Z is symmetrized before generating observations.

Value

A list with components:

Y list of nsim simulated networks in the same format as the original data

Z if return_latent=TRUE, list of nsim latent Z matrices

family the family of the model (binary, normal, etc.)

mode network mode (unipartite or bipartite)

Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

Examples

```
# Fit a model
data(YX_bin)
fit <- ame(YX_bin$Y, Xdyad = YX_bin$X, burn = 10, nscan = 100, odens = 1,
          family = "binary", verbose = FALSE)

# Simulate 10 networks from posterior
sims <- simulate(fit, nsim = 10)
```

simulate.ame_als	<i>Simulate networks from a fitted ame_als model</i>
------------------	--

Description

Draws `nsim` replicates of Y from the fitted ALS mean structure: μ , β , a , b , U , V , and the family-appropriate noise distribution. For directed unipartite normal and binary fits, reciprocal dyads use the fitted residual ρ . The returned object has class `"ame.sim"` so it is compatible with `plot_ppc_*`-style consumers (where applicable).

Usage

```
## S3 method for class 'ame_als'
simulate(object, nsim = 1, seed = NULL, ...)
```

Arguments

<code>object</code>	an <code>ame_als</code> fit.
<code>nsim</code>	integer; number of replicates to simulate (default 1).
<code>seed</code>	optional RNG seed.
<code>...</code>	ignored.

Details

ALS is a point estimator. `simulate.ame_als` holds μ , β , a , b , U , V at the point estimate and resamples the noise. For uncertainty over the parameters themselves, use [ame_als_bootstrap](#) (whose replicates each carry their own resampled Y) and combine those simulations.

Value

An object of class `"ame.sim"` with element Y – a list of `nsim` simulated outcome arrays (one matrix for a cross-section, one list-of-matrices per slice for a longitudinal fit).

simulate.lame	<i>Simulate longitudinal networks from a fitted LAME model</i>
---------------	--

Description

Generates multiple longitudinal network realizations from a fitted LAME (Longitudinal AME) model. This function performs conditional posterior predictive simulation for dynamic networks: it draws from stored MCMC samples when available and uses posterior means for latent components that were not retained.

Usage

```
## S3 method for class 'lame'
simulate(
  object,
  nsim = 100,
  seed = NULL,
  newdata = NULL,
  n_time = NULL,
  burn_in = 0,
  thin = 1,
  return_latent = FALSE,
  start_from = "posterior",
  ...
)
```

Arguments

object	fitted model object of class "lame"
nsim	number of network trajectories to simulate (default: 100)
seed	random seed for reproducibility
newdata	optional list containing new covariate data: Xdyad list of T dyadic covariate arrays (n x n x p or nA x nB x p) Xrow list of T row/sender covariate matrices (n x p or nA x p) Xcol list of T column/receiver covariate matrices (n x p or nB x p) If NULL, uses covariates from original model fit
n_time	number of time periods to simulate. If NULL, uses same as original data
burn_in	number of initial MCMC samples to discard (default: 0)
thin	thinning interval for MCMC samples (default: 1, use every sample)
return_latent	logical: return latent Z matrices in addition to Y? (default: FALSE)
start_from	character: how to initialize the simulation "posterior" start from posterior mean (default) "random" random initialization "data" use first time point from original data
...	additional arguments (not currently used)

Details**Mathematical Framework for Longitudinal Networks:**

The LAME model extends AME to multiple time periods T with potential temporal dependencies.

For each time $t = 1, \dots, T$:

$$Y_{ij,t} \sim F(Z_{ij,t})$$

where the latent network evolves as:

$$Z_{ij,t} = \beta^T x_{ij,t} + a_{i,t} + b_{j,t} + u_{i,t}^T v_{j,t} + \epsilon_{ij,t}$$

Temporal Dynamics:

LAME can incorporate three types of temporal dependencies:

1. **Static Effects:** Parameters constant over time

- $a_{i,t} = a_i, b_{j,t} = b_j$ for all t
- $u_{i,t} = u_i, v_{j,t} = v_j$ for all t

2. **Dynamic Additive Effects:** AR(1) process for random effects

$$a_{i,t} = \rho_{ab}a_{i,t-1} + \eta_{i,t}, \quad \eta_{i,t} \sim N(0, \sigma_a^2(1 - \rho_{ab}^2))$$

$$b_{j,t} = \rho_{ab}b_{j,t-1} + \xi_{j,t}, \quad \xi_{j,t} \sim N(0, \sigma_b^2(1 - \rho_{ab}^2))$$

where ρ_{ab} is the temporal correlation parameter

3. **Dynamic Multiplicative Effects:** AR(1) for latent factors

$$u_{i,t} = \rho_{uv}u_{i,t-1} + \omega_{i,t}$$

$$v_{j,t} = \rho_{uv}v_{j,t-1} + \psi_{j,t}$$

Uncertainty Quantification Process for Trajectories:

For each simulated trajectory $k = 1, \dots, \text{nsim}$:

Step 1: Parameter Sampling

- Draw MCMC iteration s uniformly from stored posterior samples
- Extract static parameters: $\beta^{(s)}$, variance components
- Extract temporal parameters if applicable: $\rho_{ab}^{(s)}, \rho_{uv}^{(s)}$

Step 2: Initialize at $t = 1$

Depending on `start_from` parameter:

- "posterior": Use posterior means as starting values
- "random": Draw from stationary distribution
- For additive effects: $a_{i,1}^{(k)} \sim N(0, \sigma_a^2)$
- For multiplicative effects: Initialize from prior

Step 3: Evolve Through Time

For each $t = 2, \dots, T$:

a) **Update Dynamic Effects** (if applicable):

$$a_{i,t}^{(k)} = \rho_{ab}^{(s)} a_{i,t-1}^{(k)} + \eta_{i,t}^{(k)}$$

where $\eta_{i,t}^{(k)} \sim N(0, \sigma_a^2(1 - [\rho_{ab}^{(s)}]^2))$

The innovation variance $\sigma_a^2(1 - \rho_{ab}^2)$ ensures stationarity

b) **Construct Latent Network:**

$$E[Z_{ij,t}^{(k)}] = \beta^{(s)T} x_{ij,t} + a_{i,t}^{(k)} + b_{j,t}^{(k)} + u_{i,t}^T v_{j,t}$$

c) **Add Dyadic Noise:**

$$Z_{ij,t}^{(k)} = E[Z_{ij,t}^{(k)}] + \epsilon_{ij,t}^{(k)}$$

with correlation structure preserved from AME model

d) **Generate Observations:** Apply appropriate link function based on family**Sources of Uncertainty in Longitudinal Context:**

1. **Cross-sectional uncertainty** (as in AME):
 - Parameter uncertainty from MCMC
 - Random effect variability
 - Dyadic noise
2. **Temporal uncertainty:**
 - Uncertainty in temporal correlation parameters ρ_{ab}, ρ_{uv}
 - Innovation noise in AR(1) processes
 - Propagation of uncertainty through time (compounds over periods)
3. **Initial condition uncertainty:**
 - Different starting values lead to different trajectories
 - Captured through start_from options

Interpretation of Multiple Trajectories:

Each simulated trajectory represents one possible evolution of the network conditional on the stored fit. Variation across trajectories captures:

- Model parameter uncertainty
- Stochastic variation in temporal evolution
- Accumulated uncertainty over time periods

The ensemble of trajectories provides prediction intervals that widen over time, reflecting increasing uncertainty in longer-term forecasts.

Special Considerations:

1. **Temporal Correlation:** Higher ρ values create smoother trajectories with more persistence
2. **Stationarity:** The AR(1) innovation variance is scaled to maintain stationary marginal distributions
3. **Missing Time Points:** If simulating beyond observed data ($n_time > T_observed$), covariates are recycled or set to zero with appropriate warnings

Limitations:

As with simulate.ame, multiplicative effects use posterior means unless the fit retained compatible latent-factor draws. Storing complete MCMC chains for $u_{i,t}, v_{j,t}$ at all time points is memory-intensive for large networks and long time series.

Value

A list with components:

Y list of nsim simulated longitudinal network trajectories, each element is a list of T networks

Z if return_latent=TRUE, list of nsim latent Z trajectories

family the family of the model (binary, normal, etc.)

mode network mode (unipartite or bipartite)

n_time number of time periods

Author(s)

Shahryar Minhas

Examples

```
# Create simple longitudinal network data
set.seed(1)
n <- 10
nms <- paste0("n", 1:n)
Y_list <- list(
  matrix(rnorm(n * n), n, n, dimnames = list(nms, nms)),
  matrix(rnorm(n * n), n, n, dimnames = list(nms, nms))
)
diag(Y_list[[1]]) <- diag(Y_list[[2]]) <- NA
fit <- lame(Y_list, family = "normal",
            nscan = 50, burn = 10, odens = 1, verbose = FALSE, plot = FALSE)

# Simulate 10 network trajectories from posterior
sims <- simulate(fit, nsim = 10)
```

simulate_posterior	<i>Simulate posterior distributions from fitted AME model</i>
--------------------	---

Description

Simulate posterior distributions from fitted AME model

Usage

```
simulate_posterior(
  fit,
  component = c("UV", "ab", "beta", "Y"),
  n_samples = 100,
  use_full_cov = FALSE,
  seed = NULL
)
```

Arguments

fit	Fitted ame model object
component	Character; which component to simulate: "UV", "ab", "beta", "Y"
n_samples	Number of posterior samples to generate
use_full_cov	For UV component, whether to use empirical variance scaling (default FALSE)
seed	Random seed for reproducibility

Details

This function can simulate posterior distributions even when they weren't saved during MCMC, by using the posterior means and variance components.

For more accurate posteriors, use `posterior_options()` during model fitting to save the actual MCMC samples.

Value

Array or matrix of posterior samples

Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

Examples

```
# Fit a model with multiplicative effects
data(YX_nrm)
fit <- ame(YX_nrm$Y, Xdyad = YX_nrm$X, R = 2,
           nscan = 100, burn = 10, odens = 1, verbose = FALSE)

# Get posterior samples of regression coefficients
beta_post <- simulate_posterior(fit, "beta", n_samples = 50)
```

simY_bin

Simulate a network, i.e. a binary relational matrix

Description

Simulates a network, i.e. a binary relational matrix

Usage

```
simY_bin(EZ, rho)
```

Arguments

EZ	square matrix giving the expected value of the latent Z matrix
rho	dyadic correlation

Value

a square binary matrix

Author(s)

Peter Hoff

simY_frn	<i>Simulate an relational matrix based on a fixed rank nomination scheme</i>
----------	--

Description

Simulate an relational matrix based on a fixed rank nomination scheme

Usage

```
simY_frn(EZ, rho, odmax, Y0)
```

Arguments

EZ	a square matrix giving the expected value of the latent Z matrix
rho	dyadic correlation
odmax	a scalar or vector giving the maximum number of nominations for each node
Y0	a square matrix identifying where missing values should be maintained

Value

a square matrix, where higher values represent stronger relationships

Author(s)

Peter Hoff

simY_nrm

Simulate a normal relational matrix

Description

Simulates a normal relational matrix

Usage

```
simY_nrm(EY, rho, s2)
```

Arguments

EY	square matrix giving the expected value of the relational matrix
rho	dyadic correlation
s2	dyadic variance

Value

a square matrix

Author(s)

Peter Hoff

simY_ord

Simulate an ordinal relational matrix

Description

Simulates an ordinal relational matrix having a particular marginal distribution

Usage

```
simY_ord(EZ, rho, Y)
```

Arguments

EZ	square matrix giving the expected value of the latent Z matrix
rho	scalar giving the within-dyad correlation
Y	ordinal relational data matrix

Value

a square matrix

Author(s)

Peter Hoff

simY_pois*Simulate a Poisson relational matrix*

Description

Simulates a relational matrix from a Poisson distribution given the log mean values

Usage

simY_pois(EZ)

Arguments

EZ square matrix giving the log expected values of the relational matrix

Value

a square matrix of counts

Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

simZ*Simulate Z given its expectation and covariance*

Description

Simulate Z given its expectation and covariance

Usage

simZ(EZ, rho, s2 = 1)

Arguments

EZ	expected value of Z
rho	dyadic correlation
s2	dyadic variance

Value

a simulated value of Z

Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

sm2el

Sociomatrix to edgelist

Description

Construction of an edgelist from a sociomatrix

Usage

```
sm2el(sm,directed=TRUE)
```

Arguments

sm a sociomatrix with possibly valued relations
directed if TRUE, only use the upper triangular part of the matrix to enumerate edges

Value

an edgelist

Author(s)

Peter Hoff

Examples

```
Y<-matrix(rpois(10*10,.5),10,10) ; diag(Y)<-NA
E<-sm2el(Y)
el2sm(E) - Y
```

snap_category_summary *Summarize snap indices by actor category*

Description

Summarize snap indices by actor category

Usage

```
snap_category_summary(fit, groups, years = NULL, side = c("u", "v"))
```

Arguments

fit	a lame fit with snap-shift MCMC output, or a lame_snap_als fit. MCMC fits should be run with retained snap draws for posterior uncertainty; ALS fits contribute their snap_prob scores as one score row.
groups	a named list mapping group names to actor names/indices, or a named vector whose values are group labels and whose names are actors.
years	optional year/period names or indices. Default uses every period.
side	"u" for sender/row-side snap indicators or "v" for receiver/column-side indicators.

Value

A data frame with one row per group-year.

snap_index_draws	<i>Extract posterior draws of snap indices</i>
------------------	--

Description

Computes draw-level averages of MCMC snap indicators over selected actors and years. The result is useful for system-level rupture indices and focal-actor rupture indices. Fits should be run with keep_snap_draws = "draws" for posterior uncertainty. If only snap_prob is present, the function returns a single score row and warns that intervals cannot be read as posterior intervals.

Usage

```
snap_index_draws(fit, actors = NULL, years = NULL, side = c("u", "v"))
```

Arguments

fit	a lame fit with snap-shift MCMC output, or a lame_snap_als fit. MCMC fits should be run with retained snap draws for posterior uncertainty; ALS fits contribute their snap_prob scores as one score row.
actors	optional actor names or indices. Default uses every actor on the selected side.
years	optional year/period names or indices. Default uses every period.
side	"u" for sender/row-side snap indicators or "v" for receiver/column-side indicators.

Value

A data frame with columns draw, year, side, n_actors, and snap_index.

snap_index_summary	<i>Summarize posterior snap indices</i>
--------------------	---

Description

Summarize posterior snap indices

Usage

```
snap_index_summary(
  fit,
  actors = NULL,
  years = NULL,
  side = c("u", "v"),
  probs = c(0.025, 0.1, 0.5, 0.9, 0.975)
)
```

Arguments

fit	a lame fit with snap-shift MCMC output, or a lame_snap_als fit. MCMC fits should be run with retained snap draws for posterior uncertainty; ALS fits contribute their snap_prob scores as one score row.
actors	optional actor names or indices. Default uses every actor on the selected side.
years	optional year/period names or indices. Default uses every period.
side	"u" for sender/row-side snap indicators or "v" for receiver/column-side indicators.
probs	numeric quantiles to report.

Value

A data frame with one row per selected year.

snap_rank_summary	<i>Summarize posterior rank uncertainty for snap years</i>
-------------------	--

Description

Ranks year-level snap indices within each retained draw, with rank 1 assigned to the highest snap index.

Usage

```
snap_rank_summary(fit, actors = NULL, years = NULL, side = c("u", "v"))
```


Arguments

fit	a lame fit with snap-shift MCMC output, or a lame_snap_als fit. MCMC fits should be run with retained snap draws for posterior uncertainty; ALS fits contribute their snap_prob scores as one score row.
actors	optional actor names or indices. Default uses every actor on the selected side.
years	optional year/period names or indices. Default uses every period.
side	"u" for sender/row-side snap indicators or "v" for receiver/column-side indicators.

Value

A data frame with year-level index means and rank probabilities.

summary.ame	<i>Summary of an AME object</i>
-------------	---------------------------------

Description

Summarizes a fitted AME (Additive and Multiplicative Effects) model, including parameter estimates, standard errors, credible intervals, and model diagnostics.

Usage

```
## S3 method for class 'ame'  
summary(object, ...)
```

Arguments

object	an object of class "ame", typically the result of fitting an AME model using the <code>ame</code> function
...	additional parameters (currently not used)

Details

The summary includes:

Regression coefficients Posterior means, posterior standard deviations, z-values, approximate p-values, and 95% credible intervals for dyadic, sender, and receiver covariates. Note: the z-values are computed as posterior mean / posterior SD, and the p-values are derived from a normal approximation. These are convenient screening statistics but are not formal frequentist test statistics. For rigorous inference, use the credible intervals or examine the full posterior via the BETA matrix directly.

Variance components Estimates and standard errors for:

- va** Variance of additive sender/row effects (asymmetric networks)
- cab** Covariance between sender and receiver effects

- vb** Variance of additive receiver/column effects (asymmetric networks)
- rho** Dyadic correlation (reciprocity in directed networks)
- ve** Residual variance

For symmetric networks, only va and ve are estimated.

Value

A list of class "summary.ame" containing:

call	The original function call
beta	Matrix of regression coefficient estimates and statistics
variance	Matrix of variance component estimates

Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

See Also

[ame](#), [print.summary.ame](#)

summary.ame.sim	<i>Summary method for AME simulations</i>
-----------------	---

Description

Summary method for AME simulations

Usage

```
## S3 method for class 'ame.sim'  
summary(object, ...)
```

Arguments

object	simulation object of class "ame.sim"
...	additional arguments (not used)

Value

summary statistics invisibly

summary.ame_als	<i>Summarize an ame_als object</i>
-----------------	------------------------------------

Description

Summarize an ame_als object

Usage

```
## S3 method for class 'ame_als'  
summary(object, ...)
```

Arguments

object	an ame_als object.
...	ignored.

Value

A list of class "summary.ame_als", printed as a table.

summary.boot_ame	<i>Summarize bootstrap results for a fast AME fit</i>
------------------	---

Description

Summarize bootstrap results for a fast AME fit

Usage

```
## S3 method for class 'boot_ame'  
summary(object, ...)  
  
## S3 method for class 'summary.boot_ame'  
print(x, ...)
```

Arguments

object	a boot_ame object.
...	ignored.
x	a summary.boot_ame object.

Value

An object of class "summary.boot_ame", printed as a set of tables.

summary.lame

*Summary of a LAME object***Description**

Summarizes a fitted LAME (Longitudinal Additive and Multiplicative Effects) model, including parameter estimates, standard errors, credible intervals, and model diagnostics.

Usage

```
## S3 method for class 'lame'
summary(object, ...)
```

Arguments

object an object of class "lame", typically the result of fitting a longitudinal AME model using the lame function

... additional parameters (currently not used)

Details

The summary includes:

Regression coefficients Posterior means, posterior standard deviations, z-values, approximate p-values, and 95% credible intervals for dyadic, sender, and receiver covariates. Note: the z-values are computed as posterior mean / posterior SD, and the p-values are derived from a normal approximation. These are convenient screening statistics but are not formal frequentist test statistics. For rigorous inference, use the credible intervals or examine the full posterior via the BETA matrix directly.

Variance components Estimates and standard errors for:

va Variance of additive sender/row effects

cab Covariance between sender and receiver effects

vb Variance of additive receiver/column effects

rho Dyadic correlation (reciprocity)

ve Residual variance

Dynamic coefficients per period Only printed when the fit was produced with dynamic_beta on at least one coefficient. The table has one row per coefficient with columns:

Mean average of the per-period posterior means across t

Min, Max smallest and largest per-period posterior mean

Drift Max - Min: the absolute range of the per-period posterior means, in coefficient units

Drift_pct $100 * \text{Drift} / |\text{Mean}|$, the drift as a percentage of the average level. Reported as NA when the time-average is near zero (within 5\ range), because a trajectory that crosses zero makes the percentage explode; read Drift in that case

Dynamic "Y" if the coefficient was flagged as dynamic, "N" if it was held static

The block also prints the per-block AR(1) hyperparameters (rho_beta = ...). For per-period credible intervals use [confint.lame](#).

Value

A list of class "summary.lame" containing:

call	The original function call
beta	Matrix of regression coefficient estimates and statistics
variance	Matrix of variance component estimates
n.periods	Number of time periods in the longitudinal data

Author(s)

Peter Hoff, Cassy Dorff, Shahryar Minhas

See Also

[lame](#), [print.summary.lame](#)

summary.lame.sim	<i>Summary method for LAME simulations</i>
------------------	--

Description

Summary method for LAME simulations

Usage

```
## S3 method for class 'lame.sim'  
summary(object, ...)
```

Arguments

object	simulation object of class "lame.sim"
...	additional arguments (not used)

Value

summary statistics

tidy	<i>S3 generic for tidy</i>
------	----------------------------

Description

Light-weight fallback generic so that calls of the form `tidy(fit)` dispatch through R's S3 system even when the **broom** or **generics** packages are not loaded. When either is loaded, its generic resolves first; this generic only fires for bare-namespace use.

Usage

```
tidy(x, ...)
```

Arguments

<code>x</code>	An object to tidy.
<code>...</code>	Passed to the relevant method.

Value

A data frame; method-specific schema.

tidy.ame	<i>Tidy method for fitted ame / lame objects</i>
----------	--

Description

Returns a data frame with one row per estimated coefficient, compatible with the **broom** idiom. For dynamic_beta fits (3-D BETA), returns one row per coefficient *per period* with a period column. Standard errors are posterior standard deviations; statistic is estimate / std.error.

Usage

```
## S3 method for class 'ame'
tidy(x, conf.int = TRUE, conf.level = 0.95, ...)

## S3 method for class 'lame'
tidy(x, conf.int = TRUE, conf.level = 0.95, ...)
```

Arguments

<code>x</code>	A fitted ame / lame object.
<code>conf.int</code>	Logical; include 95% (conf.low, conf.high). Default TRUE.
<code>conf.level</code>	Confidence level for the interval. Default 0.95.
<code>...</code>	Ignored.

Details

Note on p.value. This column is included for **broom** compatibility but is *not* a classical test. It is a two-sided Normal approximation based on the posterior mean and marginal posterior standard deviation, matching the calculation in `summary(fit)`. Use it as a compact signal that the marginal posterior is far from zero, and report it alongside the `conf.low` / `conf.high` credible interval. When sign certainty matters, compute it directly from `x$BETA`, for example `mean(sign(BETA) == sign(mean(BETA)))`.

Loaded as an S3 method against `generics::tidy` when the **generics** package is available; works as `tidy(fit)` either way once **broom** is loaded.

Value

Data frame with columns `term`, `estimate`, `std.error`, `statistic`, `p.value`, `conf.low`, `conf.high`, and (for `dynamic_beta` fits) `period`.

Examples

```
data(YX_bin_list)
fit <- lame(YX_bin_list$Y, YX_bin_list$X, family = "binary", R = 0,
           nscan = 100, burn = 20, odens = 5, verbose = FALSE)
tidy(fit)
```

tidy.ame_als

Tidy method for fitted ame_als / lame_als objects

Description

Returns a data frame with one row per regression coefficient, compatible with the **broom** idiom, so that ALS fits compose with **modelsummary** / **kableExtra** pipelines next to MCMC fits. Standard errors come from the sandwich covariance (`vcov.ame_als`) by default, or from the bootstrap object attached to `x$bootstrap` when present (preferred, fully propagated). `statistic` is `estimate / std.error`; `p.value` is the Normal-approximation two-sided tail $2(1 - \Phi(|z|))$ from the bootstrap or sandwich standard error. It is a Wald-style summary for the point estimator, not a posterior probability.

Usage

```
## S3 method for class 'ame_als'
tidy(x, conf.int = TRUE, conf.level = 0.95, ...)

## S3 method for class 'lame_als'
tidy(x, conf.int = TRUE, conf.level = 0.95, ...)
```

Arguments

x	A fitted ame_als / lame_als object.
conf.int	Logical; include conf.low / conf.high columns. Default TRUE.
conf.level	Confidence level. Default 0.95.
...	Passed to <code>vcov.ame_als</code> (e.g. cluster = "dyad").

Details

Only the intercept and dyadic-covariate coefficients are returned, matching `coef(fit)` on the sandwich-covered subset. Additive (a, b), multiplicative (U, V), and node-covariate parameters are not included; use `ame_als_bootstrap` and inspect the bootstrap object directly if you need them.

Value

Data frame with columns term, estimate, std.error, statistic, p.value, conf.low, conf.high, plus a se_source column recording "bootstrap" or "sandwich".

Examples

```
data(YX_bin_list)
Y1 <- 1 * (YX_bin_list$Y[[1]] > 0); diag(Y1) <- NA
fit <- ame_als(Y = Y1, Xdyad = YX_bin_list$X[[1]],
              family = "binary", R = 1, verbose = FALSE)
tidy(fit)
```

tidy.boot_ame	<i>Tidy method for a standalone bootstrap object (boot_ame)</i>
---------------	---

Description

`ame_als_bootstrap()` returns an object of class "boot_ame" (not "ame_als"); this tidy method exposes the bootstrap estimates as a broom-style data frame so the standalone object composes with **modelsummary** the same way an embedded `ame_als(..., bootstrap = N)` fit does.

Usage

```
## S3 method for class 'boot_ame'
tidy(x, conf.level = 0.95, ...)
```

Arguments

x	A boot_ame object.
conf.level	Confidence level. Default 0.95.
...	Ignored.

Value

Data frame with columns term, estimate, std.error, statistic, p.value, conf.low, conf.high, se_source.

trace_plot	<i>MCMC trace plots and density plots for AME/LAME model parameters</i>
------------	---

Description

Creates diagnostic plots for Markov Chain Monte Carlo (MCMC) samples from AME or LAME models. Displays trace plots to assess convergence and mixing, alongside density plots to visualize posterior distributions.

Usage

```
trace_plot(
  fit,
  params = c("all", "beta", "variance"),
  include = NULL,
  exclude = NULL,
  ncol = 3,
  nrow = NULL,
  burn.in = 0,
  thin = 1,
  title = NULL
)
```

Arguments

fit	An object of class "ame" or "lame" containing MCMC samples
params	Character vector specifying which parameters to plot: "beta" for regression coefficients, "variance" for variance components, or "all" (default) for both
include	Character vector of specific parameter names to include. Raw variance-component names ("va", "ve", "rho", ...) and their display labels ("Error Variance", ...) are both accepted. For dynamic_beta fits, per-period traces are named like "x_dyad[t1]"; supplying the base name (e.g. "x_dyad") selects all of its periods
exclude	Character vector of specific parameter names to exclude. Base names match all per-period traces, as with include
ncol	Number of columns for plot layout (default 3)
nrow	Number of rows for plot layout (default NULL, determined automatically)
burn.in	Number of initial iterations to exclude as burn-in when calculating statistics (default 0, assumes burn-in already removed)
thin	Thinning interval for display (default 1, no thinning)
title	Optional title for the plot

Details

This function produces two types of diagnostic plots:

Trace plots Show the evolution of parameter values across MCMC iterations. Good mixing is indicated by rapid exploration of the parameter space with no trends or stuck periods.

Density plots Show the posterior distribution of parameters. Multiple modes may indicate identification issues or convergence problems.

The plots help diagnose:

- Convergence: Has the chain reached the stationary distribution?
- Mixing: Is the chain exploring the parameter space efficiently?
- Autocorrelation: Are successive samples highly correlated?

Parameters displayed include:

- Regression coefficients (beta)
- Variance components (va, vb, cab, rho, ve)

Value

A ggplot2 object that can be further customized

Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

Examples

```
# Fit an AME model
data(YX_nrm)
fit <- ame(YX_nrm$Y, Xdyad = YX_nrm$X,
           nscan = 100, burn = 10, odens = 1, verbose = FALSE)

# Basic trace plots for all parameters
trace_plot(fit)

# Only regression coefficients
trace_plot(fit, params = "beta")

# Only variance components
trace_plot(fit, params = "variance")
```

update.ame	<i>Update an AME / LAME fit</i>
------------	---------------------------------

Description

S3 method for `update` that re-fits the model with modified arguments. Reuses the original call recorded in `fit$call`. If the fit was produced with `freeze_call = TRUE`, the data snapshot on `fit$data_snapshot` is used in place of looking up names in the caller's environment.

Usage

```
## S3 method for class 'ame'
update(object, ..., evaluate = TRUE)

## S3 method for class 'lame'
update(object, ..., evaluate = TRUE)
```

Arguments

<code>object</code>	A fitted ame or lame object.
<code>...</code>	Named arguments to overwrite in the original call (e.g. <code>nscan = 5000</code> , <code>dynamic_beta = TRUE</code> , <code>R = 2</code>).
<code>evaluate</code>	Logical: if TRUE (default), evaluate the updated call and return the new fit; if FALSE, return the unevaluated call.

Value

A new fitted object, or (when `evaluate = FALSE`) the modified call.

Examples

```
data(YX_bin_list)
fit <- lame(YX_bin_list$Y, YX_bin_list$X, family = "binary",
            burn = 5, nscan = 20, odens = 1, verbose = FALSE)
# toggle dynamic_beta on without rewriting the whole call
fit_dyn <- update(fit, dynamic_beta = "dyad")
dim(fit_dyn$BETA) # 3-D now
```

update.ame_als	<i>Update an ame_als / lame_als fit</i>
----------------	---

Description

S3 method for [update](#) that re-fits an ALS fit with modified arguments. Two routes:

- if ... contains only the warm-start refit knobs (`Y_new`, `X_new`, `Z_new`, `max_iter`, `tol`, `verbose`), it delegates to [ame_als_refit](#) for a fast warm-started refit;
- otherwise (e.g. changing `R`, `family`, `lambda`, `bootstrap`) it re-evaluates the original object's call with the overrides, matching the [update.ame](#) semantics on the MCMC side.

The split exists because `ame_als_refit()` is a genuinely warm-started single-fit refit (faster, narrower argument set), while changing `R` / `family` requires a cold-start refit through [ame_als](#).

Usage

```
## S3 method for class 'ame_als'
update(object, ..., evaluate = TRUE)
```

```
## S3 method for class 'lame_als'
update(object, ..., evaluate = TRUE)
```

Arguments

<code>object</code>	A fitted <code>ame_als</code> / <code>lame_als</code> object.
<code>...</code>	Named arguments. See ame_als_refit for the warm-start argument list and ame_als for the cold-start argument list.
<code>evaluate</code>	Logical: if <code>TRUE</code> (default), evaluate the updated call and return the new fit; if <code>FALSE</code> , return the unevaluated call (cold-start path only).

Value

A new fitted `ame_als` object, or (when `evaluate = FALSE` on the cold-start path) the modified call.

Examples

```
Y <- matrix(rnorm(400), 20, 20); diag(Y) <- NA
fit <- ame_als(Y, R = 1, family = "normal", verbose = FALSE)
# warm-start refit with the same arguments (fast)
fit_w <- update(fit, max_iter = 50)
# cold-start refit with a different R (full restart)
fit_R2 <- update(fit, R = 2)
```

update_variances_bipartite

Update variance parameters for bipartite

Description

Update variance parameters for bipartite

Usage

```
update_variances_bipartite(
  a,
  b,
  eta0_a = 2,
  eta0_b = 2,
  Sab0_aa = 1,
  Sab0_bb = 1
)
```

Value

List with components sigma2_a and sigma2_b

uv_plot

Visualize multiplicative effects (latent factors) from AME models

Description

Creates a two-dimensional visualization of the multiplicative effects (U and V) from an AME or LAME model. These latent factors capture network structure beyond what is explained by covariates and additive effects, including clustering, transitivity, and other higher-order dependencies.

Usage

```
uv_plot(
  fit = NULL,
  Y = NULL,
  U = NULL,
  V = NULL,
  row.names = NULL,
  col.names = NULL,
  layout = c("circle", "biplot"),
  vscale = 0.8,
  show.edges = FALSE,
  edge.alpha = 0.3,
```

```

node.size = "magnitude",
label.nodes = TRUE,
label.size = 3,
show.usernames = NULL,
sender.color = "darkred",
receiver.color = "darkblue",
colors = NULL,
title = NULL,
time_point = NULL,
plot_type = c("snapshot", "trajectory", "faceted"),
show_arrows = TRUE,
highlight = NULL
)

```

Arguments

<code>fit</code>	An object of class "ame" or "lame" containing multiplicative effects, or a network matrix <code>Y</code> if <code>U</code> and <code>V</code> are provided separately
<code>Y</code>	Network matrix (only needed if <code>fit</code> is not provided)
<code>U</code>	Matrix of sender latent factors (extracted from <code>fit</code> if not provided)
<code>V</code>	Matrix of receiver latent factors (extracted from <code>fit</code> if not provided)
<code>row.names</code>	Names for row nodes (defaults to rownames of <code>Y</code> or <code>U</code>)
<code>col.names</code>	Names for column nodes (defaults to colnames of <code>Y</code> or <code>V</code>)
<code>layout</code>	Character string specifying layout: "circle" (default) or "biplot"
<code>vscale</code>	Scaling factor for <code>V</code> positions relative to <code>U</code> (default 0.8)
<code>show.edges</code>	Logical; if TRUE, show network edges (default FALSE)
<code>edge.alpha</code>	Transparency for edges (default 0.3)
<code>node.size</code>	Size of nodes, or "degree" to scale by degree (default 3)
<code>label.nodes</code>	Logical; if TRUE, show node labels (default TRUE)
<code>label.size</code>	Size of node labels (default 3)
<code>show.usernames</code>	Integer: number of top-degree nodes to label, or NULL for default behavior
<code>sender.color</code>	Color for sender/row nodes (default "darkred")
<code>receiver.color</code>	Color for receiver/column nodes (default "darkblue")
<code>colors</code>	Optional vector of colors for nodes (e.g., for communities)
<code>title</code>	Optional title for the plot
<code>time_point</code>	For dynamic UV, which time point to plot (default: last). Can be numeric index or "average" for time-averaged positions
<code>plot_type</code>	For dynamic UV: "snapshot" (single time), "trajectory" (evolution), "faceted" (grid of time points). For static UV, this is ignored.
<code>show_arrows</code>	For trajectory plots, whether to show directional arrows
<code>highlight</code>	Optional character vector of actor names to highlight on a <code>plot_type = "trajectory"</code> plot. Highlighted actors are coloured with the colour-blind-safe Okabe-Ito palette; all other actors are rendered in grey at lower alpha. Ignored for static or snapshot plots.

Details

The multiplicative effects in AME models provide a low-rank representation of network structure through latent factors:

U matrix Sender-specific latent positions (row factors)

V matrix Receiver-specific latent positions (column factors)

UV' product Captures dyad-specific effects beyond additive terms

The visualization can show:

Circular layout Default layout placing nodes on a circle with latent positions shown as deviations

Biplot layout Shows U and V positions directly in latent space

Network overlay Optional display of actual network ties

Interpretation:

- Nodes close together in latent space tend to have similar connection patterns
- The distance between sender position (U) and receiver position (V) relates to the likelihood of a tie
- Clustering in the latent space indicates community structure

Value

A ggplot2 object that can be further customized

Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

Examples

```
# Fit an AME model with multiplicative effects
data(YX_nrm)
fit <- ame(YX_nrm$Y, Xdyad = YX_nrm$X, R = 2,
          nscan = 100, burn = 10, odens = 1, verbose = FALSE)

# Basic visualization
uv_plot(fit)

# Use biplot layout
uv_plot(fit, layout = "biplot")
```

vcov.ame

*Posterior covariance of AME model coefficients***Description**

Returns the posterior covariance matrix of regression coefficients.

Usage

```
## S3 method for class 'ame'
vcov(object, ...)

## S3 method for class 'lame'
vcov(object, ...)
```

Arguments

object	fitted AME model (class "ame")
...	additional arguments (ignored)

Value

p x p covariance matrix of posterior BETA draws

vcov.ame_als

*Sandwich covariance for the regression coefficients of a fast AME fit***Description**

Returns a heteroskedasticity-robust (optionally dyad-clustered) sandwich covariance matrix for the intercept and *dyadic*-covariate coefficients of an [ame_als](#) fit. This is a fast analytic alternative to the bootstrap for those coefficients.

Usage

```
## S3 method for class 'ame_als'
vcov(object, cluster = c("dyad", "none"), ...)
```

Arguments

object	an ame_als fit.
cluster	"dyad" (default) for a dyad-clustered robust meat, or "none" for an HC0 (heteroskedasticity-only) meat.
...	ignored.

Details

The estimate is the conditional sandwich $B^{-1}MB^{-1}$ with bread $B = D'WD$ (D the observed intercept + dyadic-covariate design, W the fit's observation weights) and meat M the heteroskedasticity-robust (`cluster = "none"`, an HC0 meat) or dyad-clustered (`cluster = "dyad"`, the default) outer product of the weighted score contributions $w_\ell e_\ell d_\ell$. For a normal or transform fit the weights are unit, so this reduces to the ordinary $D'D$ sandwich; for an IRLS fit it uses the final IRLS weights, matching the estimating equation the fit actually solved. Dyad clustering pools the score across (i, j) , (j, i) and time, so it reflects dyadic dependence (reciprocity, repeated observation).

It is **conditional**: the additive effects `a`, `b` and the multiplicative term are held fixed, so it omits their estimation uncertainty and is anti-conservative. Node-covariate, additive and multiplicative standard errors are not returned – use [ame_als_bootstrap](#) for those and for fully-propagated inference.

Value

A covariance matrix for `c(intercept, dyadic coefficients)`, with matching row/column names.

See Also

[ame_als_bootstrap](#) for bootstrap uncertainty covering all parameters.

vcov.boot_ame

Bootstrap covariance of the regression coefficients

Description

Returns the sample covariance matrix of the bootstrap replicate intercept + regression coefficients of a `boot_ame` object – the covariance underlying the reported standard errors and confidence intervals.

Usage

```
## S3 method for class 'boot_ame'
vcov(object, ...)
```

Arguments

<code>object</code>	a <code>boot_ame</code> object.
<code>...</code>	ignored.

Value

A covariance matrix over the intercept and regression coefficients.

vignette_data

*TIES sanctions data for vignettes***Description**

Longitudinal directed binary network of international economic sanctions among 35 countries across four years (1993, 1994, 1995, 2000), derived from the Threat and Imposition of Sanctions (TIES) dataset (Morgan et al. 2014). Entry $y_{ij,t} = 1$ means country i imposed sanctions on country j in year t . Network density is approximately 2%

Usage

```
data(vignette_data)
```

Format

Four objects:

Y List of 4 binary adjacency matrices (35 x 35), one per year.

Xdyad List of 4 arrays (35 x 35 x 2) of dyadic covariates: distance (geographic) and shared_igos (shared IGO memberships).

Xrow List of 4 matrices (35 x 2) of sender covariates: log_gdp and log_pop.

Xcol List of 4 matrices (35 x 2) of receiver covariates: log_gdp and log_pop.

Details

When loaded via `data(vignette_data)`, the following objects are placed in the calling environment: `Y`, `Xdyad`, `Xrow`, `Xcol`.

References

Morgan, T. Clifton, Bapat, N., & Kobayashi, Y. (2014). Threat and Imposition of Economic Sanctions 1945–2005. *Conflict Management and Peace Science*, 31(5), 541–558.

Examples

```
data(vignette_data)
cat("Countries:", nrow(Y[[1]]), "\n")
cat("Time periods:", length(Y), "\n")
```

waic.ame	<i>WAIC for AME / LAME fits</i>
----------	---------------------------------

Description

S3 method for `waic` that uses the stored `fit$log_lik`.

Usage

```
## S3 method for class 'ame'  
waic(x, ...)  
  
## S3 method for class 'lame'  
waic(x, ...)  
  
## S3 method for class 'ame_als'  
waic(x, ...)
```

Arguments

- `x` A fitted `ame` or `lame` object with `$log_lik`.
- `...` Additional arguments forwarded to `loo::waic.matrix`.

Value

A `waic` object.

Xbeta	<i>Linear combinations of submatrices of an array</i>
-------	---

Description

Computes a matrix of expected values based on an array `X` of predictors and a vector `beta` of regression coefficients.

Usage

```
Xbeta(X, beta)
```

Arguments

- `X` an `n` by `n` by `p` array
- `beta` a `p` by 1 vector

Value

An n by n matrix

Author(s)

Cassy Dorff, Shahryar Minhas, Tosin Salau

<code>Xbeta_bip_cpp</code>	<i>Compute Xbeta product for bipartite networks</i>
----------------------------	---

Description

Computes $\sum_k \beta_k * X_k$ for a single time slice

Usage

```
Xbeta_bip_cpp(X, beta)
```

Arguments

- `X` 3D array (nA x nB x p) of covariates for one time period
- `beta` Coefficient vector of length p

Value

nA x nB matrix

<code>Xcol</code>	<i>Column covariates</i>
-------------------	--------------------------

Description

Column covariates loaded by `data(vignette_data)`. See [vignette_data](#) for full details.

Format

A list of matrices of column covariates

See Also

[vignette_data](#)

Xdyad	<i>Dyadic covariates</i>
-------	--------------------------

Description

Dyadic covariates loaded by `data(vignette_data)`. See [vignette_data](#) for full details.

Format

A list of arrays of dyadic covariates

See Also

[vignette_data](#)

Xrow	<i>Row covariates</i>
------	-----------------------

Description

Row covariates loaded by `data(vignette_data)`. See [vignette_data](#) for full details.

Format

A list of matrices of row covariates

See Also

[vignette_data](#)

Y	<i>Relational matrix</i>
---	--------------------------

Description

Relational matrix loaded by `data(vignette_data)`. See [vignette_data](#) for full details.

Format

A list of square binary adjacency matrices

See Also

[vignette_data](#)

YX_bin	<i>binary relational data and covariates</i>
--------	--

Description

a synthetic dataset that includes binary relational data as well as information on eight covariates

Usage

```
data(YX_bin)
```

Format

The format is: List of 2 \$ Y: num [1:100, 1:100] NA 0 0 0 0 0 0 0 1 ... \$ X: num [1:100, 1:100, 1:8] 1 1 1 1 1 1 1 1 1 1 attr(*, "dimnames")=List of 3\$: NULL\$: NULL\$: chr [1:8] "intercept" "rgpa" "rsmoke" "cgpa" ...

Examples

```
data(YX_bin)
gof_stats(YX_bin$Y)
```

YX_bin_list	<i>Synthetic longitudinal binary relational data, list-form (latent-scale)</i>
-------------	--

Description

The list-form sibling of [YX_bin_long](#): same synthetic 4-period 50-actor panel reshaped from arrays to lists. The shipped Y entries hold the *latent probit-scale predictor* (range roughly -20 to 17), not 0/1 ties. To recover the binary tie indicator the dataset name implies, threshold at zero, e.g. `Y_bin <- lapply(YX_bin_list$Y, function(Yt) 1 * (Yt > 0))`. If passed unthresholded to `lame(..., family = "binary")` the fit will warn and silently apply the same $Y > 0$ threshold.

Format

- A list with two elements:
- Y** List of 4 numeric matrices, each [50, 50], with NA on the diagonal. Latent probit-scale predictor; threshold at 0 for the binary indicator.
 - X** List of 4 numeric arrays, each [50, 50, 3] of dyadic covariates.

YX_bin_long

synthetic longitudinal binary relational data (latent-scale)

Description

a synthetic 50-actor, 4-period dataset used by the vignettes. The shipped Y array holds the *latent probit-scale predictor* (range roughly -24 to 20), not 0/1 ties. To recover the binary tie indicator the dataset name implies, threshold at zero: $Y_bin \leftarrow (YX_bin_long\$Y > 0) * 1$. If passed unthresholded to `lame(..., family = "binary")` the fit will warn and silently apply the same $Y > 0$ threshold.

Usage

```
data(YX_bin_long)
```

Format

A list with two elements:

Y Numeric array [50, 50, 4]. Latent probit-scale predictor; threshold at 0 to get the binary tie indicator.

X Numeric array [50, 50, 3, 4] of dyadic covariates.

Examples

```
data(YX_bin_long)
# threshold latent z to 0/1 before computing binary GOF stats
Yt <- 1 * (YX_bin_long$Y[, , 1] > 0)
diag(Yt) <- NA
gof_stats(Yt)
```

YX_cbin

Censored binary nomination data and covariates

Description

a synthetic dataset that includes relational data where the number of nominations per row is censored at 10, along with information on eight covariates

Usage

```
data(YX_cbin)
```

Format

The format is: List of 2 \$ Y: num [1:100, 1:100] NA 0 0 0 1 0 0 0 0 3 ... \$ X: num [1:100, 1:100, 1:8] 1 1 1 1 1 1 1 1 1 1- attr(*, "dimnames")=List of 3\$: NULL\$: NULL\$: chr [1:8] "intercept" "rgpa" "rsmoke" "cgpa" ...

Examples

```
data(YX_cbin)
gof_stats(YX_cbin$Y)
```

YX_frn	<i>Fixed rank nomination data and covariates</i>
--------	--

Description

a synthetic dataset that includes fixed rank nomination data as well as information on eight covariates

Usage

```
data(YX_frn)
```

Format

The format is: List of 2 \$ Y: num [1:100, 1:100] NA 0 0 0 1 0 0 0 0 3 ... \$ X: num [1:100, 1:100, 1:8] 1 1 1 1 1 1 1 1 1 1- attr(*, "dimnames")=List of 3\$: NULL\$: NULL\$: chr [1:8] "intercept" "rgpa" "rsmoke" "cgpa" ...

Examples

```
data(YX_frn)
gof_stats(YX_frn$Y)
```

YX_nrm	<i>normal relational data and covariates</i>
--------	--

Description

a synthetic dataset that includes continuous (normal) relational data as well as information on eight covariates

Usage

```
data(YX_nrm)
```


Format

The format is: List of 2 \$ Y: num [1:100, 1:100] NA -4.05 -0.181 -3.053 -1.579 ... \$ X: num [1:100, 1:100, 1:8] 1 1 1 1 1 1 1 1 1- attr(*, "dimnames")=List of 3\$: NULL\$: NULL\$: chr [1:8] "intercept" "rgpa" "rsmoke" "cgpa" ...

Examples

```
data(YX_nrm)
gof_stats(YX_nrm$Y)
```

YX_ord	<i>ordinal relational data and covariates</i>
--------	---

Description

a synthetic dataset that includes ordinal relational data as well as information on seven covariates

Usage

```
data(YX_ord)
```

Format

The format is: List of 2 \$ Y: num [1:100, 1:100] NA 0 3 0 3 1 0 1 1 0 ... \$ X: num [1:100, 1:100, 1:7] 1 1 1 1 1 1 1 1 1- attr(*, "dimnames")=List of 3\$: NULL\$: NULL\$: chr [1:7] "rgpa" "rsmoke" "cgpa" "csmoke" ...

Examples

```
data(YX_ord)
gof_stats(YX_ord$Y)
```

zscores	<i>rank-based z-scores</i>
---------	----------------------------

Description

Computes the normal scores corresponding to the ranks of a data vector

Usage

```
zscores(y)
```

Arguments

`y` a numeric vector

Value

a numeric vector

Author(s)

Peter Hoff

Index

- * **Initialize**
 - bipartite_helpers, 47
- * **bipartite**
 - bipartite_helpers, 47
- * **datasets**
 - addhealthc3, 16
 - addhealthc9, 16
 - vignette_data, 226
 - Xcol, 228
 - Xdyad, 229
 - Xrow, 229
 - Y, 229
 - YX_bin, 230
 - YX_bin_list, 230
 - YX_bin_long, 231
 - YX_cbin, 231
 - YX_frn, 232
 - YX_nrm, 232
 - YX_ord, 233
- * **internal**
 - .actor_ffbs_path, 8
 - .ame_propagate_cov_na, 9
 - .build_full_design, 9
 - .exact_center_per_actor, 10
 - .fit_actor_order, 10
 - .reorder_newdata_actors, 11
 - .rotation_drift_diagnostic, 11
 - .sweep_per_actor_exact, 12
 - .xbeta_newdata, 13
 - bipartite_helpers, 47
 - compute_gof_bipartite, 53
 - ffbs_vecG, 64
 - lame-package, 7
 - list_to_array_bipartite, 117
 - log_phi_diff, 120
 - reexports, 152
 - rtnorm_interval_logp, 161
 - rZ_cbin_bip_fc, 172
 - rZ_frn_bip_fc, 174
 - rZ_ord_bip_fc, 177
 - rZ_ord_explicit_fc, 178
 - rZ_ord_sym_explicit_fc, 179
 - rZ_ord_sym_fc, 179
 - rZ_pois_bip_fc, 180
 - sample_ab_bipartite, 182
 - sample_alpha_cowles, 183
 - sample_rho_G_mh, 188
 - sample_sigma_G2, 191
 - update_variances_bipartite, 221
- * **starting**
 - bipartite_helpers, 47
- * **values**
 - bipartite_helpers, 47
 - .actor_ffbs_path, 8
 - .ame_propagate_cov_na, 9
 - .build_full_design, 9, 13
 - .exact_center_per_actor, 10
 - .fit_actor_order, 10, 11
 - .reorder_newdata_actors, 11
 - .rotation_drift_diagnostic, 11
 - .sweep_per_actor_exact, 12
 - .xbeta_newdata, 13
- ab_plot, 13, 15, 50, 126, 127, 129
- ab_plot.ame_als, 15, 34
- absdiff, 27
- absdiff (nodematch), 124
- addhealthc3, 16
- addhealthc9, 16
- als_dynamic_beta, 17, 102, 105
- als_start_vals, 18, 93, 95
- ame, 7, 9, 18, 19, 30–34, 36, 41, 44, 77, 95, 96, 102, 104, 105, 126, 129, 210
- ame_als, 7, 18, 22, 29, 34–36, 38, 45, 56, 103, 105, 127, 132, 153, 220, 224
- ame_als_bootstrap, 7, 31–34, 34, 37, 38, 51, 56, 57, 105, 197, 216, 225
- ame_als_refit, 34, 36, 37, 220
- ame_memory_settings, 38

- ame_memory_usage, 39
- ame_options, 40
- ame_parallel, 41, 107
- array_to_list, 42
- as_draws, 43
- as_draws.ame, 43
- as_draws.ame_als (as_draws.ame), 43
- as_draws.lame (as_draws.ame), 43
- as_lame_y, 27, 44
- autoplot, 152
- autoplot (reexports), 152
- autoplot.ame (autoplot.lame), 46
- autoplot.ame_als, 45
- autoplot.lame, 45, 46
- autoplot.lame_als (autoplot.ame_als), 45
- bipartite_helpers, 47
- boot_ame (ame_als_bootstrap), 34
- boot_ame-no-fitted, 47
- check_format, 48
- coef.als_dynamic_beta, 49
- coef.ame, 28, 50
- coef.ame_als, 51
- coef.boot_ame, 51
- coef.lame, 102
- coef.lame (coef.ame), 50
- coldwar, 52
- combine_ame_chains, 52
- compact_ame, 53
- compute_gof_bipartite, 53
- compute_mcmc_diagnostics, 54
- compute_XtX_Xty_bip_cpp, 54
- comtrade, 55
- confint, 22, 98
- confint.ame, 50, 55
- confint.ame_als, 31, 45, 56, 105
- confint.boot_ame, 36, 51, 56, 57
- confint.lame, 212
- confint.lame (confint.ame), 55
- design_array, 58
- design_array_listwisedel, 58
- detect_change_point, 59
- dutchcollege, 60
- dynamic_beta_prior_summary, 61, 92
- el2sm, 62
- evaluate_heldout, 63
- ffbs_vecG, 64
- fitted, 47
- fitted.ame, 65, 152
- fitted.ame_als, 66
- fitted.boot_ame (boot_ame-no-fitted), 47
- fitted.lame, 66
- forecast_pit, 67
- formula.ame, 68
- formula.lame (formula.ame), 68
- get_design_rep, 69
- get_EZ_dynamic_beta_cpp, 70
- get_fit_object, 71
- get_start_vals, 73
- ginv, 31
- glance, 74
- glance.ame, 74
- glance.ame_als, 75
- glance.lame (glance.ame), 74
- glance.lame_als (glance.ame_als), 75
- gof, 25, 28, 76, 102, 119
- gof_plot, 25, 28, 77, 78, 81, 83, 102, 119, 126, 127, 129
- gof_plot.ame_als, 34, 78, 81
- gof_stats, 82
- gof_stats_bipartite, 84
- gof_stats_unipartite, 85
- gof_temporal, 86
- init_bipartite_startvals
(bipartite_helpers), 47
- init_dynamic_ab_cpp, 87
- init_dynamic_positions, 88
- IR90s, 89
- lame, 7, 9, 17, 18, 22, 23, 28, 30, 32, 33, 36, 41, 44, 77, 89, 103–105, 107, 109, 110, 129, 207–209, 213
- lame-package, 7
- lame_als, 7, 17, 18, 33–36, 45, 97, 98, 102, 103, 127, 132, 153
- lame_multi, 42, 106
- lame_parallel, 106, 107
- lame_resume, 97, 98, 102, 108
- lame_snap_als, 33, 98, 102, 105, 109, 207–209
- latent_positions, 24, 28, 34, 50, 102, 113, 145
- lazegalaw, 114

ldZgbme, 115
 lfo, 116
 list_to_array, 117
 list_to_array_bipartite, 117
 llrmRho, 118
 log_phi_diff, 120
 logLik.ame, 118, 122
 logLik.ame_als, 119
 logLik.lame(logLik.ame), 118
 loo, 120, 121
 loo.ame, 121
 loo.ame_als(loo.ame), 121
 loo.lame(loo.ame), 121

 mhalf, 122

 nobs.ame, 122, 123
 nobs.ame_als, 123
 nobs.lame(nobs.ame), 122
 nodefactor, 27
 nodefactor(nodematch), 124
 nodematch, 27, 124

 per_actor_slopes, 125
 plot.ame, 126
 plot.ame_als, 127
 plot.lame, 127
 posterior_options, 22, 95, 96, 114, 129
 posterior_quantiles, 130
 precomputeX, 130
 predict.ame, 50, 65, 131, 136, 152
 predict.ame_als, 132
 predict.lame, 133
 prediction_draws_long, 134
 print.als_dynamic_beta, 135
 print.ame, 136
 print.ame.sim, 137
 print.ame_als, 138
 print.boot_ame, 138
 print.gof_temporal, 139
 print.lame, 139
 print.lame.sim(print.ame.sim), 137
 print.lame_multi, 140
 print.lfo_lame, 140
 print.per_actor_slopes, 141
 print.summary.ame, 141, 210
 print.summary.ame_als, 142
 print.summary.boot_ame
 (summary.boot_ame), 211

 print.summary.lame, 142, 213
 prior_summary, 143
 procrustes_align, 24, 28, 102, 114, 143

 raSab_bin_fc, 145
 raSab_cbin_fc, 146
 raSab_frnc_fc, 147
 rbeta_ab_bip_gibbs_cpp, 148
 rbeta_ab_fc, 149
 rbeta_ab_rep_fc, 150
 read_log_lik, 150
 reconstruct_EZ, 151
 reconstruct_UVPM(reconstruct_EZ), 151
 reexports, 152
 residuals, 47
 residuals.ame, 65, 152
 residuals.ame_als, 153
 residuals.boot_ame
 (boot_ame-no-fitted), 47
 residuals.lame, 153
 rhat_dynamic_beta, 154
 rmvnorm, 155
 rrho_fc, 155
 rrho_mh, 156
 rrho_mh_rep, 157
 rs2_fc, 157
 rs2_rep_fc, 158
 rSab_fc, 159
 rSuv_fc, 160
 rtnorm_interval_logp, 161
 rUV_dynamic_bip_fc_cpp, 161
 rUV_dynamic_fc, 162
 rUV_dynamic_fc_cpp, 163
 rUV_dynamic_snap_fc, 164
 rUV_dynamic_snap_fc_cpp, 165
 rUV_dynamic_t_fc, 166
 rUV_dynamic_t_fc_cpp, 167
 rUV_fc, 168
 rUV_rep_fc, 169
 rUV_sym_fc, 169
 rwish, 170
 rZ_bin_bip_batch_cpp, 171
 rZ_bin_fc, 171
 rZ_cbin_bip_fc, 172
 rZ_cbin_fc, 172, 173
 rZ_frnc_bip_fc, 174
 rZ_frnc_fc, 174, 175
 rZ_nrm_batch_cpp, 176
 rZ_nrm_fc, 176

rZ_ord_bip_fc, 177
 rZ_ord_explicit_fc, 178
 rZ_ord_fc, 177, 178, 178, 179
 rZ_ord_sym_explicit_fc, 179
 rZ_ord_sym_fc, 179, 179
 rZ_pois_bip_fc, 180
 rZ_pois_fc, 180, 181

 sample_ab_bipartite, 182
 sample_alpha_cowles, 183
 sample_beta_dynamic_cpp, 183
 sample_beta_static_cpp, 185
 sample_dynamic_ab_cpp, 186
 sample_rho_ab_cpp, 187
 sample_rho_beta_cpp, 187
 sample_rho_G_mh, 188
 sample_rho_uv, 189
 sample_sigma_ab_cpp, 190
 sample_sigma_beta_cpp, 191
 sample_sigma_G2, 191
 sample_sigma_uv, 192
 sampler_describe, 181
 sampsonmonks, 193
 sheep, 193
 simulate.ame, 136, 194
 simulate.ame_als, 34, 81, 197
 simulate.lame, 197
 simulate_posterior, 201
 simY_bin, 202
 simY_frn, 203
 simY_nrm, 204
 simY_ord, 204
 simY_pois, 205
 simZ, 205
 sm2el, 206
 snap_category_summary, 206
 snap_index_draws, 207
 snap_index_summary, 208
 snap_rank_summary, 208
 summary.ame, 28, 50, 136, 209
 summary.ame.sim, 210
 summary.ame_als, 211
 summary.boot_ame, 211
 summary.lame, 102, 212
 summary.lame.sim, 213

 t, 8
 tidy, 214
 tidy.ame, 214
 tidy.ame_als, 215
 tidy.boot_ame, 216
 tidy.lame(tidy.ame), 214
 tidy.lame_als(tidy.ame_als), 215
 trace_plot, 33, 126, 129, 217

 update, 219, 220
 update.ame, 219, 220
 update.ame_als, 220
 update.lame(update.ame), 219
 update.lame_als(update.ame_als), 220
 update_variances_bipartite, 221
 uv_plot, 34, 114, 126, 127, 129, 145, 221

 vcov.ame, 50, 224
 vcov.ame_als, 33, 45, 56, 215, 216, 224
 vcov.boot_ame, 51, 225
 vcov.lame(vcov.ame), 224
 vignette_data, 226, 228, 229

 waic, 227
 waic(loo), 120
 waic.ame, 227
 waic.ame_als(waic.ame), 227
 waic.lame(waic.ame), 227

 Xbeta, 227
 Xbeta_bip_cpp, 228
 Xcol, 228
 Xdyad, 229
 Xrow, 229

 Y, 229
 YX_bin, 230
 YX_bin_list, 230
 YX_bin_long, 230, 231
 YX_cbin, 231
 YX_frn, 232
 YX_nrm, 232
 YX_ord, 233

 zscores, 233