

# ROCK64

## Pi-2 Bus

|                         |    |  |    |                        |
|-------------------------|----|--|----|------------------------|
| 3.3V                    | 1  |  | 2  | 5V                     |
| GPIO2_D1 (I2C0_SDA)     | 3  |  | 4  | 5V                     |
| GPIO2_D0 (I2C0_SCL)     | 5  |  | 6  | GND                    |
| GPIO1_D4 (CLK32KOUT_M1) | 7  |  | 8  | GPIO2_A0 (UART2_TX_M1) |
| GND                     | 9  |  | 10 | GPIO2_A1 (UART2_RX_M1) |
| NC                      | 11 |  | 12 | GPIO2_A3               |
| GPIO0_A0                | 13 |  | 14 | GND                    |
| GPIO3_A4                | 15 |  | 16 | GPIO3_A5               |
| 3.3V                    | 17 |  | 18 | GPIO3_A6               |
| GPIO3_A1 (SPI_TXD_M2)   | 19 |  | 20 | GND                    |
| GPIO3_A2 (SPI_RXD_M2)   | 21 |  | 22 | GPIO3_A7               |
| GPIO3_A0 (SPI_CLK_M2)   | 23 |  | 24 | GPIO3_B0 (SPI_CSN0_M2) |
| GND                     | 25 |  | 26 | GPIO2_B4 (SPI_CSN1_M0) |
| GPIO2_A4 (I2C1_SDA)     | 27 |  | 28 | GPIO2_A5 (I2C1_SCL)    |
| NC                      | 29 |  | 30 | GND                    |
| NC                      | 31 |  | 32 | GPIO1_A6               |
| GPIO1_A0                | 33 |  | 34 | GND                    |
| GPIO1_A1                | 35 |  | 36 | GPIO1_A5               |
| GPIO1_A2                | 37 |  | 37 | GPIO1_A4               |
| GND                     | 39 |  | 40 | GPIO1_A3               |

### Key

- Power (5 Volts)
- Power (3.3 Volts)
- Ground
- General Inputs/Outputs
- General Inputs/Outputs  
(Only applicable if MicroSD not in used)
- I2C Interface
- SPI Interface
- UART Interface
- ID EEPROM Interface

# ROCK64

## Pi P5+ Bus

|                           |    |  |    |                          |
|---------------------------|----|--|----|--------------------------|
| 3.3V                      | 1  |  | 2  | 5V                       |
| GPIO2_C1 (I2S1_LRCKTX)    | 3  |  | 4  | GPIO2_C2 (I2S1_SCLK)     |
| GPIO2_C7 (I2S1_SDO)       | 5  |  | 6  | GPIO2_C3 (I2S1_SDI)      |
| GND                       | 7  |  | 8  | GND                      |
| GPIO2_C0 (I2S1_LRCKRX)    | 9  |  | 10 | GPIO2_B7 (I2S1_MCLK)     |
| GPIO2_C5 (I2S1_SDIO2)     | 11 |  | 12 | GPIO2_C4 (I2S1_SDIO1)    |
| GPIO0_D3 (SPDIF_TX_M0)    | 13 |  | 14 | GPIO2_C6 (I2S1_SDIO3)    |
| GND                       | 15 |  | 16 | GND                      |
| Ethernet RD+              | 17 |  | 18 | Ethernet RD-             |
| Ethernet TX+              | 19 |  | 20 | Ethernet TX-             |
| GPIO2_D1 (Ethernet Speed) | 21 |  | 22 | (Ethernet Link) GPIO2_D0 |

### Key

- Power (5 Volts)
- Power (3.3 Volts)
- Ground
- I2S Interface
- SPDIF Interface
- 10/100 Mbps Ethernet Interface  
(Speed/Link only applicable if I2C0 not in used)